

RF EXPOSURE EVALUATION REPORT

Product Name: GPON ONT
Trade Mark: Claro
Model No.: DTW5512CL
Report Number: 24071712723RFC-4
Test Standards: FCC 47 CFR Part 1 Subpart I
FCC ID: 2AL9QDTW5512CL00001
Test Result: PASS
Date of Issue: September 27, 2024

Prepared for:

Shenzhen Jiuzhou Electric Co., Ltd.
**6F, Jiuzhou Electric Building, Southern No. 12 Rd. High-tech Industrial
Park, Nanshan District, Shenzhen, China**

Prepared by:

Shenzhen UnionTrust Quality and Technology Co., Ltd.
**Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and
technology park, Longhua district, Shenzhen, China**

TEL: +86-755-2823 0888

FAX: +86-755-2823 0886

Prepared by:

David Chen

David Chen

Senior Project Engineer

Reviewed by:

Henry Lu

Henry Lu

Team Leader

Approved by:

Robbin Chen

Certified

Robbin Chen

Assistant Manager

Date:

September 27, 2024

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-FCCPART1-V1.1

Version

Version No.	Date	Description
V1.0	September 27, 2024	Original

**Shenzhen UnionTrust Quality and Technology Co., Ltd.**

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com<http://www.uttlab.com>UTTR-RF-FCCPART1-V1.1

CONTENTS

1. GENERAL INFORMATION	4
1.1 CLIENT INFORMATION	4
1.2 EUT INFORMATION	4
1.3 PRODUCT SPECIFICATION SUBJECTIVE TO THIS STANDARD	4
1.4 OTHER INFORMATION	6
1.5 GENERAL DESCRIPTION OF APPLIED STANDARDS	7
1.6 DEVIATION FROM STANDARDS	7
1.7 ABNORMALITIES FROM STANDARD CONDITIONS	7
1.8 OTHER INFORMATION REQUESTED BY THE CUSTOMER	7
2. EQUIPMENT LIST	7
3. MPE EVALUATION	8
3.1 REFERENCE DOCUMENTS FOR EVALUATION	8
3.2 MPE COMPLIANCE REQUIREMENT	8
3.2.1 LIMITS	8
3.2.2 TEST PROCEDURE	9
3.3 MPE CALCULATION METHOD	9
3.4 MPE CALCULATION RESULTS	9
3.4.1 FOR WLAN	9
3.4.2 SIMULTANEOUS MULTI-BAND TRANSMISSION MPE ANALYSIS	13
APPENDIX 1 PHOTOS OF TEST SETUP	14
APPENDIX 2 PHOTOS OF EUT CONSTRUCTIONAL DETAILS	14

1. GENERAL INFORMATION

1.1 CLIENT INFORMATION

Applicant:	Shenzhen Jiuzhou Electric Co., Ltd.
Address of Applicant:	6F, Jiuzhou Electric Building, Southern No. 12 Rd. High-tech Industrial Park, Nanshan District, Shenzhen, China
Manufacturer:	Shenzhen Jiuzhou Electric Co., Ltd.
Address of Manufacturer:	6F, Jiuzhou Electric Building, Southern No. 12 Rd. High-tech Industrial Park, Nanshan District, Shenzhen, China

1.2 EUT INFORMATION

Product Name:	GPON ONT		
Model No.:	DTW5512CL		
Trade Mark:	Claro		
DUT Stage:	Identical Prototype		
EUT Supports Function: (Provided by the customer)	2.4 GHz ISM Band:	IEEE 802.11b/g/n/ax	
	5 GHz U-NII Bands:	5 150 MHz to 5 250 MHz	IEEE 802.11a/n/ac/ax
		5 250 MHz to 5 350 MHz	IEEE 802.11a/n/ac/ax
		5 470 MHz to 5 725 MHz	IEEE 802.11a/n/ac/ax
		5 725 MHz to 5 850 MHz	IEEE 802.11a/n/ac/ax
Sample Received Date:	July 25, 2024		
Remark: The above EUT's information was provided by customer. Please refer to the specifications or user's manual for more detailed description.			

1.3 PRODUCT SPECIFICATION SUBJECTIVE TO THIS STANDARD

For 2.4 GHz ISM Band of Wi-Fi			
Frequency Band:	2400 MHz to 2483.5 MHz		
Frequency Range:	2412 MHz to 2462 MHz		
Support Standards:	IEEE 802.11b/g/n-HT20/n-HT40/ax-HE20/ax-HE40		
Type of Modulation:	IEEE 802.11b: DSSS (CCK, DQPSK, DBPSK) IEEE 802.11g/n: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11ax: OFDM/OFDMA(1024QAM, 256QAM, 64QAM, 16QAM, QPSK, BPSK)		
Data Rate:	IEEE 802.11b: Up to 11 Mbps IEEE 802.11g: Up to 54 Mbps IEEE 802.11n-HT20/HT40: Up to MCS15 IEEE 802.11ax-HE20/ HE40: Up to MCS11		
Number of Channels:	IEEE 802.11b/g/n-HT20/ax-HE20: 11 IEEE 802.11n-HT40/ax-HE40: 7		
Channel Separation:	5 MHz		
Antenna Type: (Provided by the customer)	Antenna 1	PCB Antenna	
	Antenna 2	PCB Antenna	
Antenna Gain: (Provided by the customer)	Antenna 1	4.09 dBi	
	Antenna 2	4.14 dBi	

For 5 GHz U-NII Bands of Wi-Fi					
Frequency Bands:	5150 MHz to 5250 MHz (U-NII-1)				
	5250 MHz to 5350 MHz (U-NII-2A)				
	5470 MHz to 5725 MHz (U-NII-2C)				
	5725 MHz to 5850 MHz (U-NII-3)				
Frequency Ranges:	5180 MHz to 5240 MHz				
	5260 MHz to 5320 MHz				
	5500 MHz to 5700 MHz				
	5745 MHz to 5825 MHz				
Support Standards:	IEEE 802.11a/n/ac/ax				
TPC Function:	Not Support				
DFS Operational mode:	Master				
Category:	Indoor AP				
Type of Modulation:	IEEE 802.11a/n: OFDM (64QAM, 16QAM, QPSK, BPSK)				
	IEEE 802.11ac: OFDM (256QAM, 64QAM, 16QAM, QPSK, BPSK)				
	IEEE 802.11ax: OFDM/OFDMA (1024QAM, 256QAM, 64QAM, 16QAM, QPSK, BPSK)				
Channel Spacing:	IEEE 802.11a/n-HT20/ac-VHT20/ax-HE20: 20 MHz				
	IEEE 802.11n-HT40/ac-VHT40/ax-HE40: 40 MHz				
	IEEE 802.11ac-VHT80/ax-HE80: 80 MHz				
	IEEE 802.11ac-VHT160/ax-HE160: 160 MHz				
Data Rate:	IEEE 802.11a: Up to 54 Mbps				
	IEEE 802.11n: Up to MCS15				
	IEEE 802.11ac-VHT20: Up to MCS8				
	IEEE 802.11ac-VHT40/VHT80/VHT160: Up to MCS9				
	IEEE 802.11ax-HE20/HE40/HE80/HE160: Up to MCS11				
Number of Channels:	5150 MHz to 5350 MHz: 8 for 802.11a/n-HT20/ac-VHT20/ax-HE20 4 for 802.11n-HT40/ac-VHT40/ax-HE40 2 for 802.11ac-VHT80/ax-HE80 1 for 802.11ac-VHT160/ax-HE160				
	5470 MHz to 5725 MHz: 11 for 802.11a/n-HT20/ac-VHT20/ax-HE20 5 for 802.11n-HT40/ac-VHT40/ax-HE40 2 for 802.11ac-VHT80/ax-HE80 1 for 802.11ac-VHT160/ax-HE160				
	5725 MHz to 5850 MHz: 5 for IEEE 802.11a/n-HT20/ac-VHT20/ax-HE20 2 for IEEE 802.11n-HT40/ac-VHT40/ax-HE40 1 for IEEE 802.11ac-VHT80/ax-HE80				
Smart Antenna System:	The following three antennas only support 2*2 combination				
Antenna Type: (Provided by the customer)	Antenna 1:	PCB Antenna			
	Antenna 2:	PCB Antenna			
	Antenna 3:	PCB Antenna			
Antenna Gain (dBi): (Provided by the customer)	Antenna	U-NII-1	U-NII-2A	U-NII-2C	U-NII-3
	Antenna 1:	5.37	5.23	5.19	5.36
	Antenna 2:	5.39	4.96	5.03	5.31
	Antenna 3:	4.78	4.88	4.81	4.48

1.4 OTHER INFORMATION

Test channels for 2.4 GHz ISM Band of Wi-Fi				
Mode	Tx/Rx Frequency	Test RF Channel Lists		
		Lowest(L)	Middle(M)	Highest(H)
IEEE 802.11b	2412 MHz to 2462 MHz	Channel 1	Channel 6	Channel 11
		2412 MHz	2437 MHz	2462 MHz
IEEE 802.11g	2412 MHz to 2462 MHz	Channel 1	Channel 6	Channel 11
		2412 MHz	2437 MHz	2462 MHz
IEEE 802.11n-HT20 IEEE 802.11ax-HE20	2412 MHz to 2462 MHz	Channel 1	Channel 6	Channel 11
		2412 MHz	2437 MHz	2462 MHz
IEEE 802.11n-HT40 IEEE 802.11ax-HE40	2422 MHz to 2452 MHz	Channel 3	Channel 6	Channel 9
		2422 MHz	2437 MHz	2452 MHz

Test channels for 5 GHz U-NII Bands of Wi-Fi				
Mode	Tx/Rx Frequency	Test RF Channel Lists		
		Lowest(L)	Middle(M)	Highest(H)
IEEE 802.11a IEEE 802.11n-HT20 IEEE 802.11ac-VHT20 IEEE 802.11ax-HE20	5150 - 5250 MHz	Channel 36	Channel 40	Channel 48
		5180 MHz	5200 MHz	5240 MHz
	5250 - 5350 MHz	Channel 52	Channel 56	Channel 64
		5260 MHz	5280 MHz	5320 MHz
	5470 - 5725 MHz	Channel 100	Channel 116	Channel 140
		5500 MHz	5580 MHz	5700 MHz
IEEE 802.11n-HT40 IEEE 802.11ac-VHT40 IEEE 802.11ax-HE40	5150 - 5250 MHz	Channel 149	Channel 157	Channel 165
		5745 MHz	5785 MHz	5825 MHz
	5250 - 5350 MHz	Channel 38	--	Channel 46
		5190 MHz	--	5230 MHz
	5470 - 5725 MHz	Channel 54	--	Channel 62
		5270 MHz	--	5310 MHz
IEEE 802.11ac-VHT80 IEEE 802.11ax-HE80	5150 - 5250 MHz	Channel 102	Channel 110	Channel 134
		5510 MHz	5550 MHz	5670 MHz
	5250 - 5350 MHz	Channel 151	--	Channel 159
		5755 MHz	--	5795 MHz
	5470 - 5725 MHz	--	Channel 42	--
		--	5210 MHz	--
IEEE 802.11ac-VHT160 IEEE 802.11ax-HE160	5150 - 5350 MHz	--	Channel 58	--
		--	5290 MHz	--
	5470 - 5725 MHz	Channel 106	--	Channel 122
		5530 MHz	--	5610 MHz
	5725 - 5850 MHz	--	Channel 155	--
		--	5775 MHz	--

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-FCCPART1-V1.1

1.5 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF product, according to the specifications of the manufacturers. It must comply with the requirements of the following standards:

FCC 47 CFR Part 1 Subpart I

All test items have been performed and recorded as per the above standards

1.6 DEVIATION FROM STANDARDS

None.

1.7 ABNORMALITIES FROM STANDARD CONDITIONS

None.

1.8 OTHER INFORMATION REQUESTED BY THE CUSTOMER

None.

2. EQUIPMENT LIST

Please refer to the RF test report.

3. MPE EVALUATION

3.1 REFERENCE DOCUMENTS FOR EVALUATION

No.	Identity	Document Title
1	FCC 47 CFR Part 1 Subpart I	PROCEDURES IMPLEMENTING THE NATIONAL ENVIRONMENTAL POLICY ACT OF 1969
2	KDB 447498 D01 General RF Exposure Guidance v06	RF EXPOSURE PROCEDURES AND EQUIPMENT AUTHORIZATION POLICIES FOR MOBILE AND PORTABLE DEVICES
3	KDB 662911 D01 Multiple Transmitter Output v02r01	Emissions Testing of Transmitters with Multiple Outputs in the Same Band

3.2 MPE COMPLIANCE REQUIREMENT

3.2.1 Limits

3.2.1.1 FCC 47 CFR Part 1 Subpart I

According to §1.1307(b)(1), system operating under the provisions of this section shall be operating in a manner that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure.

Limits for Occupational / Controlled Exposure

Frequency range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Times E ² , H ² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f)*	6
30-300	61.4	0.163	1.0	6
300-1500	/	/	F/300	6
1500-100000	/	/	5	6

Limits for General Population / Uncontrolled Exposure

Frequency range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Times E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	F/1500	30
1500-100000	/	/	1	30

Note: f = frequency in MHz: * = Plane-wave equivalents power density.

3.2.2 Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

3.3 MPE CALCULATION METHOD

FCC 47 CFR Part 1 Subpart I

$$S = PG/4\pi R^2 = EIRP/4\pi R^2$$

S = power density (in appropriate units, e.g., mw/cm²)

P = power input to the antenna (in appropriate units, e.g., mw)

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor is normally numeric gain.

R = 20cm distance to the center of radiation of the antenna (in appropriate units, e.g., cm)

3.4 MPE CALCULATION RESULTS

Note: For the test results, the EUT had been tested with all conditions. But only the worst case was shown in test report.

3.4.1 For WLAN

For Wi-Fi function, operating at 2412MHz to 2462 MHz for IEEE802.11b/g/n/ax and
operating at 5180 MHz to 5240 MHz for IEEE802.11a/n/ac/ax and
operating at 5260 MHz to 5320 MHz for IEEE802.11a/n/ac/ax and
operating at 5500 MHz to 5700 MHz for IEEE802.11a/n/ac/ax and
operating at 5745 MHz to 5825 MHz for IEEE802.11a/n/ac/ax

3.4.1.1 Antenna Type:

FPCB Antenna

Antenna Gain:

Chain 1: 2412MHz to 2462 MHz: 4.09dBi

Chain 2: 2412MHz to 2462 MHz: 4.14dBi

Chain 1: 5150 MHz to 5250 MHz: 5.37dBi

5250 MHz to 5350 MHz: 5.23dBi

5470 MHz to 5725 MHz: 5.19dBi

5725 MHz to 5850 MHz: 5.36dBi

Chain 2: 5150 MHz to 5250 MHz: 5.39dBi

5250 MHz to 5350 MHz: 4.96dBi

5470 MHz to 5725 MHz: 5.03dBi

5725 MHz to 5850 MHz: 5.31dBi

Chain 3: 5150 MHz to 5250 MHz: 4.78dBi

5250 MHz to 5350 MHz: 4.88dBi

5470 MHz to 5725 MHz: 4.81dBi

5725 MHz to 5850 MHz: 4.48dBi

3.4.1.2 Results for FCC 47 CFR Part 1 Subpart I

For SISO (1TX/1RX) Mode

Operating Mode		Freq.	Ant.	Declared maximum conducted output power	Max. positive tolerance according manufacturer	Antenna Gain	Calculated maximum EIRP	Declared maximum EIRP	MPE Limit	MPE Value
		(MHz)		(dBm)		(dBi)	(dBm)	(mW)	(mW/cm²)	
SISO	IEEE 802.11b	2412-2462	Ant 1	21.5	1	4.09	26.59	456.0369	1	0.0907
			Ant 2	21.5	1	4.14	26.64	461.3176	1	0.0918
	IEEE 802.11g	2412-2462	Ant 1	24.0	1	4.09	29.09	810.9611	1	0.1613
			Ant 2	24.0	1	4.14	29.14	820.3515	1	0.1632
	IEEE 802.11a	5180-5240	Ant 1	19	1	5.37	25.37	344.3499	1	0.0685
			Ant 2	19	1	5.39	25.39	345.9394	1	0.0688
			Ant 3	19	1	4.78	24.78	300.6076	1	0.0598
		5260-5320	Ant 1	15	1	5.23	21.23	132.7394	1	0.0264
			Ant 2	15	1	4.96	20.96	124.7384	1	0.0248
			Ant 3	15	1	4.88	20.88	122.4616	1	0.0244
		5500-5700	Ant 1	18	1	5.19	24.19	262.4219	1	0.0522
			Ant 2	18	1	5.03	24.03	252.9298	1	0.0503
			Ant 3	18	1	4.81	23.81	240.4363	1	0.0478
		5745-5825	Ant 1	19	1	5.36	25.36	343.5579	1	0.0683
			Ant 2	19	1	5.31	25.31	339.6253	1	0.0676
			Ant 3	19	1	4.48	26.59	456.0369	1	0.0907

For MIMO (2TX/RX) Mode

Operating Mode		Freq.	Ant.	Declared maximum conducted output power	Max. positive Tolerance according manufacturer	Antenna Gain	Calculated maximum EIRP	Declared maximum EIRP	MPE Limit	MPE Value	MIMO	
		(MHz)										
MIMO (2TX/2RX)	IEEE 802.11n-HT20 802.11ax-HE20	2412-2462	Ant 1	21	2	4.09	27.09	511.6818	1	0.1018	0.2314	1
			Ant 2	22	2	4.14	28.14	651.6284	1	0.1296		
	IEEE 802.11n-HT40 802.11ax-HE40	2422 - 2452	Ant 1	21	1	4.09	26.09	406.4433	1	0.0809	0.1727	1
			Ant 2	21	1.5	4.14	26.64	461.3176	1	0.0918		
MIMO (2TX/2RX)	IEEE 802.11n-VHT20 802.11ac-VHT20 802.11ax-HE20	5180-5240	Ant 1	19	1.5	5.37	25.87	386.3670	1	0.0769	0.1541	1
			Ant 2	19	1.5	5.39	25.89	388.1504	1	0.0772		
			Ant 3	19	1.5	4.78	25.28	337.2873	1	0.0671		
		5260-5320	Ant 1	10	1.5	5.23	16.73	47.0977	1	0.0094	0.0182	1
			Ant 2	10	1.5	4.96	16.46	44.2588	1	0.0088		
			Ant 3	10	1.5	4.88	16.38	43.4510	1	0.0086		
		5500-5700	Ant 1	13	2.0	5.19	20.19	104.4720	1	0.0208	0.0408	1
			Ant 2	13	2.0	5.03	20.03	100.6932	1	0.0200		
			Ant 3	13	2.0	4.81	19.81	95.7194	1	0.0190		
	5745-5825	Ant 1	20	2.0	5.36	27.36	544.5027	1	0.1083	0.2154	1	
Ant 2		20	2.0	5.31	27.31	538.2698	1	0.1071				

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-FCCPART1-V1.1

Operating Mode	Freq.	Ant.	Declared maximum conduct ed output power	Max. positive Toleranc e according manufacturer	Antenna Gain	Calculated maximum EIRP	Declared maximum EIRP	MPE Limit	MPE Value	MIMO	
	(MHz)										
		Ant 3	20	2.0	4.48	26.48	444.6313	1	0.0885		
MIMO (2TX/2RX)	5190-5230	Ant 1	19	1.5	5.37	25.87	386.3670	1	0.0769	0.1541	1
		Ant 2	19	1.5	5.39	25.89	388.1504	1	0.0772		
		Ant 3	19	1.5	4.78	25.28	337.2873	1	0.0671		
	5270-5310	Ant 1	11	1.0	5.23	17.23	52.8445	1	0.0105	0.0204	1
		Ant 2	11	1.0	4.96	16.96	49.6592	1	0.0099		
		Ant 3	11	1.0	4.88	16.88	48.7528	1	0.0097		
	5510-5670	Ant 1	12	1.5	5.19	18.69	73.9605	1	0.0147	0.0289	1
		Ant 2	12	1.5	5.03	18.53	71.2853	1	0.0142		
		Ant 3	12	1.5	4.81	18.31	67.7642	1	0.0135		
	5755-5795	Ant 1	21	1.0	5.36	27.36	544.5027	1	0.1083	0.2154	1
		Ant 2	21	1.0	5.31	27.31	538.2698	1	0.1071		
		Ant 3	21	1.0	4.48	26.48	444.6313	1	0.0885		
	5210	Ant 1	13	1.5	5.37	19.87	97.0510	1	0.0193	0.0387	1
		Ant 2	13	1.5	5.39	19.89	97.4990	1	0.0194		
		Ant 3	13	1.5	4.78	19.28	84.7227	1	0.0169		
	5290	Ant 1	10	1.0	5.23	16.23	41.9759	1	0.0084	0.0162	1
		Ant 2	10	1.0	4.96	15.96	39.4457	1	0.0078		
		Ant 3	10	1.0	4.88	15.88	38.7258	1	0.0077		
	5530	Ant 1	12	1.0	5.19	18.19	65.9174	1	0.0131	0.0257	1
		Ant 2	12	1.0	5.03	18.03	63.5331	1	0.0126		
		Ant 3	12	1.0	4.81	17.81	60.3949	1	0.0120		
	5610	Ant 1	12	1.0	5.19	18.19	65.9174	1	0.0131	0.0257	1
		Ant 2	12	1.0	5.03	18.03	63.5331	1	0.0126		
		Ant 3	12	1.0	4.81	17.81	60.3949	1	0.0120		
	5775	Ant 1	19	1	5.36	25.36	343.5579	1	0.0683	0.1359	1
		Ant 2	19	1	5.31	25.31	339.6253	1	0.0676		
		Ant 3	19	1	4.48	24.48	280.5434	1	0.0558		
	5250	Ant 1	10	1	5.37	16.37	43.3511	1	0.0086	0.0173	1
		Ant 2	10	1	5.39	16.39	43.5512	1	0.0087		
		Ant 3	10	1	4.78	15.78	37.8443	1	0.0075		

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-FCCPART1-V1.1

Operating Mode	Freq.	Ant.	Declared maximum conducted output power	Max. positive Tolerance according manufacturer	Antenna Gain	Calculated maximum EIRP	Declared maximum EIRP	MPE Limit	MPE Value	MIMO	
	(MHz)		(dBm)		(dBi)	(dBm)	(mW)	(mW/cm ²)		Value	Limit
	5570	Ant 1	11	1.5	5.19	17.69	58.7489	1	0.0117	0.0230	1
		Ant 2	11	1.5	5.03	17.53	56.6239	1	0.0113		
		Ant 3	11	1.5	4.81	17.31	53.8270	1	0.0107		

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-FCCPART1-V1.1

3.4.2 Simultaneous Multi-band Transmission MPE Analysis

3.4.2.1 List of Mode for Simultaneous Multi-band Transmission

No.	Configurations	Support/Not Support
1	2.4G _WLAN + 5G_WLAN	Support

3.4.2.2 Results for transmit simultaneously

FCC 47 CFR Part 1 Subpart I

No.	Configurations	Maximum MPE Value			Limits
		2.4G WLAN	5G WLAN	Transmit simultaneously	
1	2.4G _WLAN + 5G_WLAN	0.2314	0.2154	0.4468	1

Note:

According to KDB 447498 D01 General RF Exposure Guidance v06, At the transmit simultaneously calculation method is as follows:

$$\text{Transmit simultaneously MPE} = \Sigma \text{ of MPE ratios}$$

$$\text{MPE ratios} = \text{Field strengths or power density} / \text{MPE limit at the test frequency}$$

APPENDIX 1 PHOTOS OF TEST SETUP

N/A

APPENDIX 2 PHOTOS OF EUT CONSTRUCTIONAL DETAILS

Refer to Appendix 2 for EUT external and internal Photos.

*** End of Report ***

The test report is effective only with both signature and specialized stamp. The result(s) shown in this report refer only to the sample(s) tested. Without written approval of UnionTrust, this report can't be reproduced except in full.
