CENTRE OF TESTING SERVICE INTERNATIONAL

OPERATE ACCORDING TO ISO/IEC 17025

FCC ID TEST REPORT

TEST REPORT NUMBER : CGZ3170113-00039-EF

CENTRE OF TESTING SERVICE CO., LTD.

A101，No.65，Zhuji Highway,Tianhe District，Guangzhou, China

TEST REPORT For FCC ID
47 CFR PART 15 OCT, 2016

Report Reference No.	CGZ3170113-00039-EF
Date of issue	08 March 2017
Testing Laboratory Name	**CENTRE OF TESTING SERVICE CO., LTD.**
Address	A101，No.65，Zhuji Highway,Tianhe District，Guangzhou, China
Testing location/ procedure	Full application of Harmonised standards ■ Partial application of Harmonised standards □ Other standard testing method □
Applicant's name.....	CHENGHAI LUCKY BOY TOYS CO.,LTD.
Address	XIAZHOU INDUSTRIAL AREA, DUTOU, SHANGHUA, CHENGHAI DISTRICT, SHANTOU CITY, GUANGDONG PROVINCE, CHINA
Test specification	
Standard	**47 CFR PART 15 OCT, 2016; ANSI C63.10:2013**
Test Report Form No.	CTSEMC-1.0
TRF Originator.....	CENTRE OF TESTING SERVICE CO., LTD.
Master TRF.....	Dated 2009-01

CENTRE OF TESTING SERVICE CO., LTD. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the CENTRE OF TESTING SERVICE CO., LTD is acknowledged as copyright owner and source of the material. CENTRE OF TESTING SERVICE CO., LTD takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Test item description	REMOTE CONTROL PLANE
Trade Mark	/
Manufacturer	CHENGHAI LUCKY BOY TOYS CO.,LTD.
Model/Type reference	9993
Ratings	Battery 1.5V*4
Operating Frequency.....	2405.0MHz ~2475.0MHz
Result	**Positive**

Compiled by:	**Supervised by:**	**Approved by:**
Kate zhang / Fileadministrators	Duke yang / Technique principal	Vincent yao / Manager

Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

CENTRE OF TESTING SERVICE CO., LTD.
A101，No.65，Zhuji Highway,Tianhe District，Guangzhou, China
Tel：+86-20-85543113 (32 lines) Fax：+86-20-38780406
Complaint line：+86-20-85533471 E-mail：cts@cts-lab.com.cn

See Reverse For Terms And Conditions of Service

FCC ID -- T E S T R E P O R T

Test Report No. : CGZ3170113-00039-EF	08 March 2017 Date of issue

Type / Model.....	9993
EUT.....	REMOTE CONTROL PLANE
Applicant.....	CHENGHAI LUCKY BOY TOYS CO.,LTD.
Address.....	XIAZHOU INDUSTRIAL AREA, DUTOU, SHANGHUA, CHENGHAI DISTRICT, SHANTOU CITY, GUANGDONG PROVINCE, CHINA
Telephone.....	+86-0754-85887048
Fax.....	/
Contact.....	Liu He Dong
Manufacturer.....	CHENGHAI LUCKY BOY TOYS CO.,LTD.
Address.....	XIAZHOU INDUSTRIAL AREA, DUTOU, SHANGHUA, CHENGHAI DISTRICT, SHANTOU CITY, GUANGDONG PROVINCE, CHINA
Telephone.....	+86-0754-85887048
Fax.....	/
Contact.....	Liu He Dong
Factory.....	CHENGHAI LUCKY BOY TOYS CO.,LTD.
Address.....	XIAZHOU INDUSTRIAL AREA, DUTOU, SHANGHUA, CHENGHAI DISTRICT, SHANTOU CITY, GUANGDONG PROVINCE, CHINA
Telephone.....	+86-0754-85887048
Fax.....	/
Contact.....	Liu He Dong

Test Result according to the standards on page 1: **PASSED**

The test report merely corresponds to the test sample.
It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

CENTRE OF TESTING SERVICE CO., LTD.
A101，No.65，Zhuji Highway,Tianhe District，Guangzhou, China
Tel：+86-20-85543113 (32 lines) Fax：+86-20-38780406
Complaint line：+86-20-85533471 E-mail：cts@cts-lab.com.cn

See Reverse For Terms And Conditions of Service

TABLE OF CONTENTS

Description **Page**

1.TEST STANDARDS 5

2.SUMMARY 5

2.1 GENERAL REMARKS 5
2.2 FINAL ASSESSMENT 5

3.EQUIPMENT UNDER TEST 5

3.1 POWER SUPPLY SYSTEM UTILISED 5
3.2 SHORT DESCRIPTION OF THE EQUIPMENT UNDER TEST (EUT) 5
3.3 EUT OPERATION MODE 5
3.4 EUT CONFIGURATION 6

4.TEST ENVIRONMENT 7

4.1 ADDRESS OF THE TEST LABORATORY 7
4.2 TEST FACILITY 7
4.3 ENVIRONMENTAL CONDITIONS 7
4.4 DEFINITIONS OF SYMBOLS USED IN THIS TEST REPORT 7
4.5 STATEMENT OF THE MEASUREMENT UNCERTAINTY 7
4.6 MEASUREMENT UNCERTAINTY 8

5.SUMMARY OF STANDARDS AND RESULTS 8

5.1.DESCRIPTION OF STANDARDS AND RESULTS 8

6.POWER LINE CONDUCTED EMISSION TEST 9

6.1.TEST EQUIPMENT 9
6.2. BLOCK DIAGRAM OF TEST SETUP 9
6.3. POWER LINE CONDUCTED EMISSION TEST LIMITS 9
6.4.TEST PROCEDURE 9
6.5. POWER LINE CONDUCTED EMISSION TEST RESULTS 9

7.RADIATED DISTURBANCE (ELECTRIC FIELD) 10

7.1.TEST EQUIPMENT 10
7.2.BLOCK DIAGRAM OF TEST SETUP 10
7.3.RADIATED EMISSION LIMIT : 11
7.4.TEST PROCEDURE 12
7.5.RADIATED EMISSION TEST RESULTS 12

8.BAND EDGE COMPLIANCE TEST 20

8.1. TEST EQUIPMENT 20
8.2. TEST INFORMATION 20
8.3. TEST PROCEDURE 20

Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

CENTRE OF TESTING SERVICE CO., LTD.
A101，No.65，Zhuji Highway,Tianhe District，Guangzhou, China
Tel：+86-20-85543113 (32 lines) Fax：+86-20-38780406
Complaint line：+86-20-85533471 E-mail：cts@cts-lab.com.cn

See Reverse For Terms And Conditions of Service

8.4. TEST RESULTS 20

9 20 DB BANDWIDTH TEST 25

9.1. TEST EQUIPMENT 25
9.2. TEST INFORMATION 25
8.3. TEST RESULTS 25

10 ANTENNA REQUIREMENTS 28

10.1 STANDARD APPLICABLE 28
10.2 ANTENNA CONSTRUCTION AND DIRECTIONAL GAIN 28

11.DEVIATION TO TEST SPECIFICATIONS 28

Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

CENTRE OF TESTING SERVICE CO., LTD.
A101，No.65，Zhuji Highway,Tianhe District，Guangzhou, China
Tel：+86-20-85543113 (32 lines) Fax：+86-20-38780406
Complaint line：+86-20-85533471 E-mail：cts@cts-lab.com.cn

See Reverse For Terms And Conditions of Service

1.TEST STANDARDS

The tests were performed according to following standards:

■ **47 CFR PART 15 OCT, 2016**
■ **ANSI C63.10:2013**

2.SUMMARY

2.1 GENERAL REMARKS

Date of receipt of test sample	13 January 2017
Testing commenced on	13 January~08 March 2017
Testing concluded on	08 March 2017

2.2 FINAL ASSESSMENT

The FCC requirements pertaining to the technical standards and tested operation modes are

■ - fulfilled.
□ - **not** fulfilled.

The equipment under test
■ - fulfils the FCC requirements cited on page 1.
□ - **does not** fulfil the FCC requirements cited on page 1.

3.EQUIPMENT UNDER TEST

3.1 Power supply system utilised

Power supply voltage : ■ Battery 1.5V*4

3.2 Short description of the Equipment under Test (EUT)

Number of tested samples: **1**
Serial number: Prototype

3.3 EUT operation mode

The equipment under test was operated during the measurement under the following conditions:
□ TX- Y position
□ TX- Z position
■ TX- X position

Operation mode 1:TX-X Position Low (2405MHz) , TX-X Position Middle (2445MHz),
TX-X Position High (2475MHz)
Note:Operation mode 1 TX -X position of EUT is the radiated test worst case; so only these test results be recorded in the test report.

Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

CENTRE OF TESTING SERVICE CO., LTD.
A101，No.65，Zhuji Highway,Tianhe District，Guangzhou, China
Tel：+86-20-85543113 (32 lines) Fax：+86-20-38780406
Complaint line：+86-20-85533471 E-mail：cts@cts-lab.com.cn

See Reverse For Terms And Conditions of Service

3.4 EUT configuration

3.4.1. Description of configuration (EUT)

Description	:	REMOTE CONTROL PLANE
Model Number	:	9993
Operation frequency	:	2405~ 2475 MHz ISM Band
Modulation Technology	:	GFSK Modulation
Antenna	:	Integral antenna, met requirement of FCC 15.203

3.4.2. Tested Supporting System Details

N/A

Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

CENTRE OF TESTING SERVICE CO., LTD.
A101，No.65，Zhuji Highway,Tianhe District，Guangzhou, China
Tel：+86-20-85543113 (32 lines) Fax：+86-20-38780406
Complaint line：+86-20-85533471 E-mail：cts@cts-lab.com.cn

See Reverse For Terms And Conditions of Service

4.TEST ENVIRONMENT

4.1 Address of the test laboratory

A101，No.65，Zhuji Highway,Tianhe District，Guangzhou, China

Tel：+86-20-85543113 (32 lines) Fax：+86-20-38780406

4.2 Test facility

The test facility is recognized, certified, or accredited by the following organizations:

CNAS-Lab Code: L3394

CENTRE OF TESTING SERVICE CO., LTD has been assessed and proved to be in compliance with CNAS-CL01: 2006 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC 17025: 2005 General Requirements) for the Competence of Testing and Calibration Laboratories.

IC-Registration No.: 8374A

The 3m Alternate Test Site of CENTRE OF TESTING SERVICE CO., LTD has been registered by Certification and Engineering Bureau of Industry Canada for the performance of radiated measurements with Registration No. 8374A on June 6, 2011.

FCC-Registration No.: 971995

CENTRE OF TESTING SERVICE CO., LTD, EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files. Registration No.791995, July 13,2012.

4.3 Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature:	15~35 ° C
Humidity:	25~75 %
Atmospheric pressure:	86~106 kPa

4.4 Definitions of symbols used in this test report

■ - The black square indicates that the listed condition, standard or equipment is applicable for this report.

□ - The empty square indicates that the listed condition, standard or equipment is **not** applicable for this report.

4.5 Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to CISPR 16 - 4 “Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements” and is documented in the CTS quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

4.6 Measurement Uncertainty

Test Item	Frequency Range	Uncertainty	Note
Conduction disturbance	150kHz~30MHz	±1.22dB	(1)
Power disturbance	30MHz~300MHz	±1.38dB	(1)
Radiation emission (3m)	30MHz~300MHz	±3.14dB	(1)
	300MHz~1000MHz	±3.18dB	(1)
	1GHz~26.5GHz	±3.54dB	(1)

(1).This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

5.Summary of standards and results

5.1.Description of Standards and Results

The EUT have been tested according to the applicable standards as referenced below.

EMISSION		
Description of Test Item	**Standard**	**Results**
Conducted Emission Test	FCC Part 15 § 15.207 ANSI C63.10:2013	N/A
Radiated Emission Test	FCC Part 15 C § 15.249 FCC Part 15 § 209 ANSI C63.10:2013	PASSED
Band Edge Compliance Test	FCC Part 15 C § 15.249 ANSI C63.10:2013	PASSED
20 dB Bandwidth	FCC Part 15 C: 15.215 ANSI C63.10:2013	PASSED
N/A is an abbreviation for Not Applicable.		

Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

CENTRE OF TESTING SERVICE CO., LTD.
A101，No.65，Zhuji Highway,Tianhe District，Guangzhou, China
Tel：+86-20-85543113 (32 lines) Fax：+86-20-38780406
Complaint line：+86-20-85533471 E-mail：cts@cts-lab.com.cn

See Reverse For Terms And Conditions of Service

6.Power Line Conducted Emission Test

6.1.Test Equipment

Conducted Disturbance					
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal.
1	EMI Test Receiver	ROHDE & SCHWARZ	ESHS10	842884/012	2016/10
2	Artificial Mains	ROHDE & SCHWARZ	ESH3-Z5	832479/025	2016/10
3	Artificial Mains	ROHDE & SCHWARZ	ESH3-Z5	832479/026	2016/10
4	Pulse Limiter	ROHDE & SCHWARZ	ESHSZ2	100301	2016/10
5	EMI Test Software	ROHDE & SCHWARZ	ESK1	N/A	2016/10

6.2. Block Diagram of Test Setup

(EUT: 9993***)***

6.3. Power Line Conducted Emission Test Limits

Standard: FCC Part 15 : 15.207,ANSI C63.10:2013

Frequency	Maximum RF Line Voltage	
	Quasi-Peak Level dB(μV)	Average Level dB(μV)
150kHz ~ 500kHz	66 ~ 56*	56 ~ 46*
500kHz ~ 5MHz	56	46
5MHz ~ 30MHz	60	50

Notes: 1. * Decreasing linearly with logarithm of frequency.
2. The lower limit shall apply at the transition frequencies.

6.4.Test Procedure

The EUT Power connected to the power mains through a line impedance stabilization network (L.I.S.N.#2). This provides a 50 ohm coupling impedance for the EUT. Please refer the block diagram of the test setup and photographs. The other peripheral devices power cord connected to the power mains through a line impedance stabilization network (L.I.S.N.#1). Power on the PC and let it work normally, we use a keyboard test soft ware, let EUT working in test mode, then test it. Both sides of AC line are checked to find out the maximum conducted emission. In order to find the maximum emission levels, the relative positions of equipment and all of the interface cables shall be changed according to FCC Part 15C on Conducted Emission Test.

6.5. Power Line Conducted Emission Test Results

N/A (The EUT Power supply by Battery, Not Applicable.)

Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

CENTRE OF TESTING SERVICE CO., LTD.
A101，No.65，Zhuji Highway,Tianhe District，Guangzhou, China
Tel：+86-20-85543113 (32 lines) Fax：+86-20-38780406
Complaint line：+86-20-85533471 E-mail：cts@cts-lab.com.cn

See Reverse For Terms And Conditions of Service

7.Radiated disturbance (electric field)

7.1.Test Equipment

Radiated disturbance (electric field)					
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal.
1	EMI Test Receiver	ROHDE & SCHWARZ	ESCI	100868	2016/10
2	Biconical Antenna	ROHDE & SCHWARZ	HK116	100221	2016/03
3	Log per Antenna	ROHDE & SCHWARZ	HL223	100226	2016/03
4	Log per Antenna	ROHDE & SCHWARZ	HL050	100186	2016/03
5	Signal analyzer	ROHDE & SCHWARZ	FSIQ26	100311	2016/03
6	Loop Antenna	A.R.A	PLA-1030/B	1030	2016/10

7.2.Block Diagram of Test Setup

7.2.1 Block Diagram of connection between EUT and simulators



(EUT: 9993*)*

Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

CENTRE OF TESTING SERVICE CO., LTD.
A101，No.65，Zhuji Highway,Tianhe District，Guangzhou, China
Tel：+86-20-85543113 (32 lines) Fax：+86-20-38780406
Complaint line：+86-20-85533471 E-mail：cts@cts-lab.com.cn

See Reverse For Terms And Conditions of Service

7.2.2 Anechoic Chamber Setup Diagram



7.3.Radiated Emission Limit :

Standard: FCC 15.249 , FCC 15.209

Except as provided in paragraph (a) of this section, the field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following:

Fundamental Frequency (MHz)	Field Strength of Fundamental (mV/m)	Field Strength of Harmonics (μV/m)
902-928	50	500
2400-2483.5	50	500
5725-5875	50	500
24000-24250	250	2500

FREQUENCY MHz	DISTANCE Meters	FIELD STRENGTHS LIMIT	
		μV/m	dB(μV)/m
0.009 ~ 0.490	300	2400/F(kHz)	---
0.490 ~ 1.705	30	24000/F(kHz)	---
1.705 ~ 30	30	30	---
30 ~ 88	3	100	40.0
88 ~ 216	3	150	43.5
216 ~ 960	3	200	46.0
960 ~ 1000	3	500	54.0
Above 1000	3	Other:74.0 dB(μV)/m (Peak) 54.0 dB(μV)/m (Average)	

Remark： (1) Emission level dBμV = 20 log Emission level μV/m

(2) The smaller limit shall apply at the cross point between two frequency bands.

(3) Distance is the distance in meters between the measuring instrument, antenna and the closest point of any part of the device or system.

Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

CENTRE OF TESTING SERVICE CO., LTD.
A101，No.65，Zhuji Highway,Tianhe District，Guangzhou, China
Tel：+86-20-85543113 (32 lines) Fax：+86-20-38780406
Complaint line：+86-20-85533471 E-mail：cts@cts-lab.com.cn

See Reverse For Terms And Conditions of Service

7.4.Test Procedure

The EUT and its simulators are placed on a turn table, which is 0.8 meter (1.5m for above 1GHz) high above ground. The turn table can rotate 360 degrees to determine the position of the maximum emission level. The EUT is set 3 meters away from the receiving antenna, which is mounted on a antenna tower. The antenna can be moved up and down between 1 meter and 4 meters to find out the maximum emission level. Broadband antenna (calibrated bilog antenna) is used as receiving antenna. Both horizontal and vertical polarization of the antenna is set on Test. In order to find the maximum emission levels, all of the interface cables must be manipulated according to ANSI C63.10:2013 on radiated emission Test.

The frequency range from 30MHz to 1000MHz and above 1GHz. is investigated. Please see the following pages.

All measurements for radiated emissions within the restricted bands were performed using a Quasi-Peak detector with 120kHz RBW below 1GHz and a Peak and Average detector with 2MHz RBW above 1GHz,

All measurements for radiated emissions within the restricted bands were performed using a Quasi-Peak detector with 300kHz VBW below 1GHz and a Peak detector with1MHz VBW above 1GHz, A average detector with 10Hz VBW above 1GHz

Pretest x, y, z position of EUT, final, select the worst case x position test and record the test results in the report.

The test modes (TX Mode) is tested in Anechoic Chamber and all the scanning waveforms are reported on section 7.5

7.5.Radiated Emission Test Results

PASSED.

The frequency range from 9KHz~30MHz,30MHz to 230MHz, 230MHz to 1000MHz and above 1GHz. is investigated. Please see the following pages.

Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

CENTRE OF TESTING SERVICE CO., LTD.
A101，No.65，Zhuji Highway,Tianhe District，Guangzhou, China
Tel：+86-20-85543113 (32 lines) Fax：+86-20-38780406
Complaint line：+86-20-85533471 E-mail：cts@cts-lab.com.cn

See Reverse For Terms And Conditions of Service

Test Mode: Frequency range:	TX –X Position Mode 9KHz~30MHz	Result:	■ - passed □ - not passed

No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.
Remark: The test result reading value is to low, margin all > 20dB of the limit.							

Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

CENTRE OF TESTING SERVICE CO., LTD.
A101，No.65，Zhuji Highway,Tianhe District，Guangzhou, China
Tel：+86-20-85543113 (32 lines) Fax：+86-20-38780406
Complaint line：+86-20-85533471 E-mail：cts@cts-lab.com.cn

See Reverse For Terms And Conditions of Service

Channel: Test point: Frequency range:	TX –X Position Horizontal 30MHz-1GHz	Result:	■ - passed □ - not passed

EUT	REMOTE CONTROL PLANE
Test Condition	Ambient Temperature: 25°C Humidity: 56%
Test distance	3 Meter
Test Date:	13 January~08 March 2017
Operator	Duke
MODEL NO	9993



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.
1	30.5411	-16.11	32.79	16.68	40.00	-23.32	QP
2	117.1142	-16.89	32.87	15.98	43.50	-27.52	QP
3	147.4148	-15.98	33.07	17.09	43.50	-26.41	QP
4	209.6393	-10.27	32.93	22.66	43.50	-20.84	QP
5	229.6593	-11.63	33.10	21.47	46.00	-24.53	QP
6	300.0000	-1.42	31.87	30.45	46.00	-15.55	QP
Remark: Other frequency mini margin all >6 dB of Limit							

Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

CENTRE OF TESTING SERVICE CO., LTD.
A101，No.65，Zhuji Highway,Tianhe District，Guangzhou, China
Tel：+86-20-85543113 (32 lines) Fax：+86-20-38780406
Complaint line：+86-20-85533471 E-mail：cts@cts-lab.com.cn See Reverse For Terms And Conditions of Service



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.
1	328.0561	-12.35	33.96	21.61	46.00	-24.39	QP
2	555.3106	-5.67	32.47	26.80	46.00	-19.20	QP
3	657.7154	-3.30	32.65	29.35	46.00	-16.65	QP
4	734.8697	-2.24	33.02	30.78	46.00	-15.22	QP
5	868.1362	-0.83	33.19	32.36	46.00	-13.64	QP
6	953.7074	0.39	33.10	33.49	46.00	-12.51	QP
Remark: Other frequency mini margin all >6 dB of Limit							

Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

CENTRE OF TESTING SERVICE CO., LTD.
A101，No.65，Zhuji Highway,Tianhe District，Guangzhou, China
Tel：+86-20-85543113 (32 lines) Fax：+86-20-38780406
Complaint line：+86-20-85533471 E-mail：cts@cts-lab.com.cn

See Reverse For Terms And Conditions of Service

Channel:	TX –X Position Low CH	Result:	■ - passed □ - not passed
Test point:	Horizontal		
Frequency range:	1GHz-26.5GHz		

No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.
1	2405.00	7.04	77.24	84.28	114.00	-29.72	Peak
2	2405.00	7.04	76.84	83.88	94.00	-10.12	AVG

No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.
1	1440.882	1.28	41.23	42.51	74.00	-31.49	peak
2	1440.882	1.28	29.24	30.52	54.00	-23.48	AVG
3	4813.627	5.30	45.11	50.41	74.00	-23.59	peak
4	4813.627	5.30	36.06	41.36	54.00	-12.64	AVG
Remark: Other frequency mini margin all >20 dB of Limit							

Channel:	TX –X Position Middle CH	Result:	■ - passed □ - not passed
Test point:	Horizontal		
Frequency range:	1GHz-26.5GHz		

No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.
1	2445.00	7.23	74.35	81.58	114.00	-32.42	Peak
2	2445.00	7.23	73.80	81.03	94.00	-12.97	AVG

No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.
1	1661.323	2.76	39.73	42.49	74.00	-31.51	peak
2	1661.323	2.76	27.76	30.52	54.00	-23.48	AVG
3	4879.760	5.53	43.16	48.69	74.00	-25.31	peak
4	4879.760	5.53	34.09	39.62	54.00	-14.38	AVG
Remark: Other frequency mini margin all >20 dB of Limit							

Channel:	TX –X Position High CH	Result:	■ - passed □ - not passed
Test point:	Horizontal		
Frequency range:	1GHz-26.5GHz		

No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.
1	2475.00	7.44	73.93	81.37	114.00	-32.63	Peak
2	2475.00	7.44	72.25	79.69	94.00	-14.31	AVG

No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.
1	1815.631	3.65	39.64	43.29	74.00	-30.71	peak
2	1815.631	3.65	27.60	31.25	54.00	-22.75	AVG
3	5474.950	7.33	39.86	47.19	74.00	-26.81	peak
4	5474.950	7.33	28.13	35.46	54.00	-18.54	AVG
Remark: Other frequency mini margin all >20 dB of Limit							

Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

CENTRE OF TESTING SERVICE CO., LTD.
A101，No.65，Zhuji Highway,Tianhe District，Guangzhou, China
Tel：+86-20-85543113 (32 lines) Fax：+86-20-38780406
Complaint line：+86-20-85533471 E-mail：cts@cts-lab.com.cn

See Reverse For Terms And Conditions of Service

Channel:	TX –X Position	Result:	■ - passed □ - not passed
Test point:	Vertical		
Frequency range:	30MHz-1GHz		



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.
1	30.0000	-16.04	40.36	24.32	40.00	-15.68	QP
2	39.7394	-17.30	38.21	20.91	40.00	-19.09	QP
3	136.0521	-16.09	32.95	16.86	43.50	-26.64	QP
4	212.3446	-10.36	32.55	22.19	43.50	-21.31	QP
5	248.0561	-11.49	32.36	20.87	46.00	-25.13	QP
6	300.0000	-1.42	31.74	30.32	46.00	-15.68	QP
Remark: Other frequency mini margin all >20 dB of Limit							

Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

CENTRE OF TESTING SERVICE CO., LTD.
A101，No.65，Zhuji Highway,Tianhe District，Guangzhou, China
Tel：+86-20-85543113 (32 lines) Fax：+86-20-38780406
Complaint line：+86-20-85533471 E-mail：cts@cts-lab.com.cn

See Reverse For Terms And Conditions of Service



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.
1	353.3066	-11.29	32.47	21.18	46.00	-24.82	QP
2	457.1142	-8.41	32.04	23.63	46.00	-22.37	QP
3	530.0601	-6.65	33.69	27.04	46.00	-18.96	QP
4	654.9098	-3.28	32.84	29.56	46.00	-16.44	QP
5	757.3146	-1.84	33.01	31.17	46.00	-14.83	QP
6	841.4830	-0.80	32.52	31.72	46.00	-14.28	QP
Remark: Other frequency mini margin all >6 dB of Limit							

Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

CENTRE OF TESTING SERVICE CO., LTD.
A101，No.65，Zhuji Highway,Tianhe District，Guangzhou, China
Tel：+86-20-85543113 (32 lines) Fax：+86-20-38780406
Complaint line：+86-20-85533471 E-mail：cts@cts-lab.com.cn

See Reverse For Terms And Conditions of Service

Channel:	TX –X Position Low CH	Result:	■ - passed □ - not passed
Test point:	Vertical		
Frequency range:	1GHz-26.5GHz		

No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.
1	2405.00	7.04	75.92	82.96	114.00	-31.04	Peak
2	2405.00	7.04	75.36	82.40	94.00	-11.60	AVG

No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.
1	1727.455	3.14	40.81	43.95	74.00	-30.05	peak
2	1727.455	3.14	27.91	31.05	54.00	-22.95	AVG
3	4813.627	5.30	42.47	47.77	74.00	-26.23	peak
4	4813.627	5.30	30.16	35.46	54.00	-18.54	AVG
Remark: Other frequency mini margin all >20dB of Limit							

Channel:	TX –X Position Middle CH	Result:	■ - passed □ - not passed
Test point:	Vertical		
Frequency range:	1GHz-26.5GHz		

No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.
1	2445.00	7.23	72.61	79.84	114.00	-34.16	Peak
2	2445.00	7.23	72.19	79.42	94.00	-14.58	AVG

No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.
1	3733.467	3.11	37.58	40.69	74.00	-33.31	peak
2	3733.467	3.11	27.14	30.25	54.00	-23.75	AVG
3	4879.760	5.53	42.82	48.35	74.00	-25.65	peak
4	4879.760	5.53	33.99	39.52	54.00	-14.48	AVG
Remark: Other frequency mini margin all >20 dB of Limit							

Channel:	TX –X Position High CH	Result:	■ - passed □ - not passed
Test point:	Vertical		
Frequency range:	1GHz-26.5GHz		

No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.
1	2475.00	7.44	72.26	79.70	114.00	-34.3	Peak
2	2475.00	7.44	70.82	78.26	94.00	-15.74	AVG

No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.
1	3336.673	3.92	37.84	41.76	74.00	-32.24	peak
2	3336.673	3.92	26.33	30.25	54.00	-23.75	AVG
3	6136.273	9.23	39.92	49.15	74.00	-24.85	peak
4	6136.273	9.23	28.39	37.62	54.00	-16.38	AVG
Remark: Other frequency mini margin all >20 dB of Limit							

Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

CENTRE OF TESTING SERVICE CO., LTD.
A101，No.65，Zhuji Highway,Tianhe District，Guangzhou, China
Tel：+86-20-85543113 (32 lines) Fax：+86-20-38780406
Complaint line：+86-20-85533471 E-mail：cts@cts-lab.com.cn See Reverse For Terms And Conditions of Service

8.Band Edge Compliance test

8.1. Test Equipment

Band Edge Compliance test					
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal.
1	EMI Test Receiver	ROHDE & SCHWARZ	ESCI	10868	2016/10
2	Log per Antenna	ROHDE & SCHWARZ	HL050	100186	2016/03
3	Signal analyzer	ROHDE & SCHWARZ	FSIQ26	100311	2016/03

8.2. Test Information

EUT	REMOTE CONTROL PLANE
Test Condition	Ambient Temperature: 25°C Humidity: 56%
Test distance	3 Meter
Test Date:	13 January~08 March 2017
Operator	Duke
MODEL NO	9993

8.3. Test procedure

1、 The EUT operates at hopping-off test mode. The lowest or highest channels are tested to verify the largest transmission and spurious emissions power at the continuous transmission mode.
2、 Max hold the trace of the setp 1,and the EUT operates at hopping-on test mode to verify the largest spurious emissions power.
3、 Set the spectrum analyzer in the following setting in order to capture the lower and upper band-edges of the emission:
(a) PEAK: RBW=VBW=1MHz / Sweep=AUTO
(b) AVERAGE: RBW=1MHz ; VBW=3KHz(On time/1)/ Sweep=AUTO

8.4. Test Results

PASSED.

The EUT operates at hopping-off test mode. The lowest and highest channels are tested to verify the band edge emissions.

Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

CENTRE OF TESTING SERVICE CO., LTD.
A101，No.65，Zhuji Highway,Tianhe District，Guangzhou, China
Tel：+86-20-85543113 (32 lines) Fax：+86-20-38780406
Complaint line：+86-20-85533471 E-mail：cts@cts-lab.com.cn

See Reverse For Terms And Conditions of Service

Band Edges (Low)

Detector mode:Peak Polarity:Horizontal



No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.
1	2390.000	6.95	41.36	48.31	74.00	-25.69	peak
2	2400.000	7.01	51.16	58.17	74.00	-15.83	peak
3	2405.000	7.04	77.24	84.28	114.00	-29.72	peak

Detector mode:Average Polarity:Horizontal



No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.
1	2390.000	6.95	26.96	33.91	54.00	-20.09	AVG
2	2400.000	7.01	30.35	37.36	54.00	-16.64	AVG
3	2405.000	7.04	76.84	83.88	94.00	-10.12	AVG

Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

CENTRE OF TESTING SERVICE CO., LTD.
A101，No.65，Zhuji Highway,Tianhe District，Guangzhou, China
Tel：+86-20-85543113 (32 lines) Fax：+86-20-38780406
Complaint line：+86-20-85533471 E-mail：cts@cts-lab.com.cn

See Reverse For Terms And Conditions of Service

Detector mode:Peak **Polarity:Vertical**



No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.
1	2390.000	6.95	41.29	48.24	74.00	-25.76	peak
2	2400.000	7.01	49.58	56.59	74.00	-17.41	peak
3	2405.000	7.04	75.92	82.96	114.00	-31.04	peak

Detector mode:Average **Polarity:Vertical**



No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.
1	2390.000	6.95	26.98	33.93	54.00	-20.07	AVG
2	2400.000	7.01	30.17	37.18	54.00	-16.82	AVG
3	2405.000	7.04	75.36	82.40	94.00	-11.60	AVG

Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

CENTRE OF TESTING SERVICE CO., LTD.
A101，No.65，Zhuji Highway,Tianhe District，Guangzhou, China
Tel：+86-20-85543113 (32 lines) Fax：+86-20-38780406
Complaint line：+86-20-85533471 E-mail：cts@cts-lab.com.cn

See Reverse For Terms And Conditions of Service

Band Edges (High)

Detector mode:Peak Polarity:Horizontal



No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.
1	2475.000	7.44	73.93	81.37	114.00	-32.63	Peak
2	2483.500	7.49	42.21	49.70	74.00	-24.30	Peak
3	2500.000	7.58	37.45	45.03	74.00	-28.97	Peak

Detector mode:Average Polarity:Horizontal



No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.
1	2475.000	7.44	72.25	79.69	94.00	-14.31	AVG
2	2483.500	7.49	26.49	33.98	54.00	-20.02	AVG
3	2500.000	7.58	26.18	33.76	54.00	-20.24	AVG

Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

CENTRE OF TESTING SERVICE CO., LTD.
A101，No.65，Zhuji Highway,Tianhe District，Guangzhou, China
Tel：+86-20-85543113 (32 lines) Fax：+86-20-38780406
Complaint line：+86-20-85533471 E-mail：cts@cts-lab.com.cn See Reverse For Terms And Conditions of Service

Detector mode:Peak **Polarity:Vertical**



No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.
1	2475.000	7.44	72.26	79.70	114.00	-34.30	peak
2	2483.500	7.49	47.06	54.55	74.00	-19.45	peak
3	2500.000	7.58	39.87	47.45	74.00	-26.55	peak

Detector mode:Average **Polarity:Vertical**



No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.
1	2475.000	7.44	70.82	78.26	94.00	-15.73	AVG
2	2483.500	7.49	27.37	34.86	54.00	-19.14	AVG
3	2500.000	7.58	26.62	34.20	54.00	-19.80	AVG

Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

CENTRE OF TESTING SERVICE CO., LTD.
A101，No.65，Zhuji Highway,Tianhe District，Guangzhou, China
Tel：+86-20-85543113 (32 lines) Fax：+86-20-38780406
Complaint line：+86-20-85533471 E-mail：cts@cts-lab.com.cn

See Reverse For Terms And Conditions of Service

9 20 dB Bandwidth test

9.1. Test Equipment

20 dB Bandwidth test					
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal.
1	EMI Test Receiver	ROHDE & SCHWARZ	ESCI	10868	2016/10
2	Log per Antenna	ROHDE & SCHWARZ	HL050	100186	2016/03
3	Signal analyzer	ROHDE & SCHWARZ	FSIQ26	100311	2016/03

9.2. Test Information

EUT	REMOTE CONTROL PLANE
Test Condition	Ambient Temperature: 25°C Humidity: 56%
Test distance	3 Meter
Test Date:	13 January~08 March 2017
Operator	Duke
MODEL NO	9993

8.3. Test Results

PASSED.

The testing data was attached in the next pages.

Channel (MHz)	20dB Bandwidth (MHz)	Limit (MHz)	Test Result
2405	3.744	---	PASSED
2445	3.920	---	PASSED
2475	1.728	---	PASSED

Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

CENTRE OF TESTING SERVICE CO., LTD.
A101，No.65，Zhuji Highway,Tianhe District，Guangzhou, China
Tel：+86-20-85543113 (32 lines) Fax：+86-20-38780406
Complaint line：+86-20-85533471 E-mail：cts@cts-lab.com.cn

See Reverse For Terms And Conditions of Service

Test Plot:





Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

CENTRE OF TESTING SERVICE CO., LTD.
A101，No.65，Zhuji Highway,Tianhe District，Guangzhou, China
Tel：+86-20-85543113 (32 lines) Fax：+86-20-38780406
Complaint line：+86-20-85533471 E-mail：cts@cts-lab.com.cn

See Reverse For Terms And Conditions of Service

20dB Bandwidth High CH:2475MHz



Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

CENTRE OF TESTING SERVICE CO., LTD.
A101，No.65，Zhuji Highway,Tianhe District，Guangzhou, China
Tel：+86-20-85543113 (32 lines) Fax：+86-20-38780406
Complaint line：+86-20-85533471 E-mail：cts@cts-lab.com.cn

See Reverse For Terms And Conditions of Service

10 Antenna Requirements

10.1 Standard Applicable

The EUT is Integral antenna with 0dBi, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

10.2 Antenna Construction and Directional Gain

Antenna type: Integral antenna
Antenna Gain: 0dBi

11.Deviation to test specifications

The following identical model(s):

N/A

Belong to the tested device:

Product description: **REMOTE CONTROL PLANE**
Model name: **9993**

Copyright of this report is owned by Centre of Testing Service and may not be reproduced other than in full except with the written approval of the issuing Company.

CENTRE OF TESTING SERVICE CO., LTD.
A101，No.65，Zhuji Highway,Tianhe District，Guangzhou, China
Tel：+86-20-85543113 (32 lines) Fax：+86-20-38780406
Complaint line：+86-20-85533471 E-mail：cts@cts-lab.com.cn

See Reverse For Terms And Conditions of Service