

# RF Exposure Evaluation Statement

**Product Name:** Smart body fat scale

**Model No.:** Mini-HTBK, Big, Mini Pro, S1 Pro

**FCC ID:** 2ALE7-MINIHTBK

## 1.1 RF Exposure Compliance Requirement

### 1.1.1 Standard Requirement

According to KDB447498D01 General RF Exposure Guidance v06  
Standalone SAR test exclusion considerations

Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied.

### 1.1.2 Limits

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot$$
$$[f(\text{GHz})] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR, where}$$

- ☐ f(GHz) is the RF channel transmit frequency in GHz
- ☐ Power and distance are rounded to the nearest mW and mm before calculation<sup>17</sup>
- ☐ The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is  $\leq 50$  mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is  $< 5$  mm, a distance of 5 mm is applied to determine SAR test exclusion

### 1.1.3 EUT RF Exposure

| Operational Mode: BLE (worst case)                      |                                              |                           |                       |      |                  |                     |
|---------------------------------------------------------|----------------------------------------------|---------------------------|-----------------------|------|------------------|---------------------|
| Channel                                                 | Maximum Peak Conducted Output Power<br>(dBm) | Tune up tolerance<br>(dB) | Maximum tune-up Power |      | Calculated value | Exclusion threshold |
|                                                         |                                              |                           | (dBm)                 | (mW) |                  |                     |
| 2402                                                    | -0.92                                        | ±1                        | 0.08                  | 1.02 | 0.32             | 3.0                 |
| 2442                                                    | -1.13                                        | ±1                        | -0.13                 | 0.97 | 0.30             |                     |
| 2480                                                    | -1.19                                        | ±1                        | -0.19                 | 0.96 | 0.30             |                     |
| Conclusion: the calculated value ≤3.0, SAR is exempted. |                                              |                           |                       |      |                  |                     |