

Test Report Prepared By:

Electronics Test Centre  
27 East Lake Hill  
Airdrie, Alberta  
Canada  
T4A 2K3

[sales@etc-mpbtech.com](mailto:sales@etc-mpbtech.com)  
<http://www.etc-mpb.com>

Telephone: 1-403-912-0037

ETC Report #: t29e19a225-DTS\_FCC Release 2

Report date: August 14, 2019

Test Dates: July 29, 30, August 1 and 2 of 2019

**EMC testing of the Tektelic Communication Inc. Smart Room Sensor**

**in accordance with FCC Part 15.247, ANSI C63.4: 2014 and ANSI C63.10: 2013  
as referenced by FCC OET KDB 558074 D01 15.247 Measurement Guidance  
v05r02.**

**FCC ID: 2ALEPT0006338**

Tested by: Bushra Muharram

Prepared for: Tektelic Communication Inc.

7657 10<sup>th</sup> Street NE  
Calgary, Alberta  
Canada  
T2E 8X2

Telephone: 1-403-338-6910



Bushra Muharram  
[bmuhammad@etc-mpbtech.com](mailto:bmuhammad@etc-mpbtech.com)  
EMC Technologist  
Electronics Test Centre (Airdrie)



Marc Rousseau  
[marc.rousseau@mpbc.ca](mailto:marc.rousseau@mpbc.ca)  
QA Manager  
Electronics Test Centre (Airdrie)

## REVISION RECORD

| ISSUE     | DATE         | AUTHOR      | REVISIONS                                   |
|-----------|--------------|-------------|---------------------------------------------|
| DRAFT 1   | Aug 11, 2019 | M. Rousseau | Initial draft submitted for review.         |
| Release 1 | Aug 12, 2019 | M. Rousseau | Sign off                                    |
| Release 2 | Aug 14, 2019 | M. Rousseau | Correct product name to 'Smart Room Sensor' |
|           |              |             |                                             |
|           |              |             |                                             |
|           |              |             |                                             |

## TABLE OF CONTENTS

|       |                                                                                                                                   |    |
|-------|-----------------------------------------------------------------------------------------------------------------------------------|----|
| 1.0   | INTRODUCTION                                                                                                                      | 5  |
| 1.1   | Scope.....                                                                                                                        | 5  |
| 1.2   | Applicant .....                                                                                                                   | 5  |
| 1.3   | Test Sample Description .....                                                                                                     | 5  |
| 1.4   | General Test Conditions and Assumptions .....                                                                                     | 5  |
| 1.5   | Scope of Testing .....                                                                                                            | 6  |
| 1.5.1 | Test Methodology .....                                                                                                            | 6  |
| 1.5.2 | Variations in Test Methodology.....                                                                                               | 6  |
| 1.5.3 | Test Sample Verification, Configuration & Modifications .....                                                                     | 6  |
| 1.5.4 | Uncertainty of Measurement:.....                                                                                                  | 6  |
| 2.0   | TEST CONCLUSION                                                                                                                   | 7  |
| 2.1   | AC Power Line Conducted Emissions: Transmit Mode .....                                                                            | 8  |
| 2.2   | Channel Occupied Bandwidth (DTS Mode).....                                                                                        | 9  |
| 2.2.1 | Test Guidance: FCC KDB 558074 D01 15.247 Measurement<br>Guidance v05r02/ ANSI C63.10 clause 11.8 .....                            | 9  |
| 2.2.2 | Deviations From The Standard: .....                                                                                               | 9  |
| 2.2.3 | Test Equipment .....                                                                                                              | 9  |
| 2.2.4 | Test Sample Verification, Configuration & Modifications .....                                                                     | 10 |
| 2.2.5 | Channel Occupied Bandwidth Data: (DTS Mode) .....                                                                                 | 10 |
| 2.3   | Maximum conducted (average) output power (DTS Mode) .....                                                                         | 12 |
| 2.3.1 | Test Guidance: FCC KDB 558074 D01 15.247 Measurement<br>Guidance v05r02/ ANSI C63.10 Sub clause 11.9.2.2 .....                    | 12 |
| 2.3.2 | Deviations From The Standard: .....                                                                                               | 12 |
| 2.3.3 | Test Equipment .....                                                                                                              | 13 |
| 2.3.4 | Test Sample Verification, Configuration & Modifications .....                                                                     | 13 |
| 2.3.5 | Peak Output Power Data (DTS Mode).....                                                                                            | 13 |
| 2.4   | Power Spectral Density (DTS Mode).....                                                                                            | 16 |
| 2.4.1 | Test Guidance: FCC KDB 558074 D01 15.247 Measurement<br>Guidance v05r02/ Sub clause 11.10 of ANSI C63.10 .....                    | 16 |
| 2.4.2 | Deviations From The Standard: .....                                                                                               | 16 |
| 2.4.3 | Test Equipment .....                                                                                                              | 16 |
| 2.4.4 | Test Sample Verification, Configuration & Modifications .....                                                                     | 17 |
| 2.4.5 | Peak PSD Data (DTS MODE) .....                                                                                                    | 17 |
| 2.5   | Band Edge Attenuation (DTS Mode) .....                                                                                            | 19 |
| 2.5.1 | Test Guidance: ANSI C63.10-2013 Clause 11.11, 11.13.2 / FCC KDB<br>558074 D01 15.247 Measurement Guidance v05r02 Clause 8.7 ..... | 19 |
| 2.5.2 | Deviations From The Standard: .....                                                                                               | 19 |
| 2.5.3 | Test Equipment .....                                                                                                              | 20 |
| 2.5.4 | Test Sample Verification, Configuration & Modifications .....                                                                     | 20 |
| 2.5.5 | Band Edge Data (DTS MODE) .....                                                                                                   | 20 |
| 2.6   | Conducted Spurious Emissions in non-restricted frequency bands (DTS<br>Mode) .....                                                | 22 |
| 2.6.1 | Test Guidance: ANSI C63.10-2013, Clause 11.11, FCC KDB 558074<br>D01 15.247 Measurement Guidance v05r02 Clause 8.5 .....          | 22 |

|       |                                                                                                                      |    |
|-------|----------------------------------------------------------------------------------------------------------------------|----|
| 2.6.2 | Deviations From The Standard: .....                                                                                  | 22 |
| 2.6.3 | Test Equipment .....                                                                                                 | 22 |
| 2.6.4 | Test Sample Verification, Configuration & Modifications .....                                                        | 22 |
| 2.6.5 | Conducted Emissions Data: .....                                                                                      | 23 |
| 2.7   | EUT Positioning Assessment .....                                                                                     | 30 |
| 2.8   | Radiated Spurious Emissions in restricted frequency bands (TX Mode)....                                              | 31 |
| 2.8.1 | Test Guidance: ANSI C63.10-2013, Clause 11.12 / KDB 558074 D01<br>15.247 Measurement Guidance v05r02 Clause 8.6..... | 31 |
| 2.8.2 | Deviations From The Standard: .....                                                                                  | 31 |
| 2.8.4 | Test Equipment .....                                                                                                 | 32 |
| 2.8.5 | Test Sample Verification, Configuration & Modifications .....                                                        | 32 |
| 2.8.6 | Radiated Emissions Data: .....                                                                                       | 34 |
| 2.9   | RF Exposure .....                                                                                                    | 41 |
| 3.0   | TEST FACILITY .....                                                                                                  | 42 |
| 3.1   | Location .....                                                                                                       | 42 |
| 3.2   | Grounding Plan .....                                                                                                 | 42 |
| 3.3   | Power Supply .....                                                                                                   | 42 |
|       | End of Document .....                                                                                                | 43 |

## **1.0 INTRODUCTION**

### **1.1 Scope**

The purpose of this report is to present the results of compliance testing performed in accordance with FCC Part 15.247, ANSI C63.4-2014 and ANSI C63.10-2013 to gain FCC Certification Authorization for Low-Power License-Exempt transmitters. All test procedures, limits, criteria, and results described in this report apply only to the Tektelic Communication Inc. Smart Room Sensor test sample, referred to herein as the EUT (Equipment Under Test).

The sample has been provided by the customer.

This report does not imply product endorsement by the Electronics Test Centre, A2LA, nor any Canadian Government agency.

### **1.2 Applicant**

This test report has been prepared for Tektelic Communication Inc., located in Calgary, Alberta, Canada.

### **1.3 Test Sample Description**

As provided to ETC (Airdrie) by Tektelic Communication Inc.:

|                                       |                                  |                                                                                                                                                                                                    |
|---------------------------------------|----------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Product Name:</b>                  |                                  | Smart Room Sensor                                                                                                                                                                                  |
| <b>LoRa Radio</b>                     | <b>Frequency Band</b>            | 902 – 928 MHz                                                                                                                                                                                      |
|                                       | <b>Type of Modulation</b>        | Chirp Spread Spectrum                                                                                                                                                                              |
|                                       | <b>BW/Frequency Range</b>        | DTS 500kHz, 903 – 914.9 MHz                                                                                                                                                                        |
|                                       | <b>Associated Antenna</b>        | Pulse Electronics p/n:CW3012, band:902-928MHz, Ceramic chip antenna, 50 Ohms, peak gain 2 dBi                                                                                                      |
|                                       | <b>Detachable/Non Detachable</b> | Non-Detachable                                                                                                                                                                                     |
| <b>Model# / Serial# / description</b> |                                  | T0006115 / 01 / Base variant, Rx 923-928MHz<br>T0006116 / 02 / PIR variant, Rx 923-928MHz<br>T0006163 / 03 / Base variant, Rx 725.9 & 726.5MHz<br>T0006164 / 04 / PIR variant, Rx 725.9 & 726.5MHz |
| <b>Power supply:</b>                  |                                  | Internal Battery (3.2V coin cell)                                                                                                                                                                  |

**Note:** All three Tx channels and axis for T0006164 (PIR variant, Rx 725.9 & 726.5MHz) in Hybrid mode and T0006115 (Base variant, Rx 923-928MHz) in DTS mode were evaluated. Worse Chanel and Axis was selected for detail analysis for radiated emission.

### **1.4 General Test Conditions and Assumptions**

The EUT was set up and exercised using the configurations, modes of operation and arrangements defined in this report only. All inputs and outputs to and from other equipment associated with the EUT were adequately simulated.

In this report, the EUT is only tested for the DTS 500 kHz transmission. Test results regarding Hybrid 125 kHz transmission mode is provided in the separate report.

The environmental conditions are recorded during each test and are reported in the relevant sections of this document.

## 1.5 Scope of Testing

Tests were performed in accordance with FCC Part 15.247, ANSI C63.4: 2014, ANSI C63.10: 2013 as referenced in FCC OET KDB 558074 D01 15.247 Measurement Guidance v05r02.

### 1.5.1 Test Methodology

Test methods are specified in the Basic Standard as referenced and/or modified by the Product Standard in the part of Section 2 of this report associated with each particular test case.

### 1.5.2 Variations in Test Methodology

Any variance in methodology or deviation from the reference Standard is documented in the part of Section 2 of this report associated with each particular Test Case.

### 1.5.3 Test Sample Verification, Configuration & Modifications

EUT setup, configuration, protocols for operation and monitoring of EUT functions, and any modifications performed in order to meet the requirements, are detailed in each Test Case of Section 2 of this report.

### 1.5.4 Uncertainty of Measurement:

The factors contributing to uncertainty of measurement are identified and calculated in accordance with UKAS (United Kingdom Accreditation Service) document “Lab 34, The Expression of Uncertainty in EMC Testing, Aug 2002.” as based on the “ISO Guide to the Expression of Uncertainty in Measurement, 1995.”

This uncertainty estimate represents an expended uncertainty expressed at approximately 95% confidence using a coverage factor of  $k = 2$ .

| Test Method                                   | Uncertainty   |
|-----------------------------------------------|---------------|
| Radiated Emissions Level (9 KHz – 1 GHz)      | $\pm 4.6$ dB  |
| Radiated Emissions Level (1 GHz – 26.5 GHz)   | $\pm 5.31$ dB |
| Conducted Emissions Level (150 KHz – 30 MHz)  | $\pm 2.7$ dB  |
| Uncertainty Conducted Power level             | $\pm 0.5$ dB  |
| Uncertainty Conducted Spurious emission level | $\pm 0.6$ dB  |
| Uncertainty for Bandwidth test                | $\pm 1.5$ %   |

#### Modulation mode: DTS 500 kHz:

DTS modulation system operating in non-frequency hopping. The channels used for the tests are:

Low = 903 MHz

MID = 909.4 MHz (because of the pre-determined list of channels, this is the closest to the center of the band.

High. = 914.9 MHz

## 2.0 TEST CONCLUSION

### STATEMENT OF COMPLIANCE

The customer equipment referred to in this report was found to comply with the requirements, as summarized below.

The EUT was subjected to the following tests. Compliance status is reported as **Compliant** or **Non-compliant**. **N/A** indicates the test was Not Applicable to the EUT.

**Note:** Maintenance of compliance is the responsibility of the Manufacturer. Any modifications to the product should be assessed to determine their potential impact on the compliance status of the EUT with respect to the standards detailed in this test report.

The following table summarizes the tests performed in terms of the specification, class or performance criterion applied, and the EUT modification state.

| Test Case                                                                                                             | Test Type                                               | Specification                | Test Sample       | Modifications | Config.   | Result           |
|-----------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------|------------------------------|-------------------|---------------|-----------|------------------|
| <b>Frequency Range = (903 – 914.2) MHz</b><br><b>500 KHz DTS Mode Max. Conducted Tx Power = 18.45 dBm (0.07 Watt)</b> |                                                         |                              |                   |               |           |                  |
| 2.1                                                                                                                   | AC Conducted Emissions (Tx)                             | 15.207                       | Smart Room Sensor | none          | see § 2.1 | <b>N/A</b>       |
| 2.2                                                                                                                   | Occupied Bandwidth                                      | 15.247(a)(1)<br>15.247(2)(2) | Smart Room Sensor | none          | see § 2.2 | <b>Compliant</b> |
| 2.3                                                                                                                   | Max Average Output Power Conducted                      | 15.247(b)                    | Smart Room Sensor | none          | see § 2.3 | <b>Compliant</b> |
| 2.4                                                                                                                   | Power Spectral Density                                  | 15.247(e)<br>15.247(f)       | Smart Room Sensor | none          | see § 2.4 | <b>Compliant</b> |
| 2.5                                                                                                                   | Band Edge                                               | 15.247(d)                    | Smart Room Sensor | none          | see § 2.5 | <b>Compliant</b> |
| 2.6                                                                                                                   | Conducted Spurious Emission in Non-Restricted Band      | 15.247(d)                    | Smart Room Sensor | none          | see § 2.6 | <b>Compliant</b> |
| 2.7                                                                                                                   | EUT Position                                            | ANSI C63.4                   | Smart Room Sensor | none          | see § 2.7 | <b>Assessed</b>  |
| 2.8                                                                                                                   | Radiated Spurious Emission in Restricted Band (Tx Mode) | 15.205, 15.209<br>15.247(d)  | Smart Room Sensor | none          | see § 2.8 | <b>Compliant</b> |
| 2.9                                                                                                                   | RF Exposure                                             | 15.247(i)                    | Smart Room Sensor | none          | see § 2.9 | <b>Exempt</b>    |

Refer to the test data for applicable test conditions.

## 2.1 AC Power Line Conducted Emissions: Transmit Mode

|                                            |                                   |
|--------------------------------------------|-----------------------------------|
| Test Lab: Electronics Test Centre, Airdrie | EUT: Smart Room Sensor            |
| Test Personnel: N/A                        | Standard: FCC Part 15.207         |
| Date: N/A                                  | Basic Standard: ANSI C63.10: 2013 |
| <b>EUT status: Not Applicable</b>          |                                   |

The Smart Room Sensor is only battery operated and can not be connected to AC main.

## 2.2 Channel Occupied Bandwidth (DTS Mode)

|                                                   |                                                                                                 |
|---------------------------------------------------|-------------------------------------------------------------------------------------------------|
| <b>Test Lab:</b> Electronics Test Centre, Airdrie | <b>EUT:</b> Smart Room Sensor                                                                   |
| <b>Test Personnel:</b> Bushra Muharram            | <b>Standard:</b> FCC PART 15.247                                                                |
| <b>Date:</b> 2019-08-01, 02 (22.6°C, 45% RH)      | <b>Basic Standard:</b> ANSI C63.10-2013<br>KDB 558074 D01 15.247<br>Measurement Guidance v05r02 |
| <b>EUT status: Compliant</b>                      |                                                                                                 |

**Specification:** FCC Part 15.247 (a, 2), FCC 15.215 (c)

**Criteria:** Systems using digital modulation techniques may operate in the 902-928 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

### 2.2.1 Test Guidance: FCC KDB 558074 D01 15.247 Measurement Guidance v05r02/ ANSI C63.10 clause 11.8

This measurement is performed at low, mid and high frequencies, with modulation.

The RF output of EUT with an antenna connector is fed to the input of the spectrum analyzer through appropriate attenuation. The loss from the cable and the attenuator were added on the analyzer as gain offset setting there by allowing direct measurements, without the need for any further corrections.

|                                                                                                                                                         |                                                                   |
|---------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------|
| Use the following spectrum analyzer settings:                                                                                                           |                                                                   |
| Span                                                                                                                                                    | between two times and five times the channel center frequency OBW |
| RBW                                                                                                                                                     | 100 KHz                                                           |
| VBW                                                                                                                                                     | Set the VBW $\geq [3 \times \text{RBW}]$ .                        |
| Sweep                                                                                                                                                   | Auto Couple                                                       |
| Detector function                                                                                                                                       | peak                                                              |
| Trace mode                                                                                                                                              | max hold                                                          |
| Allow the trace to stabilize. The automatic bandwidth measurement capability of an instrument employed using the X dB bandwidth mode with X set to 6 dB |                                                                   |

### 2.2.2 Deviations From The Standard:

There were no deviations from the EUT setup or methodology specified in the standard.

### 2.2.3 Test Equipment

Testing was performed with the following equipment:

| Equipment              | Manufacturer          | Model #                | Asset # | Cal. Date  | Cal. Due   |
|------------------------|-----------------------|------------------------|---------|------------|------------|
| EMI receiver           | Agilent               | N9038A<br>(FW A.23.07) | 6130    | 2019-05-10 | 2020-05-10 |
| Temp/Humidity          | Extech                | 42270                  | 5892    | 2019-04-05 | 2020-04-05 |
| Attenuator             | FairView<br>Microwave | SA18N5WA-10            | 6886    | 2018-11-23 | 2019-11-23 |
| DC Blocker             | MCL                   | BLK-89-S+              | -       | 2019-01-15 | 2020-01-15 |
| CE Cable (50cm length) | Huber+Suhner          | Enviroflex 400         | -       | 2019-01-15 | 2020-01-15 |

## 2.2.4 Test Sample Verification, Configuration & Modifications


The EUT was set to transmit continuously on a selected channel with test-specific software. The output was modulated as in normal operation. The EUT modified to provide the direct access to antenna trace for conducted measurements.

For compliance purposes EUT met requirements without any modification

There is no Deviation and exclusions from test specifications.

**Test setup diagrams for Occupied Bandwidth testing:**

**Conducted:**




## 2.2.5 Channel Occupied Bandwidth Data: (DTS Mode)


### Lora 500 KHz Channels

| Channel | Freq. [MHz] | 6 dB OBW [kHz] | 99% OBW [KHz] | Limit 6 dB OBW |
|---------|-------------|----------------|---------------|----------------|
| Low     | 903         | 643.8          | 682.03        | ≥ 500 KHz      |
| Mid     | 909.4       | 644.1          | 683.51        | ≥ 500 KHz      |
| High    | 914.9       | 643.0          | 678.97        | ≥ 500 KHz      |


### Low channel



## Mid channel



## High channel



## 2.3 Maximum conducted (average) output power (DTS Mode)

|                                            |                                                         |
|--------------------------------------------|---------------------------------------------------------|
| Test Lab: Electronics Test Centre, Airdrie | EUT: Smart Room Sensor                                  |
| Test Personnel: Bushra Muharram            | Standard: FCC PART 15.247                               |
| Date: 2019-08-01, 02 (22.6°C, 45% RH)      | Basic Standard: ANSI C63.10: 2013<br>FCC OET KDB 558074 |
| <b>EUT status: Compliant</b>               |                                                         |

Specification: FCC Part 15.247(b, 3)

**Criteria** For systems using digital modulation in the 902-928 MHz bands: 1 Watt.

### 2.3.1 Test Guidance: FCC KDB 558074 D01 15.247 Measurement Guidance v05r02/ ANSI C63.10 Sub clause 11.9.2.2

This measurement is performed at low, mid and high frequencies, with modulation.

The RF output of EUT with an antenna connector is fed to the input of the spectrum analyzer through appropriate attenuation. The loss from the cable and the attenuator were added on the analyzer as gain offset setting there by allowing direct measurements, without the need for any further corrections.

| Output Power Method AVGSA-1 |                                                                                                                                                     |
|-----------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------|
| Span                        | ≥ 1.5 times the OBW                                                                                                                                 |
| RBW                         | 1 – 5 % of the OBW, ≤ 1 MHz                                                                                                                         |
| VBW                         | ≥ 3 x RBW                                                                                                                                           |
| Number of Points in sweep   | ≥ 2 x Span / RBW                                                                                                                                    |
| Sweep time                  | Auto                                                                                                                                                |
| Detector                    | RMS (Power Averaging)                                                                                                                               |
| Sweep trigger               | Free Run (If Duty Cycle ≥98%)                                                                                                                       |
| Trace Average               | At least 100 traces in power Averaging (RMS)                                                                                                        |
| Power measured              | Integrated the spectrum across the OBW of the signal using the S/A band power measurement function, with band limit set equal to the OBW band edge. |

### 2.3.2 Deviations From The Standard:

There were no deviations from the EUT setup or methodology specified in the standard.

### 2.3.3 Test Equipment

Testing was performed with the following equipment:

| Equipment              | Manufacturer          | Model #                | Asset # | Cal. Date  | Cal. Due   |
|------------------------|-----------------------|------------------------|---------|------------|------------|
| EMI receiver           | Agilent               | N9038A<br>(FW A.23.07) | 6130    | 2019-05-10 | 2020-05-10 |
| Temp/Humidity          | Extech                | 42270                  | 5892    | 2019-04-05 | 2020-04-05 |
| Attenuator             | FairView<br>Microwave | SA18N5WA-10            | 6886    | 2018-11-23 | 2019-11-23 |
| DC Blocker             | MCL                   | BLK-89-S+              | -       | 2019-01-15 | 2020-01-15 |
| CE Cable (50cm length) | Huber+Suhner          | Enviroflex 400         | -       | 2019-01-15 | 2020-01-15 |

### 2.3.4 Test Sample Verification, Configuration & Modifications

The EUT was set to a selected channel with test-specific software. The output was modulated as in normal operation.

The EUT modified to provide the direct access to antenna trace for conducted measurements.

For compliance purposes EUT met requirements without any modification

#### Test setup diagrams for Peak Power testing:

Conducted:




### 2.3.5 Peak Output Power Data (DTS Mode)


#### LoRa 500 KHz

| Channel | Freq.<br>[MHz] | Output Power<br>(dBm) | Output Power<br>Limit<br>(dBm) | Margin<br>(dB) |
|---------|----------------|-----------------------|--------------------------------|----------------|
| Low     | 903            | 15.31                 | 30                             | 14.69          |
| Mid     | 909.4          | 12.99                 | 30                             | 17.01          |
| High    | 914.9          | 14.17                 | 30                             | 15.83          |


## Low channel



## Mid channel



## High channel



## 2.4 Power Spectral Density (DTS Mode)

|                                            |                                                         |
|--------------------------------------------|---------------------------------------------------------|
| Test Lab: Electronics Test Centre, Airdrie | EUT: Smart Room Sensor                                  |
| Test Personnel: Bushra Muharram            | Standard: FCC PART 15.247                               |
| Date: 2019-08-01, 02 (22.6°C, 45% RH)      | Basic Standard: ANSI C63.10: 2013<br>FCC OET KDB 558074 |
| <b>EUT status: Compliant</b>               |                                                         |

### Specification: FCC Part 15.247(e)

**Criteria** For digitally modulated systems the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

#### 2.4.1 Test Guidance: FCC KDB 558074 D01 15.247 Measurement Guidance v05r02/ Sub clause 11.10 of ANSI C63.10

This measurement is performed at low, mid and high frequencies, in continuous transmission, with modulation.

The RF output of EUT with an antenna connector is fed to the input of the spectrum analyzer through appropriate attenuation. The loss from the cable and the attenuator were added on the analyzer as gain offset setting there by allowing direct measurements, without the need for any further corrections.

|                                                                                                      |                                                                    |
|------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------|
| Use the following spectrum analyzer settings:                                                        |                                                                    |
| Span                                                                                                 | At least 1.5 times the OBW.                                        |
| RBW                                                                                                  | 3 KHz                                                              |
| VBW                                                                                                  | Set the VBW $\geq [3 \times \text{RBW}]$ .                         |
| Sweep                                                                                                | Auto Couple                                                        |
| Detector function                                                                                    | Power averaging (RMS) or sample detector (when RMS not available). |
| Trace mode                                                                                           | Employ trace averaging (RMS) mode over a minimum of 100 traces.    |
| Allow the trace to stabilize. Use the peak marker function to determine the maximum amplitude level. |                                                                    |

#### 2.4.2 Deviations From The Standard:

There were no deviations from the EUT setup or methodology specified in the standard.

#### 2.4.3 Test Equipment

Testing was performed with this equipment:


| Equipment              | Manufacturer          | Model #                | Asset # | Cal. Date  | Cal. Due   |
|------------------------|-----------------------|------------------------|---------|------------|------------|
| EMI receiver           | Agilent               | N9038A<br>(FW A.23.07) | 6130    | 2019-05-10 | 2020-05-10 |
| Temp/Humidity          | Extech                | 42270                  | 5892    | 2019-04-05 | 2020-04-05 |
| Attenuator             | FairView<br>Microwave | SA18N5WA-10            | 6886    | 2018-11-23 | 2019-11-23 |
| DC Blocker             | MCL                   | BLK-89-S+              | -       | 2019-01-15 | 2020-01-15 |
| CE Cable (50cm length) | Huber+Suhner          | Enviroflex 400         | -       | 2019-01-15 | 2020-01-15 |

## 2.4.4 Test Sample Verification, Configuration & Modifications

The EUT was set to transmit continuously on a selected channel with test-specific software. The output was modulated as in normal operation. The EUT met the requirements without modification.

Test setup diagrams for Peak Power Spectral Density testing:

Conducted:




## 2.4.5 Peak PSD Data (DTS MODE)


### 500 KHZ Channels

| Channel | Freq. [MHz] | PSD (dBm/3KHz) | PSD Limit (dBm/3KHz) |
|---------|-------------|----------------|----------------------|
| Low     | 903         | -6.063         | 8                    |
| Mid     | 909.4       | -6.985         | 8                    |
| High    | 914.9       | -6.716         | 8                    |


### Low channel



## Mid channel



## High channel



## 2.5 Band Edge Attenuation (DTS Mode)

Test Lab: Electronics Test Centre, Airdrie

EUT: Smart Room Sensor

Test Personnel: Bushra Muharram

Standard: FCC PART 15.247

Date: 2019-08-01, 02 (22.6°C, 45% RH)

Basic Standard: ANSI C63.10: 2013

**EUT status: Compliant**

### Specification: FCC Part 15.247(d)

**Criteria:** In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

### 2.5.1 Test Guidance: ANSI C63.10-2013 Clause 11.11, 11.13.2 / FCC KDB 558074 D01 15.247 Measurement Guidance v05r02 Clause 8.7

This measurement is performed at the low and high frequencies, with modulation.

The RF output of EUT with an antenna connector is fed to the input of the spectrum analyzer through appropriate attenuation. The loss from the cable and the attenuator were added on the analyzer as gain offset setting there by allowing direct measurements, without the need for any further corrections.

Use the following spectrum analyzer settings:

|                   |                                                                                                            |
|-------------------|------------------------------------------------------------------------------------------------------------|
| Span              | That encompasses both the peak of the fundamental emission and the band-edge emission under investigation. |
| RBW               | 100 kHz                                                                                                    |
| VBW               | Set the VBW $\geq [3 \times \text{RBW}]$ .                                                                 |
| Sweep             | Auto Couple                                                                                                |
| Detector function | Peak                                                                                                       |
| Trace mode        | Max Hold.                                                                                                  |

Allow the trace to stabilize. Use the peak marker function to determine the maximum amplitude level.

### 2.5.2 Deviations From The Standard:

There were no deviations from the EUT setup or methodology specified in the standard.

### 2.5.3 Test Equipment

Testing was performed with the following equipment:

| Equipment              | Manufacturer          | Model #                | Asset # | Cal. Date  | Cal. Due   |
|------------------------|-----------------------|------------------------|---------|------------|------------|
| EMI receiver           | Agilent               | N9038A<br>(FW A.23.07) | 6130    | 2019-05-10 | 2020-05-10 |
| Temp/Humidity          | Extech                | 42270                  | 5892    | 2019-04-05 | 2020-04-05 |
| Attenuator             | FairView<br>Microwave | SA18N5WA-10            | 6886    | 2018-11-23 | 2019-11-23 |
| DC Blocker             | MCL                   | BLK-89-S+              | -       | 2019-01-15 | 2020-01-15 |
| CE Cable (50cm length) | Huber+Suhner          | Enviroflex 400         | -       | 2019-01-15 | 2020-01-15 |

### 2.5.4 Test Sample Verification, Configuration & Modifications

The EUT was set to transmit continuously on a selected channel with test-specific software. The output was modulated as in normal operation. The EUT met the requirements without modification.

Test setup diagrams for Band Edge Attenuation testing:


Conducted:




### 2.5.5 Band Edge Data (DTS MODE)

| Modulation      | Channel | Attenuation at Band Edge | Attenuation Limit at Band Edge |
|-----------------|---------|--------------------------|--------------------------------|
| 500KHz Channels | 903     | 48.545 dBc               | 30 dBc                         |
|                 | 914.9   | 65.058 dBc               | 30 dBc                         |

## Low band edge



## High band edge



## 2.6 Conducted Spurious Emissions in non-restricted frequency bands (DTS Mode)

|                                            |                                                               |
|--------------------------------------------|---------------------------------------------------------------|
| Test Lab: Electronics Test Centre, Airdrie | EUT: Smart Room Sensor                                        |
| Test Personnel: Bushra Muharram            | Standard: FCC PART 15.247                                     |
| Date: 2019-08-01, 02 (22.6°C, 45% RH)      | Basic Standard: ANSI C63.4-2014<br>FCC OET KDB 558470 v04 DTS |

### EUT status: Compliant

#### Specification: FCC Part 15.247(d)

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.

#### 2.6.1 Test Guidance: ANSI C63.10-2013, Clause 11.11, FCC KDB 558074 D01 15.247 Measurement Guidance v05r02 Clause 8.5

This measurement is performed at the low, mid and high frequencies, with modulation. The RF output of EUT with an antenna connector is fed to the input of the spectrum analyzer through appropriate attenuation. The loss from the cable and the attenuator were added on the analyzer as gain offset setting there by allowing direct measurements, without the need for any further corrections.

The spectrum analyzer is stepped through the spectrum in frequency spans selected to ensure acceptable frequency resolution. The RBW is set to 100 kHz. The VBW is set to  $\geq 300$  kHz. The Peak detector is used, with the trace set to Max Hold.

#### 2.6.2 Deviations From The Standard:

There were no deviations from the EUT setup or methodology specified in the standard.

#### 2.6.3 Test Equipment

Testing was performed with the following equipment:


| Equipment              | Manufacturer          | Model #                | Asset # | Cal. Date  | Cal. Due   |
|------------------------|-----------------------|------------------------|---------|------------|------------|
| EMI receiver           | Agilent               | N9038A<br>(FW A.23.07) | 6130    | 2019-05-10 | 2020-05-10 |
| Temp/Humidity          | Extech                | 42270                  | 5892    | 2019-04-05 | 2020-04-05 |
| Attenuator             | FairView<br>Microwave | SA18N5WA-10            | 6886    | 2018-11-23 | 2019-11-23 |
| DC Blocker             | MCL                   | BLK-89-S+              | -       | 2019-01-15 | 2020-01-15 |
| CE Cable (50cm length) | Huber+Suhner          | Enviroflex 400         | -       | 2019-01-15 | 2020-01-15 |

#### 2.6.4 Test Sample Verification, Configuration & Modifications

The EUT was set to a selected channel with test-specific software. The output was modulated as in normal operation. The EUT met the requirements without modification.


The EUT modified to provide the direct access to antenna trace for conducted measurements.

## Test setup diagram for Conducted Spurious Emissions testing:





## 2.6.5 Conducted Emissions Data:


Low channel




# Low channel





### Low channel




### Mid channel




# Mid channel





### Mid channel




### High channel



# High channel



# High channel



## 2.7 EUT Positioning Assessment

|                                                                                                                                                                                                |                                 |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------|
| Test Lab: Electronics Test Centre, Airdrie                                                                                                                                                     | EUT: Smart Room Sensor          |
| Test Personnel: Bushra Muharram                                                                                                                                                                | Standard: FCC PART 15.247       |
| Date: 2019-07-29 (23.0°C,35% RH)                                                                                                                                                               | Basic Standard: ANSI C63.4-2014 |
| <b>2<sup>nd</sup> Axis Found worse</b>                                                                                                                                                         |                                 |
| <b>Comments:</b> EUT oriented in three axis's and measurement performed for low, mid and high channels. For both EUT variants, the <b>2<sup>nd</sup> axis</b> found to be worse emission axis. |                                 |

### Specification: ANSI C63.4-2014, Clause 6.3.2.1

Portable, small, lightweight, or modular devices that may be handheld, worn on the body, or placed on a table during operation shall be positioned on a non-conducting platform, the top of which is 80 cm above the reference ground plane. The preferred area occupied by the EUT arrangement is 1 m by 1.5 m, but it may be larger or smaller to accommodate various sized EUTs (see Figure 6, Figure 7, and Figure 9). For testing purposes, ceiling- and wall-mounted devices also shall be positioned on a tabletop (see also 6.3.4 and 6.3.5). In making any tests involving handheld, body-worn, or ceiling-mounted equipment, it is essential to recognize that the measured levels may be dependent on the orientation (attitude) of the three orthogonal axes of the EUT. Thus, exploratory tests as specified in 8.3.1 shall be carried out for various axes orientations to determine the attitude having maximum or near-maximum emission level.

See photos in Test Setup photo exhibit.

## 2.8 Radiated Spurious Emissions in restricted frequency bands (TX Mode)

|                                                   |                                  |
|---------------------------------------------------|----------------------------------|
| Test Lab: Electronics Test Centre, Airdrie        | EUT: Smart Room Sensor           |
| Test Personnel: Bushra Muharram                   | Standard: FCC PART 15.247        |
| Date: July 29, 30, Aug 1 of 2019 (23.0°C, 35% RH) | Basic Standard: ANSI C63.10-2013 |

**EUT status: Compliant**

### Specification: FCC PART 15.247(d)

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

### 2.8.1 Test Guidance: ANSI C63.10-2013, Clause 11.12 / KDB 558074 D01 15.247 Measurement Guidance v05r02 Clause 8.6

From 9 kHz to 150 kHz (resolution bandwidth of 200 Hz) and from 150 kHz to 30 MHz (resolution bandwidth 9 kHz) measurements are performed with a loop antenna (as per KDB 460108).

From 30 MHz to 1000 MHz, measurements are performed with a broadband biconilog antenna and a resolution bandwidth of 120 kHz.

Above 1000 MHz, measurements are performed with a DRG Horn antenna or a Standard Gain horn, and a resolution bandwidth of 1 MHz. The EUT is raised to 150 cm above the ground plane, and the area between the EUT and the antenna mast is covered with RF absorbent material.

The scan is performed at discrete increments of turntable azimuth and antenna height, which are selected in accordance with the applicable standard in order to assure capture of frequencies of interest. Optimization is performed based on the scan data.

Frequencies having peak emissions within 10dB of the limits are optimized. The EUT is rotated in azimuth over 360 degrees and the direction of maximum emission is noted.

Antenna height is varied from 1 – 4 meters at this azimuth to obtain the maximum emission. Then the maximum level is measured with the appropriate detector and recorded. Up to 1 GHz, measurements are performed with a Quasi-Peak detector. Above 1 GHz, measurements are recorded with Peak and/or Average detectors, as applicable.

### 2.8.2 Deviations From The Standard:

There were no deviations from the EUT setup or methodology specified in the standard.

## 2.8.4 Test Equipment

Testing was performed with the following equipment:


| Equipment                           | Manufacturer        | Model #                     | Asset #        | Calibration Date | Calibration Due |
|-------------------------------------|---------------------|-----------------------------|----------------|------------------|-----------------|
| EMC Software                        | UL                  | Ver. 9.5                    | ETC-SW-EMC 2.1 | N/A              |                 |
| EMI receiver                        | Agilent             | N9038A<br>(FW A.23.07)      | 6130           | 2019-05-10       | 2020-05-10      |
| Loop Antenna                        | EMCO                | 6502                        | 10868          | 2019-04-11       | 2020-04-11      |
| Biconilog Antenna                   | ARA                 | LPB-2520/A                  | 4318           | 2018-09-19       | 2020-09-19      |
| DRG Horn                            | EMCO                | 3115                        | 19357          | 2018-09-12       | 2020-09-12      |
| Humidity/Temp Logger                | Extech Ins. Corp.   | 42270                       | 5892           | 2019-04-05       | 2020-04-05      |
| Low Noise Amplifier<br>(1 – 18 GHz) | MITEQ               | JS43-01001800-21-5P         | 4354           | 2019-01-03       | 2020-01-03      |
| Pre-Amplifier<br>(30 – 1300 MHz)    | hp                  | 8447D                       | 9291           | 2019-01-03       | 2020-01-03      |
| RE Cable below 1GHz                 | Insulated Wire Inc. | KPS-1501A-3600-KPA-01102006 | 4419           | 2019-01-03       | 2020-01-03      |
| Re Cable Above 1 GHz                | A.H. System Inc.    | SAC-26G-8.23                | 6187           | 2019-01-03       | 2020-01-03      |

## 2.8.5 Test Sample Verification, Configuration & Modifications

The EUT was set to a selected channel with test-specific software. The output was modulated as in normal operation.

The EUT met the requirements without modification.

**Test setup diagram for Radiated Spurious Emissions testing (below 1GHz):**



Above 1GHz, the EUT is raised using a low permittivity material (polystyrene) to a height of 1.5m.

## FCC Part 15.205 Restricted Bands of Operation:

| MHz                        | MHz                   | MHz             | GHz              |
|----------------------------|-----------------------|-----------------|------------------|
| 0.090 - 0.110              | 16.42 - 16.423        | 399.9 - 410     | 4.5 - 5.15       |
| <sup>1</sup> 0.495 - 0.505 | 16.69475 - 16.69525   | 608 - 614       | 5.35 - 5.46      |
| 2.1735 - 2.1905            | 16.80425 - 16.80475   | 960 - 1240      | 7.25 - 7.75      |
| 4.125 - 4.128              | 25.5 - 25.67          | 1300 - 1427     | 8.025 - 8.5      |
| 4.17725 - 4.17775          | 37.5 - 38.25          | 1435 - 1626.5   | 9.0 - 9.2        |
| 4.20725 - 4.20775          | 73 - 74.6             | 1645.5 - 1646.5 | 9.3 - 9.5        |
| 6.215 - 6.218              | 74.8 - 75.2           | 1660 - 1710     | 10.6 - 12.7      |
| 6.26775 - 6.26825          | 108 - 121.94          | 1718.8 - 1722.2 | 13.25 - 13.4     |
| 6.31175 - 6.31225          | 123 - 138             | 2200 - 2300     | 14.47 - 14.5     |
| 8.291 - 8.294              | 149.9 - 150.05        | 2310 - 2390     | 15.35 - 16.2     |
| 8.362 - 8.366              | 156.52475 - 156.52525 | 2483.5 - 2500   | 17.7 - 21.4      |
| 8.37625 - 8.38675          | 156.7 - 156.9         | 2690 - 2900     | 22.01 - 23.12    |
| 8.41425 - 8.41475          | 162.0125 - 167.17     | 3260 - 3267     | 23.6 - 24.0      |
| 12.29 - 12.293             | 167.72 - 173.2        | 3332 - 3339     | 31.2 - 31.8      |
| 12.51975 - 12.52025        | 240 - 285             | 3345.8 - 3358   | 36.43 - 36.5     |
| 12.57675 - 12.57725        | 322 - 335.4           | 3600 - 4400     | ( <sup>2</sup> ) |
| 13.36 - 13.41              |                       |                 |                  |

<sup>1</sup> Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz, <sup>2</sup> Above 38.6

The field strength of emissions appearing within these frequency bands shall not exceed the limits shown in 15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000 MHz, compliance with the emission limits in 15.209 shall be demonstrated based on the average value of the measured emissions.

### Specification: FCC15.209 Radiated emission limits.

Except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

| Frequency (MHz) | Field strength (microvolts/meter) | Measurement distance (meters) |
|-----------------|-----------------------------------|-------------------------------|
| 0.009 - 0.490   | 2400/F(kHz)                       | 300                           |
| 0.490 - 1.705   | 24000/F(kHz)                      | 30                            |
| 1.705 - 30.0    | 30                                | 30                            |
| 30 - 88         | 100                               | 3                             |
| 88 - 216        | 150                               | 3                             |
| 216 - 960       | 200                               | 3                             |
| Above 960       | 500                               | 3                             |

## 2.8.6 Radiated Emissions Data:

The emissions data are presented in tabular form, showing turntable azimuth, antenna height and polarization, the uncorrected spectrum analyzer reading, the correction factors applied, the net result, the value of the limit at the frequency investigated, and the Delta between the result and the limit.

**Meter Reading in dBμV + Antenna Factor in dB/m + Gain/Loss Factor in dB = Corrected Field Strength in dBμV/m.**

**Delta = Field Strength - Limit**

**Notes:** When a preamp is used, the resulting gain is compensated, producing a negative value for the Cable Loss.

- Measurements reported are the result of adjusting the turntable azimuth and antenna height to obtain the maximum EUT emission. This may produce a different reading than the plot trace. The plot is a Peak Hold function obtained at discrete increments of height and azimuth, while the reported measurement is obtained with the appropriate Quasi Peak or Average detector after the height and azimuth have been adjusted for maximum emission.
- Preliminary scans were performed for all channels in Transmit modes. The High band channel 914.9 MHz was selected as the worst-case condition for detailed examination.
- In Transmit mode, the EUT was assessed up to 10.0 GHz.


**Negative values for Delta indicate compliance.**

| Freq. Marker | Freq. [MHz] | Raw reading[dBμv] | Det       | Antenna Factor [dB/m] | Cable Loss [dB] | Corrected Reading [dBμv/m] | FCC 15.207 Limit [dBμv/m] | Delta [dB]      | azimuth [Deg] | Height [cm] | Polarization |
|--------------|-------------|-------------------|-----------|-----------------------|-----------------|----------------------------|---------------------------|-----------------|---------------|-------------|--------------|
| 1            | 868.3999    | 3.01              | QP        | 25.5                  | 7               | 35.51                      | 46.02                     | -10.51          | 338           | 396         | Horizontal   |
| 2            | 931.6162    | 2.6               | QP        | 26.4                  | 7.3             | 36.3                       | 46.02                     | -9.72           | 62            | 384         | Horizontal   |
| 3            | 942.9867    | 2.7               | QP        | 26.3                  | 7.3             | 36.38                      | 46.02                     | -9.64           | 228           | 286         | Horizontal   |
| 4            | 933.8592    | 2.41              | QP        | 26.3                  | 7.3             | 36.01                      | 46.02                     | -10.01          | 111           | 315         | Vertical     |
| 1            | 2723        | 48.72<br>55.21    | Ave<br>Pk | 29.7                  | -33.4           | 45.02<br>51.51             | 53.98<br>73.97            | -8.96<br>-22.46 | 21            | 153         | Horizontal   |
| 2            | 2723        | 38.79<br>47.27    | Ave<br>Pk | 29.7                  | -33.4           | 35.09<br>43.57             | 53.98<br>73.97            | -18.89<br>-30.4 | 247           | 101         | Vertical     |
| 1            | 3631.5      | 40.92<br>49.18    | Ave<br>Pk | 31.6                  | -32.5           | 40.02<br>48.28             | 53.98<br>73.97            | 13.96<br>-25.69 | 332           | 108         | Horizontal   |
| 2            | 4539.9      | 34.73<br>45.79    | Ave<br>Pk | 32.4                  | -31.3           | 35.83<br>46.89             | 53.98<br>73.97            | 18.15<br>-27.08 | 7             | 190         | Horizontal   |
| 3            | 5447.4      | 34.12<br>45.83    | Ave<br>Pk | 34                    | -30.3           | 37.82<br>49.53             | 53.98<br>73.97            | 16.16<br>-24.44 | 305           | 389         | Horizontal   |
| 4            | 7263.3      | 38.83<br>51.16    | Ave<br>Pk | 36.3                  | -27.3           | 47.83<br>60.16             | 53.98<br>73.97            | -6.15<br>-13.81 | 266           | 218         | Horizontal   |


|    |        |                |           |      |       |                |                |                          |     |     |            |
|----|--------|----------------|-----------|------|-------|----------------|----------------|--------------------------|-----|-----|------------|
| 5  | 8168.3 | 30.94<br>45.41 | Ave<br>Pk | 36.7 | -27   | 40.64<br>55.11 | 53.98<br>73.97 | -<br>13.34<br>-<br>18.86 | 299 | 244 | Horizontal |
| 6  | 9077.3 | 33.87<br>47.75 | Ave<br>Pk | 37.5 | -26.3 | 45.07<br>58.95 | 53.98<br>73.97 | -8.91<br>-<br>15.02      | 46  | 145 | Horizontal |
| 7  | 3632   | 37.19<br>48.42 | Ave<br>Pk | 31.6 | -32.5 | 36.29<br>47.52 | 53.98<br>73.97 | -<br>17.69<br>-<br>26.45 | 5   | 146 | Vertical   |
| 8  | 4538.9 | 31.27<br>42.22 | Ave<br>Pk | 32.4 | -31.3 | 32.37<br>43.32 | 53.98<br>73.97 | -<br>21.61<br>-<br>30.65 | 1   | 142 | Vertical   |
| 9  | 5445.4 | 27.82<br>41.16 | Ave<br>Pk | 34   | -30.3 | 31.52<br>44.86 | 53.98<br>73.97 | -<br>22.46<br>-<br>29.11 | 201 | 116 | Vertical   |
| 10 | 7264.3 | 31.82<br>48.03 | Ave<br>Pk | 36.3 | -27.3 | 40.82<br>57.03 | 53.98<br>73.97 | -<br>13.16<br>-<br>16.94 | 170 | 136 | Vertical   |
| 11 | 8170.8 | 30.19<br>43.67 | Ave<br>Pk | 36.7 | -27   | 39.89<br>53.37 | 53.98<br>73.97 | -<br>14.09<br>-20.6      | 214 | 100 | Vertical   |
| 12 | 9078.3 | 29.83<br>43.69 | Ave<br>Pk | 37.5 | -26.3 | 41.03<br>54.89 | 53.98<br>73.97 | -<br>12.95<br>-<br>19.08 | 227 | 101 | Vertical   |

\* Restricted Band


## Plot of Radiated Emissions: Measuring Antenna Parallel




## Plot of Radiated Emissions: Measuring Antenna Perpendicular




## Plot of Radiated Emissions: Horizontal polarization




## Plot of Radiated Emissions: Vertical polarization




## Plot of Radiated Emissions: Horizontal polarization




## Plot of Radiated Emissions: Vertical polarization




## Plot of Radiated Emissions: Horizontal polarization




## Plot of Radiated Emissions: Vertical polarization



## Plot of Radiated Emissions: Horizontal polarization



## Plot of Radiated Emissions: Vertical polarization



## 2.9 RF Exposure

|                                            |                           |
|--------------------------------------------|---------------------------|
| Test Lab: Electronics Test Centre, Airdrie | EUT: Smart Room Sensor    |
| Test Personnel:                            | Standard: FCC PART 15.247 |
| Date:                                      |                           |
| EUT status: Exempt                         |                           |

**Compliant:** RF exposure assessment to be provided in a separate Exhibit.

## **3.0 TEST FACILITY**

### **3.1 Location**

The Smart Room Sensor was tested for emissions at the Electronics Test Centre laboratory located in Airdrie, Alberta, Canada. The Radio Frequency Anechoic Chamber (RFAC), identified as Chamber 1, has a usable working space measuring 10.6 m long x 7.3 m wide x 6.5 m high.

Measurements taken at this site are accepted by Industry Canada as evidence of conformity per registration file # 2046A. This site is also listed with the FCC under Registration Number CA2046.

The floor, walls and ceiling consist of annealed steel panels. The walls and ceiling are covered with ferrite tile, augmented by RF absorbant foam material on the end wall nearest the turntable, and on the adjacent walls and the ceiling. The chamber floor supports a 15 cm high internal floor, constructed of annealed steel panels, that forms the ground plane, and is bonded to the chamber walls.

The 3-m diameter turntable is flush-mounted with the floor. A sub-floor cable-way is provided to route cables between the turntable pit and EUT support equipment located in the Control Room. Cables reach the EUT through an opening in the centre of the turntable.

Test instrumentation and EUT support equipment is located in the Control Room, consisting of two shielded vestibules joined together at the side of the main room. Cables are routed through bulkhead panels between the rooms and the test chamber as required. Power feeds are routed into the main room and vestibules through line filters providing at least 100 dB of attenuation between 10 kHz and 10 GHz.

Either floor mounted or table-top equipment can be tested at this facility.

### **3.2 Grounding Plan**

The Smart Room Sensor was placed at the centre of the test chamber turntable on top of an 80-cm high polystyrene foam table. The EUT was grounded according to Tektelic Communication Inc. specifications.

### **3.3 Power Supply**

All EUT power was supplied by an internal rechargeable battery. There is no EUT function while the battery is charging.

**End of Document**