



FCC PART 15.247

TEST REPORT

For

PROMETHEUS GROUP LLC

PO BOX 130100 BIRMINGHAM, ALABAMA 35213-0100 USA

FCC ID: 2ALGTBTC-SC

Report Type: Original Report	Product Type: Aspect Camera
Report Number: SZNS210705-27346E-RF	
Report Date: 2021-07-30	
Reviewed By: RF Engineer	Candy Li 
Prepared By: Shenzhen Accurate Technology Co., Ltd. 1/F., Building A, Changyuan New Material Port, Science & Industry Park, Nanshan District, Shenzhen, Guangdong, P.R. China Tel: (0755) 26503290 Fax: (0755) 26503396 Http://www.atc-lab.com	

Note: This report may contain data that are not covered by the A2LA accreditation and are marked with an asterisk "★".

Shenzhen Accurate Technology Co., Ltd. is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with an asterisk '*'. Customer model name, addresses, names, trademarks etc. are not considered data.

This report cannot be reproduced except in full, without prior written approval of the Company. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

TABLE OF CONTENTS

GENERAL INFORMATION.....	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
OBJECTIVE	4
TEST METHODOLOGY	4
MEASUREMENT UNCERTAINTY	5
SYSTEM TEST CONFIGURATION	6
DESCRIPTION OF TEST CONFIGURATION	6
EQUIPMENT MODIFICATIONS	6
EUT EXERCISE SOFTWARE	6
DUTY CYCLE	6
SUPPORT EQUIPMENT LIST AND DETAILS	7
EXTERNAL I/O CABLE.....	7
BLOCK DIAGRAM OF TEST SETUP	7
SUMMARY OF TEST RESULTS	8
TEST EQUIPMENT LIST	9
FCC §15.247 (I) & §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE).....	10
APPLICABLE STANDARD	10
RESULT	10
FCC §15.203 - ANTENNA REQUIREMENT.....	11
APPLICABLE STANDARD	11
ANTENNA CONNECTOR CONSTRUCTION	11
FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS	12
APPLICABLE STANDARD	12
EUT SETUP	12
EMI TEST RECEIVER SETUP.....	12
TEST PROCEDURE	12
TRANSD FACTOR & MARGIN CALCULATION.....	13
TEST DATA	13
FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS.....	16
APPLICABLE STANDARD	16
EUT SETUP	16
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP	17
TEST PROCEDURE	17
FACTOR & MARGIN CALCULATION	17
TEST DATA	17
FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH & OCCUPIED BANDWIDTH.....	23
APPLICABLE STANDARD	23
TEST PROCEDURE	23
TEST DATA	23
FCC §15.247(b) (3) - MAXIMUM CONDUCTED OUTPUT POWER.....	24
APPLICABLE STANDARD	24
TEST PROCEDURE	24
TEST DATA	24

FCC §15.247(d) – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE.....	25
APPLICABLE STANDARD	25
TEST PROCEDURE	25
TEST DATA	25
FCC §15.247(e) - POWER SPECTRAL DENSITY	26
APPLICABLE STANDARD	26
TEST PROCEDURE	26
TEST DATA	26
APPENDIX Wi-Fi.....	27
APPENDIX A: 6dB EMISSION BANDWIDTH.....	27
APPENDIX B: OCCUPIED CHANNEL BANDWIDTH	34
APPENDIX C: MAXIMUM CONDUCTED PEAK OUTPUT POWER.....	41
APPENDIX D: POWER SPECTRAL DENSITY	42
APPENDIX E: BAND EDGE MEASUREMENTS.....	49
APPENDIX F: DUTY CYCLE	53

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

Product	Aspect Camera
Tested Model	BTC-SC
Multiple Model No.	BTC-SC1, BTC-SC1B
Model Differences	Refer to DOS letter.
Frequency Range	Wi-Fi: 2412-2462MHz
Maximum Conducted Peak Output Power	13.94dBm(802.11b), 13.11dBm(802.11g), 13.14dBm(802.11n-HT20), 12.03dBm(802.11n-HT40)
Modulation Technique	DSSS, OFDM
Antenna Specification*	FPC Antenna: 2dBi(provided by the applicant)
Voltage Range	DC3.7V from battery or DC5V from adapter
Date of Test	2021-07-15 to 2021-07-28
Sample serial number	SZNS210705-27346E-RF-S1(Assigned by ATC, Shenzhen)
Received date	2021-07-05
Sample/EUT Status	Good condition
Adapter information	Model: XED-UL050100CU INPUT: 100-240V, 50/60Hz, 0.2A OUTPUT: 5V, 1000mA

Objective

This test report is in accordance with Part 2-Subpart J, Part 15-Subparts A and C of the Federal Communication Commission's rules.

The tests were performed in order to determine compliance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

And KDB 558074 D01 15.247 Meas Guidance v05r02.

All emissions measurement was performed at Shenzhen Accurate Technology Co., Ltd. The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Measurement Uncertainty

Parameter		Uncertainty
Occupied Channel Bandwidth		±5%
RF output power, conducted		±0.73dB
Unwanted Emission, conducted		±2.72dB
RF Frequency		±0.082*10 ⁻⁷
Emissions, Radiated	30MHz - 1GHz	±4.28dB
	1GHz- 18GHz	±4.98dB
	18GHz- 26.5GHz	±5.06dB
Temperature		±1℃
Humidity		±6%
Supply voltages		±0.4%

Note: The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval. Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.

Test Facility

The test site used by Shenzhen Accurate Technology Co., Ltd. to collect test data is located on the 1/F., Building A, Changyuan New Material Port, Science & Industry Park, Nanshan District, Shenzhen, Guangdong, P.R. China.

The test site has been approved by the FCC under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No.: 708358, the FCC Designation No.: CN1189. Accredited by American Association for Laboratory Accreditation (A2LA) The Certificate Number is 429 7.01.

Listed by Innovation, Science and Economic Development Canada (ISED), the Registration Number is 5077A-2.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

For 802.11b, 802.11g, 802.11n-HT20 mode and 802.11n-HT40 mode, total 11 channels are provided to testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	7	2442
2	2417	8	2447
3	2422	9	2452
4	2427	10	2457
5	2432	11	2462
6	2437	/	/

For 802.11b, 802.11g, 802.11n-HT20, EUT was tested with Channel 1, 6 and 11.
For 802.11n-HT40, EUT was tested with Channel 3, 6 and 9.

Equipment Modifications

No modification was made to the EUT tested.

EUT Exercise Software

Software “Teraterm” was used, test frequencies and power levels were configured as below:

Mode	Data Rate (Mbps)	Power Level*
802.11 b	1 Mbps	38
802.11 g	6 Mbps	46
802.11 n20	MCS0	46
802.11 n40	MCS0	46

Duty cycle

Test Result: Compliant. Please refer to the Appendix Wi-Fi.

Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
MI	TV	L43M5-ES	25131/114100057334

External I/O Cable

Cable Description	Length (m)	From Port	To
Unshielded Detachable USB Power Cable	0.92	EUT	Adapter
Unshielded Detachable HDMI Cable	1.52	EUT	TV

Block Diagram of Test Setup

For conducted emission:



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
FCC §15.247 (i) & §2.1091	Maximum Permissible Exposure(MPE)	Compliance
§15.203	Antenna Requirement	Compliance
§15.207 (a)	AC Line Conducted Emissions	Compliance
§15.205, §15.209, §15.247(d)	Spurious Emissions	Compliance
§15.247 (a)(2)	6 dB Emission Bandwidth & Occupied Bandwidth	Compliance
§15.247(b)(3)	Maximum Conducted Output Power	Compliance
§15.247(d)	100 kHz Bandwidth of Frequency Band Edge	Compliance
§15.247(e)	Power Spectral Density	Compliance

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Conducted Emissions Test					
Rohde & Schwarz	Test Receiver	ESPI	100396/003	2020/12/24	2021/12/23
R & S	L.I.S.N.	ENV216	101314	2020/12/25	2021/12/24
Anritsu Corp	50Ω Coaxial Switch	MP59B	6200506474	2020/12/25	2021/12/24
RF Coaxial Cable	Unknown	N-2m	No.2	2020/12/25	2021/12/24
Radiated Emissions Test					
Rohde&Schwarz	Test Receiver	ESR	101817	2020/12/24	2021/12/23
Rohde & Schwarz	Spectrum Analyzer	FSV-40	101495	2020/12/24	2021/12/23
A.H. Systems, inc.	Preamplifier	PAM-0118P	531	2021/07/08	2022/07/07
SONOMA INSTRUMENT	Amplifier	310 N	186131	2020/12/25	2021/12/24
Schwarzbeck	Bilog Antenna	VULB9163	9163-323	2020/01/04	2023/01/03
Schwarzbeck	Horn Antenna	BBHA9120D	9120D-1067	2020/01/05	2023/01/04
Schwarzbeck	Horn Antenna	BBHA9170	9170-359	2020/01/05	2023/01/04
Wainwright Instruments	Highpass Filter	WHKreTerminal - CM4X.6/18G-10S S	5	2020/12/25	2021/12/24
Quinstar	Amplifier	QLW-18405536-J0	15964001002	2020/11/28	2021/11/27
RF Coaxial Cable	Unknown	N-5m	No.3	2020/12/25	2021/12/24
RF Coaxial Cable	Unknown	N-5m	No.4	2020/12/25	2021/12/24
RF Coaxial Cable	Unknown	N-1m	No.5	2020/12/25	2021/12/24
RF Coaxial Cable	Unknown	N-1m	No.6	2020/12/25	2021/12/24
RF Conducted Test					
Rohde & Schwarz	Spectrum Analyzer	FSV-40	101495	2020/12/24	2021/12/23
Rohde & Schwarz	Open Switch and Control Unit	OSP120 + OSP-B157	101244 + 100866	2020/12/24	2021/12/23
WEINSCHTEL	10dB Attenuator	5324	AU 3842	Each time	

* **Statement of Traceability:** Shenzhen Accurate Technology Co., Ltd. attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

FCC §15.247 (I) & §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE)**Applicable Standard**

According to subpart 15.247 (i) and subpart 2.1091 systems operating under the provisions of this section shall be operated in a manner that ensures the public is not exposed to RF energy level in excess of the communication guidelines.

Limits for General Population/Uncontrolled Exposure

Limits for General Population/Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm²)	Averaging Time (Minutes)
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

f = frequency in MHz

* = Plane-wave equivalent power density

Result**Calculated Formulary:**

Predication of MPE limit at a given distance

$$S = \frac{PG}{4\pi R^2}$$

S = power density (in appropriate units, e.g. mW/cm²)

P = power input to the antenna (in appropriate units, e.g., mW).

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain.

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

For worst case:

Frequency (MHz)	Antenna Gain		Tune up conducted power		Evaluation Distance (cm)	Power Density (mW/cm²)	MPE Limit (mW/cm²)
	(dBi)	(numeric)	(dBm)	(mW)			
2412-2462	2	1.58	14	25.12	20	0.008	1

Note: To maintain compliance with the FCC's RF exposure guidelines, place the equipment at least 20cm from nearby persons.

Result: Pass

FCC §15.203 - ANTENNA REQUIREMENT

Applicable Standard

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
 - b. Antenna must use a unique type of connector to attach to the EUT.
- Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

And according to FCC 47 CFR section 15.247 (b), if the transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Antenna Connector Construction

The EUT has one internal FPC antenna arrangement, which was permanently attached and the antenna gain is 2 dBi, fulfill the requirement of this section. Please refer to the EUT photos.


Result: Compliance.

FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS

Applicable Standard

FCC§15.207

EUT Setup



Note: 1. Support units were connected to second LISN.
2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

During the conducted emission test, the Adapter was connected to the outlet of the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All final data was recorded in the Quasi-peak and average detection mode.

Transd Factor & Margin Calculation

The Transd factor is calculated by adding LISN VDF (Voltage Division Factor), Cable Loss and Transient Limiter Attenuation. The basic equation is as follows:

$$\text{Transd Factor} = \text{LISN VDF} + \text{Cable Loss}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7 dB means the emission is 7 dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{level}$$

$$\text{Level} = \text{reading level} + \text{Transd Factor}$$


Test Data

Environmental Conditions

Temperature:	24 °C
Relative Humidity:	48 %
ATM Pressure:	101.0 kPa

The testing was performed by Ting Lv on 2021-07-16.

EUT operation mode: Transmitting

AC 120V/60 Hz, Line**MEASUREMENT RESULT: "27341-08_fin"**


2021-7-16 05:10

Frequency MHz	Level dBuV	Transd dB	Limit dBuV	Margin dB	Detector	Line	PE
0.150000	51.20	10.8	66	14.8	QP	L1	GND
0.495000	38.80	11.0	56	17.2	QP	L1	GND
0.915000	31.40	11.1	56	24.6	QP	L1	GND
2.160000	25.50	11.3	56	30.5	QP	L1	GND
6.170000	22.20	11.5	60	37.8	QP	L1	GND
21.475000	29.40	11.7	60	30.6	QP	L1	GND

MEASUREMENT RESULT: "27341-08_fin2"

2021-7-16 05:10

Frequency MHz	Level dBuV	Transd dB	Limit dBuV	Margin dB	Detector	Line	PE
0.150000	36.30	10.8	56	19.7	AV	L1	GND
0.480000	35.90	11.0	46	10.1	AV	L1	GND
0.915000	27.40	11.1	46	18.6	AV	L1	GND
3.330000	14.20	11.4	46	31.8	AV	L1	GND
5.700000	16.60	11.5	50	33.4	AV	L1	GND
22.075000	21.70	11.7	50	28.3	AV	L1	GND

AC 120V/60 Hz, Neutral**MEASUREMENT RESULT: "27341-07_fin"**

2021-7-16 05:08

Frequency MHz	Level dBuV	Transd dB	Limit dBuV	Margin dB	Detector	Line	PE
0.150000	41.80	10.8	66	24.2	QP	N	GND
0.495000	40.00	11.0	56	16.0	QP	N	GND
0.910000	32.00	11.1	56	24.0	QP	N	GND
2.230000	23.80	11.3	56	32.2	QP	N	GND
5.640000	24.30	11.5	60	35.7	QP	N	GND
20.600000	32.40	11.7	60	27.6	QP	N	GND



MEASUREMENT RESULT: "27341-07_fin2"

2021-7-16 05:08

Frequency MHz	Level dBuV	Transd dB	Limit dBuV	Margin dB	Detector	Line	PE
0.150000	36.50	10.8	56	19.5	AV	N	GND
0.465000	32.70	11.0	47	13.3	AV	N	GND
0.910000	24.50	11.1	46	21.5	AV	N	GND
2.220000	16.70	11.3	46	29.3	AV	N	GND
5.270000	16.60	11.4	50	33.4	AV	N	GND
21.275000	25.00	11.7	50	25.0	AV	N	GND

FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS**Applicable Standard**

FCC §15.247 (d); §15.209; §15.205;

EUT Setup**Below 1 GHz:****Above 1GHz:**

The radiated emission tests were performed in the 3 meters test site, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, and FCC 15.247 limits.

EMI Test Receiver & Spectrum Analyzer Setup

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Measurement
30 MHz – 1000 MHz	100 kHz	300 kHz	120 kHz	QP
Above 1 GHz	1MHz	3 MHz	/	PK
	1MHz	10 Hz ^{Note 1}	/	Average
	1MHz	> 1/T ^{Note 2}	/	Average

Note 1: when duty cycle is no less than 98%

Note 2: when duty cycle is less than 98%

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz-1 GHz, peak and Average detection modes for frequencies above 1 GHz.

Factor & Margin Calculation

The Factor is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Factor} = \text{Meter Reading} + \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\begin{aligned} \text{Margin} &= \text{Limit} - \text{Result} / \text{Absolute Level} \\ \text{Result} / \text{Absolute Level} &= \text{Reading} + \text{Factor} \end{aligned}$$



Test Data

Environmental Conditions

Temperature:	24 °C
Relative Humidity:	48 %
ATM Pressure:	101.0 kPa

The testing was performed by Ting Lv on 2021-07-20.

EUT operation mode: Transmitting

30 MHz~1 GHz: (Worst case at 802.11b mode)**TX Channel 1:****Horizontal****Vertical**

Above 1 GHz:

Frequency (MHz)	Receiver		Turntable Angle Degree	Rx Antenna		Factor (dB/m)	Absolute Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)
	Reading (dBuV)	PK/Ave		Height (m)	Polar (H/V)				
802.11B, Low Channel									
2310	49.12	PK	220	2.0	H	-6.84	42.28	74	31.72
2310	47.88	PK	57	2.1	V	-6.84	41.04	74	32.96
2390	55.62	PK	243	1.4	H	-6.44	49.18	74	24.82
2390	49.71	PK	316	1.7	V	-6.44	43.27	74	30.73
4824	49.37	PK	30	2.0	H	2.87	52.24	74	21.76
4824	49.43	PK	24	1.3	V	2.87	52.3	74	21.7
802.11B, Middle Channel									
4874	48.36	PK	185	2.0	H	3.01	51.37	74	22.63
4874	45.94	PK	223	1.2	V	3.01	48.95	74	25.05
11B, High Channel									
2483.5	49.91	PK	226	1.6	H	-5.96	43.95	74	30.05
2483.5	49.14	PK	257	1.5	V	-5.96	43.18	74	30.82
2500	50.34	PK	186	1.6	H	-5.88	44.46	74	29.54
2500	51.03	PK	142	1.8	V	-5.88	45.15	74	28.85
4924	47.94	PK	349	1.3	H	3.17	51.11	74	22.89
4924	46.47	PK	154	1.5	V	3.17	49.64	74	24.36
802.11G, Low Channel									
2310	51.58	PK	7	2.2	H	-6.84	44.74	74	29.26
2310	52.54	PK	329	1.5	V	-6.84	45.7	74	28.3
2390	50.6	PK	260	1.5	H	-6.44	44.16	74	29.84
2390	53.38	PK	7	1.2	V	-6.44	46.94	74	27.06
4824	48.9	PK	335	1.8	H	2.87	51.77	74	22.23
4824	45.63	PK	195	2.1	V	2.87	48.5	74	25.5
802.11G, Middle Channel									
4874	49.21	PK	57	1.8	H	3.01	52.22	74	21.78
4874	46.45	PK	113	1.1	V	3.01	49.46	74	24.54
802.11G, High Channel									
2483.5	48.4	PK	54	1.6	H	-5.96	42.44	74	31.56
2483.5	50.26	PK	256	2.1	V	-5.96	44.3	74	29.7
2500	51.24	PK	254	1.8	H	-5.88	45.36	74	28.64
2500	50.56	PK	15	1.7	V	-5.88	44.68	74	29.32
4924	48.8	PK	264	1.3	H	3.17	51.97	74	22.03
4924	45.79	PK	130	1.9	V	3.17	48.96	74	25.04
802.11N20, Low Channel									
2310	52.15	PK	206	1.8	H	-6.84	45.31	74	28.69
2310	53.23	PK	66	1.3	V	-6.84	46.39	74	27.61
2390	50.87	PK	215	1.0	H	-6.44	44.43	74	29.57
2390	51.59	PK	79	1.3	V	-6.44	45.15	74	28.85
4824	50.64	PK	342	2.2	H	2.87	53.51	74	20.49
4824	45.9	PK	294	1.9	V	2.87	48.77	74	25.23

802.11N20, Middle Channel									
4874	48.73	PK	107	1.1	H	3.01	51.74	74	22.26
4874	46.54	PK	324	1.0	V	3.01	49.55	74	24.45
802.11N20, High Channel									
2483.5	50.62	PK	33	1.4	H	-5.96	44.66	74	29.34
2483.5	51.76	PK	181	1.0	V	-5.96	45.8	74	28.2
2500	50.39	PK	202	1.6	H	-5.88	44.51	74	29.49
2500	49.13	PK	266	2.1	V	-5.88	43.25	74	30.75
4924	49.45	PK	289	1.1	H	3.17	52.62	74	21.38
4924	45.44	PK	180	1.5	V	3.17	48.61	74	25.39
802.11N40, Low Channel									
2310	51.94	PK	79	2.0	H	-6.84	45.1	74	28.9
2310	52.26	PK	357	1.3	V	-6.84	45.42	74	28.58
2390	52.78	PK	44	2.1	H	-6.44	46.34	74	27.66
2390	51.74	PK	111	1.1	V	-6.44	45.3	74	28.7
4844	48.76	PK	158	1.8	H	2.92	51.68	74	22.32
4844	48.07	PK	165	1.7	V	2.92	50.99	74	23.01
802.11N40, Middle Channel									
4874	47.53	PK	221	1.7	H	3.01	50.54	74	23.46
4874	45.4	PK	122	1.1	V	3.01	48.41	74	25.59
802.11N40, High Channel									
2483.5	49.68	PK	344	1.1	H	-5.96	43.72	74	30.28
2483.5	48.34	PK	336	1.5	V	-5.96	42.38	74	31.62
2500	48.35	PK	336	1.5	H	-5.88	42.47	74	31.53
2500	48.83	PK	71	1.6	V	-5.88	42.95	74	31.05
4904	48.32	PK	190	1.2	H	3.11	51.43	74	22.57
4904	47.76	PK	271	2.1	V	3.11	50.87	74	23.13

Note:

Factor = Antenna factor (RX) + Cable Loss – Amplifier Factor

Absolute Level (Corrected Amplitude) = Factor + Reading



Margin = Limit - Absolute Level

The other spurious emission which is 20dB to the limit was not recorded.

The test result of peak was less than the limit of average, so just peak value were recorded.

1-18GHz


Pre-scan plots:

**802.11B (worst case)
Low Channel
Horizontal****Vertical**


18-25GHz

Pre-scan Plots:

802.11B (worst case)
Low Channel
Horizontal



Vertical




FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH & OCCUPIED BANDWIDTH

Applicable Standard

Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 6 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.



Test Data

Environmental Conditions

Temperature:	24 °C
Relative Humidity:	48 %
ATM Pressure:	101.0 kPa

The testing was performed by Ting Lv on 2021-07-15

EUT operation mode: Transmitting

Test Result: Compliant. Please refer to the Appendix Wi-Fi.


FCC §15.247(b) (3) - MAXIMUM CONDUCTED OUTPUT POWER

Applicable Standard

According to FCC §15.247(b) (3), for systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

Test Procedure

1. Place the EUT on a bench and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to one test equipment.
3. Add a correction factor to the display.



Test Data

Environmental Conditions

Temperature:	24 °C
Relative Humidity:	48 %
ATM Pressure:	101.0 kPa

The testing was performed by Ting Lv on 2021-07-15

EUT operation mode: Transmitting

Test Result: Compliant. Please refer to the Appendix Wi-Fi.


FCC §15.247(d) – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE

Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.



Test Data

Environmental Conditions

Temperature:	24 °C
Relative Humidity:	48 %
ATM Pressure:	101.0 kPa

The testing was performed by Ting Lv on 2021-07-15

EUT operation mode: Transmitting

Test Result: Compliant.

Conducted Band Edge Result:

Please refer to the Appendix Wi-Fi


FCC §15.247(e) - POWER SPECTRAL DENSITY

Applicable Standard

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

Test Procedure

1. Use this procedure when the maximum peak conducted output power in the fundamental emission is used to demonstrate compliance.
2. Set the RBW to: $3\text{ kHz} \leq \text{RBW} \leq 100\text{ kHz}$.
3. Set the VBW $\geq 3 \times \text{RBW}$.
4. Set the span to 1.5 times the DTS bandwidth.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level within the RBW.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.



Test Data

Environmental Conditions

Temperature:	24 °C
Relative Humidity:	48 %
ATM Pressure:	101.0 kPa

The testing was performed by Ting Lv on 2021-07-27.

EUT operation mode: Transmitting

Test Result: Compliant. Please refer to the Appendix Wi-Fi.


APPENDIX Wi-Fi



Appendix A: 6dB Emission Bandwidth



Test Result



Test Mode	Antenna	Channel[MHz]	DTS BW [MHz]	Limit[MHz]	Verdict
11B	Ant1	2412	10.160	0.5	PASS
		2437	10.160	0.5	PASS
		2462	10.160	0.5	PASS
11G	Ant1	2412	16.400	0.5	PASS
		2437	16.400	0.5	PASS
		2462	16.400	0.5	PASS
11N20SISO	Ant1	2412	17.680	0.5	PASS
		2437	17.680	0.5	PASS
		2462	17.680	0.5	PASS
11N40SISO	Ant1	2422	35.840	0.5	PASS
		2437	35.840	0.5	PASS
		2452	35.840	0.5	PASS



Test Graphs




















Appendix B: Occupied Channel Bandwidth



Test Result



TestMode	Antenna	Channel[MHz]	OCB [MHz]	Limit[MHz]	Verdict
11B	Ant1	2412	15.504	---	PASS
		2437	15.425	---	PASS
		2462	15.385	---	PASS
11G	Ant1	2412	17.902	---	PASS
		2437	17.902	---	PASS
		2462	17.942	---	PASS
11N20SISO	Ant1	2412	18.621	---	PASS
		2437	18.621	---	PASS
		2462	18.621	---	PASS
11N40SISO	Ant1	2422	36.603	---	PASS
		2437	36.603	---	PASS
		2452	36.603	---	PASS


Test Graphs


















Appendix C: Maximum conducted Peak output power**Test Result**


Test Mode	Antenna	Channel [MHz]	Result [dBm]	Limit [dBm]	Verdict
11B	Ant1	2412	13.19	<=30	PASS
		2437	13.61	<=30	PASS
		2462	13.94	<=30	PASS
11G	Ant1	2412	12.78	<=30	PASS
		2437	12.97	<=30	PASS
		2462	13.11	<=30	PASS
11N20SISO	Ant1	2412	12.80	<=30	PASS
		2437	12.94	<=30	PASS
		2462	13.14	<=30	PASS
11N40SISO	Ant1	2422	11.51	<=30	PASS
		2437	11.68	<=30	PASS
		2452	12.03	<=30	PASS



Appendix D: Power spectral density



Test Result



TestMode	Antenna	Channel[MHz]	Result[dBm/3kHz]	Limit[dBm/3kHz]	Verdict
11B	Ant1	2412	-8.89	<=8	PASS
		2437	-10.01	<=8	PASS
		2462	-10.75	<=8	PASS
11G	Ant1	2412	-16.91	<=8	PASS
		2437	-16.08	<=8	PASS
		2462	-16.00	<=8	PASS
11N20SISO	Ant1	2412	-18.01	<=8	PASS
		2437	-17.50	<=8	PASS
		2462	-17.07	<=8	PASS
11N40SISO	Ant1	2422	-19.00	<=8	PASS
		2437	-20.87	<=8	PASS
		2452	-18.94	<=8	PASS



Test Graphs






















Appendix E: Band edge measurements

Test Graphs








11N20SISO Ant1 Low 2412MHz



11N20SISO Ant1 High 2462MHz








Appendix F: Duty Cycle


Test Result

TestMode	Channel[MHz]	TransmissionDuration [ms]	Transmission Period [ms]	Duty Cycle [%]
11B	2437	12.46	12.54	99.36
11G	2437	2.09	2.19	95.43
11N20SISO	2437	1.91	1.98	96.46
11N40SISO	2437	0.92	1.04	88.46

Test Graphs







***** END OF REPORT *****