



TEST REPORT

Application No.: GZCR2112021463AT
Applicant: XDynamics Limited
Address of Applicant: Units 216-217, Photonics Centre, No. 2 Science Park East Avenue, Hong Kong.
Manufacturer: XDynamics Limited
Address of Manufacturer: Units 216-217, Photonics Centre, No. 2 Science Park East Avenue, Hong Kong.
Equipment Under Test (EUT):
EUT Name: Ground Station
Model No.: Evolve2 GroundStation
Trade Mark: Xdynamics
Standard(s) : 47 CFR Part 15, Subpart C 15.247
Date of Receipt: 2021-05-17
Date of Test: 2021-11-29 to 2021-12-28
Date of Issue: 2021-12-30

Test Result:	Pass*
---------------------	--------------

* In the configuration tested, the EUT complied with the standards specified above.

Kobe Jian
EMC Laboratory Manager



Revision Record				
Version	Chapter	Date	Modifier	Remark
01		2021-12-30		Original

Authorized for issue by				
				
		Curry Wu/Project Engineer		
				
		Ricky Liu/Reviewer		

2 Test Summary

Radio Spectrum Technical Requirement				
Item	Standard	Method	Requirement	Result
Antenna Requirement	47 CFR Part 15, Subpart C 15.247	N/A	47 CFR Part 15, Subpart C 15.203 & 15.247(b)(4)	Pass

Radio Spectrum Matter Part				
Item	Standard	Method	Requirement	Result
Conducted Emissions at AC Power Line (150kHz-30MHz)	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 6.2	47 CFR Part 15, Subpart C 15.207	Pass
Conducted Output Power		ANSI C63.10 (2013) Section 11.9.1.3	47 CFR Part 15, Subpart C 15.247(b)(3)	Pass
Minimum 6dB Bandwidth		ANSI C63.10 (2013) Section 11.8.1	47 CFR Part 15, Subpart C 15.247a(2)	Pass
Power Spectrum Density		ANSI C63.10 (2013) Section 11.10.2	47 CFR Part 15, Subpart C 15.247(e)	Pass
Conducted Band Edges Measurement		ANSI C63.10 (2013) Section 11.13.3.2	47 CFR Part 15, Subpart C 15.247(d)	Pass
Conducted Spurious Emissions		ANSI C63.10 (2013) Section 11.11	47 CFR Part 15, Subpart C 15.247(d)	Pass
Radiated Emissions which fall in the restricted bands		ANSI C63.10 (2013) Section 6.10.5	47 CFR Part 15, Subpart C 15.205 & 15.209	Pass
Radiated Spurious Emissions (Below 1GHz)		ANSI C63.10 (2013) Section 6.4,6.5,6.6	47 CFR Part 15, Subpart C 15.205 & 15.209	Pass
Radiated Spurious Emissions (Above 1GHz)		ANSI C63.10 (2013) Section 6.4,6.5,6.6	47 CFR Part 15, Subpart C 15.205 & 15.209	Pass
Duty Cycle		ANSI C63.10 (2013) Section 11.6	KDB 558074 D01 v05r02 section 6	Pass

Note:

E.U.T./EUT means Equipment Under Test.

Pass means the test result passed the test standard requirement, please find the detailed decision rule in the report relative section.

3 Contents

	Page
1 Cover Page	1
2 Test Summary	3
3 Contents	4
4 General Information.....	6
4.1 Details of E.U.T.	6
4.2 Description of Support Units	6
4.3 Measurement Uncertainty	7
4.4 Test Location.....	8
4.5 Test Facility	8
4.6 Deviation from Standards.....	9
4.7 Abnormalities from Standard Conditions	9
5 Equipment List	10
6 Radio Spectrum Technical Requirement	14
6.1 Antenna Requirement	14
6.1.1 Test Requirement:	14
6.1.2 Conclusion	14
7 Radio Spectrum Matter Test Results	15
7.1 Conducted Emissions at AC Power Line (150kHz-30MHz)	15
7.1.1 E.U.T. Operation	15
7.1.2 Test Mode Description	15
7.1.3 Test Setup Diagram	15
7.1.4 Measurement Procedure and Data.....	16
7.2 Conducted Output Power.....	19
7.2.1 E.U.T. Operation	19
7.2.2 Test Mode Description	19
7.2.3 Test Setup Diagram	19
7.2.4 Measurement Procedure and Data.....	19
7.3 Minimum 6dB Bandwidth	20
7.3.1 E.U.T. Operation	20
7.3.2 Test Mode Description	20
7.3.3 Test Setup Diagram	20
7.3.4 Measurement Procedure and Data.....	20
7.4 Power Spectrum Density.....	21
7.4.1 E.U.T. Operation	21
7.4.2 Test Mode Description	21
7.4.3 Test Setup Diagram	21
7.4.4 Measurement Procedure and Data.....	21
7.5 Conducted Band Edges Measurement	22
7.5.1 E.U.T. Operation	22
7.5.2 Test Mode Description	22
7.5.3 Test Setup Diagram	22
7.5.4 Measurement Procedure and Data.....	22



7.6	Conducted Spurious Emissions	23
7.6.1	E.U.T. Operation	23
7.6.2	Test Mode Description	23
7.6.3	Test Setup Diagram	24
7.6.4	Measurement Procedure and Data	24
7.7	Radiated Emissions which fall in the restricted bands	25
7.7.1	E.U.T. Operation	25
7.7.2	Test Mode Description	25
7.7.3	Test Setup Diagram	26
7.7.4	Measurement Procedure and Data	26
7.8	Radiated Spurious Emissions (Below 1GHz)	43
7.8.1	E.U.T. Operation	43
7.8.2	Test Mode Description	43
7.8.3	Test Setup Diagram	44
7.8.4	Measurement Procedure and Data	44
7.9	Radiated Spurious Emissions (Above 1GHz)	47
7.9.1	E.U.T. Operation	47
7.9.2	Test Mode Description	47
7.9.3	Test Setup Diagram	48
7.9.4	Measurement Procedure and Data	49
7.10	Duty Cycle	74
7.10.1	E.U.T. Operation	74
7.10.2	Test Mode Description	74
7.10.3	Test Setup Diagram	74
7.10.4	Measurement Procedure and Data	74
8	Test Setup Photo	75
9	EUT Constructional Details (EUT Photos)	75
10	Appendix	76

4 General Information

4.1 Details of E.U.T.

Power Supply:	DC 14.8V Lithium-ion 6700mAh 99.16Wh rechargeable battery (to be charged from AC/DC Adapter) AC/DC Adapter Model: BYX-17666000 Input: AC 100-240V, 50/60Hz, 1.5A Max. Output: DC17.6V, 6.6A
EUT Function:	2.4G SRD
Operation Frequency:	2412MHz, 2427MHz, 2442MHz, 2467MHz
Modulation Type:	GFSK
Number of Channels:	4
Antenna Type:	Antenna 1&2: FPC Antenna, Antenna 3&4: Dipole Antenna
Antenna Gain:	Antenna 1&2: 2dBi, Antenna 3 & 4: 5dBi
Remark:	1. Both voltages AC 120V, 50/60Hz and AC 240V, 50/60Hz were tested. Only the worst voltage (AC 120V, 60Hz) was recorded in the report. 2. Only supports SISO mode.

4.2 Description of Support Units

Description	Manufacturer	Model No.	Serial No.
Antenna	South Star Technology Co., LTD	H052	--



4.3 Measurement Uncertainty

Test Item	Measurement Uncertainty
Conducted Emissions at AC Power Line (150kHz-30MHz)	±3.12dB
Conducted Output Power	± 0.75dB
Minimum 6dB Bandwidth	± 3%
Power Spectrum Density	± 2.84dB
Conducted Band Edges Measurement	± 0.75dB
Conducted Spurious Emissions	± 0.75dB
Radiated Emissions which fall in the restricted bands	±5.08dB (1GHz-6GHz);±5.14dB(above 6GHz)
Radiated Spurious Emissions (Below 1GHz)	±5.06dB (3m); ±4.46dB (10m)
Radiated Spurious Emissions (Above 1GHz)	±5.08dB (1GHz-6GHz);±5.14dB(above 6GHz)
Duty Cycle	± 0.37%

4.4 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Guangzhou Branch EMC Laboratory,
198 Kezhu Road, Sciencetech Park, Guangzhou Economic & Technology Development District,
Guangzhou, China 510663

Tel: +86 20 82155555 Fax: +86 20 82075059

No tests were sub-contracted.

4.5 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **NVLAP (Lab Code: 200611-0)**

SGS-CSTC Standards Technical Services Co., Ltd., Guangzhou EMC Laboratory is accredited by the National Voluntary Laboratory Accreditation Program (NVLAP/NIST). NVLAP Code: 200611-0.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.

- **ACMA**

SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory can also perform testing for the Australian/New Zealand Regulatory Compliance Mark (RCM).

- **SGS UK(Certificate No.: 32), SGS-TUV SAARLAND and SGS-FIMKO**

Have approved SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory as a supplier of EMC TESTING SERVICES and SAFETY TESTING SERVICES.

- **CNAS (Lab Code: L0167)**

SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory has been assessed and in compliance with CNAS-CL01:2018 accreditation criteria for testing laboratories (identical to ISO/IEC 17025:2017 General Requirements) for the Competence of Testing Laboratories.

- **FCC Recognized Accredited Test Firm(Registration No.: 486818)**

SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory has been accredited and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Designation Number: CN5016, Test Firm Registration Number: 486818.

- **ISED (Registration No.: 4620B, CAB identifier: CN0052)**

SGS-CSTC Standards Technical Services Co., Ltd., has been registered by Innovation Science and Economic Development Canada for Wireless Device Testing laboratories to test to Canadian radio equipment requirements. Registration No. 4620B, CAB identifier: CN0052.

- **VCCI (Registration No.: R-12460, C-12584, G-20107 and T-11179)**

The 10m Semi-anechoic chamber, 966 Anechoic Chamber and Shielded Room of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: R-12460, C-12584, G-20107 and T-11179 respectively.

- **CBTL (Lab Code: TL129)**

SGS-CSTC Standards Technical Services Co., Ltd., E&E Laboratory has been assessed and fully comply with the requirements of ISO/IEC 17025:2017, the Basic Rules, IECEE 01 and Rules of procedure IECEE 02, and the relevant IECEE CB-Scheme Operational documents.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

4.6 Deviation from Standards

None

4.7 Abnormalities from Standard Conditions

None



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing/inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

5 Equipment List

Conducted Emissions at AC Power Line (150kHz-30MHz)					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
Shielding Room	ChangZhou ZhongYu	8m x 3m x 3.8m	EMC0306	N/A	N/A
Two-Line V-Network	Rohde & Schwarz	ENV216	EMC0118	2021-01-08	2022-01-06
Two-Line V-Network-GZ	Rohde & Schwarz	ENV216	EMC2135	2021-09-24	2022-09-23
Coaxial Cable	HangTianXing	2m	EMC0107	2020-09-09	2022-09-08
Test Software E3c	Audix	Ver. 5.4.1221b	GZE100-62	N/A	N/A
EMI Test Receiver(9kHz-3.6GHz)	Rohde & Schwarz	ESR3	EMC2221	2021-06-01	2022-05-31

Conducted Output Power					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
Power Meter (U2021XA_Ch2)	Agilent Technologies	U2021XA_Ch2	SEM009-02	2021-05-19	2022-05-18
6dB Attenuator	HP	8491A	EMC2062	2020-04-15	2022-04-14
MI CABLE	SGS-EMC	0.8M	EMC2136	2021-11-01	2023-11-01

Minimum 6dB Bandwidth					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
EXA Signal Analyzer(10Hz-44GHz)	Agilent Technologies	N9010A	EMC2138	2021-09-16	2022-09-15
6dB Attenuator	HP	8491A	EMC2062	2020-04-15	2022-04-14
MI CABLE	SGS-EMC	0.8M	EMC2136	2021-11-01	2023-11-01
Test Software	TST	V2.0	GZE100-78	N/A	N/A

Power Spectrum Density					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
EXA Signal Analyzer(10Hz-44GHz)	Agilent Technologies	N9010A	EMC2138	2021-09-16	2022-09-15
6dB Attenuator	HP	8491A	EMC2062	2020-04-15	2022-04-14
MI CABLE	SGS-EMC	0.8M	EMC2136	2021-11-01	2023-11-01
Test Software	TST	V2.0	GZE100-78	N/A	N/A

Conducted Band Edges Measurement					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
EXA Signal Analyzer(10Hz-44GHz)	Agilent Technologies	N9010A	EMC2138	2021-09-16	2022-09-15
6dB Attenuator	HP	8491A	EMC2062	2020-04-15	2022-04-14
MI CABLE	SGS-EMC	0.8M	EMC2136	2021-11-01	2023-11-01



Test Software	TST	V2.0	GZE100-78	N/A	N/A
---------------	-----	------	-----------	-----	-----

Conducted Spurious Emissions

Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
EXA Signal Analyzer(10Hz-44GHz)	Agilent Technologies	N9010A	EMC2138	2021-09-16	2022-09-15
6dB Attenuator	HP	8491A	EMC2062	2020-04-15	2022-04-14
MI CABLE	SGS-EMC	0.8M	EMC2136	2021-11-01	2023-11-01
Test Software	TST	V2.0	GZE100-78	N/A	N/A

Radiated Emissions which fall in the restricted bands

Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
EMI Test Receiver(20Hz-26.5GHz)	Rohde & Schwarz	ESIB26	EMC0522	2021-01-08	2022-01-07
Chamber cable(Above 1GHz)	Scoflex	KMKM-8.0m	EMC0545	2020-09-09	2022-09-08
Horn Antenna(1GHz-18GHz)	SCHWARZBECK MESS-ELEKTRONIK	BBHA 9120D	EMC2026	2019-09-25	2022-09-24
1GHz-26.5 GHz Pre-Amplifier	Agilent	8449B	EMC0521	2021-01-08	2022-01-07
2.4GHz Filter	Micro-Tronics	BRM 50702	EMC2069	2021-01-08	2022-01-07
966 Anechoic Chamber	C.R.T	9m x 6m x 6m	EMC2142	2020-12-20	2023-12-19
MXE EMI Receiver(10Hz-8.4GHz)	Keysight	N9038A	EMC2139	2021-11-01	2022-10-31
EXA Signal Analyzer(10Hz-44GHz)	Keysight	N9010A	EMC2138	2021-09-16	2022-09-15
Test Software E3	Audix	Ver.6.120110a	GZE100-61	N/A	N/A
Notch Filter (5150-5880)	Mico-Tronics	BRM50716	EMC2168	2021-07-29	2022-07-28
Horn Antenna(14-40GHz)	SCHWARZBECK	BBHA 9170	EMC2041	2020-06-28	2023-06-27
Microwave Broadband Preampfier (18-40GHz)	SCHWARZBECK	BBV 9721	EMC2172	2021-08-30	2022-08-29

Radiated Spurious Emissions (Below 1GHz)

Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
EMI Test Receiver(10Hz-26.5GHz)	Rohde & Schwarz	ESIB26	EMC0522	2021-01-08	2022-01-07
Chamber cable	HangTianXing	N/A	EMC0542	2020-09-09	2022-09-08



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Guangzhou Branch Testing Laboratory

No. 198 Kezhu Road, Science Park, Guangzhou Economic & Technology Development District, Guangzhou, China 510663 t (86-20) 82155555 f (86-20) 82075058 www.sgsgroup.com.cn
中国·广州·经济技术开发区科学城科珠路198号 邮编: 510663 t (86-20) 82155555 f (86-20) 82075058 sgs.china@sgs.com

Trilog Broadband Antenna(25MHz-1GHz)-Lab	SCHWARZBECK MESS-ELEKTRONIK	VULB 9168	SEM003-18	2019-02-22	2022-02-22
Amplifier(9kHz-1.3GHz)	HP	8447F	EMC2065	2021-05-19	2022-05-18
High Pass Filter (915MHz)	FSY MICROWAVE	HM1465-9SS	EMC2079	2021-01-08	2022-01-07
10m Semi-Anechoic Chamber	ETS	N/A	EMC0530	2019-10-20	2022-10-19
Test Software E3	Audix	Ver.6.120110a	GZE100-61	N/A	N/A
EMI Test Receiver(1Hz-8GHz)	Rohde & Schwarz	ESW8	EMC2220	2021-05-26	2022-05-25

Radiated Spurious Emissions (Above 1GHz)					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
EMI Test Receiver(20Hz-26.5GHz)	Rohde & Schwarz	ESIB26	EMC0522	2021-01-08	2022-01-07
Chamber cable(Above 1GHz)	Scoflex	KMKM-8.0m	EMC0545	2020-09-09	2022-09-08
Horn Antenna(1GHz-18GHz)	SCHWARZBECK MESS-ELEKTRONIK	BBHA 9120D	EMC2026	2019-09-25	2022-09-24
1GHz-26.5 GHz Pre-Amplifier	Agilent	8449B	EMC0521	2021-01-08	2022-01-07
2.4GHz Filter	Micro-Tronics	BRM 50702	EMC2069	2021-01-08	2022-01-07
966 Anechoic Chamber	C.R.T	9m x 6m x 6m	EMC2142	2020-12-20	2023-12-19
MXE EMI Receiver(10Hz-8.4GHz)	Keysight	N9038A	EMC2139	2021-11-01	2022-10-31
EXA Signal Analyzer(10Hz-44GHz)	Keysight	N9010A	EMC2138	2021-09-16	2022-09-15
Test Software E3	Audix	Ver.6.120110a	GZE100-61	N/A	N/A
Notch Filter (5150-5880)	Mico-Tronics	BRM50716	EMC2168	2021-07-29	2022-07-28
Horn Antenna(14-40GHz)	SCHWARZBECK	BBHA 9170	EMC2041	2020-06-28	2023-06-27
Microwave Broadband Preamplifier (18-40GHz)	SCHWARZBECK	BBV 9721	EMC2172	2021-08-30	2022-08-29



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

Duty Cycle					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
EXA Signal Analyzer(10Hz-44GHz)	Agilent Technologies	N9010A	EMC2138	2021-09-16	2022-09-15
6dB Attenuator	HP	8491A	EMC2062	2020-04-15	2022-04-14
MI CABLE	SGS-EMC	0.8M	EMC2136	2021-11-01	2023-11-01
Test Software	TST	V2.0	GZE100-78	N/A	N/A

General used equipment					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
DMM	Fluke	73	EMC0006	2021-07-05	2022-07-05
DMM	Fluke	73	EMC0007	2021-07-05	2022-07-05

6 Radio Spectrum Technical Requirement

6.1 Antenna Requirement

6.1.1 Test Requirement:

47 CFR Part 15, Subpart C 15.203 & 15.247(b)(4)

6.1.2 Conclusion

15.203 Requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

15.247(b) (4) requirement:

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

EUT Antenna:

The antenna is integrated on the main PCB and no consideration of replacement. The best case gain of the antennas are Antenna 1&2: 2dBi, Antenna 3 & 4: 5dBi.

Antenna location: Refer to internal photo.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

7 Radio Spectrum Matter Test Results

7.1 Conducted Emissions at AC Power Line (150kHz-30MHz)

Test Requirement 47 CFR Part 15, Subpart C 15.207

Test Method: ANSI C63.10 (2013) Section 6.2

Limit:

Frequency of emission(MHz)	Conducted limit(dBμV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.

Detector: Peak for pre-scan (9kHz resolution bandwidth) 0.15M to 30MHz

7.1.1 E.U.T. Operation

Operating Environment:

Temperature: 22.9 °C


Humidity: 51.5 % RH

Atmospheric Pressure: 1003 mbar

7.1.2 Test Mode Description

Pre-scan /	Mode	Description
Final test	Code	
Final test	06	Charge + TX mode_Keep the EUT in charging and continuously transmitting mode with GFSK modulation.

7.1.3 Test Setup Diagram



7.1.4 Measurement Procedure and Data

- 1) The mains terminal disturbance voltage test was conducted in a shielded room.
- 2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a 50ohm/50μH + 5ohm linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.
- 3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane.
- 4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2.
- 5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10 on conducted measurement.


Remark: LISN=Read Level+ Cable Loss+ LISN Factor



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.


Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

Test Mode: 06; Line: Live line

Pol : LINE
Mode :
Model :

Frequency MHz	Read Level dBuV	Cable Loss dB	LISN Factor dB	Measured Level dBuV	Limit Line dBuV	Over Limit dB	Remark
0.15	32.38	0.06	9.62	42.06	55.87	-13.81	Average
0.15	40.66	0.06	9.62	50.34	65.87	-15.53	QP
0.41	31.14	0.06	9.62	40.82	47.55	-6.73	Average
0.41	35.42	0.06	9.62	45.10	57.55	-12.45	QP
0.56	30.40	0.07	9.63	40.10	46.00	-5.90	Average
0.56	33.64	0.07	9.63	43.34	56.00	-12.66	QP
1.20	24.49	0.08	9.61	34.18	46.00	-11.82	Average
1.20	32.30	0.08	9.61	41.99	56.00	-14.01	QP
2.18	14.15	0.12	9.62	23.89	46.00	-22.11	Average
2.18	27.80	0.12	9.62	37.54	56.00	-18.46	QP
24.66	25.20	0.40	9.88	35.48	50.00	-14.52	Average
24.66	32.89	0.40	9.88	43.17	60.00	-16.83	QP

Test Mode: 06; Line: Neutral Line

Pol : NEUTRAL
Mode :
Model :

Frequency MHz	Read Level dBuV	Cable Loss dB	LISN Factor dB	Measured Level dBuV	Limit Line dBuV	Over Limit dB	Remark
0.15	34.75	0.06	9.55	44.36	55.87	-11.51	Average
0.15	41.25	0.06	9.55	50.86	65.87	-15.01	QP
0.42	32.92	0.06	9.56	42.54	47.51	-4.97	Average
0.42	35.59	0.06	9.56	45.21	57.51	-12.30	QP
0.57	28.70	0.07	9.54	38.31	46.00	-7.69	Average
0.57	33.52	0.07	9.54	43.13	56.00	-12.87	QP
1.62	22.38	0.10	9.55	32.03	46.00	-13.97	Average
1.62	29.53	0.10	9.55	39.18	56.00	-16.82	QP
3.19	12.50	0.15	9.56	22.21	46.00	-23.79	Average
3.19	23.81	0.15	9.56	33.52	56.00	-22.48	QP
25.32	23.00	0.41	9.82	33.23	50.00	-16.77	Average
25.32	30.28	0.41	9.82	40.51	60.00	-19.49	QP

7.2 Conducted Output Power

Test Requirement 47 CFR Part 15, Subpart C 15.247(b)(3)

Test Method: ANSI C63.10 (2013) Section 11.9.1.3

Limit:

Frequency range(MHz)	Output power of the intentional radiator(watt)
902-928	1 for ≥ 50 hopping channels
	0.25 for $25 \leq$ hopping channels < 50
	1 for digital modulation
2400-2483.5	1 for ≥ 75 non-overlapping hopping channels
	0.125 for all other frequency hopping systems
	1 for digital modulation
5725-5850	1 for frequency hopping systems and digital modulation

7.2.1 E.U.T. Operation

Operating Environment:

Temperature: 21.2 °C


Humidity: 52.4 % RH

Atmospheric Pressure: 1003 mbar

7.2.2 Test Mode Description

Pre-scan / Mode	Description
Final test Code	
Final test 05	TX mode_Keep the EUT in continuously transmitting mode with GFSK modulation.

7.2.3 Test Setup Diagram



7.2.4 Measurement Procedure and Data

cable loss=0.9dB

Please Refer to Appendix for Details



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

7.3 Minimum 6dB Bandwidth

Test Requirement 47 CFR Part 15, Subpart C 15.247a(2)

Test Method: ANSI C63.10 (2013) Section 11.8.1

Limit:

≥500 kHz

7.3.1 E.U.T. Operation

Operating Environment:

Temperature: 21.2 °C


Humidity: 52.4 % RH

Atmospheric Pressure: 1003 mbar

7.3.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	05	TX mode_Keep the EUT in continuously transmitting mode with GFSK modulation.

7.3.3 Test Setup Diagram



7.3.4 Measurement Procedure and Data

cable loss=0.9dB

Please Refer to Appendix for Details

7.4 Power Spectrum Density

Test Requirement 47 CFR Part 15, Subpart C 15.247(e)

Test Method: ANSI C63.10 (2013) Section 11.10.2

Limit:

≤8dBm in any 3 kHz band during any time interval of continuous transmission

7.4.1 E.U.T. Operation

Operating Environment:

Temperature: 21.2 °C


Humidity: 52.4 % RH

Atmospheric Pressure: 1003 mbar

7.4.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	05	TX mode_Keep the EUT in continuously transmitting mode with GFSK modulation.

7.4.3 Test Setup Diagram



7.4.4 Measurement Procedure and Data

cable loss=0.9dB

Please Refer to Appendix for Details

7.5 Conducted Band Edges Measurement

Test Requirement 47 CFR Part 15, Subpart C 15.247(d)
Test Method: ANSI C63.10 (2013) Section 11.13.3.2
Limit:

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).


7.5.1 E.U.T. Operation

Operating Environment:
Temperature: 21.2 °C Humidity: 52.4 % RH Atmospheric Pressure: 1003 mbar

7.5.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	05	TX mode_Keep the EUT in continuously transmitting mode with GFSK modulation.

7.5.3 Test Setup Diagram



7.5.4 Measurement Procedure and Data

cable loss=0.9dB

Please Refer to Appendix for Details



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.
Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com
SGS-CSTC Standards Technical Services Co., Ltd. No.198 Kezhu Road, Sciotech Park, Guangzhou Economic & Technology Development District, Guangzhou, China 510663 t (86-20) 82155555 f (86-20) 82075058 www.sgsgroup.com.cn
Guangzhou Branch Testing Laboratory 中国·广州·经济技术开发区科学城科珠路198号 邮编: 510663 t (86-20) 82155555 f (86-20) 82075058 sgs.china@sgs.com

7.6 Conducted Spurious Emissions

Test Requirement 47 CFR Part 15, Subpart C 15.247(d)

Test Method: ANSI C63.10 (2013) Section 11.11

Limit:

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

7.6.1 E.U.T. Operation

Operating Environment:

Temperature: 21.2 °C Humidity: 52.4 % RH Atmospheric Pressure: 1003 mbar


7.6.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	05	TX mode_Keep the EUT in continuously transmitting mode with GFSK modulation.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.
Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

7.6.3 Test Setup Diagram



7.6.4 Measurement Procedure and Data

cable loss=0.9dB

Please Refer to Appendix for Details

7.7 Radiated Emissions which fall in the restricted bands

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.209

Test Method: ANSI C63.10 (2013) Section 6.10.5

Measurement Distance: 3m

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

7.7.1 E.U.T. Operation

Operating Environment:

Temperature: 25.0 °C Humidity: 52.5 % RH Atmospheric Pressure: 1003 mbar

7.7.2 Test Mode Description


Pre-scan / Final test	Mode Code	Description
Pre-scan	05	TX mode_Keep the EUT in continuously transmitting mode with GFSK modulation.
Final test	06	Charge + TX mode_Keep the EUT in charging and continuously transmitting mode with GFSK modulation.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

7.7.3 Test Setup Diagram




7.7.4 Measurement Procedure and Data

- For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- Test the EUT in the lowest channel, the Highest channel.
- The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- Repeat above procedures until all frequencies measured was complete.

Remark 1: Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor

Remark 2: For frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.


Test Mode: 06; Polarity: Horizontal; Modulation:GFSK; Channel:Low; Antenna 1



race: (Discrete)

	Read	Antenna	Cable	Preamp		Limit	Over		
Freq	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	2389.352	56.22	27.33	3.48	37.59	49.44	54.00	-4.56	HORIZONTAL Average
2	2389.352	69.87	27.33	3.48	37.59	63.09	74.00	-10.91	HORIZONTAL Peak
3	2390.000	55.95	27.33	3.48	37.59	49.17	54.00	-4.83	HORIZONTAL Average
4	2390.000	68.40	27.33	3.48	37.59	61.62	74.00	-12.38	HORIZONTAL Peak
5 *	2412.000	118.63	27.38	3.47	37.59	111.89	54.00	57.89	HORIZONTAL Average
6 *	2412.000	131.23	27.38	3.47	37.59	124.49	74.00	50.49	HORIZONTAL Peak


Test Mode: 06; Polarity: Vertical; Modulation:GFSK; Channel:Low; Antenna 1



Trace: (Discrete)

	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
	MHz	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	2388.508	55.98	27.33	3.48	37.59	49.20	54.00	-4.80	VERTICAL	Average
2	2389.914	69.16	27.33	3.48	37.59	62.38	74.00	-11.62	VERTICAL	Peak
3	2390.000	55.81	27.33	3.48	37.59	49.03	54.00	-4.97	VERTICAL	Average
4	2390.000	67.69	27.33	3.48	37.59	60.91	74.00	-13.09	VERTICAL	Peak
5 *	2412.000	115.27	27.38	3.47	37.59	108.53	54.00	54.53	VERTICAL	Average
6 *	2412.000	126.93	27.38	3.47	37.59	120.19	74.00	46.19	VERTICAL	Peak


Test Mode: 06; Polarity: Horizontal; Modulation:GFSK; Channel:High; Antenna 1



Trace: (Discrete)

		ReadAntenna		Cable	Preamp		Limit	Over		
	Freq	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1 *	2467.000	115.54	27.45	3.50	37.57	108.92	54.00	54.92	HORIZONTAL	Average
2 *	2467.000	128.02	27.45	3.50	37.57	121.40	74.00	47.40	HORIZONTAL	Peak
3	2483.500	56.17	27.48	3.53	37.57	49.61	54.00	-4.39	HORIZONTAL	Average
4	2483.500	67.63	27.48	3.53	37.57	61.07	74.00	-12.93	HORIZONTAL	Peak
5	2484.844	56.32	27.48	3.53	37.57	49.76	54.00	-4.24	HORIZONTAL	Average
6	2484.844	69.53	27.48	3.53	37.57	62.97	74.00	-11.03	HORIZONTAL	Peak


Test Mode: 06; Polarity: Vertical; Modulation:GFSK; Channel:High; Antenna 1



race: (Discrete)


		ReadAntenna		Cable	Preamp		Limit	Over		
	Freq	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1 *	2467.000	114.33	27.45	3.50	37.57	107.71	54.00	53.71	VERTICAL	Average
2 *	2467.000	126.45	27.45	3.50	37.57	119.83	74.00	45.83	VERTICAL	Peak
3	2483.500	55.96	27.48	3.53	37.57	49.40	54.00	-4.60	VERTICAL	Average
4	2483.500	67.90	27.48	3.53	37.57	61.34	74.00	-12.66	VERTICAL	Peak
5	2489.768	69.57	27.49	3.47	37.56	62.97	74.00	-11.03	VERTICAL	Peak
6	2490.070	56.32	27.49	3.47	37.56	49.72	54.00	-4.28	VERTICAL	Average

Test Mode: 06; Polarity: Horizontal; Modulation:GFSK; Channel:Low; Antenna 2



	Freq	ReadAntenna	Cable	Preamp	Limit	Over			
	MHz	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	Remark
1	2386.541	69.35	27.33	3.48	37.60	62.56	74.00	-11.44	HORIZONTAL Peak
2	2387.524	56.01	27.33	3.48	37.59	49.23	54.00	-4.77	HORIZONTAL Average
3	2390.000	55.69	27.33	3.48	37.59	48.91	54.00	-5.09	HORIZONTAL Average
4	2390.000	68.77	27.33	3.48	37.59	61.99	74.00	-12.01	HORIZONTAL Peak
5 *	2412.000	115.04	27.38	3.47	37.59	108.30	54.00	54.30	HORIZONTAL Average
6 *	2412.000	127.81	27.38	3.47	37.59	121.07	74.00	47.07	HORIZONTAL Peak


Test Mode: 06; Polarity: Vertical; Modulation:GFSK; Channel:Low; Antenna 2



Trace: (Discrete)

		ReadAntenna		Cable	Preamp		Limit	Over		
	Freq	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	2389.070	56.33	27.33	3.48	37.59	49.55	54.00	-4.45	VERTICAL	Average
2	2389.633	69.55	27.33	3.48	37.59	62.77	74.00	-11.23	VERTICAL	Peak
3	2390.000	55.93	27.33	3.48	37.59	49.15	54.00	-4.85	VERTICAL	Average
4	2390.000	67.57	27.33	3.48	37.59	60.79	74.00	-13.21	VERTICAL	Peak
5 *	2412.000	119.28	27.38	3.47	37.59	112.54	54.00	58.54	VERTICAL	Average
6 *	2412.000	130.31	27.38	3.47	37.59	123.57	74.00	49.57	VERTICAL	Peak


Test Mode: 06; Polarity: Horizontal; Modulation:GFSK; Channel:High; Antenna 2



Trace: (Discrete)

		ReadAntenna		Cable	Preamp		Limit	Over		
	Freq	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1 *	2467.000	113.36	27.45	3.50	37.57	106.74	54.00	52.74	HORIZONTAL	Average
2 *	2467.000	126.66	27.45	3.50	37.57	120.04	74.00	46.04	HORIZONTAL	Peak
3	2483.500	55.98	27.48	3.53	37.57	49.42	54.00	-4.58	HORIZONTAL	Average
4	2483.500	68.15	27.48	3.53	37.57	61.59	74.00	-12.41	HORIZONTAL	Peak
5	2485.747	56.28	27.48	3.53	37.57	49.72	54.00	-4.28	HORIZONTAL	Average
6	2485.747	70.13	27.48	3.53	37.57	63.57	74.00	-10.43	HORIZONTAL	Peak


Test Mode: 06; Polarity: Vertical; Modulation:GFSK; Channel:High; Antenna 2



race: (Discrete)

		ReadAntenna		Cable	Preamp		Limit	Over		
	Freq	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1 *	2467.000	118.85	27.45	3.50	37.57	112.23	54.00	58.23	VERTICAL	Average
2 *	2467.000	130.56	27.45	3.50	37.57	123.94	74.00	49.94	VERTICAL	Peak
3	2483.500	56.27	27.48	3.53	37.57	49.71	54.00	-4.29	VERTICAL	Average
4	2483.500	67.58	27.48	3.53	37.57	61.02	74.00	-12.98	VERTICAL	Peak
5	2484.743	56.49	27.48	3.53	37.57	49.93	54.00	-4.07	VERTICAL	Average
6	2487.757	69.39	27.48	3.53	37.56	62.84	74.00	-11.16	VERTICAL	Peak


Test Mode: 06; Polarity: Horizontal; Modulation:GFSK; Channel:Low; Antenna 3



race: (Discrete)

		ReadAntenna		Cable	Preamp		Limit	Over		
	Freq	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	2388.086	69.43	27.33	3.48	37.59	62.65	74.00	-11.35	HORIZONTAL	Peak
2	2389.914	56.06	27.33	3.48	37.59	49.28	54.00	-4.72	HORIZONTAL	Average
3	2390.000	55.82	27.33	3.48	37.59	49.04	54.00	-4.96	HORIZONTAL	Average
4	2390.000	68.51	27.33	3.48	37.59	61.73	74.00	-12.27	HORIZONTAL	Peak
5 *	2412.000	118.28	27.38	3.47	37.59	111.54	54.00	57.54	HORIZONTAL	Average
6 *	2412.000	130.00	27.38	3.47	37.59	123.26	74.00	49.26	HORIZONTAL	Peak


Test Mode: 06; Polarity: Vertical; Modulation:GFSK; Channel:Low; Antenna 3



race: (Discrete)

	Read	Antenna	Cable	Preamp		Limit	Over		
Freq	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	2386.963	55.93	27.33	3.48	37.60	49.14	54.00	-4.86	VERTICAL Average
2	2386.963	68.59	27.33	3.48	37.60	61.80	74.00	-12.20	VERTICAL Peak
3	2390.000	55.69	27.33	3.48	37.59	48.91	54.00	-5.09	VERTICAL Average
4	2390.000	67.28	27.33	3.48	37.59	60.50	74.00	-13.50	VERTICAL Peak
5 *	2412.000	115.41	27.38	3.47	37.59	108.67	54.00	54.67	VERTICAL Average
6 *	2412.000	126.28	27.38	3.47	37.59	119.54	74.00	45.54	VERTICAL Peak


Test Mode: 06; Polarity: Horizontal; Modulation:GFSK; Channel:High; Antenna 3



Trace: (Discrete)

		ReadAntenna		Cable	Preamp		Limit	Over		
	Freq	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1 *	2467.000	115.46	27.45	3.50	37.57	108.84	54.00	54.84	HORIZONTAL	Average
2 *	2467.000	127.34	27.45	3.50	37.57	120.72	74.00	46.72	HORIZONTAL	Peak
3	2483.500	56.06	27.48	3.53	37.57	49.50	54.00	-4.50	HORIZONTAL	Average
4	2483.500	68.08	27.48	3.53	37.57	61.52	74.00	-12.48	HORIZONTAL	Peak
5	2486.601	56.23	27.48	3.53	37.57	49.67	54.00	-4.33	HORIZONTAL	Average
6	2489.165	69.78	27.49	3.47	37.56	63.18	74.00	-10.82	HORIZONTAL	Peak


Test Mode: 06; Polarity: Vertical; Modulation:GFSK; Channel:High; Antenna 3



race: (Discrete)

		ReadAntenna		Cable	Preamp		Limit	Over		
	Freq	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1 *	2467.000	114.40	27.45	3.50	37.57	107.78	54.00	53.78	VERTICAL	Average
2 *	2467.000	126.14	27.45	3.50	37.57	119.52	74.00	45.52	VERTICAL	Peak
3	2483.500	55.93	27.48	3.53	37.57	49.37	54.00	-4.63	VERTICAL	Average
4	2483.500	68.16	27.48	3.53	37.57	61.60	74.00	-12.40	VERTICAL	Peak
5	2495.257	69.14	27.49	3.47	37.56	62.54	74.00	-11.46	VERTICAL	Peak
6	2499.394	56.34	27.50	3.40	37.56	49.68	54.00	-4.32	VERTICAL	Average


Test Mode: 06; Polarity: Horizontal; Modulation:GFSK; Channel:Low; Antenna 4



Trace: (Discrete)

	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark	
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	2385.559	55.99	27.33	3.48	37.60	49.20	54.00	-4.80	HORIZONTAL	Average
2	2385.559	69.64	27.33	3.48	37.60	62.85	74.00	-11.15	HORIZONTAL	Peak
3	2390.000	55.83	27.33	3.48	37.59	49.05	54.00	-4.95	HORIZONTAL	Average
4	2390.000	68.44	27.33	3.48	37.59	61.66	74.00	-12.34	HORIZONTAL	Peak
5 *	2412.000	115.13	27.38	3.47	37.59	108.39	54.00	54.39	HORIZONTAL	Average
6 *	2412.000	127.20	27.38	3.47	37.59	120.46	74.00	46.46	HORIZONTAL	Peak


Test Mode: 06; Polarity: Vertical; Modulation:GFSK; Channel:Low; Antenna 4



Trace: (Discrete)

	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
	MHz	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	2388.789	56.06	27.33	3.48	37.59	49.28	54.00	-4.72	VERTICAL	Average
2	2389.492	69.18	27.33	3.48	37.59	62.40	74.00	-11.60	VERTICAL	Peak
3	2390.000	55.87	27.33	3.48	37.59	49.09	54.00	-4.91	VERTICAL	Average
4	2390.000	67.42	27.33	3.48	37.59	60.64	74.00	-13.36	VERTICAL	Peak
5 *	2412.000	118.41	27.38	3.47	37.59	111.67	54.00	57.67	VERTICAL	Average
6 *	2412.000	130.70	27.38	3.47	37.59	123.96	74.00	49.96	VERTICAL	Peak


Test Mode: 06; Polarity: Horizontal; Modulation:GFSK; Channel:High; Antenna 4



race: (Discrete)

		ReadAntenna	Cable	Preamp		Limit	Over			
	Freq	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1 *	2467.000	115.93	27.45	3.50	37.57	109.31	54.00	55.31	HORIZONTAL	Average
2 *	2467.000	128.60	27.45	3.50	37.57	121.98	74.00	47.98	HORIZONTAL	Peak
3	2483.500	56.02	27.48	3.53	37.57	49.46	54.00	-4.54	HORIZONTAL	Average
4	2483.500	68.01	27.48	3.53	37.57	61.45	74.00	-12.55	HORIZONTAL	Peak
5	2486.049	69.83	27.48	3.53	37.57	63.27	74.00	-10.73	HORIZONTAL	Peak
6	2486.055	56.45	27.48	3.53	37.57	49.89	54.00	-4.11	HORIZONTAL	Average

Test Mode: 06; Polarity: Vertical; Modulation:GFSK; Channel:High; Antenna 4



race: (Discrete)

		ReadAntenna	Cable	Preamp		Limit	Over			
	Freq	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1 *	2467.000	118.38	27.45	3.50	37.57	111.76	54.00	57.76	VERTICAL	Average
2 *	2467.000	130.15	27.45	3.50	37.57	123.53	74.00	49.53	VERTICAL	Peak
3	2483.500	56.34	27.48	3.53	37.57	49.78	54.00	-4.22	VERTICAL	Average
4	2483.500	67.76	27.48	3.53	37.57	61.20	74.00	-12.80	VERTICAL	Peak
5	2484.292	56.41	27.48	3.53	37.57	49.85	54.00	-4.15	VERTICAL	Average
6	2486.099	69.90	27.48	3.53	37.57	63.34	74.00	-10.66	VERTICAL	Peak

7.8 Radiated Spurious Emissions (Below 1GHz)

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.209
Test Method: ANSI C63.10 (2013) Section 6.4,6.5,6.6
Measurement Distance: 3m
Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

7.8.1 E.U.T. Operation

Operating Environment:

Temperature: 25.6 °C Humidity: 55.4 % RH Atmospheric Pressure: 1003 mbar


7.8.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Pre-scan	05	TX mode_Keep the EUT in continuously transmitting mode with GFSK modulation.
Final test	06	Charge + TX mode_Keep the EUT in charging and continuously transmitting mode with GFSK modulation.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.
Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

7.8.3 Test Setup Diagram



7.8.4 Measurement Procedure and Data


- For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- Test the EUT in the lowest channel, the middle channel, the Highest channel.
- The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- Repeat above procedures until all frequencies measured was complete.

Remark:


- Through pre-scan found the worst case is the lowest channel. Only the worst case is recorded in the report.
- The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:
Final Test Level = Receiver Reading + Antenna Factor + Cable Factor - Preamplifier Factor
- Scan from 9kHz to 1 GHz, the disturbance below 30MHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.

Worst Case: Antenna 1

Test Mode: 06; Polarity: Horizontal



Test Mode: 06; Polarity: Vertical



7.9 Radiated Spurious Emissions (Above 1GHz)

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.209
 Test Method: ANSI C63.10 (2013) Section 6.4,6.5,6.6
 Measurement Distance: 3m
 Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

7.9.1 E.U.T. Operation

Operating Environment:

Temperature: 25.6 °C Humidity: 55.5 % RH Atmospheric Pressure: 1003 mbar

7.9.2 Test Mode Description


Pre-scan / Final test	Mode Code	Description
Pre-scan	05	TX mode_Keep the EUT in continuously transmitting mode with GFSK modulation.
Final test	06	Charge + TX mode_Keep the EUT in charging and continuously transmitting mode with GFSK modulation.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

7.9.3 Test Setup Diagram



7.9.4 Measurement Procedure and Data

- a. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- g. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- i. Repeat above procedures until all frequencies measured was complete.

Remark:

1) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Final Test Level = Receiver Reading + Antenna Factor + Cable Factor - Preamplifier Factor


2) Scan from 1GHz to 25GHz, the disturbance above 18GHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.

3) The field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.
Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com


Test Mode: 06; Polarity: Horizontal; Modulation:GFSK; Channel:Low; Antenna1



race: (Discrete)

	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
	MHz	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1667.951	52.42	25.66	2.80	37.91	42.97	74.00	-31.03	HORIZONTAL	Peak
2	4482.150	50.76	30.78	4.99	36.81	49.72	74.00	-24.28	HORIZONTAL	Peak
3	4824.000	48.67	31.45	5.42	36.83	48.71	74.00	-25.29	HORIZONTAL	Peak
4	5830.640	49.96	32.23	6.04	36.90	51.33	54.00	-2.67	HORIZONTAL	Average
5	5830.640	53.56	32.23	6.04	36.90	54.93	74.00	-19.07	HORIZONTAL	Peak
6	7236.000	38.75	35.70	6.03	37.39	43.09	54.00	-10.91	HORIZONTAL	Average
7	7236.000	51.15	35.70	6.03	37.39	55.49	74.00	-18.51	HORIZONTAL	Peak
8	9648.000	45.22	38.40	7.06	37.42	53.26	74.00	-20.74	HORIZONTAL	Peak


Test Mode: 06; Polarity: Vertical; Modulation: GFSK; Channel: Low; Antenna1



race: (Discrete)

	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
	MHz	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1648.778	49.83	25.63	2.80	37.93	40.33	74.00	-33.67	VERTICAL	Peak
2	4495.125	49.28	30.80	5.05	36.82	48.31	74.00	-25.69	VERTICAL	Peak
3	4824.000	49.83	31.45	5.42	36.83	49.87	74.00	-24.13	VERTICAL	Peak
4	5830.640	51.65	32.23	6.04	36.90	53.02	54.00	-0.98	VERTICAL	Average
5	5830.640	54.58	32.23	6.04	36.90	55.95	74.00	-18.05	VERTICAL	Peak
6	7236.000	47.64	35.70	6.03	37.39	51.98	74.00	-22.02	VERTICAL	Peak
7	9648.000	44.92	38.40	7.06	37.42	52.96	74.00	-21.04	VERTICAL	Peak


Test Mode: 06; Polarity: Horizontal; Modulation:GFSK; Channel:middle; Antenna1



race: (Discrete)

		Read	Antenna	Cable	Preamp		Limit	Over		
	Freq	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1525.000	49.97	25.52	2.80	38.07	40.22	74.00	-33.78	HORIZONTAL	Peak
2	4495.125	49.56	30.80	5.05	36.82	48.59	74.00	-25.41	HORIZONTAL	Peak
3	4884.000	48.42	31.56	5.52	36.84	48.66	74.00	-25.34	HORIZONTAL	Peak
4	5847.517	49.86	32.25	6.00	36.90	51.21	54.00	-2.79	HORIZONTAL	Average
5	5847.517	54.00	32.25	6.00	36.90	55.35	74.00	-18.65	HORIZONTAL	Peak
6	7326.000	48.47	36.00	6.13	37.43	53.17	74.00	-20.83	HORIZONTAL	Peak
7	9768.000	44.75	38.53	7.01	37.41	52.88	74.00	-21.12	HORIZONTAL	Peak


Test Mode: 06; Polarity: Vertical; Modulation: GFSK; Channel: middle; Antenna1



race: (Discrete)


	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark	
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1692.231	50.05	25.70	2.80	37.89	40.66	74.00	-33.34	VERTICAL	Peak
2	4291.977	51.06	30.45	4.64	36.81	49.34	74.00	-24.66	VERTICAL	Peak
3	4884.000	48.25	31.56	5.52	36.84	48.49	74.00	-25.51	VERTICAL	Peak
4	5847.517	51.23	32.25	6.00	36.90	52.58	54.00	-1.42	VERTICAL	Average
5	5847.517	56.11	32.25	6.00	36.90	57.46	74.00	-16.54	VERTICAL	Peak
6	7326.000	49.73	36.00	6.13	37.43	54.43	74.00	-19.57	VERTICAL	Peak
7	9768.000	45.41	38.53	7.01	37.41	53.54	74.00	-20.46	VERTICAL	Peak

Test Mode: 06; Polarity: Horizontal; Modulation:GFSK; Channel:High; Antenna1



	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
	MHz	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1175.697	50.93	24.58	2.38	38.40	39.49	74.00	-34.51	HORIZONTAL	Peak
2	4367.058	50.06	30.62	4.68	36.81	48.55	74.00	-25.45	HORIZONTAL	Peak
3	4934.000	48.55	31.62	5.60	36.84	48.93	74.00	-25.07	HORIZONTAL	Peak
4	5847.517	50.14	32.25	6.00	36.90	51.49	54.00	-2.51	HORIZONTAL	Average
5	5847.517	54.03	32.25	6.00	36.90	55.38	74.00	-18.62	HORIZONTAL	Peak
6	7401.000	47.37	36.22	6.20	37.46	52.33	74.00	-21.67	HORIZONTAL	Peak
7	9868.000	44.42	38.60	6.98	37.41	52.59	74.00	-21.41	HORIZONTAL	Peak


Test Mode: 06; Polarity: Vertical; Modulation:GFSK; Channel:High; Antenna1



Trace: (Discrete)

	Freq	ReadAntenna	Cable	Preamp		Limit	Over		
		Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	1663.137	51.04	25.65	2.80	37.91	41.58	74.00	-32.42	VERTICAL
2	4482.150	49.94	30.78	4.99	36.81	48.90	74.00	-25.10	VERTICAL
3	4934.000	48.31	31.62	5.60	36.84	48.69	74.00	-25.31	VERTICAL
4	5847.517	52.00	32.25	6.00	36.90	53.35	54.00	-0.65	VERTICAL
5	5847.517	55.03	32.25	6.00	36.90	56.38	74.00	-17.62	VERTICAL
6	7401.000	48.29	36.22	6.20	37.46	53.25	74.00	-20.75	VERTICAL
7	9868.000	44.66	38.60	6.98	37.41	52.83	74.00	-21.17	VERTICAL


Test Mode: 06; Polarity: Horizontal; Modulation: GFSK; Channel: Low; Antenna2



Trace: (Discrete)

	Freq	ReadAntenna	Cable	Preamp		Limit	Over		
	MHz	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	1663.137	52.27	25.65	2.80	37.91	42.81	74.00	-31.19	HORIZONTAL Peak
2	3445.535	56.09	28.87	4.18	36.96	52.18	74.00	-21.82	HORIZONTAL Peak
3	4824.000	49.04	31.45	5.42	36.83	49.08	74.00	-24.92	HORIZONTAL Peak
4	5847.517	50.41	32.25	6.00	36.90	51.76	54.00	-2.24	HORIZONTAL Average
5	5847.517	54.43	32.25	6.00	36.90	55.78	74.00	-18.22	HORIZONTAL Peak
6	7236.000	48.33	35.70	6.03	37.39	52.67	74.00	-21.33	HORIZONTAL Peak
7	9648.000	44.85	38.40	7.06	37.42	52.89	74.00	-21.11	HORIZONTAL Peak


Test Mode: 06; Polarity: Vertical; Modulation:GFSK; Channel:Low; Antenna2



race: (Discrete)


	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark	
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1667.951	51.81	25.66	2.80	37.91	42.36	74.00	-31.64	VERTICAL	Peak
2	4482.150	49.64	30.78	4.99	36.81	48.60	74.00	-25.40	VERTICAL	Peak
3	4824.000	50.03	31.45	5.42	36.83	50.07	74.00	-23.93	VERTICAL	Peak
4	5847.517	51.36	32.25	6.00	36.90	52.71	54.00	-1.29	VERTICAL	Average
5	5847.517	55.17	32.25	6.00	36.90	56.52	74.00	-17.48	VERTICAL	Peak
6	7236.000	49.09	35.70	6.03	37.39	53.43	74.00	-20.57	VERTICAL	Peak
7	9648.000	45.50	38.40	7.06	37.42	53.54	74.00	-20.46	VERTICAL	Peak

Test Mode: 06; Polarity: Horizontal; Modulation:GFSK; Channel:middle; Antenna2



	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
	MHz	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1439.343	49.58	25.44	2.68	38.17	39.53	74.00	-34.47	HORIZONTAL	Peak
2	4354.454	50.19	30.59	4.68	36.81	48.65	74.00	-25.35	HORIZONTAL	Peak
3	4884.000	48.04	31.56	5.52	36.84	48.28	74.00	-25.72	HORIZONTAL	Peak
4	5847.517	48.21	32.25	6.00	36.90	49.56	54.00	-4.44	HORIZONTAL	Average
5	5847.517	54.50	32.25	6.00	36.90	55.85	74.00	-18.15	HORIZONTAL	Peak
6	7326.000	47.95	36.00	6.13	37.43	52.65	74.00	-21.35	HORIZONTAL	Peak
7	9768.000	45.21	38.53	7.01	37.41	53.34	74.00	-20.66	HORIZONTAL	Peak


Test Mode: 06; Polarity: Vertical; Modulation: GFSK; Channel: middle; Antenna2



race: (Discrete)


	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark	
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1569.721	50.92	25.55	2.80	38.00	41.27	74.00	-32.73	VERTICAL	Peak
2	3536.341	53.05	28.95	4.40	36.93	49.47	74.00	-24.53	VERTICAL	Peak
3	4884.000	48.12	31.56	5.52	36.84	48.36	74.00	-25.64	VERTICAL	Peak
4	5847.517	51.63	32.25	6.00	36.90	52.98	54.00	-1.02	VERTICAL	Average
5	5847.517	55.50	32.25	6.00	36.90	56.85	74.00	-17.15	VERTICAL	Peak
6	7326.000	48.75	36.00	6.13	37.43	53.45	74.00	-20.55	VERTICAL	Peak
7	9768.000	44.97	38.53	7.01	37.41	53.10	74.00	-20.90	VERTICAL	Peak

Test Mode: 06; Polarity: Horizontal; Modulation:GFSK; Channel:High; Antenna2




	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
	MHz	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1663.137	48.76	25.65	2.80	37.91	39.30	74.00	-34.70	HORIZONTAL	Peak
2	4367.058	49.92	30.62	4.68	36.81	48.41	74.00	-25.59	HORIZONTAL	Peak
3	4934.000	48.75	31.62	5.60	36.84	49.13	74.00	-24.87	HORIZONTAL	Peak
4	5847.517	50.61	32.25	6.00	36.90	51.96	54.00	-2.04	HORIZONTAL	Average
5	5847.517	53.29	32.25	6.00	36.90	54.64	74.00	-19.36	HORIZONTAL	Peak
6	7401.000	48.03	36.22	6.20	37.46	52.99	74.00	-21.01	HORIZONTAL	Peak
7	9868.000	44.97	38.60	6.98	37.41	53.14	74.00	-20.86	HORIZONTAL	Peak

Test Mode: 06; Polarity: Vertical; Modulation:GFSK; Channel:High; Antenna2




	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
		Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1663.137	49.45	25.65	2.80	37.91	39.99	74.00	-34.01	VERTICAL	Peak
2	4495.125	50.46	30.80	5.05	36.82	49.49	74.00	-24.51	VERTICAL	Peak
3	4934.000	48.43	31.62	5.60	36.84	48.81	74.00	-25.19	VERTICAL	Peak
4	5847.517	51.78	32.25	6.00	36.90	53.13	54.00	-0.87	VERTICAL	Average
5	5847.517	54.37	32.25	6.00	36.90	55.72	74.00	-18.28	VERTICAL	Peak
6	7401.000	48.45	36.22	6.20	37.46	53.41	74.00	-20.59	VERTICAL	Peak
7	9868.000	45.16	38.60	6.98	37.41	53.33	74.00	-20.67	VERTICAL	Peak

Test Mode: 06; Polarity: Horizontal; Modulation:GFSK; Channel:Low; Antenna3




	Freq	ReadAntenna	Cable	Preamp		Limit	Over		
	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	1525.000	49.62	25.52	2.80	38.07	39.87	74.00	-34.13	HORIZONTAL Peak
2	4354.454	50.20	30.59	4.68	36.81	48.66	74.00	-25.34	HORIZONTAL Peak
3	4824.000	48.73	31.45	5.42	36.83	48.77	74.00	-25.23	HORIZONTAL Peak
4	5847.517	49.75	32.25	6.00	36.90	51.10	54.00	-2.90	HORIZONTAL Average
5	5847.517	54.51	32.25	6.00	36.90	55.86	74.00	-18.14	HORIZONTAL Peak
6	7236.000	48.82	35.70	6.03	37.39	53.16	74.00	-20.84	HORIZONTAL Peak
7	9648.000	45.18	38.40	7.06	37.42	53.22	74.00	-20.78	HORIZONTAL Peak

Test Mode: 06; Polarity: Vertical; Modulation:GFSK; Channel:Low; Antenna3




	ReadAntenna	Cable	Preamp		Limit	Over			
Freq	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1663.137	58.34	25.65	2.80	37.91	48.88	74.00	-25.12	VERTICAL Peak
2	4469.214	49.70	30.77	4.93	36.81	48.59	74.00	-25.41	VERTICAL Peak
3	4824.000	49.43	31.45	5.42	36.83	49.47	74.00	-24.53	VERTICAL Peak
4	5847.517	51.97	32.25	6.00	36.90	53.32	54.00	-0.68	VERTICAL Average
5	5847.517	55.29	32.25	6.00	36.90	56.64	74.00	-17.36	VERTICAL Peak
6	7236.000	48.30	35.70	6.03	37.39	52.64	74.00	-21.36	VERTICAL Peak
7	9648.000	45.14	38.40	7.06	37.42	53.18	74.00	-20.82	VERTICAL Peak

Test Mode: 06; Polarity: Horizontal; Modulation:GFSK; Channel:middle; Antenna3




	Freq	ReadAntenna	Cable	Preamp		Limit	Over		
		Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	Remark
1	1677.621	49.42	25.68	2.80	37.91	39.99	74.00	-34.01	HORIZONTAL Peak
2	4367.058	50.16	30.62	4.68	36.81	48.65	74.00	-25.35	HORIZONTAL Peak
3	4884.000	48.70	31.56	5.52	36.84	48.94	74.00	-25.06	HORIZONTAL Peak
4	5847.517	51.43	32.25	6.00	36.90	52.78	54.00	-1.22	HORIZONTAL Average
5	5847.517	53.04	32.25	6.00	36.90	54.39	74.00	-19.61	HORIZONTAL Peak
6	7326.000	48.16	36.00	6.13	37.43	52.86	74.00	-21.14	HORIZONTAL Peak
7	9768.000	44.94	38.53	7.01	37.41	53.07	74.00	-20.93	HORIZONTAL Peak

Test Mode: 06; Polarity: Vertical; Modulation: GFSK; Channel: middle; Antenna3



	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
	MHz	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1331.288	51.76	25.28	2.60	38.29	41.35	74.00	-32.65	VERTICAL	Peak
2	4495.125	49.75	30.80	5.05	36.82	48.78	74.00	-25.22	VERTICAL	Peak
3	4884.000	48.09	31.56	5.52	36.84	48.33	74.00	-25.67	VERTICAL	Peak
4	5847.517	51.99	32.25	6.00	36.90	53.34	54.00	-0.66	VERTICAL	Average
5	5847.517	55.34	32.25	6.00	36.90	56.69	74.00	-17.31	VERTICAL	Peak
6	7326.000	47.47	36.00	6.13	37.43	52.17	74.00	-21.83	VERTICAL	Peak
7	9768.000	45.52	38.53	7.01	37.41	53.65	74.00	-20.35	VERTICAL	Peak


Test Mode: 06; Polarity: Horizontal; Modulation:GFSK; Channel:High; Antenna3



Trace: (Discrete)

	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
	MHz	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1611.091	50.12	25.59	2.80	37.98	40.53	74.00	-33.47	HORIZONTAL	Peak
2	4469.214	49.87	30.77	4.93	36.81	48.76	74.00	-25.24	HORIZONTAL	Peak
3	4934.000	48.83	31.62	5.60	36.84	49.21	74.00	-24.79	HORIZONTAL	Peak
4	5847.517	49.67	32.25	6.00	36.90	51.02	54.00	-2.98	HORIZONTAL	Average
5	5847.517	54.44	32.25	6.00	36.90	55.79	74.00	-18.21	HORIZONTAL	Peak
6	7401.000	48.10	36.22	6.20	37.46	53.06	74.00	-20.94	HORIZONTAL	Peak
7	9868.000	45.09	38.60	6.98	37.41	53.26	74.00	-20.74	HORIZONTAL	Peak


Test Mode: 06; Polarity: Vertical; Modulation:GFSK; Channel:High; Antenna3



race: (Discrete)

	Freq	ReadAntenna Level	Factor	Cable Loss	Preamp Factor	Level	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1663.137	52.72	25.65	2.80	37.91	43.26	74.00	-30.74	VERTICAL	Peak
2	4267.237	50.40	30.38	4.63	36.81	48.60	74.00	-25.40	VERTICAL	Peak
3	4934.000	48.86	31.62	5.60	36.84	49.24	74.00	-24.76	VERTICAL	Peak
4	5847.517	52.28	32.25	6.00	36.90	53.63	54.00	-0.37	VERTICAL	Average
5	5847.517	55.13	32.25	6.00	36.90	56.48	74.00	-17.52	VERTICAL	Peak
6	7401.000	47.87	36.22	6.20	37.46	52.83	74.00	-21.17	VERTICAL	Peak
7	9868.000	44.81	38.60	6.98	37.41	52.98	74.00	-21.02	VERTICAL	Peak


Test Mode: 06; Polarity: Horizontal; Modulation: GFSK; Channel: Low; Antenna4



race: (Discrete)


		ReadAntenna		Cable	Preamp		Limit	Over		
	Freq	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1692.231	49.18	25.70	2.80	37.89	39.79	74.00	-34.21	HORIZONTAL	Peak
2	4254.921	50.85	30.34	4.62	36.81	49.00	74.00	-25.00	HORIZONTAL	Peak
3	4824.000	49.76	31.45	5.42	36.83	49.80	74.00	-24.20	HORIZONTAL	Peak
4	5847.517	50.69	32.25	6.00	36.90	52.04	54.00	-1.96	HORIZONTAL	Average
5	5847.517	53.26	32.25	6.00	36.90	54.61	74.00	-19.39	HORIZONTAL	Peak
6	7236.000	47.74	35.70	6.03	37.39	52.08	74.00	-21.92	HORIZONTAL	Peak
7	9648.000	44.66	38.40	7.06	37.42	52.70	74.00	-21.30	HORIZONTAL	Peak

Test Mode: 06; Polarity: Vertical; Modulation:GFSK; Channel:Low; Antenna4



	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
		Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1663.137	56.30	25.65	2.80	37.91	46.84	74.00	-27.16	VERTICAL	Peak
2	4469.214	50.05	30.77	4.93	36.81	48.94	74.00	-25.06	VERTICAL	Peak
3	4824.000	49.09	31.45	5.42	36.83	49.13	74.00	-24.87	VERTICAL	Peak
4	5847.517	51.45	32.25	6.00	36.90	52.80	54.00	-1.20	VERTICAL	Average
5	5847.517	54.71	32.25	6.00	36.90	56.06	74.00	-17.94	VERTICAL	Peak
6	7236.000	48.64	35.70	6.03	37.39	52.98	74.00	-21.02	VERTICAL	Peak
7	9648.000	45.45	38.40	7.06	37.42	53.49	74.00	-20.51	VERTICAL	Peak

Test Mode: 06; Polarity: Horizontal; Modulation:GFSK; Channel:middle; Antenna4



		ReadAntenna		Cable	Preamp		Limit	Over		
	Freq	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1663.137	48.35	25.65	2.80	37.91	38.89	74.00	-35.11	HORIZONTAL	Peak
2	4193.872	49.06	30.15	4.60	36.81	47.00	74.00	-27.00	HORIZONTAL	Peak
3	4884.000	46.91	31.56	5.52	36.84	47.15	74.00	-26.85	HORIZONTAL	Peak
4	5830.640	50.42	32.23	6.04	36.90	51.79	54.00	-2.21	HORIZONTAL	Average
5	5830.640	53.53	32.23	6.04	36.90	54.90	74.00	-19.10	HORIZONTAL	Peak
6	7326.000	46.36	36.00	6.13	37.43	51.06	74.00	-22.94	HORIZONTAL	Peak
7	9768.000	44.95	38.53	7.01	37.41	53.08	74.00	-20.92	HORIZONTAL	Peak