



FCC ID: 2ALIE-GWS1XX
Report No.: T180807D10-MF

Page: 1 / 6
Rev.: 00

IEEE C95.1 2005
KDB 447498 D01 V06
47 C.F.R. Part 1, Subpart I, Section 1.1310
47 C.F.R. Part 2, Subpart J, Section 2.1091

RF EXPOSURE REPORT

For

IoT Gateway

Model: S1

Trade Name: **SIMPNIC**

Issued to

CONNECTION TECHNOLOGY SYSTEMS INC.
18F-6, No.79, Sec.1, Xintai 5th Rd., Xizhi Dist., New Taipei City 221, TAIWAN, R.O.C.

Issued by

Compliance Certification Services Inc.
No.11, Wugong 6th Rd., Wugu Dist.,
New Taipei City 24891, Taiwan. (R.O.C.)
Issued Date: November 19, 2018

Note: *This document may be altered or revised by Compliance Certification Services Inc. personnel only, and shall be noted in the revision section of the document. The client should not use it to claim product endorsement by TAF, A2LA, NIST or any government agencies. The test results in the report only apply to the tested sample.*

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.
除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部分複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.



Report No.: T180807D10-MF

Page: 2 / 6

Rev.: 00

Revision History

Rev.	Issue Date	Revisions	Effect Page	Revised By
00	November 19, 2018	Initial Issue	ALL	Allison Chen



Report No.: T180807D10-MF

Page: 3 / 6
Rev.: 00

TABLE OF CONTENTS

1. EUT SPECIFICATION.....	4
2. TEST RESULTS	5
3. MAXIMUM PERMISSIBLE EXPOSURE.....	6



Report No.: T180807D10-MF

Page: 4 / 6

Rev.: 00

1. EUT SPECIFICATION

EUT	IoT Gateway
Model	S1
Model Discrepancy	N/A
Frequency band (Operating)	☒ IEEE 802.11b/g/n HT20 Mode: 2.412GHz ~ 2.462GHz IEEE 802.11n HT40 Mode: 2.422GHz ~ 2.452GHz ☒ 908.4 ~ 916MHz ☐ Others
Device category	☐ Portable (<20cm separation) ☒ Mobile (>20cm separation) ☐ Others
Exposure classification	☐ Occupational/Controlled exposure ($S = 5\text{mW/cm}^2$) ☒ General Population/Uncontrolled exposure ($S=1\text{mW/cm}^2$)
Antenna Specification	For WIFI 2.4GHz Antenna 1 Gain : 3.24 dBi (Numeric gain: 2.11) Antenna 2 Gain : 3.46 dBi (Numeric gain: 2.22) Power Directional Gain : 3.35 dBi (Numeric gain: 2.16) For Z-Wave Antenna Gain : 0.36 dBi (Numeric gain: 1.09)
Maximum Average output power	For WIFI 2.4GHz IEEE 802.11b Mode: 22.00 dBm (158.489 mW) IEEE 802.11g Mode: 21.50 dBm (141.254 mW) IEEE 802.11n HT 20 Mode: 21.50 dBm (141.254 mW) IEEE 802.11n HT 40 Mode: 21.00 dBm (125.893 mW) For Z-Wave Z-Wave 3.00 dBm (1.995 mW)
Evaluation applied	☒ MPE Evaluation* ☐ SAR Evaluation ☐ N/A



Report No.: T180807D10-MF

Page: 5 / 6

Rev.: 00

2. TEST RESULTS

No non-compliance noted.

Calculation

Given $E = \frac{\sqrt{30 \times P \times G}}{d}$ & $S = \frac{E^2}{377}$

Where E = Field strength in Volts / meter

P = Power in Watts

G = Numeric antenna gain

d = Distance in meters

S = Power density in milliwatts / square centimeter

Combining equations and re-arranging the terms to express the distance as a function of the remaining variables yields:

$$S = \frac{30 \times P \times G}{377 d^2}$$

Changing to units of mW and cm, using:

$$P \text{ (mW)} = P \text{ (W)} / 1000 \text{ and}$$

$$d \text{ (cm)} = d \text{ (m)} / 100$$

Yields

$$S = \frac{30 \times (P/1000) \times G}{377 \times (d/100)^2} = 0.0796 \times \frac{P \times G}{d^2} \quad \text{Equation 1}$$

Where d = Distance in cm

P = Power in mW

G = Numeric antenna gain

S = Power density in mW / cm²

3. MAXIMUM PERMISSIBLE EXPOSURE

Substituting the MPE safe distance using $d = 20$ cm into Equation 1:

$$S = 0.000199 \times P \times G$$

Where P = Power in mW

G = Numeric antenna gain

S = Power density in mW / cm²

Z-Wave:

Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm ²)
916	1.995	1.09	20	0.0004	1

IEEE 802.11b Mode:

Ch.	Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm ²)
11	2462	158.489	2.22	20	0.0700	1.000

IEEE 802.11g Mode:

Ch.	Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm ²)
6	2437	141.254	2.22	20	0.0624	1.000

IEEE 802.11n HT20 Mode:

Ch.	Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm ²)
1	2412	141.254	2.16	20	0.0607	1.000

IEEE 802.11n HT40 Mode:

Ch.	Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm ²)
6	2437	125.893	2.16	20	0.0541	1.000