FCC Part 15C Test Report

FCC ID: 2ALIU-DR1M1

Product Name:	**Roby**
Trademark:	**N/A**
Model Name :	**DR1MUS001**
Serial Model:	**N/A**
Prepared For : Address :	**Beijing Today Innovation Technology Co., Ltd.** No.118, Floor 1, Building 1, No.7, North Ritan Road, Chaoyang District, Beijing, PRC
Prepared By : Address :	**Shenzhen BCTC Testing Co., Ltd.** BCTC Building & 1-2F, East of B Building, Pengzhou Industrial, Fuyuan 1st Road, Qiaotou Community, Fuyong Street, Bao'an District, Shenzhen, China
Test Date:	Jan. 05 - Jan. 12, 2018
Date of Report :	Jan. 12, 2018
Report No.:	BCTC-FY171208611E

VERIFICATION OF COMPLIANCE

Applicant's name ..... :	**Beijing Today Innovation Technology Co., Ltd.**
Address ..... :	No.118, Floor 1, Building 1, No.7, North Ritan Road, Chaoyang District, Beijing, PRC
Manufacture's Name..... :	**Beijing Today Innovation Technology Co., Ltd.**
Address ..... :	No.118, Floor 1, Building 1, No.7, North Ritan Road, Chaoyang District, Beijing, PRC
Product description	
Product name ..... :	Roby
Trademark:	N/A
Model Name:	DR1MUS001
Standards:	ANSI C63.10-2013 FCC Part15.249

This device described above has been tested by BCTC, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of BCTC, this document may be altered or revised by BCTC, personal only, and shall be noted in the revision of the document.

Test Result.....: **Pass**

Prepared by(Engineer):	Eric Yang	
Reviewer(Supervisor):	Jade Yang	
Approved(Manager):	Carson Zhang	

Table of Contents **Page**

1 . SUMMARY OF TEST RESULTS 5
1.1 TEST FACILITY 5
1.2 MEASUREMENT UNCERTAINTY 5
2 . GENERAL INFORMATION 6
2.1 GENERAL DESCRIPTION OF EUT 6
2.2 DESCRIPTION OF TEST MODES 7
2.3 TABLE OF PARAMETERS OF TEXT SOFTWARE SETTING 8
2.4 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED 8
2.5 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE) 9
2.6 EQUIPMENTS LIST FOR ALL TEST ITEMS 10
3 . EMC EMISSION TEST 11
3.1 CONDUCTED EMISSION MEASUREMENT 11
3.1.1 POWER LINE CONDUCTED EMISSION LIMITS 11
3.1.2 TEST PROCEDURE 12
3.1.3 DEVIATION FROM TEST STANDARD 12
3.1.4 TEST SETUP 12
3.1.5 EUT OPERATING CONDITIONS 12
3.1.6 TEST RESULTS 13
3.2 RADIATED EMISSION MEASUREMENT 15
3.2.1 RADIATED EMISSION LIMITS 15
3.2.2 TEST PROCEDURE 16
3.2.3 DEVIATION FROM TEST STANDARD 17
3.2.4 TEST SETUP 17
3.2.5 EUT OPERATING CONDITIONS 18
3.2.6 TEST RESULTS 19
4 . BANDWIDTH TEST 24
4.1 APPLIED PROCEDURES / LIMIT 24
4.1.1 TEST PROCEDURE 24
4.1.2 DEVIATION FROM STANDARD 24
4.1.3 TEST SETUP 24
4.1.4 EUT OPERATION CONDITIONS 24
4.1.5 TEST RESULTS 25
5 . 100 KHZ BANDWIDTH OF FREQUENCY BAND EDGE 27
5.1 DEVIATION FROM STANDARD 28
5.2 TEST SETUP 28
5.3 EUT OPERATION CONDITIONS 28

Table of Contents **Page**

5.4 TEST RESULTS **28**

6 . ANTENNA REQUIREMENT **31**

6.1 STANDARD REQUIREMENT **31**

6.2 EUT ANTENNA **31**

7 . EUT TEST PHOTO **32**

8 . PHOTOS OF THE EUT **34**

1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

FCC Part15 (15.249) , Subpart C			
Standard Section	Test Item	Judgment	Remark
15.207	Conducted Emission	PASS	
15.249	Fundamental &Radiated Spurious Emission Measurement	PASS	
15.249	Bandwidth	PASS	
15.205	Band Edge Emission	PASS	
15.203	Antenna Requirement	PASS	

NOTE:

(1)" N/A" denotes test is not applicable in this Test Report

1.1 TEST FACILITY

Shenzhen BCTC Testing Co., Ltd.
Add.: BCTC Building & 1-2F, East of B Building, Pengzhou Industrial, Fuyuan 1st Road, Qiaotou Community, Fuyong Street, Bao'an District, Shenzhen, China
Test Firm Registration Number: 712850

1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement **y** ± **U**, where expended uncertainty **U** is based on a standard uncertainty multiplied by a coverage factor of **k=2**, providing a level of confidence of approximately **95** %。

No.	Item	Uncertainty
1	Conducted Emission Test	±1.38dB
2	RF power,conducted	±0.16dB
3	Spurious emissions,conducted	±0.21dB
4	All emissions,radiated(<1G)	±4.68dB
5	All emissions,radiated(>1G)	±4.89dB
6	Temperature	±0.5°C
7	Humidity	±2%

2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

<table>
<tr><td>Equipment</td><td>Roby</td></tr>
<tr><td>Trade Name</td><td>N/A</td></tr>
<tr><td>Model Name</td><td>DR1MUS001</td></tr>
<tr><td>Serial Model</td><td>N/A</td></tr>
<tr><td>Model Difference</td><td>N/A</td></tr>
<tr><td>Product Description</td><td><table><tr><td>Operation Frequency:</td><td>2402~2480 MHz</td></tr><tr><td>Modulation Type:</td><td>GFSK</td></tr><tr><td>Bit Rate of Transmitter</td><td>2M</td></tr><tr><td>Number Of Channel</td><td>40 CH</td></tr><tr><td>Antenna Designation:</td><td>Please see Note 3.</td></tr></table>
Based on the application, features, or specification exhibited in User's Manual, the EUT is considered as an ITE/Computing Device. More details of EUT technical specification, please refer to the User's Manual.</td></tr>
<tr><td>Channel List</td><td>Please refer to the Note 2.</td></tr>
<tr><td>Power supply</td><td>DC 3.7V (from battery)
DC 5V (from USB)</td></tr>
<tr><td>Connecting I/O Port(s)</td><td>Please refer to the User's Manual</td></tr>
<tr><td>hardware version</td><td>--</td></tr>
<tr><td>Software version</td><td>--</td></tr>
<tr><td>Serial number</td><td>--</td></tr>
</table>

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.

2.

Channel List					
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
01	2402	11	2422	21	2442
02	2404	12	2424	22	2444
03	2406	13	2426	23	2446
~	~	~	~	~	~
09	2418	19	2438	39	2478
10	2420	20	2440	40	2480

3. Table for Filed Antenna

Ant.	Brand	Model Name	Antenna Type	Gain (dBi)	NOTE
1	N/A	N/A	PCB antenna	0	

2.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

For Conducted & Radiated Emission	
Final Test Mode	Description
Mode 1	CH01
Mode 2	CH20
Mode 3	CH40
Mode 4	Link Mode

Note:

(1) The measurements are performed at the highest, middle, lowest available channels.

(2) Fully-charged battery is used during the test

2.3 TABLE OF PARAMETERS OF TEXT SOFTWARE SETTING

During testing channel & power controlling software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product power parameters of FHSS

Frequency	2402 MHz	2440 MHz	2480 MHz
Channel	Low	Middle	High

2.4 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED

Conducted Emission Test



Radiated Spurious Emission Test



2.5 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	Series No.	Note
E-1	Roby	N/A	DR1MUS001	N/A	EUT
E-2	Adapter	N/A	BCTC001	N/A	Lab.Provide

Item	Shielded Type	Ferrite Core	Length	Note
C1	NO	NO	0.8M	USB cable unshielded

Note:

(1) The support equipment was authorized by Declaration of Confirmation.

(2) For detachable type I/O cable should be specified the length in cm in『Length』column.

(3) “YES” is means “shielded” “with core”; “NO” is means “unshielded” “without core”.

2.6 EQUIPMENTS LIST FOR ALL TEST ITEMS

Radiation Test equipment

Item	Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
1	Spectrum Analyzer (9kHz-26.5GHz)	Agilent	E4407B	MY45108040	2017.08.27	2018.08.26
2	Test Receiver (9kHz-7GHz)	R&S	ESPI	101318	2017.08.27	2018.08.26
3	Bilog Antenna (30MHz-1GHz)	R&S	VULB 9168	VULB91 68-438	2017.08.27	2018.08.26
4	Horn Antenna (1GHz-18GHz)	SCHWARZBECK	BBHA9120D	1201	2017.09.03	2018.09.02
5	Horn Antenna (14GHz-40GHz)	SCHWARZBECK	BBHA 9170	9170-181	2017.09.03	2018.09.02
6	Amplifier (9KHz-6GHz)	SCHWARZBECK	BBV9744	9744-0037	2017.08.27	2018.08.26
7	Amplifier (1GHz-18GHz)	SCHWARZBECK	BBV9718	9718-309	2017.08.27	2018.08.26
8	Amplifier (18GHz-40GHz)	SCHWARZBECK	BBV 9721	9721-205	2017.08.27	2018.08.26
9	Loop Antenna (9KHz-30MHz)	SCHWARZBECK	FMZB1519B	00014	2017.09.03	2018.09.02
10	RF cables1 (9kHz-1GHz)	R&S	R203	R20X	2017.08.27	2018.08.26
11	RF cables2 (1GHz-40GHz)	R&S	R204	R21X	2017.08.27	2018.08.26
12	Antenna connector	Florida RF Labs	N/A	RF 01#	2017.08.27	2018.08.26
13	Power Metter	ANRITSU	ML2487A	6K00001568	2017.08.27	2018.08.26
14	Power Sensor (AV)	ANRITSU	ML2491A	030989	2017.08.27	2018.08.26
15	Signal Analyzer 9kHz-26.5GHz	Agilent	N9010A	MY48030494	2017.08.27	2018.08.26
16	Test Receiver 20kHz-40GHz	R&S	ESU 40	100376	2017.08.27	2018.08.26
17	D.C. Power Supply	LongWei	PS-305D	010964729	2017.08.27	2018.08.26

Conduction Test equipment

Item	Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
1	Test Receiver	R&S	ESCI	1166.5950K03-1 01165-ha	2017.08.27	2018.08.26
2	LISN	SCHWARZBECK	NSLK8127	8127739	2017.08.27	2018.08.26
3	LISN	R&S	NSLK8126	8126487	2017.08.27	2018.08.26
4	RF cables	R&S	R204	R20X	2017.08.27	2018.08.26
5	Attenuator	R&S	ESH3-Z2	143206	2017.08.27	2018.08.26

3. EMC EMISSION TEST

3.1 CONDUCTED EMISSION MEASUREMENT

3.1.1 POWER LINE CONDUCTED EMISSION Limits (Frequency Range 150KHz-30MHz)

FREQUENCY (MHz)	Limit (dBuV)		Standard
	Quas -peak	Average	
0.15 -0.5	66 - 56 *	56 - 46 *	FCC
0.50 -5.0	56.00	46.00	FCC
5.0 -30.0	60.00	50.00	FCC

Note:

(1) The tighter limit applies at the band edges.

(2) The limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz

3.1.2 TEST PROCEDURE

a. The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
d. LISN at least 80 cm from nearest part of EUT chassis.
e. For the actual test configuration, please refer to the related Item –EUT Test Photos.

3.1.3 DEVIATION FROM TEST STANDARD

No deviation

3.1.4 TEST SETUP



Note: 1.Support units were connected to second LISN.
2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

3.1.5 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

We pretest AC 120V and AC 240V, the worst voltage was AC 120V and the data recording in the report

3.1.6 TEST RESULTS

Temperature :	25℃	Relative Humidity :	54%
Pressure :	1010hPa	Phase :	L
Test Voltage :	AC120V/60Hz	Test Mode :	Mode 4



Remark:
1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector	Comment
1		0.4155	36.29	9.67	45.96	57.54	-11.58	QP	
2		0.4155	26.30	9.67	35.97	47.54	-11.57	AVG	
3		0.5280	36.59	9.68	46.27	56.00	-9.73	QP	
4		0.5280	25.71	9.68	35.39	46.00	-10.61	AVG	
5		0.9420	40.47	9.69	50.16	56.00	-5.84	QP	
6		0.9420	30.95	9.69	40.64	46.00	-5.36	AVG	
7	*	1.5158	41.95	9.70	51.65	56.00	-4.35	QP	
8		1.5158	31.43	9.70	41.13	46.00	-4.87	AVG	
9		1.8818	40.90	9.71	50.61	56.00	-5.39	QP	
10		1.8818	31.32	9.71	41.03	46.00	-4.97	AVG	
11		4.2450	41.41	9.73	51.14	56.00	-4.86	QP	
12		4.2450	27.55	9.73	37.28	46.00	-8.72	AVG	

Temperature :	25℃	Relative Humidity :	54%
Pressure :	1010hPa	Phase :	N
Test Voltage :	AC120V/60Hz	Test Mode :	Mode 4



Remark:
1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector	Comment
1		0.3664	33.15	9.67	42.82	58.58	-15.76	QP	
2		0.3664	25.05	9.67	34.72	48.58	-13.86	AVG	
3		0.4694	32.77	9.68	42.45	56.52	-14.07	QP	
4		0.4694	31.20	9.68	40.88	46.52	-5.64	AVG	
5		0.6610	23.42	9.68	33.10	56.00	-22.90	QP	
6		0.6610	9.37	9.68	19.05	46.00	-26.95	AVG	
7	*	1.6755	42.60	9.70	52.30	56.00	-3.70	QP	
8		1.6755	28.94	9.70	38.64	46.00	-7.36	AVG	
9		2.9625	39.88	9.72	49.60	56.00	-6.40	QP	
10		2.9625	24.36	9.72	34.08	46.00	-11.92	AVG	
11		4.2360	39.90	9.73	49.63	56.00	-6.37	QP	
12		4.2360	26.47	9.73	36.20	46.00	-9.80	AVG	

3.2 RADIATED EMISSION MEASUREMENT

3.2.1 RADIATED EMISSION LIMITS (Frequency Range 9kHz-1000MHz)

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

FREQUENCY (MHz)	Limit (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

(1) The limit for radiated test was performed according to FCC PART 15C.

(2) The tighter limit applies at the band edges.

(3) Emission level (dBuV/m)=20log Emission level (uV/m).

FREQUENCY RANGE OF RADIATED MEASUREMENT (For unintentional radiators)

Highest frequency generated or Upper frequency of measurement used in the device or on which the device operates or tunes (MHz)	Range (MHz)
Below 1.705	30
1.705 – 108	1000
108 – 500	2000
500 – 1000	5000
Above 1000	5th harmonic of the highest frequency or 40 GHz, whichever is lower

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

3.2.2 TEST PROCEDURE

a. The measuring distance of at 3 m shall be used for measurements at frequency up to 25GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
b. The EUT was placed on the top of a rotating table 0.8 and 1.5 meters above the ground at a 3 meter semi-chamber test. The table was rotated 360 degrees to determine the position of the highest radiation.
c. The height of the equipment or of the substitution antenna shall be 0.8 m; above 1GHz, the height was 1.5m, the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
d. The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
e. If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
f. For the actual test configuration, please refer to the related Item –EUT Test Photos.
g. For the radiated emission test above 1GHz:
Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response.
The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
Note:
Both horizontal and vertical antenna polarities were tested
and performed pretest to three orthogonal axis. The worst case emissions were reported

3.2.3 DEVIATION FROM TEST STANDARD

No deviation

3.2.4 TEST SETUP

（A）Radiated Emission Test-Up Frequency Below 30MHz



（B）Radiated Emission Test-Up Frequency 30MHz~1GHz



（C）Radiated Emission Test-Up Frequency Above 1GHz



3.2.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

3.2.6 TEST RESULTS

Radiated Spurious Emission (Below 30MHz)

Temperature :	20 ℃	Relative Humidity :	48%
Pressure :	1010 hPa	Polarization :	---
Test Voltage :	AC 120V/60Hz		
Test Mode :	Link Mode		

Freq.	Reading	Limit	Margin	State
(MHz)	(dBuV/m)	(dBuV/m)	(dB)	P/F
--	--	--	--	PASS
--	--	--	--	PASS

NOTE:
The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.
Distance extrapolation factor =40 log (specific distance/test distance)(dB);
Limit line = specific limits(dBuv) + distance extrapolation factor.
Correct Factor=Antenna Factor + Cable Loss – Pre-amplifier.

Radiated Spurious Emission (Between 30MHz – 1GHz)

Temperature :	26 ℃	Relative Humidity :	54%
Pressure :	1010 hPa	Polarization :	Horizontal
Test Voltage :	AC120V/60Hz		
Test Mode : (Worst)	Link Mode		



Remark:
Factor = Antenna Factor + Cable Loss – Pre-amplifier.

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dB/m	dB	Detector
1		52.9453	29.69	-14.43	15.26	40.00	-24.74	QP
2		86.5029	49.64	-18.20	31.44	40.00	-8.56	QP
3	*	147.4036	56.76	-19.10	37.66	43.50	-5.84	QP
4		180.0165	53.02	-18.08	34.94	43.50	-8.56	QP
5		264.7457	48.52	-14.97	33.55	46.00	-12.45	QP
6		576.6443	23.86	-7.05	16.81	46.00	-29.19	QP

Temperature :	26 ℃	Relative Humidity :	54%
Pressure :	1010 hPa	Polarization :	Vertical
Test Voltage :	AC120V/60Hz		
Test Mode : (Worst)	Link Mode		



Remark:
Factor = Antenna Factor + Cable Loss – Pre-amplifier.

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dB/m	dB	Detector
1		36.2541	43.25	-16.04	27.21	40.00	-12.79	QP
2	*	86.5029	53.60	-18.20	35.40	40.00	-4.60	QP
3		142.3243	56.54	-19.34	37.20	43.50	-6.30	QP
4		178.7584	55.47	-18.14	37.33	43.50	-6.17	QP
5		262.8955	39.68	-14.99	24.69	46.00	-21.31	QP
6		627.2738	25.90	-6.50	19.40	46.00	-26.60	QP

Radiated Spurious Emission (1GHz to 10th harmonics)

GFSK

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB/m)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
Low Channel 2402MHz									
V	2402.00	101.83	38.11	7.42	20.36	91.34	114	-22.66	PK
V	2402.00	86.25	38.11	7.42	20.36	75.76	94	-18.24	AV
V	4804.00	54.37	38.65	7.80	23.61	46.87	74	-27.13	PK
V	4804.00	41.61	38.65	7.80	23.61	34.11	54	-19.89	AV
V	17850.00	43.48	38.75	10.36	26.57	41.66	74	-32.34	PK
H	2402.00	102.97	38.11	7.44	20.36	92.48	114	-21.52	PK
H	2402.00	84.64	38.11	7.44	20.36	74.15	94	-19.85	AV
H	4804.00	55.55	38.65	7.80	23.61	48.05	74	-25.95	PK
H	4804.00	42.38	38.65	7.80	23.61	34.88	54	-19.12	AV
H	17850.00	43.86	38.75	10.36	26.57	42.04	74	-31.96	PK
Middle Channel 2440MHz									
V	2440.00	102.46	38.11	7.44	20.36	92.15	114	-21.85	PK
V	2440.00	85.95	38.11	7.44	20.36	75.64	94	-18.36	AV
V	4880.00	53.29	38.65	7.80	23.61	46.05	74	-27.95	PK
V	4880.00	44.57	38.65	7.80	23.61	37.33	54	-16.67	AV
V	17850.00	44.60	38.75	10.36	26.57	42.78	74	-31.22	PK
H	2440.00	101.42	38.11	7.44	20.36	91.11	114	-22.89	PK
H	2440.00	88.04	38.11	7.44	20.36	77.73	94	-16.27	AV
H	4880.00	56.19	38.65	7.80	23.61	48.95	74	-25.05	PK
H	4880.00	43.51	38.65	7.80	23.61	36.27	54	-17.73	AV
H	17850.00	42.89	38.75	10.36	26.57	41.07	74	-32.93	PK
High Channel 2480MHz									
V	2480.00	101.24	38.17	7.47	20.51	91.05	114	-22.95	PK
V	2480.00	90.46	38.17	7.47	20.51	80.27	94	-13.73	AV
V	4960.00	55.47	38.69	7.83	23.83	48.44	74	-25.56	PK
V	4960.00	43.42	38.69	7.83	23.83	36.39	54	-17.61	AV
V	17850.00	43.83	38.75	10.36	26.57	42.01	74	-31.99	PK
H	2480.00	104.00	38.17	7.47	20.51	93.81	114	-20.19	PK
H	2480.00	95.63	38.17	7.47	20.51	85.44	94	-8.56	AV
H	4960.00	54.18	38.69	7.83	23.83	47.15	74	-26.85	PK
H	4960.00	43.12	38.69	7.83	23.83	36.09	54	-17.91	AV
H	17850.00	44.65	38.75	10.36	26.57	42.83	74	-31.17	PK

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
   Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

CONDUCTED EMISSION MEASUREMENT

GFSK

Low Channel 2402MHz





Middle Channel 2440MHz





High Channel 2480MHz





4. BANDWIDTH TEST

4.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.249) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.249	Bandwidth	(20dB bandwidth)	2400-2483.5	PASS

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	> Measurement Bandwidth or Channel Separation
RB	100KHz
VB	≥RBW
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

4.1.1 TEST PROCEDURE

a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
b. Spectrum Setting : RBW= 100KHz, VBW≥ RBW, Sweep time = Auto.

4.1.2 DEVIATION FROM STANDARD

No deviation.

4.1.3 TEST SETUP



4.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

4.1.5 TEST RESULTS

Temperature :	25 ℃	Relative Humidity :	54%
Pressure :	1012 hPa	Test Voltage :	DC 3.7V
Test Mode :	CH01 / CH20 /CH40		

	Frequency	20dB Bandwidth (KHz)	Result
GFSK	2402 MHz	1909	**PASS**
	2440 MHz	1270	**PASS**
	2480 MHz	1262	**PASS**

GFSK

CH00



CH20


Agilent
R T
Freq/Channel
Ch Freq 2.44 GHz
Trig Free
Occupied Bandwidth
Center Freq
2.44000000 GHz
Start Freq
2.43850000 GHz
Ref 10 dBm
Atten 20 dB
#Peak
Log
10
dB/
Stop Freq
2.44150000 GHz
CF Step
300.000000 kHz
Auto Man
Center 2.44 GHz
Span 3 MHz
#Res BW 100 kHz
#VBW 300 kHz
Sweep 5 ms (401 pts)
Freq Offset
0.00000000 Hz
Occupied Bandwidth
1.2155 MHz
Occ BW % Pwr 99.00 %
x dB -20.00 dB
Signal Track
On Off
Transmit Freq Error -46.364 kHz
x dB Bandwidth 1.270 MHz

CH40


Agilent
R T
Freq/Channel
Ch Freq 2.48 GHz
Trig Free
Occupied Bandwidth
Center Freq
2.48000000 GHz
Start Freq
2.47850000 GHz
Ref 10 dBm
Atten 20 dB
#Peak
Log
10
dB/
Stop Freq
2.48150000 GHz
CF Step
300.000000 kHz
Auto Man
Center 2.48 GHz
Span 3 MHz
#Res BW 100 kHz
#VBW 300 kHz
Sweep 5 ms (401 pts)
Freq Offset
0.00000000 Hz
Occupied Bandwidth
1.1906 MHz
Occ BW % Pwr 99.00 %
x dB -20.00 dB
Signal Track
On Off
Transmit Freq Error 35.613 kHz
x dB Bandwidth 1.262 MHz

5. 100 KHZ BANDWIDTH OF FREQUENCY BAND EDGE

APPLICABLE STANDARD

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

TEST PROCEDURE

a) Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.

b) Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.

c) Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.

d) Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in §15.209, whichever is the lesser attenuation.

e) Repeat above procedures until all measured frequencies were complete.

Note:
Both horizontal and vertical antenna polarities were tested
and performed pretest to three orthogonal axis. The worst case emissions were reported

5.1 DEVIATION FROM STANDARD

No deviation.

5.2 TEST SETUP

5.3 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

5.4 TEST RESULTS

Temperature :	25 ℃	Relative Humidity :	54%
Pressure :	1012 hPa	Test Voltage :	DC 3.7V
Test Mode :	CH01/CH40		

	Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB/m)	Emission evel (dBuV/m)	Limits (dBuV/m)		Result
							PK	PK	AV	
GFSK	Low Channel 2402MHz									
	H	2390.00	40.31	38.06	7.42	20.15	35.82	74.00	54.00	PASS
	H	2400.00	42.77	38.06	7.42	20.15	37.28	74.00	54.00	PASS
	V	2390.00	40.95	38.06	7.42	20.15	36.46	74.00	54.00	PASS
	V	2400.00	39.60	38.06	7.42	20.15	35.13	74.00	54.00	PASS
	High Channel 2480MHz									
	H	2483.50	43.21	38.17	7.45	20.51	36.00	74.00	54.00	PASS
	H	2483.50	41.46	38.17	7.45	20.51	38.25	74.00	54.00	PASS
	V	2485.50	42.30	38.20	7.45	20.54	36.11	74.00	54.00	PASS
	V	2485.50	41.92	38.20	7.45	20.54	38.71	74.00	54.00	PASS

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier, Margin= Emission Level - Limit
2. If the PK measured levels comply with average limit, then the average level were deemed to comply with average limit.

2402 Horizontal



2402 Vertical



2480MHz Horizonta



2480MHz Vertical



6. ANTENNA REQUIREMENT

6.1 STANDARD REQUIREMENT

15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

6.2 EUT ANTENNA

The EUT antenna is PCB antenna. It complies with the standard requirement.

7. EUT TEST PHOTO

Conducted Measurement Photos



Radiated Measurement Photos





8. PHOTOS OF THE EUT



※※※※※ **END OF REPORT** ※※※※※