

TEST REPORT

Reference No...... : WTX23X08192268W002
FCC ID : 2ALLQ-STCB6421H
Applicant : Suta (Xiamen) Smart Technology Co. Ltd
Address : No. 37-1, Haijing Middle Road, Xiamen Area (Bonded Port Area), China
(Fujian) Pilot Free Trade Zone
Manufacturer : The same as Applicant
Address : The same as Applicant
Product Name : Control Box
Model No...... : STCB6-421H-31
Standards : FCC Part 15.249
Date of Receipt sample : 2023-08-31
Date of Test..... : 2023-08-31 to 2023-09-25
Date of Issue : 2023-09-25
Test Report Form No. : WTX_Part 15_249W
Test Result..... : **Pass**

Remarks:


The results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of approver.

Prepared By:

Waltek Testing Group (Shenzhen) Co., Ltd.

Address: 1/F., Room 101, Building 1, Hongwei Industrial Park, Liuxian 2nd Road,
Block 70 Bao'an District, Shenzhen, Guangdong, China
Tel.: +86-755-33663308 Fax.: +86-755-33663309 Email: sem@waltek.com.cn

Tested by:



Gala Wang

Approved by:



Silin Chen

TABLE OF CONTENTS

1. GENERAL INFORMATION	4
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
1.2 TEST STANDARDS.....	5
1.3 TEST METHODOLOGY	5
1.4 TEST FACILITY	5
1.5 EUT SETUP AND TEST MODE	6
1.6 MEASUREMENT UNCERTAINTY	8
1.7 TEST EQUIPMENT LIST AND DETAILS	9
2. SUMMARY OF TEST RESULTS.....	12
3. ANTENNA REQUIREMENTS	13
3.1 STANDARD APPLICABLE	13
3.2 TEST RESULT.....	13
4. RADIATED EMISSIONS	14
4.1 STANDARD APPLICABLE	14
4.2 TEST PROCEDURE	14
4.3 CORRECTED AMPLITUDE & MARGIN CALCULATION.....	17
4.4 SUMMARY OF TEST RESULTS/PLOTS.....	17
5. OUT OF BAND EMISSIONS	21
5.1 STANDARD APPLICABLE	21
5.2 TEST PROCEDURE	21
5.3 SUMMARY OF TEST RESULTS/PLOTS.....	21
6. EMISSION BANDWIDTH.....	26
6.1 STANDARD APPLICABLE	26
6.2 TEST PROCEDURE	26
6.3 SUMMARY OF TEST RESULTS/PLOTS.....	26
7. CONDUCTED EMISSIONS	28
7.1 TEST PROCEDURE	28
7.2 BASIC TEST SETUP BLOCK DIAGRAM	28
7.3 TEST RECEIVER SETUP	28
7.4 SUMMARY OF TEST RESULTS/PLOTS.....	28
APPENDIX PHOTOGRAPHS.....	31

Report version

Version No.	Date of issue	Description
Rev.00	2023-09-25	Original
/	/	/

1. GENERAL INFORMATION

1.1 Product Description for Equipment Under Test (EUT)

General Description of EUT	
Product Name:	Control Box
Trade Name:	SUTA
Model No.:	STCB6-421H-31
Adding Model(s):	/
Rated Voltage:	AC120V50Hz
Battery Capacity:	/
Power Adaptor Model:	/
Software Version:	V380.00.09
Hardware Version:	V1.2
<i>Note: The test data is gathered from a production sample, provided by the manufacturer.</i>	

Technical Characteristics of EUT	
Frequency Range:	2402-2481MHz
Max. Field Strength:	91.30dBuV/m
Modulation:	GFSK
Quantity of Channels:	75
Channel Separation:	/
Antenna Type:	PCB Antenna
Antenna Gain:	-1.61dBi
<i>Note: The Antenna Gain is provided by the customer and can affect the validity of results.</i>	

1.2 Test Standards

The tests were performed according to following standards:

FCC Rules Part 15.249: Operation within the bands 902-928MHz, 2400-2483.5MHz, 5725-5875MHz, and 24.0-24.25GHz.

ANSI C63.10-2013: American National Standard for Testing Unlicensed Wireless Devices.

Maintenance of compliance is the responsibility of the manufacturer. Any modification of the product, which results in lowering the emission, should be checked to ensure compliance has been maintained.

1.3 Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, The equipment under test (EUT) was configured to measure its highest possible emission level. The test modes were adapted accordingly in reference to the Operating Instructions.

1.4 Test Facility

Address of the test laboratory

Laboratory: Waltek Testing Group (Shenzhen) Co., Ltd.

Address: 1/F., Room 101, Building 1, Hongwei Industrial Park, Liuxian 2nd Road, Block 70 Bao'an District, Shenzhen, Guangdong, China

FCC – Registration No.: 125990

Waltek Testing Group (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files. The Designation Number is CN5010, and Test Firm Registration Number is 125990.

Industry Canada (IC) Registration No.: 11464A

The 3m Semi-anechoic chamber of Waltek Testing Group (Shenzhen) Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 11464A and the CAB identifier is CN0057.

1.5 EUT Setup and Test Mode

The EUT was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements. All testing shall be performed under maximum output power condition, and to measure its highest possible emissions level, more detailed description as follows:

Channel List							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2402	20	2422	39	2442	58	2462
2	2403	21	2423	40	2443	59	2463
3	2404	22	2424	41	2444	60	2465
4	2405	23	2425	42	2445	61	2466
5	2406	24	2426	43	2446	62	2467
6	2407	25	2427	44	2447	63	2468
7	2408	26	2428	45	2449	64	2469
8	2409	27	2429	46	2450	65	2470
9	2410	28	2430	47	2451	66	2471
10	2411	29	2431	48	2452	67	2472
11	2412	30	2433	49	2453	68	2473
12	2413	31	2434	50	2454	69	2474
13	2414	32	2435	51	2455	70	2475
14	2415	33	2436	52	2456	71	2476
15	2417	34	2437	53	2457	72	2477
16	2418	35	2438	54	2458	73	2478
17	2419	36	2439	55	2459	74	2479
18	2420	37	2440	56	2460	75	2481
19	2421	38	2441	57	2461		

Test Mode List		
Test Mode	Description	Remark
TM1	Low Channel	2402MHz
TM2	Middle Channel	2441MHz
TM3	High Channel	2481MHz

Test Conditions	
Temperature:	22~25 °C
Relative Humidity:	50~55 %.
ATM Pressure:	1019 mbar

EUT Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
AC Cable	1.3	Unshielded	Without Ferrite
DC Cable	3.5	Unshielded	Without Ferrite

Special Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
/	/	/	/

Auxiliary Equipment List and Details			
Description	Manufacturer	Model	Serial Number
AC/DC Adapter	/	GS05802900200B	/

1.6 Measurement Uncertainty

Measurement uncertainty		
Parameter	Conditions	Uncertainty
RF Output Power	Conducted	$\pm 0.42\text{dB}$
Occupied Bandwidth	Conducted	$\pm 1.5\%$
Conducted Spurious Emission	Conducted	$\pm 2.17\text{dB}$
Conducted Emissions	Conducted	9-150kHz $\pm 3.74\text{dB}$
		0.15-30MHz $\pm 3.34\text{dB}$
Transmitter Spurious Emissions	Radiated	30-200MHz $\pm 4.52\text{dB}$
		0.2-1GHz $\pm 5.56\text{dB}$
		1-6GHz $\pm 3.84\text{dB}$
		6-26GHz $\pm 3.92\text{dB}$

1.7 Test Equipment List and Details

Fixed asset Number	Description	Manufacturer	Model	Serial No.	Cal Date	Due. Date
WTXE1005 A1005	Spectrum Analyzer	Agilent	N9020A	US471401 02	2023-02-25	2024-02-24
WTXE1004 A1-001	Spectrum Analyzer	Rohde & Schwarz	FSP40	100612	2023-02-25	2024-02-24
WTXE1084 A1001	Spectrum Analyzer	Agilent	N9020A	MY543205 48	2023-02-25	2024-02-24
☐ Chamber A: Below 1GHz						
WTXE1005 A1003	Spectrum Analyzer	Rohde & Schwarz	FSP30	836079/03 5	2023-02-25	2024-02-24
WTXE1007 A1001	EMI Test Receiver	Rohde & Schwarz	ESVB	825471/00 5	2023-02-25	2024-02-24
WTXE1007 A1001	Amplifier	HP	8447F	2805A034 75	2023-02-25	2024-02-24
WTXE1010 A1007	Loop Antenna	Schwarz beck	FMZB 1516	9773	2021-03-20	2024-03-19
WTXE1010 A1006	Broadband Antenna	Schwarz beck	VULB9163	9163-333	2023-03-20	2026-03-19
☐ Chamber A: Above 1GHz						
WTXE1005 A1003	Spectrum Analyzer	Rohde & Schwarz	FSP30	836079/03 5	2023-02-25	2024-02-24
WTXE1007 A1001	EMI Test Receiver	Rohde & Schwarz	ESVB	825471/00 5	2023-02-25	2024-02-24
WTXE1065 A1001	Amplifier	C&D	PAP-1G18	14918	2023-02-25	2024-02-24
WTXE1010 A1005	Horn Antenna	ETS	3117	00086197	2021-03-19	2024-03-18
WTXE1010 A1010	DRG Horn Antenna	A.H. SYSTEMS	SAS-574	571	2021-03-19	2024-03-18
WTXE1003 A1001	Pre-amplifier	Schwarzbeck	BBV 9721	9721-031	2023-02-25	2024-02-24
WTXE1004 A1-001	Spectrum Analyzer	Rohde & Schwarz	FSP40	100612	2023-02-25	2024-02-24
☐ Chamber B:Below 1GHz						
WTXE1010 A1006	Trilog Broadband Antenna	Schwarz beck	VULB9163(B)	9163-635	2021-04-09	2024-04-08
WTXE1038 A1001	Amplifier	Agilent	8447D	2944A101 79	2023-02-25	2024-02-24

WTXE1001 A1002	EMI Test Receiver	Rohde & Schwarz	ESPI	101391	2023-02-25	2024-02-24
☒ Chamber C:Below 1GHz						
WTXE1093 A1001	EMI Test Receiver	Rohde & Schwarz	ESIB 26	100401	2023-02-25	2024-02-24
WTXE1010 A1013-1	Trilog Broadband Antenna	Schwarz beck	VULB 9168	1194	2021-05-28	2024-05-27
WTXE1010 A1007	Loop Antenna	Schwarz beck	FMZB 1516	9773	2021-03-20	2024-03-19
WTXE1007 A1002	Amplifier	HP	8447F	2944A038 69	2023-02-25	2024-02-24
☒ Chamber C: Above 1GHz						
WTXE1093 A1001	EMI Test Receiver	Rohde & Schwarz	ESIB 26	100401	2023-02-25	2024-02-24
WTXE1103 A1005	Horn Antenna	POAM	RTF-11A	LP228060 221	2023-03-10	2026-03-09
WTXE1103 A1006	Amplifier	Tonscend	TAP01018050	AP22E806 235	2023-02-25	2024-02-24
WTXE1010 A1010	DRG Horn Antenna	A.H. SYSTEMS	SAS-574	571	2021-03-19	2024-03-18
WTXE1003 A1001	Pre-amplifier	Schwarzbeck	BBV 9721	9721-031	2023-02-25	2024-02-24
☐ Conducted Room 1#						
WTXE1001 A1001	EMI Test Receiver	Rohde & Schwarz	ESPI	101611	2023-02-25	2024-02-24
WTXE1002 A1001	Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100911	2023-02-25	2024-02-24
WTXE1003 A1001	AC LISN	Schwarz beck	NSLK8126	8126-224	2023-02-25	2024-02-24
☒ Conducted Room 2#						
WTXE1001 A1004	EMI Test Receiver	Rohde & Schwarz	ESPI	101259	2023-02-25	2024-02-24
WTXE1003 A1003	LISN	Rohde & Schwarz	ENV 216	100097	2023-02-25	2024-02-24

Software List			
Description	Manufacturer	Model	Version
EMI Test Software (Radiated Emission)*	Farad	EZ-EMC	RA-03A1
EMI Test Software (Conducted Emission)*	Farad	EZ-EMC	RA-03A1

*Remark: indicates software version used in the compliance certification testing.

2. SUMMARY OF TEST RESULTS

FCC Rules	Description of Test Item	Result
§15.203	Antenna Requirement	Compliant
§15.205	Restricted Band of Operation	Compliant
§15.207(a)	Conducted Emission	Compliant
§15.209(a)(f)	Radiated Spurious Emissions	Compliant
§15.249(a)	Field Strength of Emissions	Compliant
§15.249(d)	Out of Band Emission	Compliant
§15.215(c)	Emission Bandwidth	Compliant

N/A: Not applicable.

3. Antenna Requirements

3.1 Standard Applicable

According to FCC Part 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

3.2 Test Result

This product has a PCB antenna, fulfill the requirement of this section.

4. Radiated Emissions

4.1 Standard Applicable

According to §15.249(a), the field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following:

Fundamental Frequency	Field strength of fundamental (milli-volts/meter)	Field strength of Harmonics (micro-volts/meter)
902-928MHz	50	500
2400-2483.5MHz	50	500
5725-5875MHz	50	500
24.0-24.25GHz	250	2500

(d) Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50dB below the level of the fundamental or to the general radiated emission limits in §15.209, whichever is the lesser attenuation.


The emission limit in this paragraph is based on measurement instrumentation employing an average detector. The provisions in §15.35 for limiting peak emissions apply. Spurious Radiated Emissions measurements starting below or at the lowest crystal frequency.

4.2 Test Procedure


The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.205 15.249(a) and FCC Part 15.209 Limit.

The external I/O cables were draped along the test table and formed a bundle 30 to 40cm long in the middle. The spacing between the peripherals was 10cm.


The test setup for emission measurement below 30MHz.



The test setup for emission measurement from 30MHz to 1GHz.



The test setup for emission measurement above 1GHz.



Frequency :9kHz-30MHz
RBW=10KHz,
VBW =30KHz
Sweep time= Auto
Trace = max hold
Detector function = peak

Frequency :30MHz-1GHz
RBW=120KHz,
VBW=300KHz
Sweep time= Auto
Trace = max hold
Detector function = peak, QP

Frequency :Above 1GHz
RBW=1MHz,
VBW=3MHz(Peak), 10Hz(AV)
Sweep time= Auto
Trace = max hold
Detector function = peak, AV

4.3 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and the Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

$$\text{Corr. Ampl.} = \text{Indicated Reading} + \text{Ant. Factor} + \text{Cable Loss} - \text{Ampl. Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -6dB μ V means the emission is 6dB μ V below the maximum limit. The equation for margin calculation is as follows:


$$\text{Margin} = \text{Corr. Ampl.} - \text{FCC Part 15C Limit}$$

4.4 Summary of Test Results/Plots

Note: this EUT was tested in 3 orthogonal positions and the worst case position data was reported.


➤ Spurious Emissions Below 1GHz

Test Channel	Low(worst case)	Polarity:	Horizontal
--------------	-----------------	-----------	------------



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	51.8999	29.02	-8.29	20.73	40.00	-19.27	-	-	peak
2	75.3208	29.97	-11.94	18.03	40.00	-21.97	-	-	peak
3	148.9175	31.97	-8.68	23.29	43.50	-20.21	-	-	peak
4	222.2807	35.65	-11.97	23.68	46.00	-22.32	-	-	peak
5	274.4464	45.85	-9.13	36.72	46.00	-9.28	-	-	peak
6	611.4623	30.76	-1.59	29.17	46.00	-16.83	-	-	peak

Test Channel	Low(worst case)	Polarity:	Vertical
--------------	-----------------	-----------	----------



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	33.8067	35.64	-9.70	25.94	40.00	-14.06	-	-	peak
2	86.0796	35.61	-13.04	22.57	40.00	-17.43	-	-	peak
3	165.4716	33.02	-8.76	24.26	43.50	-19.24	-	-	peak
4	278.3308	41.92	-9.00	32.92	46.00	-13.08	-	-	peak
5	471.4665	34.24	-4.29	29.95	46.00	-16.05	-	-	peak
6	925.6132	32.24	1.74	33.98	46.00	-12.02	-	-	peak

Remark: '-'Means' the test Degree and Height are not recorded by the test software and only show the worst case in the test report.

Spurious Emissions Above 1GHz

Frequency	Reading	Correct	Result	Limit	Margin	Polar	Detector
(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	H/V	
Low Channel-2402MHz							
2402.00	90.15	1.15	91.30	114	-22.70	H	PK
2402.00	80.17	1.15	81.32	94	-12.68	H	AVG
4804.000	60.14	-6.13	54.01	74	-19.99	H	PK
7206.000	43.19	-6.13	37.06	74	-36.94	H	PK
2402.00	57.54	-1.64	55.9	114	-58.1	V	PK
2402.00	39.13	-1.64	37.49	94	-56.51	V	AVG
4804.498	56.52	-6.13	50.39	74	-23.61	V	PK
7206.000	41.38	-6.13	35.25	74	-38.75	V	PK
Middle Channel-2441MHz							
2441.00	87.03	-8.30	78.73	114	-35.27	H	PK
2441.00	86.59	-8.30	78.29	94	-15.71	H	AVG
4882.000	58.96	-6.13	52.83	74	-21.17	H	PK
7324.000	40.9	-6.13	34.77	74	-39.23	H	PK
2441.00	57.92	-1.64	56.28	114	-57.72	V	PK
2441.00	41.95	-1.64	40.31	94	-53.69	V	AVG
4882.000	55.49	-6.13	49.36	74	-24.64	V	PK
7324.000	40.03	-6.13	33.9	74	-40.1	V	PK
High Channel-2481MHz							
2481.00	84.07	1.32	85.39	114	-30.41	H	PK
2481.00	77.74	1.32	79.06	94	-14.94	H	AVG
4962.000	60.91	-6.13	54.78	74	-19.22	H	PK
7442.000	40.62	-6.13	34.49	74	-39.51	H	PK
2481.00	56.5	-1.64	54.86	114	-59.14	V	PK
2481.00	40.71	-1.64	39.07	94	-54.93	V	AVG
4962.000	57.22	-6.13	51.09	74	-22.91	V	PK
7444.000	40.73	-6.13	34.6	74	-39.4	V	PK

*Note: Testing is carried out with frequency rang 9kHz to the tenth harmonics, which above 5th Harmonics are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
The measurements greater than 20dB below the limit from 9kHz to 30MHz..*

5. Out of Band Emissions

5.1 Standard Applicable

Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50dB below the level of the fundamental or to the general radiated emission limits in §15.209, whichever is the lesser attenuation.

5.2 Test Procedure

As the radiation test, set the Lowest and Highest Transmitting Channel, observed the outside band of 2400MHz to 2483.5MHz, than mark the higher-level emission for comparing with the FCC rules.

5.3 Summary of Test Results/Plots


Test mode	Frequency	Limit	Result
	MHz	dBuV / dBc	
Lowest	2310.00	<54dBuV	Pass
	2390.00	<54dBuV	Pass
	2400.00	<54dBuV	Pass
Highest	2483.50	<54dBuV	Pass
	2500.00	<54dBuV	Pass

The edge emissions are below the FCC 15.209 Limits or complies with the 15.249 requirements.

Please refer to the test plots as below.


RBW: 1MHz; VBW: 3MHz

Test Channel	Low	Polarity:	Horizontal (worst case)
--------------	-----	-----------	-------------------------



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2310.000	44.04	0.98	45.02	54.00	-8.98	Ave Detector
	2310.000	57.36	0.98	58.34	74.00	-15.66	Peak Detector
2	2390.000	44.27	1.13	45.40	54.00	-8.60	Ave Detector
	2390.000	56.89	1.13	58.02	74.00	-15.98	Peak Detector
3	2401.984	82.03	1.15	83.18	94.00	-10.82	Ave Detector
	2402.184	84.42	1.15	85.57	114.00	-28.43	Peak Detector


Test Channel	High	Polarity:	Horizontal (worst case)
--------------	------	-----------	-------------------------



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2480.912	82.20	1.32	83.52	94.00	-10.48	Ave Detector
	2480.962	84.95	1.32	86.27	114.00	-27.8	Peak Detector
2	2483.500	48.63	1.32	49.95	54.00	-4.05	Ave Detector
	2483.500	64.71	1.32	66.03	74.00	-7.97	Peak Detector
3	2500.000	44.07	1.35	45.42	54.00	-8.58	Ave Detector
	2500.000	56.58	1.35	57.93	74.00	-16.07	Peak Detector


Band edge
RBW: 100kHz; VBW: 300kHz

Test Channel	Low	Polarity:	Horizontal (worst case)
--------------	-----	-----------	-------------------------



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2390.000	56.73	-18.87	37.86	54.00	-16.14	Ave Detector
	2390.000	56.17	-18.87	37.30	74.00	2390.000	Peak Detector
2	2401.784	109.53	-18.85	90.68	/	/	Ave Detector
	2401.784	109.56	-18.85	90.71	/	/	Peak Detector

Test Channel	High	Polarity:	Horizontal (worst case)
--------------	------	-----------	-------------------------



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2481.162	109.07	-18.68	90.39	/	/	Ave Detector
	2480.661	109.96	-18.68	91.28	/	/	Peak Detector
2	2483.500	70.08	-18.68	51.40	54.00	-2.60	Ave Detector
	2483.500	70.11	-18.68	51.43	74.00	-22.57	Peak Detector

6. Emission Bandwidth

6.1 Standard Applicable

According to 15.215(c), intentional radiators operating under the alternative provisions to the general emission limits, as contained in §§15.217 through 15.257 and in Subpart E of this part, must be designed to ensure that the 20dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated. The requirement to contain the designated bandwidth of the emission within the specified frequency band includes the effects from frequency sweeping, frequency hopping and other modulation techniques that may be employed as well as the frequency stability of the transmitter over expected variations in temperature and supply voltage. If a frequency stability is not specified in the regulations, it is recommended that the fundamental emission be kept within at least the central 80% of the permitted band in order to minimize the possibility of out-of-band operation.

6.2 Test Procedure

According to the ANSI 63.10-2013, the emission bandwidth test method as follows.

Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.

Set span = 1MHz, centered on a transmitting channel

RBW $\geq$ 1% 20dB Bandwidth, VBW $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold


All the trace to stabilize, use the marker-to-peak function to set the marker to the peak of the emission, use the marker-delta function to measure and record the 20dB down and 99% bandwidth of the emission.

6.3 Summary of Test Results/Plots

Test Channel	20dB Bandwidth(kHz)
Low Channel	1880
Middle Channel	1170
High Channel	870


Please refer to the following test plots:

Low Channel




Date: 25.SEP.2023 18:31:19

Middle Channel



Date: 25.SEP.2023 18:37:01

High Channel



Date: 25.SEP.2023 18:42:12


7. Conducted Emissions

7.1 Test Procedure

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 Limit.

The external I/O cables were draped along the test table and formed a bundle 30 to 40cm long in the middle. The spacing between the peripherals was 10cm.

7.2 Basic Test Setup Block Diagram




7.3 Test Receiver Setup

During the conducted emission test, the test receiver was set with the following configurations:

Start Frequency	150kHz
Stop Frequency	30MHz
Sweep Speed	Auto
IF Bandwidth.....	10kHz
Quasi-Peak Adapter Bandwidth	9kHz
Quasi-Peak Adapter Mode	Normal


7.4 Summary of Test Results/Plots

Test Mode	Communication	AC120V 60Hz	Polarity:	Neutral
-----------	---------------	-------------	-----------	---------



No.	Frequency	Limit dBuV	Level dBuV	Delta dB	Reading dBuV	Factor dB	Detector
1	170.000kHz	65.0	43.2	-21.8	33.5	9.7	QP
2	1.254MHz	56.0	29.2	-26.8	19.5	9.7	QP
3	8.586MHz	60.0	43.7	-16.3	33.8	9.9	QP
4	9.226MHz	60.0	35.3	-24.7	25.4	9.9	QP
5	13.918MHz	60.0	29.4	-30.6	19.6	9.8	QP
6	20.466MHz	60.0	16.6	-43.4	6.7	9.9	QP
7*	170.000kHz	55.0	29.2	-25.7	19.5	9.7	AV
8*	1.310MHz	46.0	24.4	-21.6	14.7	9.7	AV
9*	8.290MHz	50.0	37.0	-13.0	27.1	9.9	AV
10*	9.854MHz	50.0	34.8	-15.2	24.9	9.9	AV
11*	13.918MHz	50.0	31.9	-18.1	22.1	9.8	AV
12*	20.558MHz	50.0	18.3	-31.7	8.4	9.9	AV

Test Mode	Communication	AC120V 60Hz	Polarity:	Line
-----------	---------------	-------------	-----------	------



No.	Frequency	Limit dBuV	Level dBuV	Delta dB	Reading dBuV	Factor dB	Detector
1	166.000kHz	65.2	47.5	-17.6	37.7	9.8	QP
2	222.000kHz	62.7	37.3	-25.4	27.6	9.7	QP
3	390.000kHz	58.1	27.0	-31.1	17.1	9.9	QP
4	8.582MHz	60.0	44.6	-15.4	34.8	9.8	QP
5	9.842MHz	60.0	38.1	-21.9	28.3	9.8	QP
6	12.026MHz	60.0	38.7	-21.3	28.9	9.8	QP
7*	166.000kHz	55.2	37.5	-17.7	27.7	9.8	AV
8*	386.000kHz	48.1	38.5	-9.7	28.6	9.9	AV
9*	2.754MHz	46.0	21.6	-24.4	11.7	9.9	AV
10*	8.266MHz	50.0	40.2	-9.8	30.4	9.8	AV
11*	11.386MHz	50.0	38.8	-11.2	29.0	9.8	AV
12*	13.102MHz	50.0	31.0	-19.0	21.2	9.8	AV

APPENDIX PHOTOGRAPHS

Please refer to “ANNEX”

***** END OF REPORT *****