

**FCC 47 CFR PART 15 SUBPART C**

**CERTIFICATION TEST REPORT**

*For*

Photoelectric and Microwave Motion Sensor Switches

MODEL No.: BRI819

FCC ID: 2ALOD-BRI819

Trade Mark: N/A

REPORT NO.: ES170324020E

ISSUE DATE: April 17, 2017

*Prepared for*

NINGBO BRILLIANT ELECTRONICS CO.,LTD

401-1 Galilee Shipping Build No.177 Middle Tai'an Road,Yinzhou  
District,Ningbo,315100 China

*Prepared by*

EMTEK (SHENZHEN) CO., LTD

Bldg 69, Majialong Industry Zone, Nanshan District,  
Shenzhen, Guangdong, China

TEL: 86-755-26954280

FAX: 86-755-26954282

## TABLE OF CONTENTS

|          |                                                |           |
|----------|------------------------------------------------|-----------|
| <b>1</b> | <b>TEST RESULT CERTIFICATION .....</b>         | <b>3</b>  |
| <b>2</b> | <b>EUT TECHNICAL DESCRIPTION .....</b>         | <b>4</b>  |
| <b>3</b> | <b>SUMMARY OF TEST RESULT .....</b>            | <b>5</b>  |
| <b>4</b> | <b>TEST METHODOLOGY .....</b>                  | <b>6</b>  |
| 4.1      | GENERAL DESCRIPTION OF APPLIED STANDARDS ..... | 6         |
| 4.2      | MEASUREMENT EQUIPMENT USED .....               | 6         |
| 4.3      | DESCRIPTION OF TEST MODES .....                | 7         |
| <b>5</b> | <b>FACILITIES AND ACCREDITATIONS .....</b>     | <b>8</b>  |
| 5.1      | FACILITIES.....                                | 8         |
| 5.2      | LABORATORY ACCREDITATIONS AND LISTINGS .....   | 8         |
| <b>6</b> | <b>TEST SYSTEM UNCERTAINTY .....</b>           | <b>9</b>  |
| <b>7</b> | <b>SETUP OF EQUIPMENT UNDER TEST .....</b>     | <b>10</b> |
| 7.1      | RADIO FREQUENCY TEST SETUP 1.....              | 10        |
| 7.2      | RADIO FREQUENCY TEST SETUP 2.....              | 10        |
| 7.3      | CONDUCTED EMISSION TEST SETUP .....            | 12        |
| 7.4      | SUPPORT EQUIPMENT.....                         | 12        |
| <b>8</b> | <b>TEST REQUIREMENTS .....</b>                 | <b>13</b> |
| 8.1      | BANDWIDTH TEST .....                           | 13        |
| 8.2      | CONDUCTED EMISSIONS TEST .....                 | 15        |
| 8.3      | RADIATED SPURIOUS EMISSION .....               | 20        |
| 8.4      | BAND EDGES TEST .....                          | 28        |
| 8.5      | ANTENNA APPLICATION .....                      | 31        |

**1 TEST RESULT CERTIFICATION**

Applicant: NINGBO BRILLIANT ELECTRONICS CO.,LTD  
401-1 Galilee Shipping Build No.177 Middle Tai'an Road,Yinzhou  
District,Ningbo,315100 China

Manufacturer: NINGBO BRILLIANT ELECTRONICS CO.,LTD  
401-1 Galilee Shipping Build No.177 Middle Tai'an Road,Yinzhou  
District,Ningbo,315100 China

EUT Description: Photoelectric and Microwave Motion Sensor Switches

Model Number: BRI819

File Number: ES170324020E

Date of Test: March 22, 2017 to April 17, 2017

Measurement Procedure Used:

| APPLICABLE STANDARDS                                          |             |
|---------------------------------------------------------------|-------------|
| STANDARD                                                      | TEST RESULT |
| FCC 47 CFR Part 2, Subpart J<br>FCC 47 CFR Part 15, Subpart C | PASS        |

The above equipment was tested by EMTEK (SHENZHEN) CO., LTD. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.10 (2013) and the energy emitted by the sample EUT tested as described in this report is in compliance with the requirements of FCC Rules Part 2 and Part 15.249(2015)

The test results of this report relate only to the tested sample identified in this report.

Date of Test : March 22, 2017 to April 17, 2017

Prepared by :   
Joe Xia/Editor

Reviewer :   
Yaping Shen/Supervisor

Approve & Authorized Signer :   
Lisa Wang/Manager

## 2 EUT TECHNICAL DESCRIPTION

| Characteristics               | Description                                              |
|-------------------------------|----------------------------------------------------------|
| Device Type                   | 5.8GHz ISM Band                                          |
| Modulation:                   | Continuous Wave                                          |
| Operating Frequency Range(s): | 5824.00MHz                                               |
| Number of Channels:           | 1 channel                                                |
| Antenna Type :                | PCB Antenna                                              |
| Antenna Gain:                 | 0dBi                                                     |
| Power supply:                 | <input type="checkbox"/> DC supply:<br>Battery DC 3*1.5V |
|                               | <input checked="" type="checkbox"/> AC 120-277V 50/60Hz  |

**Note:** for more details, please refer to the User's manual of the EUT.

### 3 SUMMARY OF TEST RESULT

| FCC Part Clause                                                                                                                                                                                                                                                  | Test Parameter             | Verdict | Remark |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------|---------|--------|
| 15.207                                                                                                                                                                                                                                                           | Conducted Emission         | PASS    |        |
| 15.209                                                                                                                                                                                                                                                           | Radiated Emission          | PASS    |        |
| 15.249                                                                                                                                                                                                                                                           | Radiated Spurious Emission | PASS    |        |
| 15.249                                                                                                                                                                                                                                                           | Band edge test             | PASS    |        |
| 15.215(c)                                                                                                                                                                                                                                                        | 20dB Bandwidth             | PASS    |        |
| NOTE1: N/A (Not Applicable)<br>NOTE2: The report use radiated measurements in the restricted frequency bands. In addition, the radiated test is also performed to ensure the emissions emanating from the device cabinet also comply with the applicable limits. |                            |         |        |

#### RELATED SUBMITTAL(S) / GRANT(S):

This submittal(s) (test report) is intended for FCC ID: 2ALOD-BRI820 filing to comply with Section 15.249 of the FCC Part 15, Subpart C Rules.

## 4 TEST METHODOLOGY

### 4.1 GENERAL DESCRIPTION OF APPLIED STANDARDS

According to its specifications, the EUT must comply with the requirements of the following standards:  
FCC 47 CFR Part 2, Subpart J  
FCC 47 CFR Part 15, Subpart C

### 4.2 MEASUREMENT EQUIPMENT USED

#### 4.2.1 Conducted Emission Test Equipment

| EQUIPMENT TYPE     | MFR             | MODEL NUMBER | SERIAL NUMBER | LAST CAL.  |
|--------------------|-----------------|--------------|---------------|------------|
| Test Receiver      | Rohde & Schwarz | ESCS30       | 828985/018    | 05/28/2016 |
| L.I.S.N.           | Schwarzbeck     | NNLK8129     | 8129203       | 05/28/2016 |
| 50Ω Coaxial Switch | Anritsu         | MP59B        | M20531        | 05/29/2016 |
| Pulse Limiter      | Rohde & Schwarz | ESH3-Z2      | 100006        | 05/29/2016 |
| Voltage Probe      | Rohde & Schwarz | TK9416       | N/A           | 05/29/2016 |
| I.S.N              | Rohde & Schwarz | ENY22        | 1109.9508.02  | 05/29/2016 |

#### 4.2.2 Radiated Emission Test Equipment

| EQUIPMENT TYPE    | MFR             | MODEL NUMBER | SERIAL NUMBER | LAST CAL.  |
|-------------------|-----------------|--------------|---------------|------------|
| EMI Test Receiver | Rohde & Schwarz | ESU          | 1302.6005.26  | 05/29/2016 |
| Pre-Amplifier     | HP              | 8447D        | 2944A07999    | 05/28/2016 |
| Bilog Antenna     | Schwarzbeck     | VULB9163     | 142           | 05/28/2016 |
| Loop Antenna      | ARA             | PLA-1030/B   | 1029          | 05/28/2016 |
| Horn Antenna      | Schwarzbeck     | BBHA 9170    | BBHA9170399   | 05/28/2016 |
| Horn Antenna      | Schwarzbeck     | BBHA 9120    | D143          | 05/28/2016 |
| Cable             | Schwarzbeck     | AK9513       | ACRX1         | 05/29/2016 |
| Cable             | Rosenberger     | N/A          | FP2RX2        | 05/29/2016 |
| Cable             | Schwarzbeck     | AK9513       | CRPX1         | 05/29/2016 |
| Cable             | Schwarzbeck     | AK9513       | CRRX2         | 05/29/2016 |

#### 4.2.3 Radio Frequency Test Equipment

| EQUIPMENT TYPE    | MFR     | MODEL NUMBER | SERIAL NUMBER | LAST CAL.  |
|-------------------|---------|--------------|---------------|------------|
| Spectrum Analyzer | Agilent | E4407B       | 88156318      | 05/28/2016 |
| Signal Analyzer   | Agilent | N9010A       | My53470879    | 05/28/2016 |
| Power meter       | Anritsu | ML2495A      | 0824006       | 05/28/2016 |
| Power sensor      | Anritsu | MA2411B      | 0738172       | 05/28/2016 |

**Remark:** Each piece of equipment is scheduled for calibration once a year.

#### 4.3 DESCRIPTION OF TEST MODES

The EUT has been tested under its typical operating condition.

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

The Transmitter was operated in the normal operating mode. The TX frequency was fixed which was for the purpose of the measurements.

Those modulation Continuous Wave were used for test.

Pre-defined engineering program for regulatory testing used to control the EUT for staying in continuous transmitting and receiving mode is programmed.

☒ Frequency and Channel list:

| Channel | Frequency<br>(MHz) |
|---------|--------------------|
| 1       | 5824.00            |

## 5 FACILITIES AND ACCREDITATIONS

### 5.1 FACILITIES

All measurement facilities used to collect the measurement data are located at

Bldg 69, Majialong Industry Zone District, Nanshan District, Shenzhen, China

The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.10 and CISPR Publication 22.

### 5.2 LABORATORY ACCREDITATIONS AND LISTINGS

Site Description

EMC Lab.

: Accredited by CNAS, 2013.10.29

The certificate is valid until 2016.10.28

The Laboratory has been assessed and proved to be in compliance with CNAS-CL01:2006 (identical to ISO/IEC 17025:2005)

The Certificate Registration Number is L2291.

Accredited by TUV Rheinland Shenzhen 2015.4

The Laboratory has been assessed according to the requirements ISO/IEC 17025.

Accredited by FCC, April 17, 2013

The Certificate Registration Number is 709623.

Accredited by FCC, July 24, 2013

The Certificate Registration Number is 406365.

Accredited by Industry Canada, November 29, 2012

The Certificate Registration Number is 4480A.

Name of Firm

: EMTEK (SHENZHEN) CO., LTD.

Site Location

: Bldg 69, Majialong Industry Zone,  
Nanshan District, Shenzhen, Guangdong, China

## 6 TEST SYSTEM UNCERTAINTY

The following measurement uncertainty levels have been estimated for tests performed on the apparatus:


| Parameter                      | Uncertainty               |
|--------------------------------|---------------------------|
| Radio Frequency                | $\pm 1 \times 10^{-5}$    |
| Maximum Peak Output Power Test | $\pm 1.0\text{dB}$        |
| Conducted Emissions Test       | $\pm 2.0\text{dB}$        |
| Radiated Emission Test         | $\pm 2.0\text{dB}$        |
| Power Density                  | $\pm 2.0\text{dB}$        |
| Occupied Bandwidth Test        | $\pm 1.0\text{dB}$        |
| Band Edge Test                 | $\pm 3\text{dB}$          |
| All emission, radiated         | $\pm 3\text{dB}$          |
| Antenna Port Emission          | $\pm 3\text{dB}$          |
| Temperature                    | $\pm 0.5^{\circ}\text{C}$ |
| Humidity                       | $\pm 3\%$                 |

Measurement Uncertainty for a level of Confidence of 95%

## 7 SETUP OF EQUIPMENT UNDER TEST

### 7.1 RADIO FREQUENCY TEST SETUP 1

The WLAN component's antenna ports(s) of the EUT are connected to the measurement instrument per an appropriate attenuator. The EUT is controlled by PC/software to emit the specified signals for the purpose of measurements.



### 7.2 RADIO FREQUENCY TEST SETUP 2

The test site semi-anechoic chamber has met the requirement of NSA tolerance 4 dB according to the standards: ANSI C63.10. The test distance is 3m. The setup is according to the requirements in Section 13.1.4.1 of ANSI C63.10-2013 and CAN/CSA-CEI/IEC CISPR 22.

Below 30MHz:

The EUT is placed on a turntable 0.8 meters above the ground in the chamber, 3 meter away from the antenna (loop antenna). The Antenna should be positioned with its plane vertical at the specified distance from the EUT and rotated about its vertical axis for maximum response at each azimuth about the EUT. The center of the loop shall be 1 m above the ground. For certain applications, the loop antenna plane may also need to be positioned horizontally at the specified distance from the EUT.

Above 30MHz:


The EUT is placed on a turntable 0.8 meters above the ground in the chamber, 3 meter away from the antenna. The maximal emission value is acquired by adjusting the antenna height, polarisation and turntable azimuth. Normally, the height range of antenna is 1 m to 4 m, the azimuth range of turntable is 0° to 360°, and the receive antenna has two polarizations Vertical (V) and Horizontal (H).

Above 1GHz:


(Note: the FCC's permission to use 1.5m as an alternative per TCBC Conf call of Dec. 2, 2014.)

The EUT is placed on a turntable 1.5 meters above the ground in the chamber, 3 meter away from the antenna. The maximal emission value is acquired by adjusting the antenna height, polarisation and turntable azimuth. Normally, the height range of antenna is 1 m to 4 m, the azimuth range of turntable is 0° to 360°, and the receive antenna has two polarizations Vertical (V) and Horizontal (H).


#### (a) Radiated Emission Test Set-Up, Frequency Below 30MHz



(b) Radiated Emission Test Set-Up, Frequency Below 1000MHz



(c) Radiated Emission Test Set-Up, Frequency above 1000MHz




### 7.3 CONDUCTED EMISSION TEST SETUP

The mains cable of the EUT (maybe per AC/DC Adapter) must be connected to LISN. The LISN shall be placed 0.8 m from the boundary of EUT and bonded to a ground reference plane for LISN mounted on top of the ground reference plane. This distance is between the closest points of the LISN and the EUT. All other units of the EUT and associated equipment shall be at least 0.8m from the LISN.

Ground connections, where required for safety purposes, shall be connected to the reference ground point of the LISN and, where not otherwise provided or specified by the manufacturer, shall be of same length as the mains cable and run parallel to the mains connection at a separation distance of not more than 0.8 m.

According to the requirements in Section 13.1.4.1 of ANSI C63.10-2013 Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30 MHz using CISPR Quasi-Peak and average detector mode.



### 7.4 SUPPORT EQUIPMENT

| Item | Equipment | Mfr/Brand | Model/Type No. | FCC ID | Series No. | Note |
|------|-----------|-----------|----------------|--------|------------|------|
| N/A  | N/A       | N/A       | N/A            | N/A    | N/A        | N/A  |


#### Notes:

1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.

## 8 TEST REQUIREMENTS

### 8.1 BANDWIDTH TEST

#### 8.1.1 Block Diagram of Test Setup



#### 8.1.2 Applicable Standard

According to FCC Part 15.215(c)

#### 8.1.3 Conformance Limit

Permitted band: 5725-5850 MHz

#### 8.1.4 Test Configuration

Test according to clause 7.1 radio frequency test setup 1

#### 8.1.5 Test Procedure

The EUT was operating in controlled its channel. Printed out the test result from the spectrum by hard copy function.

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.

Set to the maximum power setting and enable the EUT transmit continuously

Set RBW = 100 kHz.

Set the video bandwidth (VBW) =300 kHz.

Set Span=2 times OBW

Set Detector = Peak.

Set Trace mode = max hold.

Set Sweep = auto couple.

Allow the trace to stabilize.


Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 20 dB relative to the maximum level measured in the fundamental emission.

Measure and record the results in the test report.

#### 8.1.6 Test Results


|               |      |             |                |
|---------------|------|-------------|----------------|
| Temperature : | 25°C | Test Date : | April 14, 2017 |
| Humidity :    | 55 % | Test By:    | King Kong      |

| Operation Mode | 20dB bandwidth(MHz) | Permitted band (MHz) | Verdict |
|----------------|---------------------|----------------------|---------|
| TX             | 5823.5835-5823.7033 | 5725-5850            | PASS    |



## 8.2 CONDUCTED EMISSIONS TEST

### 8.2.1 Block Diagram of Test Setup



### 8.2.2 Applicable Standard

According to FCC Part 15.249 and 15.207

### 8.2.3 Conformance Limit

According to §15.207, For a Class A digital device that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50  $\mu$ H/50 ohms LISN. Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequency ranges.

| Frequency<br>(MHz)                                                                                                                                                          | Limit (dB $\mu$ V) |               |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------|---------------|
|                                                                                                                                                                             | Quasi-peak Level   | Average Level |
| 0.15 ~ 0.50                                                                                                                                                                 | 66.0 ~ 56.0 *      | 56.0 ~ 46.0 * |
| 0.50 ~ 5.00                                                                                                                                                                 | 56.0               | 46.0          |
| 5.00 ~ 30.00                                                                                                                                                                | 60.0               | 50.0          |
| NOTE1-The lower limit shall apply at the transition frequencies.<br>NOTE2-The limit decreases linearly with the logarithm of the frequency in the range 0.15MHz to 0.50MHz. |                    |               |

### 8.2.4 Test Configuration

Test according to clause 7.3 conducted emission test setup

### 8.2.5 Test Procedure

The EUT is put on the plane 0.8m high above the ground by insulating support and connected to the AC mains through Line Impedance Stability Network (L.I.S.N). This provided a 50ohm coupling impedance for the tested equipments. Both sides of AC line are investigated to find out the maximum conducted emission according to the FCC regulations during conducted emission measurement.

The bandwidth of the test receiver (R&S ESU) is set at 9KHz in 150KHz~30MHz and 200Hz in 9KHz~150KHz.


The frequency range from 150kHz to 30MHz is investigated.

### 8.2.6 Test Results

**PASS.**

Please refer to the following pages.

**Test Data:**




Site site #1  
Limit: (CE)FCC PART 15 class B\_QP  
EUT: Photoelectric and Microwave Motion  
M/N: BRI819  
Mode: ON  
Note:

Phase: **N** Temperature: 21  
Power: AC 120V/60Hz Humidity: 42 %

| No. Mk. | Freq.   | Reading Level | Correct Factor | Measure-ment | Limit | Over   |          |         |
|---------|---------|---------------|----------------|--------------|-------|--------|----------|---------|
|         | MHz     | dBuV          | dB             | dBuV         | dBuV  | dB     | Detector | Comment |
| 1       | 0.1780  | 41.70         | 10.09          | 51.79        | 64.58 | -12.79 | QP       |         |
| 2       | 0.1780  | 9.10          | 10.09          | 19.19        | 54.58 | -35.39 | AVG      |         |
| 3       | 0.1940  | 41.10         | 10.09          | 51.19        | 63.86 | -12.67 | QP       |         |
| 4       | 0.1940  | 9.60          | 10.09          | 19.69        | 53.86 | -34.17 | AVG      |         |
| 5 *     | 0.1965  | 41.10         | 10.09          | 51.19        | 63.76 | -12.57 | QP       |         |
| 6       | 0.1965  | 8.90          | 10.09          | 18.99        | 53.76 | -34.77 | AVG      |         |
| 7       | 17.4280 | 32.40         | 10.58          | 42.98        | 60.00 | -17.02 | QP       |         |
| 8       | 17.4280 | 24.00         | 10.58          | 34.58        | 50.00 | -15.42 | AVG      |         |
| 9       | 17.9160 | 33.90         | 10.58          | 44.48        | 60.00 | -15.52 | QP       |         |
| 10      | 17.9160 | 25.00         | 10.58          | 35.58        | 50.00 | -14.42 | AVG      |         |
| 11      | 18.3760 | 33.30         | 10.59          | 43.89        | 60.00 | -16.11 | QP       |         |
| 12      | 18.3760 | 24.70         | 10.59          | 35.29        | 50.00 | -14.71 | AVG      |         |

\*:Maximum data x:Over limit !:over margin Comment: Factor build in receiver. Operator: Moses




Site site #1  
 Limit: (CE)FCC PART 15 class B\_QP  
 EUT: Photoelectric and Microwave Motion  
 M/N: BRI819  
 Mode: ON  
 Note:

Phase: **L1**  
 Power: AC 120V/60Hz  
 Temperature: 21  
 Humidity: 42 %

| No. | Mk. | Freq.   | Reading | Correct | Measure- | Limit | Over   |          |         |
|-----|-----|---------|---------|---------|----------|-------|--------|----------|---------|
|     |     | MHz     | Level   | Factor  | ment     |       |        | Detector | Comment |
|     |     |         | dBuV    | dB      | dBuV     | dBuV  | dB     |          |         |
| 1   |     | 0.1740  | 36.20   | 10.09   | 46.29    | 64.77 | -18.48 | QP       |         |
| 2   |     | 0.1740  | 6.40    | 10.09   | 16.49    | 54.77 | -38.28 | AVG      |         |
| 3   | *   | 0.1860  | 40.20   | 10.09   | 50.29    | 64.21 | -13.92 | QP       |         |
| 4   |     | 0.1860  | 9.70    | 10.09   | 19.79    | 54.21 | -34.42 | AVG      |         |
| 5   |     | 0.1940  | 36.90   | 10.09   | 46.99    | 63.86 | -16.87 | QP       |         |
| 6   |     | 0.1940  | 6.30    | 10.09   | 16.39    | 53.86 | -37.47 | AVG      |         |
| 7   |     | 17.3440 | 31.20   | 10.58   | 41.78    | 60.00 | -18.22 | QP       |         |
| 8   |     | 17.3440 | 22.30   | 10.58   | 32.88    | 50.00 | -17.12 | AVG      |         |
| 9   |     | 17.7720 | 32.60   | 10.58   | 43.18    | 60.00 | -16.82 | QP       |         |
| 10  |     | 17.7720 | 24.40   | 10.58   | 34.98    | 50.00 | -15.02 | AVG      |         |
| 11  |     | 18.2000 | 31.80   | 10.59   | 42.39    | 60.00 | -17.61 | QP       |         |
| 12  |     | 18.2000 | 22.50   | 10.59   | 33.09    | 50.00 | -16.91 | AVG      |         |

\*:Maximum data    x:Over limit    !:over margin    Comment: Factor build in receiver.    Operator: Moses




Site site #1  
 Limit: (CE)FCC PART 15 class B\_QP  
 EUT: Photoelectric and Microwave Motion  
 M/N: BRI819  
 Mode: ON  
 Note:

Phase: **L1**  
 Power: AC 277V/60Hz  
 Temperature: 21  
 Humidity: 42 %

| No. | Mk. | Freq.<br>MHz | Reading<br>Level<br>dBuV | Correct<br>Factor<br>dB | Measure-<br>ment<br>dBuV | Limit<br>dBuV | Over<br>dB | Detector | Comment |
|-----|-----|--------------|--------------------------|-------------------------|--------------------------|---------------|------------|----------|---------|
| 1   |     | 0.1780       | 37.00                    | 10.09                   | 47.09                    | 64.58         | -17.49     | QP       |         |
| 2   |     | 0.1780       | 4.20                     | 10.09                   | 14.29                    | 54.58         | -40.29     | AVG      |         |
| 3   |     | 0.2060       | 30.80                    | 10.09                   | 40.89                    | 63.37         | -22.48     | QP       |         |
| 4   |     | 0.2060       | 1.60                     | 10.09                   | 11.69                    | 53.37         | -41.68     | AVG      |         |
| 5   |     | 0.2820       | 32.50                    | 10.09                   | 42.59                    | 60.76         | -18.17     | QP       |         |
| 6   |     | 0.2820       | 3.60                     | 10.09                   | 13.69                    | 50.76         | -37.07     | AVG      |         |
| 7   |     | 17.3880      | 32.70                    | 10.58                   | 43.28                    | 60.00         | -16.72     | QP       |         |
| 8   |     | 17.3880      | 23.90                    | 10.58                   | 34.48                    | 50.00         | -15.52     | AVG      |         |
| 9   |     | 17.8840      | 33.10                    | 10.58                   | 43.68                    | 60.00         | -16.32     | QP       |         |
| 10  | *   | 17.8840      | 25.10                    | 10.58                   | 35.68                    | 50.00         | -14.32     | AVG      |         |
| 11  |     | 18.4040      | 32.70                    | 10.59                   | 43.29                    | 60.00         | -16.71     | QP       |         |
| 12  |     | 18.4040      | 24.40                    | 10.59                   | 34.99                    | 50.00         | -15.01     | AVG      |         |

\*:Maximum data    x:Over limit    !:over margin    Comment: Factor build in receiver.    Operator: Moses



Site site #1 Phase: **N** Temperature: 21  
Limit: (CE)FCC PART 15 class B\_QP Power: AC 277V/60Hz Humidity: 42 %  
EUT: Photoelectric and Microwave Motion  
M/N: BRI819  
Mode: ON  
Note:

| No. | Mk. | Freq.<br>MHz | Reading<br>Level<br>dBuV | Correct<br>Factor<br>dB | Measure-<br>ment<br>dBuV | Limit<br>dBuV | Over<br>dB | Detector | Comment |
|-----|-----|--------------|--------------------------|-------------------------|--------------------------|---------------|------------|----------|---------|
| 1   |     | 0.1780       | 38.70                    | 10.09                   | 48.79                    | 64.58         | -15.79     | QP       |         |
| 2   |     | 0.1780       | 6.50                     | 10.09                   | 16.59                    | 54.58         | -37.99     | AVG      |         |
| 3   |     | 0.5060       | 31.60                    | 10.07                   | 41.67                    | 56.00         | -14.33     | QP       |         |
| 4   |     | 0.5060       | 3.00                     | 10.07                   | 13.07                    | 46.00         | -32.93     | AVG      |         |
| 5   |     | 1.5860       | 26.30                    | 10.06                   | 36.36                    | 56.00         | -19.64     | QP       |         |
| 6   |     | 1.5860       | 2.90                     | 10.06                   | 12.96                    | 46.00         | -33.04     | AVG      |         |
| 7   |     | 17.3400      | 35.60                    | 10.58                   | 46.18                    | 60.00         | -13.82     | QP       |         |
| 8   |     | 17.3400      | 25.90                    | 10.58                   | 36.48                    | 50.00         | -13.52     | AVG      |         |
| 9   |     | 18.0200      | 36.50                    | 10.58                   | 47.08                    | 60.00         | -12.92     | QP       |         |
| 10  |     | 18.0200      | 27.20                    | 10.58                   | 37.78                    | 50.00         | -12.22     | AVG      |         |
| 11  |     | 18.3800      | 35.20                    | 10.59                   | 45.79                    | 60.00         | -14.21     | QP       |         |
| 12  | *   | 18.3800      | 27.60                    | 10.59                   | 38.19                    | 50.00         | -11.81     | AVG      |         |

\*:Maximum data x:Over limit !:over margin Comment: Factor build in receiver. Operator: Moses

### 8.3 RADIATED SPURIOUS EMISSION

#### 8.3.1 Block Diagram of Test Setup



#### 8.3.2 Applicable Standard

According to FCC Part 15.249 and 15.209

#### 8.3.3 Conformance Limit

According to FCC Part 15.249: radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209 (see §15.205(c)).

According to FCC Part 15.205, Restricted bands

| MHz               | MHz                 | MHz           | GHz         |
|-------------------|---------------------|---------------|-------------|
| 0.090-0.110       | 16.42-16.423        | 399.9-410     | 4.5-5.15    |
| 10.495-0.505      | 16.69475-16.69525   | 608-614       | 5.35-5.46   |
| 2.1735-2.1905     | 16.80425-16.80475   | 960-1240      | 7.25-7.75   |
| 4.125-4.128       | 25.5-25.67          | 1300-1427     | 8.025-8.5   |
| 4.17725-4.17775   | 37.5-38.25          | 1435-1626.5   | 9.0-9.2     |
| 4.20725-4.20775   | 73-74.6             | 1645.5-1646.5 | 9.3-9.5     |
| 6.215-6.218       | 74.8-75.2           | 1660-1710     | 10.6-12.7   |
| 6.26775-6.26825   | 123-138             | 2200-2300     | 14.47-14.5  |
| 8.291-8.294       | 149.9-150.05        | 2310-2390     | 15.35-16.2  |
| 8.362-8.366       | 156.52475-156.52525 | 2483.5-2500   | 17.7-21.4   |
| 8.37625-8.38675   | 156.7-156.9         | 2690-2900     | 22.01-23.12 |
| 8.41425-8.41475   | 162.0125-167.17     | 3260-3267     | 23.6-24.0   |
| 12.29-12.293      | 167.72-173.2        | 3332-3339     | 31.2-31.8   |
| 12.51975-12.52025 | 240-285             | 3345.8-3358   | 36.43-36.5  |
| 12.57675-12.57725 | 322-335.4           | 3600-4400     | (2)         |
| 13.36-13.41       |                     |               |             |

According to FCC Part 15.209, Except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

| Frequencies (MHz) | Field Strength (micorvolts/meter) | Measurement Distance (meters) |
|-------------------|-----------------------------------|-------------------------------|
| 0.009~0.490       | 2400/F(KHz)                       | 300                           |
| 0.490~1.705       | 24000/F(KHz)                      | 30                            |
| 1.705~30.0        | 30                                | 30                            |
| 30~88             | 100                               | 3                             |
| 88~216            | 150                               | 3                             |
| 216~960           | 200                               | 3                             |
| 960~1000          | 500                               | 3                             |

Remark :1. Emission level in dBuV/m=20 log (uV/m)

2. Measurement was performed at an antenna to the closed point of EUT distance of meters.

3. Distance extrapolation factor =40log(Specific distance/ test distance)( dB);

Limit line=Specific limits(dBuV) + distance extrapolation factor.

for the frequency ranges below 30 MHz, a narrower RBW is used for these ranges but the measured value should add a RBW correction factor (RBWCF) where RBWCF [dB] =10\*Ig(100 [kHz]/narrower RBW [kHz]). , the narrower RBW is 1 kHz and RBWCF is 20 dB for the frequency 9 kHz to 150 kHz, and the narrower RBW is 10 kHz and RBWCF is 10 dB for the frequency 150 kHz to 30 MHz.

Field strength of fundamental and Field strength of harmonics Limit:

| Fundamental frequency | Field strength of fundamental<br>(millivolts/meter) | Field strength of harmonics<br>(microvolts/meter) |
|-----------------------|-----------------------------------------------------|---------------------------------------------------|
| 902-928 MHz           | 50(94 dBV/m)                                        | 500(54 dBV/m)                                     |
| 2400-2483.5 MHz       | 50(94 dBV/m)                                        | 500(54 dBV/m)                                     |
| 5725-5875 MHz         | 50(94 dBV/m)                                        | 500(54 dBV/m)                                     |
| 24.0-24.25 GHz        | 250(108 dBV/m)                                      | 2500(68 dBV/m)                                    |

### 8.3.4 Test Configuration

Test according to clause 7.2 radio frequency test setup 2

### 8.3.5 Test Procedure

This test is required for any spurious emission that falls in a Restricted Band, as defined in Section 15.205. It must be performed with the highest gain of each type of antenna proposed for use with the EUT. Use the following spectrum analyzer settings:

For Above 1GHz:

The EUT was placed on a turn table which is 1.5m above ground plane.

Maximum procedure was performed on the highest emissions to ensure EUT compliance.

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz

VBW  $\geq$  RBW

Sweep = auto

Detector function = peak

Trace = max hold

For Below 1GHz:

The EUT was placed on a turn table which is 0.8m above ground plane.

Maximum procedure was performed on the highest emissions to ensure EUT compliance.

Span = wide enough to fully capture the emission being measured

RBW = 100 kHz for

VBW  $\geq$  RBW

Sweep = auto

Detector function = peak

Trace = max hold

For Below 30MHz:

The EUT was placed on a turn table which is 0.8m above ground plane.

Maximum procedure was performed on the highest emissions to ensure EUT compliance.

Span = wide enough to fully capture the emission being measured

RBW = 9kHz

VBW  $\geq$  RBW

Sweep = auto

Detector function = peak

Trace = max hold

For Below 150KHz:

The EUT was placed on a turn table which is 0.8m above ground plane.

Maximum procedure was performed on the highest emissions to ensure EUT compliance.

Span = wide enough to fully capture the emission being measured

RBW = 200Hz

VBW  $\geq$  RBW

Sweep = auto

Detector function = peak

Trace = max hold

Follow the guidelines in ANSI C63.10-2013 with respect to maximizing the emission by rotating the EUT,

measuring the emission while the EUT is situated in three orthogonal planes (if appropriate), adjusting the measurement antenna height and polarization, etc. A pre-amp and a high pass filter are required for this test, in order to provide the measuring system with sufficient sensitivity. Allow the trace to stabilize. The peak reading of the emission, after being corrected by the antenna factor, cable loss, pre-amp gain, etc., is the peak field strength, which must comply with the limit specified in Section 15.35(b). Submit this data. Now set the VBW to 10 Hz, while maintaining all of the other instrument settings. This peak level, once corrected, must comply with the limit specified in Section 15.209. If the dwell time per channel of the hopping signal is less than 100 ms, then the reading obtained with the 10 Hz VBW may be further adjusted by a "duty cycle correction factor", derived from  $20\log(\text{dwell time}/100 \text{ ms})$ , in an effort to demonstrate compliance with the 15.209 limit. Submit this data. Repeat above procedures until all frequency measured was complete.

### 8.3.6 Test Results

#### ■ Spurious Emission below 30MHz (9KHz to 30MHz)

|              |         |            |                |
|--------------|---------|------------|----------------|
| Temperature: | 24°C    | Test Date: | April 14, 2017 |
| Humidity:    | 53 %    | Test By:   | King Kong      |
| Test mode:   | TX Mode |            |                |


| Freq.<br>(MHz) | Ant.Pol.<br>H/V | Emission<br>Level(dBuV/m) |    | Limit 3m(dBuV/m) |    | Over(dB) |    |
|----------------|-----------------|---------------------------|----|------------------|----|----------|----|
|                |                 | PK                        | AV | PK               | AV | PK       | AV |
| --             | --              | --                        | -- | --               | -- | --       | -- |

Note: the amplitude of spurious emission that is attenuated by more than 20dB below the permissible limit has no need to be reported.

Distance extrapolation factor =  $40\log(\text{Specific distance}/ \text{test distance})$  ( dB);

Limit line=Specific limits(dBuV) + distance extrapolation factor


■ Spurious Emission below 1GHz (30MHz to 1GHz)



| No. | Mk. | Freq.<br>MHz | Reading<br>Level<br>dBuV | Correct<br>Factor<br>dB | Measure-<br>ment<br>dBuV/m | Limit<br>dBuV/m | Over<br>dB | Antenna<br>Height<br>cm | Table<br>Degree | Detector | Comment |
|-----|-----|--------------|--------------------------|-------------------------|----------------------------|-----------------|------------|-------------------------|-----------------|----------|---------|
| 1   | *   | 30.9618      | 42.34                    | -23.84                  | 18.50                      | 40.00           | -21.50     |                         |                 | QP       |         |
| 2   |     | 48.5015      | 33.94                    | -19.74                  | 14.20                      | 40.00           | -25.80     |                         |                 | QP       |         |
| 3   |     | 103.4421     | 32.15                    | -21.15                  | 11.00                      | 43.50           | -32.50     |                         |                 | QP       |         |
| 4   |     | 194.4534     | 31.93                    | -21.73                  | 10.20                      | 43.50           | -33.30     |                         |                 | QP       |         |
| 5   |     | 345.5952     | 32.57                    | -17.97                  | 14.60                      | 46.00           | -31.40     |                         |                 | QP       |         |
| 6   |     | 574.6258     | 32.11                    | -11.81                  | 20.30                      | 46.00           | -25.70     |                         |                 | QP       |         |

\*:Maximum data    x:Over limit    !:over margin


Operator: LH



| No. | Mk. | Freq.<br>MHz | Reading<br>Level<br>dBuV | Correct<br>Factor<br>dB | Measure-<br>ment<br>dBuV/m | Limit<br>dBuV/m | Over<br>dB | Antenna<br>Height<br>cm | Table<br>Degree<br>degree | Comment |
|-----|-----|--------------|--------------------------|-------------------------|----------------------------|-----------------|------------|-------------------------|---------------------------|---------|
| 1   |     | 40.7016      | 32.83                    | -20.53                  | 12.30                      | 40.00           | -27.70     | QP                      |                           |         |
| 2   |     | 54.4515      | 32.46                    | -19.66                  | 12.80                      | 40.00           | -27.20     | QP                      |                           |         |
| 3   |     | 103.8054     | 32.37                    | -21.17                  | 11.20                      | 43.50           | -32.30     | QP                      |                           |         |
| 4   |     | 193.0944     | 32.48                    | -21.88                  | 10.60                      | 43.50           | -32.90     | QP                      |                           |         |
| 5   |     | 312.1794     | 34.54                    | -18.64                  | 15.90                      | 46.00           | -30.10     | QP                      |                           |         |
| 6   | *   | 593.0496     | 32.07                    | -12.17                  | 19.90                      | 46.00           | -26.10     | QP                      |                           |         |

\*:Maximum data x:Over limit !:over margin


Operator: LH



| No. | Mk. | Freq.<br>MHz | Reading<br>Level<br>dBuV | Correct<br>Factor<br>dB | Measure-<br>ment<br>dBuV/m | Limit<br>dBuV/m | Over<br>dB | Antenna<br>Height<br>cm | Table<br>Degree<br>degree | Comment |
|-----|-----|--------------|--------------------------|-------------------------|----------------------------|-----------------|------------|-------------------------|---------------------------|---------|
| 1   |     | 40.9880      | 32.47                    | -20.47                  | 12.00                      | 40.00           | -28.00     | QP                      |                           |         |
| 2   | *   | 48.3316      | 33.00                    | -19.80                  | 13.20                      | 40.00           | -26.80     | QP                      |                           |         |
| 3   |     | 55.2207      | 31.85                    | -19.85                  | 12.00                      | 40.00           | -28.00     | QP                      |                           |         |
| 4   |     | 104.1701     | 31.70                    | -21.20                  | 10.50                      | 43.50           | -33.00     | QP                      |                           |         |
| 5   |     | 173.8135     | 35.11                    | -24.91                  | 10.20                      | 43.50           | -33.30     | QP                      |                           |         |
| 6   |     | 468.8762     | 33.80                    | -16.40                  | 17.40                      | 46.00           | -28.60     | QP                      |                           |         |

\*:Maximum data x:Over limit !:over margin

Operator: LH



| No. | Mk. | Freq.<br>MHz | Reading<br>Level<br>dBuV | Correct<br>Factor<br>dB | Measure-<br>ment<br>dBuV/m | Limit<br>dBuV/m | Over<br>dB | Antenna<br>Height<br>cm | Table<br>Degree<br>degree | Comment |
|-----|-----|--------------|--------------------------|-------------------------|----------------------------|-----------------|------------|-------------------------|---------------------------|---------|
| 1   | *   | 31.1797      | 43.22                    | -23.72                  | 19.50                      | 40.00           | -20.50     | QP                      |                           |         |
| 2   |     | 49.3594      | 35.88                    | -19.48                  | 16.40                      | 40.00           | -23.60     | QP                      |                           |         |
| 3   |     | 104.1701     | 32.30                    | -21.20                  | 11.10                      | 43.50           | -32.40     | QP                      |                           |         |
| 4   |     | 199.2855     | 32.24                    | -22.44                  | 9.80                       | 43.50           | -33.70     | QP                      |                           |         |
| 5   |     | 283.9791     | 32.84                    | -19.24                  | 13.60                      | 46.00           | -32.40     | QP                      |                           |         |
| 6   |     | 640.6110     | 32.06                    | -12.36                  | 19.70                      | 46.00           | -26.30     | QP                      |                           |         |

\*:Maximum data x:Over limit !:over margin

Operator: LH

■ Spurious Emission Above 1GHz (1GHz to 40GHz)

|               |      |             |                |
|---------------|------|-------------|----------------|
| Temperature : | 25℃  | Test Date : | April 14, 2017 |
| Humidity :    | 55 % | Test By:    | King Kong      |

| Freq.<br>(MHz) | Ant.Pol.<br>H/V | Emission Level(dBuV/m) |       | Limit 3m(dBuV/m) |       | Over(dB) |        |
|----------------|-----------------|------------------------|-------|------------------|-------|----------|--------|
|                |                 | PK                     | AV    | PK               | AV    | PK       | AV     |
| 7205.000       | V               | 52.71                  | 36.30 | 74.00            | 54.00 | -21.29   | -17.70 |
| 16402.000      | V               | 53.81                  | 37.50 | 74.00            | 54.00 | -20.19   | -16.50 |
| 16844.000      | V               | 55.62                  | 38.50 | 74.00            | 54.00 | -18.38   | -15.50 |
| --             | --              | --                     | --    | --               | --    | --       | --     |
| --             | --              | --                     | --    | --               | --    | --       | --     |
| --             | --              | --                     | --    | --               | --    | --       | --     |
| 5454.000       | H               | 51.18                  | 35.00 | 74.00            | 54.00 | -22.82   | -19.00 |
| 9976.000       | H               | 52.02                  | 36.20 | 74.00            | 54.00 | -21.98   | -17.80 |
| 17456.000      | H               | 55.27                  | 39.40 | 74.00            | 54.00 | -18.73   | -14.60 |

**Note:** (1) All Readings are Peak Value (VBW=3MHz) and Peak Value (VBW=10Hz).  
(2) Emission Level= Reading Level+Probe Factor +Cable Loss.  
(3) Data of measurement within this frequency range shown “ -- ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

## **8.4 BAND EDGES TEST**

### **8.4.1 Applicable Standard**

According to 15.249(d), out band emission except for harmonics shall be comply with §15.209 or at least attenuated by 50 dB below the level of the fundamental.


### **8.4.2 Test Configuration**

Test according to clause 7.1 radio frequency test setup 1

### **8.4.3 Test Procedure**

Test according to clause 8.2.4


### **8.4.4 Test Results**



| No. | Mk. | Freq.    | Reading Level | Correct Factor | Measure-ment | Limit  | Over   | Antenna Height | Table Degree |         |
|-----|-----|----------|---------------|----------------|--------------|--------|--------|----------------|--------------|---------|
|     |     | MHz      | dBuV          | dB             | dBuV/m       | dBuV/m | dB     | cm             | degree       | Comment |
| 1   |     | 5686.700 | 47.31         | 1.85           | 49.16        | 74.00  | -24.84 | peak           |              |         |
| 2   |     | 5686.700 | 31.15         | 1.85           | 33.00        | 54.00  | -21.00 | AVG            |              |         |
| 3   |     | 5824.000 | 94.20         | 2.11           | 96.31        | 114.00 | -17.69 | peak           |              |         |
| 4   | *   | 5824.000 | 89.99         | 2.11           | 91.10        | 94.00  | -2.90  | AVG            |              |         |
| 5   |     | 5880.500 | 47.29         | 2.23           | 49.52        | 74.00  | -24.48 | peak           |              |         |
| 6   |     | 5880.500 | 30.37         | 2.23           | 32.60        | 54.00  | -21.40 | AVG            |              |         |

\*:Maximum data x:Over limit !:over margin

Operator: KK



| No. | Mk. | Freq.<br>MHz | Reading<br>Level<br>dBuV | Correct<br>Factor<br>dB | Measure-<br>ment<br>dBuV/m | Limit<br>dBuV/m | Over<br>dB | Antenna<br>Height<br>cm | Table<br>Degree | Comment |
|-----|-----|--------------|--------------------------|-------------------------|----------------------------|-----------------|------------|-------------------------|-----------------|---------|
| 1   |     | 5602.700     | 46.75                    | 1.68                    | 48.43                      | 74.00           | -25.57     | peak                    |                 |         |
| 2   |     | 5602.700     | 30.22                    | 1.68                    | 31.90                      | 54.00           | -22.10     | AVG                     |                 |         |
| 3   |     | 5824.000     | 89.64                    | 2.11                    | 91.75                      | 114.00          | -22.25     | peak                    |                 |         |
| 4   | *   | 5824.000     | 87.89                    | 2.11                    | 90.00                      | 94.00           | -4.00      | AVG                     |                 |         |
| 5   |     | 5862.200     | 45.45                    | 2.18                    | 47.63                      | 74.00           | -26.37     | peak                    |                 |         |
| 6   |     | 5862.200     | 28.42                    | 2.18                    | 30.60                      | 54.00           | -23.40     | AVG                     |                 |         |

\*:Maximum data    x:Over limit    !:over margin

Operator: KK

## 8.5 ANTENNA APPLICATION

### 8.5.1 Antenna Requirement

| Standard            | Requirement                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
|---------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| FCC CRF Part 15.203 | An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §15.211, §15.213, §15.217, §15.219, or §15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded. |

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

### 8.5.2 Result

PASS.

- Note:
- ☒ Antenna use a permanently attached antenna which is not replaceable.
  - ☐ Not using a standard antenna jack or electrical connector for antenna replacement
  - ☐ The antenna has to be professionally installed (please provide method of installation)

which in accordance to section 15.203, please refer to the internal photos.