

RF exposure Estimation

1. Introduction

Applicant: Chengdu Diyue Technology Co., Ltd.
Product: ZigBee wireless communication module
Model no.: SZU06A1, SZU06A2
FCC ID: 2ALOUSZU06A
Modulation: O-QPSK
Radio technology: IEEE 802.15.4
Operational Frequency: 2405MHz-2480MHz

2. Limit and Guidelines on Exposure to Electromagnetic Fields

According to §15.247(e)(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

According to KDB 447498 D01 Mobile Portable RF Exposure v05r02, no SAR required if power is lower than the flowing threshold:

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})]$

$[\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm according to 5) in section 4.1 is applied to determine SAR test exclusion.

3. Calculation method

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$

According the test report of 708881779707-00 clause 9.1 conducted peak output power:

Model	Max Gain (dBi)	Ch.	Freq. (MHz)	Peak Power (dBm)	Average Power (dBm)	Limit (dBm)
Zigbee	3.66	11	2405	6.10	5.96	30
	3.66	19	2445	6.29	5.11	30
	3.66	26	2480	6.40	6.26	30

Conducted Power + tune up tolerance = 4.40mW (6.40dBm)

Distance = 5 mm

$f = 2.480$ GHz

$[4.40/5] \cdot \text{SQRT}(2.480) = 1.39$

$1.39 \leq 3.0$

Therefore, excluded from SAR testing.