

FCC REPORT

Applicant: Chengdu Ebyte Electronic Technology Co., Ltd.

Address of Applicant: Innovation Center D347,4# XI-XIN road, High-tech district(west), Chengdu, Sichuan, China

Equipment Under Test (EUT)

Product Name: Wireless transceiver module

Model No.: E30

Trade Mark: EBYTE

FCC ID: 2ALPH-E30

Applicable standards: FCC CFR Title 47 Part 15 Subpart C Section 15.247

Date of sample receipt: 12 Mar., 2018

Date of Test: 12 Mar., to 27 Mar., 2018

Date of report issued: 28 Mar., 2018

Test Result: PASS *

* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:



Bruce Zhang
Laboratory Manager

This report details the results of the testing carried out on one sample. The results contained in this test report do not relate to other samples of the same product and does not permit the use of the CCIS product certification mark. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report.

This report may only be reproduced and distributed in full. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards.

This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

2 Version

Version No.	Date	Description
00	28 Mar., 2018	Original

Tested by:

YT Yang

Test Engineer

Date:

28 Mar., 2018

Reviewed by:

Wimer Zhang

Project Engineer

Date:

28 Mar., 2018

3 Contents

	Page
1 COVER PAGE.....	1
2 VERSION	2
3 CONTENTS	3
4 TEST SUMMARY.....	4
5 GENERAL INFORMATION.....	5
5.1 CLIENT INFORMATION.....	5
5.2 GENERAL DESCRIPTION OF E.U.T.....	5
5.3 TEST ENVIRONMENT AND MODE	6
5.4 DESCRIPTION OF SUPPORT UNITS.....	6
5.5 MEASUREMENT UNCERTAINTY.....	6
5.6 LABORATORY FACILITY.....	6
5.7 LABORATORY LOCATION	6
5.8 TEST INSTRUMENTS LIST.....	8
6 TEST RESULTS AND MEASUREMENT DATA	9
6.1 ANTENNA REQUIREMENT:	9
6.2 CONDUCTED OUTPUT POWER	10
6.3 OCCUPY BANDWIDTH	15
6.4 POWER SPECTRAL DENSITY	17
6.5 BAND EDGE	19
6.5.1 Conducted Emission Method.....	19
6.5.2 Radiated Emission Method.....	21
6.6 SPURIOUS EMISSION.....	27
6.6.1 Conducted Emission Method.....	27
6.6.2 Radiated Emission Method.....	29
7 TEST SETUP PHOTO	36
8 EUT CONSTRUCTIONAL DETAILS	37

4 Test Summary

Test Item	Section in CFR 47	Result
Antenna requirement	15.203 & 15.247 (c)	Pass
AC Power Line Conducted Emission	15.207	Pass
Conducted Peak Output Power	15.247 (b)(3)	Pass
6dB Emission Bandwidth 99% Occupied Bandwidth	15.247 (a)(2)	Pass
Power Spectral Density	15.247 (e)	Pass
Band Edge	15.247(d)	Pass
Spurious Emission	15.205 & 15.209	Pass
<i>Pass: The EUT complies with the essential requirements in the standard.</i>		
<i>N/A: N/A: Not Applicable.</i>		

5 General Information

5.1 Client Information

Applicant:	Chengdu Ebyte Electronic Technology Co., Ltd
Address:	Innovation Center D347,4# XI-XIN road, High-tech district(west),Chengdu, Sichuan, China
Manufacturer/Factor:	Chengdu Ebyte Electronic Technology Co., Ltd.
Address:	Innovation Center D347,4# XI-XIN road, High-tech district(west),Chengdu, Sichuan, China

5.2 General Description of E.U.T.

Product Name:	Wireless transceiver module
Model No.:	E30
Operation Frequency:	907 MHz~922.5 MHz
Channel numbers:	31
Modulation technology:	FSK
Antenna Type:	External Antenna
Antenna gain:	2.0dBi
Power supply:	DC 5V

Operation Frequency each of channel for FSK					
Channel	Frequency	Channel	Frequency	Channel	Frequency
0	907.0MHz	13	913.5MHz	26	920.0MHz
1	907.5MHz	14	914.0MHz	27	920.5MHz
2	908.0MHz	15	914.5MHz	28	921.0MHz
3	908.5MHz	16	915.0MHz	29	921.5MHz
4	909.0MHz	17	915.5MHz	30	922.0MHz
5	909.5MHz	18	916.0MHz	31	922.5MHz
6	910.0MHz	19	916.5MHz		
7	910.5MHz	20	917.0MHz		
8	911.0MHz	21	917.5MHz		
9	911.5MHz	22	918.0MHz		
10	912.0MHz	23	918.5MHz		
11	912.5MHz	24	919.0MHz		
12	913.0MHz	25	919.5MHz		
Remark: Channel 0, 16 & 49 selected for FSK.					

5.3 Test environment and mode

Operating Environment:	
Temperature:	24.0 °C
Humidity:	54 % RH
Atmospheric Pressure:	1010 mbar
Test mode:	
Operation mode	Keep the EUT in continuous transmitting with modulation
The sample was placed 0.8m(below 1GHz)/1.5m(above 1GHz) above the ground plane of 3m chamber. Measurements in both horizontal and vertical polarities were performed. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, rotating the turntable, varying antenna height from 1m to 4m in both horizontal and vertical polarizations. The emissions worst-case are shown in Test Results of the following pages. Duty cycle setting during the transmission is 100% with maximum power setting for all modulations.	

5.4 Description of Support Units

Manufacturer	Description	Model	S/N	FCC ID/DoC
LENOVO	Laptop	SL510	2847A65	DoC
EBYTE	Test suite	E25 D1	N/A	N/A
Sunshiny	Adapter	XS-1201000SCN	N/A	N/A

5.5 Measurement Uncertainty

Parameters	Expanded Uncertainty
Conducted Emission (9kHz ~ 30MHz)	2.14 dB (k=2)
Radiated Emission (9kHz ~ 30MHz)	4.24 dB (k=2)
Radiated Emission (30MHz ~ 1000MHz)	4.35 dB (k=2)
Radiated Emission (1GHz ~ 18GHz)	4.44 dB (k=2)
Radiated Emission (18GHz ~ 26.5GHz)	4.56 dB (k=2)

5.6 Laboratory Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **FCC - Registration No.: 727551**

Shenzhen Zhongjian Nanfang Testing Co., Ltd. has been accredited as a testing laboratory by FCC (Federal Communications Commission). The Registration No. is 727551.

- **IC - Registration No.: 10106A-1**

The 3m Semi-anechoic chamber of Shenzhen Zhongjian Nanfang Testing Co., Ltd. has been Registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 10106A-1.

- **CNAS - Registration No.: CNAS L6048**

Shenzhen Zhongjian Nanfang Testing Co., Ltd. is accredited to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration laboratories for the competence of testing. The Registration No. is CNAS L6048.

- **A2LA - Registration No.: 4346.01**

This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2005 General requirements for the competence of testing and calibration laboratories. The test scope can be found as below link: <https://portal.a2la.org/scopepdf/4346-01.pdf>

5.7 Laboratory Location

Shenzhen Zhongjian Nanfang Testing Co., Ltd.
Address: No. B-C, 1/F., Building 2, Laodong No.2 Industrial Park, Xixiang Road,
Bao'an District, Shenzhen, Guangdong, China
Tel: +86-755-23118282, Fax: +86-755-23116366

Email: info@ccis-cb.com, Website: <http://www.ccis-cb.com>


5.8 Test Instruments list

Radiated Emission:					
Test Equipment	Manufacturer	Model No.	Serial No.	Cal. Date (mm-dd-yy)	Cal. Due date (mm-dd-yy)
3m SAC	SAEMC	9m*6m*6m	966	07-22-2017	07-21-2020
BiConiLog Antenna	SCHWARZBECK	VULB9163	497	02-25-2018	02-24-2019
Horn Antenna	SCHWARZBECK	BBHA9120D	916	02-25-2018	02-24-2019
EMI Test Software	AUDIX	E3	6.110919b	N/A	N/A
Pre-amplifier	HP	8447D	2944A09358	03-07-2018	03-06-2019
Pre-amplifier	CD	PAP-1G18	11804	03-07-2018	03-06-2019
Spectrum analyzer	Rohde & Schwarz	FSP30	101454	03-07-2018	03-06-2019
EMI Test Receiver	Rohde & Schwarz	ESRP7	101070	03-07-2018	03-06-2019
Simulated Station	Anritsu	MT8820C	6201026545	03-07-2018	03-06-2019
Cable	ZDECL	Z108-NJ-NJ-81	1608458	03-07-2018	03-06-2019
Cable	MICRO-COAX	MFR64639	K10742-5	03-07-2018	03-06-2019
Cable	SUHNER	SUCOFLEX100	58193/4PE	03-07-2018	03-06-2019


Conducted Emission:					
Test Equipment	Manufacturer	Model No.	Serial No.	Cal. Date (mm-dd-yy)	Cal. Due date (mm-dd-yy)
EMI Test Receiver	Rohde & Schwarz	ESCI	101189	03-07-2018	03-06-2019
Pulse Limiter	SCHWARZBECK	OSRAM 2306	9731	03-07-2018	03-06-2019
LISN	CHASE	MN2050D	1447	02-25-2018	02-24-2019
LISN	Rohde & Schwarz	ESH3-Z5	8438621/010	07-21-2017	07-20-2018
ISN	Schwarzbeck	CAT3 8158	CCIS0185	02-25-2018	02-24-2019
ISN	Schwarzbeck	CAT5 8158	CCIS0186	02-25-2018	02-24-2019
ISN	Schwarzbeck	NTFM 8158	CCIS0187	02-25-2018	02-24-2019
Cable	HP	10503A	N/A	03-07-2018	03-06-2019
EMI Test Software	AUDIX	E3	6.110919b	N/A	N/A

6 Test results and Measurement Data

6.1 Antenna requirement:


Standard requirement:	FCC Part15 C Section 15.203 /247(c)
<i>15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.</i>	
E.U.T Antenna:	
<i>The antenna is an external antenna which cannot replace by end-user, the best case gain of the antenna is 2.0 dBi.</i>	
	

6.2 Conducted Emission

Test Requirement:	FCC Part 15 C Section 15.207		
Test Method:	ANSI C63.10: 2013		
Test Frequency Range:	150 kHz to 30 MHz		
Class / Severity:	Class B		
Receiver setup:	RBW=9kHz, VBW=30kHz		
Limit:	Frequency range (MHz)	Limit (dBuV)	
		Quasi-peak	Average
	0.15-0.5	66 to 56*	56 to 46*
	0.5-5	56	46
	5-30	60	50
* Decreases with the logarithm of the frequency.			
Test procedure	1. The E.U.T and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.), which provides a 50ohm/50uH coupling impedance for the measuring equipment. 2. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs). 3. Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.4: 2014 on conducted measurement.		
Test setup:	 <i>Remark:</i> E.U.T: Equipment Under Test LISN: Line Impedance Stabilization Network Test table height=0.8m		
Test Instruments:	Refer to section 5.8 for details		
Test mode:	Refer to section 5.3 for details		
Test results:	Passed		

Measurement Data:

Test Phase: Neutral



Trace: 3


Site : CCIS Shielding Room
 Condition : FCC PART15 B QP LISN(RS) NEUTRAL
 EUT : Wireless trans ceiver module
 Model : E30
 Test Mode : TX mode
 Power Rating : AC 120V/60Hz
 Environment : Temp: 23 °C Humi:56% Atmos:101KPa
 Test Engineer: YT
 Remark :

	Read	LISN	Cable	Limit	Over	
Freq	Level	Factor	Loss	Level	Line	Limit
MHz	dBuV	dB	dB	dBuV	dBuV	dB
1	0.162	36.83	0.70	10.77	48.30	65.34 -17.04 QP
2	0.162	19.52	0.70	10.77	30.99	55.34 -24.35 Average
3	0.170	32.26	0.70	10.77	43.73	64.94 -21.21 QP
4	0.186	16.67	0.66	10.76	28.09	54.20 -26.11 Average
5	0.211	15.28	0.66	10.76	26.70	53.18 -26.48 Average
6	0.230	28.42	0.66	10.75	39.83	62.44 -22.61 QP
7	0.529	30.79	0.61	10.76	42.16	56.00 -13.84 QP
8	0.529	17.57	0.61	10.76	28.94	46.00 -17.06 Average
9	0.641	34.02	0.63	10.77	45.42	56.00 -10.58 QP
10	0.647	21.06	0.63	10.77	32.46	46.00 -13.54 Average
11	1.456	22.21	0.67	10.92	33.80	46.00 -12.20 Average
12	1.472	36.65	0.67	10.92	48.24	56.00 -7.76 QP

Notes:

1. An initial pre-scan was performed on the live and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Final Level = Receiver Read level + LISN Factor + Cable Loss.

Test Phase: Line




Trace: 1
 Site : CCIS Shielding Room
 Condition : FCC PART15 B QP LISN(RS) LINE
 EUT : Wireless trans ceiver module
 Model : E30
 Test Mode : TX mode
 Power Rating : AC 120V/60Hz
 Environment : Temp: 23 °C Humi:56% Atmos:101KPa
 Test Engineer: YT
 Remark :

	Read	LISN	Cable	Level	Limit	Over	
Freq	Level	Factor	Loss	Level	Line	Limit	Remark
-----	-----	-----	-----	-----	-----	-----	-----
MHz	dBuV	dB	dB	dBuV	dBuV	dB	
1	0.158	39.79	0.71	10.77	51.27	65.56	-14.29 QP
2	0.182	36.13	0.73	10.77	47.63	64.42	-16.79 QP
3	0.186	21.22	0.73	10.76	32.71	54.20	-21.49 Average
4	0.202	33.30	0.73	10.76	44.79	63.54	-18.75 QP
5	0.211	19.75	0.73	10.76	31.24	53.18	-21.94 Average
6	0.513	22.35	0.76	10.76	33.87	46.00	-12.13 Average
7	0.570	34.51	0.76	10.76	46.03	56.00	-9.97 QP
8	0.621	38.80	0.77	10.77	50.34	56.00	-5.66 QP
9	0.627	23.79	0.77	10.77	35.33	46.00	-10.67 Average
10	1.088	19.24	0.78	10.88	30.90	46.00	-15.10 Average
11	1.411	17.46	0.78	10.91	29.15	46.00	-16.85 Average
12	1.418	35.20	0.78	10.92	46.90	56.00	-9.10 QP

Notes:

1. An initial pre-scan was performed on the live and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Final Level =Receiver Read level + LISN Factor + Cable Loss.


6.3 Conducted Output Power

Test Requirement:	FCC Part15 C Section 15.247 (b)(3)
Test Method:	ANSI C63.10:2013 and KDB 558074
Limit:	30dBm
Test setup:	 The diagram illustrates the test setup. A Spectrum Analyzer is connected to an E.U.T. (Equipment Under Test) via a red cable. Both the Spectrum Analyzer and the E.U.T. are placed on a Non-Conducted Table. The table is supported by two vertical legs and sits on a Ground Reference Plane.
Test Instruments:	Refer to section 5.8 for details
Test mode:	Refer to section 5.3 for details
Test results:	Passed


Measurement Data:

Test CH	Maximum Conducted Output Power (dBm)	Limit(dBm)	Result
Lowest	20.85	30.00	Pass
Middle	20.25		
Highest	20.22		

Test plot as follows:




6.4 Occupy Bandwidth

Test Requirement:	FCC Part15 C Section 15.247 (a)(2)
Test Method:	ANSI C63.10:2013 and KDB 558074
Limit:	>500kHz
Test setup:	 The diagram illustrates the test setup. A Spectrum Analyzer is connected to an E.U.T (Equipment Under Test) via a red cable. Both the Spectrum Analyzer and the E.U.T are placed on a Non-Conducted Table. Below the table is a Ground Reference Plane.
Test Instruments:	Refer to section 5.8 for details
Test mode:	Refer to section 5.3 for details
Test results:	Passed


Measurement Data:

Test CH	6dB Emission Bandwidth (MHz)	Limit(kHz)	Result
Lowest	0.796	>500	Pass
Middle	0.804		
Highest	0.792		
Test CH	99% Occupy Bandwidth (MHz)	Limit(kHz)	Result
Lowest	0.824	N/A	N/A
Middle	0.820		
Highest	0.820		

Test plot as follows:




6.5 Power Spectral Density

Test Requirement:	FCC Part15 C Section 15.247 (e)
Test Method:	ANSI C63.10:2013 and KDB558074 D01 DTS Meas Guidance v04
Limit:	8dBm
Test setup:	 The diagram illustrates the test setup. A Spectrum Analyzer is connected to an E.U.T. (Equipment Under Test) via a red cable. Both the Spectrum Analyzer and the E.U.T. are placed on a Non-Conducted Table. The table is supported by two vertical legs. Below the table is a Ground Reference Plane.
Test Instruments:	Refer to section 5.8 for details
Test mode:	Refer to section 5.3 for details
Test results:	Passed

Measurement Data:


Test CH	Power Spectral Density (dBm)	Limit(dBm)	Result
Lowest	-19.40	8.00	Pass
Middle	-19.82		
Highest	-19.02		

Test plots as follow:




6.6 Band Edge


6.6.1 Conducted Emission Method


Test Requirement:	FCC Part15 C Section 15.247 (d)
Test Method:	ANSI C63.10:2013 and KDB 558074
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Test setup:	 The diagram illustrates the test setup. A Spectrum Analyzer is connected to an E.U.T (Equipment Under Test) via a red cable. Both the Spectrum Analyzer and the E.U.T are placed on a Non-Conducted Table. The table is supported by a Ground Reference Plane.
Test Instruments:	Refer to section 5.8 for details
Test mode:	Refer to section 5.3 for details
Test results:	Passed

Test plots as follow:



6.6.2 Radiated Emission Method


Test Requirement:	FCC Part15 C Section 15.209 and 15.205				
Test Method:	ANSI C63.10: 2013and KDB 558074				
Test Frequency Range:	960MHz to 1.240GHz				
Test site:	Measurement Distance: 3m				
Receiver setup:	Frequency	Detector	RBW	VBW	Remark
	960MHz-1GHz	Quasi-peak	120kHz	300kHz	Quasi-peak Value
	Above 1GHz	Peak	1MHz	3MHz	Peak Value
		RMS	1MHz	3MHz	Average Value
Limit:	Frequency	Limit (dBuV/m @3m)			Remark
	960MHz-1GHz	54.00			Quasi-peak Value
	Above 1GHz	54.00			Average Value
		74.00			Peak Value
Test Procedure:	1. The EUT was placed on the top of a rotating table 0.8m(below 1GHz) /1.5m(above 1GHz) above the groundat a 3 meter chamber. The table was rotated 360 degrees todetermine the position of the highest radiation. 2. The EUT was set 3 meters away from the interference-receiving antenna, whichwas mounted on the top of a variable-height antenna tower. 3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. 4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatablewas turned from 0 degrees to 360 degrees to find the maximum reading. 5. The test-receiver system was set to Peak Detect Function and SpecifiedBandwidth with Maximum Hold Mode. 6. If the emission level of the EUT in peak mode was 10dB lower than the limitspecified, then testing could be stopped and the peak values of the EUT wouldbe reported. Otherwise the emissions that did not have 10dB margin would bere-tested one by one using peak, quasi-peak or average method as specified andthen reported in a data sheet.				
Test setup:	Below 1GHz 				

	Above 1GHz 
Test Instruments:	Refer to section 5.8 for details
Test mode:	Refer to section 5.3 for details
Test results:	Passed

Below 1GHz:

Test channel: Highest channel

Test Polarization: Horizontal




Site : 3m chamber
 Condition : FCC PART15 CLASS B 3m VULB9163(30M2G) HORIZONTAL
 EUT : Wireless transceiver module
 Model : E30
 Test mode : 922.5MHz mode
 Power Rating : AC 120V/60Hz
 Environment : Temp:25.5°C Humi:55%
 Test Engineer: YT
 Remark :

	ReadAntenna	Cable	Preamp		Limit	Over	
Freq	Level	Factor	Loss	Factor	Level	Line	Limit
-----	-----	-----	-----	-----	-----	-----	-----
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB
1	974.491	10.04	21.51	4.34	0.00	35.89	54.00 -18.11

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

Test Polarization: Vertical



Site : 3m chamber
 Condition : FCC PART15 CLASS B 3m VULB9163(30M2G) VERTICAL
 EUT : Wireless transceiver module
 Model : E30
 Test mode : 922.5MHz mode
 Power Rating : AC 120V/60Hz
 Environment : Temp:25.5°C Humi:55%
 Test Engineer: YT
 Remark :

	ReadAntenna	Cable	Preamp		Limit	Over	
Freq	Level	Factor	Loss	Factor	Level	Line	Limit
-----	-----	-----	-----	-----	-----	-----	-----
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB
1	974.531	10.04	21.51	4.34	0.00	35.89	54.00 -18.11


Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

Above 1GHz:

Test channel: Highest channel

Test Polarization: Horizontal




Site : 3m chamber
 Condition : FCC PART 15 (PK) 3m BBHA9120(1G18G) HORIZONTAL
 EUT : Wireless transceiver module
 Model : E30
 Test mode : 922.5MHz mode
 Power Rating : AC 120V/60Hz
 Environment : Temp:25.5°C Humi:55%
 Test Engineer: YT
 Remark :

	Read	Antenna	Cable	Preamp		Limit	Over	
Freq	Level	Factor	Loss	Factor	Level	Line	Limit	Remark
-----	-----	-----	-----	-----	-----	-----	-----	-----
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1 1082.844	18.81	23.95	3.15	0.00	45.91	74.00	-28.09	

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

Test Polarization: Vertical



Site : 3m chamber
 Condition : FCC PART 15 (PK) 3m BBHA9120(1G18G) VERTICAL
 EUT : Wireless transceiver module
 Model : E30
 Test mode : 922.5MHz mode
 Power Rating : AC 120V/60Hz
 Environment : Temp:25.5°C Humi:55%
 Test Engineer: YT
 Remark :


	Freq	Read	Antenna	Cable	Preamp	Limit	Over	
		Level	Factor	Loss	Factor	Line	Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB
1	1009.944	19.13	24.15	3.03	0.00	46.31	74.00	-27.69

Remark:


1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

6.7 Spurious Emission

6.7.1 Conducted Emission Method



Test Requirement:	FCC Part15 C Section 15.247 (d)
Test Method:	ANSI C63.10:2013 and KDB 558074
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Test setup:	 The diagram illustrates the test setup for conducted emission measurement. A Spectrum Analyzer is connected via a red cable to an E.U.T (Equipment Under Test). Both are placed on a Non-Conducted Table, which sits on a Ground Reference Plane.
Test Instruments:	Refer to section 5.8 for details
Test mode:	Refer to section 5.3 for details
Test results:	Passed

Test plot as follows:




6.7.2 Radiated Emission Method

Test Requirement:	FCC Part15 C Section 15.209 and 15.205				
Test Method:	ANSI C63.10:2013				
Test Frequency Range:	9KHz to 25GHz				
Test site:	Measurement Distance: 3m				
Receiver setup:	Frequency	Detector	RBW	VBW	Remark
	30MHz-1GHz	Quasi-peak	120KHz	300KHz	Quasi-peak Value
	Above 1GHz	Peak	1MHz	3MHz	Peak Value
		RMS	1MHz	3MHz	Average Value
Limit:	Frequency		Limit (dBuV/m @3m)		Remark
	30MHz-88MHz		40.0		Quasi-peak Value
	88MHz-216MHz		43.5		Quasi-peak Value
	216MHz-960MHz		46.0		Quasi-peak Value
	960MHz-1GHz		54.0		Quasi-peak Value
	Above 1GHz		54.0		Average Value
			74.0		Peak Value
Test Procedure:	1. The EUT was placed on the top of a rotating table 0.8m(below 1GHz)/1.5m(above 1GHz) above the ground at a 3 meter chamber.The table was rotated 360 degrees to determine the position of the highest radiation. 2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. 3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. 4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotating table was turned from 0 degrees to 360 degrees to find the maximum reading. 5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. 6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.				

Test setup:	Below 1GHz  Above 1GHz 
Test Instruments:	Refer to section 5.8 for details
Test mode:	Refer to section 5.3 for details
Test results:	Passed
Remark:	1. Pre-scan all kind of the place mode (X-axis, Y-axis, Z-axis), and found the Y-axis is the worst case. 2. 9 kHz to 30MHz is too low, so only shows the data of above 30MHz in this report.

Measurement Data (worst case): (Channel Low mid high all have been tested , worst case of below 1GHz is only reported):
Below 1GHz:

Test Polarization: Horizontal




Site : 3m chamber
 Condition : FCC PART 15.247 3m VULB9163(30M2G) HORIZONTAL
 EUT : Wireless transceiver module
 Model : E30
 Test mode : TX Mode
 Power Rating : AC 120V/60Hz
 Environment : Temp:25.5°C Humi:55%
 Test Engineer: YT
 REMARK :

	Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	30.531	19.10	11.20	0.78	0.00	31.08	40.00	-8.92	QP
2	46.016	15.63	14.40	1.28	0.00	31.31	40.00	-8.69	QP
3	92.139	16.05	11.13	2.03	0.00	29.21	43.50	-14.29	QP
4	158.112	18.23	8.58	2.57	0.00	29.38	43.50	-14.12	QP
5	222.950	22.13	11.30	2.84	0.00	36.27	46.00	-9.73	QP
6	726.805	17.84	19.68	4.28	0.00	41.80	46.00	-4.20	QP

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

Test Polarization: Vertical



Site : 3m chamber
 Condition : FCC PART 15.247 3m VULB9163(30M2G) VERTICAL
 EUT : Wireless transceiver module
 Model : E30
 Test mode : TX Mode
 Power Rating : AC 120V/60Hz
 Environment : Temp:25.5°C Humi:55%
 Test Engineer: YT
 REMARK :

	Freq	ReadAntenna	Cable Preamp		Limit	Over	
	Level Factor	Loss Factor	Level	Line	Limit	Remark	
	MHz	dBuV	dB/m	dB	dBuV/m	dBuV/m	dB
1	30.962	20.89	11.20	0.78	0.00	32.87	40.00 -7.13 QP
2	53.131	16.50	13.76	1.32	0.00	31.58	40.00 -8.42 QP
3	86.503	18.58	10.18	1.91	0.00	30.67	40.00 -9.33 QP
4	123.266	18.85	9.96	2.20	0.00	31.01	43.50 -12.49 QP
5	296.184	15.97	13.28	2.93	0.00	32.18	46.00 -13.82 QP
6	719.200	17.26	19.52	4.25	0.00	41.03	46.00 -4.97 QP

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

Above 1GHz:

Test channel: Lowest channel								
Peak value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
1814.00	50.26	25.05	4.13	41.25	38.19	74.00	-35.81	Vertical
2721.00	51.26	26.35	5.07	41.74	40.94	74.00	-33.06	Vertical
3628.00	45.26	27.72	5.92	41.58	37.32	74.00	-36.68	Vertical
4535.00	48.41	29.47	6.84	42.08	42.64	74.00	-31.36	Vertical
5442.00	51.69	30.54	7.16	41.85	47.54	74.00	-26.46	Vertical
1814.00	52.12	25.10	4.12	41.21	40.13	74.00	-33.87	Horizontal
2721.00	51.39	26.35	5.07	41.74	41.07	74.00	-32.93	Horizontal
3628.00	48.29	27.72	5.92	41.58	40.35	74.00	-33.65	Horizontal
4535.00	50.19	29.47	6.84	42.08	36.48	74.00	-37.52	Horizontal
5442.00	55.36	30.54	7.18	41.85	51.23	74.00	-22.77	Horizontal
Average value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
1814.00	48.25	25.05	4.13	41.25	36.18	54.00	-17.82	Vertical
2721.00	48.95	26.35	5.07	41.74	38.63	54.00	-15.37	Vertical
3628.00	41.25	27.72	5.92	41.58	33.31	54.00	-20.69	Vertical
4535.00	46.32	29.47	6.84	42.08	40.55	54.00	-13.45	Vertical
5442.00	50.16	30.54	7.16	41.85	46.01	54.00	-7.99	Vertical
1814.00	41.15	25.10	4.12	41.21	28.23	54.00	-25.77	Horizontal
2721.00	42.26	26.35	5.07	41.74	31.94	54.00	-22.06	Horizontal
3628.00	42.55	27.72	5.92	41.58	34.61	54.00	-19.39	Horizontal
4535.00	42.74	29.47	6.84	42.08	36.97	54.00	-17.03	Horizontal
5442.00	41.98	30.54	7.18	41.85	37.85	54.00	-16.15	Horizontal
Remark: 1. Final Level =Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor. 2. The emission levels of other frequencies are very lower than the limit and not show in test report.								

Test channel: Middle channel								
Peak value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
1830.00	51.26	25.05	4.13	41.25	39.19	74.00	-34.81	Vertical
2745.00	52.25	26.35	5.07	41.74	41.93	74.00	-32.07	Vertical
3660.00	45.75	27.72	5.92	41.58	37.81	74.00	-36.19	Vertical
4575.00	47.16	29.47	6.84	42.08	41.39	74.00	-32.61	Vertical
5490.00	52.26	30.54	7.16	41.85	48.11	74.00	-25.89	Vertical
1830.00	51.25	25.10	4.12	41.21	39.26	74.00	-34.74	Horizontal
2745.00	52.45	26.35	5.07	41.74	42.13	74.00	-31.87	Horizontal
3660.00	49.62	27.72	5.92	41.58	41.68	74.00	-32.32	Horizontal
4575.00	49.75	29.47	6.84	42.08	36.48	74.00	-37.52	Horizontal
5490.00	54.12	30.54	7.18	41.85	49.99	74.00	-24.01	Horizontal
Average value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
1830.00	48.32	25.05	4.13	41.25	36.25	54.00	-17.75	Vertical
2745.00	47.18	26.35	5.07	41.74	36.86	54.00	-17.14	Vertical
3660.00	42.15	27.72	5.92	41.58	34.21	54.00	-19.79	Vertical
4575.00	46.65	29.47	6.84	42.08	40.88	54.00	-13.12	Vertical
5490.00	51.48	30.54	7.16	41.85	47.33	54.00	-6.67	Vertical
1830.00	41.17	25.10	4.12	41.21	28.23	54.00	-25.77	Horizontal
2745.00	42.25	26.35	5.07	41.74	31.93	54.00	-22.07	Horizontal
3660.00	42.52	27.72	5.92	41.58	34.58	54.00	-19.42	Horizontal
4575.00	42.16	29.47	6.84	42.08	36.39	54.00	-17.61	Horizontal
5490.00	41.47	30.54	7.18	41.85	37.34	54.00	-16.66	Horizontal
Remark: 1. Final Level =Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor. 2. The emission levels of other frequencies are very lower than the limit and not show in test report.								

Test channel: Highest channel								
Peak value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
1845.00	50.10	24.95	4.17	41.31	40.33	74.00	-33.67	Vertical
2767.50	50.25	26.50	5.10	41.70	43.03	74.00	-30.97	Vertical
3690.00	45.68	27.84	5.98	41.66	40.82	74.00	-33.18	Vertical
4612.50	48.48	29.90	6.89	42.12	46.73	74.00	-27.27	Vertical
5535.00	51.55	30.50	7.24	41.81	51.41	74.00	-22.59	Vertical
1845.00	52.86	24.95	4.17	41.31	43.09	74.00	-30.91	Horizontal
2767.50	52.00	26.50	5.10	41.70	44.78	74.00	-29.22	Horizontal
3690.00	49.75	27.84	5.98	41.66	44.89	74.00	-29.11	Horizontal
4612.50	49.97	29.90	6.89	42.12	48.22	74.00	-25.78	Horizontal
5535.00	55.80	30.50	7.24	41.81	55.66	74.00	-18.34	Horizontal
Average value								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
1845.00	47.21	24.95	4.17	41.31	37.44	54.00	-16.56	Vertical
2767.50	47.54	26.50	5.10	41.70	40.32	54.00	-13.68	Vertical
3690.00	40.26	27.84	5.98	41.66	35.40	54.00	-18.60	Vertical
4612.50	45.58	29.90	6.89	42.12	43.83	54.00	-10.17	Vertical
5535.00	49.43	30.50	7.24	41.81	49.29	54.00	-4.71	Vertical
1845.00	40.22	25.10	4.12	41.21	28.23	54.00	-25.77	Horizontal
2767.50	43.37	26.35	5.07	41.74	33.05	54.00	-20.95	Horizontal
3690.00	41.29	27.72	5.92	41.58	33.35	54.00	-20.65	Horizontal
4612.50	42.25	29.47	6.84	42.08	36.48	54.00	-17.52	Horizontal
5535.00	41.85	30.54	7.18	41.85	37.72	54.00	-16.28	Horizontal
Remark: 1. Final Level =Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor. 2. The emission levels of other frequencies are very lower than the limit and not show in test report.								