



Company: Beam Authentic  
Model Tested: BEAM1  
DLS Project: 8791

166 South Carter, Genoa City, WI 53128

## RF Exposure Compliance

**Company:** Beam Authentic  
**Model:** BEAM1  
**Formal Name:** BEAM1  
**FCC ID:** 2ALRSBZ

**Rule Part:** CFR 47 Part 1.1307(b)  
CFR 47 Part 2.1093

**Test Procedure:** FCC 447498 10 D01 General RF Exposure Guidance v06  
4.3. General SAR test exclusion guidance  
4.3.1. Standalone SAR test exclusion considerations

**Limits:** The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at *test separation distances*  $\leq 50$  mm are determined by:

$$\left[ \frac{(\text{max. power of channel, including tune-up tolerance, mW})}{(\text{min. test separation distance, mm})} \right] \cdot \sqrt{f(\text{GHz})} \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR, where:}$$

$f(\text{GHz})$  is the RF channel transmit frequency in GHz.

Power and distance are rounded to the nearest mW and mm before calculation.

The result is rounded to one decimal place for comparison.

When the minimum *test separation distance* is  $< 5$  mm, a distance of 5 mm is applied to determine SAR test exclusion.

**Output Power:** This is a portable device. The maximum peak e.i.r.p. measured  $-13 \text{ dBm} = 0.05 \text{ mW}$ .

**Exclusion threshold:**  $[1\text{mW} / 5 \text{ mm}] \times [\sqrt{2.480 \text{ GHz}}] = 0.31$

**Results:**  $0.31 \leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR.  
SAR measurement is not necessary.