



## RF Exposure Evaluation Declaration

---

**FCC ID:** 2ALS8-KS0022

**Applicant:** Ninebot (Changzhou) Tech Co., Ltd.

**Product:** Segway eKickScooter Ninebot E3 Go

**Model No.:** 051903U, 051903N

**FCC Rule Part(s):** FCC Part 2.1091

**Result:** Complies

**Evaluation Date:** 2026-05-07

**Reviewed By:**

*Vincent Yu*

Vincent Yu

**Approved By:**

*Robin Wu*

Robin Wu



The test results relate only to the samples tested.

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report. Testing was performed in accordance with the applicable measurement procedures. The test results reported herein apply only to the specific item(s) tested.

The test report shall not be reproduced except in full without the written approval of MRT Technology (Suzhou) Co., Ltd.

### Revision History

| Report No.       | Version | Description    | Issue Date | Note  |
|------------------|---------|----------------|------------|-------|
| R26S1062039-U401 | V01     | Initial Report | 2026-05-12 | Valid |
|                  |         |                |            |       |

---

## CONTENTS

| Description                           | Page     |
|---------------------------------------|----------|
| <b>1. General Information .....</b>   | <b>4</b> |
| 1.1. Applicant.....                   | 4        |
| 1.2. Manufacturer .....               | 4        |
| 1.3. Testing Facility.....            | 4        |
| 1.4. Product Information .....        | 5        |
| 1.5. Antenna Details .....            | 5        |
| 1.6. Device Classification .....      | 5        |
| 1.7. Applied Standards .....          | 5        |
| <b>2. RF Exposure Evaluation.....</b> | <b>6</b> |
| 2.1. Limits .....                     | 6        |
| 2.2. MPE Exemptions.....              | 7        |
| 2.3. Calculated Result .....          | 9        |

## 1. General Information

### 1.1. Applicant

Ninebot (Changzhou) Tech Co., Ltd.

16F-17F, Block A, Building 3, No.18 Changwu Mid. Road, Wujin Dist., Changzhou, Jiangsu

### 1.2. Manufacturer

Ninebot (Changzhou) Tech Co., Ltd.

16F-17F, Block A, Building 3, No.18 Changwu Mid. Road, Wujin Dist., Changzhou, Jiangsu

### 1.3. Testing Facility

|                                     |                                                                                                                                           |
|-------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------|
| <input checked="" type="checkbox"/> | <b>Test Site - MRT Suzhou Laboratory</b>                                                                                                  |
|                                     | <b>Laboratory Location (Suzhou - Wuzhong)</b><br>D8 Building, No.2 Tian'edang Rd., Wuzhong Economic Development Zone, Suzhou, China       |
|                                     | <b>Laboratory Location (Suzhou - SIP)</b><br>4b Building, Liando U Valley, No.200 Xingpu Rd., Shengpu Town, Suzhou Industrial Park, China |
|                                     | <b>Laboratory Location (Suzhou - Wujiang)</b><br>Building 1, No.1 Xingdong Road, Wujiang, Suzhou, Jiangsu, People's Republic of China     |
|                                     | <b>Laboratory Accreditations</b>                                                                                                          |
|                                     | A2LA: 3628.01 CNAS: L10551<br>FCC: CN1166 ISED: CN0001                                                                                    |
| <input type="checkbox"/>            | <b>Test Site - MRT Shenzhen Laboratory</b>                                                                                                |
|                                     | <b>Laboratory Location (Shenzhen)</b><br>1G, Building A, Junxiangda Building, Zhongshanyuan Road West, Nanshan District, Shenzhen, China  |
|                                     | <b>Laboratory Accreditations</b>                                                                                                          |
|                                     | A2LA: 3628.02<br>FCC: CN1284 ISED: CN0105                                                                                                 |
| <input type="checkbox"/>            | <b>Test Site - MRT Taiwan Laboratory</b>                                                                                                  |
|                                     | <b>Laboratory Location (Taiwan)</b><br>No. 38, Fuxing 2nd Rd., Guishan Dist., Taoyuan City 333, Taiwan (R.O.C.)                           |
|                                     | <b>Laboratory Accreditations</b>                                                                                                          |
|                                     | TAF: 3261<br>FCC: 291082, TW3261 ISED: TW3261                                                                                             |

#### 1.4. Product Information

|                                                                                                                                                                                                       |                                                                                                                           |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------|
| Product Name                                                                                                                                                                                          | Segway eKickScooter Ninebot E3 Go                                                                                         |
| Model No.                                                                                                                                                                                             | 051903U, 051903N                                                                                                          |
| Bluetooth Specification                                                                                                                                                                               | Bluetooth_LE Only                                                                                                         |
| Antenna Specification                                                                                                                                                                                 | Refer to clause 1.5                                                                                                       |
| Operating Temp.                                                                                                                                                                                       | -10 °C ~ +45 °C                                                                                                           |
| Power Type                                                                                                                                                                                            | By Battery                                                                                                                |
| Accessory(ies)                                                                                                                                                                                        |                                                                                                                           |
| AC Adapter #1                                                                                                                                                                                         | Model: NBW41D001D7D<br>Input: 100-240 V ~ 50-60 Hz 2.0 A MAX<br>Rated output: 41 VDC 1.7 A<br>Manufacturer: Weihai Hitai  |
| AC Adapter #2                                                                                                                                                                                         | Model: NBW41D001D7D<br>Input: 100-240 V ~ 50-60 Hz 2.0 A MAX<br>Rated output: 41 VDC 1.7 A<br>Manufacturer: FSP-Powerland |
| Notes:                                                                                                                                                                                                |                                                                                                                           |
| 1. The information of the EUT (Equipment Under Test) was provided by the manufacturer. The accuracy, completeness, and validity of the information are solely the responsibility of the manufacturer. |                                                                                                                           |
| 2. These models are for different marketing purpose, others are identical.                                                                                                                            |                                                                                                                           |

#### 1.5. Antenna Details

| Technology   | Frequency Range<br>(MHz) | Antenna Type | Antenna Gain<br>(dBi) |
|--------------|--------------------------|--------------|-----------------------|
| Bluetooth-LE | 2400 ~ 2483.5            | PCB Antenna  | -1.26                 |

#### 1.6. Device Classification

According to the user manual, this device is classified as a Mobile Device. So, the RF exposure evaluation requirements of § 2.1091 for mobile device exposure conditions subject to MPE limits.

#### 1.7. Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- FCC Part 2.1091
- KDB 447498 D04 Interim General RF Exposure Guidance v01

## 2. RF Exposure Evaluation

### 2.1. Limits

According to FCC §1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in §1.1307(b)

Limits For Maximum Permissible Exposure (MPE)

| Frequency Range<br>(MHz)                                  | Electric Field<br>Strength (V/m) | Magnetic Field<br>Strength (A/m) | Power Density<br>(mW/cm <sup>2</sup> ) | Average Time<br>(Minutes) |
|-----------------------------------------------------------|----------------------------------|----------------------------------|----------------------------------------|---------------------------|
| (A) Limits for Occupational/ Control Exposures            |                                  |                                  |                                        |                           |
| 0.3 ~ 3.0                                                 | 614                              | 1.63                             | *(100)                                 | ≤6                        |
| 3.0 ~ 30                                                  | 1842/f                           | 4.89/f                           | *(900/f <sup>2</sup> )                 | <6                        |
| 30 ~ 300                                                  | 61.4                             | 0.163                            | 1.0                                    | <6                        |
| 300 ~ 1500                                                | --                               | --                               | f/300                                  | <6                        |
| 1500 ~ 100000                                             | --                               | --                               | 5                                      | <6                        |
| (B) Limits for General Population/ Uncontrolled Exposures |                                  |                                  |                                        |                           |
| 0.3 ~ 1.34                                                | 614                              | 1.63                             | *(100)                                 | <30                       |
| 1.34 ~ 30                                                 | 824/f                            | 2.19/f                           | *(180/f <sup>2</sup> )                 | <30                       |
| 30 ~ 300                                                  | 27.5                             | 0.073                            | 0.2                                    | <30                       |
| 300 ~ 1500                                                | --                               | --                               | f/1500                                 | <30                       |
| 1500 ~ 100000                                             | --                               | --                               | 1.0                                    | <30                       |

f= frequency in MHz. \* = Plane-wave equivalent power density.

## 2.2. MPE Exemptions

**For single RF sources** (i.e., any single fixed RF source, mobile device, or portable device, as defined in paragraph §1.1307(b)(2) of this section): A single RF source is exempt if:

**(Option A)** The available maximum time-averaged power is no more than 1 mW, regardless of separation distance. This exemption may not be used in conjunction with other exemption criteria other than those in paragraph §1.1307(b)(3)(ii)(A) of this section.

Medical implant devices may only use this exemption and that in paragraph §1.1307(b)(3)(ii)(A);

**(Option B)** Or the available maximum time-averaged power or effective radiated power (ERP), whichever is greater, is less than or equal to the threshold P (mW) described in the following formula. This method shall only be used at separation distances (cm) from 0.5 centimeters to 40 centimeters and at frequencies from 0.3 GHz to 6 GHz (inclusive). P is given by:

$$P_{th}(mW) = \{ERP_{20cm}(d/20 \text{ cm})^x \quad d \leq 20 \text{ cm}$$

$$P_{th}(mW) = \{ERP_{20cm} \quad 20 \text{ cm} < d \leq 40 \text{ cm}$$

Where

$$x = -\log_{10} \left( \frac{60}{ERP_{20cm}\sqrt{f}} \right) \text{ and } f \text{ is in GHz;}$$

and

$$ERP_{20cm}(mW) = \{2040f \quad 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz}$$

$$ERP_{20cm}(mW) = \{3060 \quad 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz}$$

**(Option C)** Or using Table 1 and the minimum separation distance (R in meters) from the body of a nearby person for the frequency (f in MHz) at which the source operates, the ERP (watts) is no more than the calculated value prescribed for that frequency. For the exemption in Table 1 to apply, R must be at least  $\lambda/2\pi$ , where  $\lambda$  is the free-space operating wavelength in meters. If the ERP of a single RF source is not easily obtained, then the available maximum time-averaged power may be used in lieu of ERP if the physical dimensions of the radiating structure(s) do not exceed the electrical length of  $\lambda/4$  or if the antenna gain is less than that of a half-wave dipole (1.64 linear value).

Table 1 to §1.1307(b)(3)(i)(C) - Single RF Sources Subject to Routine Environmental Evaluation

| RF Source Frequency (MHz) | Threshold ERP (watts)              |
|---------------------------|------------------------------------|
| 0.3 ~ 1.34                | 1920R <sup>2</sup>                 |
| 1.34 ~ 30                 | 3450R <sup>2</sup> /f <sup>2</sup> |
| 30 ~ 300                  | 3.83R <sup>2</sup>                 |
| 300 ~ 1500                | 0.0128R <sup>2</sup> f             |
| 1500 ~ 100000             | 19.2R <sup>2</sup>                 |

**For multiple RF sources:** Multiple RF sources are exempt if:

(A) The available maximum time-averaged power of each source is no more than 1 mW and there is a separation distance of two centimeters between any portion of a radiating structure operating and the nearest portion of any other radiating structure in the same device, except if the sum of multiple sources is less than 1 mW during the time-averaging period, in which case they may be treated as a single source (separation is not required). This exemption may not be used in conjunction with other exemption criteria other than those in paragraph §1.1307(b)(3)(i)(A) of this section. Medical implant devices may only use this exemption and that in paragraph §1.1307(b)(3)(i)(A).

(B) in the case of fixed RF sources operating in the same time-averaging period, or of multiple mobile or portable RF sources within a device operating in the same time averaging period, if the sum of the fractional contributions to the applicable thresholds is less than or equal to 1 as indicated in the following equation.

$$\sum_{i=1}^a \frac{P_i}{P_{th,i}} + \sum_{j=1}^b \frac{ERP_j}{ERP_{th,j}} + \sum_{k=1}^c \frac{Evaluated_k}{Exposure\ Limit_k} \leq 1$$

Where:

**a** = number of fixed, mobile, or portable RF sources claiming exemption using paragraph §1.1307(b)(3)(i)(B) of this section for  $P_{th}$ , including existing exempt transmitters and those being added.

**b** = number of fixed, mobile, or portable RF sources claiming exemption using paragraph §1.1307(b)(3)(i)(C) of this section for Threshold ERP, including existing exempt transmitters and those being added.

**c** = number of existing fixed, mobile, or portable RF sources with known evaluation for the specified minimum distance including existing evaluated transmitters.

$P_i$  = the available maximum time-averaged power or the ERP, whichever is greater, for fixed, mobile, or portable RF source  $i$  at a distance between 0.5 cm and 40 cm (inclusive).

$P_{th,i}$  = the exemption threshold power ( $P_{th}$ ) according to paragraph §1.1307(b)(3)(i)(B) of this section for fixed, mobile, or portable RF source  $i$ .

$ERP_j$  = the ERP of fixed, mobile, or portable RF source  $j$ .

**$ERP_{th,j}$**  = exemption threshold ERP for fixed, mobile, or portable RF source  $j$ , at a distance of at least  $\lambda/2\pi$  according to the applicable formula of paragraph §1.1307(b)(3)(i)(C) of this section.

**$Evaluated_k$**  = the maximum reported SAR or MPE of fixed, mobile, or portable RF source  $k$  either in the device or at the transmitter site from an existing evaluation at the location of exposure.

**$Exposure Limit_k$**  = either the general population/uncontrolled maximum permissible exposure (MPE) or specific absorption rate (SAR) limit for each fixed, mobile, or portable RF source  $k$ , as applicable from §1.1310 of this chapter.

### 2.3. Calculated Result

|           |                                   |
|-----------|-----------------------------------|
| Product   | Segway eKickScooter Ninebot E3 Go |
| Test Item | RF Exposure Evaluation            |

| Test Mode    | Frequency Band (MHz) | Tune-up Conducted Power (dBm) | Antenna Gain (dBi) | Tune-up ERP (dBm) | Tune-up ERP (mW) |
|--------------|----------------------|-------------------------------|--------------------|-------------------|------------------|
| Bluetooth-LE | 2400 ~ 2483.5        | 3.13                          | -1.26              | -0.28             | 0.94             |

Notes:

1. Bluetooth-LE Tune-up power (dBm) is referenced from report No.: R26S1062039-U201.
2. Tune-up ERP (dBm) = Tune-up Conducted Power (dBm) + Antenna Gain (dBi) - 2.15.

### CONCLUSION:

The Tune-up ERP of the device is 0.94 mW and it is less than 1 mW, so the device qualifies for RF exposure test exemption.

\_\_\_\_\_ The End \_\_\_\_\_