

FCC 47 CFR PART 15 SUBPART C

TEST REPORT

For

Product Name: Wireless Node Controller

Brand Name: MOONS'

Model No.: MSDK6149

Series Model.: MSDK6137,MSDK6131,MSDK6159

FCC ID: 2ALUV-MSDK61XX

Test Report Number:

C170411E02-RPW

Issued for

Shanghai MOONS' Automation Control Co.,Ltd.

No.168 Mingjia Rd, Minhang District,Shanghai 201107

Issued by

Compliance Certification Services Inc.

Kun shan Laboratory

**No.10 Weiye Rd., Innovation park, Eco&Tec,
Development Zone, Kunshan City, Jiangsu, China**

TEL: 86-512-57355888

FAX: 86-512-57370818



TESTING CERT #2541.01

Note: This report shall not be reproduced except in full, without the written approval of Compliance Certification Services Inc. This document may be altered or revised by Compliance Certification Services Inc. personnel only, and shall be noted in the revision section of the document. The client should not use it to claim product endorsement by A2LA or any government agencies. The test results in the report only apply to the tested sample.

TABLE OF CONTENTS

1.	TEST RESULT CERTIFICATION.....	4
2.	EUT DESCRIPTION.....	5
3.	TEST METHODOLOGY	6
3.1.	EUT CONFIGURATION	6
3.2.	EUT EXERCISE	6
3.3.	GENERAL TEST PROCEDURES.....	6
3.4.	FCC PART 15.205 RESTRICTED BANDS OF OPERATIONS.....	7
3.5.	DESCRIPTION OF TEST MODES.....	8
3.6.	ANTENNA DESCRIPTION	8
4.	INSTRUMENT CALIBRATION.....	9
4.1.	MEASURING INSTRUMENT CALIBRATION	9
5.	FACILITIES AND ACCREDITATIONS	11
5.1.	FACILITIES	11
5.2.	EQUIPMENT.....	11
5.3.	LABORATORY ACCREDITATIONS AND LISTING	11
5.4.	TABLE OF ACCREDITATIONS AND LISTINGS	12
6.	SETUP OF EQUIPMENT UNDER TEST	13
6.1.	SETUP CONFIGURATION OF EUT	13
6.2.	SUPPORT EQUIPMENT.....	13
7.	FCC PART 15.247 REQUIREMENTS.....	14
7.1.	6DB BANDWIDTH	14
7.2.	PEAK POWER.....	17
7.3.	PEAK POWER SPECTRAL DENSITY	19
7.4.	SPURIOUS EMISSIONS	23
7.5.	RADIATED EMISSIONS.....	30
7.6.	POWERLINE CONDUCTED EMISSIONS	38



Revision History

Rev.	Issue Date	Report NO.	Effect Page	Contents
00	May 7, 2017	C170411E02-RPW	ALL	N/A

1. TEST RESULT CERTIFICATION

Product Name:	Wireless Node Controller
Trade Name:	MOONS'
Model Name.:	MSDK6149
Series Model:	MSDK6137, MSDK6131, MSDK6159
Applicant Discrepancy:	Initial
Device Category:	Mobile unit
Date of Test:	April 20~May 7, 2017
Applicant:	Shanghai MOONS' Automation Control Co.,Ltd. No.168 Mingjia Rd, Minhang District, Shanghai 201107
Manufacturer:	Shanghai MOONS' Automation Control Co.,Ltd. No.168 Mingjia Rd, Minhang District, Shanghai 201107
Application Type:	Certification

APPLICABLE STANDARDS

STANDARD	TEST RESULT
FCC 47 CFR Part 15 Subpart C	No non-compliance noted


We hereby certify that:

The above equipment was tested by Compliance Certification Services Inc. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.10: 2013 and the energy emitted by the sample EUT tested as described in this report is in compliance with the requirements of FCC Rules Part 15.207, 15.209, 15.247.

The test results of this report relate only to the tested sample EUT identified in this report.

Approved by:

Jeff.Fang
RF Manager
Compliance Certification Service Inc.

Tested by:

Lily.Wang
Test Engineer
Compliance Certification Service Inc.

2. EUT DESCRIPTION

Product Name:	Wireless Node Controller
Brand Name:	MOONS'
Model Name:	MSDK6149
Series Model:	MSDK6137, MSDK6131, MSDK6159
Model Discrepancy:	See table of model discrepancy
Power Rating:	INPUT:100-277VAC 50/60Hz OUTPUT:100-277VAC 50/60Hz 1000VA
Frequency Range:	2405~2475MHz
Transmit Power:	Channel 2405:11.24 dBm
Modulation Technique:	O-QPSK
Number of Channels:	15 Channels
Antenna Specification:	monopole antenna Gain: 2.88 dBi

Remark:

1.The sample selected for test was engineering sample that approximated to production product and was provided by manufacturer.

2.This submittal(s) (test report) is intended for **FCC ID: 2ALUV-MSDK61XX** filing to comply with Section 15.207, 15.209 and 15.247 of the FCC Part 15, Subpart C Rules.

Model Discrepancy:

Model Name	Input voltage	Output current	Dimming	GPS	Light Sensor	Metering	shell color
MSDK6149	100 to 277VAC	5A	0-10Vdc*2	Yes	Yes	Yes	Blue
MSDK6137			0-10Vdc	No	Yes		
MSDK6131			0-10Vdc	No	No		
MSDK6159			DALI	Yes	Yes		

3. TEST METHODOLOGY

The tests documented in this report were performed in accordance with ANSI C63.10 2013 and FCC CFR 47 15.207, 15.209 and 15.247.

3.1.EUT CONFIGURATION

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner that intends to maximize its emission characteristics in a continuous normal application.

3.2.EUT EXERCISE

The EUT was operated in the engineering mode to fix the TX frequency that was for the purpose of the measurements.

According to its specifications, the EUT must comply with the requirements of the Section 15.207, 15.209 and 15.247 under the FCC Rules Part 15 Subpart C.

3.3.GENERAL TEST PROCEDURES

Conducted Emissions

The EUT is placed on the turntable, which is 0.8 m above ground plane. According to the requirements in Section 13.1.4.1 of ANSI C63.10 2013 Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using CISPR Quasi-peak and average detector modes.

Radiated Emissions

Under 1GHz

The EUT is placed on a turn table, which is 0.8 m above ground plane. The turntable shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3m away from the receiving antenna, which varied from 1m to 4m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the maximum emissions, exploratory radiated emission measurements were made according to the requirements in Section 13.1.4.1 of ANSI C63.10:2013.

Above 1GHz

The EUT is placed on a turn table, which is 1.5 m above ground plane. The turntable shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3m away from the receiving antenna, which varied from 1m to 4m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the maximum emissions, exploratory radiated emission measurements were made according to the requirements in Section 13.1.4.1 of ANSI C63.10:2013.

3.4.FCC PART 15.205 RESTRICTED BANDS OF OPERATIONS

Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
¹ 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2655 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	(²)
13.36 - 13.41			

¹ Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.

² Above 38.6

Except as provided in paragraphs (d) and (e), the field strength of emissions appearing within these frequency bands shall not exceed the limits shown in Section 15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in Section 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000 MHz, compliance with the emission limits in Section 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in Section 15.35 apply to these measurements.

3.5.DESCRPTION OF TEST MODES


Software used to control the EUT for staying in continuous transmitting and receiving mode is programmed. The worst-case data are determined to be as follows for each mode based on investigation by measuring the average power, peak power and PPSD across all channel, bandwidths, and modulations.

3.6.ANTENNA DESCRIPTION

an intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached or an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section”

* the antenna of this EUT is a unique(monopole Antenna).

* the EUT complies with the requirement of 15.203.



4. INSTRUMENT CALIBRATION

4.1.MEASURING INSTRUMENT CALIBRATION

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipment, which is traceable to recognized national standards.

Equipment Used for Emissions Measurement

Conducted Emissions Test Site					
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Date	Calibration Due
Spectrum Analyzer	Agilent	E4446A	MY44020154	2016-9-10	2017-9-9
Spectrum Analyzer	RS	FSU26	200789	2016-7-21	2017-7-20
Power meter	Anritsu	ML2495A	1445010	2016-5-16	2017-5-15
Power sensor	Anritsu	MA2411B	1339220	2016-5-16	2017-5-15
Power SPLITTER	Mini-Circuits	ZN2PD-9G	SF078500430	N.C.R	N.C.R
DC Power Supply	AGILENT	E3632A	MY50340053	N.C.R	N.C.R
Temp. / Humidity Gauge	Anymetre	TH603	CCS007	2016-11-1	2017-10-31
Test Software			EZ-EMC		

977 Chamber					
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Date	Calibration Due
Spectrum Analyzer	Agilent	E4446A	MY44020154	2016-9-10	2017-9-9
Spectrum Analyzer	RS	FSU26	200789	2016-7-21	2017-7-20
EMI Test Receiver	R&S	ESCI	101378	2017-1-5	2018-1-4
Pre-Amplifier	MINI	ZFL-1000VH2	070306	2017-1-5	2018-1-4
Pre-Amplifier	Miteq	JS41-00101800-32-10P	1675713	2016-7-21	2017-7-20
Bilog Antenna	Sunol	JB1	A062604	2016-5-29	2017-5-28
Bilog Antenna	Sunol	JB1	A110204-1	2016-5-29	2017-5-28
Loop Antenna	SCHWARZBECK	HXYZ9170	9170-108	2017-3-4	2018-3-3
Horn-antenna	SCHWARZBECK	9120D	D:266	2017-3-5	2018-3-4
Horn-antenna	SCHWARZBECK	9120D	D:267	2016-11-10	2017-11-9
Turn Table	CT	CT123	4165	N.C.R	N.C.R
Antenna Tower	CT	CTERG23	3256	N.C.R	N.C.R
Controller	CT	CT100	95637	N.C.R	N.C.R
Test Software			EZ-EMC		

Conducted Emission					
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Date	Calibration Due
EMI TEST RECEIVER	R&S	ESCI	100781	2017-2-28	2018-2-27
V (V-LISN)	SCHWARZBECK	NNLK 8129	8129-143	2016-11-1	2017-10-31
TWO-LINE V-NETWORK	R&S	ENV216	101604	2016-11-1	2017-10-31
Pulse LIMITER	R&S	ESH3-Z2	100524	2017-1-5	2018-1-4
Test Software			EZ-EMC		

Remark: The measurement uncertainty is less than +/- 2.81dB, which is evaluated as per the NAMAS NIS 81 and CISPR/A/291/CDV.

Expanded Uncertainty (95% CONFIDENCE INTERVAL): K=2

5. FACILITIES AND ACCREDITATIONS

5.1.FACILITIES

All measurement facilities used to collect the measurement data are located at CCS China Kunshan Lab at 10#Weiye Rd, Innovation Park Eco. & Tec. Development Zone

Kunshan city JiangSu, (215300), CHINA.

The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.10 2013 and CISPR Publication 22.

5.2.EQUIPMENT

Radiated emissions are measured with one or more of the following types of linearly polarized antennas: tuned dipole, biconical, log periodic, bi-log, and/or ridged waveguide, horn. Spectrum analyzers with pre-selectors and quasi-peak detectors are used to perform radiated measurements.

Conducted emissions are measured with Line Impedance Stabilization Networks and EMI Test Receivers.

Calibrated wideband preamplifiers, coaxial cables, and coaxial attenuators are also used for making measurements.

All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."

5.3.LABORATORY ACCREDITATIONS AND LISTING

The test facilities used to perform radiated and conducted emissions tests are accredited by American Association for Laboratory Accreditation Program for the specific scope accreditation under Lab Code: 200581-0 to perform Electromagnetic Interference tests according to FCC Part 15 and CISPR 22 requirements. In addition, the test facilities are listed with Industry Canada, Certification and Engineering Bureau, 2324E-1 for 10m chamber, 2324E-2 for 3m chamber; the test facilities are listed with USA, Certification and Engineering Bureau, 424105 for 10m chamber, 238958 for 3m chamber.

5.4.TABLE OF ACCREDITATIONS AND LISTINGS

Country	Agency	Scope of Accreditation	Logo
USA	A2LA	47 CFR FCC Part 15/18 (using ANSI C63.10 :2013); VCCI V3; CNS 13438; CNS 13439; CNS 13803; CISPR 11; EN 55011; CISPR 13; EN 55013; CISPR 22:2005; CISPR 22:1997 +A1 :2000+A2 :2002; EN 55022:2006; EN55022 :1998 +A1 :2001+A2 :2003; EN 61000-6-3 (excluding discontinuous interference); EN 61000-6-4; AS/NZS CISPR 22; CAN/CSA-CEI/IEC CISPR 22; EN 61000-3-2; EN 61000-3-3; EN550024; EN 61000-4-2; EN 61000-4-3; EN61000-4-4; EN 61000-4-5; EN 61000-4-6; IEC 61000-4-8; EN 61000-4-11; IEC61000-3-2; IEC61000-3-3; IEC 61000-4-2; IEC 61000-4-3; IEC 61000-4-4; IEC 61000-4-5; IEC 61000-4-6; IEC 61000-4-8; IEC 61000-4-11; EN 300 220-3; EN 300 328; EN 300 330-2; EN 300 440-1; EN 300-440-2; EN 300 893; EN 301 489-01; EN 301 489-3; EN 301 489-07; EN 301 489-17; 47 CFR FCC Part 15, 22, 24	 TESTING CERT #2541.01
USA	FCC	3/10 meter Sites to perform FCC Part 15/18 measurements	 93105, 90471
Japan	VCCI	3/10 meter Sites and conducted test sites to perform radiated/conducted measurements	VCCI R-1600 C-1707 G-216

* No part of this report may be used to claim or imply product endorsement by A2LA or any agency of the US Government.

6. SETUP OF EQUIPMENT UNDER TEST

6.1.SETUP CONFIGURATION OF EUT

See test photographs attached in Appendix 1 for the actual connections between EUT and support equipment.

6.2.SUPPORT EQUIPMENT

No.	Device Type	Brand	Model	Series No.	FCC ID
1.	N/A	N/A	N/A	N/A	N/A

Remark:

2. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
3. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.


7. FCC PART 15.247 REQUIREMENTS

7.1.6DB BANDWIDTH

LIMIT

According to §15.247(a)(2), systems using digital modulation techniques may operate in the 902 - 928 MHz, and 2400 - 2483.5 MHz bands, and 5725 - 5850 MHz bands. The minimum 6dB bandwidth shall be at least 500kHz.

Test Configuration



TEST PROCEDURE



The transmitter output is connected to the spectrum analyzer. The RBW is set to 1% to 3% of the selected span. The VBW is set to 3 times the RBW. The sweep time is occupied.

TEST RESULTS


No non-compliance noted

Test Data

Channel	Frequency (MHz)	Bandwidth (MHz)	Limit (kHz)	Result
Low	2405	1.530	>500	PASS
Mid	2440	1.563		PASS
High	2475	1.571		PASS

Test Plot**6dB Bandwidth (CH Low)****6dB Bandwidth (CH Mid)**

6dB Bandwidth (CH High)




7.2. PEAK POWER

LIMIT

The maximum peak output power of the intentional radiator shall not exceed the following:

1. According to §15.247(b)(3), for systems using digital modulation in the bands of 902-928 MHz, and 2400-2483.5 MHz: 1 Watt.
2. According to §15.247(b)(4), the conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Test Configuration



TEST PROCEDURE

1. The EUT transmitter output is connected to the Power meter.
The Power meter is set to the peak power detection.
2. The testing follows the Measurement Procedure FCC KDB No. 558074 D01 DTS Meas. Guidance v04. 9.1.3 PKPM1 Peak-reading power meter method.

TEST RESULTS

No non-compliance noted

**Test Data**

Channel	Frequency (MHz)	Peak Output Power (dBm)	Limit (dBm)
Low	2405	11.24	30.00
Mid	2440	10.78	30.00
High	2475	9.87	30.00


7.3. PEAK POWER SPECTRAL DENSITY

LIMIT

1. According to §15.247(e), for digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

2. According to §15.247(f), the digital modulation operation of the hybrid system, with the frequency hopping turned off, shall comply with the power density requirements of paragraph (d) of this section.

Test Configuration



TEST PROCEDURE

1. Place the EUT on the table and set it in transmitting mode.

Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.

2. Set the spectrum analyzer as RBW = 3 kHz, VBW = 10 kHz, Span = 1.5 times the DTS bandwidth, Sweep = auto

3. Record the max reading.



4. Repeat the above procedure until the measurements for all frequencies are completed.

TEST RESULTS

No non-compliance noted

**Test Data**

Channel	Frequency (MHz)	PPSD (dBm)	Limit (dBm)	Result
Low	2405	-0.36	8.00	PASS
Mid	2440	-0.95	8.00	PASS
High	2475	-2.35	8.00	PASS

Test Plot**PPSD (CH Low)****PPSD(CH Mid)**

PPSD (CH High)



* RBW 3 kHz

Marker 1 [T1]

* VBW 10 kHz


-2.35 dBm

SWT 270 ms

2.474897885 GHz

Ref 20 dBm

* Att 10 dB




7.4.SPURIOUS EMISSIONS

Conducted Measurement

LIMIT

According to §15.247(d), in any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in 15.209(a) (see Section 15.205(c)).

Test Configuration



TEST PROCEDURE



Conducted RF measurements of the transmitter output were made to confirm that the EUT antenna port conducted emissions meet the specified limit and to identify any spurious signals that require further investigation or measurements on the radiated emissions site.



The transmitter output is connected to the spectrum analyzer. The resolution bandwidth is set to 100 kHz. The video bandwidth is set to 300 kHz.

Measurements are made over the 30MHz to 40GHz range with the transmitter set to the lowest, middle, and highest channels.



TEST RESULTS

No non-compliance noted

Test Plot**OUT-OF-BAND SPURIOUS EMISSIONS-CONDUCTED MEASUREMENT****CH Low**




CH Mid






Ref 20 dBm * Att 10 dB * RBW 100 kHz Marker 1 [T1] -45.23 dBm
* VBW 300 kHz 4.877804878 GHz
SWT 2.3 s





CH High



Ref 20 dBm * Att 10 dB * RBW 100 kHz Marker 1 [T1] 6.81 dBm
* VBW 300 kHz 2.474740400 GHz
SWT 2.5 ms








* RBW 100 kHz Marker 1 [T1]
 * VBW 300 kHz -51.77 dBm
 SWT 2.3 s 12.378048780 GHz

Ref 20 dBm

* Att 10 dB



7.5.RADIATED EMISSIONS

LIMIT

Radiated emissions from 9 kHz to 25 GHz were measured according to the methods defines in ANSI C63.10-2013. The EUT was placed above the ground plane, 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz. The interface cables and equipment positions were varied within limits of reasonable applications to determine the positions producing maximum radiated emissions

1. According to §15.209(a), except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:



FREQUENCIES(MHz)	FIELD STRENGTH (microvolts/meter)	MEASUREMENT DISTANCE(meters)
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3


Remark: Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g., Sections 15.231 and 15.241.

2. In the emission table above, the tighter limit applies at the band edges.

Frequency (MHz)	Field Strength (μ V/m at 3-meter)	Field Strength (dB μ V/m at 3-meter)
30-88	100	40
88-216	150	43.5
216-960	200	46
Above 960	500	54

Test Configuration

Below 30MHz**Below 1 GHz****Above 1 GHz**



TEST PROCEDURE

1. The EUT is placed on a turntable above ground plane, which is 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
6. Set the spectrum analyzer in the following setting as:

Below 1GHz:

RBW=100kHz / VBW=300kHz / Sweep=AUTO

Above 1GHz:

PEAK: RBW=VBW=1MHz / Sweep=AUTO

AVERAGE: RBW=1MHz / Sweep=AUTO


VBW=10Hz, when duty cycle is no less than 98 percent.

$VBW \geq 1/T$, when duty cycle is less than 98 percent, where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.


Band	Duty Cycle(%)	T(ms)	1/T(kHz)	VBW Setting
IEEE 802.15.4	100	--	--	10Hz

7. Repeat above procedures until the measurements for all frequencies are complete.

TEST RESULTS


RESTRICTED BANDEDGE (Low Channel, Horizontal)

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Degree (deg.)	Remark
1	2373.077	62.46	-7.47	54.99	74.00	-19.01	100	111	peak
2	2373.077	55.44	-7.47	47.97	54.00	-6.03	100	56	AVG
3	2390.000	58.96	-7.31	51.65	74.00	-22.35	100	236	peak

RESTRICTED BANDEDGE (Low Channel, Vertical)


No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Degree (deg.)	Remark
1	2373.269	64.01	-7.47	56.54	74.00	-17.46	100	236	peak
2	2373.269	56.90	-7.47	49.43	54.00	-4.57	100	259	AVG
3	2390.000	59.25	-7.31	51.94	74.00	-22.06	100	251	peak

RESTRICTED BANDEDGE (High Channel, Horizontal)



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Degree (deg.)	Remark
1	2483.500	61.34	-6.44	54.90	74.00	-19.10	100	167	peak
2	2483.500	49.96	-6.44	43.52	54.00	-10.48	100	257	AVG
3	2506.250	62.46	-6.23	56.23	74.00	-17.77	100	129	peak
4	2506.250	49.76	-6.23	43.53	54.00	-10.47	133	0	AVG

RESTRICTED BANDEDGE (High Channel, Vertical)



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Degree (deg.)	Remark
1	2483.500	63.34	-6.44	56.90	74.00	-17.10	200	195	peak
2	2483.500	50.82	-6.44	44.38	54.00	-9.62	198	192	AVG
3	2506.490	62.70	-6.23	56.47	74.00	-17.53	201	186	peak
4	2506.490	52.60	-6.23	46.37	54.00	-7.63	202	165	AVG

Test Result of Radiated Emission**Below 30MHz**

The interference of the frequency value is lower than the limit below 20 db, measured as the background noise values and will not be recorded.

30MHz-1GHz

Operation Mode:	Normal Link	Test Date:	2017-4-20
Temperature:	25°C	Tested by:	Lily.Wang
Humidity:	48% RH	Polarity:	Ver. / Hor.

Frequency (MHz)	Ant. Pol. (H/V)	Reading (dBuV)	Correction Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
141.5500	V	12.87	13.55	26.42	43.50	-17.08	Peak
283.1700	V	10.48	16.47	26.95	46.00	-19.05	Peak
425.7600	V	12.84	20.94	33.78	46.00	-12.22	Peak
567.3800	V	11.62	22.66	34.28	46.00	-11.72	Peak
709.0000	V	8.80	25.39	34.19	46.00	-11.81	Peak
850.6200	V	11.24	25.91	37.15	46.00	-8.85	Peak
141.5500	H	12.73	13.55	26.28	43.50	-17.22	Peak
425.7600	H	6.27	20.94	27.21	46.00	-18.79	Peak
567.3800	H	8.91	22.66	31.57	46.00	-14.43	Peak
701.2400	H	5.47	25.41	30.88	46.00	-15.12	Peak
861.2900	H	6.34	26.06	32.40	46.00	-13.60	Peak
945.6800	H	5.29	27.37	32.66	46.00	-13.34	Peak

Remark:

1. Measuring frequencies from 30 MHz to the 1GHz (No emission found between lowest internal used/generated frequency to 30 MHz).
2. Radiated emissions measured in frequency range from 30 MHz to 1000MHz were made with an instrument using peak/quasi-peak detector mode.
3. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
4. Margin (dB) = Result (dBuV/m) – Limit (dBuV/m).

Above 1 GHz

Operation Mode: TX / CH Low

Test Date: 2017-5-2

Temperature: 24°C

Tested by: Lily.Wang

Humidity: 48 % RH

Polarity: Ver. / Hor.

Horizontal

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Degree (deg.)	Remark
1	4813.962	57.71	-5.26	52.45	54.00	-1.55	198	211	AVG
2	4814.103	70.29	-5.26	65.03	74.00	-8.97	200	197	peak
3	7211.538	50.54	6.30	56.84	74.00	-17.16	200	123	peak
4	7211.782	39.94	6.30	46.24	54.00	-7.76	202	137	AVG
5	12033.654	43.21	10.42	53.63	74.00	-20.37	200	227	peak
N/A									

Vertical

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Degree (deg.)	Remark
1	4813.866	54.80	-5.26	49.54	54.00	-4.46	202	219	AVG
2	4814.103	64.79	-5.26	59.53	74.00	-14.47	200	235	peak
3	7211.538	47.25	6.30	53.55	74.00	-20.45	200	125	peak
4	9636.218	43.50	7.76	51.26	74.00	-22.74	200	142	peak
5	12032.116	38.19	10.41	48.60	54.00	-5.40	198	134	AVG
6	12033.654	46.75	10.42	57.17	74.00	-16.83	200	120	peak

Operation Mode: TX /CH Mid

Test Date: 2017-5-2

Temperature: 24°C

Tested by: Lily.Wang

Humidity: 48 % RH

Polarity: Ver. / Hor.

Horizontal

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Degree (deg.)	Remark
1	4868.590	67.30	-5.22	62.08	74.00	-11.92	200	129	peak
2	4868.975	56.51	-5.22	51.29	54.00	-2.71	198	234	AVG
3	7319.430	42.32	6.40	48.72	54.00	-5.28	202	137	AVG
4	7320.513	51.44	6.40	57.84	74.00	-16.16	200	129	peak
5	12197.115	42.44	11.12	53.56	74.00	-20.44	200	239	peak
N/A									

Vertical

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Degree (deg.)	Remark
1	4868.590	63.95	-5.22	58.73	74.00	-15.27	200	12	peak
2	4869.975	53.22	-5.22	48.00	54.00	-6.00	202	1	AVG
3	7319.686	42.09	6.40	48.49	54.00	-5.51	202	142	AVG
4	7320.513	50.94	6.40	57.34	74.00	-16.66	200	126	peak
5	9772.436	45.45	7.93	53.38	74.00	-20.62	200	117	peak
6	12197.115	43.32	11.12	54.44	74.00	-19.56	200	90	peak
7	12197.115	35.44	11.12	46.56	54.00	-7.44	198	103	AVG

**Operation Mode:** TX / CH High**Test Date:** 2017-5-2**Temperature:** 24°C**Tested by:** Lily.Wang**Humidity:** 48 % RH**Polarity:** Ver. / Hor.**Horizontal**

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Degree (deg.)	Remark
1	4948.942	54.07	-5.15	48.92	54.00	-5.08	203	145	AVG
2	4950.320	63.92	-5.15	58.77	74.00	-15.23	200	150	peak
3	7428.750	42.26	6.50	48.76	54.00	-5.24	198	112	AVG
4	7429.487	52.04	6.50	58.54	74.00	-15.46	200	121	peak
5	12387.628	35.92	11.94	47.86	54.00	-6.14	202	159	AVG
6	12387.820	42.56	11.95	54.51	74.00	-19.49	200	127	peak

Vertical

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Degree (deg.)	Remark
1	4950.320	58.53	-5.15	53.38	74.00	-20.62	200	182	peak
2	7429.205	41.12	6.50	47.62	54.00	-6.38	147	217	AVG
3	7429.487	51.42	6.50	57.92	74.00	-16.08	200	123	peak
4	9908.654	45.33	8.10	53.43	74.00	-20.57	200	121	peak
5	12387.628	36.07	11.94	48.01	54.00	-5.99	202	106	AVG
6	12387.820	44.22	11.95	56.17	74.00	-17.83	200	91	peak

7.6.POWERLINE CONDUCTED EMISSIONS

LIMIT

According to §15.207(a), except as shown in paragraphs (b) and (c) of this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50 μ H/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequency ranges.

Frequency Range (MHz)	Limits (dB μ V)	
	Quasi-peak	Average
0.15 to 0.50	66 to 56*	56 to 46*
0.50 to 5	56	46
5 to 30	60	50

* Decreases with the logarithm of the frequency.

Test Configuration

See test photographs attached in Appendix 1 for the actual connections between EUT and support equipment.

TEST PROCEDURE

- 1.The EUT was placed on a table, which is 0.8m above ground plane.
- 2.Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
- 3.Repeat above procedures until all frequency measured were complete.


TEST RESULTS

The initial step in collecting conducted data is a spectrum analyzer peak scan of the measurement range. Significant peaks are then marked as shown on the following data page, and these signals are then quasi-peaked.

TEST DATA

Job No.:	C170411E02	Date:	2017-4-20
Model No.:	MSDK6149	Time:	9:24:15
Standard:	FCC Class B	Temp.(C)/Hum.(%)	22(C)/48%
Test item:	Conduction test	Test By:	Lily.Wang
Line:	L1	Test Voltage:	AC 120V/60Hz
Model:		Description:	

L1




No.	Frequency (MHz)	QuasiPeak reading (dBuV)	Average reading (dBuV)	Correction factor (dB)	QuasiPeak result (dBuV)	Average result (dBuV)	QuasiPeak limit (dBuV)	Average limit (dBuV)	QuasiPeak margin (dB)	Average margin (dB)	Remark
1	0.1751	26.20	12.54	20.55	46.75	33.09	64.71	54.71	-17.96	-21.62	Pass
2	0.2305	21.77	10.51	20.47	42.24	30.98	62.43	52.43	-20.19	-21.45	Pass
3	0.2859	18.96	9.12	20.50	39.46	29.62	60.64	50.64	-21.18	-21.02	Pass
4	0.3145	18.29	7.76	20.54	38.83	28.30	59.85	49.85	-21.02	-21.55	Pass
5*	0.4302	21.60	9.61	20.51	42.11	30.12	57.25	47.25	-15.14	-17.13	Pass
6	4.6306	11.98	7.13	20.59	32.57	27.72	56.00	46.00	-23.43	-18.28	Pass

Note: 1. L1 = Line One (Live Line) / L2 = Line Two (Neutral Line).

Job No.:	C170411E02	Date:	2017-4-20
Model No.:	MSDK6149	Time:	9:19:12
Standard:	FCC Class B	Temp.(C)/Hum.(%)	22(C)/48%
Test item:	Conduction test	Test By:	Lily.Wang
Line:	L2	Test Voltage:	AC 120V/60Hz
Model:		Description:	

L2



No.	Frequency (MHz)	QuasiPeak reading (dBuV)	Average reading (dBuV)	Correction factor (dB)	QuasiPeak result (dBuV)	Average result (dBuV)	QuasiPeak limit (dBuV)	Average limit (dBuV)	QuasiPeak margin (dB)	Average margin (dB)	Remark
1	0.1729	26.10	13.39	20.38	46.48	33.77	64.82	54.82	-18.34	-21.05	Pass
2	0.2258	21.67	9.57	20.42	42.09	29.99	62.60	52.60	-20.51	-22.61	Pass
3	0.2918	20.87	11.02	20.45	41.32	31.47	60.47	50.47	-19.15	-19.00	Pass
4	0.3543	20.97	10.21	20.47	41.44	30.68	58.86	48.86	-17.42	-18.18	Pass
5*	0.4277	23.55	11.24	20.45	44.00	31.69	57.30	47.30	-13.30	-15.61	Pass
6	4.7451	10.02	4.49	20.73	30.75	25.22	56.00	46.00	-25.25	-20.78	Pass

Note: 1. L1 = Line One (Live Line) / L2 = Line Two (Neutral Line).

Remark:

1. The measuring frequencies range between 0.15 MHz and 30 MHz.
2. The emissions measured in the frequency range between 0.15 MHz and 30 MHz were made with an instrument using Quasi-peak detector and Average detector.
3. "—" denotes the emission level was or more than 2dB below the Average limit, and no re-check was made.
4. The IF bandwidth of SPA between 0.15 MHz and 30 MHz was 10 KHz. The IF bandwidth of Test Receiver between 0.15 MHz and 30 MHz was 9 kHz.

END OF REPORT