

Test Report

FCC ID: 2ALVE-PMO

Date of issue: Apr. 24, 2017

Sample Description:	BLUETOOTH HEADSET
Model(s):	PMO SOUNDBAND, PMO SOUNDBAND BK, PMO SOUNDBAND RE, PMO SOUNDBAND WH, PMO SOUNDBAND GL, PMO SOUNDBAND SV, PMO SOUNDBAND RG
Applicant:	TRI-A Technology and Consulting Co.,Ltd.
Address:	Room 802, No.1009, Yishan Road, Xuhui District, Shanghai, 200233 China
Date of Test:	Apr. 18, 2017 to Apr. 24, 2017

Shenzhen Microtest Co., Ltd.
<http://www.mtitest.com>



This test report is valid for the tested samples only. It cannot be reproduced except in full without prior written consent of Shenzhen Microtest Co., Ltd.

Table of Contents

Table of Contents	2
1 General description	5
1.1 Feature of equipment under test (EUT).....	5
1.2 Operation channel list.....	5
1.3 Test frequency channel.....	5
1.4 EUT operation mode	5
1.5 Test conditions.....	5
1.6 Ancillary equipment list.....	6
1.7 Measurement uncertainty	6
2 Testing site	6
3 List of test equipment	7
4 Test Result	8
4.1 Conducted emission	8
4.2 Antenna requirement	11
4.3 Maximum peak output power	12
4.4 6dB emission bandwidth.....	14
4.5 Power spectral density	16
4.6 Band edge spurious emission	18
4.7 Radiated emission.....	20

Test Result Certification	
Applicant's name:	TRI-A Technology and Consulting Co.,Ltd.
Address:	Room 802, No.1009, Yishan Road, Xuhui District, Shanghai, 200233 China
Manufacture's Name:	Dongguan Sambon Electronics Co., Ltd.
Address:	No.2-52, Xihu Industry Area, Lincun Village, Tangxia Town, Dongguan City, Guangdong Province, China
Product name:	BLUETOOTH HEADSET
Trademark:	N/A
Model name:	PMO SOUNDBAND, PMO SOUNDBAND BK, PMO SOUNDBAND RE, PMO SOUNDBAND WH, PMO SOUNDBAND GL, PMO SOUNDBAND SV, PMO SOUNDBAND RG
Standards:	FCC Part 15.247
Test Procedure:	ANSI C63.10-2013 558074 D01 DTS Meas Guidance v03r05

This device described above has been tested by Shenzhen Toby Technology Co., Ltd. and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

Tested by:

Sang di Huang

Sangdi Huang

Apr. 24, 2017

Reviewed by:

Leon Chen

Leon Chen

Apr. 24, 2017

Approved by:

Tom Xue

Tom Xue

Apr. 24, 2017

Summary of Test Result

Item	FCC Part No.	Description of Test	Result
1	15.203	Antenna requirement	Pass
2	15.207	AC power line conducted emission	Pass
3	15.247(b)(3)	Maximum peak output power	Pass
4	15.247(a)(2)	6dB emission bandwidth	Pass
5	15.247(e)	Power spectral density (PSD)	Pass
8	15.247(d)	Band edge spurious emission	Pass
9	15.247(d), 15.205, 15.209	Radiated emission	Pass

1 General description

1.1 Feature of equipment under test (EUT)

Product name:	BLUETOOTH HEADSET
Model name:	PMO SOUNDBAND, PMO SOUNDBAND BK, PMO SOUNDBAND RE, PMO SOUNDBAND WH, PMO SOUNDBAND GL, PMO SOUNDBAND SV, PMO SOUNDBAND RG
Operating frequency range:	Tx/Rx: 2402MHz~2480MHz
Bluetooth version:	V4.1 Dual mode
Modulation type:	GFSK
Power source:	DC 3.7V by battery
Antenna designation:	Chip antenna (Antenna Gain: 1.25dBi)

1.2 Operation channel list

Channel	Frequency	Channel	Frequency	Channel	Frequency
0	2402MHz	10	2422MHz	20	2442MHz
1	2404MHz	11	2424MHz	21	2444MHz
---	---	---	---	---	---
---	---	---	---	---	---
8	2418MHz	18	2438MHz	38	2478MHz
9	2420MHz	19	2440MHz	39	2480MHz

1.3 Test frequency channel

Low	2402MHz
Middle	2442MHz
High	2480MHz

1.4 EUT operation mode

During testing, RF test program provided by the manufacture to control the Tx operation followed the test requirement. The EUT is configured to transmit continuously (duty cycle > 98 %) at the maximum power control level.

1.5 Test conditions

During the measurement the environmental conditions were within the listed ranges:

- Temperature: 20°C~30°C
- Humidity: 30%~70%
- Atmospheric pressure: 98kPa~101kPa

1.6 Ancillary equipment list

Equipment	Model Name	S/N	Manufacturer	Certificate type
Adapter	HW-050200U01	/	HUAWEI	FCC VOC

1.7 Measurement uncertainty

Measurement Uncertainty for a Level of Confidence of 95 %, $U=2 \times U_c(y)$

RF frequency	1×10^{-7}
RF power, conducted	± 1 dB
Conducted emission(150kHz~30MHz)	± 2.5 dB
Radiated emission(30MHz~1GHz)	± 4.2 dB
Radiated emission (above 1GHz)	± 4.3 dB
Temperature	± 1 degree
Humidity	± 5 %

2 Testing site

Test Site	Shenzhen Toby Technology Co., Ltd.
Test Site Location	1 A/F., Bldg.6, Yusheng Industrial Zone The National Road No.107 Xixiang Section 467, Shenzhen, Guangdong, China
FCC Registration No.:	811562
CNAS Registration No.:	CNAS L5813

3 List of test equipment

For AC power line conducted emission:

Equipment	Manufacturer	Model	Serial No.	Calibration Due
LISN	R&S	ENV216	101313	2017.12.06
LISN	SCHWARZBECK	NNLK 8129	8129245	2017.12.25
Pulse Limiter	SCHWARZBECK	VTSD 9561F	9716	2017.12.25
Test Cable	N/A	N/A	C01	2017.12.06
EMI Test Receiver	R&S	ESCI	101160	2017.12.06

For Radiated emission:

Equipment	Manufacturer	Model	Serial No.	Calibration Due
Log-Bicon Antenna	MESS-ELEKTRONIK	VULB 9160	3058	2017.12.11
Horn Antenna	Schwarzbeck	BBHA 9120D	631	2017.12.05
Horn Antenna	Schwarzbeck	BBHA 9170	373	2017.12.05
Test Cable	United Microwave	57793	1m	2017.12.05
Test Cable	United Microwave	A30A30-5006	10m	2017.12.05
Microwave Pre-amplifier	Agilent	8449B	3008A01714	2017.12.05
Pre-Amplifier	Anritsu	MH648A	M09961	2017.12.05
EMI Test Receiver	R&S	ESPI-7	101318	2017.12.05
Spectrum analyzer	Agilent	E4470B	MY41441082	2017.06.01
Spectrum analyzer	Agilent	N9020A	MY49100060	2018.03.03

For RF conducted emission:

Equipment	Manufacturer	Model	Serial No.	Calibration Due
EMI Test Receiver	R&S	ESCI	101160	2017.12.06

Note: the calibration interval of the above test instruments is 12 months and the calibrations are traceable to international system unit (SI).

4 Test Result

4.1 Conducted emission

4.1.1 Limit

Frequency (MHz)	Limit	
	Quasi-peak	Average
0.15-0.5	66 to 56	56 to 46
0.5-5	56	46
5-30	60	50


Note: Decreases with the logarithm of the frequency from 0.15MHz to 0.5MHz.

4.1.2 Test method

1. The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipment powered from additional LISN(s). The LISN provide 50 Ohm/50uH of coupling impedance for the measuring instrument.
2. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
3. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
4. LISN at least 80 cm from nearest part of EUT chassis.
5. The resolution bandwidth of EMI test receiver is set at 9kHz.


4.1.3 Test Result

Temperature:	26℃	Relative Humidity:	47%
Pressure:	101kPa	Polarization:	L
Test voltage:	AC 120V/60Hz	Test mode:	Transmitting



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1		0.1737	41.98	-0.03	41.95	64.78	-22.83	QP	
2		0.1737	24.85	-0.03	24.82	54.78	-29.96	AVG	
3		0.4778	33.84	-0.03	33.81	56.38	-22.57	QP	
4	*	0.4778	26.47	-0.03	26.44	46.38	-19.94	AVG	
5		1.1700	35.26	-0.04	35.22	56.00	-20.78	QP	
6		1.1700	25.98	-0.04	25.94	46.00	-20.06	AVG	
7		2.6099	30.36	-0.05	30.31	56.00	-25.69	QP	
8		2.6099	21.64	-0.05	21.59	46.00	-24.41	AVG	
9		3.9180	31.12	-0.05	31.07	56.00	-24.93	QP	
10		3.9180	20.97	-0.05	20.92	46.00	-25.08	AVG	
11		10.1700	32.78	-0.09	32.69	60.00	-27.31	QP	
12		10.1700	19.10	-0.09	19.01	50.00	-30.99	AVG	

Temperature:	26℃	Relative Humidity:	47%
Pressure:	101kPa	Polarization:	N
Test voltage:	AC 120V/60Hz	Test mode:	Transmitting



No.	Mk.	Freq. MHz	Reading Level dBμV	Correct Factor dB	Measure- ment dBμV	Limit dBμV	Over dB	Detector	Comment
1		0.1700	37.58	-0.03	37.55	64.96	-27.41	QP	
2		0.1700	21.96	-0.03	21.93	54.96	-33.03	AVG	
3		0.3019	26.77	-0.03	26.74	60.19	-33.45	QP	
4		0.3019	16.44	-0.03	16.41	50.19	-33.78	AVG	
5		0.4580	29.18	-0.03	29.15	56.73	-27.58	QP	
6		0.4580	18.77	-0.03	18.74	46.73	-27.99	AVG	
7	*	1.4900	33.14	-0.04	33.10	56.00	-22.90	QP	
8		1.4900	20.57	-0.04	20.53	46.00	-25.47	AVG	
9		2.6139	30.93	-0.05	30.88	56.00	-25.12	QP	
10		2.6139	20.29	-0.05	20.24	46.00	-25.76	AVG	
11		3.8660	30.49	-0.05	30.44	56.00	-25.56	QP	
12		3.8660	20.63	-0.05	20.58	46.00	-25.42	AVG	

4.2 Antenna requirement

4.2.1 Requirement defined in FCC 15.203

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §15.211, §15.213, §15.217, §15.219, or §15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

4.2.2 EUT antenna description

The antenna of EUT is a permanently attached Chip antenna; the maximum gain of the antenna is 1.25dBi. So the antenna meets the requirement of this part.

4.3 Maximum peak output power

4.3.1 Limits

Conducted peak output power limit is 1W (30dBm).

4.3.2 Test Method

Use the following spectrum analyzer settings:

RBW = 1MHz($\geq$ 6dB bandwidth, see section 4.4)

VBW $\geq$ 3RBW

Detector = peak

Trace mode = max hold

Sweep time = auto couple

Allow trace to fully stabilize.


Use peak marker function to determine the peak amplitude level.

4.3.3 Test Result


Frequency (MHz)	Peak output power (dBm)	Limit (dBm)
2402	-2.412	30
2442	-0.919	30
2480	-2.217	30

Test plots as below:


2402MHz



2442MHz



2480MHz



4.4 6dB emission bandwidth

4.4.1 Limits

The minimum 6 dB bandwidth shall be at least 500 kHz.

4.4.2 Test method

Use the following spectrum analyzer settings:

RBW = 100kHz

VBW $\geq$ 3RBW

Detector = peak

Trace mode = max hold

Sweep time = auto couple


Allow the trace to stabilize, measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

4.4.3 Test result


Frequency (MHz)	6dB emission bandwidth (MHz)	Limit
2402	0.695	500kHz
2442	0.694	
2480	0.695	

Test plots as below:


2402MHz



2442MHz



2480MHz



4.5 Power spectral density

4.5.1 Limits

The power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3kHz band during any time interval of continuous transmission.

4.5.2 Test method

Span = 1.5 times DTS bandwidth (6dB emission bandwidth, see section 4.4)

RBW = 3kHz to 100kHz

VBW $\geq$ 3RBW

Detector = peak

Sweep time = auto

Trace mode = max hold


Allow the trace to stabilize. Use the peak marker function to determine the maximum amplitude level within the RBW.

4.5.3 Test result


Frequency (MHz)	PSD (dBm/100kHz)	Limit (dBm/3kHz)
2402	-2.718	8
2442	-1.403	
2480	-2.506	

Test plots as below:


2402MHz



2442MHz



2480MHz



4.6 Band edge spurious emission

4.6.1 Limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits.

4.6.2 Test method


Use the following spectrum analyser settings:

Set RBW=100 kHz. VBW $\geq$ 3RBW. Detector = peak, Sweep time = auto couple, Trace mode = max hold.


4.6.3 Test Result

Test plots as below:

Low edge



Up edge



4.7 Radiated emission

4.7.1 Limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. Attenuation below the general limits defined in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits defined in §15.209(a).

Radiated emission limits defined in FCC 15.209:

Frequency (MHz)	Field strength $\mu\text{V/m}$	Field strength $\text{dB}\mu\text{V/m}$	Detector	Measurement distance
30-88	100	40	QP	3m
88-216	150	43.5	QP	
216-960	200	46	QP	
960-1000	500	46	QP	
Above 1000	500	54	AV	
Above 1000	5000	74	PK	

Restricted bands defined in FCC 15.205:

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	Above 38.6
13.36-13.41			

4.7.2 Test method

1. The EUT is placed on a turntable, which is 0.8m above ground plane for test frequency range below 1GHz, and 1.5m above ground plane for test frequency range above 1GHz.
2. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.
3. Use the following spectrum analyzer settings:

Span = wide enough to fully capture the emission being measured, RBW = 1 MHz for $f \geq 1\text{GHz}$, 100 kHz for $f < 1\text{GHz}$, VBW $\geq$ RBW, Sweep = auto, Detector function = peak, Trace = max hold
4. Follow the guidelines in ANSI C63.4-2014 with respect to maximizing the emission by rotating the EUT, adjusting the measurement antenna height and polarization, etc. The peak reading of the emission, after being corrected by the antenna factor, cable loss, pre-amp gain, etc., is the peak field strength, submit this data. Each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
5. The peak level, once corrected, must comply with the limit specified in Section 15.209. Set the RBW = 1MHz, VBW = 3MHz, Detector = RMS for AV value, while maintaining all of the other instrument settings.
6. The three orthogonal axis (x, y, z) are pre-tested, only the worst emission were reported

4.7.3 Test Result

Transmitter channel: 2402MHz					
Frequency	Ant. Polarization	Emission level	Limits	Detector	Result
(MHz)	H / V	dBμV/m	dBμV/m		
159.78	V	32.2	43.5	QP	Pass
159.78	H	34.3	43.5	QP	
2390	V	46.73	74	PK	
2390	H	48.34	74	PK	
4804	V	50.12	74	PK	
4804	H	50.74	74	PK	
Transmitter channel: 2442MHz					
Frequency	Ant. Polarization	Emission level	Limits	Detector	Result
(MHz)	H / V	dBμV/m	dBμV/m		
159.78	V	31.6	43.5	QP	Pass
159.78	H	33.1	43.5	QP	
4884	V	50.59	74	PK	
4884	H	51.24	74	PK	
Transmitter channel: 2480MHz					
Frequency	Ant. Polarization	Emission level	Limits	Detector	Result
(MHz)	H / V	dBμV/m	dBμV/m		
159.78	V	32.2	43.5	QP	Pass
159.78	H	34.4	43.5	QP	
2483.5	V	46.91	74	PK	
2483.5	H	48.76	74	PK	
4960	V	50.23	74	PK	
4960	H	50.86	74	PK	

Note: If the PK measured values lower than average mode limit, the EUT shall be deemed to meet average limits and then no additional average mode measurement performed.

----END OF REPORT----