

Appendix B

Highest Test Plots

Table of Contents

1. 2.4G Head-worn 0mm SAR 3

1. 2.4G Head-worn 0mm SAR

Date: 30.07.2026

Test Laboratory: Guangdong Dongdian Testing Service Co., Ltd.

Q26070611-2E

Serial: S26070611-011

Communication System: UID 0, Bluetooth (0); Communication System Band: Bluetooth; Frequency: 2480 MHz; Communication System PAR: 0 dB; PMF: 1.12202e-005

Medium parameters used: $f = 2480$ MHz; $\sigma = 1.755$ S/m; $\epsilon_r = 39.782$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2011)

DASY Configuration:

- Probe: EX3DV4 - SN3906; ComF(7.91, 7.91, 7.91) @ 2480 MHz; Calibrated: 22.06.2026
- Sensor-Surface: 1.4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn1366; Calibrated: 22.06.2026
- Phantom: ELI v5.0; Type: QDOVA002AA; Serial: TP:1197
- DASY52 52.10.4(1535); SEMCAD X 14.6.14(7501)

Configuration/L front side DHS 2480 MHz/Area Scan (9x9x1): Measurement grid: $dx=10$ mm, $dy=10$ mm

Maximum value of SAR (measured) = 0.0368 W/kg

Configuration/L front side DHS 2480 MHz/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 4.529 V/m; Power Drift = 0.12 dB


Peak SAR (extrapolated) = 0.0680 W/kg

SAR(1 g) = 0.025 W/kg; SAR(10 g) = 0.011 W/kg

Smallest distance from peaks to all points 3 dB below: Larger than measurement grid (> 15 mm)

Ratio of SAR at M2 to SAR at M1 = 39.8%

Maximum value of SAR (measured) = 0.0490 W/kg



Date: 30.07.2026

Test Laboratory: Guangdong Dongdian Testing Service Co., Ltd.

Q26070611-2E

Serial: S26070611-011

Communication System: UID 0, Bluetooth (0); Communication System Band: Bluetooth; Frequency: 2480 MHz;Communication System PAR: 0 dB; PMF: 1.12202e-005

Medium parameters used: $f = 2480\text{ MHz}$; $\sigma = 1.755\text{ S/m}$; $\epsilon_r = 39.782$; $\rho = 1000\text{ kg/m}^3$

Phantom section: Flat Section

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2011)

DASY Configuration:

- Probe: EX3DV4 - SN3906; ComF(7.91, 7.91, 7.91) @ 2480 MHz; Calibrated: 22.06.2026
- Sensor-Surface: 1.4mm (Mechanical Surface Detection), $z = 1.0, 31.0$
- Electronics: DAE4 Sn1366; Calibrated: 22.06.2026
- Phantom: ELI v5.0; Type: QDOVA002AA; Serial: TP:1197
- DASY52 52.10.4(1535); SEMCAD X 14.6.14(7501)

Configuration/R back side 2DH5 2480 MHz/Area Scan (9x9x1): Measurement grid: $dx=10\text{mm}$, $dy=10\text{mm}$
Maximum value of SAR (measured) = 0.0359 W/kg

Configuration/R back side 2DH5 2480 MHz/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$
Reference Value = 1.679 V/m; Power Drift = 0.13 dB
Peak SAR (extrapolated) = 0.115 W/kg
SAR(1 g) = 0.020 W/kg; SAR(10 g) = 0.00692 W/kg
Smallest distance from peaks to all points 3 dB below: Larger than measurement grid ($> 15\text{ mm}$)
Ratio of SAR at M2 to SAR at M1 = 39%
Maximum value of SAR (measured) = 0.0386 W/kg

