

TEST REPORT

Application No.: SZCR2601000199AT
Applicant: Cosonic Intelligent Technologies Co.,Ltd.
Address of Applicant: NO.3 Keyuan Road, Songshan Lake District, Dongguan, Guangdong 523808 China
Manufacturer: Cosonic Intelligent Technologies Co.,Ltd.
Address of Manufacturer: NO.3 Keyuan Road, Songshan Lake District, Dongguan City, Guangdong Province
Factory: COSONIC VIETNAM COMPANY LIMITED
Address of Factory: Lot C51, Ba Thien II Industrial Park, Thien Ke Ward, Binh Xuyen District, Vinh Phuc Province, Vietnam

Equipment Under Test (EUT):

EUT Name: Wireless earphones
Model No.: AABLK36017613, AAWHT36017613 ♣
 ♣ Please refer to section 2 of this report which indicates which model was actually tested and which were electrically identical.
Trade Mark: ONN
FCC ID: 2ALVK-ONN36017613
Standard(s) : 47 CFR Part 15, Subpart C 15.247
Date of Receipt: 2026-01-13
Date of Test: 2026-02-15 to 2026-03-13
Date of Issue: 2026-03-18

Test Result:	Pass*
---------------------	--------------

* In the configuration tested, the EUT complied with the standards specified above.

Keny Xu

Keny Xu
EMC Laboratory Manager




SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/2

Report No.: SZCR260100019903

Page: 2 of 100

Revision Record				
Version	Chapter	Date	Modifier	Remark
01		2026-03-18		Original

Authorized for issue by:				
				
		Bill Chen/Project Engineer		
				
		Eric Fu/Reviewer		



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Testing & Calibration Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

2 Test Summary

Radio Spectrum Technical Requirement				
Item	Standard	Method	Requirement	Result
Antenna Requirement	47 CFR Part 15, Subpart C 15.247	N/A	47 CFR Part 15, Subpart C 15.203 & 15.247(b)(4)	Pass

Radio Spectrum Matter Part				
Item	Standard	Method	Requirement	Result
Radiated Emissions which fall in the restricted bands	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2020) Section 6.10.5 & 11.12	47 CFR Part 15, Subpart C 15.205 & 15.209	Pass
Radiated Spurious Emissions Below 1GHz		ANSI C63.10 (2020) Section 6.4,6.5	47 CFR Part 15, Subpart C 15.205 & 15.209	Pass
Radiated Spurious Emissions Above 1GHz		ANSI C63.10 (2020) Section 6.6 & 11.12	47 CFR Part 15, Subpart C 15.205 & 15.209	Pass
Maximum Conducted Output Power		ANSI C63.10 (2020) Section 11.9.1	47 CFR Part 15, Subpart C 15.247(b)(3)	Pass
Minimum 6dB Bandwidth		ANSI C63.10 (2020) Section 11.8.1	47 CFR Part 15, Subpart C 15.247a(2)	Pass
Power Spectral Density		ANSI C63.10 (2020) Section 11.10.2	47 CFR Part 15, Subpart C 15.247(e)	Pass
Conducted Band Edges Measurement		ANSI C63.10 (2020) Section 6.10.4	47 CFR Part 15, Subpart C 15.247(d)	Pass
Conducted Spurious Emissions		ANSI C63.10 (2020) Section 11.11	47 CFR Part 15, Subpart C 15.247(d)	Pass

Declaration of EUT Family Grouping:

Model No.: AABLK36017613, AAWHT36017613

Only the model AABLK36017613 was tested, since according to the declaration from the applicant, the electrical circuit design, PCB layout, components used and internal wiring and functions were identical for the above models, with only difference being of color.



3 Contents

	Page
1 Cover Page	1
2 Test Summary	3
3 Contents	4
4 General Information	6
4.1 Details of E.U.T.	6
4.2 Description of Support Units	6
4.3 Measurement Uncertainty	6
4.4 Test Location	7
4.5 Test Facility	7
4.6 Deviation from Standards	7
4.7 Abnormalities from Standard Conditions	7
5 Equipment List	8
6 Radio Spectrum Technical Requirement	10
6.1 Antenna Requirement	10
6.1.1 Test Requirement:	10
6.1.2 Conclusion	10
7 Radio Spectrum Matter Test Results	11
7.1 Radiated Emissions which fall in the restricted bands	11
7.1.1 E.U.T. Operation	11
7.1.2 Test Mode Description	12
7.1.3 Test Setup Diagram	12
7.1.4 Measurement Procedure and Data	13
7.2 Radiated Spurious Emissions Below 1GHz	22
7.2.1 E.U.T. Operation	22
7.2.2 Test Mode Description	23
7.2.3 Test Setup Diagram	23
7.2.4 Measurement Procedure and Data	24
7.3 Radiated Spurious Emissions Above 1GHz	29
7.3.1 E.U.T. Operation	29
7.3.2 Test Mode Description	29
7.3.3 Test Setup Diagram	30
7.3.4 Measurement Procedure and Data	30
7.4 Maximum Conducted Output Power	44
7.4.1 E.U.T. Operation	44
7.4.2 Test Mode Description	44
7.4.3 Test Setup Diagram	45
7.4.4 Measurement Procedure and Data	45
7.5 Minimum 6dB Bandwidth	46
7.5.1 E.U.T. Operation	46



SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/2

Report No.: SZCR260100019903

Page: 5 of 100

7.5.2	Test Mode Description	46
7.5.3	Test Setup Diagram	46
7.5.4	Measurement Procedure and Data.....	46
7.6	Power Spectral Density	47
7.6.1	E.U.T. Operation	47
7.6.2	Test Mode Description	47
7.6.3	Test Setup Diagram	47
7.6.4	Measurement Procedure and Data.....	47
7.7	Conducted Band Edges Measurement	48
7.7.1	E.U.T. Operation	48
7.7.2	Test Mode Description	48
7.7.3	Test Setup Diagram	49
7.7.4	Measurement Procedure and Data.....	49
7.8	Conducted Spurious Emissions	50
7.8.1	E.U.T. Operation	50
7.8.2	Test Mode Description	50
7.8.3	Test Setup Diagram	51
7.8.4	Measurement Procedure and Data.....	51
8	Test Setup Photo	52
9	EUT Constructional Details (EUT Photos)	52
10	Appendix.....	53



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Inspection & Testing Services Laboratory

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

4 General Information

4.1 Details of E.U.T.

Power supply:	Lithium Ion Battery: DC 3.85V 36mAh 0.1386Wh rechargeable battery which charged by charging case for left earbud and right earbud Lithium Ion Battery: DC 3.7V 610mAh rechargeable battery which charged by USB port for charging case
Cable(s):	Type C cable: 23cm unshielded
Operation Frequency:	2402MHz to 2480MHz
Modulation Type:	GFSK
Number of Channels:	40
Channel Spacing:	2MHz
Antenna Type:	FPC Antenna
Antenna Gain:	Left earbud:-2.45dBi Right earbud:-3.04dBi

Remark: The information in this section is provided by the applicant or manufacturer, SGS is not liable to the accuracy, suitability, reliability or/and integrity of the information.

4.2 Description of Support Units

Description	Manufacturer	Model No.	Serial No.
--	--	--	--

The EUT has been tested as an independent unit.

4.3 Measurement Uncertainty

Test Item	Measurement Uncertainty
Radiated Emissions which fall in the restricted bands	$\pm 6.0\text{dB}$ (Below 1GHz); $\pm 4.6\text{dB}$ (Above 1GHz)
Radiated Spurious Emissions Below 1GHz	$\pm 6.0\text{dB}$ for 3m; $\pm 5.0\text{dB}$ for 10m
Radiated Spurious Emissions Above 1GHz	$\pm 4.6\text{dB}$ (1-18GHz); $\pm 4.8\text{dB}$ (18-40GHz)
Maximum Conducted Output Power	$\pm 0.4\text{dB}$
Minimum 6dB Bandwidth	$\pm 0.3\%$
Power Spectral Density	$\pm 0.4\text{dB}$
Conducted Band Edges Measurement	$\pm 2.7\text{dB}$
Conducted Spurious Emissions	$\pm 2.7\text{dB}$

Remark:

The U_{lab} (lab Uncertainty) is less than $U_{\text{CISPR/ETSI}}$ (CISPR/ETSI Uncertainty), so the test results
 – compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit;
 – non-compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit.

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/2

Report No.: SZCR260100019903

Page: 7 of 100

4.4 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen Branch

No. 1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China. 518057.

Tel: +86 755 2601 2053 Fax: +86 755 2671 0594

No tests were sub-contracted.

4.5 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

• A2LA (Certificate No. 3816.01)

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 3816.01.

• VCCI (Member No. 1937)

The 3m Fully-anechoic chamber for above 1GHz, 10m Semi-anechoic chamber for below 1GHz, Shielded Room for Mains Port Conducted Interference Measurement and Telecommunication Port Conducted Interference Measurement of SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen EMC laboratory have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-20026, R-14188, C-12383 and T-11153 respectively.

• FCC –Designation Number: CN1336

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized as an accredited testing laboratory.

Designation Number: CN1336. Test Firm Registration Number: 787754.

• Innovation, Science and Economic Development Canada

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized by ISED as an accredited testing laboratory.

CAB identifier: CN0006.

IC#: 4620C.

4.6 Deviation from Standards

None

4.7 Abnormalities from Standard Conditions

None



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch EMC Laboratory

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.ssgroup.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

5 Equipment List

Radiated Emissions which fall in the restricted bands					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
3m Fully-Anechoic Chamber	AUDIX	N/A	SEM001-02	2025-05-07	2028-05-06
Signal Analyzer	Rohde & Schwarz	FSV40	SEM008-04	2026-02-02	2027-02-01
Horn Antenna	Rohde&Schwarz	HF907	SEM003-07	2025-07-22	2026-07-21
Microwave system amplifier	Agilent	83017A	SEM005-25	2025-09-10	2026-09-09
Measurement Software	AUDIX	e3 V8.2014-6-27	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM026-01	2025-07-05	2026-07-04
Broad-Band Horn Antenna	Schwarzbeck	BBHA 9170	SEM003-15	2025-07-22	2027-07-21
Pre-Amplifier	Compliance Directions Systems Inc.	PAP-2640-50	SEM005-08	2025-03-21	2026-03-20

Radiated Spurious Emissions Below 1GHz					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
Loop Antenna	ETS-Lindgren	6502	SEM003-08	2025-11-17	2027-11-16
3m Semi-Anechoic Chamber	ETS-LINDGREN	N/A	SEM001-01	2023-06-19	2026-06-18
MXE EMI Receiver	Agilent Technologies	N9038A	SEM004-15	2025-07-25	2026-07-24
BiConiLog Antenna	ETS-LINDGREN	3142C	SEM003-01	2025-08-29	2027-08-28
Pre-Amplifier	Agilent Technologies	8447D	SEM005-01	2026-02-02	2027-02-01
Measurement Software	AUDIX	e3 V8.2014-6-27	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM025-01	2025-07-05	2026-07-04



SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/2

Report No.: SZCR260100019903

Page: 9 of 100

Radiated Spurious Emissions Above 1GHz					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
3m Fully-Anechoic Chamber	AUDIX	N/A	SEM001-02	2025-05-07	2028-05-06
Signal Analyzer	Rohde & Schwarz	FSV40	SEM008-04	2026-02-02	2027-02-01
Horn Antenna	Rohde&Schwarz	HF907	SEM003-07	2025-07-22	2026-07-21
Microwave system amplifier	Agilent	83017A	SEM005-25	2025-09-10	2026-09-09
Measurement Software	AUDIX	e3 V8.2014-6-27	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM026-01	2025-07-05	2026-07-04
Broad-Band Horn Antenna	Schwarzbeck	BBHA 9170	SEM003-15	2025-07-22	2027-07-21
Pre-Amplifier	Compliance Directions Systems Inc.	PAP-2640-50	SEM005-08	2025-03-21	2026-03-20

RF Conducted Test					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
Power Sensor	TST PASS	TSPS2023R	SEM009-26	2026-02-04	2027-02-03
Power Sensor	KEYSIGHT	U2021XA	SEM009-16	2026-02-04	2027-02-03
DC Power Supply	Chroma	62012P-80-60	SEM011-11	2025-07-24	2026-07-23
MXA Signal Analyzer	KEYSIGHT	N9020A	SEM004-19	2026-02-03	2027-02-02
Measurement Software	TST PASS	TST PASS V2.0	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM031-01	2025-07-05	2026-07-04
Attenuator	Huber+Suhner	6620_SMA-50-1	SEM021-09	2026-02-02	2027-02-01

General used equipment					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
Humidity/ Temperature Indicator	deli	8838	SEM002-32	2025-07-23	2026-07-22
Humidity/ Temperature Indicator	deli	8838	SEM002-33	2025-07-23	2026-07-22
Barometer	Changchun Meteorological Industry Factory	DYM3	SEM002-01	2026-02-14	2027-02-13



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch Laboratory
 No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
 中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

6 Radio Spectrum Technical Requirement

6.1 Antenna Requirement

6.1.1 Test Requirement:

47 CFR Part 15, Subpart C 15.203 & 15.247(b)(4)

6.1.2 Conclusion

Standard Requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

15.247(b) (4) requirement:

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

EUT Antenna:

The antenna is integrated on the main PCB and no consideration of replacement. The best case gain of the antenna is Left earbud:-2.45dBi Right earbud:-3.04dBi.

Antenna location: Refer to internal photo.



7 Radio Spectrum Matter Test Results

7.1 Radiated Emissions which fall in the restricted bands

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.209
 Test Method: ANSI C63.10 (2020) Section 6.10.5 & 11.12
 Measurement Distance: 3m
 Test Engineer: Tommy Luo

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

7.1.1 E.U.T. Operation

Operating Environment:


Temperature: 21.5 °C Humidity: 51.2 % RH Atmospheric Pressure: 1010 mbar



7.1.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	04	TX mode(1Mbps)(Left earbud)_Keep the EUT in continuously transmitting mode with GFSK modulation.
Final test	05	TX mode(2Mbps)(Left earbud)_Keep the EUT in continuously transmitting mode with GFSK modulation.
Final test	06	TX mode(1Mbps)(Right earbud)_Keep the EUT in continuously transmitting mode with GFSK modulation.
Final test	07	TX mode(2Mbps)(Right earbud)_Keep the EUT in continuously transmitting mode with GFSK modulation.

7.1.3 Test Setup Diagram



7.1.4 Measurement Procedure and Data

- a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- g. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- h. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- j. Repeat above procedures until all frequencies measured was complete.

Remark 1: Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor

Remark 2: For frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Testing and Calibration Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com


BLE_1M_TX_CH_00_Horizontal-Peak



Site : chamber
Condition: 3m HORIZONTAL
Job No : 00199AT00200AT
Mode : 2402 Band edge
BLE 1M L

Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark	Aux Factor
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB		dB
1 2370.093	16.10	29.10	32.79	34.58	46.99	74.00	-27.01	Peak	0.00
2 2390.000	16.13	29.10	32.78	31.93	44.38	74.00	-29.62	Peak	0.00
3 p 2402.000	16.15	29.09	32.77	80.89	93.36	74.00	19.36	Peak	0.00


BLE_1M_TX_CH_00_Horizontal-AVG



Site : chamber
Condition: 3m HORIZONTAL
Job No : 00199AT00200AT
Mode : 2402 Band edge
BLE 1M L

Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark	Aux Factor
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB		dB
1 2371.701	16.11	29.10	32.79	21.94	34.36	54.00	-19.64	Average	0.00
2 2390.000	16.13	29.10	32.78	21.68	34.13	54.00	-19.87	Average	0.00
3 q 2402.000	16.15	29.09	32.77	73.80	86.27	54.00	32.27	Average	0.00


BLE_1M_TX_CH_00_Vertical-Peak



Site : chamber
Condition: 3m VERTICAL
Job No : 00199AT00200AT
Mode : 2402 Band edge
BLE 1M L

Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark	Aux Factor
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB		dB
1 2372.505	16.11	29.10	32.79	35.27	47.69	74.00	-26.31	Peak	0.00
2 2390.000	16.13	29.10	32.78	32.32	44.77	74.00	-29.23	Peak	0.00
3 p 2402.000	16.15	29.09	32.77	75.81	88.28	74.00	14.28	Peak	0.00

BLE_1M_TX_CH_00_Vertical-AVG



Site : chamber
Condition: 3m VERTICAL
Job No : 00199AT00200AT
Mode : 2402 Band edge
BLE 1M L

Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark	Aux Factor
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB		dB
1 2389.659	16.13	29.10	32.78	21.72	34.17	54.00	-19.83	Average	0.00
2 2390.000	16.13	29.10	32.78	21.41	33.86	54.00	-20.14	Average	0.00
3 q 2402.000	16.15	29.09	32.77	66.79	79.26	54.00	25.26	Average	0.00




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com


BLE_1M_TX_CH_39_Horizontal-Peak



Site : chamber
Condition: 3m HORIZONTAL
Job No : 00199AT00200AT
Mode : 2480 Band edge
BLE 1M L

Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over	Remark	Aux Factor
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB		dB
1 p 2480.000	16.27	28.90	32.73	84.57	97.01	74.00	23.01	Peak	0.00
2 2483.500	16.28	28.90	32.73	34.18	46.63	74.00	-27.37	Peak	0.00
3 2486.094	16.28	28.90	32.73	34.64	47.09	74.00	-26.91	Peak	0.00


BLE_1M_TX_CH_39_Horizontal-AVG



Site : chamber
Condition: 3m HORIZONTAL
Job No : 00199AT00200AT
Mode : 2480 Band edge
BLE 1M L

Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over	Remark	Aux Factor
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB		dB
1 q 2480.000	16.27	28.90	32.73	73.56	86.00	54.00	32.00	Average	0.00
2 2483.500	16.28	28.90	32.73	22.72	35.17	54.00	-18.83	Average	0.00
3 2483.646	16.28	28.90	32.73	22.64	35.09	54.00	-18.91	Average	0.00


BLE_1M_TX_CH_39_Vertical-Peak



Site : chamber
Condition: 3m VERTICAL
Job No : 00199AT00200AT
Mode : 2480 Band edge
BLE 1M L

Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over	Remark	Aux Factor
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB		dB
1 p 2480.000	16.27	28.90	32.73	78.03	90.47	74.00	16.47	Peak	0.00
2 2483.500	16.28	28.90	32.73	32.98	45.43	74.00	-28.57	Peak	0.00
3 2498.091	16.30	28.90	32.73	35.28	47.75	74.00	-26.25	Peak	0.00

BLE_1M_TX_CH_39_Vertical-AVG




Site : chamber
Condition: 3m VERTICAL
Job No : 00199AT00200AT
Mode : 2480 Band edge
BLE 1M L

Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over	Remark	Aux Factor
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB		dB
1 q 2480.000	16.27	28.90	32.73	68.63	81.07	54.00	27.07	Average	0.00
2 2483.500	16.28	28.90	32.73	21.68	34.13	54.00	-19.87	Average	0.00
3 2491.873	16.29	28.90	32.73	22.08	34.54	54.00	-19.46	Average	0.00




BLE_2M_TX_CH_00_Horizontal-Peak



Site : chamber
Condition: 3m HORIZONTAL
Job No : 00199AT00200AT
Mode : 2402 Band edge
BLE 2M L

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over	Remark	Aux Factor
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB		dB
1	2376.530	16.11	29.10	32.79	33.98	46.49	74.00	-27.60	Peak	0.00
2	2390.000	16.13	29.10	32.78	32.59	45.04	74.00	-28.96	Peak	0.00
3 p	2402.000	16.15	29.09	32.77	80.69	93.16	74.00	19.16	Peak	0.00


BLE_2M_TX_CH_00_Horizontal-AVG



Site : chamber
Condition: 3m HORIZONTAL
Job No : 00199AT00200AT
Mode : 2402 Band edge
BLE 2M L

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over	Remark	Aux Factor
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB		dB
1	2373.511	16.11	29.10	32.79	21.02	34.24	54.00	-19.76	Average	0.00
2	2390.000	16.13	29.10	32.78	21.37	33.82	54.00	-20.18	Average	0.00
3 q	2402.000	16.15	29.09	32.77	61.30	73.77	54.00	19.77	Average	0.00


BLE_2M_TX_CH_00_Vertical-Peak



Site : chamber
Condition: 3m VERTICAL
Job No : 00199AT00200AT
Mode : 2402 Band edge
BLE 2M L

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over	Remark	Aux Factor
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB		dB
1	2371.002	16.11	29.10	32.79	34.12	46.54	74.00	-27.46	Peak	0.00
2	2390.000	16.13	29.10	32.78	31.72	44.17	74.00	-29.83	Peak	0.00
3 p	2402.000	16.15	29.09	32.77	75.62	88.09	74.00	14.09	Peak	0.00

BLE_2M_TX_CH_00_Vertical-AVG




Site : chamber
Condition: 3m VERTICAL
Job No : 00199AT00200AT
Mode : 2402 Band edge
BLE 2M L

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over	Remark	Aux Factor
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB		dB
1	2389.761	16.13	29.10	32.78	21.75	34.20	54.00	-19.80	Average	0.00
2	2390.000	16.13	29.10	32.78	21.53	33.98	54.00	-20.02	Average	0.00
3 q	2402.000	16.15	29.09	32.77	57.68	70.15	54.00	16.15	Average	0.00




BLE_2M_TX_CH_39_Horizontal-Peak



Site : chamber
Condition: 3m HORIZONTAL
Job No : 00199AT00200AT
Mode : 2400 Band edge
BLE 2M L

Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark	Aux Factor
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB		dB
1 p 2480.000	16.27	28.90	32.73	64.64	97.08	74.00	23.08	Peak	0.00
2 2483.500	16.28	28.90	32.73	34.12	46.57	74.00	-27.43	Peak	0.00
3 2484.420	16.28	28.90	32.73	34.78	47.23	74.00	-26.77	Peak	0.00


BLE_2M_TX_CH_39_Horizontal-AVG



Site : chamber
Condition: 3m HORIZONTAL
Job No : 00199AT00200AT
Mode : 2400 Band edge
BLE 2M L

Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark	Aux Factor
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB		dB
1 q 2480.000	16.27	28.90	32.73	64.05	76.49	54.00	22.49	Average	0.00
2 2483.500	16.28	28.90	32.73	23.00	35.45	54.00	-18.55	Average	0.00
3 2483.646	16.28	28.90	32.73	22.45	34.90	54.00	-19.10	Average	0.00


BLE_2M_TX_CH_39_Vertical-Peak



Site : chamber
Condition: 3m VERTICAL
Job No : 00199AT00200AT
Mode : 2400 Band edge
BLE 2M L

Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark	Aux Factor
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB		dB
1 p 2480.000	16.27	28.90	32.73	77.98	90.42	74.00	16.42	Peak	0.00
2 2483.500	16.28	28.90	32.73	32.70	45.15	74.00	-28.85	Peak	0.00
3 2489.294	16.28	28.90	32.73	34.75	47.20	74.00	-26.80	Peak	0.00

BLE_2M_TX_CH_39_Vertical-AVG




Site : chamber
Condition: 3m VERTICAL
Job No : 00199AT00200AT
Mode : 2400 Band edge
BLE 2M L

Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark	Aux Factor
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB		dB
1 q 2480.000	16.27	28.90	32.73	59.25	71.69	54.00	17.69	Average	0.00
2 2483.500	16.28	28.90	32.73	21.55	34.00	54.00	-20.00	Average	0.00
3 2488.194	16.28	28.90	32.73	22.31	34.76	54.00	-19.24	Average	0.00




BLE_1M_TX_CH_00_Horizontal-Peak



Site : chamber
Condition: 3m HORIZONTAL
Job No : 00199AT00200AT
Mode : 2402 Band edge
BLE 1M R

Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over	Remark	Aux Factor
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB		dB
1 2347.601	16.07	29.07	32.00	33.91	46.25	74.00	-27.75	Peak	0.00
2 2390.000	16.13	29.10	32.78	32.54	44.99	74.00	-29.01	Peak	0.00
3 p 2402.000	16.15	29.09	32.77	82.09	94.56	74.00	20.56	Peak	0.00


BLE_1M_TX_CH_00_Horizontal-AVG



Site : chamber
Condition: 3m HORIZONTAL
Job No : 00199AT00200AT
Mode : 2402 Band edge
BLE 1M R

Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over	Remark	Aux Factor
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB		dB
1 2369.189	16.10	29.10	32.79	21.90	34.31	54.00	-19.69	Average	0.00
2 2390.000	16.13	29.10	32.78	21.30	33.75	54.00	-20.25	Average	0.00
3 q 2402.000	16.15	29.09	32.77	71.66	84.13	54.00	30.13	Average	0.00


BLE_1M_TX_CH_00_Vertical-Peak



Site : chamber
Condition: 3m VERTICAL
Job No : 00199AT00200AT
Mode : 2402 Band edge
BLE 1M R

Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over	Remark	Aux Factor
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB		dB
1 2376.329	16.11	29.10	32.79	34.03	46.45	74.00	-27.55	Peak	0.00
2 2390.000	16.13	29.10	32.78	33.65	46.10	74.00	-27.90	Peak	0.00
3 p 2402.000	16.15	29.09	32.77	75.80	88.27	74.00	14.27	Peak	0.00

BLE_1M_TX_CH_00_Vertical-AVG



Site : chamber
Condition: 3m VERTICAL
Job No : 00199AT00200AT
Mode : 2402 Band edge
BLE 1M R

Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over	Remark	Aux Factor
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB		dB
1 2352.481	16.08	29.10	32.80	21.75	34.13	54.00	-19.87	Average	0.00
2 2390.000	16.13	29.10	32.78	21.49	33.94	54.00	-20.06	Average	0.00
3 q 2402.000	16.15	29.09	32.77	66.85	79.32	54.00	25.32	Average	0.00




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编:518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com


BLE_1M_TX_CH_39_Horizontal-Peak



Site : chamber
Condition: 3m HORIZONTAL
Job No : 00199AT00200AT
Mode : 2400 Band edge
BLE 1M R

Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark	Aux Factor
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB		dB
1 p 2480.000	16.27	28.90	32.73	81.89	94.33	74.00	20.33	Peak	0.00
2 2483.500	16.28	28.90	32.73	32.85	45.30	74.00	-28.70	Peak	0.00
3 2496.686	16.30	28.90	32.73	34.46	46.93	74.00	-27.07	Peak	0.00


BLE_1M_TX_CH_39_Horizontal-AVG



Site : chamber
Condition: 3m HORIZONTAL
Job No : 00199AT00200AT
Mode : 2400 Band edge
BLE 1M R

Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark	Aux Factor
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB		dB
1 q 2480.000	16.27	28.90	32.73	71.90	84.34	54.00	30.34	Average	0.00
2 2483.500	16.28	28.90	32.73	22.31	34.76	54.00	-19.24	Average	0.00
3 2484.221	16.28	28.90	32.73	22.30	34.75	54.00	-19.25	Average	0.00


BLE_1M_TX_CH_39_Vertical-Peak



Site : chamber
Condition: 3m VERTICAL
Job No : 00199AT00200AT
Mode : 2400 Band edge
BLE 1M R

Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark	Aux Factor
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB		dB
1 p 2480.000	16.27	28.90	32.73	72.45	84.89	74.00	10.89	Peak	0.00
2 2483.500	16.28	28.90	32.73	32.63	45.08	74.00	-28.92	Peak	0.00
3 2494.679	16.29	28.90	32.73	35.03	47.49	74.00	-26.51	Peak	0.00

BLE_1M_TX_CH_39_Vertical-AVG




Site : chamber
Condition: 3m VERTICAL
Job No : 00199AT00200AT
Mode : 2400 Band edge
BLE 1M R

Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark	Aux Factor
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB		dB
1 q 2480.000	16.27	28.90	32.73	63.86	76.30	54.00	22.30	Average	0.00
2 2483.500	16.28	28.90	32.73	21.84	34.29	54.00	-19.71	Average	0.00
3 2498.267	16.30	28.90	32.73	22.25	34.72	54.00	-19.28	Average	0.00




BLE_2M_TX_CH_00_Horizontal-Peak



Site : chamber
Condition: 3m HORIZONTAL
Job No : 00199AT00200AT
Mode : 2402 Band edge
BLE 2M R

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over	Remark	Aux Factor
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB		dB
1	2385.916	16.13	29.10	32.78	34.14	46.59	74.00	-27.41	Peak	0.00
2	2390.000	16.13	29.10	32.78	32.25	44.70	74.00	-29.30	Peak	0.00
3 p	2402.000	16.15	29.09	32.77	82.08	94.55	74.00	20.55	Peak	0.00


BLE_2M_TX_CH_00_Horizontal-AVG



Site : chamber
Condition: 3m HORIZONTAL
Job No : 00199AT00200AT
Mode : 2402 Band edge
BLE 2M R

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over	Remark	Aux Factor
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB		dB
1	2354.875	16.08	29.10	32.80	21.86	34.24	54.00	-19.76	Average	0.00
2	2390.000	16.13	29.10	32.78	21.48	33.93	54.00	-20.07	Average	0.00
3 q	2402.000	16.15	29.09	32.77	65.73	78.20	54.00	24.20	Average	0.00


BLE_2M_TX_CH_00_Vertical-Peak



Site : chamber
Condition: 3m VERTICAL
Job No : 00199AT00200AT
Mode : 2402 Band edge
BLE 2M R

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over	Remark	Aux Factor
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB		dB
1	2353.778	16.08	29.10	32.80	33.77	46.15	74.00	-27.85	Peak	0.00
2	2390.000	16.13	29.10	32.78	32.38	44.83	74.00	-29.17	Peak	0.00
3 p	2402.000	16.15	29.09	32.77	75.86	88.33	74.00	14.33	Peak	0.00

BLE_2M_TX_CH_00_Vertical-AVG



Site : chamber
Condition: 3m VERTICAL
Job No : 00199AT00200AT
Mode : 2402 Band edge
BLE 2M R

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over	Remark	Aux Factor
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB		dB
1	2374.517	16.11	29.10	32.79	21.83	34.25	54.00	-19.75	Average	0.00
2	2390.000	16.13	29.10	32.78	21.29	33.74	54.00	-20.26	Average	0.00
3 q	2402.000	16.15	29.09	32.77	63.93	76.40	54.00	22.40	Average	0.00




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编:518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com


BLE_2M_TX_CH_39_Horizontal-Peak



Site : chamber
Condition: 3m HORIZONTAL
Job No : 00199AT00200AT
Mode : 2400 Band edge
BLE 2M R

Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over	Remark	Aux Factor
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB		dB
1 p 2480.000	16.27	28.90	32.73	81.84	94.28	74.00	20.28	Peak	0.00
2 2483.500	16.28	28.90	32.73	33.35	45.60	74.00	-28.20	Peak	0.00
3 2491.998	16.29	28.90	32.73	34.44	46.90	74.00	-27.10	Peak	0.00


BLE_2M_TX_CH_39_Horizontal-AVG



Site : chamber
Condition: 3m HORIZONTAL
Job No : 00199AT00200AT
Mode : 2400 Band edge
BLE 2M R

Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over	Remark	Aux Factor
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB		dB
1 q 2480.000	16.27	28.90	32.73	62.06	74.50	54.00	20.50	Average	0.00
2 2483.500	16.28	28.90	32.73	22.12	34.57	54.00	-19.43	Average	0.00
3 2484.171	16.28	28.90	32.73	22.07	34.52	54.00	-19.48	Average	0.00


BLE_2M_TX_CH_39_Vertical-Peak



Site : chamber
Condition: 3m VERTICAL
Job No : 00199AT00200AT
Mode : 2400 Band edge
BLE 2M R

Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over	Remark	Aux Factor
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB		dB
1 p 2480.000	16.27	28.90	32.73	72.52	84.96	74.00	10.96	Peak	0.00
2 2483.500	16.28	28.90	32.73	33.67	46.12	74.00	-27.88	Peak	0.00
3 2495.481	16.29	28.90	32.73	34.73	47.19	74.00	-26.81	Peak	0.00

BLE_2M_TX_CH_39_Vertical-AVG



Site : chamber
Condition: 3m VERTICAL
Job No : 00199AT00200AT
Mode : 2400 Band edge
BLE 2M R

Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over	Remark	Aux Factor
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB		dB
1 q 2480.000	16.27	28.90	32.73	55.35	67.79	54.00	13.79	Average	0.00
2 2483.500	16.28	28.90	32.73	21.57	34.02	54.00	-19.98	Average	0.00
3 2485.619	16.28	28.90	32.73	22.08	34.53	54.00	-19.47	Average	0.00



7.2 Radiated Spurious Emissions Below 1GHz

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.209
 Test Method: ANSI C63.10 (2020) Section 6.4,6.5
 Measurement Distance: 3m
 Test Engineer: Mason Wu

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
960-1000	500	3

Note

1: The emission limits for the ranges 9-90 kHz and 110-490 kHz are based on measurements employing a linear average detector.

2. At frequencies below 1GHz, measurements may be performed at a distance different to specified in the regulations.

Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor+ Aux Factor (if applicable)

The aux factor needs to be added when measurements are performed at a distance other than the limit distance provided.

EX. Below 30MHz, Aux Factor = 40 dB/decade of distance, the aux factor is $40\log(3/300) = -80\text{dB}$ (for 3m test distance).

EX. Above 30MHz, Aux Factor = 20 dB/decade of distance, the aux factor is $20\log(10/3) = 10.46\text{dB}$ (for 10m test distance).

7.2.1 E.U.T. Operation

Operating Environment:


Temperature: 23.5 °C Humidity: 46.8 % RH Atmospheric Pressure: 1020 mbar



7.2.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	04	TX mode(1Mbps)(Left earbud)_Keep the EUT in continuously transmitting mode with GFSK modulation.
Pre-scan	05	TX mode(2Mbps)(Left earbud)_Keep the EUT in continuously transmitting mode with GFSK modulation.
Final test	06	TX mode(1Mbps)(Right earbud)_Keep the EUT in continuously transmitting mode with GFSK modulation.
Pre-scan	07	TX mode(2Mbps)(Right earbud)_Keep the EUT in continuously transmitting mode with GFSK modulation.

7.2.3 Test Setup Diagram



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

7.2.4 Measurement Procedure and Data

- a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8m above the ground at a semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3m or 10m away from the interference-receiving antenna, which was mounted on the variable-height antenna tower.
- c. The antenna height is varied from 1m to 4m above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1m to 4m (for the test frequency of below 30MHz, the antenna was tuned to heights 1m) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using quasi-peak method as specified and then reported in a data sheet.
- g. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- i. Repeat above procedures until all frequencies measured was complete.


Remark:

1. Scan from 9kHz to 30MHz, the disturbance below 30MHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only below points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.
2. The disturbance below 1GHz was very low and the harmonics were the highest point could be found when testing, so only the worst-case test curve is displayed.



30MHz-1GHz

Test Mode: 04; Polarity: Horizontal




Site : chamber
Condition: 3m HORIZONTAL
Job No. : 00199AT/00200AT
Test Mode: 04

		Ant	Cable	Preamp	Read		Limit	Over	
	Freq	Factor	Loss	Factor	Level	Level	Line	Limit	Remark
	MHz	dB/m	dB	dB	dBuV	dBuV/m	dBuV/m	dB	
1	31.289	20.79	0.75	27.65	24.23	18.12	40.00	-21.88	QP
2	80.644	10.73	1.11	27.61	25.01	9.24	40.00	-30.76	QP
3	229.293	16.60	1.84	27.70	22.79	13.53	46.00	-32.47	QP
4	393.472	20.41	2.47	27.73	24.27	19.42	46.00	-26.58	QP
5	675.208	25.53	3.34	27.89	25.44	26.42	46.00	-19.58	QP
6 q	903.309	28.69	3.99	26.95	24.81	30.54	46.00	-15.46	QP



Test Mode: 04; Polarity: Vertical



Site : chamber

Condition: 3m VERTICAL


Job No. : 00199AT/00200AT

Test Mode: 04

	Ant	Cable	Preamp	Read		Limit	Over	
Freq	Factor	Loss	Factor	Level	Level	Line	Limit	Remark
MHz	dB/m	dB	dB	dBuV	dBuV/m	dBuV/m	dB	
1	30.853	21.01	0.75	27.65	23.78	17.89	40.00	-22.11 QP
2	51.301	12.77	0.90	27.63	23.44	9.48	40.00	-30.52 QP
3	229.293	16.60	1.84	27.70	22.99	13.73	46.00	-32.27 QP
4	400.432	20.48	2.49	27.75	24.64	19.86	46.00	-26.14 QP
5	677.580	25.58	3.34	27.89	25.05	26.08	46.00	-19.92 QP
6 q	929.008	28.83	4.04	26.80	24.10	30.17	46.00	-15.83 QP



Test Mode: 06; Polarity: Horizontal




Site : chamber
Condition: 3m HORIZONTAL
Job No. : 00199AT/00200AT
Test Mode: 06

	Ant	Cable	Preamp	Read		Limit	Over	
Freq	Factor	Loss	Factor	Level	Level	Line	Limit	Remark
MHz	dB/m	dB	dB	dBuV	dBuV/m	dBuV/m	dB	
1	30.105	21.40	0.74	27.65	24.25	18.74	40.00	-21.26 QP
2	54.071	12.24	0.91	27.63	25.72	11.24	40.00	-28.76 QP
3	228.490	16.46	1.83	27.70	24.73	15.32	46.00	-30.68 QP
4	382.588	20.40	2.43	27.71	25.97	21.09	46.00	-24.91 QP
5	679.960	25.62	3.35	27.88	26.50	27.59	46.00	-18.41 QP
6 q	952.094	29.21	4.08	26.66	25.34	31.97	46.00	-14.03 QP



Test Mode: 06; Polarity: Vertical



Site : chamber
Condition: 3m VERTICAL
Job No. : 00199AT/00200AT
Test Mode: 06

	Ant	Cable	Preamp	Read		Limit	Over	
	Freq	Factor	Loss	Factor	Level	Level	Line	Limit Remark
	MHz	dB/m	dB	dB	dBuV	dBuV/m	dBuV/m	dB
1	30.105	21.40	0.74	27.65	24.81	19.30	40.00	-20.70 QP
2	51.121	12.80	0.90	27.63	28.26	14.33	40.00	-25.67 QP
3	226.894	16.21	1.83	27.71	25.36	15.69	46.00	-30.31 QP
4	381.249	20.43	2.43	27.71	25.84	20.99	46.00	-25.01 QP
5	679.960	25.62	3.35	27.88	27.04	28.13	46.00	-17.87 QP
6 q	945.440	29.06	4.07	26.70	25.52	31.95	46.00	-14.05 QP



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

7.3 Radiated Spurious Emissions Above 1GHz

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.209
 Test Method: ANSI C63.10 (2020) Section 6.6 & 11.12
 Measurement Distance: 3m
 Test Engineer: Tommy Luo

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
Above 1000	500	3

Note:

At Above 18GHz, measurements may be performed at a distance shorter than that specified in the regulations

Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor+ Aux Factor (if applicable)

The aux factor needs to be added when measurements are performed at a distance other than the limit distance provided.

EX. Above 18GHz, Aux Factor = 20 dB/decade of distance, the aux factor is $20\log(1/3) = -9.54\text{dB}$ (for 1m test distance).

7.3.1 E.U.T. Operation

Operating Environment:


Temperature: 21.6 °C Humidity: 56.8 % RH Atmospheric Pressure: 1020 mbar

7.3.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	04	TX mode(1Mbps)(Left earbud)_Keep the EUT in continuously transmitting mode with GFSK modulation.
Final test	05	TX mode(2Mbps)(Left earbud)_Keep the EUT in continuously transmitting mode with GFSK modulation.
Final test	06	TX mode(1Mbps)(Right earbud)_Keep the EUT in continuously transmitting mode with GFSK modulation.
Final test	07	TX mode(2Mbps)(Right earbud)_Keep the EUT in continuously transmitting mode with GFSK modulation.



7.3.3 Test Setup Diagram



7.3.4 Measurement Procedure and Data


- For above 1GHz, the EUT was placed on the top of a rotating table 1.5m above the ground at a 3m fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation. The EUT was set 3m away from the interference-receiving antenna from 1GHz to 18GHz, and 1m away from the interference-receiving antenna above 18GHz.
- The interference-receiving antenna was mounted on the variable-height antenna tower, with its boresight facing the EUT throughout the test.
- The antenna height is varied from 1m to 4m above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1m to 4m and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- Test the EUT in the lowest channel, the middle channel, the Highest channel.
- The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- Repeat above procedures until all frequencies measured was complete.

Remark:


- Scan from 1GHz to 10th harmonic of the highest frequency or 40 GHz, whichever is lower.
- As shown in this section, for frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.
- For the frequency above 18GHz, testing had been executed under all test modes, only the worst-case test curve is displayed in the report.
- For devices with multiple operating modes, measurements on the middle channel is used to determine the worst-case mode(s). Only the worst-case mode with the highest output power and the mode with the highest output power spectral density for each modulation family (e.g., OFDM and direct sequence spread spectrum) is recorded in the test report.




BLE_1M_TX_CH_00_Horizontal-Peak




BLE_1M_TX_CH_00_Horizontal-Avg




BLE_1M_TX_CH_00_Vertical-Peak



BLE_1M_TX_CH_00_Vertical-Avg




BLE_1M_TX_CH_19_Horizontal-Peak



Site : chamber
Condition: 3m HORIZONTAL
Job No : 00199AT/00200AT
Mode : 2440 TX RSE
BLE 1M L

Freq	Cable Loss	Factor	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark	Aux Factor
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	dB		dB
1 4405.090	7.12	34.74	54.26	56.20	43.80	74.00	-30.20	Peak	0.00	
2 4880.000	7.47	34.62	54.21	59.33	47.21	74.00	-26.79	Peak	0.00	
3 5967.033	8.88	34.77	53.13	55.33	45.85	74.00	-28.15	Peak	0.00	
4 7320.000	8.46	35.70	53.17	53.33	44.32	74.00	-29.68	Peak	0.00	
5 9760.000	10.69	37.38	53.29	53.65	48.43	74.00	-25.57	Peak	0.00	
6 p17741.740	11.35	43.84	52.53	51.56	54.22	74.00	-19.78	Peak	0.00	


BLE_1M_TX_CH_19_Horizontal-Avg



Site : chamber
Condition: 3m HORIZONTAL
Job No : 00199AT/00200AT
Mode : 2440 TX RSE
BLE 1M L

Freq	Cable Loss	Factor	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark	Aux Factor
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	dB		dB
1 4354.454	7.09	34.44	54.26	48.94	36.21	54.00	-17.79	Average	0.00	
2 4880.000	7.47	34.62	54.21	55.43	43.31	54.00	-10.69	Average	0.00	
3 6340.436	8.90	34.92	53.14	47.20	37.88	54.00	-16.12	Average	0.00	
4 7320.000	8.46	35.70	53.17	46.92	37.91	54.00	-16.09	Average	0.00	
5 9760.000	10.69	37.38	53.29	50.14	44.92	54.00	-9.08	Average	0.00	
6 q17793.090	11.38	43.89	52.50	43.00	45.85	54.00	-8.15	Average	0.00	


BLE_1M_TX_CH_19_Vertical-Peak



Site : chamber
Condition: 3m VERTICAL
Job No : 00199AT/00200AT
Mode : 2440 TX RSE
BLE 1M L

Freq	Cable Loss	Factor	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark	Aux Factor
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	dB		dB
1 3845.537	6.69	33.04	54.40	59.76	45.09	74.00	-28.91	Peak	0.00	
2 4880.000	7.47	34.62	54.21	59.95	47.83	74.00	-26.17	Peak	0.00	
3 6737.287	8.73	35.20	53.18	54.27	45.82	74.00	-28.98	Peak	0.00	
4 7320.000	8.46	35.70	53.17	54.17	45.16	74.00	-28.84	Peak	0.00	
5 9760.000	10.69	37.38	53.29	54.88	49.66	74.00	-24.34	Peak	0.00	
6 p17793.090	11.38	43.89	52.50	51.06	53.83	74.00	-20.17	Peak	0.00	

BLE_1M_TX_CH_19_Vertical-Avg




Site : chamber
Condition: 3m VERTICAL
Job No : 00199AT/00200AT
Mode : 2440 TX RSE
BLE 1M L

Freq	Cable Loss	Factor	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark	Aux Factor
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	dB		dB
1 3132.079	5.97	32.18	54.90	53.40	36.65	54.00	-17.35	Average	0.00	
2 4880.000	7.47	34.62	54.21	55.70	43.58	54.00	-10.42	Average	0.00	
3 6880.991	8.92	35.08	53.11	47.49	38.38	54.00	-15.62	Average	0.00	
4 7320.000	8.46	35.70	53.17	46.47	37.40	54.00	-16.54	Average	0.00	
5 9760.000	10.69	37.38	53.29	50.08	44.86	54.00	-9.14	Average	0.00	
6 q17741.740	11.35	43.84	52.53	43.23	45.89	54.00	-8.11	Average	0.00	




BLE_1M_TX_CH_39_Horizontal-Peak



Site : chamber
Condition: 3m HORIZONTAL
Job No : 00199AT/00200AT
Mode : 2400 TX RSE
BLE 1M L

Freq	Cable Loss	Factor	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark	Aux Factor
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	dB		dB
1 4341.886	7.09	34.34	54.26	56.03	43.20	74.00	-30.80	Peak	0.00	
2 4960.000	7.53	34.56	54.20	60.42	48.31	74.00	-25.69	Peak	0.00	
3 6106.616	8.92	35.07	53.11	54.60	45.48	74.00	-28.52	Peak	0.00	
4 7440.000	8.43	35.96	53.15	56.11	47.35	74.00	-26.65	Peak	0.00	
5 9920.000	10.64	37.30	53.23	54.44	49.15	74.00	-24.85	Peak	0.00	
6 p17639.470	11.28	43.68	52.58	51.42	53.80	74.00	-20.20	Peak	0.00	


BLE_1M_TX_CH_39_Horizontal-Avg



Site : chamber
Condition: 3m HORIZONTAL
Job No : 00199AT/00200AT
Mode : 2400 TX RSE
BLE 1M L

Freq	Cable Loss	Factor	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark	Aux Factor
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	dB		dB
1 4392.376	7.11	34.74	54.26	49.10	36.69	54.00	-17.31	Average	0.00	
2 4960.000	7.53	34.56	54.20	58.26	46.15	54.00	-7.85	Average	0.00	
3 6340.436	8.90	34.92	53.14	47.49	38.17	54.00	-15.83	Average	0.00	
4 7440.000	8.43	35.96	53.15	47.54	38.78	54.00	-15.22	Average	0.00	
5 q 9920.000	10.64	37.30	53.23	52.94	47.65	54.00	-6.35	Average	0.00	
6 17690.530	11.32	43.78	52.55	44.12	46.67	54.00	-7.33	Average	0.00	


BLE_1M_TX_CH_39_Vertical-Peak



Site : chamber
Condition: 3m VERTICAL
Job No : 00199AT/00200AT
Mode : 2400 TX RSE
BLE 1M L

Freq	Cable Loss	Factor	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark	Aux Factor
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	dB		dB
1 4379.699	7.11	34.64	54.26	56.35	43.84	74.00	-30.16	Peak	0.00	
2 4960.000	7.53	34.56	54.20	60.76	48.65	74.00	-25.35	Peak	0.00	
3 6106.616	8.92	35.07	53.11	54.84	45.72	74.00	-28.28	Peak	0.00	
4 7440.000	8.43	35.96	53.15	54.72	45.96	74.00	-28.04	Peak	0.00	
5 9920.000	10.64	37.30	53.23	54.64	49.35	74.00	-24.65	Peak	0.00	
6 p17741.740	11.35	43.84	52.53	50.74	53.40	74.00	-20.60	Peak	0.00	

BLE_1M_TX_CH_39_Vertical-Avg




Site : chamber
Condition: 3m VERTICAL
Job No : 00199AT/00200AT
Mode : 2400 TX RSE
BLE 1M L

Freq	Cable Loss	Factor	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark	Aux Factor
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	dB		dB
1 4405.090	7.12	34.74	54.26	49.44	37.04	54.00	-16.96	Average	0.00	
2 4960.000	7.53	34.56	54.20	52.51	40.40	54.00	-13.60	Average	0.00	
3 6470.026	8.88	35.54	53.15	46.93	38.20	54.00	-15.80	Average	0.00	
4 7440.000	8.43	35.96	53.15	47.97	39.21	54.00	-14.79	Average	0.00	
5 q 9920.000	10.64	37.30	53.23	52.29	47.00	54.00	-7.00	Average	0.00	
6 17948.050	11.47	44.09	52.43	42.40	45.53	54.00	-8.47	Average	0.00	




BLE_2M_TX_CH_00_Horizontal-Peak



Site : chamber
Condition: 3m HORIZONTAL
Job No : 00199AT/00200AT
Mode : 2402 TX RSE
BLE 2M L

Freq	Cable Loss	Factor	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark	Aux Factor
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	dB		dB
1 4379.699	7.11	34.64	54.26	55.64	43.13	74.00	-30.87	Peak	0.00	
2 4804.000	7.41	34.32	54.22	57.48	44.99	74.00	-29.01	Peak	0.00	
3 5949.811	8.86	34.70	53.15	54.84	45.25	74.00	-28.75	Peak	0.00	
4 7206.000	8.50	35.70	53.18	53.16	44.18	74.00	-29.82	Peak	0.00	
5 9608.000	10.74	37.42	53.35	52.96	47.77	74.00	-26.23	Peak	0.00	
6 p17690.530	11.32	43.78	52.55	50.60	53.15	74.00	-20.85	Peak	0.00	


BLE_2M_TX_CH_00_Horizontal-Avg



Site : chamber
Condition: 3m HORIZONTAL
Job No : 00199AT/00200AT
Mode : 2402 TX RSE
BLE 2M L

Freq	Cable Loss	Factor	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark	Aux Factor
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	dB		dB
1 4392.376	7.11	34.74	54.26	48.98	36.57	54.00	-17.43	Average	0.00	
2 4804.000	7.41	34.32	54.22	56.29	43.80	54.00	-10.20	Average	0.00	
3 6954.852	8.59	35.79	53.20	46.51	37.69	54.00	-16.31	Average	0.00	
4 7206.000	8.50	35.70	53.18	46.34	37.36	54.00	-16.64	Average	0.00	
5 9608.000	10.74	37.42	53.35	49.93	44.74	54.00	-9.26	Average	0.00	
6 q17793.090	11.38	43.89	52.50	43.30	46.07	54.00	-7.93	Average	0.00	


BLE_2M_TX_CH_00_Vertical-Peak



Site : chamber
Condition: 3m VERTICAL
Job No : 00199AT/00200AT
Mode : 2402 TX RSE
BLE 2M L

Freq	Cable Loss	Factor	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark	Aux Factor
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	dB		dB
1 4379.699	7.11	34.64	54.26	56.32	43.81	74.00	-30.19	Peak	0.00	
2 4804.000	7.41	34.32	54.22	58.52	46.03	74.00	-27.97	Peak	0.00	
3 5967.033	8.88	34.77	53.13	55.38	45.90	74.00	-28.10	Peak	0.00	
4 7206.000	8.50	35.70	53.18	53.96	44.98	74.00	-29.02	Peak	0.00	
5 9608.000	10.74	37.42	53.35	53.96	48.77	74.00	-25.23	Peak	0.00	
6 p17793.090	11.38	43.89	52.50	51.31	54.08	74.00	-19.92	Peak	0.00	

BLE_2M_TX_CH_00_Vertical-Avg




Site : chamber
Condition: 3m VERTICAL
Job No : 00199AT/00200AT
Mode : 2402 TX RSE
BLE 2M L

Freq	Cable Loss	Factor	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark	Aux Factor
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	dB		dB
1 4379.699	7.11	34.64	54.26	49.97	37.46	54.00	-16.54	Average	0.00	
2 4804.000	7.41	34.32	54.22	52.36	39.87	54.00	-14.13	Average	0.00	
3 6880.991	8.92	35.08	53.11	47.40	38.29	54.00	-15.71	Average	0.00	
4 7206.000	8.50	35.70	53.18	46.56	37.58	54.00	-16.42	Average	0.00	
5 9608.000	10.74	37.42	53.35	49.07	43.88	54.00	-10.12	Average	0.00	
6 q17793.090	11.38	43.89	52.50	42.78	45.55	54.00	-8.45	Average	0.00	




BLE_2M_TX_CH_19_Horizontal-Peak



Site : chamber
Condition: 3m HORIZONTAL
Job No : 00199AT/00200AT
Mode : 2440 TX RSE

BLE 2M L		Cable	Ant	Preamp	Read	Level	Limit	Over	Remark	Aux
Freq		Loss	Factor	Factor	Level	dBuV/m	dBuV/m	Limit		Factor
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	dB		dB
1	4341.886	7.09	34.34	54.26	55.83	43.00	74.00	-31.00	Peak	0.00
2	4880.000	7.47	34.62	54.21	58.33	46.21	74.00	-27.79	Peak	0.00
3	5949.811	8.86	34.70	53.15	55.03	45.44	74.00	-28.56	Peak	0.00
4	7320.000	8.46	35.70	53.17	53.32	44.31	74.00	-29.69	Peak	0.00
5	9760.000	10.69	37.38	53.29	53.68	48.46	74.00	-25.54	Peak	0.00
6	p17639.470	11.28	43.68	52.58	51.20	53.58	74.00	-20.42	Peak	0.00


BLE_2M_TX_CH_19_Horizontal-Avg



Site : chamber
Condition: 3m HORIZONTAL
Job No : 00199AT/00200AT
Mode : 2440 TX RSE

BLE 2M L		Cable	Ant	Preamp	Read	Level	Limit	Over	Remark	Aux
Freq		Loss	Factor	Factor	Level	dBuV/m	dBuV/m	Limit		Factor
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	dB		dB
1	4354.454	7.09	34.44	54.26	48.80	36.07	54.00	-17.93	Average	0.00
2	4880.000	7.47	34.62	54.21	55.52	43.40	54.00	-10.60	Average	0.00
3	6088.991	8.92	35.08	53.11	47.78	38.67	54.00	-15.33	Average	0.00
4	7320.000	8.46	35.70	53.17	47.00	38.07	54.00	-15.93	Average	0.00
5	9760.000	10.69	37.38	53.29	49.96	44.74	54.00	-9.26	Average	0.00
6	q17639.470	11.28	43.68	52.58	43.18	45.56	54.00	-8.44	Average	0.00


BLE_2M_TX_CH_19_Vertical-Peak



Site : chamber
Condition: 3m VERTICAL
Job No : 00199AT/00200AT
Mode : 2440 TX RSE

BLE 2M L		Cable	Ant	Preamp	Read	Level	Limit	Over	Remark	Aux
Freq		Loss	Factor	Factor	Level	dBuV/m	dBuV/m	Limit		Factor
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	dB		dB
1	4354.454	7.09	34.44	54.26	56.45	43.72	74.00	-30.28	Peak	0.00
2	4880.000	7.47	34.62	54.21	56.58	44.46	74.00	-29.54	Peak	0.00
3	6954.052	8.59	35.79	53.20	53.91	45.09	74.00	-28.91	Peak	0.00
4	7320.000	8.46	35.70	53.17	54.43	45.42	74.00	-28.58	Peak	0.00
5	9760.000	10.69	37.38	53.29	54.56	49.34	74.00	-24.66	Peak	0.00
6	p17741.740	11.35	43.84	52.53	50.25	52.91	74.00	-21.09	Peak	0.00

BLE_2M_TX_CH_19_Vertical-Avg




Site : chamber
Condition: 3m VERTICAL
Job No : 00199AT/00200AT
Mode : 2440 TX RSE

BLE 2M L		Cable	Ant	Preamp	Read	Level	Limit	Over	Remark	Aux
Freq		Loss	Factor	Factor	Level	dBuV/m	dBuV/m	Limit		Factor
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	dB		dB
1	4379.699	7.11	34.64	54.26	48.76	36.25	54.00	-17.75	Average	0.00
2	4880.000	7.47	34.62	54.21	53.41	41.29	54.00	-12.71	Average	0.00
3	5967.033	8.88	34.77	53.13	47.93	38.45	54.00	-15.55	Average	0.00
4	7320.000	8.46	35.70	53.17	46.89	37.88	54.00	-16.12	Average	0.00
5	q 9760.000	10.69	37.38	53.29	52.21	46.99	54.00	-7.01	Average	0.00
6	17639.470	11.28	43.68	52.58	43.57	45.95	54.00	-8.05	Average	0.00




BLE_2M_TX_CH_39_Horizontal-Peak



Site : chamber
Condition: 3m HORIZONTAL
Job No : 00199AT/00200AT
Mode : 2400 TX RSE
BLE 2M L

Freq	Cable Loss	Factor	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over	Remark	Aux Factor
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	dB		dB
1 4341.886	7.09	34.34	54.26	56.36	43.53	74.00	-30.47	Peak	0.00	
2 4960.000	7.53	34.56	54.20	57.48	45.37	74.00	-28.63	Peak	0.00	
3 6088.991	8.92	35.08	53.11	54.93	45.82	74.00	-28.18	Peak	0.00	
4 7440.000	8.43	35.96	53.15	56.01	47.25	74.00	-26.75	Peak	0.00	
5 9920.000	10.64	37.30	53.23	52.99	47.70	74.00	-26.30	Peak	0.00	
6 p17690.530	11.32	43.78	52.55	50.79	53.34	74.00	-20.66	Peak	0.00	


BLE_2M_TX_CH_39_Horizontal-Avg



Site : chamber
Condition: 3m HORIZONTAL
Job No : 00199AT/00200AT
Mode : 2400 TX RSE
BLE 2M L

Freq	Cable Loss	Factor	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over	Remark	Aux Factor
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	dB		dB
1 4379.699	7.11	34.64	54.26	48.99	36.48	54.00	-17.52	Average	0.00	
2 4960.000	7.53	34.56	54.20	57.14	45.03	54.00	-8.97	Average	0.00	
3 6088.991	8.92	35.08	53.11	47.47	38.36	54.00	-15.64	Average	0.00	
4 7440.000	8.43	35.96	53.15	47.30	38.54	54.00	-15.46	Average	0.00	
5 q 9920.000	10.64	37.30	53.23	51.40	46.11	54.00	-7.89	Average	0.00	
6 17639.470	11.28	43.68	52.58	43.35	45.73	54.00	-8.27	Average	0.00	


BLE_2M_TX_CH_39_Vertical-Peak



Site : chamber
Condition: 3m VERTICAL
Job No : 00199AT/00200AT
Mode : 2400 TX RSE
BLE 2M L

Freq	Cable Loss	Factor	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over	Remark	Aux Factor
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	dB		dB
1 4392.376	7.11	34.74	54.26	56.26	43.85	74.00	-30.15	Peak	0.00	
2 4960.000	7.53	34.56	54.20	59.74	47.63	74.00	-26.37	Peak	0.00	
3 6071.417	8.92	35.04	53.11	54.19	45.84	74.00	-28.96	Peak	0.00	
4 7440.000	8.43	35.96	53.15	55.84	47.08	74.00	-26.92	Peak	0.00	
5 9920.000	10.64	37.30	53.23	54.15	48.86	74.00	-25.14	Peak	0.00	
6 p17639.470	11.28	43.68	52.58	50.99	53.37	74.00	-20.63	Peak	0.00	

BLE_2M_TX_CH_39_Vertical-Avg




Site : chamber
Condition: 3m VERTICAL
Job No : 00199AT/00200AT
Mode : 2400 TX RSE
BLE 2M L

Freq	Cable Loss	Factor	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over	Remark	Aux Factor
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	dB		dB
1 4379.699	7.11	34.64	54.26	48.97	36.48	54.00	-17.54	Average	0.00	
2 4960.000	7.53	34.56	54.20	57.44	45.33	54.00	-8.67	Average	0.00	
3 5967.833	8.88	34.77	53.13	47.68	38.12	54.00	-15.88	Average	0.00	
4 7440.000	8.43	35.96	53.15	48.18	39.42	54.00	-14.58	Average	0.00	
5 q 9920.000	10.64	37.30	53.23	52.54	47.25	54.00	-6.75	Average	0.00	
6 17741.740	11.35	43.84	52.53	43.19	45.85	54.00	-8.15	Average	0.00	




BLE_1M_TX_CH_00_Horizontal-Peak



Site : chamber
Condition: 3m HORIZONTAL
Job No : 00199AT/00200AT
Mode : 2402 TX RSE
BLE 1M R

Freq	Cable Loss	Factor	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark	Aux Factor
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	dB		dB
1 3141.145	5.98	32.34	54.89	60.63	44.06	74.00	-29.94	Peak		0.00
2 4804.000	7.41	34.32	54.22	59.19	46.70	74.00	-27.30	Peak		0.00
3 6088.991	8.92	35.08	53.11	54.66	45.55	74.00	-28.45	Peak		0.00
4 7206.000	8.50	35.70	53.18	54.00	45.82	74.00	-28.18	Peak		0.00
5 9608.000	10.74	37.42	53.35	53.30	48.11	74.00	-25.89	Peak		0.00
6 p17793.090	11.38	43.89	52.50	50.31	53.00	74.00	-20.92	Peak		0.00


BLE_1M_TX_CH_00_Horizontal-Avg



Site : chamber
Condition: 3m HORIZONTAL
Job No : 00199AT/00200AT
Mode : 2402 TX RSE
BLE 1M R

Freq	Cable Loss	Factor	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark	Aux Factor
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	dB		dB
1 4367.058	7.10	34.54	54.26	48.95	36.33	54.00	-17.67	Average		0.00
2 4804.000	7.41	34.32	54.22	55.60	43.11	54.00	-10.89	Average		0.00
3 6106.616	8.92	35.07	53.11	46.90	37.78	54.00	-16.22	Average		0.00
4 7206.000	8.50	35.70	53.18	46.72	37.74	54.00	-16.26	Average		0.00
5 9608.000	10.74	37.42	53.35	46.53	41.34	54.00	-12.66	Average		0.00
6 q17948.050	11.47	44.09	52.43	42.57	45.70	54.00	-8.30	Average		0.00


BLE_1M_TX_CH_00_Vertical-Peak



Site : chamber
Condition: 3m VERTICAL
Job No : 00199AT/00200AT
Mode : 2402 TX RSE
BLE 1M R

Freq	Cable Loss	Factor	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark	Aux Factor
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	dB		dB
1 3196.094	6.01	32.87	54.85	61.16	45.19	74.00	-28.81	Peak		0.00
2 4804.000	7.41	34.32	54.22	57.15	44.66	74.00	-29.34	Peak		0.00
3 6470.026	8.88	35.54	53.15	53.85	45.12	74.00	-28.88	Peak		0.00
4 7206.000	8.50	35.70	53.18	53.97	44.99	74.00	-29.01	Peak		0.00
5 9608.000	10.74	37.42	53.35	52.41	47.22	74.00	-26.78	Peak		0.00
6 p17741.740	11.35	43.84	52.53	50.97	53.63	74.00	-20.37	Peak		0.00

BLE_1M_TX_CH_00_Vertical-Avg



Site : chamber
Condition: 3m VERTICAL
Job No : 00199AT/00200AT
Mode : 2402 TX RSE
BLE 1M R


Freq	Cable Loss	Factor	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark	Aux Factor
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	dB		dB
1 3186.869	6.01	32.79	54.85	52.89	36.84	54.00	-17.16	Average		0.00
2 4804.000	7.41	34.32	54.22	52.94	40.45	54.00	-13.55	Average		0.00
3 6451.353	8.88	35.50	53.15	46.89	38.12	54.00	-15.88	Average		0.00
4 7206.000	8.50	35.70	53.18	47.60	38.62	54.00	-15.38	Average		0.00
5 9608.000	10.74	37.42	53.35	46.28	41.09	54.00	-12.91	Average		0.00
6 q17793.090	11.38	43.89	52.50	43.40	46.17	54.00	-7.83	Average		0.00



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com


BLE_1M_TX_CH_19_Horizontal-Peak



Site : chamber
Condition: 3m HORIZONTAL
Job No : 00199AT/00200AT
Mode : 2440 TX RSE
BLE 1M R

Freq	Cable Loss	Factor	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over	Remark	Aux Factor
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	dB		dB
1 4354.454	7.09	34.44	54.26	56.12	43.39	74.00	-30.61	Peak		0.00
2 4880.000	7.47	34.62	54.21	58.02	45.90	74.00	-28.10	Peak		0.00
3 5949.811	8.86	34.70	53.15	55.14	45.55	74.00	-28.45	Peak		0.00
4 7320.000	8.46	35.70	53.17	53.38	44.37	74.00	-29.63	Peak		0.00
5 9760.000	10.69	37.38	53.29	53.70	48.48	74.00	-25.52	Peak		0.00
6 p17741.740	11.35	43.84	52.53	50.29	52.95	74.00	-21.05	Peak		0.00


BLE_1M_TX_CH_19_Horizontal-Avg



Site : chamber
Condition: 3m HORIZONTAL
Job No : 00199AT/00200AT
Mode : 2440 TX RSE
BLE 1M R

Freq	Cable Loss	Factor	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over	Remark	Aux Factor
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	dB		dB
1 4367.058	7.10	34.54	54.26	48.99	36.37	54.00	-17.63	Average		0.00
2 4880.000	7.47	34.62	54.21	54.63	42.51	54.00	-11.49	Average		0.00
3 6088.991	8.92	35.08	53.11	47.32	38.21	54.00	-15.79	Average		0.00
4 7320.000	8.46	35.70	53.17	46.80	37.59	54.00	-16.41	Average		0.00
5 9760.000	10.69	37.38	53.29	47.65	42.43	54.00	-11.57	Average		0.00
6 q17639.470	11.28	43.68	52.58	43.56	45.94	54.00	-8.06	Average		0.00


BLE_1M_TX_CH_19_Vertical-Peak



Site : chamber
Condition: 3m VERTICAL
Job No : 00199AT/00200AT
Mode : 2440 TX RSE
BLE 1M R

Freq	Cable Loss	Factor	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over	Remark	Aux Factor
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	dB		dB
1 4443.453	7.14	34.28	54.25	56.31	43.48	74.00	-30.52	Peak		0.00
2 4880.000	7.47	34.62	54.21	57.48	45.36	74.00	-28.64	Peak		0.00
3 5583.251	8.29	34.70	53.53	57.42	46.88	74.00	-27.12	Peak		0.00
4 7320.000	8.46	35.70	53.17	53.76	44.75	74.00	-29.25	Peak		0.00
5 9760.000	10.69	37.38	53.29	53.14	47.92	74.00	-26.08	Peak		0.00
6 p17690.530	11.32	43.78	52.55	50.37	52.92	74.00	-21.08	Peak		0.00

BLE_1M_TX_CH_19_Vertical-Avg




Site : chamber
Condition: 3m VERTICAL
Job No : 00199AT/00200AT
Mode : 2440 TX RSE
BLE 1M R

Freq	Cable Loss	Factor	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over	Remark	Aux Factor
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	dB		dB
1 4367.058	7.10	34.54	54.26	49.22	36.60	54.00	-17.40	Average		0.00
2 4880.000	7.47	34.62	54.21	53.62	41.50	54.00	-12.50	Average		0.00
3 6470.026	8.88	35.54	53.15	47.26	38.53	54.00	-15.47	Average		0.00
4 7320.000	8.46	35.70	53.17	46.53	37.52	54.00	-16.48	Average		0.00
5 9760.000	10.69	37.38	53.29	49.83	43.81	54.00	-10.19	Average		0.00
6 q17793.090	11.38	43.89	52.58	42.75	45.52	54.00	-8.48	Average		0.00




BLE_1M_TX_CH_39_Horizontal-Peak



Site : chamber
Condition: 3m HORIZONTAL
Job No : 00199AT/00200AT
Mode : 2400 TX RSE

BLE 1M R		Cable	Ant	Preamp	Read	Level	Limit	Over	Remark	Aux
Freq		Loss	Factor	Factor	Level	dBuV/m	Line	Limit		Factor
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB		dB
1	4367.058	7.10	34.54	54.26	56.23	43.61	74.00	-30.39	Peak	0.00
2	4960.000	7.53	34.56	54.20	58.54	46.43	74.00	-27.57	Peak	0.00
3	6071.417	8.92	35.04	53.11	54.22	45.07	74.00	-28.93	Peak	0.00
4	7440.000	8.43	35.96	53.15	54.77	46.01	74.00	-27.99	Peak	0.00
5	9920.000	10.64	37.30	53.23	54.09	48.80	74.00	-25.20	Peak	0.00
6	17793.090	11.38	43.89	52.50	51.19	53.96	74.00	-20.04	Peak	0.00


BLE_1M_TX_CH_39_Horizontal-Avg



Site : chamber
Condition: 3m HORIZONTAL
Job No : 00199AT/00200AT
Mode : 2400 TX RSE

BLE 1M R		Cable	Ant	Preamp	Read	Level	Limit	Over	Remark	Aux
Freq		Loss	Factor	Factor	Level	dBuV/m	Line	Limit		Factor
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB		dB
1	4379.699	7.11	34.64	54.26	48.71	36.20	54.00	-17.80	Average	0.00
2	4960.000	7.53	34.56	54.20	56.93	44.02	54.00	-9.18	Average	0.00
3	6088.991	8.92	35.08	53.11	47.57	38.46	54.00	-15.54	Average	0.00
4	7440.000	8.43	35.96	53.15	47.62	38.06	54.00	-15.14	Average	0.00
5	9920.000	10.64	37.30	53.23	50.63	45.34	54.00	-8.66	Average	0.00
6	17793.090	11.38	43.89	52.50	42.57	45.34	54.00	-8.66	Average	0.00


BLE_1M_TX_CH_39_Vertical-Peak



Site : chamber
Condition: 3m VERTICAL
Job No : 00199AT/00200AT
Mode : 2400 TX RSE

BLE 1M R		Cable	Ant	Preamp	Read	Level	Limit	Over	Remark	Aux
Freq		Loss	Factor	Factor	Level	dBuV/m	Line	Limit		Factor
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB		dB
1	4181.768	7.00	33.80	54.28	59.77	46.29	74.00	-27.71	Peak	0.00
2	4960.000	7.53	34.56	54.20	60.65	48.54	74.00	-25.46	Peak	0.00
3	6995.172	8.56	35.71	53.20	54.04	45.11	74.00	-28.89	Peak	0.00
4	7440.000	8.43	35.96	53.15	54.64	45.88	74.00	-28.12	Peak	0.00
5	9920.000	10.64	37.30	53.23	52.40	47.11	74.00	-26.89	Peak	0.00
6	17793.090	11.38	43.89	52.50	50.30	53.07	74.00	-20.93	Peak	0.00

BLE_1M_TX_CH_39_Vertical-Avg



Site : chamber
Condition: 3m VERTICAL
Job No : 00199AT/00200AT
Mode : 2400 TX RSE


BLE 1M R		Cable	Ant	Preamp	Read	Level	Limit	Over	Remark	Aux
Freq		Loss	Factor	Factor	Level	dBuV/m	Line	Limit		Factor
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB		dB
1	4417.841	7.13	34.59	54.26	48.79	36.25	54.00	-17.75	Average	0.00
2	4960.000	7.53	34.56	54.20	53.07	40.96	54.00	-13.04	Average	0.00
3	6088.991	8.92	35.08	53.11	47.27	38.16	54.00	-15.84	Average	0.00
4	7440.000	8.43	35.96	53.15	47.38	38.62	54.00	-15.38	Average	0.00
5	9920.000	10.64	37.30	53.23	48.31	43.02	54.00	-10.98	Average	0.00
6	177639.470	11.28	43.68	52.58	43.10	45.48	54.00	-8.52	Average	0.00



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com


BLE_2M_TX_CH_00_Horizontal-Peak



Site : chamber
Condition: 3m HORIZONTAL
Job No : 00199AT/00200AT
Mode : 2402 TX RSE
BLE 2M R

Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark	Aux Factor
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB		dB
1 4392.376	7.11	34.74	54.26	56.26	43.85	74.00	-30.15	Peak	0.00
2 4804.000	7.41	34.32	54.22	57.63	45.14	74.00	-28.86	Peak	0.00
3 6106.616	8.92	35.07	53.11	54.89	45.77	74.00	-28.23	Peak	0.00
4 7206.000	8.50	35.70	53.18	53.96	44.98	74.00	-29.02	Peak	0.00
5 9608.000	10.74	37.42	53.35	52.27	47.08	74.00	-26.92	Peak	0.00
6 p17793.090	11.38	43.89	52.50	50.57	53.34	74.00	-20.66	Peak	0.00


BLE_2M_TX_CH_00_Horizontal-Avg



Site : chamber
Condition: 3m HORIZONTAL
Job No : 00199AT/00200AT
Mode : 2402 TX RSE
BLE 2M R

Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark	Aux Factor
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB		dB
1 4367.058	7.10	34.54	54.26	48.57	35.95	54.00	-18.05	Average	0.00
2 4804.000	7.41	34.32	54.22	55.04	42.55	54.00	-11.45	Average	0.00
3 6088.991	8.92	35.08	53.11	47.14	38.03	54.00	-15.97	Average	0.00
4 7206.000	8.50	35.70	53.18	46.43	37.45	54.00	-16.55	Average	0.00
5 9608.000	10.74	37.42	53.35	48.32	43.13	54.00	-10.87	Average	0.00
6 q17639.470	11.28	43.68	52.58	43.03	45.41	54.00	-8.59	Average	0.00


BLE_2M_TX_CH_00_Vertical-Peak



Site : chamber
Condition: 3m VERTICAL
Job No : 00199AT/00200AT
Mode : 2402 TX RSE
BLE 2M R

Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark	Aux Factor
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB		dB
1 3912.009	6.78	33.72	54.35	57.10	43.25	74.00	-30.75	Peak	0.00
2 4804.000	7.41	34.32	54.22	57.61	45.12	74.00	-28.88	Peak	0.00
3 6358.789	8.89	34.95	53.14	54.57	45.27	74.00	-28.73	Peak	0.00
4 7206.000	8.50	35.70	53.18	53.83	44.85	74.00	-29.15	Peak	0.00
5 9608.000	10.74	37.42	53.35	51.89	46.70	74.00	-27.30	Peak	0.00
6 p17639.470	11.28	43.68	52.58	51.40	53.78	74.00	-20.22	Peak	0.00

BLE_2M_TX_CH_00_Vertical-Avg




Site : chamber
Condition: 3m VERTICAL
Job No : 00199AT/00200AT
Mode : 2402 TX RSE
BLE 2M R

Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark	Aux Factor
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB		dB
1 4405.090	7.12	34.74	54.26	48.49	36.09	54.00	-17.91	Average	0.00
2 4804.000	7.41	34.32	54.22	51.00	38.51	54.00	-15.49	Average	0.00
3 6213.441	8.91	34.75	53.12	47.13	37.67	54.00	-16.33	Average	0.00
4 7206.000	8.50	35.70	53.18	46.36	37.38	54.00	-16.62	Average	0.00
5 9608.000	10.74	37.42	53.35	45.57	40.38	54.00	-13.62	Average	0.00
6 q17639.470	11.28	43.68	52.58	43.18	45.56	54.00	-8.44	Average	0.00



BLE_2M_TX_CH_19_Horizontal-Peak




Site : chamber
Condition: 3m HORIZONTAL
Job No : 00199AT/00200AT
Mode : 2440 TX RSE

BLE 2M R

	Freq	Cable Loss	Factor	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over	Remark	Aux Factor
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	dB		dB
1	4367.058	7.10	34.54	54.26	56.97	44.35	74.00	-29.65	Peak		0.00
2	4880.000	7.47	34.62	54.21	57.47	45.35	74.00	-28.65	Peak		0.00
3	6071.417	8.92	35.04	53.11	54.85	45.70	74.00	-28.30	Peak		0.00
4	7320.000	8.46	35.70	53.17	53.16	44.15	74.00	-29.85	Peak		0.00
5	9760.000	10.69	37.38	53.29	52.69	47.47	74.00	-26.53	Peak		0.00
6	p17844.590	11.41	43.90	52.48	50.13	52.96	74.00	-21.04	Peak		0.00

BLE_2M_TX_CH_19_Horizontal-Avg




Site : chamber
Condition: 3m HORIZONTAL
Job No : 00199AT/00200AT
Mode : 2440 TX RSE

BLE 2M R

	Freq	Cable Loss	Factor	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over	Remark	Aux Factor
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	dB		dB
1	4379.699	7.11	34.64	54.26	48.98	36.47	54.00	-17.53	Average		0.00
2	4880.000	7.47	34.62	54.21	54.49	42.37	54.00	-11.63	Average		0.00
3	6002.265	8.81	35.30	53.16	47.19	38.14	54.00	-15.86	Average		0.00
4	7320.000	8.46	35.70	53.17	46.54	37.53	54.00	-16.47	Average		0.00
5	9760.000	10.69	37.38	53.29	49.66	44.44	54.00	-9.56	Average		0.00
6	q17639.470	11.28	43.68	52.58	43.93	46.31	54.00	-7.69	Average		0.00

BLE_2M_TX_CH_19_Vertical-Peak




Site : chamber
Condition: 3m VERTICAL
Job No : 00199AT/00200AT
Mode : 2440 TX RSE

BLE 2M R

	Freq	Cable Loss	Factor	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over	Remark	Aux Factor
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	dB		dB
1	4379.699	7.11	34.64	54.26	56.49	43.98	74.00	-30.02	Peak		0.00
2	4880.000	7.47	34.62	54.21	56.47	44.35	74.00	-29.65	Peak		0.00
3	6071.417	8.92	35.04	53.11	54.58	45.43	74.00	-28.57	Peak		0.00
4	7320.000	8.46	35.70	53.17	53.16	44.15	74.00	-29.85	Peak		0.00
5	9760.000	10.69	37.38	53.29	53.57	48.35	74.00	-25.65	Peak		0.00
6	p17690.530	11.32	43.78	52.55	51.88	54.43	74.00	-19.57	Peak		0.00

BLE_2M_TX_CH_19_Vertical-Avg



Site : chamber
Condition: 3m VERTICAL
Job No : 00199AT/00200AT
Mode : 2440 TX RSE

BLE 2M R


	Freq	Cable Loss	Factor	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over	Remark	Aux Factor
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	dB		dB
1	3901.516	6.77	33.79	54.36	50.00	36.20	54.00	-17.80	Average		0.00
2	4880.000	7.47	34.62	54.21	50.10	37.98	54.00	-16.02	Average		0.00
3	6186.616	8.92	35.07	53.11	47.22	38.10	54.00	-15.90	Average		0.00
4	7320.000	8.46	35.70	53.17	46.80	37.07	54.00	-16.93	Average		0.00
5	9760.000	10.69	37.38	53.29	45.66	40.44	54.00	-13.56	Average		0.00
6	q17793.090	11.38	43.89	52.50	42.88	45.65	54.00	-8.35	Average		0.00



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com


BLE_2M_TX_CH_39_Horizontal-Peak



Site : chamber
Condition: 3m HORIZONTAL
Job No : 00199AT/00200AT
Mode : 2400 TX RSE
BLE 2M R

Freq	Cable Loss	Factor	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over	Remark	Aux Factor
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	dB		dB
1 4354.454	7.09	34.44	54.26	56.53	43.80	74.00	-30.20	Peak		0.00
2 4960.000	7.53	34.56	54.20	58.31	46.20	74.00	-27.80	Peak		0.00
3 6106.616	8.92	35.07	53.11	54.55	45.43	74.00	-28.57	Peak		0.00
4 7440.000	8.43	35.96	53.15	54.41	45.65	74.00	-28.35	Peak		0.00
5 9920.000	10.64	37.30	53.23	53.62	48.33	74.00	-25.67	Peak		0.00
6 p17741.740	11.35	43.84	52.53	50.61	53.27	74.00	-20.73	Peak		0.00


BLE_2M_TX_CH_39_Horizontal-Avg



Site : chamber
Condition: 3m HORIZONTAL
Job No : 00199AT/00200AT
Mode : 2400 TX RSE
BLE 2M R

Freq	Cable Loss	Factor	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over	Remark	Aux Factor
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	dB		dB
1 4379.699	7.11	34.64	54.26	48.60	36.09	54.00	-17.91	Average		0.00
2 4960.000	7.53	34.56	54.20	55.06	42.95	54.00	-11.05	Average		0.00
3 5949.811	8.86	34.70	53.15	47.90	38.31	54.00	-15.69	Average		0.00
4 7440.000	8.43	35.96	53.15	47.58	38.02	54.00	-15.98	Average		0.00
5 9920.000	10.64	37.30	53.23	48.65	43.36	54.00	-10.64	Average		0.00
6 q17896.250	11.44	43.90	52.45	42.13	45.02	54.00	-8.98	Average		0.00


BLE_2M_TX_CH_39_Vertical-Peak



Site : chamber
Condition: 3m VERTICAL
Job No : 00199AT/00200AT
Mode : 2400 TX RSE
BLE 2M R

Freq	Cable Loss	Factor	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over	Remark	Aux Factor
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	dB		dB
1 4379.699	7.11	34.64	54.26	56.40	43.89	74.00	-30.11	Peak		0.00
2 4960.000	7.53	34.56	54.20	57.35	45.24	74.00	-28.76	Peak		0.00
3 6358.789	8.89	34.95	53.14	54.95	45.65	74.00	-28.35	Peak		0.00
4 7440.000	8.43	35.96	53.15	54.49	45.73	74.00	-28.27	Peak		0.00
5 9920.000	10.64	37.30	53.23	53.58	48.29	74.00	-25.71	Peak		0.00
6 p17487.180	11.19	43.40	52.65	51.39	53.33	74.00	-20.67	Peak		0.00

BLE_2M_TX_CH_39_Vertical-Avg




Site : chamber
Condition: 3m VERTICAL
Job No : 00199AT/00200AT
Mode : 2400 TX RSE
BLE 2M R

Freq	Cable Loss	Factor	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over	Remark	Aux Factor
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	dB		dB
1 4367.058	7.10	34.54	54.26	48.99	36.37	54.00	-17.63	Average		0.00
2 4960.000	7.53	34.56	54.20	50.86	38.75	54.00	-15.25	Average		0.00
3 6470.026	8.88	35.54	53.15	46.77	38.04	54.00	-15.96	Average		0.00
4 7440.000	8.43	35.96	53.15	47.11	38.55	54.00	-15.45	Average		0.00
5 q 9920.000	10.64	37.30	53.23	51.37	46.08	54.00	-7.92	Average		0.00
6 17793.090	11.38	43.89	52.50	42.43	45.20	54.00	-8.80	Average		0.00



Above 18GHz


BLE_1M_TX_CH_00_Horizontal



Site : chamber
Condition: 3m HORIZONTAL
Job No : 00199AT/00200AT
Mode : 2402 TX RSE
BLE

Freq	Cable	Ant	Preamp	Read	Level	Limit	Over	Aux
MHz	Loss	Factor	Factor	Level	dBuV/m	dBuV/m	Limit	Factor
	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	dB
1 18250.070	5.00	36.50	56.45	53.51	29.02	74.00	-44.98 Peak	-9.54
2 19355.390	5.94	37.80	56.73	52.37	29.84	74.00	-44.16 Peak	-9.54
3 20292.990	5.90	38.18	56.46	50.70	28.78	74.00	-45.22 Peak	-9.54
4 22138.750	6.07	37.54	54.16	51.57	31.48	74.00	-42.52 Peak	-9.54
5 23310.510	6.75	38.60	52.03	51.92	35.70	74.00	-38.30 Peak	-9.54
6 p23844.920	6.77	38.94	50.37	51.79	37.59	74.00	-36.41 Peak	-9.54

BLE_1M_TX_CH_00_Vertical



Site : chamber
Condition: 3m VERTICAL
Job No : 00199AT/00200AT
Mode : 2402 TX RSE
BLE

Freq	Cable	Ant	Preamp	Read	Level	Limit	Over	Aux
MHz	Loss	Factor	Factor	Level	dBuV	dBuV/m	dBuV/m	Factor
	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	dB
1 18260.860	5.03	36.51	56.42	52.76	28.34	74.00	-45.66 Peak	-9.54
2 19714.760	5.88	37.71	56.81	53.36	30.60	74.00	-43.40 Peak	-9.54
3 21081.210	6.05	37.37	55.05	50.68	29.51	74.00	-44.49 Peak	-9.54
4 22255.420	6.16	37.49	54.04	51.20	31.27	74.00	-42.73 Peak	-9.54
5 23371.850	6.76	38.60	51.47	50.79	35.14	74.00	-38.86 Peak	-9.54
6 p24351.550	6.80	39.04	51.25	52.48	37.53	74.00	-36.47 Peak	-9.54



7.4 Maximum Conducted Output Power

Test Requirement 47 CFR Part 15, Subpart C 15.247(b)(3)
 Test Method: ANSI C63.10 (2020) Section 11.9.1
 Test Engineer: Linvo Ding

Limit:

Frequency range(MHz)	Output power of the intentional radiator(watt)
902-928	1 for ≥ 50 hopping channels
	0.25 for $25 \leq$ hopping channels < 50
	1 for digital modulation
2400-2483.5	1 for ≥ 75 non-overlapping hopping channels
	0.125 for all other frequency hopping systems
	1 for digital modulation
5725-5850	1 for frequency hopping systems and digital modulation

7.4.1 E.U.T. Operation

Operating Environment:


Temperature: 25.7 °C Humidity: 40.1 % RH Atmospheric Pressure: 1020 mbar

7.4.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	04	TX mode(1Mbps)(Left earbud)_Keep the EUT in continuously transmitting mode with GFSK modulation.
Final test	05	TX mode(2Mbps)(Left earbud)_Keep the EUT in continuously transmitting mode with GFSK modulation.
Final test	06	TX mode(1Mbps)(Right earbud)_Keep the EUT in continuously transmitting mode with GFSK modulation.
Final test	07	TX mode(2Mbps)(Right earbud)_Keep the EUT in continuously transmitting mode with GFSK modulation.



7.4.3 Test Setup Diagram



7.4.4 Measurement Procedure and Data

Note: Since the verify power the same operating range bandwidth and smaller power can be covered by the higher power.

Please Refer to Appendix for Details



7.5 Minimum 6dB Bandwidth

Test Requirement 47 CFR Part 15, Subpart C 15.247a(2)
 Test Method: ANSI C63.10 (2020) Section 11.8.1
 Test Engineer: Linvo Ding

Limit:
 ≥500 kHz


7.5.1 E.U.T. Operation

Operating Environment:
 Temperature: 25.7 °C Humidity: 40.1 % RH Atmospheric Pressure: 1020 mbar

7.5.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	04	TX mode(1Mbps)(Left earbud)_Keep the EUT in continuously transmitting mode with GFSK modulation.
Final test	05	TX mode(2Mbps)(Left earbud)_Keep the EUT in continuously transmitting mode with GFSK modulation.
Final test	06	TX mode(1Mbps)(Right earbud)_Keep the EUT in continuously transmitting mode with GFSK modulation.
Final test	07	TX mode(2Mbps)(Right earbud)_Keep the EUT in continuously transmitting mode with GFSK modulation.

7.5.3 Test Setup Diagram



7.5.4 Measurement Procedure and Data

Please Refer to Appendix for Details



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.
 Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com
 No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
 中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

7.6 Power Spectral Density

Test Requirement 47 CFR Part 15, Subpart C 15.247(e)
 Test Method: ANSI C63.10 (2020) Section 11.10.2
 Test Engineer: Linvo Ding

Limit:

≤8dBm in any 3 kHz band during any time interval of continuous transmission

7.6.1 E.U.T. Operation


Operating Environment:

Temperature: 25.7 °C Humidity: 40.1 % RH Atmospheric Pressure: 1020 mbar

7.6.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	04	TX mode(1Mbps)(Left earbud)_Keep the EUT in continuously transmitting mode with GFSK modulation.
Final test	05	TX mode(2Mbps)(Left earbud)_Keep the EUT in continuously transmitting mode with GFSK modulation.
Final test	06	TX mode(1Mbps)(Right earbud)_Keep the EUT in continuously transmitting mode with GFSK modulation.
Final test	07	TX mode(2Mbps)(Right earbud)_Keep the EUT in continuously transmitting mode with GFSK modulation.

7.6.3 Test Setup Diagram



7.6.4 Measurement Procedure and Data

Please Refer to Appendix for Details



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
 Shenzhen Branch, China, EMC Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.ssgroup.com.cn
 中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

7.7 Conducted Band Edges Measurement

Test Requirement 47 CFR Part 15, Subpart C 15.247(d)
 Test Method: ANSI C63.10 (2020) Section 6.10.4
 Test Engineer: Linvo Ding

Limit:

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

7.7.1 E.U.T. Operation

Operating Environment:


Temperature: 25.7 °C Humidity: 40.1 % RH Atmospheric Pressure: 1020 mbar

7.7.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	04	TX mode(1Mbps)(Left earbud)_Keep the EUT in continuously transmitting mode with GFSK modulation.
Final test	05	TX mode(2Mbps)(Left earbud)_Keep the EUT in continuously transmitting mode with GFSK modulation.
Final test	06	TX mode(1Mbps)(Right earbud)_Keep the EUT in continuously transmitting mode with GFSK modulation.
Final test	07	TX mode(2Mbps)(Right earbud)_Keep the EUT in continuously transmitting mode with GFSK modulation.



7.7.3 Test Setup Diagram



7.7.4 Measurement Procedure and Data

Please Refer to Appendix for Details



7.8 Conducted Spurious Emissions

Test Requirement: 47 CFR Part 15, Subpart C 15.247(d)
 Test Method: ANSI C63.10 (2020) Section 11.11
 Test Engineer: Linvo Ding

Limit:

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

7.8.1 E.U.T. Operation

Operating Environment:


Temperature: 25.7 °C Humidity: 40.1 % RH Atmospheric Pressure: 1020 mbar

7.8.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	04	TX mode(1Mbps)(Left earbud)_Keep the EUT in continuously transmitting mode with GFSK modulation.
Final test	05	TX mode(2Mbps)(Left earbud)_Keep the EUT in continuously transmitting mode with GFSK modulation.
Final test	06	TX mode(1Mbps)(Right earbud)_Keep the EUT in continuously transmitting mode with GFSK modulation.
Final test	07	TX mode(2Mbps)(Right earbud)_Keep the EUT in continuously transmitting mode with GFSK modulation.



7.8.3 Test Setup Diagram



7.8.4 Measurement Procedure and Data

Please Refer to Appendix for Details

8 Test Setup Photo

Refer to Appendix - Test Setup Photo for SZCR2601000199AT

9 EUT Constructional Details (EUT Photos)

Refer to Appendix_Photographs of EUT Constructional Details for SZCR2601000199AT



10 Appendix

For right earbud:

1. Duty Cycle

1.1 Test Result


1.1.1 Ant1

Ant1							
Mode	TX Type	Frequency (MHz)	T_on (ms)	Period (ms)	Duty Cycle (%)	Duty Cycle Correction Factor (dB)	Max. DC Variation (%)
1M	SISO	2402	0.395	0.629	62.80	2.02	0.17
		2440	0.395	0.625	63.20	1.99	0.00
		2480	0.395	0.625	63.20	1.99	0.03
2M	SISO	2402	0.212	0.625	33.92	4.70	0.02
		2440	0.208	0.621	33.49	4.75	0.22
		2480	0.212	0.625	33.92	4.70	0.02




1.2 Test Graph


1.2.1 Ant1




1M_HCH_2480MHz_Ant1_NTNV




2M_LCH_2402MHz_Ant1_NTNV



2M_MCH_2440MHz_Ant1_NTNV



2M_HCH_2480MHz_Ant1_NTNV



2. Bandwidth

2.1 Test Result

2.1.1 OBW


Mode	TX Type	Frequency (MHz)	ANT	99% Occupied Bandwidth (MHz)		Verdict
				Result	Limit	
1M	SISO	2402	1	1.023	/	Pass
		2440	1	1.029	/	Pass
		2480	1	1.029	/	Pass
2M	SISO	2402	1	2.026	/	Pass
		2440	1	2.025	/	Pass
		2480	1	2.024	/	Pass

2.1.2 6dB BW


Mode	TX Type	Frequency (MHz)	ANT	6dB Bandwidth (MHz)		Verdict
				Result	Limit	
1M	SISO	2402	1	0.661	≥ 0.5	Pass
		2440	1	0.670	≥ 0.5	Pass
		2480	1	0.686	≥ 0.5	Pass
2M	SISO	2402	1	1.142	≥ 0.5	Pass
		2440	1	1.177	≥ 0.5	Pass
		2480	1	1.166	≥ 0.5	Pass

2.2 Test Graph


2.2.1 OBW




1M_HCH_2480MHz_Ant1_NTNV




2M_LCH_2402MHz_Ant1_NTNV




2M_MCH_2440MHz_Ant1_NTNV




2M_HCH_2480MHz_Ant1_NTNV




2.2.2 6dB BW




1M_HCH_2480MHz_Ant1_NTNV




2M_LCH_2402MHz_Ant1_NTNV



2M_MCH_2440MHz_Ant1_NTNV



2M_HCH_2480MHz_Ant1_NTNV



3. Maximum Conducted Output Power

3.1 Test Result

3.1.1 Power

Mode	TX Type	Frequency (MHz)	Maximum Peak Conducted Output Power (dBm)		Verdict
			ANT1	Limit	
1M	SISO	2402	-4.60	<=30	Pass
		2440	-5.64	<=30	Pass
		2480	-7.06	<=30	Pass
2M	SISO	2402	-4.75	<=30	Pass
		2440	-5.89	<=30	Pass
		2480	-7.23	<=30	Pass

Note1: Antenna Gain: Ant1: -3.04dBi;

4. Maximum Power Spectral Density

4.1 Test Result


4.1.1 PSD

Mode	TX Type	Frequency (MHz)	Maximum PSD (dBm)		Verdict
			ANT1	Limit	
1M	SISO	2402	-21.14	<=8	Pass
		2440	-22.94	<=8	Pass
		2480	-23.63	<=8	Pass
2M	SISO	2402	-24.80	<=8	Pass
		2440	-25.10	<=8	Pass
		2480	-25.53	<=8	Pass


Note1: Antenna Gain: Ant1: -3.04dBi;

4.2 Test Graph


4.2.1 PSD




1M_HCH_2480MHz_Ant1_NTNV




2M_LCH_2402MHz_Ant1_NTNV



2M_MCH_2440MHz_Ant1_NTNV



2M_HCH_2480MHz_Ant1_NTNV



5. Unwanted Emissions In Non-restricted Frequency Bands

5.1 Test Result

5.1.1 Ref

Mode	TX Type	Frequency (MHz)	ANT	Level of Reference (dBm)
1M	SISO	2402	1	-4.55
		2440	1	-5.61
		2480	1	-6.95
2M	SISO	2402	1	-4.66
		2440	1	-5.85
		2480	1	-7.19


5.1.2 CSE

Mode	TX Type	Frequency (MHz)	ANT	Level of Reference (dBm)	Limit (dBm)	Verdict
1M	SISO	2402	1	-4.55	-24.55	Pass
		2440	1	-4.55	-24.55	Pass
		2480	1	-4.55	-24.55	Pass
2M	SISO	2402	1	-4.66	-24.66	Pass
		2440	1	-4.66	-24.66	Pass
		2480	1	-4.66	-24.66	Pass




5.2 Test Graph


5.2.1 Ref




1M_HCH_2480MHz_Ant1_NTNV




2M_LCH_2402MHz_Ant1_NTNV




2M_MCH_2440MHz_Ant1_NTNV




2M_HCH_2480MHz_Ant1_NTNV




5.2.2 CSE




1M_MCH_2440MHz_Ant1_NTNV




1M_HCH_2480MHz_Ant1_NTNV




1M_HCH_2480MHz_Ant1_NTNV




2M_LCH_2402MHz_Ant1_NTNV




2M_LCH_2402MHz_Ant1_NTNV




2M_MCH_2440MHz_Ant1_NTNV



2M_HCH_2480MHz_Ant1_NTNV



2M_HCH_2480MHz_Ant1_NTNV



SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/2

Report No.: SZCR260100019903

Page: 77 of 100

For left earbud:

1. Duty Cycle

1.1 Test Result

1.1.1 Ant1

Ant1							
Mode	TX Type	Frequency (MHz)	T_on (ms)	Period (ms)	Duty Cycle (%)	Duty Cycle Correction Factor (dB)	Max. DC Variation (%)
1M	SISO	2402	0.395	0.629	62.80	2.02	0.17
		2440	0.395	0.625	63.20	1.99	0.03
		2480	0.395	0.625	63.20	1.99	0.00
2M	SISO	2402	0.211	0.625	33.76	4.72	0.00
		2440	0.207	0.621	33.33	4.77	0.23
		2480	0.211	0.625	33.76	4.72	0.02



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Testing & Calibration Laboratory


Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com


No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

1.2 Test Graph


1.2.1 Ant1




1M_HCH_2480MHz_Ant1_NTNV




2M_LCH_2402MHz_Ant1_NTNV



2M_MCH_2440MHz_Ant1_NTNV



2M_HCH_2480MHz_Ant1_NTNV



2. Bandwidth

2.1 Test Result

2.1.1 OBW

Mode	TX Type	Frequency (MHz)	ANT	99% Occupied Bandwidth (MHz)		Verdict
				Result	Limit	
1M	SISO	2402	1	1.032	/	Pass
		2440	1	1.032	/	Pass
		2480	1	1.033	/	Pass
2M	SISO	2402	1	2.033	/	Pass
		2440	1	2.031	/	Pass
		2480	1	2.031	/	Pass


2.1.2 6dB BW

Mode	TX Type	Frequency (MHz)	ANT	6dB Bandwidth (MHz)		Verdict
				Result	Limit	
1M	SISO	2402	1	0.667	≥ 0.5	Pass
		2440	1	0.662	≥ 0.5	Pass
		2480	1	0.663	≥ 0.5	Pass
2M	SISO	2402	1	1.155	≥ 0.5	Pass
		2440	1	1.163	≥ 0.5	Pass
		2480	1	1.158	≥ 0.5	Pass




2.2 Test Graph


2.2.1 OBW




1M_HCH_2480MHz_Ant1_NTNV




2M_LCH_2402MHz_Ant1_NTNV




2M_MCH_2440MHz_Ant1_NTNV




2M_HCH_2480MHz_Ant1_NTNV




2.2.2 6dB BW




1M_HCH_2480MHz_Ant1_NTNV




2M_LCH_2402MHz_Ant1_NTNV



2M_MCH_2440MHz_Ant1_NTNV



2M_HCH_2480MHz_Ant1_NTNV



3. Maximum Conducted Output Power

3.1 Test Result

3.1.1 Power

Mode	TX Type	Frequency (MHz)	Maximum Peak Conducted Output Power (dBm)		Verdict
			ANT1	Limit	
1M	SISO	2402	-5.34	<=30	Pass
		2440	-6.60	<=30	Pass
		2480	-7.92	<=30	Pass
2M	SISO	2402	-5.66	<=30	Pass
		2440	-6.70	<=30	Pass
		2480	-8.02	<=30	Pass

Note1: Antenna Gain: Ant1: -2.45dBi;

4. Maximum Power Spectral Density

4.1 Test Result


4.1.1 PSD

Mode	TX Type	Frequency (MHz)	Maximum PSD (dBm)		Verdict
			ANT1	Limit	
1M	SISO	2402	-21.29	<=8	Pass
		2440	-22.90	<=8	Pass
		2480	-23.61	<=8	Pass
2M	SISO	2402	-24.78	<=8	Pass
		2440	-25.09	<=8	Pass
		2480	-25.55	<=8	Pass


Note1: Antenna Gain: Ant1: -2.45dBi;

4.2 Test Graph


4.2.1 PSD




1M_HCH_2480MHz_Ant1_NTNV




2M_LCH_2402MHz_Ant1_NTNV



2M_MCH_2440MHz_Ant1_NTNV



2M_HCH_2480MHz_Ant1_NTNV



5. Unwanted Emissions In Non-restricted Frequency Bands

5.1 Test Result

5.1.1 Ref

Mode	TX Type	Frequency (MHz)	ANT	Level of Reference (dBm)
1M	SISO	2402	1	-5.29
		2440	1	-6.57
		2480	1	-7.84
2M	SISO	2402	1	-5.59
		2440	1	-6.67
		2480	1	-7.97


5.1.2 CSE

Mode	TX Type	Frequency (MHz)	ANT	Level of Reference (dBm)	Limit (dBm)	Verdict
1M	SISO	2402	1	-5.29	-25.29	Pass
		2440	1	-5.29	-25.29	Pass
		2480	1	-5.29	-25.29	Pass
2M	SISO	2402	1	-5.59	-25.59	Pass
		2440	1	-5.59	-25.59	Pass
		2480	1	-5.59	-25.59	Pass




5.2 Test Graph

5.2.1 Ref



1M_HCH_2480MHz_Ant1_NTNV



2M_LCH_2402MHz_Ant1_NTNV

