FCC RF Test Report

APPLICANT	:	S&R Land LLC
EQUIPMENT	:	Digital Media Receiver
MODEL NAME	:	XC56PY
FCC ID	:	2ALWB-7232
STANDARD	:	FCC Part 15 Subpart C §15.247
CLASSIFICATION	:	(DTS) Digital Transmission System

The testing was completed on Aug. 25, 2017. We, SPORTON INTERNATIONAL INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.

Reviewed by: Joseph Lin / Supervisor

Approved by: Jones Tsai / Manager

Testing Laboratory 1190

SPORTON INTERNATIONAL INC.
No. 52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan District, Tao Yuan City, Taiwan, R.O.C.

TABLE OF CONTENTS

REVISION HISTORY **3**
SUMMARY OF TEST RESULT **4**
1 GENERAL DESCRIPTION **5**
1.1 Applicant 5
1.2 Product Feature of Equipment Under Test 5
1.3 Product Specification of Equipment Under Test 6
1.4 Modification of EUT 6
1.5 Testing Location 7
1.6 Applicable Standards 7
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST **8**
2.1 Carrier Frequency and Channel 8
2.2 Test Mode 8
2.3 Connection Diagram of Test System 9
2.4 Support Unit used in test configuration and system 10
2.5 EUT Operation Test Setup 10
2.6 Measurement Results Explanation Example 10
3 TEST RESULT **11**
3.1 6dB and 99% Bandwidth Measurement 11
3.2 Peak Output Power Measurement 13
3.3 Power Spectral Density Measurement 14
3.4 Conducted Band Edges and Spurious Emission Measurement 16
3.5 Radiated Band Edges and Spurious Emission Measurement 47
3.6 AC Conducted Emission Measurement 51
3.7 Antenna Requirements 53
4 LIST OF MEASURING EQUIPMENT **54**
5 UNCERTAINTY OF EVALUATION **55**
APPENDIX A. CONDUCTED TEST RESULTS
APPENDIX B. AC CONDUCTED EMISSION TEST RESULT
APPENDIX C. RADIATED SPURIOUS EMISSION
APPENDIX D. RADIATED SPURIOUS EMISSION PLOTS
APPENDIX E. DUTY CYCLE PLOTS

REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR740606-01C	Rev. 01	Initial issue of report	Aug. 29, 2017

SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result
3.1	15.247(a)(2)	6dB Bandwidth	≥ 0.5MHz	Pass
3.1	-	99% Bandwidth	-	Pass
3.2	15.247(b)	Power Output Measurement	≤ 30dBm	Pass
3.3	15.247(e)	Power Spectral Density	≤ 8dBm/3kHz	Pass
3.4	15.247(d)	Conducted Band Edges	≤ 20dBc	Pass
		Conducted Spurious Emission		Pass
3.5	15.247(d)	Radiated Band Edges and Radiated Spurious Emission	15.209(a) & 15.247(d)	Pass
3.6	15.207	AC Conducted Emission	15.207(a)	Pass
3.7	15.203 & 15.247(b)	Antenna Requirement	N/A	Pass

1 General Description

1.1 Applicant

S&R Land LLC
4000 S. Faber Place Drive, Suite 300
Charleston, South Carolina 29405

1.2 Product Feature of Equipment Under Test

Product Feature	
Equipment	Digital Media Receiver
Model Name	XC56PY
FCC ID	2ALWB-7232
EUT supports Radios application	WLAN 11b/g/n HT20 WLAN 11a/n HT20/HT40 Bluetooth BR/EDR/LE

1.3 Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx/Rx Channel Frequency Range	2412 MHz ~ 2472 MHz
Maximum (Peak) Output Power to antenna	**<Ant. 1>** 802.11b : 22.00 dBm (0.1585 W) 802.11g : 25.61 dBm (0.3639 W) 802.11n HT20 : 25.62 dBm (0.3648 W) **<Ant. 2>** 802.11b : 22.86 dBm (0.1932 W) 802.11g : 25.03 dBm (0.3184 W) 802.11n HT20 : 25.12 dBm (0.3251 W)
99% Occupied Bandwidth	**<Ant. 1>** 802.11b : 12.75MHz 802.11g : 18.50MHz 802.11n HT20 : 19.40MHz **<Ant. 2>** 802.11b : 13.15MHz 802.11g : 18.20MHz 802.11n HT20 : 19.00MHz
Antenna Type / Gain	**<Ant 1>** Fixed Internal Antenna with gain 3.3 dBi **<Ant 2>** Fixed Internal Antenna with gain 2.5 dBi
Type of Modulation	802.11b : DSSS (DBPSK / DQPSK / CCK) 802.11g/n : OFDM (BPSK / QPSK / 16QAM / 64QAM)
Antenna Function for Transmitter	<table><tr><td></td><td>Ant. 1</td><td>Ant. 2</td></tr><tr><td>802.11 b/g/n</td><td>V</td><td>V</td></tr></table>

1.4 Modification of EUT

No modifications are made to the EUT during all test items.

1.5 Testing Location

Sporton Lab is accredited to ISO 17025 by Taiwan Accreditation Foundation (TAF code : 1190) and the FCC designation No. TW0007 under the FCC 2.948(e) by Mutual Recognition Agreement (MRA) in FCC Test.

Test Site	SPORTON INTERNATIONAL INC.	
Test Site Location	No. 52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan District, Tao Yuan City, Taiwan, R.O.C. TEL: +886-3-327-3456 FAX: +886-3-328-4978	
Test Site No.	**Sporton Site No.**	
	TH05-HY	CO05-HY

Note: The test site complies with ANSI C63.4 2014 requirement.

Test Site	SPORTON INTERNATIONAL INC.
Test Site Location	No.58, Aly. 75, Ln. 564, Wenhua 3rd Rd. Guishan Dist, Taoyuan City, Taiwan (R.O.C.) TEL: +886-3-327-0868 FAX: +886-3-327-0855
Test Site No.	**Sporton Site No.**
	03CH13-HY

Note: The test site complies with ANSI C63.4 2014 requirement.

1.6 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- FCC Part 15 Subpart C §15.247
- FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v04
- ANSI C63.10-2013

Remark: All test items were verified and recorded according to the standards and without any deviation during the test.

2 Test Configuration of Equipment Under Test

a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower).

b. AC power line Conducted Emission was tested under maximum output power.

2.1 Carrier Frequency and Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
2400-2483.5 MHz	1	2412	8	2447
	2	2417	9	2452
	3	2422	10	2457
	4	2427	11	2462
	5	2432	12	2467
	6	2437	13	2472
	7	2442		

2.2 Test Mode

Final test mode of conducted test items and radiated spurious emissions are considering the modulation and worse data rates as below table.

Single Antenna

Modulation	Data Rate
802.11b	**1 Mbps**
802.11g	**6 Mbps**
802.11n HT20	**MCS0**

Test Cases	
AC Conducted Emission	Mode 1 :WLAN (2.4GHz) Link + Bluetooth Link + MP3 + Adapter

2.3 Connection Diagram of Test System

<WLAN Tx Mode>



<AC Conducted Emission Mode>



2.4 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	WLAN AP	ASUS	RT-AC66U	MSQ-RTAC66U	N/A	Unshielded, 1.8 m
2.	Speaker	JAWBONE	JAMBOX	V3J-JBE	N/A	N/A
3.	iPod Earphone	Apple	N/A	Verification	Unshielded, 1.0 m	N/A

2.5 EUT Operation Test Setup

The RF test items, programmed RF utility, “CMD” installed in the notebook make the EUT provide functions like channel selection and power level for continuous transmitting and receiving signals.

2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example:
The spectrum analyzer offset is derived from RF cable loss and attenuator factor.
Offset = RF cable loss + attenuator factor.
Following shows an offset computation example with cable loss 4.2 dB and 10dB attenuator.

Offset(dB) = RF cable loss(dB) + attenuator factor(dB).
= 4.2 + 10 = 14.2 (dB)

3 Test Result

3.1 6dB and 99% Bandwidth Measurement

3.1.1 Limit of 6dB and 99% Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.

3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedures

1. The testing follows FCC KDB Publication No. 558074 DTS D01 Meas. Guidance v04.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6 dB bandwidth must be greater than 500 kHz.
5. For 99% Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) = 1MHz and set the Video bandwidth (VBW) = 3MHz.
6. Measure and record the results in the test report.

3.1.4 Test Setup



3.1.5 Test Result of 6dB and 99% Occupied Bandwidth

Please refer to Appendix A.

Minimum 6dB Bandwidth	Maximum 99% Occupied Bandwidth
	
Date: 17.AUG.2017 21:33:47	Date: 18.AUG.2017 16:51:05

Note : The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

3.2 Peak Output Power Measurement

3.2.1 Limit of Peak Output Power

For systems using digital modulation in the 2400-2483.5MHz, the limit for peak output power is 30dBm. If transmitting antenna with directional gain greater than 6dBi is used, the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.

3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.2.3 Test Procedures

1. The testing follows the Measurement Procedure of FCC KDB No. 558074 DTS D01 Meas. Guidance v04 section 9.1.3 PKPM1 Peak power meter method.
2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Measure the conducted output power and record the results in the test report.

3.2.4 Test Setup



3.2.5 Test Result of Peak Output Power

Please refer to Appendix A.

3.2.6 Test Result of Average output Power (Reporting Only)

Please refer to Appendix A

3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8dBm in any 3kHz band at any time interval of continuous transmission.

3.3.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.3.3 Test Procedures

1. The testing follows Measurement Procedure 10.2 Method PKPSD of FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v04.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth VBW = 10 kHz In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6dB BW)
5. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.
6. Measure and record the results in the test report.

3.3.4 Test Setup



3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A.

Worst Case Power Density (dBm/3kHz) for Antenna 1



Date: 18.AUG.2017 15:10:21

Worst Case Power Density (dBm/3kHz) for Antenna 2



Date: 17.AUG.2017 21:25:23

3.4 Conducted Band Edges and Spurious Emission Measurement

3.4.1 Limit of Conducted Band Edges and Spurious Emission Measurement

In any 100 kHz bandwidth outside of the authorized frequency band, the emissions which fall in the non-restricted bands shall be attenuated at least 20 dB / 30dB relative to the maximum PSD level in 100 kHz by RF conducted measurement.

3.4.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.4.3 Test Procedures

1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v04.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

3.4.4 Test Setup



3.4.5 Test Result of Conducted Band Edges and Spurious Emission

Number of TX = 1, Ant. 1 (Measured)

Number of TX	1	**Ant. :**	1
Test Mode :	802.11b	**Temperature :**	21~25℃
Test Band :	2.4GHz Low	**Relative Humidity :**	51~54%
Test Channel :	01	**Test Engineer :**	Aking Chang

WLAN 802.11b Channel 01

100kHz PSD reference Level



Date: 18.AUG.2017 14:40:06

Low Channel Plot



Date: 18.AUG.2017 14:41:24

Spurious Emission 30MHz~3GHz



Date: 18.AUG.2017 14:41:36

Spurious Emission 2GHz~25GHz



Date: 18.AUG.2017 14:41:44

Number of TX :	1	**Ant. :**	1
Test Mode :	802.11b	**Temperature :**	21~25℃
Test Band :	2.4GHz Mid	**Relative Humidity :**	51~54%
Test Channel :	06	**Test Engineer :**	Aking Chang

WLAN 802.11b Channel 06

100kHz PSD reference Level



Date: 18.AUG.2017 14:49:33

Mid Channel Plot

Spurious Emission 30MHz~3GHz



Date: 18.AUG.2017 14:49:46

Spurious Emission 2GHz~25GHz



Date: 18.AUG.2017 14:49:55

Number of TX :	1	**Ant. :**	1
Test Mode :	802.11b	**Temperature :**	21~25℃
Test Band :	2.4GHz High	**Relative Humidity :**	51~54%
Test Channel :	11	**Test Engineer :**	Aking Chang

WLAN 802.11b Channel 11

100kHz PSD reference Level



Date: 18.AUG.2017 14:58:06

High Channel Plot



Date: 18.AUG.2017 14:59:29

Spurious Emission 30MHz~3GHz



Date: 18.AUG.2017 14:59:40

Spurious Emission 2GHz~25GHz



Date: 18.AUG.2017 14:59:49

Number of TX :	1	**Ant. :**	1
Test Mode :	802.11b	**Temperature :**	21~25℃
Test Band :	2.4GHz High	**Relative Humidity :**	51~54%
Test Channel :	12	**Test Engineer :**	Aking Chang

WLAN 802.11b Channel 12

100kHz PSD reference Level



Date: 18.AUG.2017 15:10:42

High Channel Plot



Date: 18.AUG.2017 15:21:16

Spurious Emission 30MHz~3GHz



Date: 18.AUG.2017 15:21:52

Spurious Emission 2GHz~25GHz



Date: 18.AUG.2017 15:22:00

Number of TX :	1	**Ant. :**	1
Test Mode :	802.11b	**Temperature :**	21~25℃
Test Band :	2.4GHz High	**Relative Humidity :**	51~54%
Test Channel :	13	**Test Engineer :**	Aking Chang

WLAN 802.11b Channel 13

100kHz PSD reference Level



Date: 18.AUG.2017 15:30:34

High Channel Plot



Date: 18.AUG.2017 15:40:29

Spurious Emission 30MHz~3GHz



Date: 18.AUG.2017 15:43:14

Spurious Emission 2GHz~25GHz



Date: 18.AUG.2017 15:43:23

Number of TX :	1	**Ant. :**	1
Test Mode :	802.11g	**Temperature :**	21~25℃
Test Band :	2.4GHz Low	**Relative Humidity :**	51~54%
Test Channel :	01	**Test Engineer :**	Aking Chang

WLAN 802.11g Channel 01

100kHz PSD reference Level



Date: 18.AUG.2017 15:54:15

Low Channel Plot



Date: 18.AUG.2017 15:54:54

Spurious Emission 30MHz~3GHz



Date: 18.AUG.2017 15:55:04

Spurious Emission 2GHz~25GHz



Date: 18.AUG.2017 15:55:13

Number of TX :	1	**Ant. :**	1
Test Mode :	802.11g	**Temperature :**	21~25℃
Test Band :	2.4GHz Mid	**Relative Humidity :**	51~54%
Test Channel :	06	**Test Engineer :**	Aking Chang

WLAN 802.11g Channel 06

100kHz PSD reference Level



Date: 18.AUG.2017 16:09:21

Mid Channel Plot

Spurious Emission 30MHz~3GHz



Date: 18.AUG.2017 16:09:48

Spurious Emission 2GHz~25GHz



Date: 18.AUG.2017 16:09:56

Number of TX :	1	**Ant. :**	1
Test Mode :	802.11g	**Temperature :**	21~25℃
Test Band :	2.4GHz High	**Relative Humidity :**	51~54%
Test Channel :	11	**Test Engineer :**	Aking Chang

WLAN 802.11g Channel 11

100kHz PSD reference Level



Date: 18.AUG.2017 16:00:42

High Channel Plot



Date: 18.AUG.2017 16:02:53

Spurious Emission 30MHz~3GHz



Date: 18.AUG.2017 16:03:04

Spurious Emission 2GHz~25GHz



Date: 18.AUG.2017 16:03:12

Number of TX :	1	**Ant. :**	1
Test Mode :	802.11g	**Temperature :**	21~25℃
Test Band :	2.4GHz High	**Relative Humidity :**	51~54%
Test Channel :	12	**Test Engineer :**	Aking Chang

WLAN 802.11g Channel 12

100kHz PSD reference Level



Date: 18.AUG.2017 16:16:22

High Channel Plot



Date: 18.AUG.2017 17:22:14

Spurious Emission 30MHz~3GHz



Date: 18.AUG.2017 16:21:31

Spurious Emission 2GHz~25GHz



Date: 18.AUG.2017 16:21:40

Number of TX :	1	**Ant. :**	1
Test Mode :	802.11g	**Temperature :**	21~25℃
Test Band :	2.4GHz High	**Relative Humidity :**	51~54%
Test Channel :	13	**Test Engineer :**	Aking Chang

WLAN 802.11g Channel 13

100kHz PSD reference Level



Date: 18.AUG.2017 16:27:35

High Channel Plot



Date: 18.AUG.2017 16:28:16

Spurious Emission 30MHz~3GHz



Date: 18.AUG.2017 16:29:44

Spurious Emission 2GHz~25GHz



Date: 18.AUG.2017 16:29:52

Number of TX :	1	**Ant. :**	1
Test Mode :	802.11n HT20	**Temperature :**	21~25℃
Test Band :	2.4GHz Low	**Relative Humidity :**	51~54%
Test Channel :	01	**Test Engineer :**	Aking Chang

WLAN 802.11n HT20 Channel 01

100kHz PSD reference Level



Date: 18.AUG.2017 16:43:42

Low Channel Plot



Date: 18.AUG.2017 16:44:00

Spurious Emission 30MHz~3GHz



Date: 18.AUG.2017 16:44:45

Spurious Emission 2GHz~25GHz



Date: 18.AUG.2017 16:44:54

Number of TX :	1	**Ant. :**	1
Test Mode :	802.11n HT20	**Temperature :**	21~25℃
Test Band :	2.4GHz Mid	**Relative Humidity :**	51~54%
Test Channel :	06	**Test Engineer :**	Aking Chang

WLAN 802.11n HT20 Channel 06

100kHz PSD reference Level



Date: 18.AUG.2017 16:50:12

Mid Channel Plot

Spurious Emission 30MHz~3GHz



Date: 18.AUG.2017 16:50:25

Spurious Emission 2GHz~25GHz



Date: 18.AUG.2017 16:50:33

Number of TX :	1	**Ant. :**	1
Test Mode :	802.11n HT20	**Temperature :**	21~25℃
Test Band :	2.4GHz High	**Relative Humidity :**	51~54%
Test Channel :	11	**Test Engineer :**	Aking Chang

WLAN 802.11n HT20 Channel 11

100kHz PSD reference Level



Date: 18.AUG.2017 16:56:12

High Channel Plot



Date: 18.AUG.2017 16:56:31

Spurious Emission 30MHz~3GHz



Date: 18.AUG.2017 16:57:17

Spurious Emission 2GHz~25GHz



Date: 18.AUG.2017 16:57:25

Number of TX :	1	**Ant. :**	1
Test Mode :	802.11n HT20	**Temperature :**	21~25℃
Test Band :	2.4GHz High	**Relative Humidity :**	51~54%
Test Channel :	12	**Test Engineer :**	Aking Chang

WLAN 802.11n HT20 Channel 12

100kHz PSD reference Level



Date: 18.AUG.2017 17:01:43

High Channel Plot



Date: 18.AUG.2017 17:06:17

Spurious Emission 30MHz~3GHz



Date: 18.AUG.2017 17:16:20

Spurious Emission 2GHz~25GHz



Date: 18.AUG.2017 17:16:28

Number of TX :	1	**Ant. :**	1
Test Mode :	802.11n HT20	**Temperature :**	21~25℃
Test Band :	2.4GHz High	**Relative Humidity :**	51~54%
Test Channel :	13	**Test Engineer :**	Aking Chang

WLAN 802.11n HT20 Channel 13

100kHz PSD reference Level



Date: 18.AUG.2017 17:11:15

High Channel Plot



Date: 18.AUG.2017 17:11:35

Spurious Emission 30MHz~3GHz



Date: 18.AUG.2017 17:12:03

Spurious Emission 2GHz~25GHz



Date: 18.AUG.2017 17:12:12

Number of TX = 1, Ant. 2 (Measured)

Number of TX	1	**Ant. :**	2
Test Mode :	802.11b	**Temperature :**	21~25℃
Test Band :	2.4GHz Low	**Relative Humidity :**	51~54%
Test Channel :	01	**Test Engineer :**	Aking Chang

WLAN 802.11b Channel 01

100kHz PSD reference Level



Date: 17.AUG.2017 21:25:36

Low Channel Plot



Date: 17.AUG.2017 21:25:48

Spurious Emission 30MHz~3GHz



Date: 17.AUG.2017 21:25:59

Spurious Emission 2GHz~25GHz



Date: 17.AUG.2017 21:26:08

Number of TX :	1	**Ant. :**	2
Test Mode :	802.11b	**Temperature :**	21~25℃
Test Band :	2.4GHz Mid	**Relative Humidity :**	51~54%
Test Channel :	06	**Test Engineer :**	Aking Chang

WLAN 802.11b Channel 06

100kHz PSD reference Level



Date: 17.AUG.2017 21:28:01

Mid Channel Plot

Spurious Emission 30MHz~3GHz



Date: 17.AUG.2017 21:28:12

Spurious Emission 2GHz~25GHz



Date: 17.AUG.2017 21:28:20

Number of TX :	1	**Ant. :**	2
Test Mode :	802.11b	**Temperature :**	21~25℃
Test Band :	2.4GHz High	**Relative Humidity :**	51~54%
Test Channel :	11	**Test Engineer :**	Aking Chang

WLAN 802.11b Channel 11

100kHz PSD reference Level



Date: 17.AUG.2017 21:30:56

High Channel Plot



Date: 17.AUG.2017 21:31:19

Spurious Emission 30MHz~3GHz



Date: 17.AUG.2017 21:31:42

Spurious Emission 2GHz~25GHz



Date: 17.AUG.2017 21:31:51

Number of TX :	1	**Ant. :**	2
Test Mode :	802.11b	**Temperature :**	21~25℃
Test Band :	2.4GHz High	**Relative Humidity :**	51~54%
Test Channel :	12	**Test Engineer :**	Aking Chang

WLAN 802.11b Channel 12

100kHz PSD reference Level



Date: 17.AUG.2017 21:34:25

High Channel Plot



Date: 17.AUG.2017 21:34:46

Spurious Emission 30MHz~3GHz



Date: 17.AUG.2017 21:35:03

Spurious Emission 2GHz~25GHz



Date: 17.AUG.2017 21:35:12

Number of TX :	1	**Ant. :**	2
Test Mode :	802.11b	**Temperature :**	21~25℃
Test Band :	2.4GHz High	**Relative Humidity :**	51~54%
Test Channel :	13	**Test Engineer :**	Aking Chang

WLAN 802.11b Channel 13

100kHz PSD reference Level



Date: 17.AUG.2017 21:39:35

High Channel Plot



Date: 17.AUG.2017 21:41:10

Spurious Emission 30MHz~3GHz



Date: 17.AUG.2017 21:43:09

Spurious Emission 2GHz~25GHz



Date: 17.AUG.2017 21:43:17

Number of TX :	1	**Ant. :**	2
Test Mode :	802.11g	**Temperature :**	21~25℃
Test Band :	2.4GHz Low	**Relative Humidity :**	51~54%
Test Channel :	01	**Test Engineer :**	Aking Chang

WLAN 802.11g Channel 01

100kHz PSD reference Level



Date: 17.AUG.2017 21:46:44

Low Channel Plot



Date: 17.AUG.2017 21:47:09

Spurious Emission 30MHz~3GHz



Date: 17.AUG.2017 21:47:24

Spurious Emission 2GHz~25GHz



Date: 17.AUG.2017 21:47:33

Number of TX :	1	**Ant. :**	2
Test Mode :	802.11g	**Temperature :**	21~25℃
Test Band :	2.4GHz Mid	**Relative Humidity :**	51~54%
Test Channel :	06	**Test Engineer :**	Aking Chang

WLAN 802.11g Channel 06

100kHz PSD reference Level



Date: 17.AUG.2017 21:49:14

Mid Channel Plot

Spurious Emission 30MHz~3GHz



Date: 17.AUG.2017 21:49:26

Spurious Emission 2GHz~25GHz



Date: 17.AUG.2017 21:49:35

Number of TX :	1	**Ant. :**	2
Test Mode :	802.11g	**Temperature :**	21~25℃
Test Band :	2.4GHz High	**Relative Humidity :**	51~54%
Test Channel :	11	**Test Engineer :**	Aking Chang

WLAN 802.11g Channel 11

100kHz PSD reference Level



Date: 17.AUG.2017 22:21:23

High Channel Plot



Date: 17.AUG.2017 22:21:34

Spurious Emission 30MHz~3GHz



Date: 17.AUG.2017 22:21:47

Spurious Emission 2GHz~25GHz



Date: 17.AUG.2017 22:21:56

Number of TX :	1	**Ant. :**	2
Test Mode :	802.11g	**Temperature :**	21~25℃
Test Band :	2.4GHz High	**Relative Humidity :**	51~54%
Test Channel :	12	**Test Engineer :**	Aking Chang

WLAN 802.11g Channel 12

100kHz PSD reference Level



Date: 17.AUG.2017 22:24:04

High Channel Plot



Date: 17.AUG.2017 22:24:17

Spurious Emission 30MHz~3GHz



Date: 17.AUG.2017 22:24:30

Spurious Emission 2GHz~25GHz



Date: 17.AUG.2017 22:24:38

Number of TX :	1	**Ant. :**	2
Test Mode :	802.11g	**Temperature :**	21~25℃
Test Band :	2.4GHz High	**Relative Humidity :**	51~54%
Test Channel :	13	**Test Engineer :**	Aking Chang

WLAN 802.11g Channel 13

100kHz PSD reference Level



Date: 17.AUG.2017 22:26:19

High Channel Plot



Date: 17.AUG.2017 22:26:31

Spurious Emission 30MHz~3GHz



Date: 17.AUG.2017 22:26:44

Spurious Emission 2GHz~25GHz



Date: 17.AUG.2017 22:26:53

Number of TX :	1	**Ant. :**	2
Test Mode :	802.11n HT20	**Temperature :**	21~25℃
Test Band :	2.4GHz Low	**Relative Humidity :**	51~54%
Test Channel :	01	**Test Engineer :**	Aking Chang

WLAN 802.11n HT20 Channel 01

100kHz PSD reference Level



Date: 17.AUG.2017 22:28:38

Low Channel Plot



Date: 17.AUG.2017 22:28:51

Spurious Emission 30MHz~3GHz



Date: 17.AUG.2017 22:29:05

Spurious Emission 2GHz~25GHz



Date: 17.AUG.2017 22:29:14

Number of TX :	1	**Ant. :**	2
Test Mode :	802.11n HT20	**Temperature :**	21~25℃
Test Band :	2.4GHz Mid	**Relative Humidity :**	51~54%
Test Channel :	06	**Test Engineer :**	Aking Chang

WLAN 802.11n HT20 Channel 06

100kHz PSD reference Level



Date: 17.AUG.2017 22:31:01

Mid Channel Plot

Spurious Emission 30MHz~3GHz



Date: 17.AUG.2017 22:31:12

Spurious Emission 2GHz~25GHz



Date: 17.AUG.2017 22:31:21

Number of TX :	1	**Ant. :**	2
Test Mode :	802.11n HT20	**Temperature :**	21~25℃
Test Band :	2.4GHz High	**Relative Humidity :**	51~54%
Test Channel :	11	**Test Engineer :**	Aking Chang

WLAN 802.11n HT20 Channel 11

100kHz PSD reference Level



Date: 17.AUG.2017 22:33:06

High Channel Plot



Date: 17.AUG.2017 22:33:20

Spurious Emission 30MHz~3GHz



Date: 17.AUG.2017 22:33:34

Spurious Emission 2GHz~25GHz



Date: 17.AUG.2017 22:33:42

Number of TX :	1	**Ant. :**	2
Test Mode :	802.11n HT20	**Temperature :**	21~25℃
Test Band :	2.4GHz High	**Relative Humidity :**	51~54%
Test Channel :	12	**Test Engineer :**	Aking Chang

WLAN 802.11n HT20 Channel 12

100kHz PSD reference Level



Date: 17.AUG.2017 22:36:22

High Channel Plot



Date: 17.AUG.2017 22:36:35

Spurious Emission 30MHz~3GHz



Date: 17.AUG.2017 22:36:49

Spurious Emission 2GHz~25GHz



Date: 17.AUG.2017 22:36:57

Number of TX :	1	**Ant. :**	2
Test Mode :	802.11n HT20	**Temperature :**	21~25℃
Test Band :	2.4GHz High	**Relative Humidity :**	51~54%
Test Channel :	13	**Test Engineer :**	Aking Chang

WLAN 802.11n HT20 Channel 13

100kHz PSD reference Level



Date: 17.AUG.2017 22:40:10

High Channel Plot



Date: 17.AUG.2017 22:40:56

Spurious Emission 30MHz~3GHz



Date: 17.AUG.2017 22:41:08

Spurious Emission 2GHz~25GHz



Date: 17.AUG.2017 22:41:16

3.5 Radiated Band Edges and Spurious Emission Measurement

3.5.1 Limit of Radiated band edge and Spurious Emission Measurement

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the output power of this device was measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.5.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.5.3 Test Procedures

1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v04.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
6. For testing below 1GHz, if the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the CISPR quasi-peak method and reported.
7. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than average limit (that means the emission level in average mode also complies with the limit in average mode), then peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
8. Use the following spectrum analyzer settings:
   (1) Span shall wide enough to fully capture the emission being measured;
   (2) Set RBW=100 kHz for f < 1 GHz; VBW ≥ RBW; Sweep = auto; Detector function = peak; Trace = max hold;
   (3) Set RBW = 1 MHz, VBW= 3MHz for f ≥ 1 GHz for peak measurement.
   For average measurement:
   - VBW = 10 Hz, when duty cycle is no less than 98 percent.
   - VBW ≥ 1/T, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

3.5.4 Test Setup

For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



3.5.5 Test Results of Radiated Spurious Emissions (9kHz ~ 30MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

There is a comparison data of both open-field test site and semi-Anechoic chamber, and the result came out very similar.

3.5.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix C and D.

3.5.7 Duty Cycle

Please refer to Appendix E.

3.5.8 Test Result of Radiated Spurious Emission (30MHz ~ 10th Harmonic)

Please refer to Appendix C and D.

3.6 AC Conducted Emission Measurement

3.6.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of Emission (MHz)	Conducted Limit (dBμV)	
	Quasi-Peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.

3.6.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.6.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room, and it was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF bandwidth = 9kHz) with Maximum Hold Mode.

3.6.4 Test Setup



AMN = Artificial mains network (LISN)
AE = Associated equipment
EUT = Equipment under test
ISN = Impedance stabilization network

3.6.5 Test Result of AC Conducted Emission

Please refer to Appendix B.

3.7 Antenna Requirements

3.7.1 Standard Applicable

If directional gain of transmitting Antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. The use of a permanently attached Antenna or of an Antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the rule.

3.7.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.7.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.

4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Power Meter	Anritsu	ML2495A	0932001	N/A	Sep. 29, 2016	Jul. 26, 2017 ~ Aug. 25, 2017	Sep. 28, 2017	Conducted (TH05-HY)
Power Sensor	Anritsu	MA2411B	0846202	300MHz~40GHz	Sep. 29, 2016	Jul. 26, 2017 ~ Aug. 25, 2017	Sep. 28, 2017	Conducted (TH05-HY)
Spectrum Analyzer	Rohde & Schwarz	FSP40	100057	9kHz-40GHz	Nov. 25, 2016	Jul. 26, 2017 ~ Aug. 25, 2017	Nov. 24, 2017	Conducted (TH05-HY)
AC Power Source	ChainTek	APC-1000W	N/A	N/A	N/A	Jul. 11, 2017	N/A	Conduction (CO05-HY)
EMI Test Receiver	Rohde & Schwarz	ESCI 7	100724	9kHz~7GHz	Aug. 30, 2016	Jul. 11, 2017	Aug. 29, 2017	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100080	9kHz~30MHz	Nov. 29, 2016	Jul. 11, 2017	Nov. 28, 2017	Conduction (CO05-HY)
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100315	9 kHz~30 MHz	May 15, 2017	Aug. 12, 2017 ~ Aug. 25, 2017	May 14, 2019	Radiation (03CH13-HY)
Amplifier	Sonoma-Instrument	310 N	187282	9KHz~1GHz	Dec. 21, 2016	Aug. 12, 2017 ~ Aug. 25, 2017	Dec. 20, 2017	Radiation (03CH13-HY)
Bilog Antenna	TESEQ	CBL 6111D&00800N1D01N-06	40103&04	30MHz to 1GHz	Jan. 07, 2017	Aug. 12, 2017 ~ Aug. 25, 2017	Jan. 06, 2018	Radiation (03CH13-HY)
Horn Antenna	SCHWARZBECK	BBHA 9120 D	9120D-1241	1GHz ~ 18GHz	May 02, 2017	Aug. 12, 2017 ~ Aug. 25, 2017	May 01, 2018	Radiation (03CH13-HY)
Preamplifier	MITEQ	AMF-7D-00101800-30-10P	1590074	1GHz~18GHz	May. 22, 2017	Aug. 12, 2017 ~ Aug. 25, 2017	May. 21, 2018	Radiation (03CH13-HY)
Preamplifier	Keysight	83017A	MY53270147	1GHz~26.5GHz	Jan. 09, 2017	Aug. 12, 2017 ~ Aug. 25, 2017	Jan. 08, 2018	Radiation (03CH13-HY)
Spectrum Analyzer	Keysight	N9010A	MY55370526	N/A	Mar. 15, 2017	Aug. 12, 2017 ~ Aug. 25, 2017	Mar. 14, 2018	Radiation (03CH13-HY)
Controller	EMEC	EM1000	N/A	Control Turn table & Ant Mast	N/A	Aug. 12, 2017 ~ Aug. 25, 2017	N/A	Radiation (03CH13-HY)
Antenna Mast	EMEC	AM-BS-4500-B	N/A	1m~4m	N/A	Aug. 12, 2017 ~ Aug. 25, 2017	N/A	Radiation (03CH13-HY)
Turn Table	EMEC	TT2000	N/A	0~360 Degree	N/A	Aug. 12, 2017 ~ Aug. 25, 2017	N/A	Radiation (03CH13-HY)
SHF-EHF Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA9170584	18GHz- 40GHz	Nov. 08, 2016	Aug. 12, 2017 ~ Aug. 25, 2017	Nov. 07, 2017	Radiation (03CH13-HY)
EMI Test Receiver	Agilent	N9038A(MXE)	MY53290053	20Hz to 26.5GHz	Jan. 12, 2017	Aug. 12, 2017 ~ Aug. 25, 2017	Jan. 11, 2018	Radiation (03CH13-HY)
Preamplifier	MITEQ	TTA 1840-35-HG	1887435	18GHz ~ 40GHz	Oct. 13, 2016	Aug. 12, 2017 ~ Aug. 25, 2017	Oct. 12, 2017	Radiation (03CH13-HY)

5 Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150kHz ~ 30MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	2.70

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	4.90

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	5.40

Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	4.30