


RF TEST REPORT



Report No.: 17070300-FCC-R

Supersede Report No.: N/A

Applicant	Shenzhen VVFLY Electronics Co., LTD.	
Product Name	Snore stopper	
Model No.	SL70	
Serial No.	YA1313,YA2313,YA3313,YA4313,YA1413,YA1513,YA1613	
Test Standard	FCC Part 15.247: 2016, ANSI C63.10: 2013	
Test Date	April 21 to May 02, 2017	
Issue Date	May 03, 2017	
Test Result	☒ Pass ☐ Fail	
Equipment complied with the specification ☒		
Equipment did not comply with the specification ☐		
		
Leen Yang Test Engineer	David Huang Checked By	
This test report may be reproduced in full only Test result presented in this test report is applicable to the tested sample only		

Issued by:

SIEMIC (SHENZHEN-CHINA) LABORATORIES

Zone A, Floor 1, Building 2 Wan Ye Long Technology Park

South Side of Zhoushi Road, Bao' an District, Shenzhen, Guangdong China 518108

Phone: +86 0755 2601 4629801 Email: China@siemic.com.cn

Laboratories Introduction

SIEMIC, headquartered in the heart of Silicon Valley, with superior facilities in US and Asia, is one of the leading independent testing and certification facilities providing customers with one-stop shop services for Compliance Testing and Global Certifications.



In addition to testing and certification, SIEMIC provides initial design reviews and compliance management throughout a project. Our extensive experience with China, Asia Pacific, North America, European, and International compliance requirements, assures the fastest, most cost effective way to attain regulatory compliance for the global markets.

Accreditations for Conformity Assessment

Country/Region	Scope
USA	EMC, RF/Wireless, SAR, Telecom
Canada	EMC, RF/Wireless, SAR, Telecom
Taiwan	EMC, RF, Telecom, SAR, Safety
Hong Kong	RF/Wireless, SAR, Telecom
Australia	EMC, RF, Telecom, SAR, Safety
Korea	EMI, EMS, RF, SAR, Telecom, Safety
Japan	EMI, RF/Wireless, SAR, Telecom
Singapore	EMC, RF, SAR, Telecom
Europe	EMC, RF, SAR, Telecom, Safety

Test Report No.	17070300-FCC-R
Page	3 of 45

This page has been left blank intentionally.

CONTENTS

1. REPORT REVISION HISTORY	5
2. CUSTOMER INFORMATION	5
3. TEST SITE INFORMATION	5
4. EQUIPMENT UNDER TEST (EUT) INFORMATION	6
5. TEST SUMMARY	7
6. MEASUREMENTS, EXAMINATION AND DERIVED RESULTS	8
6.1 ANTENNA REQUIREMENT	8
6.2 DTS (6 DB) CHANNEL BANDWIDTH	9
6.3 MAXIMUM OUTPUT POWER	11
6.4 POWER SPECTRAL DENSITY	13
6.5 BAND-EDGE & UNWANTED EMISSIONS INTO RESTRICTED FREQUENCY BANDS	15
6.6 AC POWER LINE CONDUCTED EMISSIONS	18
6.7 RADIATED EMISSIONS & RESTRICTED BAND	24
ANNEX A. TEST INSTRUMENT	30
ANNEX B. EUT AND TEST SETUP PHOTOGRAPHS	31
ANNEX C. TEST SETUP AND SUPPORTING EQUIPMENT	40
ANNEX D. USER MANUAL / BLOCK DIAGRAM / SCHEMATICS / PARTLIST	44
ANNEX E. DECLARATION OF SIMILARITY	45

1. Report Revision History

Report No.	Report Version	Description	Issue Date
17070300-FCC-R	NONE	Original	May 03, 2017

2. Customer information

Applicant Name	Shenzhen VVFLY Electronics Co., LTD.
Applicant Add	Room 1310, Changhong Science and Technology Building, Southern District in High-Tech Zone, Nanshan Districts, Shenzhen, China
Manufacturer	Shenzhen VVFLY Electronics Co., LTD.
Manufacturer Add	Room 1310, Changhong Science and Technology Building, Southern District in High-Tech Zone, Nanshan Districts

3. Test site information

Lab performing tests	SIEMIC (Shenzhen-China) LABORATORIES
Lab Address	Zone A, Floor 1, Building 2 Wan Ye Long Technology Park South Side of Zhoushi Road, Bao' an District, Shenzhen, Guangdong China 518108
FCC Test Site No.	718246
IC Test Site No.	4842E-1
Test Software of Radiated Emission	Radiated Emission Program-To Shenzhen v2.0
Test Software of Conducted Emission	EZ-EMC(ver.lcp-03A1)

4. Equipment under Test (EUT) Information

Description of EUT:	Snore stopper
Main Model:	SL70
Serial Model:	YA1313,YA2313,YA3313,YA4313,YA1413,YA1513,YA1613
Date EUT received:	April 21, 2017
Test Date(s):	April 21 to May 02, 2017
Equipment Category :	DTS
Antenna Gain:	3.1dBi
Antenna Type:	Ceramic chip antenna
Type of Modulation:	GFSK
RF Operating Frequency (ies):	2402-2480 MHz (TX/RX)
Max. Output Power:	0.310dBm
Number of Channels:	40CH
Port:	USB Port
Trade Name :	BEURER
Input Power:	Battery: Spec: 3.7V,0.296Wh USB: DC5V
FCC ID:	2ALXG-SL70

5. Test Summary

The product was tested in accordance with the following specifications.

All testing has been performed according to below product classification:

FCC Rules	Description of Test	Result
§15.203	Antenna Requirement	Compliance
§15.247 (a)(2)	DTS (6 dB) CHANNEL BANDWIDTH	Compliance
§15.247(b)(3)	Conducted Maximum Output Power	Compliance
§15.247(e)	Power Spectral Density	Compliance
§15.247(d)	Band-Edge & Unwanted Emissions into Restricted Frequency Bands	Compliance
§15.207 (a),	AC Power Line Conducted Emissions	Compliance
§15.205, §15.209, §15.247(d)	Radiated Emissions & Unwanted Emissions into Restricted Frequency Bands	Compliance

Measurement Uncertainty

Emissions		
Test Item	Description	Uncertainty
Band-Edge & Unwanted Emissions into Restricted Frequency Bands and Radiated Emissions & Unwanted Emissions into Restricted Frequency Bands	Confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2 (for EUTs < 0.5m X 0.5m X 0.5m)	+5.6dB/-4.5dB
-	-	-

6. Measurements, Examination And Derived Results

6.1 Antenna Requirement

Applicable Standard

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
- b. Antenna must use a unique type of connector to attach to the EUT.

Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

And according to FCC 47 CFR section 15.247 (b), if the transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Antenna Connector Construction

The EUT has 1 antenna:


A permanently attached Ceramic chip antenna for BLE, the gain is 3.1dBi for BLE.

The antenna meets up with the ANTENNA REQUIREMENT.

Result: Compliance.

6.2 DTS (6 dB) Channel Bandwidth

Temperature	22 °C
Relative Humidity	58%
Atmospheric Pressure	1025mbar
Test date :	April 25, 2017
Tested By :	Leen Yang

Spec	Item	Requirement	Applicable
§ 15.247(a)(2)	a)	6dB BW ≥ 500kHz;	☒
RSS Gen(4.6.1)	b)	99% BW: For FCC reference only; required by IC.	☒
Test Setup	 Spectrum Analyzer EUT		
Test Procedure	558074 D01 DTS MEAS Guidance v03r03, 8.1 DTS bandwidth 6dB Emission bandwidth measurement procedure - Set RBW = 100 kHz. - Set the video bandwidth (VBW) ≥ 3 RBW. - Detector = Peak. - Trace mode = max hold. - Sweep = auto couple. - Allow the trace to stabilize. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.		
Remark			
Result	☒ Pass ☐ Fail		

Test Data ☒ Yes ☐ N/A


Test Plot ☒ Yes (See below) ☐ N/A

6dB Bandwidth measurement result


Test Data

CH	Frequency (MHz)	6dB Bandwidth (kHz)	99% Occupied Bandwidth (MHz)
Low	2402	663.5	1.0431
Mid	2440	664.2	1.0423
High	2480	674.5	1.0444


Test Plots



6dB Bandwidth - Low CH 2402



6dB Bandwidth - Mid CH 2440




6dB Bandwidth - High CH 2480

6.3 Maximum Output Power

Temperature	22 °C
Relative Humidity	58%
Atmospheric Pressure	1025mbar
Test date :	April 25, 2017
Tested By :	Leen Yang

Requirement(s):

Spec	Item	Requirement	Applicable
§15.247(b) (3),RSS210 (A8.4)	a)	FHSS in 2400-2483.5MHz with ≥ 75 channels: ≤ 1 Watt	☐
	b)	FHSS in 5725-5850MHz: ≤ 1 Watt	☐
	c)	For all other FHSS in the 2400-2483.5MHz band: ≤ 0.125 Watt.	☐
	d)	FHSS in 902-928MHz with ≥ 50 channels: ≤ 1 Watt	☐
	e)	FHSS in 902-928MHz with ≥ 25 & <50 channels: ≤ 0.25 Watt	☐
	f)	DTS in 902-928MHz, 2400-2483.5MHz: ≤ 1 Watt	☒
Test Setup	 Spectrum Analyzer EUT		
Test Procedure	558074 D01 DTS MEAS Guidance v03r03, 9.1.2 Integrated band power method Maximum output power measurement procedure a) Set the RBW $\geq$ DTS bandwidth. b) Set VBW $\geq 3 \times$ RBW. c) Set span $\geq 3 \times$ RBW d) Sweep time = auto couple. e) Detector = peak. f) Trace mode = max hold. g) Allow trace to fully stabilize. h) Use peak marker function to determine the peak amplitude level.		
Remark			
Result	☒ Pass ☐ Fail		

Test Data ☒ Yes ☐ N/A


Test Plot ☒ Yes (See below) ☐ N/A

Output Power measurement result

Test Data


Type	CH	Frequency (MHz)	Conducted Power (dBm)	Limit (dBm)	Result
Output power	Low	2402	0.310	30	Pass
	Mid	2440	0.127	30	Pass
	High	2480	0.242	30	Pass

Test Plots



6.4 Power Spectral Density

Temperature	22 °C
Relative Humidity	58%
Atmospheric Pressure	1025mbar
Test date :	April 25, 2017
Tested By :	Leen Yang

Spec	Item	Requirement	Applicable
§15.247(e)	a)	The power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.	☒
Test Setup	 Spectrum Analyzer EUT		
Test Procedure	558074 D01 DTS MEAS Guidance v03r03, 10.2 power spectral density method power spectral density measurement procedure - a) Set analyzer center frequency to DTS channel center frequency. - b) Set the span to 1.5 times the DTS bandwidth. - c) Set the RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$. - d) Set the VBW $\geq 3 \times \text{RBW}$. - e) Detector = peak. - f) Sweep time = auto couple. - g) Trace mode = max hold. - h) Allow trace to fully stabilize. - i) Use the peak marker function to determine the maximum amplitude level within the RBW. - j) If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.		
Remark			
Result	☒ Pass ☐ Fail		

Test Data ☒ Yes ☐ N/A
 Test Plot ☒ Yes (See below) ☐ N/A

Power Spectral Density measurement result

Test Data

Type	CH	Freq (MHz)	Reading (dBm)	Factor (dB)	Result (dBm)	Limit (dBm)	Result
PSD	Low	2402	-6.444	-5.23	-11.674	8	Pass
	Mid	2440	-3.894	-5.23	-9.124	8	Pass
	High	2480	-6.791	-5.23	-12.021	8	Pass

Note: factor= $10\log(3/10)=-5.23$

Test Plots



PSD - Low CH 2402



PSD - Mid CH 2440




PSD - High CH 2480

6.5 Band-Edge & Unwanted Emissions into Restricted Frequency Bands

Temperature	23 °C
Relative Humidity	59%
Atmospheric Pressure	1026mbar
Test date :	April 26, 2017
Tested By :	Leen Yang

Requirement(s):

Spec	Item	Requirement	Applicable
§15.247(d)	a)	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits.	☒
Test Setup			
Test Procedure	Radiated Method Only 1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator. 2. Position the EUT without connection to measurement instrument. Put it on the Rotated table and turn on the EUT and make it operate in transmitting mode. Then set it to Low Channel and High Channel within its operating range, and make sure the instrument is operated in its linear range.		


Test Report No.	17070300-FCC-R
Page	16 of 45

	- 3. First, set both RBW and VBW of spectrum analyzer to 100 kHz with a convenient frequency span including 100kHz bandwidth from band edge, check the emission of EUT, if pass then set Spectrum Analyzer as below: a. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasiy Peak detection at frequency below 1GHz. b. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz with Peak detection for Peak measurement at frequency above 1GHz. c. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 10Hz with Peak detection for Average Measurement as below at frequency above 1GHz. - 4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency. - 5. Repeat above procedures until all measured frequencies were complete.
Remark	
Result	☒ Pass ☐ Fail

Test Data ☐ Yes ☒ N/A
Test Plot ☒ Yes (See below) ☐ N/A

Test Plots

Band Edge measurement result




Note: Both Horizontal and vertical polarities were investigated

6.6 AC Power Line Conducted Emissions

Temperature	25 °C
Relative Humidity	57%
Atmospheric Pressure	1024mbar
Test date :	April 24, 2017
Tested By :	Leen Yang

Requirement(s):

Spec	Item	Requirement	Applicable														
47CFR§15.207, RSS210 (A8.1)	a)	For Low-power radio-frequency devices that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 [mu] H/50 ohms line impedance stabilization network (LISN). The lower limit applies at the boundary between the frequencies ranges.	☒														
		<table><tr><th rowspan="2">Frequency ranges (MHz)</th><th colspan="2">Limit (dBµV)</th></tr><tr><th>QP</th><th>Average</th></tr><tr><td>0.15 ~ 0.5</td><td>66 – 56</td><td>56 – 46</td></tr><tr><td>0.5 ~ 5</td><td>56</td><td>46</td></tr><tr><td>5 ~ 30</td><td>60</td><td>50</td></tr></table>		Frequency ranges (MHz)	Limit (dBµV)		QP	Average	0.15 ~ 0.5	66 – 56	56 – 46	0.5 ~ 5	56	46	5 ~ 30	60	50
		Frequency ranges (MHz)			Limit (dBµV)												
				QP	Average												
		0.15 ~ 0.5		66 – 56	56 – 46												
		0.5 ~ 5		56	46												
5 ~ 30	60	50															

Test Setup	 Note: 1.Support units were connected to second LISN. 2.Both of LISNs (AMN) are 80cm from EUT and at least 80cm from other units and other metal planes support units.
------------	---

Procedure	- The EUT and supporting equipment were set up in accordance with the requirements of the standard on top of a 1.5m x 1m x 0.8m high, non-metallic table. - The power supply for the EUT was fed through a 50W/50mH EUT LISN, connected to filtered mains. - The RF OUT of the EUT LISN was connected to the EMI test receiver via a low-loss
-----------	---


Test Report No.	17070300-FCC-R
Page	19 of 45

	coaxial cable. 4. All other supporting equipment were powered separately from another main supply. 5. The EUT was switched on and allowed to warm up to its normal operating condition. 6. A scan was made on the NEUTRAL line (for AC mains) or Earth line (for DC power) over the required frequency range using an EMI test receiver. 7. High peaks, relative to the limit line, The EMI test receiver was then tuned to the selected frequencies and the necessary measurements made with a receiver bandwidth setting of 10 kHz. 8. Step 7 was then repeated for the LIVE line (for AC mains) or DC line (for DC power).
Remark	
Result	☒ Pass ☐ Fail

Test Data ☒ Yes ☐ N/A

Test Plot ☒ Yes (See below) ☐ N/A

Test Mode: Transmitting Mode




Test Data

Phase Line Plot at 120Vac, 60Hz

No.	P/L	Frequency (MHz)	Reading (dBμV)	Detector	Corrected (dB)	Result (dBμV)	Limit (dBμV)	Margin (dB)
1	L1	0.2787	17.81	QP	10.03	27.84	60.85	-33.01
2	L1	0.2787	-0.01	AVG	10.03	10.02	50.85	-40.83
3	L1	0.4815	20.23	QP	10.03	30.26	56.31	-26.05
4	L1	0.4815	2.53	AVG	10.03	12.56	46.31	-33.75
5	L1	0.5517	16.51	QP	10.03	26.54	56.00	-29.46
6	L1	0.5517	4.05	AVG	10.03	14.08	46.00	-31.92
7	L1	0.7467	10.28	QP	10.03	20.31	56.00	-35.69
8	L1	0.7467	-0.94	AVG	10.03	9.09	46.00	-36.91
9	L1	1.7646	8.38	QP	10.04	18.42	56.00	-37.58
10	L1	1.7646	-2.57	AVG	10.04	7.47	46.00	-38.53
11	L1	3.9360	6.48	QP	10.07	16.55	56.00	-39.45
12	L1	3.9360	-2.41	AVG	10.07	7.66	46.00	-38.34

Test Mode: Transmitting Mode




Test Data

Phase Neutral Plot at 120Vac, 60Hz

No.	P/L	Frequency (MHz)	Reading (dBuV)	Detector	Corrected (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)
1	N	0.1773	19.56	QP	10.02	29.58	64.61	-35.03
2	N	0.1773	-0.88	AVG	10.02	9.14	54.61	-45.47
3	N	0.2670	18.41	QP	10.02	28.43	61.21	-32.78
4	N	0.2670	-2.00	AVG	10.02	8.02	51.21	-43.19
5	N	0.4074	17.29	QP	10.02	27.31	57.70	-30.39
6	N	0.4074	-4.31	AVG	10.02	5.71	47.70	-41.99
7	N	0.4854	16.29	QP	10.02	26.31	56.25	-29.94
8	N	0.4854	0.06	AVG	10.02	10.08	46.25	-36.17
9	N	4.4118	8.36	QP	10.06	18.42	56.00	-37.58
10	N	4.4118	-3.92	AVG	10.06	6.14	46.00	-39.86
11	N	7.3953	6.44	QP	10.10	16.54	60.00	-43.46
12	N	7.3953	-3.23	AVG	10.10	6.87	50.00	-43.13

Test Mode: Transmitting Mode




Test Data

Phase Line Plot at 240Vac, 60Hz

No.	P/L	Frequency (MHz)	Reading (dBμV)	Detector	Corrected (dB)	Result (dBμV)	Limit (dBμV)	Margin (dB)
1	L1	0.2280	40.06	QP	10.03	50.09	62.52	-12.43
2	L1	0.2280	31.42	AVG	10.03	41.45	52.52	-11.07
3	L1	0.2904	33.77	QP	10.03	43.80	60.51	-16.71
4	L1	0.2904	26.72	AVG	10.03	36.75	50.51	-13.76
5	L1	0.3255	40.51	QP	10.03	50.54	59.57	-9.03
6	L1	0.3255	33.03	AVG	10.03	43.06	49.57	-6.51
7	L1	0.5790	21.95	QP	10.03	31.98	56.00	-24.02
8	L1	0.5790	14.97	AVG	10.03	25.00	46.00	-21.00
9	L1	0.6804	18.18	QP	10.03	28.21	56.00	-27.79
10	L1	0.6804	6.58	AVG	10.03	16.61	46.00	-29.39
11	L1	1.3005	13.76	QP	10.03	23.79	56.00	-32.21
12	L1	1.3005	6.44	AVG	10.03	16.47	46.00	-29.53

Test Mode: Transmitting Mode



Test Data

Phase Neutral Plot at 240Vac, 60Hz


No.	P/L	Frequency (MHz)	Reading (dBμV)	Detector	Corrected (dB)	Result (dBμV)	Limit (dBμV)	Margin (dB)
1	N	0.2280	39.54	QP	10.02	49.56	62.52	-12.96
2	N	0.2280	27.47	AVG	10.02	37.49	52.52	-15.03
3	N	0.2904	32.08	QP	10.02	42.10	60.51	-18.41
4	N	0.2904	25.02	AVG	10.02	35.04	50.51	-15.47
5	N	0.3216	39.07	QP	10.02	49.09	59.67	-10.58
6	N	0.3216	31.87	AVG	10.02	41.89	49.67	-7.78
7	N	0.5790	24.28	QP	10.02	34.30	56.00	-21.70
8	N	0.5790	16.80	AVG	10.02	26.82	46.00	-19.18
9	N	1.3005	16.21	QP	10.03	26.24	56.00	-29.76
10	N	1.3005	8.22	AVG	10.03	18.25	46.00	-27.75
11	N	2.2677	15.31	QP	10.04	25.35	56.00	-30.65
12	N	2.2677	7.36	AVG	10.04	17.40	46.00	-28.60

6.7 Radiated Emissions & Restricted Band

Temperature	25 °C
Relative Humidity	57%
Atmospheric Pressure	1024mbar
Test date :	April 24, 2017
Tested By :	Leen Yang

Requirement(s):

Spec	Item	Requirement	Applicable										
47CFR§15.247(d), RSS210 (A8.5)	a)	Except higher limit as specified elsewhere in other section, the emissions from the low-power radio-frequency devices shall not exceed the field strength levels specified in the following table and the level of any unwanted emissions shall not exceed the level of the fundamental emission. The tighter limit applies at the band edges <table><tr><th>Frequency range (MHz)</th><th>Field Strength (µV/m)</th></tr><tr><td>30 – 88</td><td>100</td></tr><tr><td>88 – 216</td><td>150</td></tr><tr><td>216 - 960</td><td>200</td></tr><tr><td>Above 960</td><td>500</td></tr></table>	Frequency range (MHz)	Field Strength (µV/m)	30 – 88	100	88 – 216	150	216 - 960	200	Above 960	500	☒
	Frequency range (MHz)	Field Strength (µV/m)											
	30 – 88	100											
	88 – 216	150											
216 - 960	200												
Above 960	500												
b)	For non-restricted band, In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB or 30dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, determined by the measurement method on output power to be used. Attenuation below the general limits specified in § 15.209(a) is not required ☒ 20 dB down ☐ 30 dB down	☒											
c)	or restricted band, emission must also comply with the radiated emission limits specified in 15.209	☒											


Test Setup	
Procedure	- The EUT was switched on and allowed to warm up to its normal operating condition. - The test was carried out at the selected frequency points obtained from the EUT characterization. Maximization of the emissions, was carried out by rotating the EUT, changing the antenna polarization, and adjusting the antenna height in the following manner: - Vertical or horizontal polarization (whichever gave the higher emission level over a full rotation of the EUT) was chosen. - The EUT was then rotated to the direction that gave the maximum emission. - Finally, the antenna height was adjusted to the height that gave the maximum emission. - The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasi Peak detection at frequency below 1GHz. - The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz with Peak detection for Peak measurement at frequency above 1GHz. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 10Hz with Peak detection for Average Measurement as below at frequency above 1GHz. - Steps 2 and 3 were repeated for the next frequency point, until all selected frequency points were measured.
Remark	Different RF configuration has been evaluated but not much difference was found. The data presented here is the worst case data with EUT under 802.11n – HT20-2437MHz mode.
Result	☒ Pass ☐ Fail

Test Data ☒ Yes ☐ N/A

Test Plot ☒ Yes (See below) ☐ N/A

Test Mode: Transmitting Mode

Below 1GHz




Test Data

Vertical Polarity Plot @3m

No.	P/L	Frequency	Reading	Detect or	Ant_F	PA_G	Cab_L	Result	Limit	Margin	Height	Degr ee
		(MHz)	(dBuV/m)		(dB/m)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	(cm)	(°)
1	V	47.6586	43.42	peak	9.43	22.34	0.78	31.29	40.00	-8.71	100	193
2	V	43.6585	41.05	peak	11.49	22.29	0.76	31.01	40.00	-8.99	100	333
3	V	37.4165	35.00	peak	15.79	22.26	0.77	29.30	40.00	-10.70	100	240
4	V	54.2610	40.63	peak	7.93	22.39	0.78	26.95	40.00	-13.05	200	85
5	V	89.5900	38.76	peak	7.98	22.32	0.96	25.38	43.50	-18.12	100	50
6	V	74.6569	35.09	peak	7.71	22.40	0.96	21.36	40.00	-18.64	100	286

Below 1GHz



Test Data

Horizontal Polarity Plot @3m

No.	P/L	Frequency	Reading	Detect or	Ant_F	PA_G	Cab_L	Result	Limit	Margin	Height	Degree
		(MHz)	(dBuV/m)		(dB/m)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	(cm)	(°)
1	H	43.8119	42.96	peak	11.38	22.29	0.76	32.81	40.00	-7.19	100	22
2	H	37.4165	35.92	peak	15.79	22.26	0.77	30.22	40.00	-9.78	100	137
3	H	47.6586	45.05	peak	9.43	22.34	0.78	32.92	40.00	-7.08	100	161
4	H	62.4314	38.19	peak	7.42	22.40	0.81	24.02	40.00	-15.98	100	277
5	H	74.6569	40.08	peak	7.71	22.40	0.96	26.35	40.00	-13.65	100	333
6	H	53.8818	37.45	peak	7.97	22.39	0.78	23.81	40.00	-16.19	100	15

Above 1GHz

Test Mode:	Transmitting Mode
------------	-------------------

Low Channel (2402 MHz)

Frequency (MHz)	S.A. Reading (dBμV)	Detector (PK/AV)	Polarity (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	Pre-Amp. Gain (dB)	Cord. Amp. (dBμV/m)	Limit (dBμV/m)	Margin (dB)
4804	38.59	AV	V	33.83	6.86	31.72	47.56	54	-6.44
4804	37.61	AV	H	33.83	6.86	31.72	46.58	54	-7.42
4804	49.22	PK	V	33.83	6.86	31.72	58.19	74	-15.81
4804	46.58	PK	H	33.83	6.86	31.72	55.55	74	-18.45
17794	24.36	AV	V	45.03	11.21	32.38	48.22	54	-5.78
17794	23.15	AV	H	45.03	11.21	32.38	47.01	54	-6.99
17794	40.25	PK	V	45.03	11.21	32.38	64.11	74	-9.89
17794	39.47	PK	H	45.03	11.21	32.38	63.33	74	-10.67

Middle Channel (2440 MHz)

Frequency (MHz)	S.A. Reading (dBμV)	Detector (PK/AV)	Polarity (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	Pre-Amp. Gain (dB)	Cord. Amp. (dBμV/m)	Limit (dBμV/m)	Margin (dB)
4880	39.47	AV	V	33.86	6.82	31.82	48.33	54	-5.67
4880	38.12	AV	H	33.86	6.82	31.82	46.98	54	-7.02
4880	47.53	PK	V	33.86	6.82	31.82	56.39	74	-17.61
4880	46.28	PK	H	33.86	6.82	31.82	55.14	74	-18.86
17803	24.19	AV	V	45.15	11.18	32.41	48.11	54	-5.89
17803	23.58	AV	H	45.15	11.18	32.41	47.5	54	-6.5
17803	41.02	PK	V	45.15	11.18	32.41	64.94	74	-9.06
17803	39.86	PK	H	45.15	11.18	32.41	63.78	74	-10.22

High Channel (2480 MHz)

Frequency (MHz)	S.A. Reading (dBμV)	Detector (PK/AV)	Polarity (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	Pre-Amp. Gain (dB)	Cord. Amp. (dBμV/m)	Limit (dBμV/m)	Margin (dB)
4960	38.79	AV	V	33.9	6.76	31.92	47.53	54	-6.47
4960	37.61	AV	H	33.9	6.76	31.92	46.35	54	-7.65
4960	48.21	PK	V	33.9	6.76	31.92	56.95	74	-17.05
4960	47.13	PK	H	33.9	6.76	31.92	55.87	74	-18.13
17797	24.35	AV	V	45.22	11.35	32.38	48.54	54	-5.46
17797	23.68	AV	H	45.22	11.35	32.38	47.87	54	-6.13
17797	40.61	PK	V	45.22	11.35	32.38	64.8	74	-9.2
17797	39.75	PK	H	45.22	11.35	32.38	63.94	74	-10.06

Note:

1, The testing has been conformed to $10 \times 2480 \text{ MHz} = 24,800 \text{ MHz}$

2, All other emissions more than 30 dB below the limit

3, X-Axis, Y-Axis and Z-Axis were investigated. The results above show only the worst case.

Annex A. TEST INSTRUMENT

Instrument	Model	Serial #	Cal Date	Cal Due	In use
AC Line Conducted					
EMI test receiver	ESCS30	8471241027	09/16/2016	09/15/2017	☒
Line Impedance	LI-125A	191106	09/24/2016	09/23/2017	☒
Line Impedance	LI-125A	191107	09/24/2016	09/23/2017	☒
LISN	ISN T800	34373	09/24/2016	09/23/2017	☒
Double Ridge Horn Antenna (1 ~18GHz)	AH-118	71283	09/23/2016	09/22/2017	☒
Transient Limiter	LIT-153	531118	08/31/2016	08/30/2017	☒
RF conducted test					
Agilent ESA-E SERIES	E4407B	MY45108319	09/16/2016	09/15/2017	☒
Power Splitter	1#	1#	08/31/2016	08/30/2017	☒
DC Power Supply	E3640A	MY40004013	09/16/2016	09/15/2017	☒
Radiated Emissions					
EMI test receiver	ESL6	100262	09/16/2016	09/15/2017	☒
Positioning Controller	UC3000	MF780208282	11/18/2016	11/17/2017	☒
OPT 010 AMPLIFIER (0.1-1300MHz)	8447E	2727A02430	08/31/2016	08/30/2017	☒
Microwave Preamplifier (1 ~ 26.5GHz)	8449B	3008A02402	03/23/2017	03/22/2018	☒
Bilog Antenna (30MHz~6GHz)	JB6	A110712	09/20/2016	09/19/2017	☒
Double Ridge Horn Antenna (1 ~18GHz)	AH-118	71283	09/23/2016	09/22/2017	☒
Universal Radio Communication Tester	CMU200	121393	09/24/2016	09/23/2017	☒

Annex B. EUT And Test Setup Photographs

Annex B.i. Photograph: EUT External Photo

Whole Package View




EUT - Front View




EUT - Rear View




EUT - Top View




EUT - Bottom View



EUT - Left View



EUT - Right View



USB Port



Annex B.ii. Photograph: EUT Internal Photo

Cover Off - Top View 1




Cover Off - Top View 2




Battery - Front View




Battery - Rear View




Mainboard - Front View



Mainboard – Rear View



BLE - Antenna View




Annex B.iii. Photograph: Test Setup Photo



Conducted Emissions Test Setup Front View



Conducted Emissions Test Setup Side View



Radiated Spurious Emissions Test Setup Below 1GHz




Radiated Spurious Emissions Test Setup Above
1GHz


Annex C. TEST SETUP AND SUPPORTING EQUIPMENT

Annex C.ii. TEST SET UP BLOCK


Block Configuration Diagram for AC Line Conducted Emissions



Block Configuration Diagram for Radiated Emissions (Below 1GHz) .



Block Configuration Diagram for Radiated Emissions (Above 1GHz) .



Annex C. ii. SUPPORTING EQUIPMENT DESCRIPTION

The following is a description of supporting equipment and details of cables used with the EUT.

Supporting Equipment:

Manufacturer	Equipment Description	Model	Serial No
Shenzhen VVFLY Electronics Co., L TD.	Adapter	P6200	SP052
Shenzhen VVFLY Electronics Co., L TD.	phone	N9200	AD4500

Supporting Cable:

Cable type	Shield Type	Ferrite Core	Length	Serial No
USB Cable	Un-shielding	No	0.8m	SP052

Annex D. User Manual / Block Diagram / Schematics / Partlist

Please see the attachment


Annex E. DECLARATION OF SIMILARITY

Differences Declaration

To whom concern, We company **Shenzhen VVFLY Electronics Co., LTD.** hereby declares: The product model(s) YA1313 , YA2313 , YA3313 , YA4313 , YA1413 , YA1513 , YA1613 is(or are) identical in the same PCB layout, interior structure and electrical circuits with the model **SL70** which tested in **SIEMIC (Shenzhen-China) Laboratories** the only differences are the model name and appearance color for commercial purpose.

Authorized signature: 黄志伟

Position: 产品经理

Company stamp: 

Date: 2017.5.10