

FCC Part 15C

Measurement and Test Report

For

Intrinity Global Limited.

**Unit 1707, Floor 17, Westley Square, 48 Hoi Yuen Road, Kwun Tong,
Hong Kong**

FCC ID: 2ALZ6-TVT280

FCC Rule(s):	<u>FCC Part 15.247</u>
Product Description:	<u>Visual IR Thermometer</u>
Tested Model:	<u>TVT280</u>
Report No.:	<u>STR17048310I-3</u>
Tested Date:	<u>2017-04-27 to 2017-05-25</u>
Issued Date:	<u>2017-05-26</u>
Tested By:	<u>Rode Liu / Engineer</u>
Reviewed By:	<u>Silin Chen / EMC Manager</u>
Approved & Authorized By:	<u>Jandy So / PSQ Manager</u>
Prepared By:	

Rode Liu

Silin Chen

Jandy So

Shenzhen SEM.Test Technology Co., Ltd.

1/F, Building A, Hongwei Industrial Park, Liuxian 2nd Road,
Bao'an District, Shenzhen, P.R.C. (518101)

Tel.: +86-755-33663308 Fax.: +86-755-33663309 Website: www.semtest.com.cn

Note: This test report is limited to the above client company and the product model only. It may not be duplicated without prior permitted by Shenzhen SEM.Test Technology Co., Ltd.

TABLE OF CONTENTS

1. GENERAL INFORMATION.....	3
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....	3
1.2 TEST STANDARDS.....	4
1.3 TEST METHODOLOGY.....	4
1.4 TEST FACILITY.....	4
1.5 EUT SETUP AND TEST MODE.....	5
1.6 MEASUREMENT UNCERTAINTY.....	5
1.7 TEST EQUIPMENT LIST AND DETAILS.....	6
2. SUMMARY OF TEST RESULTS.....	7
3. RF EXPOSURE.....	8
3.1 STANDARD APPLICABLE.....	8
3.2 TEST RESULT.....	8
4. ANTENNA REQUIREMENT.....	9
4.1 STANDARD APPLICABLE.....	9
4.2 EVALUATION INFORMATION.....	9
5. POWER SPECTRAL DENSITY.....	10
5.1 STANDARD APPLICABLE.....	10
5.2 TEST PROCEDURE.....	10
5.3 ENVIRONMENTAL CONDITIONS.....	10
5.4 SUMMARY OF TEST RESULTS/PLOTS.....	10
6. 6DB BANDWIDTH.....	13
6.1 STANDARD APPLICABLE.....	13
6.2 TEST PROCEDURE.....	13
6.3 ENVIRONMENTAL CONDITIONS.....	13
6.4 SUMMARY OF TEST RESULTS/PLOTS.....	13
7. RF OUTPUT POWER.....	16
7.1 STANDARD APPLICABLE.....	16
7.2 TEST PROCEDURE.....	16
7.3 ENVIRONMENTAL CONDITIONS.....	16
7.4 SUMMARY OF TEST RESULTS/PLOTS.....	16
8. FIELD STRENGTH OF SPURIOUS EMISSIONS.....	17
8.1 STANDARD APPLICABLE.....	17
8.2 TEST PROCEDURE.....	17
8.3 CORRECTED AMPLITUDE & MARGIN CALCULATION.....	18
8.4 ENVIRONMENTAL CONDITIONS.....	18
8.5 SUMMARY OF TEST RESULTS/PLOTS.....	19
9. OUT OF BAND EMISSIONS.....	26
9.1 STANDARD APPLICABLE.....	26
9.2 TEST PROCEDURE.....	26
9.3 ENVIRONMENTAL CONDITIONS.....	27
9.4 SUMMARY OF TEST RESULTS/PLOTS.....	27
10. CONDUCTED EMISSIONS.....	32
10.1 TEST PROCEDURE.....	32
10.2 BASIC TEST SETUP BLOCK DIAGRAM.....	32
10.3 ENVIRONMENTAL CONDITIONS.....	32
10.4 TEST RECEIVER SETUP.....	33
10.5 SUMMARY OF TEST RESULTS/PLOTS.....	33
10.6 CONDUCTED EMISSIONS TEST DATA.....	33

1. GENERAL INFORMATION

1.1 Product Description for Equipment Under Test (EUT)

Client Information

Applicant: Intrinity Global Limited.
Address of applicant: Unit 1707, Floor 17, Westley Square, 48 Hoi Yuen Road, Kwun Tong, Hong Kong

Manufacturer: Intrinity Global Limited.
Address of manufacturer: Unit 1707, Floor 17, Westley Square, 48 Hoi Yuen Road, Kwun Tong, Hong Kong

General Description of EUT	
Product Name:	Visual IR Thermometer
Trade Name:	/
Model No.:	TVT280
Adding Model(s):	TSD200
Rated Voltage:	DC 3.7V by battery
Battery Capacity:	/
<i>Note: The test data is gathered from a production sample, provided by the manufacturer. The appearance of others models listed in the report is different from main-test model TVT280, but the circuit and the electronic construction do not change, declared by the manufacturer.</i>	

Technical Characteristics of EUT	
Bluetooth Version:	V4.1(BLE mode)
Frequency Range:	2402-2480MHz
RF Output Power:	0.217dBm (Conducted)
Data Rate:	1Mbps
Modulation:	GFSK
Quantity of Channels:	40
Channel Separation:	2MHz
Type of Antenna:	Chip Antenna
Antenna Gain:	1.0dBi
Lowest Internal Frequency:	32.768kHz

1.2 Test Standards

The following report is prepared on behalf of the Intrinity Global Limited. in accordance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 of the Federal Communication Commissions rules.

The objective is to determine compliance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 of the Federal Communication Commissions rules.

Maintenance of compliance is the responsibility of the manufacturer. Any modification of the product, which result in lowering the emission, should be checked to ensure compliance has been maintained.

1.3 Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard for Testing Unlicensed Wireless Devices, and ANSI C63.4-2014, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz. The measurement guide KDB 558074 D01 v04 for digital transmission systems shall be performed also.

1.4 Test Facility

FCC – Registration No.: 934118

Shenzhen SEM.Test Technology Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files and the Registration is 934118.

Industry Canada (IC) Registration No.: 11464A

The 3m Semi-anechoic chamber of Shenzhen SEM.Test Technology Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 11464A.

CNAS Registration No.: L4062

Shenzhen SEM.Test Technology Co., Ltd. is a testing organization accredited by China National Accreditation Service for Conformity Assessment (CNAS) according to ISO/IEC 17025. The accreditation certificate number is L4062. All measurement facilities used to collect the measurement data are located at 1/F, Building A, Hongwei Industrial Park, Liuxian 2nd Road, Bao'an District, Shenzhen, P.R.C (518101).

1.5 EUT Setup and Test Mode

The EUT was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements. All testing shall be performed under maximum output power condition, and to measure its highest possible emissions level, more detailed description as follows:

Test Mode List		
Test Mode	Description	Remark
TM1	GFSK(BLE)	2402MHz, 2442MHz, 2480MHz

Accessories Equipment List and Details			
Description	Manufacturer	Model No.	Serial Number
Notebook	Lenovo	E10	/
Adapter	/	/	/
Accessories Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With Core/Without Core
/	/	/	/
EUT Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With Core/Without Core
USB cable	1.0	Shielded	With Core

1.6 Measurement Uncertainty

Measurement uncertainty		
Parameter	Conditions	Uncertainty
RF Output Power	Conducted	$\pm 0.42\text{dB}$
Occupied Bandwidth	Conducted	$\pm 1.5\%$
Power Spectral Density	Conducted	$\pm 1.8\text{dB}$
Conducted Spurious Emission	Conducted	$\pm 2.17\text{dB}$
Conducted Emissions	Conducted	$\pm 2.88\text{dB}$
Transmitter Spurious Emissions	Radiated	$\pm 5.1\text{dB}$

1.7 Test Equipment List and Details

No.	Description	Manufacturer	Model	Serial No.	Cal Date	Due Date
SEMT-1072	Spectrum Analyzer	Agilent	E4407B	MY41440400	2016-06-04	2017-06-03
SEMT-1031	Spectrum Analyzer	Rohde & Schwarz	FSP30	836079/035	2016-06-04	2017-06-03
SEMT-1007	EMI Test Receiver	Rohde & Schwarz	ESVB	825471/005	2016-06-04	2017-06-03
SEMT-1008	Amplifier	Agilent	8447F	3113A06717	2016-06-04	2017-06-03
SEMT-1043	Amplifier	C&D	PAP-1G18	2002	2016-06-04	2017-06-03
SEMT-1011	Broadband Antenna	Schwarz beck	VULB9163	9163-333	2016-06-04	2017-06-03
SEMT-1042	Horn Antenna	ETS	3117	00086197	2016-06-04	2017-06-03
SEMT-1121	Horn Antenna	Schwarzbeck	BBHA 9170	BBHA9170582	2016-06-04	2017-06-03
SEMT-1069	Loop Antenna	Schwarz beck	FMZB 1516	9773	2016-06-04	2017-06-03
SEMT-1001	EMI Test Receiver	Rohde & Schwarz	ESPI	101611	2016-06-04	2017-06-03
SEMT-1003	L.I.S.N	Schwarz beck	NSLK8126	8126-224	2016-06-04	2017-06-03
SEMT-1002	Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100911	2016-06-04	2017-06-03

2. SUMMARY OF TEST RESULTS

FCC Rules	Description of Test Item	Result
§ 2.1093	RF Exposure	Compliant
§ 15.203; § 15.247(b)(4)(i)	Antenna Requirement	Compliant
§15.205	Restricted Band of Operation	Compliant
§ 15.207(a)	Conducted Emission	Compliant
§ 15.247(e)	Power Spectral Density	Compliant
§ 15.247(a)(2)	6 dB Bandwidth	Compliant
§ 15.247(b)(3)	RF Output Power	Compliant
§ 15.209(a)	Radiated Emission	Compliant
§ 15.247(d)	Band Edge (Out of Band Emissions)	Compliant

N/A: not applicable

3. RF Exposure

3.1 Standard Applicable

According to § 1.1307 and § 2.1093, the portable transmitter must comply the RF exposure requirements.

3.2 Test Result

This product complied with the requirement of the RF exposure, please see the RF Exposure Report.

4. Antenna Requirement

4.1 Standard Applicable

According to FCC Part 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

4.2 Evaluation Information

This product has a chip antenna, fulfill the requirement of this section.

5. Power Spectral Density

5.1 Standard Applicable

According to 15.247(a)(1)(iii), For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

5.2 Test Procedure

According to the KDB 558074 D01 v04, the test method of power spectral density as below:

- Set analyzer center frequency to DTS channel center frequency.
- Set the span to 1.5 times the DTS bandwidth.
- Set the RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
- Set the VBW $\geq 3 \times \text{RBW}$.
- Detector = peak.
- Sweep time = auto couple.
- Trace mode = max hold.
- Allow trace to fully stabilize.
- Use the peak marker function to determine the maximum amplitude level within the RBW.
- If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

5.3 Environmental Conditions


Temperature:	26° C
Relative Humidity:	54%
ATM Pressure:	1011 mbar

5.4 Summary of Test Results/Plots


Test Mode	Test Channel MHz	Power Spectral Density dBm/3kHz	Limit dBm/3kHz
GFSK(BLE)	2402	-17.93	8
	2442	-20.7	8
	2480	-25.59	8

Please refer to the following test plots:


Low Channel



Middle Channel



High Channel



6. 6dB Bandwidth

6.1 Standard Applicable

According to 15.247(a)(2). Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

6.2 Test Procedure

- Set RBW = 100 kHz.
- Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
- Detector = Peak.
- Trace mode = max hold.
- Sweep = auto couple.
- Allow the trace to stabilize.
- Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

6.3 Environmental Conditions

Temperature:	25° C
Relative Humidity:	53%
ATM Pressure:	1018 mbar


6.4 Summary of Test Results/Plots

Test Mode	Test Channel MHz	6 dB Bandwidth kHz	99% Bandwidth kHz	Limit kHz
GFSK(BLE)	2402	735.774	1056.1	≥ 500
	2442	754.979	1053.5	≥ 500
	2480	714.869	1051.9	≥ 500


Please refer to the following test plots:

For BLE


Low Channel:



Middle Channel:



High Channel:



7. RF Output Power

7.1 Standard Applicable

According to 15.247(b)(3). For systems using digital modulation in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands: 1 Watt.

7.2 Test Procedure

According to section KDB-558074 D01 v04 section 9.1.1, this procedure shall be used when the measurement instrument has available a resolution bandwidth that is greater than the DTS bandwidth.

- Set the RBW $\geq$ DTS bandwidth.
- Set VBW $\geq 3 \times$ RBW.
- Set span $\geq 3 \times$ RBW
- Sweep time = auto couple.
- Detector = peak.
- Trace mode = max hold.
- Allow trace to fully stabilize.
- Use peak marker function to determine the peak amplitude level.

7.3 Environmental Conditions

Temperature:	26° C
Relative Humidity:	57%
ATM Pressure:	1011 mbar

7.4 Summary of Test Results/Plots

Test Mode	Frequency MHz	Reading dBm	Output Power mW	Limit mW
GFSK(BLE)	2402	0.217	1.05	1000
	2442	-0.424	0.91	1000
	2480	0.022	1.01	1000

Note: the antenna gain of 1.0dBi less than 6dBi maximum permission antenna gain value based on 1 watt peak output power limit.

8. Field Strength of Spurious Emissions

8.1 Standard Applicable


According to §15.247(d), in any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).


The emission limit in this paragraph is based on measurement instrumentation employing an average detector. The provisions in §15.35 for limiting peak emissions apply. Spurious Radiated Emissions measurements starting below or at the lowest crystal frequency.

8.2 Test Procedure

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.205 15.247(a) and FCC Part 15.209 Limit.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle. The spacing between the peripherals was 10 cm.





Frequency :9kHz-30MHz

RBW=10KHz,

VBW =30KHz

Sweep time= Auto

Trace = max hold

Detector function = peak

Frequency :30MHz-1GHz

RBW=120KHz,

VBW=300KHz

Sweep time= Auto

Trace = max hold

Detector function = peak, QP

Frequency :Above 1GHz

RBW=1MHz,

VBW=3MHz(Peak), 10Hz(AV)

Sweep time= Auto

Trace = max hold

Detector function = peak, AV

8.3 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and the Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

$$\text{Corr. Ampl.} = \text{Indicated Reading} + \text{Ant. Factor} + \text{Cable Loss} - \text{Ampl. Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -6dBμV means the emission is 6dBμV below the maximum limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Corr. Ampl.} - \text{FCC Part 15 Limit}$$

8.4 Environmental Conditions

Temperature:	25 °C
Relative Humidity:	52%
ATM Pressure:	1012 mbar

8.5 Summary of Test Results/Plots


According to the data below, the FCC Part 15.205, 15.209 and 15.247 standards, and had the worst cases:

Note: this EUT was tested in 3 orthogonal positions and the worst case position data was reported.

Plot of Radiated Emissions Test Data


EUT: Visual IR Thermometer
Tested Model: TVT280
Operating Condition: Transmitting-Low channel (2402MHz)
Comment: DC 3.7V

Test Specification: Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	91.1746	31.06	-13.36	17.70	43.50	-25.80	230	100	peak
2	229.2931	54.48	-11.77	42.71	46.00	-3.29	97	100	peak
3	255.6231	53.49	-10.26	43.23	46.00	-2.77	298	100	peak
4	366.8231	30.74	-7.59	23.15	46.00	-22.85	102	100	peak
5	480.5276	28.47	-5.36	23.11	46.00	-22.89	348	100	peak
6	790.6188	28.30	0.21	28.51	46.00	-17.49	317	100	peak

Test Specification: Vertical



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	35.0048	46.20	-11.55	34.65	40.00	-5.35	333	100	peak
2	233.3487	51.46	-11.47	39.99	46.00	-6.01	92	100	peak
3	258.3264	45.59	-10.14	35.45	46.00	-10.55	335	100	peak
4	365.5391	45.63	-7.65	37.98	46.00	-8.02	119	100	peak
5	399.0302	45.42	-7.58	37.84	46.00	-8.16	347	100	peak
6	560.6928	48.44	-5.74	42.70	46.00	-3.30	241	100	peak

Plot of Radiated Emissions Test Data


EUT: Visual IR Thermometer

Tested Model: TVT280

Operating Condition: Transmitting-Middle channel (2442MHz)


Comment: DC 3.7V

Test Specification: Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	229.2931	54.12	-11.77	42.35	46.00	-3.65	66	100	peak
2	255.6231	49.75	-10.26	39.49	46.00	-6.51	263	100	peak
3	369.4047	29.50	-7.48	22.02	46.00	-23.98	72	100	peak
4	480.5276	27.86	-5.36	22.50	46.00	-23.50	165	100	peak
5	631.6884	28.24	-3.03	25.21	46.00	-20.79	81	100	peak
6	796.1830	28.01	0.03	28.04	46.00	-17.96	98	100	peak

Test Specification: Vertical



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	35.2512	45.14	-11.49	33.65	40.00	-6.35	71	100	peak
2	39.0245	42.94	-10.63	32.31	40.00	-7.69	243	100	peak
3	45.5348	38.63	-10.44	28.19	40.00	-11.81	90	100	peak
4	135.5062	44.87	-14.55	30.32	43.50	-13.18	277	100	peak
5	229.2931	46.05	-11.77	34.28	46.00	-11.72	50	100	peak
6	252.0627	42.83	-10.42	32.41	46.00	-13.59	102	100	peak

Plot of Radiated Emissions Test Data


EUT: Visual IR Thermometer

Tested Model: TVT280

Operating Condition: Transmitting-High channel (2480MHz)


Comment: DC 3.7V

Test Specification: Horizontal



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	229.2931	54.82	-11.77	43.05	46.00	-2.95	111	100	peak
2	255.6231	52.85	-10.26	42.59	46.00	-3.41	186	100	peak
3	366.8231	30.05	-7.59	22.46	46.00	-23.54	112	100	peak
4	494.1984	28.81	-5.95	22.86	46.00	-23.14	123	100	peak
5	618.5369	28.45	-2.90	25.55	46.00	-20.45	95	100	peak
6	779.6068	27.83	0.54	28.37	46.00	-17.63	314	100	peak

Test Specification: Vertical



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	34.7602	45.19	-11.60	33.59	40.00	-6.41	97	100	peak
2	39.1616	43.41	-10.59	32.82	40.00	-7.18	107	100	peak
3	120.2766	43.03	-13.72	29.31	43.50	-14.19	126	100	peak
4	159.7844	41.59	-15.03	26.56	43.50	-16.94	136	100	peak
5	217.5443	46.56	-12.37	34.19	46.00	-11.81	148	100	peak
6	252.0627	43.24	-10.42	32.82	46.00	-13.18	232	100	peak

Spurious Emissions Above 1GHz

Transmitting: BLE mode:

Frequency	Reading	Correct	Result	Limit	Margin	Polar	Detector
(MHz)	(dBuV/m)	dB	(dBuV/m)	(dBuV/m)	(dB)	H/V	
Low Channel-2402MHz							
4804	55.82	-3.59	52.23	74	-21.77	H	PK
4804	40.00	-3.59	36.41	54	-17.59	H	AV
7206	56.91	-0.52	56.39	74	-17.61	H	PK
7206	37.92	-0.52	37.40	54	-16.60	H	AV
4804	57.95	-3.59	54.36	74	-19.64	V	PK
4804	38.93	-3.59	35.34	54	-18.66	V	AV
7206	56.30	-0.52	55.78	74	-18.22	V	PK
7206	39.99	-0.52	39.47	54	-14.53	V	AV
Middle Channel-2442MHz							
4884	57.95	-3.49	54.46	74	-19.54	H	PK
4884	38.54	-3.49	35.05	54	-18.95	H	AV
7326	55.74	-0.47	55.27	74	-18.73	H	PK
7326	39.75	-0.47	39.28	54	-14.72	H	AV
4884	56.30	-3.49	52.81	74	-21.19	V	PK
4884	38.04	-3.49	34.55	54	-19.45	V	AV
7326	55.20	-0.47	54.73	74	-19.27	V	PK
7326	38.76	-0.47	38.29	54	-15.71	V	AV
High Channel-2480MHz							
4960	56.03	-3.41	52.62	74	-21.38	H	PK
4960	38.71	-3.41	35.30	54	-18.70	H	AV
7440	55.27	-0.42	54.85	74	-19.15	H	PK
7440	39.59	-0.42	39.17	54	-14.83	H	AV
4960	56.30	-3.41	52.89	74	-21.11	V	PK
4960	37.33	-3.41	33.92	54	-20.08	V	AV
7440	54.06	-0.42	53.64	74	-20.36	V	PK
7440	37.47	-0.42	37.05	54	-16.95	V	AV

Note: Testing is carried out with frequency rang 9kHz to the tenth harmonics, other than listed in the table above are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

9. Out of Band Emissions

9.1 Standard Applicable

According to §15.247 (d) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).

9.2 Test Procedure

According to the KDB 558074 D01 v04, the band-edge radiated test method as follows:

Set span = wide enough to capture the peak level of the emission operating on the channel closest to the bandedge, as well as any modulation products which fall outside of the authorized band of operation (2310MHz to 2420MHz for low bandedge, 2460MHz to 2500MHz for the high bandedge)

RBW = 1MHz, VBW = 1MHz for peak value measured

RBW = 1MHz, VBW = 10Hz for average value measured

Sweep = auto; Detector function = peak/average; Trace = max hold

All the trace to stabilize, set the marker on the emission at the bandedge, or on the highest modulation product outside of the band, if this level is greater than that at the bandedge. Enable the marker-delta function, then use the marker-to-peak function to move the marker to the peak of the in-band emission. Those emission must comply with the 15.209 limit for fall in the restricted bands listed in section 15.205. Note that the method of measurement KDB publication number: 913591 may be used for the radiated bandedge measurements.

According to the KDB 558074 D01 v04, the conducted spurious emissions test method as follows:

1. Set start frequency to DTS channel edge frequency.
2. Set stop frequency so as to encompass the spectrum to be examined.
3. Set RBW = 100 kHz.
4. Set VBW $\geq$ 300 kHz.
5. Detector = peak.
6. Trace Mode = max hold.
7. Sweep = auto couple.
8. Allow the trace to stabilize (this may take some time, depending on the extent of the span).
9. Use peak marker function to determine maximum amplitude of all unwanted emissions within any 100 kHz bandwidth.

Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) are attenuated by at least the minimum requirements specified in section 8.1. Report the three highest emissions relative to the limit.

9.3 Environmental Conditions


Temperature:	23°C
Relative Humidity:	54%
ATM Pressure:	1011 mbar

9.4 Summary of Test Results/Plots

Restricted Bandedge (Radiated)


Lowest Bandedge-BLE

Horizontal (Worst case)



No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2310.00	36.09	-3.26	32.83	54.00	-21.17	Average Detector
	2310.00	48.40	-3.26	45.14	74.00	-28.86	Peak Detector
2	2390.00	36.28	-3.05	33.23	54.00	-20.77	Average Detector
	2390.00	48.95	-3.05	45.90	74.00	-28.10	Peak Detector



Highest Bandedge-BLE
Horizontal (Worst case)





No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2479.95	93.54	-2.81	90.73	/	/	Average Detector
	2479.85	98.84	-2.81	96.03	/	/	Peak Detector
2	2483.50	55.31	-2.80	52.51	54.00	-1.49	Average Detector
	2483.50	61.08	-2.80	58.28	74.00	-15.72	Peak Detector
3	2500.00	35.82	-2.75	33.07	54.00	-20.93	Average Detector
	2500.00	48.74	-2.75	45.99	74.00	-28.01	Peak Detector

Out of Bandedge and Spurious Emission (Conducted)



Lowest



Middle Channel:



High Channel:




10. Conducted Emissions

10.1 Test Procedure

The setup of EUT is according with per ANSI C63.4-2014 measurement procedure. The specification used was with the FCC Part 15.207 Limit.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle. The spacing between the peripherals was 10 cm.

10.2 Basic Test Setup Block Diagram



10.3 Environmental Conditions

Temperature:	25 °C
Relative Humidity:	52%
ATM Pressure:	1012 mbar

10.4 Test Receiver Setup

During the conducted emission test, the test receiver was set with the following configurations:

Start Frequency	150 kHz
Stop Frequency.....	30 MHz
Sweep Speed	Auto
IF Bandwidth.....	10 kHz
Quasi-Peak Adapter Bandwidth	9 kHz
Quasi-Peak Adapter Mode	Normal

10.5 Summary of Test Results/Plots

According to the data in section 10.6, the EUT complied with the FCC Part 15.207 Conducted margin for this device, with the *worst* margin reading of:


-2.31 dB at **0.7540 MHz** in the **Line, QP** detector, 0.15-30MHz

10.6 Conducted Emissions Test Data

Plot of Conducted Emissions Test Data


EUT: Visual IR Thermometer
Tested Model: TVT280
Operating Condition: Transmitting
Comment: AC 120V/60Hz, Adapter DC 5V

Test Specification: Neutral



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.4940	24.07	9.80	33.87	46.10	-12.23	AVG
2*	0.6060	39.81	9.79	49.60	56.00	-6.40	QP
3	0.7380	22.71	9.78	32.49	46.00	-13.51	AVG
4	0.8100	39.74	9.78	49.52	56.00	-6.48	QP
5	2.3340	16.10	9.73	25.83	46.00	-20.17	AVG
6	2.3980	33.56	9.73	43.29	56.00	-12.71	QP

Test Specification: Line



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.6020	43.65	9.79	53.44	56.00	-2.56	QP
2	0.6020	25.65	9.79	35.44	46.00	-10.56	AVG
3	0.7500	26.02	9.78	35.80	46.00	-10.20	AVG
4*	0.7540	43.91	9.78	53.69	56.00	-2.31	QP
5	2.3580	37.31	9.73	47.04	56.00	-8.96	QP
6	2.3580	18.27	9.73	28.00	46.00	-18.00	AVG

***** END OF REPORT *****