



FCC PART 15.249 TEST REPORT

On Behalf of

CCL ELECTRONICS LTD

Unit 1-3, 9/F., Wang Lung Industrial Building, 11 Lung Tak Street,
Tsuen Wan, KongHong

FCC ID: 2ALZ7-3131B0701
Model: C3131B, C3137B

August 14, 2026

This Report Concerns: ☒ Original Report	Equipment Type: All-In-One Wireless Transmitter
Test Engineer:	Fan Yang / <i>Fan Yang</i>
Report Number:	QCT26HR-1873E-01
Test Date:	August 13, 2026
Test Result:	Pass
Reviewed By:	Vincent Yang / <i>Vincent Yang</i>
Approved By:	Kendy Wang / <i>Kendy Wang</i>
Prepared By:	Shenzhen QC Testing Laboratory Co., Ltd. East of 1/F., Building E, Xinghong Science Park, No.111, Shuiku Road, Fenghuanggang, Xixiang Street, Bao'an District, Shenzhen, Guangdong, China Tel: 0755-23008269 Fax: 0755-23726780





Table of Contents

1. GENERAL INFORMATION	4
1.1 Product Description for Equipment under Test (EUT)	4
1.2 System Test Configuration	4
1.3 Test Facility	5
1.4 Measurement Uncertainty	5
2. SUMMARY OF TEST RESULTS	6
3. LIST OF TEST AND MEASUREMENT INSTRUMENTS	7
3.1 Radiated Emission Test	7
3.2 RF Conducted test	7
4. ANTENNA REQUIREMENT	8
5. RADIATED EMISSION METHOD	9
5.1. Applicable Standard	9
5.2. Limit	9
5.3. Receiver setup	9
5.4. Test setup	9
5.5. Test Procedure	10
5.6. Test Data	11
6. 20DB OCCUPY BANDWIDTH	20
6.1. Applicable Standard	20
6.2. Limit	20
6.3. Test setup	20
6.4. Test Data	20



Report Number

Description

Issued Date

QCT26HR-1873E-01

Initial Issue

2026-08-14



1. GENERAL INFORMATION

1.1 Product Description for Equipment under Test (EUT)

EUT Description	All-In-One Wireless Transmitter
Model No.	C3131B, C3137B
Model Difference:	All the models are electrical identical including the same software parameter and hardware design (i.e., circuit design, PCB Layout, RF module/circuit, antenna type and antenna location, components on PCB, etc.), same mechanical structure and design (including product enclosure, materials, etc.), the only differences are as follows: C3131B has UV and photometric functions, while C3137B does not. We tested all items at the C3131B, and only test the spurious emission (30MHz - 1GHz) at the C3137B
Tested Model	C3131B, C3137B
Sample(s) Status	Engineer sample
Operation Frequency:	915MHz
Channel numbers:	1
Modulation type:	FSK
Antenna Type:	Spring Antenna
Antenna gain*1:	0dBi
Power supply:	4.5V DC (Powered by 3*1.5V AA battery)
Trade Mark:	N/A
Applicant	CCL ELECTRONICS LTD
Address	Unit 1-3, 9/F., Wang Lung Industrial Building, 11 Lung Tak Street, Tsuen Wan, KongHong
Manufacturer	CCL ELECTRONICS LTD
Address	Unit 1-3, 9/F, Wang Lung Industrial Building, 11 Lung Tak Street, Tsuen Wan, Hong Kong
Sample No.	C3131B: Y26H1873E01YN C3137B: Y26H1873E02YN

Note: *1This information provided by Manufacturer, SZ QC Lab is not responsible for the accuracy of this information.

1.2 System Test Configuration

1.2.1 Support Equipment

N/A

1.2.2 Test mode and voltage

Transmitting mode: The manufacturer provides the engineering sample to set the continuously transmitting mode, and the power level is the default.

Test voltage: DC 4.5V

RF power setting	Default power
Test software	Press and hold the "test" key while powering on the device to set the continuously transmitting mode



1.3 Test Facility

Test Firm : Shenzhen QC Testing Laboratory Co., Ltd.

The testing quality ability of our laboratory meet with "Quality Law of People's Republic of China" Clause 19. The testing quality system of our laboratory meets with ISO/IEC-17025 requirements. This approval result is accepted by MRA of APLAC.

Our test facility is recognized, certified, or accredited by the following organizations:

CNAS – Registration No.: L8464

The EMC Laboratory has been accredited by CNAS, and in compliance with ISO/IEC 17025:2017 General Requirements for testing Laboratories.

A2LA Certificate Number: 6759.01

The EMC Laboratory has been accredited by A2LA, and in compliance with ISO/IEC 17025:2017 General Requirements for testing Laboratories.

FCC Registration Number: 561109

The EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications commission.

IC Registration Number: 29628

CAB identifier: CN0141

The EMC Laboratory has been registered and fully described in a report filed with the (IC) Industry Canada.

1.4 Measurement Uncertainty

Parameter	Uncertainty
Occupied Channel Bandwidth	3.43%
RF output power, conducted	0.63dB
Power Spectral Density, conducted	0.69dB
Unwanted Emissions, conducted	0.90dB
AC Power Line Conducted Emission	2.70dB
Radiated Spurious Emission test (9kHz-30MHz)	2.68dB
Radiated Spurious Emission test (30MHz-1000MHz)	3.94dB
Radiated Spurious Emission test (1000MHz-18000MHz)	4.70dB
Radiated Spurious Emission test (18GHz-40GHz)	4.80dB
Temperature	0.375°C
Humidity	1.2679%
DC and low frequency voltages	0.18%
Time	0.133%
Duty cycle	0.133%

Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2



2. Summary of Test Results

Test Item	Section	Result
Antenna Requirement	15.203	Pass
Conduction Emission	15.207	Not Applicable
Radiated Emissions	15.205, 15.209, 15.249	Pass
20dB Bandwidth	15.215 (c)	Pass

Note: 1. In the configuration tested, the EUT complied with the standards specified above.

2. Test according to ANSI C63.10-2020 + Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024.

3. All indications of Pass/Fail in this report are opinions expressed by Shenzhen QC Testing Laboratory Co., Ltd. based on interpretations and/or observations of test results. Measurement Uncertainties were not taken into account and are published for informational purposes only.

4. The EUT is powered by the battery, and Conduction Emission is not applicable.



3. List of Test and Measurement Instruments

3.1 Radiated Emission Test

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal.Due
1	EMI Test Receiver	R&S	ESIB 7	2277573376	2026.03.12	2027.03.11
2	EMI Test Receiver	ESPI3	ESPI3	101131	2026.03.12	2027.03.11
3	Spectrum Analyzer	Rohde&Schwarz	FSV 40	101458	2026.03.13	2027.03.12
4	TRILOG Broadband Test-Antenna	SCHWARZBECK	VULB9168	VULB9168-588	2026.03.14	2028.03.13
5	Loop Antenna	EMCO	6502	2133	2026.03.14	2028.03.13
6	horn antenna	SCHWARZBECK	BBHA9120D	2069	2026.03.14	2028.03.13
7	Horn Antenna	COM-MW	ZLB7-18-40G-950	12221225	2025.08.19	2027.08.18
8	Pre-amplifier	MITEQ	TTA0001-18	2063645	2026.03.12	2027.03.11
9	Pre-amplifier	MITEQ	TTA1800-30-HG	2063644	2026.03.12	2027.03.11
10	Pre-amplifier	COM-MW	DLAN-18000-40000-02	10229104	2026.03.12	2027.03.11
11	966 Camber	ZhongYU	9*6*6	/	2025.08.12	2028.08.11
12	Test Software	Farad	EZ-EMC Ver QCT03A2 RE+	N/A	N/A	N/A

3.2 RF Conducted test

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal.Due
1.	Spectrum Analyzer	ROHDE&SCHWARZ	FSV 40	101458	2026.03.13	2027.03.12



4. Antenna requirement

Standard requirement: FCC Part15 C Section 15.203

15.203 requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

EUT Antenna: The antenna is Spring Antenna, reference to the Internal Photos for details.

5. Radiated Emission Method

5.1. Applicable Standard

FCC Part15 C Section 15.249

5.2. Limit

Fundamental frequency	Field strength of fundamental (millivolts/meter)	Field strength of harmonics (microvolts/meter)
902-928 MHz	50	500
2400-2483.5 MHz	50	500
5725-5875 MHz	50	500
24.0-24.25 GHz	250	2500

As per FCC Section 15.249

(c) Field strength limits are specified at a distance of 3 meters.


(d) Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in §15.209, whichever is the lesser attenuation.

5.3. Receiver setup


Frequency	Detector	RBW	VBW	Value
9KHz-150KHz	Quasi-peak	200Hz	600Hz	Quasi-peak
150KHz-30MHz	Quasi-peak	9KHz	30KHz	Quasi-peak
30MHz-1GHz	Quasi-peak	100KHz	300KHz	Quasi-peak
Above 1GHz	Peak	1MHz	3MHz	Peak
	Peak	1MHz	10Hz	Average

5.4. Test setup


For radiated emissions from 9kHz to 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



5.5. Test Procedure

1. The EUT was placed on the top of a rotating table (0.8 meters for below 1GHz and 1.5 meters for above 1GHz) above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation.
2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading.
5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.



5.6. Test Data

Temperature	25-26°C	Humidity	49-54%
ATM Pressure	101kPa	Antenna Gain	0dBi
Test by	Fan Yang	Test result	PASS

Remarks:


1. Pre-scan all kind of the place mode (X-axis, Y-axis, Z-axis), and found the Y-axis which it is worse case.
2. Data of measurement within frequency range 9kHz-30MHz are the noise floor or attenuated more than 20dB below the permissible limits or the field strength is too small to be measured, so test data does not present in this report.



C3137B

Below 1GHz:


Horizontal



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	36.0007	7.18	15.26	22.44	40.00	17.56	QP
2	54.8348	6.17	14.13	20.30	40.00	19.70	QP
3	122.4038	6.25	13.36	19.61	43.50	23.89	QP
4	333.6865	8.08	15.49	23.57	46.00	22.43	QP
5	734.4913	5.41	23.57	28.98	46.00	17.02	QP
6 *	915.0000	48.85	26.36	75.21	/	/	peak



Vertical



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	34.6385	6.18	15.42	21.60	40.00	18.40	QP
2	59.6492	5.30	13.72	19.02	40.00	20.98	QP
3	124.5686	7.52	13.50	21.02	43.50	22.48	QP
4	393.4723	5.16	17.47	22.63	46.00	23.37	QP
5	675.2078	5.30	22.51	27.81	46.00	18.19	QP
6 *	915.0000	43.54	26.36	69.90	/	/	peak


Frequency (MHz)	Read Level (dBuV)	polarization	Factor (dB/m)	Peak value (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)
915	48.85	H	26.36	75.21	93.98	18.77
915	43.54	V	26.36	69.9	93.98	24.08



C3131B

Below 1GHz:


Horizontal



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	40.7016	5.05	14.62	19.67	40.00	20.33	QP
2	57.1914	4.08	13.92	18.00	40.00	22.00	QP
3	125.0066	6.19	13.53	19.72	43.50	23.78	QP
4	307.8313	9.37	14.63	24.00	46.00	22.00	QP
5	578.6699	3.83	21.02	24.85	46.00	21.15	QP
6	750.1083	4.44	23.87	28.31	46.00	17.69	QP
7 *	915.0000	51.43	26.36	77.79	/	/	peak



Vertical




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	34.6385	4.18	15.42	19.60	40.00	20.40	QP
2	39.5757	4.02	14.70	18.72	40.00	21.28	QP
3	59.6493	4.30	13.72	18.02	40.00	21.98	QP
4	125.0065	8.87	13.53	22.40	43.50	21.10	QP
5	375.9385	7.98	16.89	24.87	46.00	21.13	QP
6	616.3716	4.80	21.64	26.44	46.00	19.56	QP
7 *	915.0000	44.67	26.36	71.03	/	/	peak

Frequency (MHz)	Read Level (dBμV)	polarization	Factor (dB/m)	Peak value (dBμV/m)	Average Limit (dBμV/m)	Margin (dB)
915	51.43	H	26.36	77.79	93.98	16.19
915	44.67	V	26.36	71.03	93.98	22.95



Above 1G:
Horizontal




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	1402.814	59.89	-24.77	35.12	74.00	38.88	peak
2	1986.095	59.05	-22.72	36.33	74.00	37.67	peak
3	2741.574	67.47	-21.12	46.35	74.00	27.65	peak
4	3962.780	61.19	-20.30	40.89	74.00	33.11	peak
5	4549.881	61.26	-19.11	42.15	74.00	31.85	peak
6 *	6918.310	60.50	-12.70	47.80	74.00	26.20	peak



Vertical

100.0 dBuV/m




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	1380.384	58.51	-24.79	33.72	74.00	40.28	peak
2	1945.360	60.44	-23.03	37.41	74.00	36.59	peak
3	2741.574	62.92	-21.12	41.80	74.00	32.20	peak
4	3664.376	62.92	-20.38	42.54	74.00	31.46	peak
5	5767.665	61.56	-16.50	45.06	74.00	28.94	peak
6 *	6950.243	58.77	-12.61	46.16	74.00	27.84	peak




Band Edge:

Horizontal



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	902.0000	3.71	26.24	29.95	46.00	16.05	QP
2 *	915.0000	56.30	26.36	82.66	/	/	peak
3	928.0000	4.07	26.47	30.54	46.00	15.46	QP



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	902.0000	3.37	26.24	29.61	46.00	16.39	QP
2 *	915.0000	52.48	26.36	78.84	/	/	peak
3	928.0000	3.69	26.47	30.16	46.00	15.84	QP

Frequency (MHz)	Read Level (dBuV)	polarization	Factor (dB/m)	Peak value (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)
915	56.3	H	26.36	82.66	93.98	11.32
915	52.48	V	26.36	78.84	93.98	15.14

Remarks:

1. Level = Receiver Read level + Factor
2. The emission levels of other frequencies are very lower than the limit and not show in test report.
3. If the peak (or quasi-peak) measured value complies with the average limit, it is unnecessary to perform an average measurement, so AV emission value did not show in above table if the peak value complies with average limit.

6. 20dB Occupy Bandwidth


6.1. Applicable Standard

FCC Part15 C Section 15.215

6.2. Limit

N/A

6.3. Test setup



6.4. Test Data


Temperature	22.8°C	Humidity	47%
ATM Pressure	101kPa	Antenna Gain	0dBi
Test by	Fan Yang	Test result	PASS

Please refer to following table and plots.



Test Frequency (MHz)	-20dB bandwidth (MHz)
915	0.153

Test plot as follows:



Date: 13.AUG.2026 14:00:29

-----THE END OF TEST REPORT-----