



SECO S.p.A.
Via A. Grandi 20 52100 Arezzo – Italy
Ph: +39 0575 26979
Fax: +39 0575 350210
P.IVA – VAT IT 00325250512

Cap. Soc. € 1.048.343,74
Reg. Imprese n. 4196 Arezzo
REA n. 70645
Meccanografico AR007079
Iscri. Reg. Pile e Accumulatori n. IT20080P00006356

Pag.1 of 4



RF Exposure and Transmitter Power Considerations for the SECO PC-Gateway SYS-C31-DMV

Contains FCC ID: 2ALZB-AW276 and FCC ID: XMR201903EG25G

For mobile product operation the FCC requires that the calculated MPE be equal to or less than a given limit dependent on frequency at a distance of 20 cm from a device to the body of a user.

The transmitter operation for the PC-Gateway SYS-C31-DMV utilises a certified BT / BT LE / 2.4 GHz WLAN / 5GHz WLAN module (FCC ID: 2ALZB-AW276), together with a certified cellular module EG25-G (FCC ID: XMR201903EG25G).

These modules have been certified for the following operating bands:

BT BR ER / BT LE: 2402 to 2480 MHz

2.4 GHz WLAN: 2412 to 2462 MHz

5 GHz WLAN: 5180 to 5240 MHz, 5260 to 5320 MHz, 5500 to 5700 MHz, 5745 to 5825 MHz

GSM850 / WCDMA850 B5 / LTE B5: 824 to 849 MHz

GSM1900 / WCDMA B2 / LTE B2: 1850 to 1910 MHz

WCDMA B4 / LTE B4: 1710 to 1755 MHz

LTE B7: 2500 to 2570 MHz

LTE B12: 699 to 716 MHz

LTE B13: 777 to 787 MHz

LTE B25: 1850 to 1915 MHz

LTE B26: 814 to 849 MHz

LTE B38: 2570 to 2620 MHz

LTE B41: 2496 to 2690 MHz

The following FCC Rule Parts and procedures are applicable:

Part 1.1310 – Radiofrequency radiation exposure limits

KDB447498 D01 v06

Mobile and Portable Devices RF Exposure Procedures and Equipment Authorisation Policies

WWW.SECO.COM



Design



Manufacturing



Systems



IoT



SECO S.p.A.
Via A. Grandi 20 52100 Arezzo – Italy
Ph: +39 0575 26979
Fax: +39 0575 350210
P.IVA – VAT IT 00325250512

Cap. Soc. € 1.048.343,74
Reg. Imprese n. 4196 Arezzo
REA n. 70645
Meccanografico AR007079
Iscr. Reg. Pile e Accumulatori n. IT20080P00006356

Pag.2 of 4



MPE CALCULATIONS

The MPE calculation used to calculate the safe operating distance for the user is:

$$S = \text{EIRP} / 4 \pi R^2$$

Where

- S = Power density
- EIRP = Effective Isotropic Radiated Power (EIRP = P x G)
- P = Conducted Transmitter Power
- G = Antenna Gain (relative to an isotropic radiator)
- R = distance to the centre of radiation of the antenna (safe operating distance)

Power Density Requirement

From table 1 (b) - Limits for General Population/ Uncontrolled Exposure of FCC §1.1310 (e) for $f > 1500\text{MHz}$, $S_{\text{req}} = 1.0 \text{ mW/cm}^2$

From table 1 (b) - Limits for General Population/ Uncontrolled Exposure of FCC §1.1310 (e) for $f < 1500\text{MHz}$, $S_{\text{req}} = f/1500 \text{ mW/cm}^2$

(f = operating frequency)

WWW.SECO.COM



Design



Manufacturing



Systems



IoT

VALUES

Powers are from the BT BR / EDR, BT LE, 2.4 GHz WLAN and 5 GHz WLAN FCC Grant listings and the cellular module FCC Grant RF Exposure Evaluation report.

Refer to antenna datasheet *Multi Band antenna _ DYNAFLEX - 814_1000RG316_SMMRP* for antenna gain values.

Frequency Range (MHz)	Operating Band	Max. Conducted Average Output Power (dBm)	Antenna Gain (dBi)	EIRP (mW)	Calculated Distance R @ S _{req} (cm)	Power Density S mw/ cm ²		
						Limit S _{req}	Calculated S _n @ 20cm	S _n /S _{req}
2402 - 2480	BT BR/EDR	7.0	2.7	9.3	0.86	1.0	0.0019	0.0019
2402 - 2480	BT LE	4.8	2.7	5.6	0.67	1.0	0.0011	0.0011
2412 - 2462	2.4 GHz WLAN	29.7	¹ 2.1 / ² 2.7	³ 251.4	16.09	1.0	0.6468	0.6468
³ 5180 - 5825	5 GHz WLAN	22.9	⁴ 1.6 / ⁵ 0.7	⁶ 510.9	6.38	1.0	0.1016	0.1016
824 - 849	GSM850	25.8	2.8	724.4	10.24	0.55	0.1441	0.2620
824 - 849	WCDMA B5 LTE B5	25.0	2.8	602.6	9.34	0.55	0.1199	0.2180
1850 - 1910	GSM1900	22.8	2.9	371.5	5.44	1.0	0.0739	0.0739
1850 - 1910	WCDMA B2 LTE B2	25.0	2.9	616.6	7.00	1.0	0.1227	0.1227
1710 - 1755	WCDMA B4 LTE B4	25.0	0.3	338.8	5.19	1.0	0.0674	0.0674
2500 - 2570	LTE B7	25.0	0.3	338.8	5.19	1.0	0.0674	0.0674
699 - 716	LTE B12	25.0	1.3	426.6	8.50	0.47	0.0849	0.1806
777 - 787	LTE B13	25.0	1.3	426.6	8.08	0.52	0.0849	0.1633
1850 - 1915	LTE B25	25.0	2.9	616.6	7.00	1.0	0.1227	0.1227
814 - 849	LTE B26	25.0	2.8	602.6	9.60	0.54	0.1199	0.2220
2570 - 2620	LTE B38	25.0	0.3	338.8	5.19	1.0	0.0674	0.0674
2496 - 2690	LTE B41	25.0	0.3	338.8	5.19	1.0	0.0674	0.0674

¹802.11 Blue channel 2.4 GHz band antenna gain

²802.11 Red channel 2.4 GHz band antenna gain

³Value stated is for the sub-band with the highest recorded output power of all four 5 GHz WLAN sub-bands

⁴802.11 Blue channel 5 GHz band antenna gain

⁵802.11 Red channel 5 GHz band antenna gain

⁶Combined EIRP derived from summation of blue and red channel EIRPs



KDB447498 D01 v06 Section 7.2 SIMULTANEOUS TRANSMISSION CONSIDERATIONS

Worst case summation of calculated MPE ratios S_n/S_{req} .

BT BR/EDR and 2.4 GHz WLAN operation:

$$\text{ie: } \Sigma \text{MPE}_{\text{ratios}} = (S_1 / S_{\text{req1}}) + (S_2 / S_{\text{req2}})$$

$$= 0.0019 + 0.6468$$

$$= \mathbf{0.6487}$$

Bluetooth and Cellular (GSM850) operation:

$$\text{ie: } \Sigma \text{MPE}_{\text{ratios}} = (S_1 / S_{\text{req1}}) + (S_3 / S_{\text{req3}})$$

$$= 0.0019 + 0.2620$$

$$= \mathbf{0.2639}$$

Σ of MPE ratios < 1.0, so in accordance with KDB447498 Section 7.2, simultaneous transmission test exclusion applies.

Conclusion

The required 20 cm RF exposure limits for General Population / Uncontrolled Exposure will not be exceeded for the SECO PC-Gateway SYS-C31-DMV using the listed antenna.

Yours faithfully,

Alessandro Pali / Senior Manager

