

RF EXPOSURE REPORT

Applicant	Shenzhen Hopewin Electronic Material Co.,Ltd
Address	Room O-P, Floor 4, Block 9C, Baoneng Science Park, Qingxiang Road, QingHu Industrial Estate, Longhua Street, Longhua District, Shenzhen

Manufacturer or Supplier	Shenzhen Hopewin Electronic Material Co.,Ltd
Address	Room O-P, Floor 4, Block 9C, Baoneng Science Park, Qingxiang Road, QingHu Industrial Estate, Longhua Street, Longhua District, Shenzhen
Product	Gateway
Brand Name	Cloudleaf
Model	GW-1.5-I
Additional Model & Model Difference	N/A
Date of tests	Nov. 12, 2019 ~ Dec. 09, 2019

☒ **FCC Part 2 (Section 2.1091)**

☒ **KDB 447498 D01**

☒ **IEEE C95.1**

CONCLUSION: The submitted sample was found to COMPLY with the test requirement

Tested by Breeze Jiang Project Engineer / EMC Department	Approved by Glyn He Supervisor / EMC Department
	 Date: Dec. 16, 2019

This report is governed by, and incorporates by reference, CPS Conditions of Service as posted at the date of issuance of this report at <http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute you unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.

Table of Contents

RELEASE CONTROL RECORD	3
1. CERTIFICATION.....	4
2. RF EXPOSURE LIMIT	5
3. MPE CALCULATION FORMULA.....	5
4. CLASSIFICATION	5
5. ANTENNA GAIN	6
6. CALCULATION RESULT OF MAXIMUM CONDUCTED POWER.....	6



Test Report No.: FM191119N021

RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
FM191119N021	Original release	Dec. 16, 2019

1. CERTIFICATION

FCC ID:	2AM29-HBW04
PRODUCT:	Gateway
BRAND NAME:	Cloudleaf
MODEL NO.:	GW-1.5-I
ADDITIONAL NO.:	N/A
APPLICANT:	Shenzhen Hopewin Electronic Material Co.,Ltd
STANDARDS:	FCC Part 2 (Section 2.1091)
	KDB 447498 D01
	IEEE C95.1

2. RF EXPOSURE LIMIT

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

FREQUENCY RANGE (MHz)	ELECTRIC FIELD STRENGTH (V/m)	MAGNETIC FIELD STRENGTH (A/m)	POWER DENSITY (mW/cm ²)	AVERAGE TIME (minutes)
LIMITS FOR GENERAL POPULATION / UNCONTROLLED EXPOSURE				
300-1500	...	...	F/1500	30
1500-100,000	...	...	1.0	30

F = Frequency in MHz

3. MPE CALCULATION FORMULA

$$P_d = (P_{out} * G) / (4 * \pi * r^2)$$

where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

4. CLASSIFICATION

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as **Mobile Device**.

5. ANTENNA GAIN

The antennas provided to the EUT, please refer to the following table:

Function	Transmitter Circuit	Peak Gain (dBi)	Antenna Type
BT-LE(GFSK)	Chain 0	1.5	FPC Antenna
The UUT using 4 Antenna for use, But only one antenna can transmit at a time. In practical use, it will automatically switch to the single antenna with the best transceiver quality according to the transceiver quality.			
WLAN 2.4GHz	Chain 0	1.38	PCB Antenna
WLAN 5GHz	Chain 0	4.0	PCB Antenna
GPRS/WCDMA	Chain 0	1.5	Dipole Antenna

6. CALCULATION RESULT OF MAXIMUM CONDUCTED AV POWER

The tuned conducted Average Power (declared by client)

Mode	Frequency (MHz)	Target Power (dBm)	Tolerance (dBm)	Lower Tolerance (dBm)	Upper Tolerance (dBm)
BT-LE(GFSK)	2402-2480	-2	+/-2	-4	0
WLAN 2.4GHz	2412~2462	25	+/-1	24	26
WLAN 5GHz	5180~5825	20	+/-1	19	21
GPRS 850	824.2~648.2	33	+0/-1.5	31.5	33.0
GPRS 1900	1850.2~1909.8	30	+0/-1.5	28.5	30
WCDMA 850	826.4~846.6	23	+/-1	22	24
WCDMA 1700	1712.4~1752.6	23	+/-1	22	24
WCDMA 1900	1852.4~1907.6	23	+/-1	22	24

The measured conducted Average Power

Moudel	FCC ID	Mode	Frequency (MHz)	Averaged Power (dBm)
BT-LE module	2AM29-HBW04	BT-LE(GFSK)	2402~2480	-2.35
Wi-Fi Dongle	KA2WA171C1	WLAN 2.4GHz	2412~2462	25.01
		WLAN 5GHz	5180~5825	20.14
HE910 Module	RI7HE910	GPRS 850	824.2~648.2	33.00
		GPRS 1900	1850.2~1909.8	30.00
		WCDMA 850	826.4~846.6	23.90
		WCDMA 1700	1712.4~1752.6	23.54
		WCDMA 1900	1852.4~1907.6	23.90



FREQUENCY BAND (MHz)	MAX AVERAGE POWER (dBm)	ANTENNA GAIN (dBi)	DISTANCE (cm)	POWER DENSITY (mW/cm ²)	LIMIT (mW/cm ²)
BT-LE(GFSK) 2402-2480	0.0	1.5	20	0.000281	1.0
WLAN 2.4GHz	26.0	1.38	20	0.108825	1.0
WLAN 5GHz	21.0	4.0	20	0.062911	1.0
GPRS	33.0	1.5	20	0.560698	1.0
WCDMA	23.70	1.5	20	0.065876	1.0

Note:

When the product is in normal use. All the wireless functions can work at the same time.

Wifi can only transmit a single frequency band (2.4ghz or 5GHz)

Mobile communication function (GPRS/WCDMA) can only work in a single frequency band

FREQUENCY BAND (MHz)	POWER DENSITY (mW/cm ²)	TOTAL POWER DENSITY (mW/cm ²)	LIMIT (mW/cm ²)	CONCLUSION
BT-LE(GFSK) 2402-2480	0.000281	0.669804	1.0	Pass
WLAN 2.4GHz	0.108825			
GPRS	0.560698			

--- END ---