

Shenzhen Hopewin Electronic Material Co.,Ltd.

2018/7/26

To: Federal Communications Commission
7435 Oakland Mills Road
Columbia, MD

FCC ID: **2AM29-W1**


To Whom It May Concern:

This letter is to ascertain that **Shenzhen Hopewin Electronic Material Co.,Ltd.** Product **Fast Wireless Charger , W1**, has been the units used for conducting FCC compliance testing, and it meets 680106 D01 RF Exposure Wireless Charging App v03 Clause 5(b) all 6 conditions.

1	Power transfer frequency is less than 1 MHz
Reply:	Yes, frequency is 100 - 205 KHz
2	Output power from each primary coil is less than or equal to 15 watts.
Reply:	Yes, output power of the primary coil is 5W.
3	The transfer system includes only single primary and secondary coils. This includes charging systems that may have multiple primary coils and clients that are able to detect and allow coupling only between individual pairs of coils.
Reply:	Yes, the transfer system includes only single primary and secondary coils.
4	Client device is placed directly in contact with the transmitter.
Reply:	Yes, client device is placed directly in contact with the transmitter.
5	Mobile exposure conditions only (portable exposure conditions are not covered by this exclusion).
Reply:	Yes, the EUT is a Mobile Wireless Charger
6	The aggregate H-field strengths at 15 cm surrounding the device and 20 cm above the top surface from all simultaneous transmitting coils are demonstrated to be less than 50% of the MPE limit.
Reply:	Yes, the EUT field strength levels are 50% x MPE limit.

If you have any question or concerns, pls. contact us.

Sincerely,

Signature: 

Name: Xiao Luo

Title: Certification engineer

Tel: 0755-23592580

Email: qualityengineer03@hhsyhk.com