



FCC Part 15C Test Report

FCC ID: 2AM5B-WH8

Product Name:	WiFi Industrial Endoscope
Trademark:	N/A
Model Name :	WH8 WH3.9, WH5, WH6, WH7, H8, WH9, H10, H11, H12, H13, H14, H 15, H16, H17.
Prepared For :	Shenzhen Changsite Technology Co., Ltd
Address :	Room 602, Tongshengchuangye Building, Dalang Street, Longhua New District, Shenzhen City, P.R.China
Prepared By :	Shenzhen BCTC Technology Co., Ltd.
Address :	No.101, Yousong Road, Longhua New District, Shenzhen, China
Test Date:	Jun. 28 – Jul. 05, 2017
Date of Report :	Jul. 05, 2017
Report No.:	BCTC-FY170704568E



TEST RESULT CERTIFICATION

Applicant's name..... : **Shenzhen Changsite Technology Co., Ltd**
Address..... : Room 602, Tongshengchuangye Building, Dalang Street,
Longhua New District, Shenzhen City, P.R.China
Manufacture's Name..... : **Shenzhen Changsite Technology Co., Ltd**
Address..... : Room 602, Tongshengchuangye Building, Dalang Street,
Longhua New District, Shenzhen City, P.R.China
Product description
Product name..... : WiFi Industrial Endoscope
Model and/or type reference : WH8
Standards..... : FCC Part15.247
ANSI C63.10:2013
KDB 558074 D01 DTS Meas Guidance v03r03

This device described above has been tested by BCTC, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of BCTC, this document may be altered or revised by BCTC, personal only, and shall be noted in the revision of the document.

Prepared by(Engineer): Eric Yang
Reviewer(Supervisor): Jade Yang
Approved(Manager): Carson Zhang






Table of Contents

	Page
1 . SUMMARY OF TEST RESULTS	5
1.1 TEST FACILITY	6
1.2 MEASUREMENT UNCERTAINTY	6
2 . GENERAL INFORMATION	7
2.1 GENERAL DESCRIPTION OF EUT	7
2.2 DESCRIPTION OF TEST MODES	8
2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	9
2.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)	9
2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS	10
3 . EMC EMISSION TEST	11
3.1 CONDUCTED EMISSION MEASUREMENT	11
3.1.1 POWER LINE CONDUCTED EMISSION LIMITS	11
3.1.2 TEST PROCEDURE	11
3.1.3 DEVIATION FROM TEST STANDARD	11
3.1.4 TEST SETUP	12
3.1.5 EUT OPERATING CONDITIONS	12
3.1.6 TEST RESULTS	13
3.2 RADIATED EMISSION MEASUREMENT	15
3.2.1 RADIATED EMISSION LIMITS	15
3.2.2 TEST PROCEDURE	16
3.2.3 DEVIATION FROM TEST STANDARD	16
3.2.4 TEST SETUP	16
3.2.5 EUT OPERATING CONDITIONS	18
3.2.6 TEST RESULTS (BETWEEN 9KHZ – 30 MHZ)	19
3.2.7 TEST RESULTS (BETWEEN 30MHZ – 1GHZ)	20
3.3 RADIATED BAND EMISSION MEASUREMENT	27
3.3.1 TEST REQUIREMENT:	27
3.3.2 TEST PROCEDURE	27
3.3.3 DEVIATION FROM TEST STANDARD	28
3.3.4 TEST SETUP	28
3.3.5 EUT OPERATING CONDITIONS	28
4 . POWER SPECTRAL DENSITY TEST	30
4.1 APPLIED PROCEDURES / LIMIT	30
4.1.1 TEST PROCEDURE	30
4.1.2 DEVIATION FROM STANDARD	30



Table of Contents

	Page
4.1.3 TEST SETUP	30
4.1.4 EUT OPERATION CONDITIONS	30
4.1.5 TEST RESULTS	31
5 . BANDWIDTH TEST	39
5.1 APPLIED PROCEDURES / LIMIT	39
5.1.1 TEST PROCEDURE	39
5.1.2 DEVIATION FROM STANDARD	39
5.1.3 TEST SETUP	39
5.1.4 EUT OPERATION CONDITIONS	39
5.1.5 TEST RESULTS	40
6 . PEAK OUTPUT POWER TEST	48
6.1 APPLIED PROCEDURES / LIMIT	48
6.1.1 TEST PROCEDURE	48
6.1.2 DEVIATION FROM STANDARD	48
6.1.3 TEST SETUP	48
6.1.4 EUT OPERATION CONDITIONS	48
6.1.5 TEST RESULTS	49
7 . 100 KHZ BANDWIDTH OF FREQUENCY BAND EDGE	50
7.1 APPLICABLE STANDARD	50
7.2 TEST PROCEDURE	50
7.3 DEVIATION FROM STANDARD	50
7.4 TEST SETUP	50
7.5 EUT OPERATION CONDITIONS	51
7.1 TEST RESULTS	51
8 . DUTY CYCLE OF TEST SIGNAL	56
8.1 STANDARD REQUIREMENT	56
8.2 FORMULA:	56
9 . ANTENNA REQUIREMENT	59
9.1 STANDARD REQUIREMENT	59
9.2 EUT ANTENNA	59
10 . EUT TEST PHOTO	60
11 . EUT PHOTO	62
APPENDIX-PHOTOGRAPHS OF EUT CONSTRUCTIONAL DETAILS	



1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

FCC Part15 (15.247) , Subpart C			
Standard Section	Test Item	Judgment	Remark
15.207	Conducted Emission	PASS	
15.247 (a)(2)	6dB Bandwidth	PASS	
15.247 (b)	Peak Output Power	PASS	
15.247 (c)	Radiated Spurious Emission	PASS	
15.247 (d)	Power Spectral Density	PASS	
15.205	Restricted Band of Operation	PASS	
15.247 (d)	Band Edge (Out of Band Emissions)	PASS	
15.203	Antenna Requirement	PASS	

NOTE:

(1) "N/A" denotes test is not applicable in this Test Report



1.1 TEST FACILITY

Shenzhen BCTC Technology Co., Ltd.

Add. : No.101,Yousong Road,Longhua New District, Shenzhen,China

FCC Registered No.: 187086

1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately **95 %**.

No.	Item	Uncertainty
1	Conducted Emission Test	$\pm 1.38\text{dB}$
2	RF power,conducted	$\pm 0.16\text{dB}$
3	Spurious emissions,conducted	$\pm 0.21\text{dB}$
4	All emissions,radiated(<1G)	$\pm 4.68\text{dB}$
5	All emissions,radiated(>1G)	$\pm 4.89\text{dB}$
6	Temperature	$\pm 0.5^{\circ}\text{C}$
7	Humidity	$\pm 2\%$



2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

Equipment	WiFi Industrial Endoscope	
Trade Name	N/A	
Model Name	WH8	
Serial Model	WH3.9, WH5, WH6, WH7, H8, WH9, H10, H11, H12, H13, H14, H 15, H16, H17.	
Model Difference	All the model are the same circuit and RF module, except model names and different for color.	
Product Description	Operation Frequency:	802.11b/g/n20MHz:2412~2462 MHz 802.11n40MHz:2422~2452 MHz
	Modulation Type:	WIFI: OFDM/DSSS
	Bit Rate of Transmitter	802.11b:11/5.5/2/1 Mbps 802.11g:54/48/36/24/18/12/9/6Mbps 802.11n Up to 150Mbps
	Number Of Channel	802.11b/g/n20MHz:11 CH 802.11n40MHz: 7 CH
	Antenna Designation:	Please see Note 3.
	Based on the application, features, or specification exhibited in User's Manual, the EUT is considered as an ITE/Computing Device. More details of EUT technical specification, please refer to the User's Manual.	
Channel List	Please refer to the Note 2.	
Power Source	DC 3.7V	
hardware version	--	
Software version	--	
Serial number	--	
Connecting I/O Port(s)	Please refer to the User's Manual	

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.



2.

Channel List for 802.11b/g/n(20)							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
01	2412	04	2427	07	2442	10	2457
02	2417	05	2432	08	2447	11	2462
03	2422	06	2437	09	2452		

Channel List for 802.11n(40)							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
03	2422	05	2432	07	2442	09	2452
04	2427	06	2437	08	2447		

3.

Table for Filed Antenna

Ant.	Brand	Model Name	Antenna Type	Gain (dBi)	NOTE
1	N/A	N/A	PCB Antenna	0	

2.2 DESCRIPTION OF TEST MODES

Pretest Mode	Description
Mode 1	802.11b CH1/ CH6/ CH11
Mode 2	802.11g CH1/ CH6/ CH11
Mode 3	802.11n20 CH1/ CH6/ CH11
Mode 4	802.11n40 CH3/ CH6/ CH9
Mode 5	Link Mode

Conducted Emission	
Final Test Mode	Description
Mode 5	Link Mode

For Radiated Emission	
Final Test Mode	Description
Mode 1	802.11b CH1/ CH6/ CH11
Mode 2	802.11g CH1/ CH6/ CH11
Mode 3	802.11n20 CH1/ CH6/ CH11
Mode 4	802.11n40 CH3/ CH6/ CH9


Note:

(1) The measurements are performed at all Bit Rate of Transmitter, the worst data was reported.




2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED

Radiated Spurious Emission Test



Conducted Emission Test



2.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	Series No.	Note
E-1	WiFi Industrial Endoscope	N/A	WH8	N/A	EUT
E-2	Adapter	N/A	HKL-0500100	N/A	Lab Provide

Item	Shielded Type	Ferrite Core	Length	Note
C-1	NO	NO	0.8M	USB cable unshielded

Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.



2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS

Radiation Test equipment

Item	Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
1	Spectrum Analyzer (9kHz-26.5GHz)	Agilent	E4407B	MY45108040	2016.08.27	2017.08.26
2	Test Receiver (9kHz-7GHz)	R&S	ESPI	101318	2016.08.27	2017.08.26
3	Bilog Antenna (30MHz-1GHz)	R&S	VULB 9168	VULB91 68-438	2016.08.27	2017.08.26
4	Horn Antenna (1GHz-18GHz)	SCHWARZBECK	BBHA9120D	1201	2016.09.03	2017.09.03
5	Horn Antenna (14GHz-40GHz)	SCHWARZBECK	BBHA 9170	9170-181	2016.09.03	2017.09.03
6	Amplifier (9KHz-6GHz)	SCHWARZBECK	BBV9744	9744-0037	2016.08.27	2017.08.26
7	Amplifier (1GHz-18GHz)	SCHWARZBECK	BBV9718	9718-309	2016.08.27	2017.08.26
8	Amplifier (18GHz-40GHz)	SCHWARZBECK	BBV 9721	9721-205	2016.08.27	2017.08.26
9	Loop Antenna (9KHz-30MHz)	SCHWARZBECK	FMZB1519B	00014	2016.09.03	2017.09.03
10	RF cables1 (9kHz-1GHz)	R&S	R203	R20X	2016.08.27	2017.08.26
11	RF cables2 (1GHz-40GHz)	R&S	R204	R21X	2016.08.27	2017.08.26
12	Antenna connector	Florida RF Labs	N/A	RF 01#	2016.08.27	2017.08.26
13	Power Metter	ANRITSU	ML2487A	6K00001568	2016.08.27	2017.08.26
14	Power Sensor (AV)	ANRITSU	ML2491A	030989	2016.08.27	2017.08.26
15	Signal Analyzer 9kHz-26.5GHz	Agilent	N9010A	MY48030494	2016.08.27	2017.08.26
16	Test Receiver 20kHz-40GHz	R&S	ESU 40	100376	2016.08.27	2017.08.26
17	D.C. Power Supply	LongWei	PS-305D	010964729	2016.08.27	2017.08.26

Conduction Test equipment

Item	Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
1	Test Receiver	R&S	ESCI	1166.5950K03-1011 65-ha	2016.08.27	2017.08.26
2	LISN	SCHWARZBECK	NSLK8127	8127739	2016.08.27	2017.08.26
3	LISN	R&S	NSLK8126	8126487	2016.08.27	2017.08.26
4	RF cables	R&S	R204	R20X	2016.08.27	2017.08.26
5	Attenuator	R&S	ESH3-Z2	143206	2016.08.27	2017.08.26



3. EMC EMISSION TEST

3.1 CONDUCTED EMISSION MEASUREMENT

3.1.1 POWER LINE CONDUCTED EMISSION Limits (Frequency Range 150KHz-30MHz)

FREQUENCY (MHz)	Limit (dBuV)		Standard
	Quasi-peak	Average	
0.15 -0.5	66 - 56 *	56 - 46 *	FCC
0.50 -5.0	56.00	46.00	FCC
5.0 -30.0	60.00	50.00	FCC

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz


3.1.2 TEST PROCEDURE

- a. The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- d. LISN at least 80 cm from nearest part of EUT chassis.
- e. For the actual test configuration, please refer to the related Item –EUT Test Photos.

3.1.3 DEVIATION FROM TEST STANDARD

No deviation

3.1.4 TEST SETUP



Note: 1.Support units were connected to second LISN.

2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes


3.1.5 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

We pretest AC 120V and AC 240V, the worst voltage was AC 120V and the data recording in the report.



Temperature :	26°C	Relative Humidity :	54%
Pressure :	1010hPa	Phase :	N
Test Voltage :	AC 120V/60Hz	Test Mode :	Mode 5



Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1		0.1900	35.41	9.65	45.06	64.03	-18.97	QP	
2		0.1900	21.75	9.65	31.40	54.03	-22.63	AVG	
3	*	0.5740	35.66	9.68	45.34	56.00	-10.66	QP	
4		0.5740	24.91	9.68	34.59	46.00	-11.41	AVG	
5		1.0540	28.17	9.69	37.86	56.00	-18.14	QP	
6		1.0540	16.51	9.69	26.20	46.00	-19.80	AVG	
7		2.7500	26.57	9.72	36.29	56.00	-19.71	QP	
8		2.7500	13.79	9.72	23.51	46.00	-22.49	AVG	
9		5.5099	25.19	9.75	34.94	60.00	-25.06	QP	
10		5.5099	13.00	9.75	22.75	50.00	-27.25	AVG	
11		18.7739	26.98	9.86	36.84	60.00	-23.16	QP	
12		18.7739	11.31	9.86	21.17	50.00	-28.83	AVG	



3.2 RADIATED EMISSION MEASUREMENT

3.2.1 RADIATED EMISSION LIMITS (Frequency Range 9kHz-1000MHz)

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

FREQUENCY (MHz)	Limit (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	25GHz
RB / VB (emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP



3.2.2 TEST PROCEDURE

Below 1GHz test procedure as below:

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

Above 1GHz test procedure as below:

- g. Different between above is the test site, change from Semi- Anechoic Chamber to fully Anechoic Chamber and change form table 0.8 metre to 1.5 metre(Above 18GHz the distance is 1 meter and table is 1.5 metre).
- h. Test the EUT in the lowest channel ,the middle channel ,the Highest channel

Note:

Both horizontal and vertical antenna polarities were tested
and performed pretest to three orthogonal axis. The worst case emissions were reported


We pretest AC 120V and AC 240V, the worst voltage was AC 120V and the data recording in the report.

3.2.3 DEVIATION FROM TEST STANDARD


No deviation

3.2.4 TEST SETUP


(A) Radiated Emission Test-Up Frequency Below 30MHz



(B) Radiated Emission Test-Up Frequency 30MHz~1GHz



(C) Radiated Emission Test-Up Frequency Above 1GHz



3.2.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

**3.2.6 TEST RESULTS (BETWEEN 9KHZ – 30 MHZ)**

Temperature:	20℃	Relative Humidity:	48%
Pressure:	1010 hPa	Test Voltage :	DC 3.7V
Test Mode :	Mode 5	Polarization :	--

Freq.	Reading	Limit	Margin	State
(MHz)	(dBuV/m)	(dBuV/m)	(dB)	P/F
--	--	--	--	PASS
--	--	--	--	PASS

NOTE:

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.


Distance extrapolation factor = $40 \log (\text{specific distance/test distance})$ (dB);

Limit line = specific limits(dBuv) + distance extrapolation factor.



3.2.7 TEST RESULTS (BETWEEN 30MHZ – 1GHZ)

Temperature :	26℃	Relative Humidity :	54%
Pressure :	1010 hPa	Polarization :	Horizontal
Test Voltage :	DC 3.7V		
Test Mode :	Mode 5		




Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dB/m	Over dB	Detector
1		119.8555	38.87	-18.07	20.80	43.50	-22.70	QP
2		193.0945	52.64	-16.27	36.37	43.50	-7.13	QP
3	*	360.4476	54.66	-10.40	44.26	46.00	-1.74	QP
4		408.9460	47.82	-9.13	38.69	46.00	-7.31	QP
5		455.9057	47.16	-8.33	38.83	46.00	-7.17	QP
6		842.1295	38.27	-0.47	37.80	46.00	-8.20	QP



Temperature :	26°C	Relative Humidity :	54%
Pressure :	1010 hPa	Polarization :	Vertical
Test Voltage :	DC 3.7V		
Test Mode :	Mode 5		



Remark:
Factor = Antenna Factor + Cable Loss – Pre-amplifier.

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dB/m	Over dB	Detector
1		192.4186	39.98	-16.35	23.63	43.50	-19.87	QP
2	!	360.4476	53.18	-10.40	42.78	46.00	-3.22	QP
3	!	601.4265	44.60	-4.47	40.13	46.00	-5.87	QP
4	!	649.6597	46.38	-3.82	42.56	46.00	-3.44	QP
5	!	672.8444	44.89	-3.42	41.47	46.00	-4.53	QP
6	*	836.2443	44.00	-0.58	43.42	46.00	-2.58	QP



3.2.8 TEST RESULTS (1ghz~25ghz)

802.11b

Polar (H/V)	Frequency	Meter Reading	Pre-amplifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
		Low Channel:2412							
V	4824.00	65.23	39.55	7.85	25.66	59.19	74.00	-14.81	PK
V	4824.00	48.65	39.55	7.85	25.66	42.61	54.00	-11.39	AV
V	7236.00	66.35	38.33	7.52	24.55	60.09	74.00	-13.91	PK
V	7236.00	47.78	38.33	7.52	24.55	41.52	54.00	-12.48	AV
V	15450.00	45.35	35.23	6.75	26.59	43.46	74.00	-30.54	PK
H	4824.00	67.43	39.55	7.85	25.66	61.39	74.00	-12.61	PK
H	4824.00	49.26	39.55	7.85	25.66	43.22	54.00	-10.78	AV
H	7236.00	65.75	38.33	7.52	23.55	58.49	74.00	-15.51	PK
H	7236.00	46.35	38.33	7.52	23.22	38.76	54.00	-15.24	AV
H	15450.00	45.37	35.45	6.75	27.88	44.55	74.00	-29.45	PK

Polar (H/V)	Frequency	Meter Reading	Pre-amplifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
		Middle Channel:2437							
V	4874.00	66.87	38.89	7.57	25.45	61.00	74.00	-13.00	PK
V	4874.00	49.62	38.89	7.57	25.45	43.75	54.00	-10.25	AV
V	7311.00	67.46	38.78	7.35	24.78	60.81	74.00	-13.19	PK
V	7311.00	47.35	38.78	7.35	24.78	40.70	54.00	-13.30	AV
V	15450.00	46.32	35.89	6.42	26.47	43.32	74.00	-30.68	PK
H	4874.00	65.94	38.89	7.57	25.45	60.07	74.00	-13.93	PK
H	4874.00	48.66	38.89	7.57	25.45	42.79	54.00	-11.21	AV
H	7311.00	67.58	38.78	7.35	24.78	60.93	74.00	-13.07	PK
H	7311.00	45.72	38.78	7.35	24.78	39.07	54.00	-14.93	AV
H	15450.00	44.38	36.68	6.42	26.65	40.77	74.00	-33.23	PK

Polar (H/V)	Frequency	Meter Reading	Pre-amplifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
		High Channel:2462							
V	4924.00	67.25	38.75	7.46	25.45	61.41	74.00	-12.59	PK
V	4924.00	44.47	38.75	7.46	25.45	38.63	54.00	-15.37	AV
V	7386.00	66.10	38.65	7.22	24.78	59.45	74.00	-14.55	PK
V	7386.00	43.35	38.65	7.22	24.78	36.70	54.00	-17.30	AV
V	15450.00	47.38	35.58	6.35	26.47	44.62	74.00	-29.38	PK
H	4924.00	66.32	38.75	7.46	25.45	60.48	74.00	-13.52	PK
H	4924.00	44.78	38.75	7.46	25.45	38.94	54.00	-15.06	AV
H	7386.00	62.57	38.65	7.22	24.78	55.92	74.00	-18.08	PK
H	7386.00	43.78	38.65	7.22	24.78	37.13	54.00	-16.87	AV
H	15450.00	45.24	36.42	6.32	26.65	41.79	74.00	-32.21	PK

**Remark:**

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier, Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

802.11g

Polar (H/V)	Frequency	Meter Reading	Pre-amplifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
		Low Channel:2412							
V	4824.00	66.73	39.55	7.85	25.66	60.69	74.00	-13.31	PK
V	4824.00	48.85	39.55	7.85	25.66	42.81	54.00	-11.19	AV
V	7236.00	67.13	38.33	7.52	24.55	60.87	74.00	-13.13	PK
V	7236.00	48.37	38.33	7.52	24.55	42.11	54.00	-11.89	AV
V	15450.00	45.63	35.23	6.75	26.59	43.74	74.00	-30.26	PK
H	4824.00	67.36	39.55	7.85	25.66	61.32	74.00	-12.68	PK
H	4824.00	50.16	39.55	7.85	25.66	44.12	54.00	-9.88	AV
H	7236.00	69.39	38.33	7.52	23.55	62.13	74.00	-11.87	PK
H	7236.00	42.64	38.33	7.52	23.22	35.05	54.00	-18.95	AV
H	15450.00	47.56	35.45	6.75	27.88	46.74	74.00	-27.26	PK

Polar (H/V)	Frequency	Meter Reading	Pre-amplifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
		Middle Channel:2437							
V	4874.00	67.21	38.89	7.57	25.45	61.34	74.00	-12.66	PK
V	4874.00	49.82	38.89	7.57	25.45	43.95	54.00	-10.05	AV
V	7311.00	67.71	38.78	7.35	24.78	61.06	74.00	-12.94	PK
V	7311.00	47.78	38.78	7.35	24.78	41.13	54.00	-12.87	AV
V	15450.00	52.12	35.89	6.42	26.47	49.12	74.00	-24.88	PK
H	4874.00	65.58	38.89	7.57	25.45	59.71	74.00	-14.29	PK
H	4874.00	49.68	38.89	7.57	25.45	43.81	54.00	-10.19	AV
H	7311.00	68.77	38.78	7.35	24.78	62.12	74.00	-11.88	PK
H	7311.00	48.31	38.78	7.35	24.78	41.66	54.00	-12.34	AV
H	15450.00	45.37	36.68	6.42	26.65	41.76	74.00	-32.24	PK

Polar (H/V)	Frequency	Meter Reading	Pre-amplifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
		High Channel:2462							
V	4924.00	66.37	38.75	7.46	25.45	60.53	74.00	-13.47	PK
V	4924.00	48.05	38.75	7.46	25.45	42.21	54.00	-11.79	AV
V	7386.00	67.38	38.65	7.22	24.78	60.73	74.00	-13.27	PK
V	7386.00	49.05	38.65	7.22	24.78	42.40	54.00	-11.60	AV
V	15450.00	46.35	35.58	6.35	26.47	43.59	74.00	-30.41	PK
H	4924.00	47.36	38.75	7.46	25.45	41.52	74.00	-32.48	PK
H	4924.00	46.95	38.75	7.46	25.45	41.11	54.00	-12.89	AV
H	7386.00	63.36	38.65	7.22	24.78	56.71	74.00	-17.29	PK
H	7386.00	48.74	38.65	7.22	24.78	42.09	54.00	-11.91	AV
H	15450.00	46.46	36.42	6.32	26.65	43.01	74.00	-30.99	PK

**Remark:**

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier, Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

802.11n(20MHz)

Polar (H/V)	Frequency	Meter Reading	Pre-amplifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
		Low Channel:2412							
V	4824.00	66.24	39.55	7.85	25.66	60.20	74.00	-13.80	PK
V	4824.00	46.37	39.55	7.85	25.66	40.33	54.00	-13.67	AV
V	7236.00	64.61	38.33	7.52	24.55	58.35	74.00	-15.65	PK
V	7236.00	46.28	38.33	7.52	24.55	40.02	54.00	-13.98	AV
V	15450.00	49.14	35.23	6.75	26.59	47.25	74.00	-26.75	PK
H	4824.00	65.24	39.55	7.85	25.66	59.20	74.00	-14.80	PK
H	4824.00	47.66	39.55	7.85	25.66	41.62	54.00	-12.38	AV
H	7236.00	67.44	38.33	7.52	23.55	60.18	74.00	-13.82	PK
H	7236.00	50.15	38.33	7.52	23.22	42.56	54.00	-11.44	AV
H	15450.00	45.38	35.45	6.75	27.88	44.56	74.00	-29.44	PK

Polar (H/V)	Frequency	Meter Reading	Pre-amplifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
		Middle Channel:2437							
V	4874.00	66.71	38.89	7.57	25.45	60.84	74.00	-13.16	PK
V	4874.00	49.38	38.89	7.57	25.45	43.51	54.00	-10.49	AV
V	7311.00	67.31	38.78	7.35	24.78	60.66	74.00	-13.34	PK
V	7311.00	47.38	38.78	7.35	24.78	40.73	54.00	-13.27	AV
V	15450.00	46.06	35.89	6.42	26.47	43.06	74.00	-30.94	PK
H	4874.00	65.15	38.89	7.57	25.45	59.28	74.00	-14.72	PK
H	4874.00	49.44	38.89	7.57	25.45	43.57	54.00	-10.43	AV
H	7311.00	69.37	38.78	7.35	24.78	62.72	74.00	-11.28	PK
H	7311.00	48.56	38.78	7.35	24.78	41.91	54.00	-12.09	AV
H	15450.00	48.93	36.68	6.42	26.65	45.32	74.00	-28.68	PK

Polar (H/V)	Frequency	Meter Reading	Pre-amplifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
		High Channel:2462							
V	4924.00	66.74	38.75	7.46	25.45	60.90	74.00	-13.10	PK
V	4924.00	48.87	38.75	7.46	25.45	43.03	54.00	-10.97	AV
V	7386.00	66.03	38.65	7.22	24.78	59.38	74.00	-14.62	PK
V	7386.00	47.85	38.65	7.22	24.78	41.20	54.00	-12.80	AV
V	15450.00	45.93	35.58	6.35	26.47	43.17	74.00	-30.83	PK
H	4924.00	65.11	38.75	7.46	25.45	59.27	74.00	-14.73	PK
H	4924.00	49.24	38.75	7.46	25.45	43.40	54.00	-10.60	AV
H	7386.00	68.02	38.65	7.22	24.78	61.37	74.00	-12.63	PK
H	7386.00	47.46	38.65	7.22	24.78	40.81	54.00	-13.19	AV
H	15450.00	49.37	36.42	6.32	26.65	45.92	74.00	-28.08	PK

**Remark:**

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier, Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

802.11n(40MHz)

Polar (H/V)	Frequency	Meter Reading	Pre-amplifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
		Low Channel:2422							
V	4844.000	65.52	39.55	7.77	25.66	59.40	74	-14.60	PK
V	4844.000	47.64	39.55	7.77	25.66	41.52	54	-12.48	AV
V	7266.000	64.65	38.33	7.30	24.55	58.17	74	-15.83	PK
V	7266.000	45.62	38.33	7.30	24.55	39.14	54	-14.86	AV
V	15450.00	46.25	35.23	6.60	26.59	44.21	74	-29.79	PK
H	4844.000	66.72	39.55	7.77	25.66	60.60	74	-13.40	PK
H	4844.000	42.35	39.55	7.77	25.66	36.23	54	-17.77	AV
H	7266.000	62.43	38.33	7.30	23.55	54.95	74	-19.05	PK
H	7266.000	46.75	38.33	7.30	23.22	38.94	54	-15.06	AV
H	15450.00	45.25	35.45	6.60	27.88	44.28	74	-29.72	PK

Polar (H/V)	Frequency	Meter Reading	Pre-amplifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
		Middle Channel:2437							
V	4874.00	65.25	38.89	7.57	25.45	59.38	74.00	-14.62	PK
V	4874.00	47.34	38.89	7.57	25.45	41.47	54.00	-12.53	AV
V	7311.00	67.35	38.78	7.35	24.78	60.70	74.00	-13.30	PK
V	7311.00	47.49	38.78	7.35	24.78	40.84	54.00	-13.16	AV
V	15450.00	46.87	35.89	6.42	26.47	43.87	74.00	-30.13	PK
H	4874.00	66.25	38.89	7.57	25.45	60.38	74.00	-13.62	PK
H	4874.00	47.25	38.89	7.57	25.45	41.38	54.00	-12.62	AV
H	7311.00	64.44	38.78	7.35	24.78	57.79	74.00	-16.21	PK
H	7311.00	48.25	38.78	7.35	24.78	41.60	54.00	-12.40	AV
H	15450.00	46.23	36.68	6.42	26.65	42.62	74.00	-31.38	PK

Polar (H/V)	Frequency	Meter Reading	Pre-amplifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detector Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
		High Channel:2452							
V	4904.00	67.02	38.75	7.38	25.45	61.10	74	-12.90	PK
V	4904.00	47.34	38.75	7.38	25.45	41.42	54	-12.58	AV
V	7356.00	63.45	38.65	7.15	24.78	56.73	74	-17.27	PK
V	7356.00	46.27	38.65	7.15	24.78	39.55	54	-14.45	AV
V	15450.00	47.23	35.58	6.25	26.47	44.37	74	-29.63	PK
H	4904.00	66.86	38.75	7.38	25.45	60.94	74	-13.06	PK
H	4904.00	44.55	38.75	7.38	25.45	38.63	54	-15.37	AV
H	7356.00	59.43	38.65	7.15	24.78	52.71	74	-21.29	PK
H	7356.00	46.19	38.65	7.15	24.78	39.47	54	-14.53	AV
H	15450.00	45.28	36.42	6.25	26.65	41.76	74	-32.24	PK



Remark:

- 1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
Margin= Emission Level - Limit**
- 2. If peak below the average limit, the average emission was no test.**
- 3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.**



3.3 RADIATED BAND EMISSION MEASUREMENT

3.3.1 TEST REQUIREMENT:

FCC Part15 C Section 15.209 and 15.205

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

FREQUENCY (MHz)	Limit (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	2300MHz
Stop Frequency	2520
RB / VB (emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average

3.3.2 TEST PROCEDURE

Above 1GHz test procedure as below:

- a. 1. The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- g. Test the EUT in the lowest channel,the Highest channel

Note:


Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported

3.3.3 DEVIATION FROM TEST STANDARD

No deviation

3.3.4 TEST SETUP

Radiated Emission Test-Up Frequency Above 1GHz



3.3.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.



3.3.6 TEST RESULT

	Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre- amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB/m)	Emission evel (dBuV/m)	Limits (dBuV/m)		Result
							PK	PK	AV	
802.11b	Low Channel 2412MHz									
	H	2390.00	56.35	38.06	7.42	20.15	45.86	74.00	54.00	PASS
	H	2400.00	57.24	38.06	7.42	20.15	46.75	74.00	54.00	PASS
	V	2390.00	57.35	38.06	7.42	20.15	46.86	74.00	54.00	PASS
	V	2400.00	56.28	38.06	7.42	20.15	45.79	74.00	54.00	PASS
	High Channel 2462MHz									
	H	2483.50	57.75	38.17	7.45	20.54	47.57	74.00	54.00	PASS
	H	2485.50	56.68	38.17	7.45	20.54	46.50	74.00	54.00	PASS
	V	2483.50	57.87	38.20	7.45	20.54	47.66	74.00	54.00	PASS
V	2485.50	56.46	38.20	7.45	20.54	46.25	74.00	54.00	PASS	
802.11g	Low Channel 2412MHz									
	H	2390.00	59.25	38.06	7.42	20.15	48.76	74.00	54.00	PASS
	H	2400.00	58.64	38.06	7.42	20.15	48.15	74.00	54.00	PASS
	V	2390.00	60.23	38.06	7.42	20.15	49.74	74.00	54.00	PASS
	V	2400.00	59.75	38.06	7.42	20.15	49.26	74.00	54.00	PASS
	High Channel 2462MHz									
	H	2483.50	58.44	38.17	7.45	20.54	48.26	74.00	54.00	PASS
	H	2485.50	57.87	38.17	7.45	20.54	47.69	74.00	54.00	PASS
	V	2483.50	58.65	38.20	7.45	20.54	48.44	74.00	54.00	PASS
V	2485.50	58.77	38.20	7.45	20.54	48.56	74.00	54.00	PASS	
802.11N20	Low Channel 2412MHz									
	H	2390.00	58.59	38.06	7.42	20.15	48.10	74.00	54.00	PASS
	H	2400.00	59.96	38.06	7.42	20.15	49.47	74.00	54.00	PASS
	V	2390.00	60.03	38.06	7.42	20.15	49.54	74.00	54.00	PASS
	V	2400.00	59.11	38.06	7.42	20.15	48.62	74.00	54.00	PASS
	High Channel 2462MHz									
	H	2483.50	59.25	38.17	7.45	20.54	49.07	74.00	54.00	PASS
	H	2485.50	59.62	38.17	7.45	20.54	49.44	74.00	54.00	PASS
	V	2483.50	58.47	38.20	7.45	20.54	48.26	74.00	54.00	PASS
V	2485.50	58.45	38.20	7.45	20.54	48.24	74.00	54.00	PASS	
802.11N40	Low Channel 2422MHz									
	H	2390.00	58.16	38.06	7.42	20.15	47.67	74.00	54.00	PASS
	H	2400.00	59.25	38.06	7.42	20.15	48.76	74.00	54.00	PASS
	V	2390.00	59.36	38.06	7.42	20.15	48.87	74.00	54.00	PASS
	V	2400.00	58.71	38.06	7.42	20.15	48.22	74.00	54.00	PASS
	High Channel 2452MHz									
	H	2483.50	58.05	38.17	7.45	20.54	47.87	74.00	54.00	PASS
	H	2485.50	58.63	38.17	7.45	20.54	48.45	74.00	54.00	PASS
	V	2483.50	58.57	38.20	7.45	20.54	48.36	74.00	54.00	PASS
V	2485.50	58.36	38.20	7.45	20.54	48.15	74.00	54.00	PASS	
Remark:										
1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier, Margin= Emission Level - Limit										
2. If the PK measured levels comply with average limit, then the average level were deemed to comply with average limit.										



4. POWER SPECTRAL DENSITY TEST

4.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247	Power Spectral Density	8 dBm (in any 3KHz)	2400-2483.5	PASS


4.1.1 TEST PROCEDURE

1. Set analyzer center frequency to DTS channel center frequency.
2. Set the span to 1.5 times the DTS bandwidth.
3. Set the RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
4. Set the VBW $\geq 3 \times \text{RBW}$.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level within the RBW.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

4.1.2 DEVIATION FROM STANDARD

No deviation.

4.1.3 TEST SETUP



4.1.4 EUT OPERATION CONDITIONS


The EUT tested system was configured as the statements of 2.1 Unless otherwise a special operating condition is specified in the follows during the testing.





4.1.5 TEST RESULTS

Temperature :	25°C	Relative Humidity :	60%
Pressure :	1015 hPa	Test Voltage :	DC 3.7V
Test Mode :	TX b Mode		

Frequency	Power Density (dBm)	Limit (dBm)	Result
2412 MHz	-13.29	8	PASS
2437 MHz	-15.68	8	PASS
2462 MHz	-14.53	8	PASS










Temperature :	25°C	Relative Humidity :	60%
Pressure :	1015 hPa	Test Voltage :	DC 3.7V
Test Mode :	TX g Mode		

Frequency	Power Density (dBm)	Limit (dBm)	Result
2412 MHz	-12.31	8	PASS
2437 MHz	-16.17	8	PASS
2462 MHz	-14.71	8	PASS










Temperature :	25°C	Relative Humidity :	60%
Pressure :	1015 hPa	Test Voltage :	DC 3.7V
Test Mode :	TX n Mode(20M)		

Frequency	Power Density (dBm)	Limit (dBm)	Result
2412 MHz	-12.85	8	PASS
2437 MHz	-12.17	8	PASS
2462 MHz	-13.92	8	PASS









Temperature :	25°C	Relative Humidity :	60%
Pressure :	1015 hPa	Test Voltage :	DC 3.7V
Test Mode :	TX n Mode(40M)		


Frequency	Power Density (dBm)	Limit (dBm)	Result
2422 MHz	-13.50	8	PASS
2437 MHz	-15.02	8	PASS
2452 MHz	-15.67	8	PASS



TX CH06



TX CH09





5. BANDWIDTH TEST

5.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(a)(2)	Bandwidth	$\geq 500\text{KHz}$ (6dB bandwidth)	2400-2483.5	PASS

5.1.1 TEST PROCEDURE

1. Set RBW = 100 kHz.
2. Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

5.1.2 DEVIATION FROM STANDARD

No deviation.

5.1.3 TEST SETUP



5.1.4 EUT OPERATION CONDITIONS


The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.




5.1.5 TEST RESULTS

Temperature :	25°C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC 3.7V
Test Mode :	TX b Mode		


Channel	Frequency (MHz)	6dB bandwidth (MHz)	Limit (kHz)	Result
Low	2412	9.202	500	Pass
Middle	2437	9.627	500	Pass
High	2462	9.328	500	Pass



TX CH 06




TX CH 11






Temperature :	25°C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC 3.7V
Test Mode :	TX g Mode		


Channel	Frequency (MHz)	6dB bandwidth (MHz)	Limit (kHz)	Result
Low	2412	16.447	500	Pass
Middle	2437	15.688	500	Pass
High	2462	15.958	500	Pass



TX CH 06




TX CH 11






Temperature :	25°C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC 3.7V
Test Mode :	TX n Mode(20M)		

Channel	Frequency (MHz)	6dB bandwidth (MHz)	Limit (kHz)	Result
Low	2412	17.553	500	Pass
Middle	2437	17.224	500	Pass
High	2462	17.362	500	Pass









Temperature :	25°C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC 3.7V
Test Mode :	TX n Mode(40M)		

Channel	Frequency (MHz)	6dB bandwidth (MHz)	Limit (kHz)	Result
Low	2422	36.253	500	Pass
Middle	2437	36.124	500	Pass
High	2452	36.505	500	Pass







6. PEAK OUTPUT POWER TEST

6.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(b)(3)	Peak Output Power	1 watt or 30dBm	2400-2483.5	PASS

6.1.1 TEST PROCEDURE

- a. The EUT was directly connected to the Power meter

6.1.2 DEVIATION FROM STANDARD

No deviation.

6.1.3 TEST SETUP



6.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.



6.1.5 TEST RESULTS

Temperature :	25°C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC 3.7V

TX 802.11b Mode			
Test Channe	Frequency	Maximum Conducted Output Power(PK)	LIMIT
	(MHz)	(dBm)	dBm
CH01	2412	8.83	30
CH06	2437	8.69	30
CH11	2462	8.37	30
TX 802.11g Mode			
CH01	2412	8.81	30
CH06	2437	8.63	30
CH11	2462	8.72	30
TX 802.11n-HT20 Mode			
CH01	2412	8.94	30
CH06	2437	8.75	30
CH11	2462	8.86	30
TX 802.11n-HT40 Mode			
CH03	2422	7.64	30
CH06	2437	7.38	30
CH09	2452	7.56	30



7. 100 KHZ BANDWIDTH OF FREQUENCY BAND EDGE

7.1 APPLICABLE STANDARD

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).


7.2 TEST PROCEDURE

- a) Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- b) Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
- c) Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
- d) Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
- e) Repeat above procedures until all measured frequencies were complete.

7.3 DEVIATION FROM STANDARD

No deviation.

7.4 TEST SETUP






7.5 EUT OPERATION CONDITIONS


The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

7.1 TEST RESULTS


802.11b: Band Edge, Left Side




802.11b: Band Edge, Right Side



802.11g: Band Edge, Left Side




802.11g: Band Edge, Right Side







802.11n-HT20: Band Edge, Left Side




802.11n-HT20: Band Edge, Right Side



802.11n-HT40: Band Edge, Left Side



802.11n-HT40: Band Edge, Right Side





8. DUTY CYCLE OF TEST SIGNAL

8.1 STANDARD REQUIREMENT

Pre-analysis Check: While conducting average power measurement, duty cycle of each mode shall be checked to ensure its duty cycle in order to compensate for the loss due to insufficient ratio of duty cycle.

All duty cycle is pre-scanned, and result as obtained below shows only the most representative ones where duty cycle is conducted as the given transmission with given virtual operation that expresses the percentage.

8.2 FORMULA:

Duty Cycle = $T_{on} / (T_{on} + T_{off})$

Measurement Procedure:


1. Set span = Zero
2. RBW = 8MHz
3. VBW = 8MHz,
4. Detector = Peak

Duty Cycle:


	Duty Cycle	Duty Fator (dB)
802.11b	1	0
802.11g	1	0
802.11n(HT20)	1	0
802.11n(HT40)	1	0



802.11b




802.11g






802.11n20



802.11n40





9. ANTENNA REQUIREMENT

9.1 STANDARD REQUIREMENT

15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

9.2 EUT ANTENNA

The EUT antenna is (PCB) antenna. It complies with the standard requirement.

10. EUT TEST PHOTO


Conducted Measurement Photos



Radiated Measurement Photos



Radiated Measurement Photos



11. EUT PHOTO



***** END OF REPORT *****