



FCC TEST REPORT

**Test report
On Behalf of
Streamax Technology Co.,Ltd.
For
CAMERA
Model No.: C6D**

FCC ID: 2AM6L-C6D

Prepared for : Streamax Technology Co.,Ltd.
21-23/F, Building B1, Zhiyuan, No. 1001, Xueyuan Avenue, Nanshan District,
Shenzhen, Guangdong,P.R. China.

Prepared By : Shenzhen HUAK Testing Technology Co., Ltd.
1F, B2 Building, Junfeng Zhongcheng Zhizao Innovation Park, Fuhai Street,
Bao'an District, Shenzhen City, China

Date of Test: Jul. 05, 2018 ~ Aug. 31, 2018

Date of Report: Aug. 31, 2018

Report Number: HUAK180903942E



TEST RESULT CERTIFICATION

Applicant's name : Streamax Technology Co.,Ltd.
21-23/F, Building B1, Zhiyuan, No. 1001, Xueyuan Avenue,
Address : Nanshan District, Shenzhen, Guangdong,P.R. China.

Manufacture's Name..... : Streamax Electronics Co.,Ltd.
5th-6thFloor, West, Chuangxiang 2nd Building, Yanxiang
Address : Technology Park, 11# High-tech West Road, Guangming District,
Shenzhen, Guangdong Province, P.R. China .

Product description

Trade Mark: Streamax
Product name..... : CAMERA
Model and/or type reference : C6D

Standards..... : FCC Part 15.247
KDB 558074 D01 DTS Meas Guidance v04

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen HUAK Testing Technology Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen HUAK Testing Technology Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Date of Test..... :
Date (s) of performance of tests..... : **Jul. 05, 2018 ~ Aug. 31, 2018**
Date of Issue..... : **Aug. 31, 2018**
Test Result : **Pass**

Testing Engineer : 

(Gary Qian)

Technical Manager : 

(Eden Hu)

Authorized Signatory : 

(Jason Zhou)



Revision History

Report Version	Revise Time	Issued Date	Valid Version	Notes
V1.0	/	Aug. 31, 2018	Valid	Initial Release



TABLE OF CONTENTS

1. GENERAL INFORMATION	6
1.1. PRODUCT DESCRIPTION	6
1.2. RELATED SUBMITTAL(S)/GRANT(S)	6
1.3. TEST METHODOLOGY	6
1.4. TEST FACILITY	7
1.5. SPECIAL ACCESSORIES	7
1.6. EQUIPMENT MODIFICATIONS	7
2. MEASUREMENT UNCERTAINTY	8
3. SYSTEM TEST CONFIGURATION	9
3.1. CONFIGURATION OF TESTED SYSTEM	9
3.2. EQUIPMENT USED IN TESTED SYSTEM	9
4. SUMMARY OF TEST RESULTS	11
5. DESCRIPTION OF TEST MODES	12
6. RADIATED EMISSION	13
6.1. MEASUREMENT PROCEDURE	13
6.2. TEST SETUP	14
6.3. LIMITS AND MEASUREMENT RESULT	15
6.4. TEST RESULT	16
7. BAND EDGE EMISSION	19
7.1. MEASUREMENT PROCEDURE	19
7.2. TEST SET-UP	19
7.3. RADIATED TEST RESULT	20
8. CONDUCTED TEST RESULT	21
9. 6DB BANDWIDTH	22
9.1. TEST PROCEDURE	22
9.2. SUMMARY OF TEST RESULTS/PLOTS	22
10. CONDUCTED OUTPUT POWER	23
10.1. MEASUREMENT PROCEDURE	23
10.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	23
10.3. LIMITS AND MEASUREMENT RESULT	24
11. MAXIMUM CONDUCTED OUTPUT POWER SPECTRAL DENSITY	25
11.1. MEASUREMENT PROCEDURE	25
11.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	25
11.3. LIMITS AND MEASUREMENT RESULT	26



12. CONDUCTED SPURIOUS EMISSION.....	27
12.1. MEASUREMENT PROCEDURE	27
12.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION).....	28
12.3. MEASUREMENT EQUIPMENT USED	28
12.4. LIMITS AND MEASUREMENT RESULT.....	28
13. APPENDIX A: PHOTOGRAPHS OF TEST SETUP	31



1. GENERAL INFORMATION

1.1. PRODUCT DESCRIPTION

The EUT is designed as “CAMERA”. It is designed by way of utilizing the GFSK technology to achieve the system operation.

A major technical description of EUT is described as following:

Operation Frequency	2.402 GHz to 2.480GHz
Bluetooth Version	V4.1(BLE)
Modulation	GFSK
Number of channels	40 Channel(37 Hopping Channel,3 advertising Channel)
Antenna Designation	PCB Antenna
Antenna Gain	0.5dBi
Hardware Version	1439.02
Software Version	V232
Power Supply	DC 9~36V
Test Power Supply	DC 12V

1.2. RELATED SUBMITTAL(S)/GRANT(S)

This submittal(s) (test report) is intended for **FCC ID: 2AM6L-C6D** filing to comply with Section 15.247of the FCC Part 15, Subpart C Rules.

1.3. TEST METHODOLOGY

All measurements contained in this report were conducted with KDB 558074, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

The equipment under test (EUT) was configured to measure its highest possible emission level. The test modes were adapted accordingly in reference to the Operating Instructions. The EUT was tested in all three orthogonal planes and the worse case was showed.

**1.4. TEST FACILITY**

Test Firm	Shenzhen HUAK Testing Technology Co., Ltd.
Address	1F, B2 Building, Junfeng Zhongcheng Zhizao Innovation Park, Fuhai Street, Bao'an District, Shenzhen City, China
Designation Number	CN1229
Registration Number	616276

1.5. SPECIAL ACCESSORIES

Refer to section 1.2.

1.6. EQUIPMENT MODIFICATIONS

Not available for this EUT intended for grant.



2. MEASUREMENT UNCERTAINTY

Test	Measurement Uncertainty	Notes
Transmitter power conducted	± 0.57 dB	(1)
Transmitter power Radiated	± 2.20 dB	(1)
Conducted spurious emission 9KHz-40 GHz	± 2.20 dB	(1)
Occupied Bandwidth	± 0.01 ppm	(1)
Radiated Emission 30~1000MHz	± 4.10 dB	(1)
Radiated Emission Above 1GHz	± 4.32 dB	(1)
Conducted Disturbance 0.15~30MHz	± 3.20 dB	(1)


- (1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.



3. SYSTEM TEST CONFIGURATION

3.1. CONFIGURATION OF TESTED SYSTEM

Configuration:



3.2. EQUIPMENT USED IN TESTED SYSTEM

Item	Equipment	Model No.	ID or Specification	Remark
1	CAMERA	C6D	2AM6L-C6D	EUT
2	Antenna	N/A	N/A	Accessory

**ALL TEST EQUIPMENT LIST**

Equipment	Manufacturer	Model	S/N	Cal. Due
Receiver	R&S	ESCI 7	HKE-010	Dec. 28, 2018
LISN	R&S	ENV216	HKE-002	Dec. 28, 2018
Conducted test software	Tonscend	TS+ Rev 2.5.0.0	HKE-081	N/A
Power meter	Agilent	E4417B	HKE-107	Dec. 28, 2018
Power Sensor	Agilent	E9327A	HKE-113	Dec. 28, 2018
RF cable	Times	1-40G	HKE-034	Dec. 28, 2018
RF automatic control unit	Tonscend	JS0806-2	HKE-060	Dec. 28, 2018
Spectrum analyzer	Agilent	N9020A	HKE-048	Dec. 28, 2018
RF Cable (9KHz-26.5GHz)	Tonscend	170660	N/A	Dec. 28, 2018
Signal generator	Agilent	N5183A	HKE-071	Dec. 28, 2018
Receiver	R&S	ESCI-7	HKE-010	Dec. 28, 2018
Preamplifier	EMCI	EMC051845SE	HKE-015	Dec. 28, 2018
Preamplifier	Agilent	83051A	HKE-016	Dec. 28, 2018
Loop antenna	Schwarzbeck	FMZB 1519 B	HKE-014	Dec. 28, 2018
Broadband antenna	Schwarzbeck	VULB 9163	HKE-012	Dec. 28, 2018
Horn antenna	Schwarzbeck	9120D	HKE-013	Dec. 28, 2018
Antenna Mast	Keleto	CC-A-4M	N/A	N/A
Position controller	Taiwan MF	MF7802	HKE-011	Dec. 28, 2018
RF cable (9KHz-1GHz)	Times	381806-001	N/A	N/A



4. SUMMARY OF TEST RESULTS

FCC RULES	DESCRIPTION OF TEST	RESULT
§15.203	Antenna Requirement	Compliant
§15.209 §15.247(d)	Radiated Emission	Compliant
§15.247(d)	Band Edges	Compliant
§15.247	6 dB Bandwidth	Compliant
§15.247(b)	Conducted Power	Compliant
§15.247(e)	Maximum Conducted Output Power SPECTRAL Density	Compliant
§15.207	Line Conduction Emission	Compliant
§15.207	Conduction Emission	Compliant



5. DESCRIPTION OF TEST MODES

The EUT has been operated in three modulations: GFSK independently.

NO.	TEST MODE DESCRIPTION
1	Low channel TX
2	Middle channel TX
3	High channel TX
4	Normal Operating (BT)

Note:

1. All the test modes can be supply by Built-in Li-ion battery, only the result of the worst case was recorded in the report if no any records.
2. For Radiated Emission, 3axis were chosen for testing for each applicable mode.
3. EUT is operating at its maximum duty cycle>or equal 98%




6. RADIATED EMISSION

6.1. MEASUREMENT PROCEDURE


1. The EUT was placed on the top of the turntable 0.8 or 1.5 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
4. For each suspected emissions, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
6. For emissions above 1GHz, use 1MHz VBW and RBW for peak reading. Then 1MHz RBW and 10Hz VBW for average reading in spectrum analyzer. Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum values.
8. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High - Low scan is not required in this case.

6.2. TEST SETUP


Radiated Emission Test-Setup Frequency Below 30MHz



RADIATED EMISSION TEST SETUP 30MHz-1000MHz



RADIATED EMISSION TEST SETUP ABOVE 1000MHz





6.3. LIMITS AND MEASUREMENT RESULT

15.209 Limit in the below table has to be followed

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

Note: All modes were tested For restricted band radiated emission,
the test records reported below are the worst result compared to other modes.




6.4. TEST RESULT

RADIATED EMISSION BELOW 30MHZ

No emission found between lowest internal used/generated frequencies to 30MHz.

RADIATED EMISSION BELOW 1GHZ

RADIATED EMISSION TEST- (30MHZ-1GHZ) -HORIZONTAL




No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		110.8333	29.40	7.98	37.38	43.50	-6.12	peak			
2	!	185.2000	27.35	11.31	38.66	43.50	-4.84	peak			
3	!	371.1167	22.89	18.88	41.77	46.00	-4.23	peak			
4	*	500.4500	22.90	21.14	44.04	46.00	-1.96	peak			
5	!	519.8500	19.47	21.67	41.14	46.00	-4.86	peak			
6	!	742.9500	14.20	26.43	40.63	46.00	-5.37	peak			

RESULT: PASS



RADIATED EMISSION TEST- (30MHZ-1GHZ) -VERTICAL



No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1	*	68.8000	34.88	4.73	39.61	40.00	-0.39	peak			
2	!	148.0167	27.62	15.25	42.87	43.50	-0.63	peak			
3	!	249.8667	31.14	13.89	45.03	46.00	-0.97	peak			
4	!	333.9333	25.53	17.67	43.20	46.00	-2.80	peak			
5	!	371.1167	24.76	18.88	43.64	46.00	-2.36	peak			
6	!	519.8500	20.19	21.67	41.86	46.00	-4.14	peak			

RESULT: PASS

Note: 1. Factor=Antenna Factor + Cable loss, Margin=Measurement-Limit.

2. The “Factor” value can be calculated automatically by software of measurement system.

3. All test modes for different EUT are pre-tested. The low channel for GFSK mode is the worst case and recorded in the report.

**RADIATED EMISSION ABOVE 1GHZ**

Frequency	Emission Level	Limits	Margin	Detector	Comment
(MHz)	(dBμV/m)	(dBμV/m)	(dB)	Type	
Low Channel (2402 MHz)					
4804	51.6	74	-22.4	Pk	Vertical
4804	39.05	54	-14.95	AV	Vertical
4804	51.56	74	-22.44	Pk	Horizontal
4804	38.54	54	-15.46	AV	Horizontal
Mid Channel (2440 MHz)					
4880	51.8	74	-22.2	Pk	Vertical
4880	39.22	54	-14.78	AV	Vertical
4880	51.75	74	-22.25	Pk	Horizontal
4880	38.73	54	-15.27	AV	Horizontal
High Channel (2480 MHz)					
4960	51.95	74	-22.05	pk	Vertical
4960	39.42	54	-14.58	AV	Vertical
4960	51.93	74	-22.07	pk	Horizontal
4960	38.92	54	-15.08	AV	Horizontal

RESULT: PASS

Note: 1~25GHz scan with GFSK. No recording in the test report at least have 20dB margin.

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

Emission Level = Meter Reading + Factor

Margin = Emission - Level Limit



7. BAND EDGE EMISSION

7.1. MEASUREMENT PROCEDURE

1) Radiated restricted band edge measurements

The radiated restricted band edge measurements are measured with an EMI test receiver connected to the receive antenna while the EUT is transmitting

2) Conducted Emissions at the bang edge

a) The transmitter output was connected to the spectrum analyzer


b) Set RBW=100kHz, VBW=300kHz

c) Suitable frequency span including 100kHz bandwidth from band edge

7.2. TEST SET-UP

Radiated same as 6.2

Conducted set up



**7.3. RADIATED TEST RESULT**

Frequency	Emission Level	Limits	Margin	Detector	Comment
(MHz)	(dBμV/m)	(dBμV/m)	(dB)	Type	
GFSK					
2399.9	52.43	74	-21.57	peak	Vertical
2399.9	39.42	54	-14.58	AVG	Vertical
2399.9	52.83	74	-21.17	peak	Horizontal
2399.9	39.27	54	-14.73	AVG	Horizontal
2483.6	52.34	74	-21.66	peak	Vertical
2483.6	39.35	54	-14.65	AVG	Vertical
2483.6	53.43	74	-20.57	peak	Horizontal
2483.6	39.78	54	-14.22	AVG	Horizontal

RESULT: PASS

Note: Factor=Antenna Factor + Cable loss - Amplifier gain,

Emission Level = Meter Reading + Factor


Margin= Emission Level -Limit.

The “Factor” value can be calculated automatically by software of measurement system.



8. CONDUCTED TEST RESULT

Test Graph





9. 6DB BANDWIDTH


9.1. TEST PROCEDURE

1. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
2. Set the EUT Work on the top, the middle and the bottom operation frequency individually.
3. Set SPA Centre Frequency = Operation Frequency, RBW= 100 KHz, VBW $\geq$ RBW.
4. Set SPA Trace 1 Max hold, then View.

9.2. SUMMARY OF TEST RESULTS/PLOTS

Mode	Channel	6dB Bandwidth [KHz]	Verdict
BLE	LCH	707.0	PASS
BLE	MCH	704.0	PASS
BLE	HCH	706.8	PASS

Test Graph






10. CONDUCTED OUTPUT POWER

10.1. MEASUREMENT PROCEDURE

1. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
2. Set the EUT Work on the top, middle and the bottom operation frequency individually.
3. Use the following spectrum analyzer settings:
 - Set the RBW $\geq$ DTS bandwidth
 - Set the VBW $\geq 3 \times$ RBW
 - Set the span $\geq 3 \times$ RBW
 - Detector = peak
 - Sweep time = auto couple
 - Trace mode = max hold
4. Allow the trace to stabilize. Use peak marker function to determine the peak amplitude level
5. Record the result form the Spectrum Analyzer.

Note: The EUT was tested according to KDB 558074 for compliance to FCC 47CFR 15.247 requirements.

10.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)






10.3. LIMITS AND MEASUREMENT RESULT

Channel	Peak Power (dBm)	Applicable Limits (dBm)	Pass/Fail
Low Channel	1.661	30	Pass
Middle Channel	2.210	30	Pass
High Channel	2.276	30	Pass

Test Graph





11. MAXIMUM CONDUCTED OUTPUT POWER SPECTRAL DENSITY


11.1. MEASUREMENT PROCEDURE

(1). Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
(2). Set the EUT Work on the top, the middle and the bottom operation frequency individually.

(3). Set SPA Trace 1 Max hold, then View.

Note: The EUT was tested according to KDB 558074 for compliance to FCC 47CFR 15.247 requirements.

11.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)






11.3. LIMITS AND MEASUREMENT RESULT

Mode	Channel	PSD [dBm/3kHz]	Limit[dBm/3kHz]	Verdict
BLE	LCH	-14.885	8	PASS
BLE	MCH	-13.584	8	PASS
BLE	HCH	-14.614	8	PASS

Test Graph





12. CONDUCTED SPURIOUS EMISSION

12.1. MEASUREMENT PROCEDURE

1. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
2. Set the EUT Work on the top, the Middle and the bottom operation frequency individually.
3. Set the Span = wide enough to capture the peak level of the in-band emission and all spurious emissions from the lowest frequency generated in the EUT up through the 10th harmonic.
RBW = 100 kHz; VBW $\geq$ RBW; Sweep = auto; Detector function = peak.
4. Set SPA Trace 1 Max hold, then View.

Note: The EUT was tested according to DA000705 for compliance to FCC 47CFR 15.247 requirements. Owing to satisfy the requirements of the number of measurement points, we set the RBW=1MHz, VBW $>$ RBW, scan up through 10th harmonic, and consider the tested results as the worst case, if the tested results conform to the requirement, we can deem that the real tested results(set the RBW=100KHz, VBW $>$ RBW) are conform to the requirement.

**12.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)**

The same as described in section 8.2

12.3. MEASUREMENT EQUIPMENT USED


The same as described in section 6


12.4. LIMITS AND MEASUREMENT RESULT

LIMITS AND MEASUREMENT RESULT		
Applicable Limits	Measurement Result	
	Test Data	Criteria
In any 100 KHz Bandwidth Outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produce by the intentional radiator shall be at least 20 dB below that in 100KHz bandwidth within the band that contains the highest level of the desired power. In addition, radiation emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in§15.209(a))	At least -20dBc than the limit Specified on the BOTTOM Channel	PASS
	At least -20dBc than the limit Specified on the TOP Channel	PASS




Test Graph





13. APPENDIX A: PHOTOGRAPHS OF TEST SETUP

RADIATED EMISSION TEST SETUP



RADIATED EMISSION ABOVE 1G TEST SETUP



----END OF REPORT----