



EMF TEST REPORT

Product Name: Sentinel

Model Number: S5

FCC ID: 2AM6L-S5

Issued For : Streamax Technology Co., Ltd.

21-23/F, Building B1, Zhiyuan, No. 1001 Xueyuan Avenue,
Nanshan District, Shenzhen, Guangdong China 518055

Issued By : Shenzhen LGT Test Service Co., Ltd.

Room 205, Building 13, Zone B, Zhenxiong Industrial Park,
No.177, Renmin West Road, Jinsha, Kengzi Street, Pingshan
District, Shenzhen, Guangdong, China

Report Number: LGT26E170HA01

Sample Received Date: May 25, 2026

Date of Test: May 25, 2026 ~ July 31, 2026

Date of Issue: July 31, 2026

The test report is effective only with both signature and specialized stamp. This report shall not be reproduced except in full without the written approval of the Laboratory. The results in this report only apply to the tested sample.



TEST REPORT CERTIFICATION

Applicant: Streamax Technology Co., Ltd.

Address: 21-23/F, Building B1, Zhiyuan, No. 1001 Xueyuan Avenue, Nanshan District, Shenzhen, Guangdong China 518055

Product Name: Sentinel

Trademark: Streamax

Model Number: S5

Sample Status: Normal

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
FCC 47 CFR §2.1091 KDB 447498 D01 General RF Exposure Guidance v06	PASS

Prepared by:

chris chen

Chris Chen
Engineer

Approved by:

V. Ma

Technical Director





TABLE OF CONTENTS

1 . GENERAL INFORMATION	5
1.1 GENERAL DESCRIPTION OF THE EUT	5
1.2 TEST LABORATORY	5
2 . FCC 47CFR § 2.1091 REQUIREMENT	6
2.1 TEST STANDARDS	6
2.2 LIMIT	6
2.3 EUT OPERATION CONDITION	7
2.4 CLASSIFICATION	7
2.5 TEST RESULT	8



Revision History

Rev.	Issue Date	Revisions
00	July 31, 2026	Initial Issue



1. GENERAL INFORMATION

1.1 GENERAL DESCRIPTION OF THE EUT

Product Name:	Sentinel	
Test Model Number:	S5	
Series Number:	N/A	
Model Difference:	N/A	
Frequency Bands:	2.4G WLAN	802.11b/g/n/ax(20MHz): 2412~2462MHz 802.11n/ax(40MHz):2422~2452MHz
	5G WLAN	IEEE 802.11a/n(HT20)/ ac(VHT20): 5.180GHz-5.240GHz IEEE 802.11n(HT40)/ ac(VHT40): 5.190GHz-5.230GHz IEEE 802.11 ac(VHT80): 5.210GHz IEEE 802.11a/n(HT20)/ ac(VHT20): 5.745GHz-5.825GHz IEEE 802.11a/n(HT40)/ac(VHT40): 5.755GHz-5.795GHz IEEE 802.11 ac(VHT80): 5.775GHz
	WCDMA	Band V: 824 MHz ~ 849 MHz Band II: 1850 MHz ~ 1910 MHz Band IV: 1710 MHz ~ 1755 MHz
	LTE	LTE Band 2:1850~1910MHz LTE Band 4:1710~1755MHz LTE Band 5: 824~849MHz LTE Band 12: 699-716MHz LTE Band 13: 777-787MHz LTE Band 14: 788-798 MHz LTE Band 66: 1710-1780MHz LTE Band 71: 663-698MHz
Rating:	Input: DC 9-36V	
Hardware Version:	N/A	
Software Version:	N/A	

1.2 TEST LABORATORY

Company Name:	Shenzhen LGT Test Service Co., Ltd.
Address:	Room 205, Building 13, Zone B, Zhenxiong Industrial Park, No.177, Renmin West Road, Jinsha, Kengzi Street, Pingshan District, Shenzhen, Guangdong, China
Accreditation Certificate:	FCC Registration No.: 746540
	CAB ID: CN0136



2. FCC 47CFR §2.1091 REQUIREMENT

2.1 TEST STANDARDS

The limit for Maximum Permissible Exposure (MPE) specified in FCC 1.1310 is followed. The gain of the antennas used in the product is extracted from the Antenna data sheets provided and also the maximum total power input to the antenna is measured. Through the Friis transmission formula and the maximum gain of the antenna, we can calculate the distance, away from the product, where the limit of MPE is reached.

Although the Friis Transmission formula is far field assumption, the calculated result of that is an over-prediction for near field power density. It is taken as worst case to specify the safety range.

2.2 LIMIT

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environmental impact of the human exposure to radio-frequency (RF) radiation as specified in 1.1307 (b)

Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)
Limits for Occupational / controlled Exposures			
0.3-3.0	614	1.63	*(100)
3.0-30	1842/f	4.89/f	*(900/f ²)
30-300	61.4	0.163	1.0
300 - 1500	--	--	F/300
1500 – 100000	--	--	5.0
Limits for General population / Uncontrolled Exposure			
0.3-1.34	614	1.63	*(100)
1.34-30	824/f	2.19/f	*(180/f ²)
30-300	27.5	0.073	0.2
300 - 1500	--	--	F/1500
1500 – 100000	--	--	1.0

F= Frequency in MHz

* = Plane-wave equivalent power density.

Friss Formula

Friss Transmission Formula: $P_d = (P_{out} * G) / (4 * \pi * r^2)$

Where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = Distance between observation point and the center of radiator in cm

If we know the maximum gain of the antenna and the total output power to the antenna, through calculation, we will know MPE value at distance 20cm.



2.3 EUT OPERATION CONDITION

EUT was enabled to transmit and receive at lowest, middle and highest channels.

2.4 CLASSIFICATION

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. Warning statement to the user for keeping at least 20cm or more separation distance from the antenna should be included in the User manual. So, this device is classified as Mobile device.



2.5 TEST RESULT

Turn up Result

Mode	Turn up Power
WCDMA B2	23±1dBm
WCDMA B4	23.5±1dBm
WCDMA B5	23.5±1dBm
LTE B2	24.5±1dBm
LTE B4	24.5±1dBm
LTE B5	24.5±1dBm
LTE B12	23.5±1dBm
LTE B13	23.5±1dBm
LTE B14	23.5±1dBm
LTE B66	24±1dBm
LTE B71	24±1dBm
2.4G WIFI-802.11b	17±1dBm
2.4G WIFI-802.11g	14±2dBm
2.4G WIFI-802.11n(HT20)	15.5±1dBm
2.4G WIFI-802.11n(HT40)	14±1dBm
2.4G WIFI-802.11ax(SU20)	15±1dBm
2.4G WIFI-802.11ax(SU40)	15±1dBm
5G WIFI-802.11a	13±3dBm
5G WIFI-802.11n(HT20)	12±3dBm
5G WIFI-802.11n(HT40)	12±2dBm
5G WIFI-802.11ac(VHT20)	12±3dBm
5G WIFI-802.11ac(VHT40)	12.5±3dBm
5G WIFI-802.11ac(VHT40)	13±2dBm



The MPE result of worst mode:

RF Function	Max Turn up Power (dBm)	Max Turn up Power (mW)	ANT Gain (dBi)	ANT Gain (gain of antenna in linear scale)	Power Density (mW/cm ²)	Limit (mW/cm ²)	Ratio	Result
2.4G WIFI	16.00	39.81	2.9	1.95	0.015	1	0.015	Pass
5G WIFI	14.50	28.18	4.3	2.69	0.015	1	0.015	Pass

RF Function	Max Turn up Power (dBm)	Duty cycle factor	Max Power (dBm)	Max Power (mW)	ANT Gain (dBi)	ANT Gain (gain of antenna in linear scale)	Power Density (mW/cm ²)	Limit (mW/cm ²)	Ratio	Result
WCDMA Band 2	24	0	24	251.19	0	1.00	0.050	1.000	0.050	Pass
WCDMA Band 4	24.5	0	24.5	281.84	0	1.00	0.056	1.000	0.056	Pass
WCDMA Band 5	24.5	0	24.5	281.84	0	1.00	0.056	0.549	0.102	Pass
LTE Band 2	25.5	0	25.5	354.81	0	1.00	0.071	1.000	0.071	Pass
LTE Band 4	24.5	0	24.5	281.84	0	1.00	0.056	1.000	0.056	Pass
LTE Band 5	25.5	0	25.5	354.81	0	1.00	0.071	0.549	0.128	Pass
LTE Band 12	24.5	0	24.5	281.84	0	1.00	0.056	0.466	0.120	Pass
LTE Band 13	24.5	0	24.5	281.84	0	1.00	0.056	0.518	0.108	Pass
LTE Band 14	24.5	0	24.5	281.84	0	1.00	0.056	0.525	0.107	Pass
LTE Band 66	25	-1.99	23.0	200.17	0	1.00	0.040	1.000	0.040	Pass
LTE Band 71	25	-1.99	23.0	200.17	0	1.00	0.040	0.442	0.090	Pass

Multiple transmission: 2.4G WIFI+LTE Band 5=0.015+0.128=0.143 < 1

Note:

1. The RF Exposure is less than the limit, complies with the exemption requirements.

※※※※※END OF THE REPORT※※※※※