

TEST REPORT

Applicant: Fujian Newland Payment Technology Co.,Ltd.

Address: No. B602, Building #1, Haixia Jingmao Plaza, Fuzhou Bonded Area
350015, Fuzhou, Fujian, China

Product Name: POS Terminal

FCC ID: 2AM6U-NAS3G001

IC: 25226-NAS3G001

HVIN: S3_33_30_01_01, S3_33_31_01_01, S3_73_30_01_01

47 CFR Part 2, 47 CFR Part 22, Subpart H
47 CFR Part 24, Subpart E, 47 CFR Part 27, 47 CFR Part 90
RSS-130 Issue 2, February 2019
RSS-132 Issue 4, January 31, 2023
RSS-133 Issue 7, July 24, 2024
Standard(s): RSS-139 Issue 4, Amendment October, 2022*
RSS-140 Issue 1 April 2018
RSS-199 Issue 4, July 2023
RSS-Gen, Issue 5, February 2021 Amendment 2
ANSI C63.26-2015

Report Number: 2602R50571E-RF-00E

Report Date: 2026/4/28

The above device has been tested and found compliant with the requirement of the relevant standards by Bay Area Compliance Laboratories Corp. (Dongguan).

Alice Tan

Reviewed By: Alice Tan

Title: RF Engineer

Pedro Yun

Approved By: Pedro Yun

Title: RF Supervisor

Bay Area Compliance Laboratories Corp. (Dongguan)
No.12, Pulong East 1st Road, Tangxia Town, Dongguan, Guangdong, China

Tel: +86-769-86858888

Fax: +86-769-86858891

www.baclcorp.com.cn

Note: The information marked ▲ is provided by the applicant, the laboratory is not responsible for its authenticity and this information can affect the validity of the result in the test report. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This report cannot be reproduced except in full, without prior written approval of the Company. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0. This report may contain data that are not covered by the accreditation scope and shall be marked with ★. This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the U.S. Government. Each test item follows the test standard(s) without deviation.

CONTENTS

DOCUMENT REVISION HISTORY	4
1. GENERAL INFORMATION	5
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	5
1.2 ACCESSORY INFORMATION	5
1.3 OPERATION VOLTAGE (V_{DC}) [▲]	5
1.4 TRANSMISSION ANTENNA INFORMATION▲	6
1.5 EQUIPMENT MODIFICATIONS	6
2. SUMMARY OF TEST RESULTS	7
3. DESCRIPTION OF TEST CONFIGURATION	14
3.1 EUT OPERATION CONDITION:	14
3.2 SUPPORT EQUIPMENT LIST AND DETAILS	17
3.3 SUPPORT CABLE LIST AND DETAILS	18
3.4 BLOCK DIAGRAM OF TEST SETUP.....	19
3.5 TEST FACILITY	20
3.6 MEASUREMENT UNCERTAINTY	20
4. REQUIREMENTS AND TEST PROCEDURES	21
4.1 TRANSMITTER OUTPUT POWER AND EQUIVALENT RADIATED POWER:.....	21
4.1.1 Applicable Standard	21
4.1.2 Test Setup Block	25
4.1.3 Test Procedure	25
4.1.4 Test Results	25
4.2 TRANSMITTER UNWANTED EMISSIONS-RADIATED SPURIOUS EMISSIONS:	26
4.2.1 Applicable Standard	26
4.2.2 Test setup	31
4.2.3 Test Procedure	32
4.2.4 Test Results	33
4.3 FREQUENCY SUB-BANDS	34
4.3.1 Applicable Standard	34
4.3.2 Judgment	34
4.4 BAND PLAN	34
4.4.1 Applicable Standard	34
4.4.2 Judgment	36
4.5 TYPES OF MODULATION	36
4.5.1 Applicable Standard	36
4.5.2 Judgment	37
4.6 FREQUENCY BLOCK.....	37
4.6.1 Applicable Standard	37
4.6.2 Judgment	37
4.7 ADDITIONAL REQUIREMENTS FOR SUBSCRIBER EQUIPMENT.....	37
4.7.1 Applicable Standard	37

4.7.2 Judgment 37

4.8 INTEROPERABILITY REQUIREMENT 37

4.8.1 Applicable Standard 37

4.8.2 Judgment 37

5. Test DATA AND RESULTS 38

5.1 SPOT CHECK WITH MAXIMUM CONDUCTED OUTPUT POWER 38

5.2 EIRP/ERP CALCULATED AND RESULTS 40

5.3 RADIATED SPURIOUS EMISSIONS 45

EXHIBIT A - EUT PHOTOGRAPHS 59

EXHIBIT B - TEST SETUP PHOTOGRAPHS 60

DOCUMENT REVISION HISTORY

Revision Number	Report Number	Description of Revision	Date of Revision
1.0	2602R50571E-RF-00E	Original Report	2026/4/28

1. GENERAL INFORMATION

1.1 Product Description for Equipment under Test (EUT)

EUT Name:	POS Terminal
EUT Model:	S30
Operation Bands and modes:	LTE: Band 2/4/5/7/12/13/14/17/25/26/41/66/71
Modulation Type:	QPSK, 16QAM
Rated Input Voltage:	3.8Vdc from battery or 5.0Vdc from Adapter or 5.0Vdc from Base
Serial Number:	For Radiated Spurious Emissions Below 1G tests: 3J9F-3(Configuration 2#) For Radiated Spurious Emissions Above 1G test: 3J9F-1(Configuration 1#) For RF Conducted Test: 3J9F-6 (Configuration 1#)
EUT Received Date:	2026/4/3
EUT Received Status:	Good
Note: Per 15B&ICES 003 Issue 7 report, Configuration 2#+ Adapter 3# was the worst for AC Line Conducted Emissions, Configuration 2#+ Adapter 3#+Base was the worst for Radiated Spurious Emissions Below 1G, and Configuration 1#+ Adapter 1# was the worst for Radiated Spurious Emissions Above 1G so only performed it this report.	

Configuration Information:

Configuration	HVIN	MIC	ESIM
Configuration 1#	S3_33_31_01_01	√	×
Configuration 2#	S3_33_30_01_01	×	×
Configuration 3#	S3_73_30_01_01	×	√

1.2 Accessory Information

Accessory Description	Manufacturer	Model	Parameters
Adapter 1#	SHENZHEN HONOR ELECTRONIC CO.,LTD.	ADS-12B-06 05010E	Input: 100-240Vac 50/60Hz MAX 0.3A Output: 5.0Vdc 2.0A 10.0W
Adapter 2#	SHENZHEN HONOR ELECTRONIC CO.,LTD.	ADS-12EA-05 05010E	Input: 100-240Vac, 50/60Hz; Max 0.3A Output: 5.0Vdc 2.0A 10.0W
Adapter 3#	XIAMEN KELI ELECTRONICS CO.,LTD	KL-WD050200	Input: 100-240Vac 50/60Hz 0.5A Output: 5.0Vdc 2.0A 10.0W

1.3 Operation Voltage (V_{DC})[▲]

Lowest:	3.5	Normal:	3.8	Highest:	4.35
---------	-----	---------	-----	----------	------

1.4 Transmission Antenna Information ▲

Antenna	Antenna Type	Operation Bands	Antenna Frequency Range (MHz)	Antenna Gain (Gr) (dBi)	Lc (dB)
Main	FPC	LTE B2	1850-1910	-5.01	0
		LTE B4	1710-1755	-4.58	0
		LTE B5	824-849	-5.14	0
		LTE B7	2500-2570	-4.47	0
		LTE B12	699-716	-7.81	0
		LTE B13	777-787	-7.61	0
		LTE B14	788-798	-7.91	0
		LTE B17	704-716	-7.87	0
		LTE B25	1850-1915	-5.01	0
		LTE B26	814-824	-5.67	0
		LTE B26	824-849	-5.14	0
		LTE B41	2496-2690	-4.47	0
		LTE B66	1710-1780	-4.58	0
		LTE B71	663-698	-7.81	0
Note: 1.IC does not support LTE B26(814-824), the frequency range of IC's LTE B41 is 2500-2690MHz. 2.Lc= Signal Attenuation in the connecting cable between the transmitter and antenna, in dB.					

1.5 Equipment Modifications

No modifications are made to the EUT during all test items.

2. SUMMARY OF TEST RESULTS

Cellular Band: LTE Band 5/ LTE Band 26(824-849MHz):

FCC Standard Rule(s)	ISED Standard Rule(s)	Description of Test	Result	Note
/	RSS-132 Clause 5.1	Frequency Sub-bands	Compliant	Please refer to section 4.3.2
/	RSS-132 Clause 5.2	Types of Modulation	Compliant	Please refer to section 4.5.2
§ 2.1055, § 22.355	RSS-132 Clause 5.3	Frequency stability	Compliant*	The test result please refer to report PD20240152-R3A [▲] ANNEEX A.3 page 26 & ANNEEX A.11 page 35 for FCC and PD20240152-R4A [▲] ANNEEX A.3 page 26& ANNEEX A.10 page 35 for IC
§2.1046; § 22.913	RSS-132 Clause 5.4	Transmitter output power and effective radiated power (e.r.p.)	Reporting	The test result please refer to report PD20240152-R3A [▲] ANNEEX A.3 page1-5& ANNEEX A.11 page1-8 for FCC and PD20240152-R4A [▲] ANNEEX A.3 page1-5& ANNEEX A.10 page1-8 for IC
§ 2.1051, § 22.917 (a)	RSS-132 Clause 5.5	Transmitter unwanted emissions- at Antenna Terminal	Compliant*	The test result please refer to report PD20240152-R3A [▲] ANNEEX A.3 page 11-25& ANNEEX A.11 page 16-34 for FCC and PD20240152-R4A [▲] ANNEEX A.3 page 11-25& ANNEEX A.10 page 16-34 for IC
§ 22.917 (a)	RSS-132 Clause 5.5	Transmitter unwanted emissions- Out of band emission	Compliant*	The test result please refer to report PD20240152-R3A [▲] ANNEEX A.3 page 8-10& ANNEEX A.11 page 12-15 for FCC and PD20240152-R4A [▲] ANNEEX A.3 page 8-10& ANNEEX A.10 page 12-15 for IC
§ 2.1053, § 22.917 (a)	RSS-132 Clause 5.5	Transmitter unwanted emissions- Radiated Spurious emissions	Compliant	Please refer to section 5.3
§ 2.1049; § 22.905	RSS-Gen Clause 6.7	Occupied Bandwidth	Compliant*	The test result please refer to report PD20240152-R3A [▲] ANNEEX A.3 page 6-7& ANNEEX A.11 page 9-11 for FCC and PD20240152-R4A [▲] ANNEEX A.3 page 6-7& ANNEEX A.10 page 9-11 for IC

PCS Band: LTE Band 2/ LTE Band 25:

FCC Standard Rule(s)	ISED Standard Rule(s)	Description of Test	Result	Note
/	RSS-133 Clause 5.2	Band plan	Compliant	Please refer to section 4.4.2
/	RSS-133 Clause 5.3	Types of Modulation	Compliant	Please refer to section 4.5.2
§ 2.1055, § 24.235	RSS-133 Clause 5.4	Frequency stability	Compliant*	The test result please refer to report PD20240152-R3A [▲] ANNEEX A.1 page 39& ANNEEX A.9 page 39 for FCC and PD20240152-R4A [▲] ANNEEX A.1 page 39& ANNEEX A.9 page 39 for IC
§2.1046, § 24.232	RSS-133 Clause 5.5	Transmitter output power	Reporting	The test result please refer to report PD20240152-R3A [▲] ANNEEX A.1 page 1-7& ANNEEX A.9 page 1-7 for FCC and PD20240152-R4A [▲] ANNEEX A.1 page 1-7& ANNEEX A.9 page 1-7 for IC
§ 2.1051, § 24.238 (a)	RSS-133 Clause 5.6	Transmitter unwanted emissions- at Antenna Terminal	Compliant*	The test result please refer to report PD20240152-R3A [▲] ANNEEX A.1 page 16-38& ANNEEX A.9 page 16-38 for FCC and PD20240152-R4A [▲] ANNEEX A.1 page 16-38& ANNEEX A.9 page 16-38 for IC
§ 24.238 (a)	RSS-133 Clause 5.6	Transmitter unwanted emissions- Out of band emission	Compliant*	The test result please refer to report PD20240152-R3A [▲] ANNEEX A.1 page 11-15& ANNEEX A.9 page 11-15 for FCC and PD20240152-R4A [▲] ANNEEX A.1 page 11-15& ANNEEX A.9 page 11-15 for IC
§ 2.1053, § 24.238 (a)	RSS-133 Clause 5.6	Transmitter unwanted emissions- Radiated Spurious emissions	Compliant	Please refer to section 5.3
§ 2.1049, § 24.238	RSS-Gen Clause 6.7	Occupied Bandwidth	Compliant*	The test result please refer to report PD20240152-R3A [▲] ANNEEX A.1 page 8-10& ANNEEX A.9 page 8-10 for FCC and PD20240152-R4A [▲] ANNEEX A.1 page 8-10& ANNEEX A.9 page 8-10 for IC

LTE Band 26(814-824MHz):

FCC Standard Rule(s)	ISED Standard Rule(s)	Description of Test	Result	Note
§90.213	/	Frequency stability	Compliant*	The test result please refer to report PD20240152-R3A [▲] ANNEEX A.10 page 25 for FCC
§2.1046; §90.635	/	Transmitter output power and effective radiated power (e.r.p.)	Reporting	The test result please refer to report PD20240152-R3A [▲] ANNEEX A.10 page 1-6 for FCC
§ 2.1051, §90.691	/	Transmitter unwanted emissions- at Antenna Terminal	Compliant*	The test result please refer to report PD20240152-R3A [▲] ANNEEX A.10 page 12-24 for FCC
§90.691	/	Transmitter unwanted emissions- Out of band emission	Compliant*	The test result please refer to report PD20240152-R3A [▲] ANNEEX A.10 page 9-11 for FCC
§ 2.1053, §90.691	/	Transmitter unwanted emissions- Radiated Spurious emissions	Compliant	Please refer to section 5.3
§ 2.1049; §90.209	/	Occupied Bandwidth	Compliant*	The test result please refer to report PD20240152-R3A [▲] ANNEEX A.10 page 7-8 for FCC

AWS Band: LTE Band 4/LTE B66:

FCC Standard Rule(s)	ISED Standard Rule(s)	Description of Test	Result	Note
/	RSS-139 Clause 5.2	Band Plan	Compliant	Please refer to section 4.4.2
/	RSS-139 Clause 5.3	Types of Modulation	Compliant	Please refer to section 4.5.2
/	RSS-139 Clause 5.7	Additional Requirements for Subscriber Equipment	Compliant	Please refer to section 4.7.2
§ 2.1055	RSS-139 Clause 5.4	Frequency stability	Compliant*	The test result please refer to report PD20240152-R3A [▲] ANNEEX A.2 page 48& ANNEEX A.13 page 39 for FCC and PD20240152-R4A [▲] ANNEEX A.2 page 48& ANNEEX A.12 page 39 for IC
FCC§2.1046, §27.50	RSS-139 Clause 5.5	Transmitter Output Power	Reporting	The test result please refer to report PD20240152-R3A [▲] ANNEEX A.2 page 1-7& ANNEEX A.13 page 1-7 for FCC and PD20240152-R4A [▲] ANNEEX A.2 page 1-7& ANNEEX A.12 page 1-7 for IC
FCC§ 2.1051, §27.53	RSS-139 Clause 5.6	Transmitter unwanted emissions- at Antenna Terminal	Compliant*	The test result please refer to report PD20240152-R3A [▲] ANNEEX A.2 page 16-47& ANNEEX A.13 page 16-38 for FCC and PD20240152-R4A [▲] ANNEEX A.2 page 16-47& ANNEEX A.12 page 16-38 for IC
§27.53	RSS-139 Clause 5.6	Transmitter unwanted emissions- Bandedge	Compliant*	The test result please refer to report PD20240152-R3A [▲] ANNEEX A.2 page 11-15& ANNEEX A.13 page 11-15 for FCC and PD20240152-R4A [▲] ANNEEX A.2 page 11-15& ANNEEX A.12 page 11-15 for IC
§ 2.1053, §27.53	RSS-139 Clause 5.6	Transmitter unwanted emissions- Radiated Spurious emissions	Compliant	Please refer to section 5.3
§ 2.1049, §27.53	RSS-Gen Clause 6.7	Occupied Bandwidth	Compliant*	The test result please refer to report PD20240152-R3A [▲] ANNEEX A.2 page 8-10& ANNEEX A.13 page 8-10 for FCC and PD20240152-R4A [▲] ANNEEX A.2 page 8-10& ANNEEX A.12 page 8-10 for IC

BRS/EBS Band: LTE Band 7/LTE Band 41:

FCC Standard Rule(s)	ISED Standard Rule(s)	Description of Test	Result	Note
/	RSS-199 Clause 5.2	Frequency Plan	Compliant	Please refer to section 4.4.2
/	RSS-199 Clause 5.3	Types of Modulation	Compliant	Please refer to section 4.5.2
§ 2.1055	RSS-199 Clause 5.4	Frequency stability	Compliant*	The test result please refer to report PD20240152-R3A [▲] ANNEEX A.4 page 26& ANNEEX A.12 page 26 for FCC and PD20240152-R4A [▲] ANNEEX A.4 page 26& ANNEEX A.11 page 19 for IC
FCC§2.1046, §27.50	RSS-199 Clause 5.5	Transmitter Output Power and Equivalent Isotropically Radiated Power	Reporting	The test result please refer to report PD20240152-R3A [▲] ANNEEX A.4 page 1-5& ANNEEX A.12 page 1-5 for FCC and PD20240152-R4A [▲] ANNEEX A.4 page 1-5& ANNEEX A.11 page 1-5 for IC
FCC§ 2.1051, §27.53	RSS-199 Clause 5.6	Transmitter unwanted emissions- at Antenna Terminal	Compliant*	The test result please refer to report PD20240152-R3A [▲] ANNEEX A.4 page 11-25& ANNEEX A.12 page 11-25 for FCC and PD20240152-R4A [▲] ANNEEX A.4 page 11-25& ANNEEX A.11 page 11-18 for IC
§27.53	RSS-199 Clause 5.6	Transmitter unwanted emissions- Out of band emission	Compliant*	The test result please refer to report PD20240152-R3A [▲] ANNEEX A.4 page 8-10& ANNEEX A.12 page 8-10 for FCC and PD20240152-R4A [▲] ANNEEX A.4 page 8-10& ANNEEX A.11 page 8-10 for IC
§ 2.1053, §27.53	RSS-199 Clause 5.6	Transmitter unwanted emissions- Radiated Spurious emissions	Compliant	Please refer to section 5.3
§ 2.1049, §27.53	RSS-Gen Clause 6.7	Occupied Bandwidth	Compliant*	The test result please refer to report PD20240152-R3A [▲] ANNEEX A.4 page 6-7& ANNEEX A.12 page 6-7 for FCC and PD20240152-R4A [▲] ANNEEX A.4 page 6-7& ANNEEX A.11 page 6-7 for IC

LTE Band 12/13/17/71:

FCC Standard Rule(s)	ISED Standard Rule(s)	Description of Test	Result	Note
/	RSS-130 Clause 4.2	Types of modulation	Compliant	Please refer to section 4.5.2
/	RSS-130 Clause 4.3	Frequency block	Compliant	Please refer to section 4.6.2
/	RSS-130 Clause 4.4	Interoperability requirement	Compliant	Please refer to section 4.8.2
§ 2.1055	RSS-130 Clause 4.5	Transmitter frequency stability	Compliant*	The test result please refer to report PD20240152-R3A [▲] ANNEEX A.5 page 26& ANNEEX A.6 page 14& ANNEEX A.8 page 17 & ANNEEX A.14 page 26 for FCC and PD20240152-R4A [▲] ANNEEX A.5 page 26& ANNEEX A.6 page 14& ANNEEX A.8 page 17& ANNEEX A.13 page 19 for IC
§2.1046, §27.50	RSS-130 Clause 4.6	Transmitter output power and effective radiated power (e.r.p.)	Reporting	The test result please refer to report PD20240152-R3A [▲] ANNEEX A.5 page 1-5 & ANNEEX A.6 page 1-3& ANNEEX A.8 page 1-4 & ANNEEX A.14 page 1-5 for FCC and PD20240152-R4A [▲] ANNEEX A.5 page 1-5& ANNEEX A.6 page 1-3& ANNEEX A.8 page 1-4& ANNEEX A.13 page 1-5 for IC
§ 2.1051, §27.53	RSS-130 Clause 4.7	Transmitter unwanted emissions- at Antenna Terminal	Compliant*	The test result please refer to report PD20240152-R3A [▲] ANNEEX A.5 page 11-25& ANNEEX A.6 page 8-13& ANNEEX A.8 page 9-16& ANNEEX A.14 page 11-25 for FCC and PD20240152-R4A [▲] ANNEEX A.5 page 11-25&ANNEEX A.6 page 8-13& ANNEEX A.8 page 9-16& ANNEEX A.13 page 11-18 for IC
§27.53	RSS-130 Clause 4.7	Transmitter unwanted emissions- Out of band emission	Compliant*	The test result please refer to report PD20240152-R3A [▲] ANNEEX A.5 page 8-10 & ANNEEX A.6 page 6-7& ANNEEX A.8 page 7-8& ANNEEX A.14 page 8-10 for FCC and PD20240152-R4A [▲] ANNEEX A.5 page 8-10& ANNEEX A.6 page 6-7& ANNEEX A.8 page 7-8& ANNEEX A.13 page 8-10 for IC
§ 2.1053, §27.53	RSS-130 Clause 4.7	Transmitter unwanted emissions- Radiated Spurious emissions	Compliant	Please refer to section 5.3
§ 2.1049, §27.53	RSS-Gen Clause 6.7	Occupied Bandwidth	Compliant*	The test result please refer to report PD20240152-R3A [▲] ANNEEX A.5 page 6-7 & ANNEEX A.6 page 4-5& ANNEEX A.8 page 5-6& ANNEEX A.14 page 6-7 for FCC and PD20240152-R4A [▲] ANNEEX A.5 page 6-7&ANNEEX A.6 page 4-5&ANNEEX A.8 page 5-6& ANNEEX A.13 page 6-7 for IC

LTE Band 14:

FCC Standard Rule(s)	ISED Standard Rule(s)	Description of Test	Result	Note
/	RSS-140 Clause 4.1	Types of modulation	Compliant	Please refer to section 4.5.2
§90.531	/	Band plan	Compliant	Please refer to section 4.4.2
§ 2.1055, §90.213	RSS-140 Clause 4.2	Transmitter frequency stability	Compliant*	The test result please refer to report PD20240152-R3A [▲] ANNEEX A.7 page 24 for FCC and PD20240152-R4A [▲] ANNEEX A.7 page 13 for IC
§2.1046, §90.542	RSS-140 Clause 4.3	Transmitter output power and effective radiated power (e.r.p.)	Reporting	The test result please refer to report PD20240152-R3A [▲] ANNEEX A.7 page 1-3 for FCC and PD20240152-R4A [▲] ANNEEX A.7 page 1-3 for IC
§ 2.1051, §90.543	RSS-140 Clause 4.4	Transmitter unwanted emissions- at Antenna Terminal	Compliant*	The test result please refer to report PD20240152-R3A [▲] ANNEEX A.7 page 19-23 for FCC and PD20240152-R4A [▲] ANNEEX A.7 page 8-12 for IC
§90.543	RSS-140 Clause 4.4	Transmitter unwanted emissions- Out of band emission	Compliant*	The test result please refer to report PD20240152-R3A [▲] ANNEEX A.7 page 6-18 for FCC and PD20240152-R4A [▲] ANNEEX A.7 page 6-7 for IC
§ 2.1053, §90.543	RSS-140 Clause 4.4	Transmitter unwanted emissions- Radiated Spurious emissions	Compliant	Please refer to section 5.3
§ 2.1049, §90.543	RSS-Gen Clause 6.7	Occupied Bandwidth	Compliant*	The test result please refer to report PD20240152-R3A [▲] ANNEEX A.7 page 4-5 for FCC and PD20240152-R4A [▲] ANNEEX A.7 page 4-5 for IC

Note 1:

Compliant*: The device built in a certified module, model: SC200E-NA, FCC ID: XMR2024SC200ENA, IC: 10224A-024SC200ENA, per spot check, the RF parameters are identical with the original module report, therefore, the RF conducted test items please refer to the module FCC report: PD20240152-R3A[▲] and IC report: PD20240152-R4A[▲], which was issued by Hefei Panwin Technology Co., Ltd. on 2025/02/06 for FCC and 2025/02/06 for IC. (according to KDB 996369 D02 Module Q&A v02r02, Answer 1 b))

The Bay Area Compliance Laboratories Corp.(Dongguan) is responsible for all the information provided in this report, except when information is provided by the customer as identified in this report.

3. DESCRIPTION OF TEST CONFIGURATION

3.1 EUT Operation Condition:

The EUT was configured for testing according to ANSI C63.26-2015.

The test items were performed with the EUT operating at testing mode. The device operates on LTE band 2/4/5/7/12/13/14/17/25/26/41/66/71, test was performed with channels as below table:

Frequency Bands	Bandwidth (MHz)	Test Frequency (MHz)		
		Low	Middle	High
LTE Band 2	1.4	1850.7	1880	1909.3
	3	1851.5	1880	1908.5
	5	1852.5	1880	1907.5
	10	1855	1880	1905
	15	1857.5	1880	1902.5
	20	1860	1880	1900
LTE Band 4	1.4	1710.7	1732.5	1754.3
	3	1711.5	1732.5	1753.5
	5	1712.5	1732.5	1752.5
	10	1715	1732.5	1750
	15	1717.5	1732.5	1747.5
	20	1720	1732.5	1745
LTE Band 5	1.4	824.7	836.5	848.3
	3	825.5	836.5	847.5
	5	826.5	836.5	846.5
	10	829	836.5	844
LTE Band 7	5	2502.5	2535	2567.5
	10	2505	2535	2565
	15	2507.5	2535	2562.5
	20	2510	2535	2560
LTE Band 12	1.4	699.7	707.5	715.3
	3	700.5	707.5	714.5
	5	701.5	707.5	713.5
	10	704	707.5	711
LTE Band 13	5	779.5	/	784.5
	10	/	782	/
LTE Band 14	5	790.5	/	795.5
	10	/	793	/
LTE Band 17	5	706.5	710	713.5
	10	709	710	711
LTE Band 25	1.4	1850.7	1882.5	1914.3
	3	1851.5	1882.5	1913.5
	5	1852.5	1882.5	1912.5
	10	1855	1882.5	1910
	15	1857.5	1882.5	1907.5
	20	1860	1882.5	1905

Frequency Bands	Bandwidth (MHz)	Test Frequency (MHz)		
		Low	Middle	High
LTE Band 26 (814-824MHz) (only for FCC)	1.4	814.7	819	823.3
	3	815.5	819	822.5
	5	816.5	819	821.5
	10	/	819	/
LTE Band 26 (824-849MHz)	1.4	824.7	836.5	848.3
	3	825.5	836.5	847.5
	5	826.5	836.5	846.5
	10	829	836.5	844
	15	831.5	836.5	841.5
LTE Band 41 (2496-2690MHz) (For FCC)	5	2498.5	2593	2687.5
	10	2501	2593	2685
	15	2503.5	2593	2682.5
	20	2506	2593	2680
LTE Band 41 (2500-2690MHz) (For IC)	5	2502.5	2595	2687.5
	10	2505	2595	2685
	15	2507.5	2595	2682.5
	20	2510	2595	2680
LTE Band 66	1.4	1710.7	1745	1779.3
	3	1711.5	1745	1778.5
	5	1712.5	1745	1777.5
	10	1715	1745	1775
	15	1717.5	1745	1772.5
	20	1720	1745	1770
LTE Band 71	5	665.5	680.5	695.5
	10	668	680.5	693
	15	670.5	680.5	690.5
	20	673	680.5	688

The maximum power was configured per 3GPP Standard for each operation modes as below setting:

LTE (FDD):

The following tests were conducted according to the test requirements in 3GPP TS36.101

The following tests were conducted according to the test requirements outlined in section 6.2 of the 3GPP TS36.101 specification.

UE Power Class: 3 (23 +/- 2dBm). The allowed Maximum Power Reduction (MPR) for the maximum output power due to higher order modulation and transmit bandwidth configuration (resource blocks) is specified in Table 6.2.3-1 of the 3GPP TS36.101.

Table 6.2.3-1: Maximum Power Reduction (MPR) for Power Class 3

Modulation	Channel bandwidth / Transmission bandwidth (RB)						MPR (dB)
	1.4 MHz	3.0 MHz	5 MHz	10 MHz	15 MHz	20 MHz	
QPSK	> 5	> 4	> 8	> 12	> 16	> 18	≤ 1
16 QAM	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	≤ 1
64 QAM	> 5	> 4	> 8	> 12	> 16	> 18	≤ 2

The allowed A-MPR values specified below in Table 6.2.4.-1 of 3GPP TS36.101 are in addition to the allowed MPR requirements. All the measurements below were performed with A-MPR disabled, by using Network Signaling Value of "NS_01".

Table 6.2.4-1: Additional Maximum Power Reduction (A-MPR)

Network Signalling value	Requirements (sub-clause)	E-UTRA Band	Channel bandwidth (MHz)	Resources Blocks (N_{RB})	A-MPR (dB)
NS_01	6.6.2.1.1	Table 5.5-1	1.4, 3, 5, 10, 15, 20	Table 5.6-1	NA
NS_03	6.6.2.2.1	2, 4, 10, 23, 25, 35, 36	3	>5	≤ 1
			5	>6	≤ 1
			10	>6	≤ 1
			15	>8	≤ 1
			20	>10	≤ 1
NS_04	6.6.2.2.2	41	5	>6	≤ 1
			10, 15, 20	See Table 6.2.4-4	
NS_05	6.6.3.3.1	1	10, 15, 20	≥ 50	≤ 1
NS_06	6.6.2.2.3	12, 13, 14, 17	1.4, 3, 5, 10	Table 5.6-1	n/a
NS_07	6.6.2.2.3	13	10	Table 6.2.4-2	Table 6.2.4-2
	6.6.3.3.2				
NS_08	6.6.3.3.3	19	10, 15	> 44	≤ 3
NS_09	6.6.3.3.4	21	10, 15	> 40	≤ 1
				> 55	≤ 2
NS_10		20	15, 20	Table 6.2.4-3	Table 6.2.4-3
NS_11	6.6.2.2.1	23 ¹	1.4, 3, 5, 10	Table 6.2.4-5	Table 6.2.4-5
..					
NS_32	-	-	-	-	-

Note 1: Applies to the lower block of Band 23, i.e. a carrier placed in the 2000-2010 MHz region.

LTE(TDD):

Table 4.2-1: Configuration of special subframe (lengths of DwPTS/GP/UpPTS).

Special subframe configuration	Normal cyclic prefix in downlink			Extended cyclic prefix in downlink		
	DwPTS	UpPTS		DwPTS	UpPTS	
		Normal cyclic prefix in uplink	Extended cyclic prefix in uplink		Normal cyclic prefix in uplink	Extended cyclic prefix in uplink
0	$6592 \cdot T_s$	$2192 \cdot T_s$	$2560 \cdot T_s$	$7680 \cdot T_s$	$2192 \cdot T_s$	$2560 \cdot T_s$
1	$19760 \cdot T_s$			$20480 \cdot T_s$		
2	$21952 \cdot T_s$			$23040 \cdot T_s$		
3	$24144 \cdot T_s$			$25600 \cdot T_s$		
4	$26336 \cdot T_s$	$4384 \cdot T_s$	$5120 \cdot T_s$	$7680 \cdot T_s$	$4384 \cdot T_s$	$5120 \cdot T_s$
5	$6592 \cdot T_s$			$20480 \cdot T_s$		
6	$19760 \cdot T_s$			$23040 \cdot T_s$		
7	$21952 \cdot T_s$			$12800 \cdot T_s$		
8	$24144 \cdot T_s$			-	-	-
9	$13168 \cdot T_s$			-	-	-

Table 4.2-2: Uplink-downlink configurations.

Uplink-downlink configuration	Downlink-to-Uplink Switch-point periodicity	Subframe number									
		0	1	2	3	4	5	6	7	8	9
0	5 ms	D	S	U	U	U	D	S	U	U	U
1	5 ms	D	S	U	U	D	D	S	U	U	D
2	5 ms	D	S	U	D	D	D	S	U	D	D
3	10 ms	D	S	U	U	U	D	D	D	D	D
4	10 ms	D	S	U	U	D	D	D	D	D	D
5	10 ms	D	S	U	D	D	D	D	D	D	D
6	5 ms	D	S	U	U	U	D	S	U	U	D

Calculated Duty Cycle

Uplink-Downlink Configuration	Downlink-to-Uplink Switch-point Periodicity	Subframe Number										Calculated Duty Cycle (%)
		0	1	2	3	4	5	6	7	8	9	
0	5 ms	D	S	U	U	U	D	S	U	U	U	63.33
1	5 ms	D	S	U	U	D	D	S	U	U	D	43.33
2	5 ms	D	S	U	D	D	D	S	U	D	D	23.33
3	10 ms	D	S	U	U	U	D	D	D	D	D	31.67
4	10 ms	D	S	U	U	D	D	D	D	D	D	21.67
5	10 ms	D	S	U	D	D	D	D	D	D	D	11.67
6	5 ms	D	S	U	U	U	D	S	U	U	D	53.33

Calculated Duty Cycle = Extended cyclic prefix in uplink $\times (T_s) \times \#$ of S + $\#$ of U

Example for Calculated Duty Cycle for Uplink-Downlink Configuration 0:

Calculated Duty Cycle = $5120 \times [1/(15000 \times 2048)] \times 2 + 6 \text{ ms} = 63.33\%$

where

$T_s = 1/(15000 \times 2048)$ seconds

3.2 Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
Fujian Newland Payment Technology Co.,Ltd.	Base	/	3EJM-1
R&S	Wideband Radio Communication Tester	CMW500	147473
Unknown	Antenna	Unknown	Unknown
/	SIM Card	/	180722

3.3 Support Cable List and Details


Cable Description	Shielding Type	Ferrite Core	Length (m)	From Port	To
DC Cable	no	no	1.2	Adapter	EUT
DC Cable	no	no	1.2	Adapter	Base
Signal Cable	no	no	3.0	Antenna	CMW500

3.4 Block Diagram of Test Setup

Radiated Spurious emissions Below 1G:



Radiated Spurious emissions Above 1G:



3.5 Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Dongguan) to collect test data is located on the No.12, Pulong East 1st Road, Tangxia Town, Dongguan, Guangdong, China.

The lab has been recognized as the FCC accredited lab under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No.: 829273, the FCC Designation No.: CN5044.

The lab has been recognized by Innovation, Science and Economic Development Canada to test to Canadian radio equipment requirements, the CAB identifier: CN0022.

3.6 Measurement Uncertainty

Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty. The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval.

Parameter	Measurement Uncertainty
Occupied Channel Bandwidth	±5 %
RF output power, conducted	±0.55 dB
Power Spectral Density, conducted	±0.55 dB
Unwanted Emissions, radiated	30MHz~1GHz: 5.12 dB, 1GHz~18GHz: 5.61 dB, 18GHz~26.5GHz: 5.33 dB, 26.5GHz~40GHz: 5.33 dB
Unwanted Emissions, conducted	±2.47 dB
Temperature	±1 °C
Humidity	±5%
DC and low frequency voltages	±0.4%
Duty Cycle	1%
RF Frequency	±0.076×10 ⁻⁶

4. REQUIREMENTS AND TEST PROCEDURES

4.1 Transmitter output power and equivalent radiated power:

4.1.1 Applicable Standard

FCC §22.913

(a)(5) The ERP of mobile transmitters and auxiliary test transmitters must not exceed 7watts.

(d) *Power measurement.* Measurement of the ERP of Cellular base transmitters and repeaters must be made using an average power measurement technique. The peak-to-average ratio (PAR) of the transmission must not exceed 13 dB. Power measurements for base transmitters and repeaters must be made in accordance with either of the following:

- (1) A Commission-approved average power technique (see FCC Laboratory's Knowledge Database); or
- (2) For purposes of this section, peak transmit power must be measured over an interval of continuous transmission using instrumentation calibrated in terms of an rmseivalent voltage. The measurement results shall be properly adjusted for any instrument limitations, such as detector response times, limited resolution bandwidth capability when compared to the emission bandwidth, sensitivity, etc., so as to obtain a true peak measurement for the emission in question over the full bandwidth of the channel.

FCC §24.232

(c) Mobile and portable stations are limited to 2 watts EIRP and the equipment must employ a means for limiting power to the minimum necessary for successful communications.

(d) Power measurements for transmissions by stations authorized under this section may be made either in accordance with a Commission-approved average power technique or in compliance with paragraph (e) of this section. In both instances, equipment employed must be authorized in accordance with the provisions of § 24.51. In measuring transmissions in this band using an average power technique, the peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

FCC §27.50

(a)(3) *Mobile and portable stations.*

(i) For mobile and portable stations transmitting in the 2305-2315 MHz band or the 2350-2360 MHz band, the average EIRP must not exceed 50 milliwatts within any 1 megahertz of authorized bandwidth, *except that* for mobile and portable stations compliant with 3GPP LTE standards or another advanced mobile broadband protocol that avoids concentrating energy at the edge of the operating band the average EIRP must not exceed 250 milliwatts within any 5 megahertz of authorized bandwidth but may exceed 50 milliwatts within any 1 megahertz of authorized bandwidth. For mobile and portable stations using time division duplexing (TDD) technology, the duty cycle must not exceed 38 percent in the 2305-2315 MHz and 2350-2360 MHz bands. Mobile and portable stations using FDD technology are restricted to transmitting in the 2305-2315 MHz band. Power averaging shall not include intervals in which the transmitter is off.

(ii) Mobile and portable stations are not permitted to transmit in the 2315-2320 MHz and 2345-2350 MHz bands.

(iii) *Automatic transmit power control.* Mobile and portable stations transmitting in the 2305-2315 MHz band or in the 2350-2360 MHz band must employ automatic transmit power control when operating so the stations operate with the minimum power necessary for successful communications.

(iv) *Prohibition on external vehicle-mounted antennas.* The use of external vehicle-mounted antennas for mobile and portable stations transmitting in the 2305-2315 MHz band or the 2350-2360 MHz band is prohibited.

(b)(10) Portable stations (hand-held devices) transmitting in the 746-757 MHz, 776-788 MHz, and 805-806 MHz bands are limited to 3 watts ERP.

(c)(10) Portable stations (hand-held devices) in the 600 MHz uplink band and the 698-746 MHz band, and fixed and mobile stations in the 600 MHz uplink band are limited to 3 watts ERP.

(d)(4) Fixed, mobile, and portable (hand-held) stations operating in the 1710-1755 MHz band and mobile and portable stations operating in the 1695-1710 MHz and 1755-1780 MHz bands are limited to 1 watt EIRP. Fixed stations operating in the 1710-1755 MHz band are limited to a maximum antenna height of 10 meters above ground. Mobile and portable stations operating in these bands must employ a means for limiting power to the minimum necessary for successful communications.

(h) The following power limits shall apply in the BRS and EBS:

(2) Mobile and other user stations. Mobile stations are limited to 2.0 watts EIRP. All user stations are limited to 2.0 watts transmitter output power.

(k) The following power requirements apply to stations transmitting in the 3450-3550 MHz band:

(3) Mobile devices are limited to 1 Watt (30 dBm) EIRP. Mobile devices operating in these bands must employ a means for limiting power to the minimum necessary for successful communications.

(4) Equipment employed must be authorized in accordance with the provisions of § 27.51. Power measurements for transmissions by stations authorized under this section may be made either in accordance with a Commission-approved average power technique or in compliance with paragraph(k)(5) of this section. In measuring transmissions in this band using an average power technique, the peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

FCC §90.635

(b) The maximum output power of the transmitter for mobile stations is 100 watts (20 dBw).

FCC §90.542

(a) (7) Portable stations (hand-held devices) transmitting in the 758-768 MHz band and the 788-798 MHz band are limited to 3 watts ERP.

RSS-130 clause 4.6.1

The transmitter output power shall be measured in terms of average power. In addition, the peak-to-average power ratio (PAPR) of the transmitter shall not exceed 13 dB for more than 0.1% of the time and shall use a signal corresponding to the highest PAPR during periods of continuous transmission.

RSS-130 clause 4.6.2 Frequency bands 617-652 MHz and 663-698 MHz

The e.r.p. shall not exceed 3 watts for mobile equipment, fixed subscriber equipment and portable equipment.

For base and fixed equipment other than fixed subscriber equipment, refer to SRSP-518 for the equivalent isotropically radiated power (e.i.r.p.) limits.

RSS-130 clause 4.6.3 Frequency bands 698-756 MHz and 777-787 MHz

The e.r.p. shall not exceed 30 watts for mobile equipment and outdoor fixed subscriber equipment. The e.r.p. shall not exceed 3 watts for portable equipment and indoor fixed subscriber equipment.

For base and fixed equipment other than fixed subscriber equipment, refer to SRSP-518 for the e.i.r.p. limits.

RSS-132 clause 5.4

The transmitter output power shall be measured in terms of average power. The equivalent radiated power (e.r.p.) shall not exceed 7 watts for mobile equipment and 3 watts for portable equipment.

The effective isotropic radiated power (e.i.r.p.) shall not exceed the limits specified in SRSP-503 for base station equipment.

In addition, the peak-to-average power ratio (PAPR) of the transmitter shall not exceed 13 dB for more than 0.1% of the time using a signal corresponding to the highest PAPR during periods of continuous transmission.

RSS-133 clause 5.5

The maximum power spectral density of the equipment, measured in terms of average values, shall comply with the limits specified in table 2. These limits are either specified in terms of equivalent isotropically radiated power (e.i.r.p.) or TRP for the purpose of certification and may not apply to all deployment scenarios. Consult SRSP-510 for more deployment details in the bands 1850-1915 MHz and 1930-1995 MHz.

AAS equipment with eight antenna elements or less can demonstrate compliance with the e.i.r.p limit specified for non-AAS equipment in table 2, instead of the TRP limit.

Table 2: Maximum power spectral density of equipment

Equipment type	Maximum power spectral density
Non-AAS fixed station and base station	3280 W/MHz e.i.r.p
AAS fixed station and base station	46 dBm/MHz TRP
Subscriber equipment	2 W /channel bandwidth e.i.r.p

In addition, the peak-to-average power ratio (PAPR) of the equipment shall not exceed 13 dB for more than 0.1% of the time, using a signal corresponding to the highest PAPR during periods of continuous transmission.

RSS-140 clause 4.3

The equivalent radiated power (e.r.p.) for control and mobile equipment shall not exceed 30 W. The e.r.p. for portable equipment including handheld devices shall not exceed 3 W. Fixed and base station equipment shall comply with the e.r.p. limits in SRSP-540.

In addition, the peak to average power ratio (PAPR) of the equipment shall not exceed 13 dB for more than 0.1% of the time, using a signal that corresponds to the highest PAPR during periods of continuous transmission.

RSS-139 clause 5.5

The maximum output power of the equipment shall comply with the limits specified below. In the tables, maximum power refers to the equivalent isotropically radiated power (e.i.r.p.) or total radiated power (TRP), measured in terms of average values.

The limits in this RSS are specified for the purpose of certification and may not apply to all deployment scenarios. Consult SRSP-513 and SRSP-519 for more details on the bands 2110-2180 MHz and 2180-2200 MHz respectively.

Table 3: Maximum power of equipment in the band 1710-1780 MHz

Equipment type	Maximum power
Fixed station and base station	30 dBm e.i.r.p./channel bandwidth
Subscriber equipment	30 dBm e.i.r.p./channel bandwidth

Table 4: Maximum power of equipment in the band 2110-2180 MHz

Equipment type	Maximum power
Non-AAS fixed station and base station	65 dBm e.i.r.p./MHz
AAS fixed station and base station	46 dBm TRP/MHz
Subscriber equipment	30 dBm e.i.r.p./channel bandwidth

Table 5: Maximum power of equipment in the band 2180-2200 MHz

Equipment type	Maximum power
Non-AAS base station	65 dBm e.i.r.p./MHz
AAS base station	46 dBm TRP/MHz

In addition, the peak to average power ratio (PAPR) of the equipment shall not exceed 13 dB for more than 0.1% of the time, using a signal that corresponds to the highest PAPR during periods of continuous transmission.

RSS-199 Clause 5.5

The maximum output power of the equipment shall comply with the limits specified in table 3. In this table, maximum power refers to the equivalent isotropically radiated power (e.i.r.p.) or total radiated power (TRP), measured in terms of average values.

Subscriber equipment other than fixed subscriber equipment shall not exceed an e.i.r.p of 2W per channel bandwidth.

Fixed subscriber equipment shall not exceed the following:

- i. conducted power of 2W per channel bandwidth for all ports
- ii. e.i.r.p of 40 W per channel bandwidth

The maximum power limits for fixed station and base station are provided in Table 3. The limits in this RSS are specified for the purpose of certification and may not apply to all deployment scenarios. Consult SRSP-517 for more deployment details in the band 2500-2690 MHz.


Table 3: Maximum power of fixed station and base station in the band 2500-2690 MHz

Equipment type	Maximum power
Non-AAS fixed station and base station	e.i.r.p of 1640 W /MHz
AAS fixed station and base station	TRP of 43 dBm /MHz

In addition, the peak-to-average power ratio (PAPR) of the transmitter shall not exceed 13 dB for more than 0.1% of the time and shall use a signal corresponding to the highest PAPR during periods of continuous transmission.

4.1.2 Test Setup Block

For RF Output Power:



Note: The Insertion loss of the RF cable and coaxial Attenuator was offset into the Reading of CMW500.

4.1.3 Test Procedure

According to CFR Part 2.1046, ANSI C63.26-2015 Section 5.2.5.5:

Connect the instrument and the EUT according to the Test Setup Block, and then read the Test results on the CMW500/Wireless Communication Test Set.

4.1.4 Test Results

Please refer to section 5.1.

4.2 Transmitter unwanted emissions-Radiated Spurious emissions:

4.2.1 Applicable Standard

FCC §22.917

(a) Out of band emissions. The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.

(b) Measurement procedure. Compliance with these rules is based on the use of measurement instrumentation employing a reference bandwidth as follows:

(1) In the spectrum below 1 GHz, instrumentation should employ a reference bandwidth of 100 kHz or greater. In the 1 MHz bands immediately outside and adjacent to the frequency block, a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. A narrower resolution bandwidth is permitted in all cases to improve measurement accuracy, provided that the measured power is integrated over the full required reference bandwidth (i.e., 100 kHz or 1 percent of emission bandwidth, as specified). The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.

(2) In the spectrum above 1 GHz, instrumentation should employ a reference bandwidth of 1 MHz

FCC §24.238

The rules in this section govern the spectral characteristics of emissions in the Broadband Personal Communications Service.

(a) Out of band emissions. The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.

(b) Measurement procedure. Compliance with these rules is based on the use of measurement instrumentation employing a resolution bandwidth of 1 MHz or greater. However, in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. A narrower resolution bandwidth is permitted in all cases to improve measurement accuracy provided the measured power is integrated over the full required measurement bandwidth (i.e. 1 MHz or 1 percent of emission bandwidth, as specified). The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.

(c) Alternative out of band emission limit. Licensees in this service may establish an alternative out of band emission limit to be used at specified band edge(s) in specified geographical areas, in lieu of that set forth in this section, pursuant to a private contractual arrangement of all affected licensees and applicants. In this event, each party to such contract shall maintain a copy of the contract in their station files and disclose it to prospective assignees or transferees and, upon request, to the FCC.

(d) Interference caused by out of band emissions. If any emission from a transmitter operating in this service results in interference to users of another radio service, the FCC may require a greater attenuation of that emission than specified in this section.

FCC §27.53

(a) For operations in the 2305-2320 MHz band and the 2345-2360 MHz band, the power of any emission outside a licensee's frequency band(s) of operation shall be attenuated below the transmitter power P (with averaging performed only during periods of transmission) within the licensed band(s) of operation, in watts, by the following amounts:

(4) For mobile and portable stations operating in the 2305-2315 MHz and 2350-2360 MHz bands:

(i) By a factor of not less than: $43 + 10 \log(P)$ dB on all frequencies between 2305 and 2320 MHz and on all frequencies between 2345 and 2360 MHz that are outside the licensed band(s) of operation, not less than $55 + 10 \log(P)$ dB on all frequencies between 2320 and 2324 MHz and on all frequencies between 2341 and 2345 MHz, not less than $61 + 10 \log(P)$ dB on all frequencies between 2324 and 2328 MHz and on all frequencies

between 2337 and 2341 MHz, and not less than $67 + 10 \log(P)$ dB on all frequencies between 2328 and 2337 MHz;

(ii) By a factor of not less than $43 + 10 \log(P)$ dB on all frequencies between 2300 and 2305 MHz, $55 + 10 \log(P)$ dB on all frequencies between 2296 and 2300 MHz, $61 + 10 \log(P)$ dB on all frequencies between 2292 and 2296 MHz, $67 + 10 \log(P)$ dB on all frequencies between 2288 and 2292 MHz, and $70 + 10 \log(P)$ dB below 2288 MHz;

(iii) By a factor of not less than $43 + 10 \log(P)$ dB on all frequencies between 2360 and 2365 MHz, and not less than $70 + 10 \log(P)$ dB above 2365 MHz.

(c) For operations in the 746-758 MHz band and the 776-788 MHz band, the power of any emission outside the licensee's frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, measured in watts, in accordance with the following:

(1) On any frequency outside the 746-758 MHz band, the power of any emission shall be attenuated outside the band below the transmitter power (P) by at least $43 + 10 \log(P)$ dB;

(2) On any frequency outside the 776-788 MHz band, the power of any emission shall be attenuated outside the band below the transmitter power (P) by at least $43 + 10 \log(P)$ dB;

(3) On all frequencies between 763-775 MHz and 793-805 MHz, by a factor not less than $76 + 10 \log(P)$ dB in a 6.25 kHz band segment, for base and fixed stations;

(4) On all frequencies between 763-775 MHz and 793-805 MHz, by a factor not less than $65 + 10 \log(P)$ dB in a 6.25 kHz band segment, for mobile and portable stations;

(5) Compliance with the provisions of paragraphs (c)(1) and (c)(2) of this section is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kHz or greater. However, in the 100 kHz bands immediately outside and adjacent to the frequency block, a resolution bandwidth of at least 30 kHz may be employed;

(6) Compliance with the provisions of paragraphs (c)(3) and (c)(4) of this section is based on the use of measurement instrumentation such that the reading taken with any resolution bandwidth setting should be adjusted to indicate spectral energy in a 6.25 kHz segment.

(f) For operations in the 746-758 MHz, 775-788 MHz, and 805-806 MHz bands, emissions in the band 1559-1610 MHz shall be limited to -70 dBW/MHz equivalent isotropically radiated power (EIRP) for wideband signals, and -80 dBW EIRP for discrete emissions of less than 700 Hz bandwidth. For the purpose of equipment authorization, a transmitter shall be tested with an antenna that is representative of the type that will be used with the equipment in normal operation.

(g) For operations in the 600 MHz band and the 698-746 MHz band, the power of any emission outside a licensee's frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, measured in watts, by at least $43 + 10 \log(P)$ dB. Compliance with this provision is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kilohertz or greater. However, in the 100 kilohertz bands immediately outside and adjacent to a licensee's frequency block, a resolution bandwidth of at least 30 kHz may be employed.

(h) AWS emission limits

(1) **General protection levels.** Except as otherwise specified below, for operations in the 1695-1710 MHz, 1710-1755 MHz, 1755-1780 MHz, 1915-1920 MHz, 1995-2000 MHz, 2000-2020 MHz, 2110-2155 MHz, 2155-2180 MHz, and 2180-2200 bands, the power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) in watts by at least $43 + 10 \log_{10}(P)$ dB.

(m)(4) For mobile digital stations, the attenuation factor shall be not less than $40 + 10 \log(P)$ dB on all frequencies between the channel edge and 5 megahertz from the channel edge, $43 + 10 \log(P)$ dB on all frequencies between 5 megahertz and X megahertz from the channel edge, and $55 + 10 \log(P)$ dB on all frequencies more than X megahertz from the channel edge, where X is the greater of 6 megahertz or the actual emission bandwidth as defined in paragraph (m)(6) of this section. In addition, the attenuation factor shall not be less than $43 + 10 \log(P)$ dB on all frequencies between 2490.5 MHz and 2496 MHz and $55 + 10 \log(P)$ dB

at or below 2490.5 MHz. Mobile Satellite Service licensees operating on frequencies below 2495 MHz may also submit a documented interference complaint against BRS licensees operating on channel BRS Channel 1 on the same terms and conditions as adjacent channel BRS or EBS licensees.

FCC §90.691

(a) Out-of-band emission requirement shall apply only to the “outer” channels included in an EA license and to spectrum adjacent to interior channels used by incumbent licensees. The emission limits are as follows:

(1) For any frequency removed from the EA licensee's frequency block by up to and including 37.5 kHz, the power of any emission shall be attenuated below the transmitter power (P) in watts by at least $116 \log_{10}(f/6.1)$ decibels or $50 + 10 \log_{10}(P)$ decibels or 80 decibels, whichever is the lesser attenuation, where f is the frequency removed from the center of the outer channel in the block in kilohertz and where f is greater than 12.5 kHz.

(2) For any frequency removed from the EA licensee's frequency block greater than 37.5 kHz, the power of any emission shall be attenuated below the transmitter power (P) in watts by at least $43 + 10 \log_{10}(P)$ decibels or 80 decibels, whichever is the lesser attenuation, where f is the frequency removed from the center of the outer channel in the block in kilohertz and where f is greater than 37.5 kHz.

FCC §90.543

(c) Out-of-band emission limit. On any frequency outside of the frequency ranges covered by the ACP tables in this section, the power of any emission must be reduced below the mean output power (P) by at least $43 + 10 \log(P)$ dB measured in a 100 kHz bandwidth for frequencies less than 1 GHz, and in a 1 MHz bandwidth for frequencies greater than 1 GHz.

RSS-130 clause 4.7.1 General unwanted emissions limits

The unwanted emissions in any 100 kHz bandwidth on any frequency outside the low frequency edge and the high frequency edge of each frequency block range(s), shall be attenuated below the transmitter power, P (dBW), by at least $43 + 10 \log_{10} p$ (watts), dB. However, in the 100 kHz band immediately outside of the equipment's frequency block range, a resolution bandwidth of 30 kHz may be employed.

RSS-130 clause 4.7.2 Additional unwanted emissions limits

In addition to the limit outlined in section 4.7.1 above, equipment operating in the frequency bands 746-756 MHz and 777-787 MHz shall also comply with the following restrictions:

a) The power of any unwanted emissions in any 6.25 kHz bandwidth for all frequencies between 763-775 MHz and 793-806 MHz shall be attenuated below the transmitter power, P (dBW), by at least:

- (i) $76 + 10 \log_{10} p$ (watts), dB, for base and fixed equipment, and
- (ii) $65 + 10 \log_{10} p$ (watts), dB, for mobile and portable equipment.

b) The e.i.r.p. in the band 1559-1610 MHz shall not exceed -70 dBW/MHz for wideband signal and -80 dBW for discrete emission with bandwidth less than 700 Hz.

RSS-132 clause 5.5

Mobile and base station equipment shall comply with the limits in (i) and (ii) below.

- (i) In the first 1.0 MHz band immediately outside and adjacent to each of the sub-bands specified in Section 5.1, the power of emissions per any 1% of the occupied bandwidth shall be attenuated (in dB) below the transmitter output power P (dBW) by at least $43 + 10 \log_{10} p$ (watts).
- (ii) After the first 1.0 MHz immediately outside and adjacent to each of the sub-bands, the power of emissions in any 100 kHz bandwidth shall be attenuated (in dB) below the transmitter output power P (dBW) by at least $43 + 10 \log_{10} p$ (watts). If the measurement is performed using 1% of the occupied bandwidth, power integration over 100 kHz is required.

RSS-133 clause 5.6

Unwanted emissions shall be measured in terms of average values while the transmitter is operating at the manufacturer's rated power and modulated as specified in RSS-Gen.

Equipment shall meet the unwanted emission limits, specified in table 3, outside each frequency block group. For each channel bandwidth supported by the equipment under test, the unwanted emissions shall be measured and reported for two channel frequencies: one located as close as possible to the low end and one located as close as possible to the high end of the equipment's operating frequency range.

For the unwanted emission limits, in the 1 MHz bands immediately outside and adjacent to the frequency block group, the power shall be measured with a resolution bandwidth of at least 1% of the occupied bandwidth (OBW). Beyond these 1 MHz bands, a resolution bandwidth of 1 MHz shall be used. A narrower resolution bandwidth may be used, provided that the measured power is integrated over the full required measurement bandwidth of 1 MHz, or 1% of the OBW, as applicable.

For all equipment, the TRP or total conducted power (sum of conducted power across all antenna connectors), where applicable, of the unwanted emissions outside the frequency block or frequency block group shall not exceed the limits shown in the table 3.

Table 3: Unwanted emission limits for all equipment

Offset frequency from the edge of the frequency block group (MHz)	Unwanted emission limit
≤ 1	-13 dBm/(1% of OBW)
> 1	-13 dBm/MHz

RSS-139 clause 5.6

Unwanted emissions shall be measured in terms of average values.

For all equipment, the TRP or total conducted power (sum of conducted power across all antenna connectors) of the unwanted emissions outside the frequency block or frequency block group shall not exceed the limits shown in table 6.

Table 6: Unwanted emission limits	
Offset from the edge of the frequency block or frequency block group	Unwanted emission limits
≤1 MHz	-13 dBm/(1% of OB*)
>1 MHz	-13 dBm/MHz

*OB is the occupied bandwidth.

In addition to complying with the above limits, equipment operating in the band 2180-2200 MHz may require additional filtering (see SRSP-519).

RSS-140 clause 4.4

The power of any unwanted emission outside the bands 758-768 MHz and 788-798 MHz shall be attenuated below the transmitter output power P in dBW as follows, where p is the transmitter output power in watts:

a) For any frequency between 769-775 MHz and 799-806 MHz:

- i) $76 + 10 \log(p)$, dB in a 6.25 kHz band for fixed and base station equipment
- ii) $65 + 10 \log(p)$, dB in a 6.25 kHz band for mobile and portable/hand-held equipment

b) For any frequency between 775-788 MHz, above 806 MHz, and below 758 MHz: $43 + 10 \log(p)$, dB in a bandwidth of 100 kHz or greater. However, in the 100 kHz bands immediately outside and adjacent to the frequency bands 758-768 MHz and 788-798 MHz, a resolution bandwidth of 30 kHz may be employed.

In addition, the equivalent isotropically radiated power (e.i.r.p.) of all emissions, including harmonics in the band 1559-1610 MHz, shall not exceed -70 dBW/MHz for wideband emissions, and -80 dBW/kHz for discrete emissions of less than 700 Hz bandwidth.

RSS-199 clause 5.6

Unwanted emissions shall be measured in terms of average values when the transmitter is operating at the manufacturer's rated power and modulated as specified in RSS-Gen.

Equipment shall meet the unwanted emission limits, specified below, outside each frequency block group. For each channel bandwidth supported by the equipment under test, the unwanted emissions shall be measured and reported for two channel frequencies: one located as close as possible to the low end and one located as close as possible to the high end of the equipment's operating frequency range.

For the unwanted emission limits, in the 1 MHz band immediately outside and adjacent to the frequency block group, the power shall be measured with a resolution bandwidth of at least 1% of the occupied bandwidth for fixed stations, base stations, and fixed subscriber equipment, and 2% for subscriber equipment other than fixed subscriber equipment. Beyond this 1 MHz band, a resolution bandwidth of 1 MHz shall be used. A narrower resolution bandwidth can be used, provided that the measured power is integrated over the full required measurement bandwidth of 1 MHz, or 1% or 2% of the occupied bandwidth, as applicable.

For all equipment, the TRP or total conducted power (sum of conducted power across all antenna connectors), where applicable, of the unwanted emissions outside the frequency block or frequency block group shall not exceed the limits shown in the tables below.

Table 4: Unwanted emission limits for fixed station, base station and fixed subscriber equipment	
Offset from the edge of the frequency block or frequency block group (MHz)	Unwanted emission limits
≤ 1	-13 dBm/(1% of OB*)
> 1	-13 dBm/MHz

*OB is the occupied bandwidth

Table 5: Unwanted emission limits for subscriber equipment other than fixed subscriber equipment	
Offset from the edge of the frequency block or frequency block group (MHz)	Unwanted emission limits
0-1	-10 dBm/(2% of OB*)
1-5	-10 dBm/MHz
5-X**	-13 dBm/MHz
$\geq X$	-25 dBm/MHz

*OB is the occupied bandwidth

** X is 6 MHz or the equipment occupied bandwidth, whichever is greater

In addition to complying with the limits in table 5, subscriber equipment other than fixed subscriber equipment shall not exceed -13 dBm/MHz on all frequencies between 2490.5 MHz and 2496 MHz, and -25 dBm/MHz at or below 2490.5 MHz.

4.2.2 Test setup

According to ANSI C63.26-2015 Section 5.5.3:




Figure 6 —Test site-up for radiated ERP and/or EIRP measurements




Figure 7 —Substitution method set-up for radiated emission

4.2.3 Test Procedure

According to ANSI C63.26-2015 Section 5.5.3:

- a) Place the EUT in the center of the turntable. The EUT shall be configured to transmit into the standard non-radiating load (for measuring radiated spurious emissions), connected with cables of minimal length unless specified otherwise. If the EUT uses an adjustable antenna, the antenna shall be positioned to the length that produces the worst case emission at the fundamental operating frequency.
- b) Each emission under consideration shall be evaluated:
 - 1) Raise and lower the measurement antenna in accordance 5.5.2, as necessary to enable detection of the maximum emission amplitude relative to measurement antenna height.
 - 2) Rotate the EUT through 360° to determine the maximum emission level relative to the axial position.
 - 3) Return the turntable to the azimuth where the highest emission amplitude level was observed.
 - 4) Vary the measurement antenna height again through 1 m to 4 m again to find the height associated with the maximum emission amplitude.
 - 5) Record the measured emission amplitude level and frequency using the appropriate RBW.
- c) Repeat step b) for each emission frequency with the measurement antenna oriented in both the horizontal and vertical polarizations to determine the orientation that gives the maximum emissions amplitude.
- d) Set-up the substitution measurement with the reference point of the substitution antenna located as near as possible to where the center of the EUT radiating element was located during the initial EUT measurement.
- e) Maintain the previous measurement instrument settings and test set-up, with the exception that the EUT is removed and replaced by the substitution antenna.
- f) Connect a signal generator to the substitution antenna; locate the signal generator so as to minimize any potential influences on the measurement results. Set the signal generator to the frequency where emissions are detected, and set an output power level such that the radiated signal can be detected by the measurement instrument, with sufficient dynamic range relative to the noise floor.
- g) For each emission that was detected and measured in the initial test [i.e., in step b) and step c)]:
 - 1) Vary the measurement antenna height between 1 m to 4 m to maximize the received (measured) signal amplitude.
 - 2) Adjust the signal generator output power level until the amplitude detected by the measurement instrument equals the amplitude level of the emission previously measured directly in step b) and step c).
 - 3) Record the output power level of the signal generator when equivalence is achieved in step 2).
- h) Repeat step e) through step g) with the measurement antenna oriented in the opposite polarization.
- i) Calculate the emission power in dBm referenced to a half-wave dipole using the following equation:

$$P_e = P_s(\text{dBm}) - \text{cable loss (dB)} + \text{antenna gain (dBd)}$$

where

P_e = equivalent emission power in dBm

P_s = source (signal generator) power in dBm

NOTE—dBd refers to the measured antenna gain in decibels relative to a half-wave dipole.

- j) Correct the antenna gain of the substitution antenna if necessary to reference the emission power to a half-wave dipole. When using measurement antennas with the gain specified in dBi, the equivalent dipole-referenced gain can be determined from: $\text{gain (dBd)} = \text{gain (dBi)} - 2.15 \text{ dB}$. If necessary, the antenna gain can be calculated from calibrated antenna factor information
- k) Provide the complete measurement results as a part of the test report.

4.2.4 Test Results

Please refer to section 5.2.

4.3 Frequency Sub-bands

4.3.1 Applicable Standard

RSS-132 clause 5.1

The frequency bands 824-849 MHz and 869-894 MHz are divided into sub-bands as described in SRSP-503. These sub-bands are:

824-835 MHz, 835-845 MHz, 845-846.5 MHz, and 846.5-849 MHz for mobile transmit; and

869-880 MHz, 880-890 MHz, 890-891.5 MHz, and 891.5-894 MHz for base transmit.

4.3.2 Judgment

Compliant, the device operates in this band is divided into sub-bands as described in SRSP-503.

4.4 Band plan

4.4.1 Applicable Standard

RSS-133 clause 5.2

The bands 1850-1915 MHz and 1930-1995 MHz are divided into 11 paired frequency blocks as shown in table 1. Frequency blocks may be aggregated to form a frequency block group. SRSP 510, Technical Requirements for Personal Communications Services (PCS) in the Bands 1850-1915 MHz and 1930-1995 MHz, contains the detailed band plan.

Table 1: Paired frequency blocks in the 1850-1915 MHz and 1930-1995 MHz bands

Block	Lower sub-band (MHz)	Upper sub-band (MHz)	Total spectrum (MHz)
A	1850-1865	1930-1945	30
D	1865-1870	1945-1950	10
B1	1870-1875	1950-1955	10
B2	1875-1880	1955-1960	10
B3	1880-1885	1960-1965	10
E	1885-1890	1965-1970	10
F	1890-1895	1970-1975	10
C1	1895-1900	1975-1980	10
C2	1900-1905	1980-1985	10
C3	1905-1910	1985-1990	10
G	1910-1915	1990-1995	10

RSS-139 clause 5.2

The bands 1710-1780 MHz and 2110-2180 MHz are divided into 11 paired blocks as shown in table 1. Standard Radio System Plan SRSP-513, Technical Requirements for Advanced Wireless Services in the Bands 1710-1780 MHz and 2110-2180 MHz, contains the detailed band plan.

Table 1: Frequency blocks in the bands 1710-1780 MHz and 2110-2180 MHz			
Block	Lower sub-band (MHz)	Upper sub-band (MHz)	Total block size (MHz)
Block A	1710-1720	2110-2120	20
Block B	1720-1730	2120-2130	20
Block C	1730-1735	2130-2135	10
Block D	1735-1740	2135-2140	10
Block E	1740-1745	2140-2145	10
Block F	1745-1755	2145-2155	20
Block G	1755-1760	2155-2160	10
Block H	1760-1765	2160-2165	10
Block I	1765-1770	2165-2170	10
Block J1	1770-1775	2170-2175	10
Block J2	1775-1780	2175-2180	10

The band 2180-2200 MHz is divided into two downlink-only blocks, as shown in table 2. SRSP-519, Technical Requirements for the Ancillary Terrestrial Component of Mobile-Satellite Service Systems Operating in the Bands 2000-2020 MHz and 2180-2200 MHz, contains the detailed band plan. In this RSS, AWS-4 is referred to as ATC band 2180-2200 MHz.

Table 2: Frequency blocks in the bands 2180-2200 MHz		
Block	Frequency range (MHz)	Block size (MHz)
Block C	2180-2190	10
Block D	2190-2200	10

The blocks listed in tables 1 and 2 can be aggregated to form a larger channel.

RSS-199 Clause 5.2

The band 2500-2690 MHz is divided into 7 paired blocks and 2 unpaired blocks as shown in table 1 and 2. SRSP-517 contains the detailed band plan. Frequency blocks can be aggregated to form a frequency block

Table 1: Paired frequency blocks in the band 2500-2690 MHz

Block	Uplink frequencies (MHz)	Block	Downlink frequencies (MHz)	Total spectrum (MHz)
A	2500-2510	A'	2620-2630	10+10
B	2510-2520	B'	2630-2640	10+10
C	2520-2530	C'	2640-2650	10+10
D	2530-2540	D'	2650-2660	10+10
E	2540-2550	E'	2660-2670	10+10
F	2550-2560	F'	2670-2680	10+10
G	2560-2570	G'	2680-2690	10+10

Table 2: Unpaired frequency blocks in the band 2500-2690 MHz

Block	Frequencies (MHz)	Total spectrum (MHz)
H	2570-2595	25
I	2595-2620	25

group.

4.4.2 Judgment

Compliant, the device operates in this band is Compliant with SRSP-510, SRSP-513, SRSP-517.

4.5 Types of Modulation**4.5.1 Applicable Standard****RSS-130 clause 4.2**

Equipment certified under this standard shall employ digital modulation

RSS-132 clause 5.2

Equipment certified under this standard shall use digital modulation.

RSS-133 clause 5.3

The modulation used shall be digital.

RSS-139 clause 5.3

Devices may use any type of modulation technique. The type of modulation shall be documented in the test report.

RSS-140 clause 4.1

Equipment shall employ digital modulation techniques.

RSS-199 Clause 5.3

The modulation used shall be digital.

4.5.2 Judgment

Compliant, the device operates under this standard use digital modulation.

4.6 Frequency block**4.6.1 Applicable Standard****RSS-130 clause 4.3**

The frequency bands 617-652 MHz, 663-698 MHz, 698-756 MHz and 777-787 MHz are divided into small frequency blocks as per SRSP-518. Equipment shall operate according to the frequency plan given in the SRSP.

4.6.2 Judgment

Compliant, the device operates in the frequency bands 663-698 MHz, 698-756 MHz and 777-787 MHz are divided into small frequency blocks as per SRSP-518. Equipment shall operate according to the frequency plan given in the SRSP.

4.7 Additional requirements for subscriber equipment**4.7.1 Applicable Standard**

RSS-139 clause 5.7

Subscriber equipment other than fixed subscriber equipment shall use transmitter power control to limit power. The applicant shall include, with the application for certification, a declaration of compliance that confirms the control requirement was met and that includes a description of how the requirement was met. The declaration of compliance may be included as a separate document or attached (e.g. as an annex) to the test report.

Subscriber equipment operating in the band 1755-1780 MHz shall operate only when under the control of a base station. The applicant shall include, with the application for certification, a declaration of compliance that confirms the control requirement was met and that includes a description of how the requirement was met. The declaration of compliance may be included as a separate document or attached (e.g. as an annex) to the test report.

4.7.2 Judgment

Compliant, the devices use transmitter power control to limit power and operate under the control of a base station.

4.8 Interoperability requirement**4.8.1 Applicable Standard**

RSS-130 clause 4.4

Mobile and portable stations in the bands 617-652 MHz and 663-698 MHz must be capable of operating on all frequencies in these bands.

4.8.2 Judgment

Compliant, the device employs all the range of 663-698MHz for this band.

5. Test DATA AND RESULTS

5.1 Spot Check With Maximum Conducted Output Power

Serial Number:	3J9F-6	Test Date:	2026/4/24
Test Site:	RF	Test Mode:	Transmitting
Tester:	Loge Long	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	22.9	Relative Humidity: (%)	47	ATM Pressure: (kPa)	100.7
----------------------	------	------------------------------	----	---------------------------	-------

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Wideband Radio Communication Tester	CMW500	149216	2025/7/28	2026/7/27

* Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data:

LTE B2:						
Test Bandwidth & Modulation	Resource Block & RB offset	Conducted Average Output Power(dBm)			Maximum EIRP (dBm)	EIRP Limit (dBm)
		Lowest Channel	Middle Channel	Highest Channel		
1.4MHz QPSK	RB1#0	23.57	23.17	23.14	18.56	33
	RB6#0	22.52	22.51	22.59		
	RB1#2	23.34	23.39	23.42		
	RB1#5	23.47	23.11	23.08		
1.4MHz 16QAM	RB1#0	22.55	22.56	22.6	17.87	33
	RB6#0	21.43	21.71	21.34		
	RB1#2	22.52	22.88	22.59		
	RB1#5	22.53	22.65	22.3		
3MHz QPSK	RB1#0	23.15	23.22	23.41	18.4	33
	RB15#0	22.74	22.76	22.67		
	RB1#8	23.36	23.4	22.53		
	RB1#14	23.2	23.14	22.65		
3MHz 16QAM	RB1#0	22.56	22.64	22.67	17.79	33
	RB15#0	21.54	21.74	21.66		
	RB1#8	22.57	22.8	21.8		
	RB1#14	22.53	22.19	22.19		
5MHz QPSK	RB1#0	23.46	23.15	23.07	18.45	33
	RB25#0	22.73	22.84	22.68		
	RB1#12	23.46	23.32	23.38		
	RB1#24	23	23.25	23.11		
5MHz 16QAM	RB1#0	22.79	22.66	22.56	17.78	33
	RB25#0	21.66	21.9	21.55		
	RB1#12	22.67	22.74	22.62		
	RB1#24	22.6	22.75	22.27		

10MHz QPSK	RB1#0	22.87	23.25	23.44	18.64	33
	RB50#0	22.76	22.8	22.77		
	RB1#24	23.15	23.43	23.49		
	RB1#49	23.12	23.17	23.65		
10MHz 16QAM	RB1#0	22.71	22.85	22.53	18.15	33
	RB50#0	21.84	21.82	21.66		
	RB1#24	23.04	23.16	22.94		
	RB1#49	22.83	22.6	22.85		
15MHz QPSK	RB1#0	23.14	23.26	23.23	18.59	33
	RB75#0	23.6	22.74	22.72		
	RB1#38	23.24	23.34	23.1		
	RB1#74	23.11	23.47	23.12		
15MHz 16QAM	RB1#0	22.7	22.82	22.42	17.83	33
	RB75#0	21.64	21.65	21.61		
	RB1#38	22.84	22.83	22.56		
	RB1#74	22.6	22.61	22.59		
20MHz QPSK	RB1#0	23.34	23.4	23.79	18.78	33
	RB100#0	22.73	22.8	22.82		
	RB1#49	23.64	23.75	23.71		
	RB1#99	23.27	23.34	23.7		
20MHz 16QAM	RB1#0	22.45	22.74	23.57	18.56	33
	RB100#0	21.51	21.84	21.8		
	RB1#49	23.2	23.33	23.49		
	RB1#99	22.57	23.26	23.23		
Note: EIRP=Conducted Power(dBm) - Lc(dB) + Gt(dBi)						
					Result:	Pass

5.2 EIRP/ERP calculated and Results

Test Data:

Per-spot check, the conducted output power is consistent with the original report, so the Maximum EIRP/ERP was re-calculated.

LTE B2 band:

Test Mode	Maximum Conducted Average Output Power(dBm)	EIRP (dBm)	EIRP Limit (dBm)
1.4MHz QPSK	23.62	18.61	33
1.4MHz 16QAM	22.94	17.93	33
3MHz QPSK	23.69	18.68	33
3MHz 16QAM	23.22	18.21	33
5MHz QPSK	23.57	18.56	33
5MHz 16QAM	22.84	17.83	33
10MHz QPSK	23.66	18.65	33
10MHz 16QAM	23.18	18.17	33
15MHz QPSK	23.50	18.49	33
15MHz 16QAM	22.90	17.89	33
20MHz QPSK	23.88	18.87	33
20MHz 16QAM	23.61	18.60	33

LTE B4 band:

Test Mode	Maximum Conducted Average Output Power(dBm)	EIRP (dBm)	EIRP Limit (dBm)
1.4MHz QPSK	23.24	18.66	30
1.4MHz 16QAM	22.80	18.22	30
3MHz QPSK	23.17	18.59	30
3MHz 16QAM	22.57	17.99	30
5MHz QPSK	23.25	18.67	30
5MHz 16QAM	22.40	17.82	30
10MHz QPSK	23.28	18.70	30
10MHz 16QAM	23.06	18.48	30
15MHz QPSK	23.33	18.75	30
15MHz 16QAM	23.11	18.53	30
20MHz QPSK	23.37	18.79	30
20MHz 16QAM	23.23	18.65	30

LTE B5 band:

Test Mode	Maximum Conducted Average Output Power(dBm)	ERP (dBm)	ERP Limit (dBm)
1.4MHz QPSK	23.27	15.98	38.45
1.4MHz 16QAM	23.16	15.87	38.45
3MHz QPSK	23.14	15.85	38.45
3MHz 16QAM	22.58	15.29	38.45
5MHz QPSK	23.39	16.10	38.45
5MHz 16QAM	22.76	15.47	38.45
10MHz QPSK	23.55	16.26	38.45
10MHz 16QAM	22.98	15.69	38.45

LTE B7 band:

Test Mode	Maximum Conducted Average Output Power(dBm)	EIRP (dBm)	EIRP Limit (dBm)
5MHz QPSK	23.66	19.19	33
5MHz 16QAM	23.08	18.61	33
10MHz QPSK	23.62	19.15	33
10MHz 16QAM	23.40	18.93	33
15MHz QPSK	23.65	19.18	33
15MHz 16QAM	23.26	18.79	33
20MHz QPSK	23.81	19.34	33
20MHz 16QAM	23.52	19.05	33

LTE B12 band:

Test Mode	Maximum Conducted Average Output Power(dBm)	ERP (dBm)	ERP Limit (dBm)
1.4MHz QPSK	23.32	13.36	34.77
1.4MHz 16QAM	22.84	12.88	34.77
3MHz QPSK	23.20	13.24	34.77
3MHz 16QAM	22.86	12.90	34.77
5MHz QPSK	23.17	13.21	34.77
5MHz 16QAM	22.83	12.87	34.77
10MHz QPSK	23.37	13.41	34.77
10MHz 16QAM	22.84	12.88	34.77

LTE B13 band:

Test Mode	Maximum Conducted Average Output Power(dBm)	ERP (dBm)	ERP Limit (dBm)
5MHz QPSK	23.33	13.57	34.77
5MHz 16QAM	22.79	13.03	34.77
10MHz QPSK	23.09	13.33	34.77
10MHz 16QAM	22.75	12.99	34.77

LTE B14 band:

Test Mode	Maximum Conducted Average Output Power(dBm)	ERP (dBm)	ERP Limit (dBm)
5MHz QPSK	23.22	13.16	34.77
5MHz 16QAM	22.85	12.79	34.77
10MHz QPSK	23.06	13.00	34.77
10MHz 16QAM	22.67	12.61	34.77

LTE B17 band:

Test Mode	Maximum Conducted Average Output Power(dBm)	ERP (dBm)	ERP Limit (dBm)
5MHz QPSK	23.10	13.08	34.77
5MHz 16QAM	22.66	12.64	34.77
10MHz QPSK	23.36	13.34	34.77
10MHz 16QAM	23.22	13.20	34.77

LTE B25 band:

Test Mode	Maximum Conducted Average Output Power(dBm)	EIRP (dBm)	EIRP Limit (dBm)
1.4MHz QPSK	23.71	18.70	33
1.4MHz 16QAM	23.03	18.02	33
3MHz QPSK	23.50	18.49	33
3MHz 16QAM	22.83	17.82	33
5MHz QPSK	23.61	18.60	33
5MHz 16QAM	23.20	18.19	33
10MHz QPSK	23.66	18.65	33
10MHz 16QAM	23.18	18.17	33
15MHz QPSK	23.63	18.62	33
15MHz 16QAM	23.35	18.34	33
20MHz QPSK	23.87	18.86	33
20MHz 16QAM	23.68	18.67	33

LTE B26 band:(814-824MHz only for FCC)

Test Mode	Maximum Conducted Average Output Power(dBm)	ERP (dBm)	ERP Limit (dBm)
1.4MHz QPSK	23.32	15.50	50
1.4MHz 16QAM	23.22	15.40	50
3MHz QPSK	23.42	15.60	50
3MHz 16QAM	22.97	15.15	50
5MHz QPSK	23.23	15.41	50
5MHz 16QAM	22.85	15.03	50
10MHz QPSK	23.15	15.33	50
10MHz 16QAM	22.80	14.98	50

LTE B26 band: (824-849MHz)

Test Mode	Maximum Conducted Average Output Power(dBm)	ERP (dBm)	ERP Limit (dBm)
1.4MHz QPSK	23.38	16.09	38.45
1.4MHz 16QAM	22.78	15.49	38.45
3MHz QPSK	23.18	15.89	38.45
3MHz 16QAM	22.95	15.66	38.45
5MHz QPSK	23.20	15.91	38.45
5MHz 16QAM	22.43	15.14	38.45
10MHz QPSK	23.38	16.09	38.45
10MHz 16QAM	22.97	15.68	38.45
15MHz QPSK	23.14	15.85	38.45
15MHz 16QAM	22.89	15.60	38.45

LTE B41 band(2496-2690MHz for FCC):

Test Mode	Maximum Conducted Average Output Power(dBm)	EIRP (dBm)	EIRP Limit (dBm)
5MHz QPSK	23.42	18.95	33
5MHz 16QAM	23.00	18.53	33
10MHz QPSK	23.37	18.90	33
10MHz 16QAM	22.78	18.31	33
15MHz QPSK	23.53	19.06	33
15MHz 16QAM	22.81	18.34	33
20MHz QPSK	23.48	19.01	33
20MHz 16QAM	23.03	18.56	33

LTE B41 band(2500-2690MHz for IC):

Test Mode	Maximum Conducted Average Output Power(dBm)	EIRP (dBm)	EIRP Limit (dBm)
5MHz QPSK	23.51	19.04	33
5MHz 16QAM	22.87	18.40	33
10MHz QPSK	23.26	18.79	33
10MHz 16QAM	22.75	18.28	33
15MHz QPSK	23.24	18.77	33
15MHz 16QAM	22.66	18.19	33
20MHz QPSK	23.53	19.06	33
20MHz 16QAM	23.06	18.59	33

LTE B66 band:

Test Mode	Maximum Conducted Average Output Power(dBm)	EIRP (dBm)	EIRP Limit (dBm)
1.4MHz QPSK	23.14	18.56	30
1.4MHz 16QAM	22.69	18.11	30
3MHz QPSK	23.14	18.56	30
3MHz 16QAM	22.34	17.76	30
5MHz QPSK	23.16	18.58	30
5MHz 16QAM	22.40	17.82	30
10MHz QPSK	23.25	18.67	30
10MHz 16QAM	22.81	18.23	30
15MHz QPSK	23.16	18.58	30
15MHz 16QAM	22.61	18.03	30
20MHz QPSK	23.32	18.74	30
20MHz 16QAM	23.25	18.67	30

LTE B71 band:

Test Mode	Maximum Conducted Average Output Power(dBm)	ERP (dBm)	EIRP Limit (dBm)
5MHz QPSK	23.07	13.11	34.77
5MHz 16QAM	22.37	12.41	34.77
10MHz QPSK	23.07	13.11	34.77
10MHz 16QAM	22.71	12.75	34.77
15MHz QPSK	23.37	13.41	34.77
15MHz 16QAM	22.89	12.93	34.77
20MHz QPSK	23.30	13.34	34.77
20MHz 16QAM	23.12	13.16	34.77

Note:

1. $EIRP = \text{Maximum Conducted Average Output Power(dBm)} - L_C(\text{dB}) + G_T(\text{dBi})$

$ERP = \text{Maximum Conducted Average Output Power(dBm)} - L_C(\text{dB}) + G_T(\text{dBd})$

$G_T(\text{dBd}) = G_T(\text{dBi}) - 2.15$

2. Maximum Conducted Average Output Power please refer to FCC report:PD20240152-R3A▲ and IC report : PD20240152-R4A▲.

5.3 Radiated Spurious Emissions

Serial Number:	3J9F-3, 3J9F-1	Test Date:	2026/4/14~2026/4/18
Test Site:	Chamber 10m, Chamber A	Test Mode:	Transmitting
Tester:	Mikey Lin, Jayce Wang	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	24.2~25	Relative Humidity: (%)	40~45	ATM Pressure: (kPa)	100.6~101.1
----------------------	---------	---------------------------	-------	------------------------	-------------

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
30MHz~1000MHz					
Sunol Sciences	Hybrid Antenna	JB3	A060611-1	2025/6/23	2028/6/22
Narda	Coaxial Attenuator	779-6dB	04269	2025/6/23	2028/6/22
Unknown	Coaxial Cable	C-NJNJ-50	C-1000-01	2025/7/1	2026/6/30
Unknown	Coaxial Cable	C-NJNJ-50	C-0400-04	2025/7/1	2026/6/30
Unknown	Coaxial Cable	C-NJNJ-50	C-0530-01	2025/7/1	2026/6/30
Sonoma	Amplifier	310N	185914	2025/8/25	2026/8/24
R&S	EMI Test Receiver	ESR3	102453	2025/6/25	2026/6/24
EMCO	Adjustable Dipole Antenna	3121C	9109-753	N/A	N/A
Micro-Coax	Coaxial Cable	UFA210B	99G1448	2025/9/4	2026/9/3
Agilent	Signal Generator	E8247C	MY43321350	2025/7/28	2026/7/27
E-Microwave	Band Rejection Filter	OBF-ZP-703-748-SMAF	OE01902425	2025/6/6	2026/6/5
E-Microwave	Band Rejection Filter	BSF-ZP-777-787-SMAF	OE01902430	2025/6/6	2026/6/5
Sinoscite	Band Rejection Filter	BSF824-862MS	1438001	2025/6/6	2026/6/5
Above 1GHz					
AH	Horn Antenna	SAS-571	1177	2026/1/22	2029/1/21
ETS-Lindgren	Horn Antenna	3115	000 527 35	2023/9/7	2026/9/6
Ducommun Technologies	Horn Antenna	ARH-4223-02	1007726-02 1304	2026/2/21	2029/2/20
Ducommun Technologies	Horn Antenna	ARH-4223-02	1007726-03 1304	2026/2/6	2029/2/5
Ducommun Technologies	Horn Antenna	ARH-2823-02	1007726-01 1302	2026/2/6	2029/2/5
Ducommun Technologies	Horn Antenna	ARH-2823-02	1007726-02 1302	2026/2/21	2029/2/20
HUBER+SUHNER	Coaxial Cable	SUCOFLEX 126EA	MY369/26/26EA	2025/7/1	2026/6/30
Xinhang Macrowave	Coaxial Cable	XH360A-2.92/J-2.92/J-6M-A	20231208001 #0001	2025/11/14	2026/11/13
Micro-Coax	Coaxial Cable	UFA210B	99G1448	2025/9/4	2026/9/3
AH	Preamplifier	PAM-0118P	530	2025/6/3	2026/6/2
AH	Preamplifier	PAM-1840VH	191	2025/7/31	2026/7/30
R&S	Spectrum Analyzer	FSP 38	100478	2025/7/28	2026/7/27
Agilent	Signal Generator	E8247C	MY43321350	2025/7/28	2026/7/27
Sinoscite	Band Rejection Filter	BSF1710-1785MN	0383003	2025/6/6	2026/6/5
Sinoscite	Band Rejection Filter	BSF1850-1910MS	0935V2001	2025/6/5	2026/6/4
Mini-Circuits	High Pass Filter	VHF-1200+	31102	2025/7/1	2026/6/30
Micro-tronics	High Pass Filter	HPM50111	G217	2025/11/29	2026/11/28

* Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data:

After pre-scan in the X, Y and Z axes of orientation, the worst case(Y axe) is below:

LTE Bands:

(The Worst modulation and bandwidth were below)

LTE Band 2(30MHz-20GHz):

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
1RB, 1.4MHz, QPSK, Frequency:1850.7 MHz								
365.47	H	36.95	-71.16	0.00	0.60	-71.76	-13.00	58.76
40.37	V	50.25	-35.28	-25.91	0.17	-61.36	-13.00	48.36
3701.40	H	52.36	-61.59	10.72	0.74	-51.61	-13.00	38.61
3701.40	V	51.42	-62.43	10.72	0.74	-52.45	-13.00	39.45
5552.10	H	50.18	-61.66	11.69	1.05	-51.02	-13.00	38.02
5552.10	V	49.87	-61.15	11.69	1.05	-50.51	-13.00	37.51
1RB, 1.4MHz, QPSK, Frequency:1880 MHz								
365.83	H	36.99	-71.11	0.00	0.60	-71.71	-13.00	58.71
40.05	V	51.37	-33.88	-26.33	0.17	-60.38	-13.00	47.38
3760.00	H	52.21	-61.53	10.76	0.75	-51.52	-13.00	38.52
3760.00	V	51.36	-62.19	10.76	0.75	-52.18	-13.00	39.18
5640.00	H	50.45	-61.57	11.67	1.05	-50.95	-13.00	37.95
5640.00	V	50.14	-61.13	11.67	1.05	-50.51	-13.00	37.51
1RB, 1.4MHz, QPSK, Frequency:1909.3 MHz								
365.92	H	36.83	-71.27	0.00	0.60	-71.87	-13.00	58.87
41.28	V	50.33	-35.97	-24.71	0.17	-60.85	-13.00	47.85
3818.60	H	52.02	-61.49	10.79	0.76	-51.46	-13.00	38.46
3818.60	V	51.69	-61.55	10.79	0.76	-51.52	-13.00	38.52
5727.90	H	50.33	-62.14	11.65	1.05	-51.54	-13.00	38.54
5727.90	V	49.46	-62.14	11.65	1.05	-51.54	-13.00	38.54

LTE Band 4(30MHz-18GHz):

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
1RB, 1.4MHz, QPSK, Frequency:1710.7 MHz								
365.06	H	37.42	-70.70	0.00	0.60	-71.30	-13.00	58.30
41.27	V	49.26	-37.03	-24.72	0.17	-61.92	-13.00	48.92
3421.40	H	51.45	-60.95	10.54	0.72	-51.13	-13.00	38.13
3421.40	V	51.52	-60.52	10.54	0.72	-50.70	-13.00	37.70
5132.10	H	50.26	-59.78	10.74	0.95	-49.99	-13.00	36.99
5132.10	V	50.41	-58.38	10.74	0.95	-48.59	-13.00	35.59
1RB, 1.4MHz, QPSK, Frequency:1732.5 MHz								
364.29	H	37.55	-70.58	0.00	0.60	-71.18	-13.00	58.18
40.52	V	50.23	-35.42	-25.71	0.17	-61.30	-13.00	48.30
3465.00	H	51.74	-61.59	10.57	0.72	-51.74	-13.00	38.74
3465.00	V	51.36	-61.73	10.57	0.72	-51.88	-13.00	38.88
5197.50	H	50.43	-59.86	10.91	0.97	-49.92	-13.00	36.92
5197.50	V	50.25	-58.84	10.91	0.97	-48.90	-13.00	35.90
1RB, 1.4MHz, QPSK, Frequency:1754.3MHz								
364.88	H	36.54	-71.58	0.00	0.60	-72.18	-13.00	59.18
41.38	V	50.66	-35.73	-24.58	0.17	-60.48	-13.00	47.48
3508.60	H	51.68	-62.38	10.61	0.72	-52.49	-13.00	39.49
3508.60	V	51.27	-62.67	10.61	0.72	-52.78	-13.00	39.78
5262.90	H	50.02	-61.10	11.08	0.99	-51.01	-13.00	38.01
5262.90	V	49.98	-59.98	11.08	0.99	-49.89	-13.00	36.89

LTE Band 5(30MHz-10GHz):

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
1RB, 1.4MHz, QPSK, Frequency: 824.7 MHz								
365.29	H	37.48	-70.63	0.00	0.60	-71.23	-13.00	58.23
40.88	V	49.52	-36.44	-25.24	0.17	-61.85	-13.00	48.85
1649.40	H	51.11	-67.79	9.44	0.44	-58.79	-13.00	45.79
1649.40	V	52.68	-66.27	9.44	0.44	-57.27	-13.00	44.27
2474.10	H	50.46	-63.64	9.24	0.62	-55.02	-13.00	42.02
2474.10	V	50.52	-63.82	9.24	0.62	-55.20	-13.00	42.20
3298.80	H	49.86	-61.79	10.44	0.72	-52.07	-13.00	39.07
3298.80	V	49.84	-61.64	10.44	0.72	-51.92	-13.00	38.92
1RB, 1.4MHz, QPSK, Frequency: 836.5 MHz								
366.74	H	37.62	-70.47	0.00	0.60	-71.07	-13.00	58.07
41.14	V	49.08	-37.10	-24.90	0.17	-62.17	-13.00	49.17
1673.00	H	50.02	-68.97	9.48	0.45	-59.94	-13.00	46.94
1673.00	V	52.31	-66.71	9.48	0.45	-57.68	-13.00	44.68
2509.50	H	50.97	-62.73	9.22	0.62	-54.13	-13.00	41.13
2509.50	V	50.85	-63.04	9.22	0.62	-54.44	-13.00	41.44
3346.00	H	50.43	-61.35	10.48	0.72	-51.59	-13.00	38.59
3346.00	V	50.12	-61.38	10.48	0.72	-51.62	-13.00	38.62
1RB, 1.4MHz, QPSK, Frequency: 848.3 MHz								
365.42	H	37.66	-70.45	0.00	0.60	-71.05	-13.00	58.05
41.17	V	50.27	-35.94	-24.86	0.17	-60.97	-13.00	47.97
1696.60	H	50.65	-68.44	9.51	0.46	-59.39	-13.00	46.39
1696.60	V	52.54	-66.55	9.51	0.46	-57.50	-13.00	44.50
2544.90	H	51.26	-62.35	9.29	0.63	-53.69	-13.00	40.69
2544.90	V	51.52	-62.03	9.29	0.63	-53.37	-13.00	40.37
3393.20	H	50.23	-61.70	10.51	0.72	-51.91	-13.00	38.91
3393.20	V	50.31	-61.21	10.51	0.72	-51.42	-13.00	38.42

LTE Band 7 (30MHz-26GHz):

1RB, 5MHz, QPSK, Frequency: 2502.5 MHz								
Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
364.28	H	36.74	-71.39	0.00	0.60	-71.99	-25.00	46.99
39.26	V	49.55	-35.34	-26.04	0.17	-61.55	-25.00	36.55
5005.00	H	53.22	-57.25	10.41	0.92	-47.76	-25.00	22.76
5005.00	V	51.05	-58.20	10.41	0.92	-48.71	-25.00	23.71
7507.50	H	50.87	-56.21	10.81	1.20	-46.60	-25.00	21.60
7507.50	V	50.14	-57.38	10.81	1.20	-47.77	-25.00	22.77
1RB, 5MHz, QPSK, Frequency:2535 MHz								
364.33	H	35.93	-72.20	0.00	0.60	-72.80	-25.00	47.80
39.64	V	50.09	-34.96	-26.23	0.17	-61.36	-25.00	36.36
5070.00	H	53.32	-56.77	10.58	0.94	-47.13	-25.00	22.13
5070.00	V	51.52	-57.31	10.58	0.94	-47.67	-25.00	22.67
7605.00	H	51.18	-55.54	10.88	1.21	-45.87	-25.00	20.87
7605.00	V	50.31	-56.83	10.88	1.21	-47.16	-25.00	22.16
1RB, 5MHz, QPSK, Frequency: 2567.5 MHz								
366.82	H	35.12	-72.96	0.00	0.60	-73.56	-25.00	48.56
40.08	V	50.16	-35.12	-26.29	0.17	-61.58	-25.00	36.58
5135.00	H	52.87	-57.18	10.75	0.96	-47.39	-25.00	22.39
5135.00	V	50.54	-58.26	10.75	0.96	-48.47	-25.00	23.47
7702.50	H	51.23	-55.12	10.96	1.23	-45.39	-25.00	20.39
7702.50	V	49.87	-56.89	10.96	1.23	-47.16	-25.00	22.16

LTE Band 12 (30MHz-10GHz):

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
1RB, 1.4MHz, QPSK, Frequency: 699.7MHz								
365.41	H	36.42	-71.69	0.00	0.60	-72.29	-13.00	59.29
40.57	V	51.33	-34.37	-25.65	0.17	-60.19	-13.00	47.19
1399.40	H	51.68	-64.93	8.62	0.53	-56.84	-13.00	43.84
1399.40	V	53.23	-63.73	8.62	0.53	-55.64	-13.00	42.64
2099.10	H	50.52	-65.33	9.84	0.57	-56.06	-13.00	43.06
2099.10	V	51.74	-64.58	9.84	0.57	-55.31	-13.00	42.31
2798.80	H	49.87	-64.46	9.80	0.69	-55.35	-13.00	42.35
2798.80	V	49.46	-64.94	9.80	0.69	-55.83	-13.00	42.83
1RB, 1.4MHz, QPSK, Frequency: 707.5 MHz								
365.52	H	36.29	-71.82	0.00	0.60	-72.42	-13.00	59.42
40.26	V	51.68	-33.75	-26.06	0.17	-59.98	-13.00	46.98
1415.00	H	51.35	-65.51	8.71	0.51	-57.31	-13.00	44.31
1415.00	V	52.65	-64.55	8.71	0.51	-56.35	-13.00	43.35
2122.50	H	50.44	-65.67	9.80	0.57	-56.44	-13.00	43.44
2122.50	V	51.13	-65.42	9.80	0.57	-56.19	-13.00	43.19
2830.00	H	49.58	-64.87	9.86	0.69	-55.70	-13.00	42.70
2830.00	V	49.46	-65.09	9.86	0.69	-55.92	-13.00	42.92
1RB, 1.4MHz, QPSK, Frequency: 715.3 MHz								
365.49	H	36.07	-72.04	0.00	0.60	-72.64	-13.00	59.64
40.64	V	51.06	-34.70	-25.56	0.17	-60.43	-13.00	47.43
1430.60	H	51.52	-65.58	8.80	0.49	-57.27	-13.00	44.27
1430.60	V	52.36	-65.07	8.80	0.49	-56.76	-13.00	43.76
2145.90	H	50.82	-65.56	9.77	0.58	-56.37	-13.00	43.37
2145.90	V	51.48	-65.31	9.77	0.58	-56.12	-13.00	43.12
2861.20	H	50.02	-64.55	9.92	0.70	-55.33	-13.00	42.33
2861.20	V	49.65	-65.04	9.92	0.70	-55.82	-13.00	42.82

LTE Band 13 (30MHz-10GHz):

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
1RB, 5MHz, QPSK, Frequency: 779.5MHz								
364.28	H	38.15	-69.98	0.00	0.60	-70.58	-13.00	57.58
41.29	V	50.28	-36.03	-24.70	0.17	-60.90	-13.00	47.90
1559.00	H	54.54	-63.96	9.29	0.41	-55.08	-40.00	15.08
1559.00	V	52.87	-65.80	9.29	0.41	-56.92	-40.00	16.92
2338.50	H	52.43	-63.31	9.46	0.60	-54.45	-13.00	41.45
2338.50	V	50.76	-65.10	9.46	0.60	-56.24	-13.00	43.24
3118.00	H	50.13	-62.19	10.29	0.73	-52.63	-13.00	39.63
3118.00	V	49.58	-63.67	10.29	0.73	-54.11	-13.00	41.11
1RB, 5MHz, QPSK, Frequency:784.5 MHz								
364.37	H	38.66	-69.47	0.00	0.60	-70.07	-13.00	57.07
41.33	V	50.74	-35.61	-24.64	0.17	-60.42	-13.00	47.42
1569.00	H	53.69	-64.86	9.31	0.41	-55.96	-40.00	15.96
1569.00	V	52.43	-66.27	9.31	0.41	-57.37	-40.00	17.37
2353.50	H	52.04	-63.56	9.43	0.60	-54.73	-13.00	41.73
2353.50	V	51.53	-64.21	9.43	0.60	-55.38	-13.00	42.38
3138.00	H	50.74	-61.52	10.31	0.73	-51.94	-13.00	38.94
3138.00	V	50.23	-62.60	10.31	0.73	-53.02	-13.00	40.02

LTE Band 14 (30MHz-10GHz):

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
1RB, 5MHz, QPSK, Frequency: 790.5MHz								
366.42	H	38.44	-69.65	0.00	0.60	-70.25	-13.00	57.25
39.52	V	49.29	-35.71	-26.17	0.17	-62.05	-13.00	49.05
1581.00	H	53.52	-65.09	9.33	0.42	-56.18	-40.00	16.18
1581.00	V	51.12	-67.63	9.33	0.42	-58.72	-40.00	18.72
2371.50	H	51.65	-63.78	9.41	0.60	-54.97	-13.00	41.97
2371.50	V	50.36	-65.24	9.41	0.60	-56.43	-13.00	43.43
3162.00	H	49.76	-62.42	10.33	0.73	-52.82	-13.00	39.82
3162.00	V	49.82	-62.51	10.33	0.73	-52.91	-13.00	39.91
1RB, 5MHz, QPSK, Frequency:795.5 MHz								
366.56	H	38.43	-69.66	0.00	0.60	-70.26	-13.00	57.26
39.88	V	49.52	-35.64	-26.34	0.17	-62.15	-13.00	49.15
1591.00	H	53.51	-65.15	9.35	0.42	-56.22	-40.00	16.22
1591.00	V	51.47	-67.31	9.35	0.42	-58.38	-40.00	18.38
2386.50	H	51.34	-63.95	9.38	0.61	-55.18	-13.00	42.18
2386.50	V	50.78	-64.70	9.38	0.61	-55.93	-13.00	42.93
3182.00	H	50.15	-61.97	10.35	0.73	-52.35	-13.00	39.35
3182.00	V	49.74	-62.17	10.35	0.73	-52.55	-13.00	39.55

LTE Band 17 (30MHz-10GHz):

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
1RB, 5MHz, QPSK, Frequency: 706.5MHz								
365.48	H	37.52	-70.59	0.00	0.60	-71.19	-13.00	58.19
39.71	V	51.33	-33.75	-26.26	0.17	-60.18	-13.00	47.18
1413.00	H	52.62	-64.21	8.70	0.52	-56.03	-13.00	43.03
1413.00	V	52.78	-64.39	8.70	0.52	-56.21	-13.00	43.21
2119.50	H	51.43	-64.64	9.81	0.57	-55.40	-13.00	42.40
2119.50	V	50.64	-65.88	9.81	0.57	-56.64	-13.00	43.64
2826.00	H	50.52	-63.92	9.85	0.69	-54.76	-13.00	41.76
2826.00	V	50.17	-64.36	9.85	0.69	-55.20	-13.00	42.20
1RB, 5MHz, QPSK, Frequency:710 MHz								
365.96	H	37.65	-70.45	0.00	0.60	-71.05	-13.00	58.05
39.73	V	51.85	-33.24	-26.27	0.17	-59.68	-13.00	46.68
1420.00	H	53.58	-63.36	8.74	0.51	-55.13	-13.00	42.13
1420.00	V	52.43	-64.84	8.74	0.51	-56.61	-13.00	43.61
2130.00	H	51.87	-64.33	9.79	0.58	-55.12	-13.00	42.12
2130.00	V	49.66	-66.97	9.79	0.58	-57.76	-13.00	44.76
2840.00	H	49.86	-64.63	9.88	0.69	-55.44	-13.00	42.44
2840.00	V	49.13	-65.46	9.88	0.69	-56.27	-13.00	43.27
1RB, 5MHz, QPSK, Frequency: 713.5 MHz								
365.28	H	38.05	-70.06	0.00	0.60	-70.66	-13.00	57.66
39.36	V	51.62	-33.31	-26.09	0.17	-59.57	-13.00	46.57
1427.00	H	53.62	-63.43	8.78	0.50	-55.15	-13.00	42.15
1427.00	V	52.14	-65.24	8.78	0.50	-56.96	-13.00	43.96
2140.50	H	51.79	-64.53	9.78	0.58	-55.33	-13.00	42.33
2140.50	V	50.81	-65.93	9.78	0.58	-56.73	-13.00	43.73
2854.00	H	50.26	-64.28	9.91	0.70	-55.07	-13.00	42.07
2854.00	V	49.92	-64.73	9.91	0.70	-55.52	-13.00	42.52

LTE Band 25 (30MHz-20GHz):

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
1RB, 1.4MHz, QPSK, Frequency: 1850.7 MHz								
365.22	H	37.61	-70.50	0.00	0.60	-71.10	-13.00	58.10
40.93	V	50.07	-35.93	-25.17	0.17	-61.27	-13.00	48.27
3701.40	H	51.52	-62.43	10.72	0.74	-52.45	-13.00	39.45
3701.40	V	51.65	-62.20	10.72	0.74	-52.22	-13.00	39.22
5552.10	H	50.33	-61.51	11.69	1.05	-50.87	-13.00	37.87
5552.10	V	50.59	-60.43	11.69	1.05	-49.79	-13.00	36.79
7402.80	H	50.43	-56.82	10.86	1.20	-47.16	-13.00	34.16
7402.80	V	50.56	-57.07	10.86	1.20	-47.41	-13.00	34.41
1RB, 1.4MHz, QPSK, Frequency:1882.5 MHz								
365.91	H	38.25	-69.85	0.00	0.60	-70.45	-13.00	57.45
40.38	V	50.72	-34.81	-25.90	0.17	-60.88	-13.00	47.88
3765.00	H	50.64	-63.08	10.76	0.75	-53.07	-13.00	40.07
3765.00	V	51.83	-61.69	10.76	0.75	-51.68	-13.00	38.68
5647.50	H	50.68	-61.40	11.67	1.05	-50.78	-13.00	37.78
5647.50	V	51.25	-60.07	11.67	1.05	-49.45	-13.00	36.45
7530.00	H	50.41	-56.59	10.82	1.20	-46.97	-13.00	33.97
7530.00	V	50.81	-56.62	10.82	1.20	-47.00	-13.00	34.00
1RB, 1.4MHz, QPSK, Frequency: 1914.3 MHz								
365.07	H	39.23	-68.89	0.00	0.60	-69.49	-13.00	56.49
40.03	V	50.76	-34.48	-26.36	0.17	-61.01	-13.00	48.01
3828.60	H	50.87	-62.60	10.80	0.76	-52.56	-13.00	39.56
3828.60	V	51.62	-61.57	10.80	0.76	-51.53	-13.00	38.53
5742.90	H	50.43	-62.01	11.65	1.05	-51.41	-13.00	38.41
5742.90	V	50.58	-60.99	11.65	1.05	-50.39	-13.00	37.39
7657.20	H	50.11	-56.41	10.93	1.22	-46.70	-13.00	33.70
7657.20	V	50.23	-56.70	10.93	1.22	-46.99	-13.00	33.99

LTE Band 26 (30MHz-10GHz):
814-824MHz(only for FCC):

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
1RB, 1.4MHz, QPSK, Frequency: 814.7 MHz								
365.42	H	38.61	-69.50	0.00	0.60	-70.10	-13.00	57.10
40.50	V	51.10	-34.54	-25.74	0.17	-60.45	-13.00	47.45
1629.40	H	53.52	-65.30	9.41	0.43	-56.32	-13.00	43.32
1629.40	V	52.14	-66.76	9.41	0.43	-57.78	-13.00	44.78
2444.10	H	56.44	-58.09	9.29	0.61	-49.41	-13.00	36.41
2444.10	V	51.68	-63.08	9.29	0.61	-54.40	-13.00	41.40
3258.80	H	50.72	-61.10	10.41	0.72	-51.41	-13.00	38.41
3258.80	V	50.43	-61.07	10.41	0.72	-51.38	-13.00	38.38
1RB, 1.4MHz, QPSK, Frequency:819 MHz								
366.85	H	38.15	-69.93	0.00	0.60	-70.53	-13.00	57.53
40.88	V	51.46	-34.50	-25.24	0.17	-59.91	-13.00	46.91
1638.00	H	53.48	-65.37	9.42	0.44	-56.39	-13.00	43.39
1638.00	V	52.54	-66.38	9.42	0.44	-57.40	-13.00	44.40
2457.00	H	56.71	-57.63	9.27	0.61	-48.97	-13.00	35.97
2457.00	V	51.37	-63.21	9.27	0.61	-54.55	-13.00	41.55
3276.00	H	50.46	-61.28	10.42	0.72	-51.58	-13.00	38.58
3276.00	V	50.79	-60.70	10.42	0.72	-51.00	-13.00	38.00
1RB, 1.4MHz, QPSK, Frequency: 823.3 MHz								
366.73	H	38.33	-69.76	0.00	0.60	-70.36	-13.00	57.36
40.70	V	51.65	-34.16	-25.48	0.17	-59.81	-13.00	46.81
1646.60	H	53.21	-65.68	9.43	0.44	-56.69	-13.00	43.69
1646.60	V	52.46	-66.49	9.43	0.44	-57.50	-13.00	44.50
2469.90	H	55.86	-58.30	9.25	0.62	-49.67	-13.00	36.67
2469.90	V	51.52	-62.88	9.25	0.62	-54.25	-13.00	41.25
3293.20	H	50.33	-61.34	10.43	0.72	-51.63	-13.00	38.63
3293.20	V	50.48	-61.00	10.43	0.72	-51.29	-13.00	38.29

**LTE Band 26 (30MHz-10GHz):
824-849MHz:**

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
1RB, 1.4MHz, QPSK, Frequency: 824.7 MHz								
364.93	H	36.71	-71.41	0.00	0.60	-72.01	-13.00	59.01
41.87	V	51.69	-35.12	-23.93	0.17	-59.22	-13.00	46.22
1649.40	H	53.11	-65.79	9.44	0.44	-56.79	-13.00	43.79
1649.40	V	52.74	-66.21	9.44	0.44	-57.21	-13.00	44.21
2474.10	H	55.58	-58.52	9.24	0.62	-49.90	-13.00	36.90
2474.10	V	57.62	-56.72	9.24	0.62	-48.10	-13.00	35.10
3298.80	H	51.43	-60.22	10.44	0.72	-50.50	-13.00	37.50
3298.80	V	50.76	-60.72	10.44	0.72	-51.00	-13.00	38.00
1RB, 1.4MHz, QPSK, Frequency: 836.5 MHz								
364.38	H	36.86	-71.27	0.00	0.60	-71.87	-13.00	58.87
41.93	V	51.75	-35.11	-23.85	0.17	-59.13	-13.00	46.13
1673.00	H	53.24	-65.75	9.48	0.45	-56.72	-13.00	43.72
1673.00	V	52.46	-66.56	9.48	0.45	-57.53	-13.00	44.53
2509.50	H	55.38	-58.32	9.22	0.62	-49.72	-13.00	36.72
2509.50	V	59.84	-54.05	9.22	0.62	-45.45	-13.00	32.45
3346.00	H	50.17	-61.61	10.48	0.72	-51.85	-13.00	38.85
3346.00	V	50.54	-60.96	10.48	0.72	-51.20	-13.00	38.20
1RB, 1.4MHz, QPSK, Frequency: 848.3 MHz								
367.82	H	35.99	-72.08	0.00	0.61	-72.69	-13.00	59.69
41.06	V	50.08	-36.04	-25.00	0.17	-61.21	-13.00	48.21
1696.60	H	52.57	-66.52	9.51	0.46	-57.47	-13.00	44.47
1696.60	V	52.43	-66.66	9.51	0.46	-57.61	-13.00	44.61
2544.90	H	57.42	-56.19	9.29	0.63	-47.53	-13.00	34.53
2544.90	V	58.76	-54.79	9.29	0.63	-46.13	-13.00	33.13
3393.20	H	52.14	-59.79	10.51	0.72	-50.00	-13.00	37.00
3393.20	V	51.31	-60.21	10.51	0.72	-50.42	-13.00	37.42

**LTE Band 41 (30MHz-27GHz):
For FCC(2496-2690MHz):**

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
1RB, 5MHz, QPSK, Frequency: 2498.5 MHz								
366.27	H	36.23	-71.86	0.00	0.60	-72.46	-25.00	47.46
41.45	V	49.27	-37.18	-24.49	0.17	-61.84	-25.00	36.84
4997.00	H	51.87	-58.64	10.40	0.92	-49.16	-25.00	24.16
4997.00	V	51.74	-57.57	10.40	0.92	-48.09	-25.00	23.09
7495.50	H	50.58	-56.54	10.80	1.20	-46.94	-25.00	21.94
7495.50	V	50.35	-57.20	10.80	1.20	-47.60	-25.00	22.60
1RB, 5MHz, QPSK, Frequency:2593 MHz								
365.71	H	36.37	-71.73	0.00	0.60	-72.33	-25.00	47.33
41.36	V	49.06	-37.31	-24.60	0.17	-62.08	-25.00	37.08
5186.00	H	52.25	-58.00	10.88	0.97	-48.09	-25.00	23.09
5186.00	V	51.54	-57.50	10.88	0.97	-47.59	-25.00	22.59
7779.00	H	50.43	-55.63	11.02	1.24	-45.85	-25.00	20.85
7779.00	V	50.52	-55.94	11.02	1.24	-46.16	-25.00	21.16
1RB, 5MHz, QPSK, Frequency: 2687.5 MHz								
366.68	H	38.48	-69.61	0.00	0.60	-70.21	-25.00	45.21
41.25	V	49.30	-36.98	-24.75	0.17	-61.90	-25.00	36.90
5375.00	H	52.13	-58.95	11.38	1.02	-48.59	-25.00	23.59
5375.00	V	51.27	-58.99	11.38	1.02	-48.63	-25.00	23.63
8062.50	H	50.23	-54.96	11.20	1.28	-45.04	-25.00	20.04
8062.50	V	50.46	-55.06	11.20	1.28	-45.14	-25.00	20.14

For IC(2500-2690MHz):

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
1RB, 5MHz, QPSK, Frequency: 2502.5 MHz								
366.68	H	36.54	-71.55	0.00	0.60	-72.15	-25.00	47.15
41.74	V	48.76	-37.94	-24.10	0.17	-62.21	-25.00	37.21
5005.00	H	51.21	-59.26	10.41	0.92	-49.77	-25.00	24.77
5005.00	V	50.19	-59.06	10.41	0.92	-49.57	-25.00	24.57
7507.50	H	49.89	-57.19	10.81	1.20	-47.58	-25.00	22.58
7507.50	V	50.24	-57.28	10.81	1.20	-47.67	-25.00	22.67
1RB, 5MHz, QPSK, Frequency:2595 MHz								
368.21	H	36.42	-71.64	0.00	0.61	-72.25	-25.00	47.25
42.33	V	49.11	-38.09	-23.32	0.17	-61.58	-25.00	36.58
5190.00	H	52.18	-58.08	10.89	0.97	-48.16	-25.00	23.16
5190.00	V	51.95	-57.10	10.89	0.97	-47.18	-25.00	22.18
7785.00	H	49.86	-56.18	11.03	1.24	-46.39	-25.00	21.39
7785.00	V	49.77	-56.66	11.03	1.24	-46.87	-25.00	21.87
1RB, 5MHz, QPSK, Frequency: 2687.5 MHz								
366.74	H	37.68	-70.41	0.00	0.60	-71.01	-25.00	46.01
41.48	V	49.36	-37.11	-24.45	0.17	-61.73	-25.00	36.73
5375.00	H	51.66	-59.42	11.38	1.02	-49.06	-25.00	24.06
5375.00	V	51.17	-59.09	11.38	1.02	-48.73	-25.00	23.73
8062.50	H	49.98	-55.21	11.20	1.28	-45.29	-25.00	20.29
8062.50	V	50.23	-55.29	11.20	1.28	-45.37	-25.00	20.37

LTE Band 66 (30MHz-18GHz):

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
1RB, 1.4MHz, QPSK, Frequency: 1710.7 MHz								
364.20	H	37.52	-70.61	0.00	0.60	-71.21	-13.00	58.21
41.29	V	49.58	-36.73	-24.70	0.17	-61.60	-13.00	48.60
3421.40	H	53.62	-58.78	10.54	0.72	-48.96	-13.00	35.96
3421.40	V	52.43	-59.61	10.54	0.72	-49.79	-13.00	36.79
5132.10	H	51.52	-58.52	10.74	0.95	-48.73	-13.00	35.73
5132.10	V	50.74	-58.05	10.74	0.95	-48.26	-13.00	35.26
1RB, 1.4MHz, QPSK, Frequency: 1745 MHz								
364.03	H	37.41	-70.72	0.00	0.60	-71.32	-13.00	58.32
41.79	V	49.76	-36.98	-24.04	0.17	-61.19	-13.00	48.19
3490.00	H	53.54	-60.32	10.59	0.72	-50.45	-13.00	37.45
3490.00	V	52.14	-61.56	10.59	0.72	-51.69	-13.00	38.69
5235.00	H	51.23	-59.53	11.01	0.98	-49.50	-13.00	36.50
5235.00	V	50.68	-58.90	11.01	0.98	-48.87	-13.00	35.87
1RB, 1.4MHz, QPSK, Frequency: 1779.3 MHz								
364.55	H	37.11	-71.01	0.00	0.60	-71.61	-13.00	58.61
41.86	V	49.70	-37.10	-23.94	0.17	-61.21	-13.00	48.21
3558.60	H	53.21	-60.82	10.64	0.73	-50.91	-13.00	37.91
3558.60	V	52.25	-61.66	10.64	0.73	-51.75	-13.00	38.75
5337.90	H	51.22	-60.12	11.28	1.01	-49.85	-13.00	36.85
5337.90	V	50.46	-59.90	11.28	1.01	-49.63	-13.00	36.63

LTE Band 71 (30MHz-10GHz):

Frequency (MHz)	Polar (H/V)	Receiver Reading (dBμV)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
1RB, 5MHz, QPSK, Frequency: 665.5 MHz								
364.19	H	36.74	-71.39	0.00	0.60	-71.99	-13.00	58.99
41.29	V	51.22	-35.09	-24.70	0.17	-59.96	-13.00	46.96
1331.00	H	53.58	-62.39	8.22	0.63	-54.80	-13.00	41.80
1331.00	V	53.41	-62.80	8.22	0.63	-55.21	-13.00	42.21
1996.50	H	52.15	-64.12	9.99	0.56	-54.69	-13.00	41.69
1996.50	V	51.12	-65.47	9.99	0.56	-56.04	-13.00	43.04
2662.00	H	50.36	-63.25	9.52	0.66	-54.39	-13.00	41.39
2662.00	V	49.87	-63.68	9.52	0.66	-54.82	-13.00	41.82
1RB, 5MHz, QPSK, Frequency:680.5 MHz								
364.47	H	36.81	-71.32	0.00	0.60	-71.92	-13.00	58.92
41.67	V	51.37	-35.27	-24.20	0.17	-59.64	-13.00	46.64
1361.00	H	54.52	-61.73	8.39	0.59	-53.93	-13.00	40.93
1361.00	V	52.36	-64.18	8.39	0.59	-56.38	-13.00	43.38
2041.50	H	52.71	-63.34	9.93	0.56	-53.97	-13.00	40.97
2041.50	V	50.23	-66.20	9.93	0.56	-56.83	-13.00	43.83
2722.00	H	49.65	-64.19	9.64	0.67	-55.22	-13.00	42.22
2722.00	V	49.87	-64.12	9.64	0.67	-55.15	-13.00	42.15
1RB, 5MHz, QPSK, Frequency: 695.5 MHz								
364.66	H	36.60	-71.52	0.00	0.60	-72.12	-13.00	59.12
41.83	V	51.68	-35.09	-23.98	0.17	-59.24	-13.00	46.24
1391.00	H	53.26	-63.28	8.57	0.55	-55.26	-13.00	42.26
1391.00	V	54.11	-62.76	8.57	0.55	-54.74	-13.00	41.74
2086.50	H	52.24	-63.66	9.86	0.57	-54.37	-13.00	41.37
2086.50	V	51.57	-64.78	9.86	0.57	-55.49	-13.00	42.49
2782.00	H	50.22	-64.00	9.76	0.68	-54.92	-13.00	41.92
2782.00	V	49.86	-64.45	9.76	0.68	-55.37	-13.00	42.37

Note:

- 1) The unit of Antenna Gain is dBd for frequency below 1GHz, and the unit of Antenna Gain is dBi for frequency above 1GHz.
- 2) Absolute Level = Substituted Level - Cable loss + Antenna Gain
- 3) Margin = Limit-Absolute Level

EXHIBIT A - EUT PHOTOGRAPHS

Please refer to the attachment 2602R50571E-RF-EXP EUT EXTERNAL PHOTOGRAPHS and
2602R50571E-RF-INP EUT INTERNAL PHOTOGRAPHS

EXHIBIT B - TEST SETUP PHOTOGRAPHS

Please refer to the attachment 2602R50571E-RF-00E-TSP TEST SETUP PHOTOGRAPHS.

******* END OF REPORT *******