

Prüfbericht-Nr.: Test report no.:	CN25JRLS 006	Auftrags-Nr.: Order no.:	168581279	Seite 1 von 11 Page 1 of 11
Kunden-Referenz-Nr.: Client reference no.:	N/A	Auftragsdatum: Order date:	2025-10-28	
Auftraggeber: Client:	Fujian Newland Payment Technology Co.,Ltd. No. B602, Building #1, Haixia Jingmao Plaza, Fuzhou Bonded Area 350015, Fujian, China			
Prüfgegenstand: Test item:	Unattended Terminal			
Bezeichnung / Typ-Nr.: Identification / Type no.:	U200			
Auftrags-Inhalt: Order content:	Test Report			
Prüfgrundlage: Test specification:	CFR Title 47 FCC Part 2: Section 2.1091 RSS-102 Issue 6 December 2023			
Wareneingangsdatum: Date of sample receipt:	2025-10-31	Please refer to Photo Document		
Prüfmuster-Nr.: Test sample no:	A004122957-005~012 A004122977-005~013			
Prüfzeitraum: Testing period:	2025-12-20 - 2025-12-31			
Ort der Prüfung: Place of testing:	TÜV Rheinland (Shenzhen) Co., Ltd.			
Prüflaboratorium: Testing laboratory:	TÜV Rheinland (Shenzhen) Co., Ltd.			
Prüfergebnis*: Test result*:	Pass			
geprüft von: tested by:			genehmigt von: authorized by:	
Datum: Date:	2026-01-15	Ausstellungsdatum: Issue date:		2026-01-15
Stellung / Position:	Sachverständige(r)/Expert	Stellung / Position:		Sachverständige(r)/Expert
Sonstiges / Other:	FCC ID: 2AM6U-NAU200C, IC: 25226-NAU200C, HVIN: U6C_33_01_00_00, U6C_33_03_00_00 PMN: Unattended Terminal			
Zustand des Prüfgegenstandes bei Anlieferung: Condition of the test item at delivery:	Prüfmuster vollständig und unbeschädigt Test item complete and undamaged			
* Legende:	P(ass) = entspricht o.g. Prüfgrundlage(n) F(ail) = entspricht nicht o.g. Prüfgrundlage(n) N/A = nicht anwendbar N/T = nicht getestet			
* Legend:	P(ass) = passed a.m. test specification(s) F(ail) = failed a.m. test specification(s) N/A = not applicable N/T = not tested			
Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens. <i>This test report only relates to the above mentioned test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any test mark.</i>				

Prüfbericht-Nr.: CN25JRLS 006
Test report no.:

Seite 2 von 11
Page 2 of 11

Anmerkungen
Remarks

1	Alle eingesetzten Prüfmittel waren zum angegebenen Prüfzeitraum gemäß eines festgelegten Kalibrierungsprogramms unseres Prüfhauses kalibriert. Sie entsprechen den in den Prüfprogrammen hinterlegten Anforderungen. Die Rückverfolgbarkeit der eingesetzten Prüfmittel ist durch die Einhaltung der Regelungen unseres Managementsystems gegeben. Detaillierte Informationen bezüglich Prüfkonditionen, Prüfequipment und Messunsicherheiten sind im Prüflabor vorhanden und können auf Wunsch bereitgestellt werden. <i>The equipment used during the specified testing period was calibrated according to our test laboratory calibration program. The equipment fulfils the requirements included in the relevant standards. The traceability of the test equipment used is ensured by compliance with the regulations of our management system. Detailed information regarding test conditions, equipment and measurement uncertainty is available in the test laboratory and could be provided on request.</i>
2	Wie vertraglich vereinbart, wurde dieses Dokument nur digital unterzeichnet. Der TÜV Rheinland hat nicht überprüft, welche rechtlichen oder sonstigen diesbezüglichen Anforderungen für dieses Dokument gelten. Diese Überprüfung liegt in der Verantwortung des Benutzers dieses Dokuments. Auf Verlangen des Kunden kann der TÜV Rheinland die Gültigkeit der digitalen Signatur durch ein gesondertes Dokument bestätigen. Diese Anfrage ist an unseren Vertrieb zu richten. Eine Umweltgebühr für einen solchen zusätzlichen Service wird erhoben. Informationen zur Verifizierung der Authentizität unserer Dokumente erhalten Sie auf folgender Webseite: go.tuv.com/digital-signature <i>As contractually agreed, this document has been signed digitally only. TUV Rheinland has not verified and unable to verify which legal or other pertaining requirements are applicable for this document. Such verification is within the responsibility of the user of this document. Upon request by its client, TUV Rheinland can confirm the validity of the digital signature by a separate document. Such request shall be addressed to our Sales department. An environmental fee for such additional service will be charged. For information on verifying the authenticity of our documents, please visit the following website: go.tuv.com/digital-signature</i>
3	Prüfklausel mit der Note * wurden an qualifizierte Unterauftragnehmer vergeben und sind unter der jeweiligen Prüfklausel des Berichts beschrieben. Abweichungen von Prüfspezifikation(en) oder Kundenanforderungen sind in der jeweiligen Prüfklausel im Bericht aufgeführt. <i>Test clauses with remark of * are subcontracted to qualified subcontractors and described under the respective test clause in the report.</i> <i>Deviations of testing specification(s) or customer requirements are listed in specific test clause in the report.</i>
4	Die Entscheidungsregel für Konformitätserklärungen basierend auf numerischen Messergebnissen in diesem Prüfbericht basiert auf der "Null-Grenzwert-Regel" und der "Einfachen Akzeptanz" gemäß ILAC G8:2019 und IEC Guide 115:2023, es sei denn, in der auf Seite 1 dieses Berichts genannten angewandten Norm ist etwas anderes festgelegt oder vom Kunden gewünscht. Dies bedeutet, dass die Messunsicherheit nicht berücksichtigt wird und daher auch nicht im Prüfbericht angegeben wird. Zu weiteren Informationen bezüglich des Risikos durch diese Entscheidungsregel siehe ILAC G8:2019. <i>The decision rule for statements of conformity, based on numerical measurement results, in this test report is based on the "Zero Guard Band Rule" and "Simple Acceptance" in accordance with ILAC G8:2019 and IEC Guide 115:2023, unless otherwise specified in the applied standard mentioned on Page 1 of this report or requested by the customer. This means that measurement uncertainty is not taken in account and hence also not declared in the test report. For additional information to the resulting risk based of this decision rule please refer to ILAC G8:2019.</i>

Prüfbericht - Nr.: CN25JRLS 006
Test Report No.:

Seite 3 von 11
Page 3 of 11

Test Summary

3.1.1 RF EXPOSURE COMPLIANCE
RESULT: Pass

Contents

1.	TEST SITES.....	5
1.1	TEST FACILITIES.....	5
1.2	TRACEABILITY.....	5
1.3	CALIBRATION.....	5
1.4	LOCATION OF ORIGINAL DATA.....	5
1.5	STATUS OF FACILITY USED FOR TESTING.....	5
2.	GENERAL PRODUCT INFORMATION.....	6
2.1	GENERAL DESCRIPTION.....	6
2.2	RATING AND SYSTEM DETAILS.....	6
3.	TEST RESULTS.....	7
3.1	RF EXPOSURE EVALUATION.....	7
3.1.1	RF Exposure Compliance.....	7

1. Test Sites

1.1 Test Facilities

TÜV Rheinland (Shenzhen) Co., Ltd.

2-3F, 101 & 102, No.2, Nuclear Power Industrial Park, Fuming Community, Fucheng Street, Longhua District, Shenzhen 518000, China

FCC Accreditation Designation No.: 694916

ISED wireless device testing laboratory: 25069

1.2 Traceability

All measurement equipment calibrations are traceable to NIST or where calibration is performed outside the United States, to equivalent nationally recognized standards organizations.

1.3 Calibration

Equipment requiring calibration is calibrated periodically by the manufacturer or according to manufacturer's specifications. Additionally all equipment is verified for proper performance on a regular basis using in house standards or comparisons.

1.4 Location of Original Data

The original copies of all test data taken during actual testing were attached at Appendixes of this report and delivered to the applicant. A copy has been retained in the TÜV Rheinland (Shenzhen) file for certification follow-up purposes.

1.5 Status of Facility Used for Testing

The TÜV Rheinland (Shenzhen) Co., Ltd. Test facility located at 2-3F, 101 & 102, No.2, Nuclear Power Industrial Park, Fuming Community, Fucheng Street, Longhua District, Shenzhen 518000, China is listed on the US Federal Communications Commission list of facilities approved to perform measurements.

2. General Product Information

2.1 General Description

The Product is Unattended Terminal which supports LTE, Bluetooth, 2.4GHz Wi-Fi, 5GHz Wi-Fi and NFC functions.

For details refer to the User Manual, Technical Description and Circuit Diagram.

2.2 Rating and System details

Table 1: Technical Specification of EUT

General Information of EUT	Value
Kind of Equipment:	Unattended Terminal
Type Designation:	U200
FCC ID:	2AM6U-NAU200C
IC:	25226-NAU200C
HVIN:	U6C_33_01_00_00, U6C_33_03_00_00 The differences between the two configurations is that the U6C_33_01_00_00 has one more brightness sensor, which has no impact on RF characteristics at all. And this difference was evaluated in EMC test.
PMN:	Unattended Terminal
Operating Voltage:	DC 7-48V
Testing Voltage:	DC 12V via the AC/DC adapter (AC 120V, 60Hz)

3. Test Results

3.1 RF Exposure Evaluation

3.1.1 RF Exposure Compliance

RESULT:
Pass

Test standard : CFR Title 47 FCC Part 2.1091
RSS-102 Issue 6
KDB 447498 D01 General RF Exposure Guidance v06

Limit : Table 1 of CFR Title 47 FCC Part 1.1310
Section 6.6 of RSS-102 Issue 6

This device is mobile device, and the applicant declares that the minimum separation distance is greater than 20cm. Therefore, MPE measurement or computational modelling should be used to determine compliance.

3.1.1.1 RF Exposure Compliance Requirement for FCC

a) Radio Frequency Exposure Limit

According to ANSI/IEEE C95.1-1992, the criteria listed in Table 1 shall be used to evaluate the environmental impact of human exposure to radio frequency (RF) radiation as specified in §1.1310.

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3-3.0	614	1.63	*(100)	6
3.0-30	1842/f	4.89/f	*(900/f ²)	6
30-300	61.4	0.163	1.0	6
300-1500			f/300	6
1500-100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500			f/1500	30
1500-100,000			1.0	30

b) Radio Frequency Exposure Calculation Formula

$$S = \frac{PG}{4\pi R^2}$$

where: S = power density (in appropriate units, e.g. mW/cm²)
P = power input to the antenna (in appropriate units, e.g., mW)
G = power gain of the antenna in the direction of interest relative to an isotropic radiator
R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

or:

$$S = \frac{EIRP}{4\pi R^2}$$

where: EIRP = equivalent (or effective) isotropically radiated power

c) RF Exposure Calculations for FCC, stand-alone mode

Operating Mode	Max. average EIRP incl. tune-up (dBm)	Distance (cm)	MPE (mW/cm ²)	Limit (mW/cm ²)	Verdict
*Bluetooth	12	20	0.003	1.0	Pass
*2.4GHz Wi-Fi	22	20	0.032	1.0	Pass
*5GHz Wi-Fi	22	20	0.032	1.0	Pass
**NFC	Less than -20dBm	20	< 0.0001	0.1	Pass

Note: *refer to reports CN25JRLS 002 and 003 for output power.
**refer to the report CN25JRLS 005.

Prüfbericht - Nr.: CN25JRLS 006
Test Report No.:
Seite 9 von 11
Page 9 of 11

Operating Mode	Max. average Power incl. tune-up (dBm)	Distance (cm)	Antenna gain (dBi)	MPE (mW/cm ²)	Limit (mW/cm ²)	Verdict
LTE Band 2	25.00	20	2.73	0.118	1.0000	Pass
LTE Band 4	25.00	20	2.29	0.107	1.0000	Pass
LTE Band 5	25.00	20	2.78	0.119	0.5493	Pass
LTE Band 7	25.00	20	0.29	0.067	1.0000	Pass
LTE Band 12	25.00	20	-0.65	0.054	0.4660	Pass
LTE Band 13	25.00	20	1.67	0.092	0.5180	Pass
LTE Band 14	25.00	20	2.14	0.103	0.5253	Pass
LTE Band 17	25.00	20	-0.65	0.054	0.4693	Pass
LTE Band 25	25.00	20	2.73	0.118	1.0000	Pass
LTE Band 26	25.00	20	2.78	0.119	0.5427	Pass
LTE Band 41	25.00	20	2.98	0.125	1.0000	Pass
LTE Band 66	25.00	20	2.29	0.107	1.0000	Pass
LTE Band 71	25.00	20	-0.91	0.051	0.4420	Pass

Note: Refer to the report CN25JRLS 004.

d) RF Exposure Calculations for FCC, Simultaneous mode

Co-location Mode (Worst-case)	Sum of the MPE ratios	Limit	Verdict
Bluetooth + Wi-Fi+ NFC+LTE B5	0.003/1+0.032/1+0.119/0.549=0.252	1.0	Pass

e) Conclusion

Therefore the maximum calculations result of above are meet the requirement of Radio Frequency Exposure (MPE) limit.

3.1.1.2 RSS-102 Exemption Limits for Routine Evaluation – RF Exposure Evaluation

Field reference level (FRL) exposure evaluation is required if the separation distance between the user and/or bystander and the device's radiating element is greater than 20 cm (i.e. mobile devices), except when the device operates as follows:

- below 20 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 1 W (adjusted for tune-up tolerance);
- at or above 20 MHz and below 48 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than $4.49/f^{0.5}$ W (adjusted for tune-up tolerance), where f is in MHz;
- at or above 48 MHz and below 300 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 0.6 W (adjusted for tune-up tolerance);
- at or above 300 MHz and below 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than $1.31 \times 10^{-2} f^{0.6834}$ W (adjusted for tune-up tolerance), where f is in MHz;
- at or above 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 5 W (adjusted for tune-up tolerance).

In these cases, the information contained in the RF exposure technical brief may be limited to information that demonstrates how the e.i.r.p. was derived.

a) RF Exposure Calculations for ISED, Stand-alone mode

Operating Mode	Max. average EIRP incl. tune-up (dBm)	Distance (cm)	Maximum EIRP (W)	Threshold power (W)	Verdict
*Bluetooth	12	20	0.0158	2.68	Pass
*2.4GHz Wi-Fi	22	20	0.1585	2.70	Pass
*5GHz Wi-Fi	22	20	0.1585	4.52	Pass
**NFC	Less than -20dBm	20	< 0.001	1.0	Pass

Note: *refer to reports CN25L5XC 002 and 003 for output power.

**refer to the report CN25L5XC 004.

Operating Mode	Max. average Power incl. tune-up (dBm)	Distance (cm)	Antenna gain (dBi)	EIRP (W)	Threshold power (W)	Verdict
LTE Band 2	25.00	20	2.73	0.593	2.239	Pass
LTE Band 4	25.00	20	2.29	0.536	2.122	Pass
LTE Band 5	25.00	20	2.78	0.600	1.288	Pass
LTE Band 7	25.00	20	0.29	0.338	2.751	Pass
LTE Band 12	25.00	20	-0.65	0.272	1.151	Pass
LTE Band 13	25.00	20	1.67	0.465	1.238	Pass
LTE Band 14	25.00	20	2.14	0.518	1.250	Pass
LTE Band 17	25.00	20	-0.65	0.272	1.157	Pass
LTE Band 25	25.00	20	2.73	0.593	2.239	Pass
LTE Band 26	25.00	20	2.78	0.600	1.278	Pass
LTE Band 41	25.00	20	2.98	0.628	2.748	Pass

Prüfbericht - Nr.: CN25JRLS 006
Test Report No.:Seite 11 von 11
Page 11 of 11

LTE Band 66	25.00	20	2.29	0.536	2.122	Pass
LTE Band 71	25.00	20	-0.91	0.256	1.076	Pass
Note: *refer to reports CN25JRLS 002 and 003 for output power. **refer to the report CN25JRLS 005.						

b) RF Exposure Calculations for ISED, Simultaneous mode

Co-location Mode	Sum of the ratios	Limit	Verdict
Bluetooth + Wi-Fi+ NFC+LTE B5	$0.0158/2.68 + 0.158/2.7 +$ $0.600/1.288 = 0.53$	1.0	Pass

c) Conclusion

"RF Radiation Exposure Statement Caution: This Transmitter must be installed to provide a separation distance of at least 20 cm from all persons."