

System Check_H2450

DUT: Dipole 2450 MHz; Type:D2450V2; SN:927

Communication System: CW; Frequency: 2450 MHz;Duty Cycle: 1:1
Medium: H2450 Medium parameters used: $f = 2450\text{ MHz}$; $\sigma = 1.83\text{ S/m}$; $\epsilon_r = 39.52$; $\rho = 1000\text{ kg/m}^3$
Ambient Temperature : $22.8\text{ }^{\circ}\text{C}$; Liquid Temperature : $22.6\text{ }^{\circ}\text{C}$

DASY5 Configuration:
- Probe: EX3DV4 - SN3970; Calibrated: 2025/6/5
- Electronics: DAE4 Sn1418; Calibrated: 2025/6/5
- Phantom: SAM; Type: QD000P40CD; Serial: TP:1794
- Measurement SW: DASY52, Version 52.10 (4); SEMCAD X Version 14.6.14 (7501)

Pin=250mW/Area Scan (61x61x1): Interpolated grid: $dx=1.500\text{ mm}$, $dy=1.500\text{ mm}$
Maximum value of SAR (interpolated) = 21.8 W/kg

Pin=250mW/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$
Reference Value = 99.334 V/m ; Power Drift = 0.09 dB
Peak SAR (extrapolated) = 31.7 W/kg
SAR(1 g) = 13.12 W/kg ; SAR(10 g) = 6.14 W/kg
Maximum value of SAR (measured) = 21.5 W/kg

