

SAR TEST REPORT

FCC ID: 2AM8GCHAMELEON5R

Product: RUGGEDIZED HAND-HELD DEVICE

Model No.: CHAMELEON 5R SINGLE

Additional Model: CHAMELEON 5R DUAL

Trade Mark: CHAMELEON

Report No.: TCT210218E025

Issued Date: Feb. 25, 2021

Issued for:

Guangzhou Lie Dun Electronics Technology CO., Ltd
No.4 plant of No.43 South International Trade Avenue, Hualong Town, Panyu
District, Guangzhou, Guangdong, China

Issued By:

Shenzhen Tongce Testing Lab.
1B/F, Building 1, Yibaolai Industrial Park, Qiaotou, Fuyong, Baoan District,
Shenzhen, Guangdong, China
TEL: +86-755-27673339
FAX: +86-755-27673332

Note: This report shall not be reproduced except in full, without the written approval of Shenzhen Tongce Testing Lab..

This document may be altered or revised by Shenzhen Tongce Testing Lab. personnel only, and shall be noted in the revision section of the document. The test results in the report only apply to the tested sample.

TABLE OF CONTENTS

1.	Test Certification	3
2.	Facilities and Accreditations	4
2.1.	Facilities.....	4
2.2.	Location	4
2.3.	Environment Condition:	4
3.	Test Result Summary	5
4.	EUT Description.....	7
5.	RF Exposure Limit.....	9
6.	SAR Measurement System Configuration.....	10
6.1.	SAR Measurement Set-up	10
6.2.	E-field Probe.....	11
6.3.	Phantom.....	11
6.4.	Device Holder	12
6.5.	Data Storage and Evaluation.....	13
6.6.	Position of the wireless device in relation to the phantom	14
6.7.	Tissue Dielectric Parameters	17
6.8.	Tissue-equivalent Liquid Properties	18
6.9.	System Check.....	19
7.	Measurement Procedure.....	20
8.	Conducted Output Power	23
9.	Exposure Position Consideration	42
9.1.	EUT Antenna Location.....	42
9.2.	Test Position Consideration.....	42
10.	SAR Test Results Summary	43
10.1.	Head 1g SAR Data	43
10.2.	Body-Worn 1g SAR Data.....	47
10.3.	Hotspot 1g SAR Data.....	49
10.4.	Simultaneous Transmission Conclusion	52
10.5.	SAR Simultaneous Transmission Analysis.....	54
10.6.	Measurement Uncertainty (450MHz-3GHz).....	62
10.7.	Test Equipment List	64
11.	System Check Results	65
12.	SAR Test Data.....	93
13.	Appendix A: EUT Photos	175
14.	Appendix C: Probe Calibration Certificate	180
15.	Appendix D: Dipole Calibration Report	197
16.	Appendix E: SAR SYSTEM VALIDATION.....	265
17.	Appendix F: The Check Data of Impedance and Return Loss.....	267

1. Test Certification

Product:	RUGGEDIZED HAND-HELD DEVICE
Model No.:	CHAMELEON 5R SINGLE
Additional Model No.	CHAMELEON 5R DUAL
Trade Mark:	CHAMELEON
Applicant:	Guangzhou Lie Dun Electronics Technology CO., Ltd
Address:	No.4 plant of No.43 South International Trade Avenue, Hualong Town, Panyu District, Guangzhou, Guangdong, China
Manufacturer:	Guangzhou Lie Dun Electronics Technology CO., Ltd
Address:	No.4 plant of No.43 South International Trade Avenue, Hualong Town, Panyu District, Guangzhou, Guangdong, China
Date of Test:	Feb. 18, 2021 – Feb. 24, 2021
SAR Max. Values:	0.45 W/Kg (1g) for head; 0.74 W/Kg (1g) for Body-worn; 0.81 W/Kg (1g) for Hotspot;
Applicable Standards:	FCC 47 CFR § 2.1093 IEEE1528-2013:Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate in the Human Head from Wireless Communications Devices: Measurement Techniques KDB447498 D01:General RF Exposure Guidance v06 KDB865664 D01:SAR measurement 100MHz to 6GHz v01r04 KDB865664 D02:RF Exposure Reporting v01r02. KDB941225 D01:3G SAR Procedures v03r01 KDB248227 D01:802.11 wi-fi SAR v02r02 KDB941225 D05:SAR for LTE devices v02r05 KDB941225 D06:Hotspot Mode v02r01 KDB941225 D07:UMPC Mini Tablet v01r02 KDB690783 D01:SAR Listings on Grant v01r03

The above equipment has been tested by Shenzhen Tongce Testing Lab. and found compliance with the requirements set forth in the technical standards mentioned above. The results of testing in this report apply only to the product/system, which was tested. Other similar equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties.

Tested By:



karl

Date:

Oct. 10, 2020

Reviewed By:



Beryl Zhao

Date:

Oct. 12, 2020

Approved By:



Tomsin

Date:

Oct 12, 2020

2. Facilities and Accreditations

2.1. Facilities

The test facility is recognized, certified, or accredited by the following organizations:

- FCC - Registration No.: 645098

Shenzhen Tongce Testing Lab

The 3m Semi-anechoic chamber has been registered and fully described in a report with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files.

- IC - Registration No.: 10668A-1

The 3m Semi-anechoic chamber of Shenzhen Tongce Testing Lab.. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing

2.2. Location

Shenzhen Tongce Testing Lab

Address: 1B/F., Building 1, Yibaolai Industrial Park, Qiaotou, Fuyong, Baoan District, Shenzhen, Guangdong, China

2.3. Environment Condition:

Temperature:	18°C ~25°C
Humidity:	35%~75% RH
Atmospheric Pressure:	1011 mbar

3. Test Result Summary

The maximum results of Specific Absorption Rate (SAR) found during test as bellows:
<Highest Reported standalone SAR Summary>

Exposure Position	Frequency Band	Reported SAR (W/kg)	Equipment Class	Highest Reported SAR (W/kg)
Head 1-g SAR	GSM 850	0.44	PCE	0.44
	GSM 1900	0.40		
	WCDMA Band II	0.40		
	WCDMA Band V	0.36		
	LTE Band 2	0.30		
	LTE Band 4	0.36		
	LTE Band 5	0.24		
	LTE Band 7	0.24		
	LTE Band 26	0.24		
	LTE Band 41	0.24		
	WLAN 2.4 GHz	0.21	DTS	
	WLAN 5.2 GHz	0.22	NII	
	WLAN 5.8 GHz	0.29	NII	
Body-worn 1-g SAR (10 mm Gap)	GSM 850	0.66	PCE	0.74
	GSM 1900	0.63		
	WCDMA Band II	0.74		
	WCDMA Band V	0.35		
	LTE Band 2	0.47		
	LTE Band 4	0.59		
	LTE Band 5	0.23		
	LTE Band 7	0.32		
	LTE Band 26	0.54		
	LTE Band 41	0.31		
	WLAN 2.4 GHz	0.18	DTS	
	WLAN 5.2 GHz	0.27	NII	
	WLAN 5.8 GHz	0.20	NII	
Hotspot 1-g SAR (10 mm Gap)	GSM 850	0.71	PCE	0.81
	GSM 1900	0.63		
	WCDMA Band II	0.81		
	WCDMA Band V	0.35		
	LTE Band 2	0.50		
	LTE Band 4	0.61		
	LTE Band 5	0.24		
	LTE Band 7	0.35		
	LTE Band 26	0.62		
	LTE Band 41	0.34		
	WLAN 2.4 GHz	0.20	DTS	
	WLAN 5.2 GHz	0.28	NII	
	WLAN 5.8 GHz	0.38	NII	

<Highest Reported simultaneous SAR Summary>

Exposure Position	Frequency Band	Highest Reported Simultaneous Transmission SAR (W/kg)
Head 1-g SAR	GSM850 + WIFI 5G	0.71
Body 1-g SAR (10 mm Gap)	WCDMA Band II + WIFI 5G	1.01
Hotspot 1-g SAR (10 mm Gap)	WCDMA Band II + WIFI 5G	1.19

Note:

1. The highest simultaneous transmission is scalar summation of Reported standalone SAR per FCC KDB 690783 D01 v01r03, and scalar SAR summation of all possible simultaneous transmission scenarios are < 1.6W/kg.
2. This device is compliance with Specific Absorption Rate (SAR) for general population/uncontrolled exposure limits specified in FCC 47 CFR part 2 (2.1093) and ANSI/IEEE C95.1-2005, and had been tested in accordance with the measurement methods and procedures specified in IEEE 1528-2013.
3. This EUT owns four cards, after we perform the pretest for these two SIM card; we found the SIM 1 is the worst case, so its result is recorded in this report.

4. EUT Description

Product Name:	RUGGEDIZED HAND-HELD DEVICE
Model :	CHAMELEON 5R SINGLE
Additional Model:	CHAMELEON 5R DUAL
Trade Mark:	CHAMELEON
Power Supply:	Rechargeable Li-ion Battery DC3.8V
2G	
Operation Band:	GSM850, GSM1900
Supported type:	GSM/GPRS
Power Class:	GSM850:Power Class 5; GSM1900:Power Class 0
Modulation Type:	GMSK for GSM/GPRS
GSM Release Version:	R99
GPRS Multislot Class:	12
EGPRS Multislot Class:	N/A
3G	
Operation Band:	FDD Band II & FDD Band V
Power Class:	Power Class 3
Modulation Type:	QPSK for WCDMA/HSDPA/HSUPA
WCDMA Release Version:	R99
HSDPA Release Version:	Release 5
HSUPA Release Version:	Release 6
DC-HSUPA Release Version:	Not Supported
LTE	
Operation Band:	LTE Band 2 & LTE Band 4 & LTE Band 5 & LTE Band 7& LTE Band 26 & LTE Band 41
Power Class:	Power Class 3
Modulation Type:	QPSK &16-QAM for LTE
Wi-Fi 2.4G	
Supported type:	802.11b/802.11g/802.11n
Modulation:	802.11b: DSSS 802.11g/802.11n:OFDM
Operation frequency:	802.11b/802.11g/802.11n(HT20):2412MHz~2462MHz; 802.11n(HT40):2422MHz~2452MHz
Channel number:	802.11b/802.11g/802.11n(HT20):11; 802.11n(HT40):7
Channel separation:	5MHz

Bluetooth	
Bluetooth Version:	Supported 4.0
Modulation:	GFSK(1Mbps)
Operation frequency:	2402MHz~2480MHz
Channel number:	40
Channel separation:	2MHz
Wi-Fi 5G	
Operation Frequency:	Band 1: 5180 MHz -5240 MHz Band 4: 5725 MHz -5850 MHz
Channel Bandwidth:	802.11a: 20MHz 802.11n: 20MHz, 40MHz 802.11ac: 20MHz, 40MHz, 80MHz
Modulation Technology:	Orthogonal Frequency Division Multiplexing(OFDM)
Modulation Type:	256QAM, 64QAM, 16QAM, BPSK, QPSK

5. RF Exposure Limit

Type Exposure	SAR (W/kg)
	Uncontrolled Exposure Limit
Spatial Peak SAR (averaged over any 1 g of tissue)	1.60
Spatial Peak SAR (hands/wrists/feet/ankles averaged over 10g)	4.00
Spatial Peak SAR (averaged over the whole body)	0.08
Note: 1. The Spatial Peak value of the SAR averaged over any 1 gram of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time. 2. The Spatial Average value of the SAR averaged over the whole body. 3. The Spatial Peak value of the SAR averaged over any 10 grams of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.	

6. SAR Measurement System Configuration

6.1. SAR Measurement Set-up

The OPENSAR system for performing compliance tests consist of the following items:

A standard high precision 6-axis robot (KUKA) with controller and software.

KUKA Control Panel (KCP)

A dosimetric probe, i.e., an isotropic E-field probe optimized and calibrated for usage in tissue simulating liquid. The probe is equipped with a Video Positioning System (VPS).

The stress sensor is composed with mechanical and electronic when the electronic part detects a change on the electro-mechanical switch; it sends an “Emergency signal” to the robot controller that to stop robot’s moves A computer operating Windows XP.


OPENSAR software Remote control with teaches pendant and additional circuitry for robot safety such as warning lamps, etc.

The SAM phantom enabling testing left-hand right-hand and body usage.

The Position device for handheld EUT

Tissue simulating liquid mixed according to the given recipes.

System validation dipoles to validate the proper functioning of the system.



KUKA SAR Test Sysytem Configuration

6.2. E-field Probe

The SAR measurement is conducted with the dosimetric probe (manufactured by MVG). The probe is specially designed and calibrated for use in liquid with high permittivity. The dosimetric probe has special calibration in liquid at different frequency. This probe has a built in optical surface detection system to prevent from collision with phantom.

Probe Specification

Construction Symmetrical design with triangular core
Interleaved sensors
Built-in shielding against static charges
PEEK enclosure material (resistant to organic solvents, e.g., DGBE)
Calibration ISO/IEC 17025 calibration service available.

Device Type	COMOSAR DOSIMETRIC E FIELD PROBE
Manufacturer	MVG
Model	SSE2
Serial Number	SN 41/18 EPG0331
Frequency Range of Probe	0.40 GHz-6GHz
Resistance of Three Dipoles at Connector	Dipole 1:R1=0.181MΩ Dipole 2:R3=0.193MΩ Dipole 3:R3=0.195MΩ




Photo of E-Field Probe

6.3. Phantom

The SAM Phantom SAM120 is constructed of a fiberglass shell integrated in a wooden table. The shape of the shell is in compliance with the specification set in IEEE P1528 and CENELEC IEC 62209-1, IEC 62209-2:2010.

The phantom enables the dosimetric evaluation of left and right hand phone usage as well as body mounted usage at the flat phantom region.


A cover prevents the evaporation of the liquid.

Reference markings on the Phantom allow the complete setup of all predefined phantom positions and measurement grids by manually teaching three points in the robot

System checking was performed using the flat section, whilst Head SAR tests used the left and right head profile sections.

Body SAR testing also used the flat section between the head profiles.


Name: COMOSAR IEEE SAM PHANTOM
S/N: SN 19/15 SAM 120
Manufacture: MVG

**SAM Twin Phantom**

6.4. Device Holder

In combination with the Generic Twin Phantom SAM120, the Mounting Device enables the rotation of the mounted transmitter in spherical coordinates whereby the rotation points is the ear opening. The devices can be easily, accurately, and repeatedly positioned according to the FCC and CENELEC specifications.

The device holder can be locked at different phantom locations (left head, right head, flat phantom).

**COMOSAR Mobile
phone positioning
system**

6.5. Data Storage and Evaluation

Data Storage

The OPENSAR software stores the acquired data from the data acquisition electronics as raw data (in microvolt readings from the probe sensors), together with all necessary software parameters for the data evaluation (probe calibration data, liquid parameters and device frequency and modulation data) in measurement files. The software evaluates the desired unit and format for output each time the data is visualized or exported. This allows verification of the complete software setup even after the measurement and allows correction of incorrect parameter settings. For example, if a measurement has been performed with a wrong crest factor parameter in the device setup, the parameter can be corrected afterwards and the data can be re-evaluated.

The measured data can be visualized or exported in different units or formats, depending on the selected probe type ([V/m], [A/m], [°C], [mW/g], [mW/cm²], [dBrel], etc.). Some of these units are not available in certain situations or show meaningless results, e.g., a SAR output in a lossless media will always be zero. Raw data can also be exported to perform the evaluation with other software packages.

Data Evaluation

The OPENSAR software automatically executes the following procedures to calculate the field units from the microvolt readings at the probe connector. The parameters used in the evaluation are stored in the configuration modules of the software:

Probe parameters:	- Sensitivity	Normi, ai0, ai1, ai2
	- Conversion factor	ConvFi
	- Diode compression point	Dcpi
Device parameters:	- Frequency	f
	- Crest factor	cf
Media parameters:	- Conductivity	σ
	- Density	ρ

These parameters must be set correctly in the software. They can be found in the component documents or they can be imported into the software from the configuration files issued for the OPENSAR components. In the direct measuring mode of the millimeter option, the parameters of the actual system setup are used. In the scan visualization and export modes, the parameters stored in the corresponding document files are used.

The first step of the evaluation is a linearization of the filtered input signal to account for the compression characteristics of the detector diode. The compensation depends on the input signal, the diode type and the DC-transmission factor from the diode to the evaluation electronics. If the exciting field is pulsed, the crest factor of the signal must be known to correctly compensate for peak power. The formula for each channel can be given as:

$$V_i = U_i + U_i^2 \cdot c f / d c p i$$

With	V_i	= compensated signal of channel i	(i = x, y, z)
	U_i	= input signal of channel i	(i = x, y, z)
	cf	= crest factor of exciting field	(MVG parameter)
	dcpi	= diode compression point	(MVG parameter)

From the compensated input signals the primary field data for each channel can be evaluated:

$$\text{E-field probes: } E_i = (V_i / \text{Normi} \cdot \text{ConvF})^{1/2}$$

$$\text{H-field probes: } H_i = (V_i)^{1/2} \cdot (ai0 + ai1 f + ai2 f^2) / f$$

With	V_i	= compensated signal of channel i	(i = x, y, z)
	Normi	= sensor sensitivity of channel i	(i = x, y, z)
		[mV/(V/m)²] for E-field Probes	
	ConvF	= sensitivity enhancement in solution	
	aij	= sensor sensitivity factors for H-field probes	
	f	= carrier frequency [GHz]	
	E_i	= electric field strength of channel i in V/m	
	H_i	= magnetic field strength of channel i in A/m	

The RSS value of the field components gives the total field strength (Hermitian magnitude):

$$E_{tot} = (E_x^2 + E_y^2 + E_z^2)^{1/2}$$

The primary field data are used to calculate the derived field units.

$$SAR = (E_{tot})^2 \cdot \sigma / (\rho \cdot 1000)$$

with SAR = local specific absorption rate in mW/g
 E_{tot} = total field strength in V/m
 σ = conductivity in [mho/m] or [Siemens/m]
 ρ = equivalent tissue density in g/cm³


Note that the density is normally set to 1 (or 1.06), to account for actual brain density rather than the density of the simulation liquid. The power flow density is calculated assuming the excitation field to be a free space field.

6.6. Position of the wireless device in relation to the phantom

Handset Reference Points


$$P_{pwe} = E_{tot}^2 / 3770 \text{ or } P_{pwe} = H_{tot}^2 \cdot 37.7$$

With P_{pwe} = equivalent power density of a plane wave in mW/cm²
 E_{tot} = total electric field strength in V/m
 H_{tot} = total magnetic field strength in A/m




W_t Width of the handset at the level of the acoustic
 W_b Width of the bottom of the handset
A Midpoint of the width w_t of the handset at the level of the acoustic output
B Midpoint of the width w_b of the bottom of the handset

Positioning for Cheek / Touch



Positioning for Ear / 15° Tilt



Body Worn Accessory Configurations

To position the device parallel to the phantom surface with either keypad up or down.

To adjust the device parallel to the flat phantom.

To adjust the distance between the device surface and the flat phantom to 15mm or holster surface and the flat phantom to 0 mm.





Illustration for Body Worn Position

Wireless Router (Hotspot) Configurations

Some battery-operated handsets have the capability to transmit and receive internet connectivity through simultaneous transmission of WIFI in conjunction with a separate licensed transmitter. The FCC has provided guidance in KDB Publication 941225 D06 where SAR test considerations for handsets (L x W ≥


9 cm x 5 cm) are based on a composite test separation distance of 10 mm from the front, back and edges of the device with antennas 2.5 cm or closer to the edge of the device, determined from general mixed use conditions for this type of devices. Since the hotspot SAR results may overlap with the body-worn accessory SAR requirements, the more conservative configurations can be considered, thus excluding some body-worn accessory SAR tests.

When the user enables the personal wireless router functions for the handset, actual operations include simultaneous transmission of both the WIFI transmitter and another licensed transmitter. Both transmitters often do not transmit at the same transmitting frequency and thus cannot be evaluated for SAR under actual use conditions. Therefore, SAR must be evaluated for each frequency transmission and mode separately and summed with the WIFI transmitter according to KDB 648474 publication procedures. The "Portable Hotspot" feature on the handset was NOT activated, to ensure the SAR measurements were evaluated for a single transmission frequency RF signal.

**Illustration for Hotspot Position****Limb-worn device**

A limb-worn device is a unit whose intended use includes being strapped to the arm or leg of the user while transmitting (except in idle mode). It is similar to a body-worn device. Therefore, the test positions of 6.1.4.4 also apply. The strap shall be opened so that it is divided into two parts as shown in Figure 9. The device shall be positioned directly against the phantom surface with the strap straightened as much as possible and the back of the device towards the phantom.

If the strap cannot normally be opened to allow placing in direct contact with the phantom surface, it may be necessary to break the strap of the device but ensuring to not damage the antenna.

**Test position for limb-worn devices**

6.7. Tissue Dielectric Parameters

The liquid used for the frequency range of 100MHz-6G consisted of water, sugar, salt and Cellulose. The liquid has been previously proven to be suited for worst-case. The following Table shows the detail solution. It's satisfying the latest tissue dielectric parameters requirements proposed by the IEEE 1528 and IEC 62209.

The simulating liquids should be checked at the beginning of a series of SAR measurements to determine of the determine of the dielectric parameter are within the tolerances of the specified target values. The measured conductivity and relative permittivity should be within $\pm 5\%$ of the target values.

The following materials are used for producing the tissue-equivalent materials

Targets for tissue simulating liquid

Frequency (MHz)	Liquid Type	Liquid Type (σ)	$\pm 5\%$ Range	Permittivity (ϵ)	$\pm 5\%$ Range
300	Head	0.87	0.83~0.91	45.3	43.04~47.57
450	Head	0.87	0.83~0.91	43.5	41.33~45.68
835	Head	0.90	0.86~0.95	41.5	39.43~43.58
900	Head	0.97	0.92~1.02	41.5	39.43~43.58
1800-2000	Head	1.40	1.33~1.47	40.0	38.00~42.00
2450	Head	1.80	1.71~1.89	39.2	37.24~41.16
2600	Head	1.96	1.86~2.06	39.0	37.05~40.95
3000	Head	2.40	2.28~2.52	38.5	36.58~40.43
5800	Head	5.27	5.01~5.53	35.3	33.54~37.07
300	Body	0.92	0.87~0.97	58.2	55.29~61.11
450	Body	0.94	0.89~0.99	56.7	53.87~59.54
835	Body	0.97	0.92~1.02	55.2	52.44~57.96
900	Body	1.05	1.00~1.10	55.0	52.25~57.75
1800-2000	Body	1.52	1.44~1.60	53.3	50.64~55.97
2450	Body	1.95	1.85~2.05	52.7	50.07~55.34
2600	Body	2.16	2.05~2.27	52.5	49.88~55.13
3000	Body	2.73	2.60~2.87	52.0	49.40~54.60
5800	Body	6.00	5.70~6.30	48.2	45.79~50.61

(ϵ_r = relative permittivity, σ = conductivity and $\rho = 1000 \text{ kg/m}^3$)

6.8. Tissue-equivalent Liquid Properties


Test Date dd/mm/yy	Temp °C	Tissue Type	Measured Frequency (MHz)	ϵ_r	σ (s/m)	Dev ϵ_r (%)	Dev σ (%)
02/18/2021	22°C	835H	825	41.43	0.86	-0.17	-4.44
			835	41.42	0.87	-0.19	-3.33
			850	40.39	0.88	-2.67	-2.22
02/19/2021	22°C	1800H	1710	39.11	1.34	-2.23	-4.29
			1720	39.10	1.35	-2.25	-3.57
			1750	39.08	1.37	-2.30	-2.14
			1800	39.07	1.38	-2.33	-1.43
02/20/2021	22°C	1900H	1850	39.11	1.34	-2.23	-4.29
			1880	39.10	1.35	-2.25	-3.57
			1900	39.08	1.37	-2.30	-2.14
			1910	39.07	1.38	-2.33	-1.43
02/22/2021	22°C	2450H	2410	37.84	1.79	-3.47	-0.56
			2435	37.85	1.81	-3.44	0.56
			2450	37.82	1.83	-3.52	1.67
			2460	37.80	1.84	-3.57	2.22
02/23/2021	22°C	2600H	20850	38.86	1.93	-0.36	-1.53
			21100	38.85	1.92	-0.39	-2.04
			21350	38.89	1.90	-0.28	-3.06
02/23/2021	22°C	5200H	5200	36.68	4.45	-3.32	-4.04
02/23/2021	22°C	5800H	5800	34.81	5.08	-3.49	-4.14
02/18/2021	22°C	835B	825	55.26	0.93	0.11	-4.12
			835	55.24	0.94	0.07	-3.09
			850	55.21	0.97	0.02	0.00
02/19/2021	22°C	1800B	1710	53.34	1.49	0.08	-1.97
			1720	53.32	1.50	0.04	-1.32
			1750	53.31	1.51	0.02	-0.66
			1800	53.29	1.53	-0.02	0.66
02/20/2021	22°C	1900B	1850	53.34	1.49	0.08	-1.97
			1880	53.32	1.50	0.04	-1.32
			1900	53.31	1.51	0.02	-0.66
			1910	53.29	1.53	-0.02	0.66
02/22/2021	22°C	2450B	2410	54.65	1.97	3.70	1.03
			2435	54.63	1.98	3.66	1.54
			2450	54.62	2.01	3.64	3.08
			2460	54.59	2.03	3.59	4.10
02/23/2021	22°C	2600B	20850	51.96	2.10	-1.02	-2.78
			21100	52.01	2.11	-0.93	-2.31
			21350	52.13	2.13	-0.70	-1.39
02/23/2021	22°C	5200B	5200	48.94	1.92	-1.54	-1.56
02/23/2021	22°C	5800B	5800	48.20	5.95	1.54	2.77

6.9. System Check

The SAR system must be validated against its performance specifications before it is deployed. When SAR probe and system component or software are changed, upgraded or recalibrated, these must be validated with the SAR system(s) that operates with such component. Reference dipoles are used with the required tissue-equivalent media for system validation.

System check results have to be equal or near the values determined during dipole calibration with the relevant liquids and test system ($\pm 10\%$).

System check is performed regularly on all frequency bands where tests are performed with the OPENSAR system.



System Check Set-up

Verification Results

Frequency (MHz)	Liquid Type	Measured Value in 100mW (W/kg)		Normalized to 1W (W/kg)		Target Value (W/kg)		Deviation (%)	
		1 g Average	10 g Average	1 g Average	10 g Average	1 g Average	10 g Average	1 g Average	10 g Average
835	Head	0.89	0.57	8.90	5.70	9.53	6.12	-6.61	-6.86
1800	Head	3.75	2.20	37.53	21.98	37.67	20.23	-0.37	8.65
1900	Head	3.58	1.90	35.80	19.00	39.26	20.49	-8.81	-7.27
2450	Head	4.99	2.36	49.90	23.60	53.26	24.15	-6.31	-2.28
2600	Head	5.41	2.43	54.14	24.30	54.31	24.14	-0.31	0.66
5200	Head	5.01	15.90	50.10	159.00	51.70	161.10	-3.09	-1.30
5800	Head	5.25	18.20	52.50	182.00	51.40	181.10	2.14	0.33
835	Body	0.95	0.63	9.50	6.30	9.62	6.44	-1.25	-2.17
1800	Body	3.78	2.05	37.79	20.46	37.69	20.57	0.27	-0.54
1900	Body	3.77	1.99	37.70	19.90	38.71	20.53	-2.61	-3.07
2450	Body	5.07	2.42	50.70	24.16	50.63	23.40	0.14	3.25
2600	Body	5.37	2.38	53.65	23.81	53.26	23.89	0.73	-0.33
5200	Body	17.63	6.02	173.80	59.97	172.00	60.96	1.05	-1.62
5800	Body	18.30	6.18	181.20	61.50	182.25	62.59	-0.58	-1.74

Comparing to the original SAR value provided by MVG, the verification data should be within its specification of 10%. Below table shows the target SAR and measured SAR after normalized to 1W input power. The table as below indicates the system performance check can meet the variation criterion and the plots can be referred to Section 10 of this report.

7. Measurement Procedure

Conducted power measurement

For WWAN power measurement, use base station simulator to configure EUT WWAN transition in conducted connection with RF cable, at maximum power in each supported wireless interface and frequency band.

Read the WWAN RF power level from the base station simulator.

For WLAN/BT power measurement, use engineering software to configure EUT WLAN/BT continuously transmission, at maximum RF power in each supported wireless interface and frequency band.

Connect EUT RF port through RF cable to the power meter or spectrum analyser, and measure WLAN/BT output power.

Conducted power measurement

Use base station simulator to configure EUT WWAN transmission in radiated connection, and engineering software to configure EUT WLAN/BT continuously transmission, at maximum RF power, in the highest power channel.

Place the EUT in positions as Appendix B demonstrates.

Set scan area, grid size and other setting on the MVG software.

Measure SAR results for the highest power channel on each testing position.

Find out the largest SAR result on these testing positions of each band.

Measure SAR results for other channels in worst SAR testing position if the Reported SAR or highest power channel is larger than 0.8 W/kg.

According to the test standard, the recommended procedure for assessing the peak spatial-average SAR value consists of the following steps:

Power reference measurement

Area scan

Zoom scan

Power drift measurement

Spatial Peak SAR Evaluation

The procedure for spatial peak SAR evaluation has been implemented according to the test standard. It can be conducted for 1g and 10g, as well as for user-specific masses. The MVG software includes all numerical procedures necessary to evaluate the spatial peak SAR value.

The base for the evaluation is a "cube" measurement. The measured volume must include the 1g and 10g cubes with the highest averaged SAR values. For that purpose, the center of the measured volume is aligned to the interpolated peak SAR value of a previously performed area scan.

The entire evaluation of the spatial peak values is performed within the post-processing engine (SEMCAD). The system always gives the maximum values for 1g and 10g cubes. The algorithm to find the cube with highest averaged SAR is divided into the following stages:

Extraction of the measured data (grid and values) from the Zoom Scan.

Calculation of the SAR value at every measurement point based on all stored data (A/D values and measurement parameters).

Generation of a high-resolution mesh within the measured volume.

Interpolation of all measured values from the measurement grid to the high-resolution grid

Extrapolation of the entire 3-D field distribution to the phantom surface over the distance from sensor to surface

Calculation of the averaged SAR within masses of 1g and 10g.

Power Reference Measurement

The Power Reference Measurement and Power Drift Measurement are for monitoring the power drift of the device under test in the batch process. The minimum distance of probe sensors to surface determines the closest measurement point to phantom surface. This distance cannot be smaller than the distance of sensor calibration points to probe tip as defined in the probe properties

Area & Zoom Scan Procedures

First Area Scan is used to locate the approximate location(s) of the local peak SAR value(s). The measurement grid within an Area Scan is defined by the grid extent, grid step size and grid offset. Next, in order to determine the EM field distribution in a three-dimensional spatial extension, Zoom Scan is required. The Zoom Scan is performed around the highest E-field value to determine the averaged SAR-distribution over 10g. Area scan and zoom scan resolution setting follows KDB 865664 D01v01r03 quoted below.

			$\leq 3\text{ GHz}$	$> 3\text{ GHz}$
Maximum distance from closest measurement point (geometric center of probe sensors) to phantom surface			$5\text{ mm} \pm 1\text{ mm}$	$\frac{1}{2} \cdot \delta \cdot \ln(2)\text{ mm} \pm 0.5\text{ mm}$
Maximum probe angle from probe axis to phantom surface normal at the measurement location			$30^\circ \pm 1^\circ$	$20^\circ \pm 1^\circ$
Maximum area scan spatial resolution: $\Delta x_{\text{Area}}, \Delta y_{\text{Area}}$			$\leq 2\text{ GHz}: \leq 15\text{ mm}$ $2 - 3\text{ GHz}: \leq 12\text{ mm}$	$3 - 4\text{ GHz}: \leq 12\text{ mm}$ $4 - 6\text{ GHz}: \leq 10\text{ mm}$
			When the x or y dimension of the test device, in the measurement plane orientation, is smaller than the above, the measurement resolution must be $\leq$ the corresponding x or y dimension of the test device with at least one measurement point on the test device.	
Maximum zoom scan spatial resolution: $\Delta x_{\text{Zoom}}, \Delta y_{\text{Zoom}}$			$\leq 2\text{ GHz}: \leq 8\text{ mm}$ $2 - 3\text{ GHz}: \leq 5\text{ mm}^*$	$3 - 4\text{ GHz}: \leq 5\text{ mm}^*$ $4 - 6\text{ GHz}: \leq 4\text{ mm}^*$
Maximum zoom scan spatial resolution, normal to phantom surface	uniform grid: $\Delta z_{\text{Zoom}}(n)$		$\leq 5\text{ mm}$	$3 - 4\text{ GHz}: \leq 4\text{ mm}$ $4 - 5\text{ GHz}: \leq 3\text{ mm}$ $5 - 6\text{ GHz}: \leq 2\text{ mm}$
	graded grid	$\Delta z_{\text{Zoom}}(1)$: between 1 st two points closest to phantom surface	$\leq 4\text{ mm}$	$3 - 4\text{ GHz}: \leq 3\text{ mm}$ $4 - 5\text{ GHz}: \leq 2.5\text{ mm}$ $5 - 6\text{ GHz}: \leq 2\text{ mm}$
		$\Delta z_{\text{Zoom}}(n>1)$: between subsequent points	$\leq 1.5 \cdot \Delta z_{\text{Zoom}}(n-1)\text{ mm}$	
Minimum zoom scan volume	x, y, z		$\geq 30\text{ mm}$	$3 - 4\text{ GHz}: \geq 28\text{ mm}$ $4 - 5\text{ GHz}: \geq 25\text{ mm}$ $5 - 6\text{ GHz}: \geq 22\text{ mm}$
Note: δ is the penetration depth of a plane-wave at normal incidence to the tissue medium; see IEEE Std 1528-2013 for details.				
* When zoom scan is required and the <u>reported</u> SAR from the <i>area scan based 1-g SAR estimation</i> procedures of KDB Publication 447498 is $\leq 1.4\text{ W/kg}$, $\leq 8\text{ mm}$, $\leq 7\text{ mm}$ and $\leq 5\text{ mm}$ zoom scan resolution may be applied, respectively, for 2 GHz to 3 GHz, 3 GHz to 4 GHz and 4 GHz to 6 GHz.				

Volume Scan Procedures

The volume scan is used for assess overlapping SAR distributions for antennas transmitting in different frequency bands. It is equivalent to an oversized zoom scan used in standalone measurements. The measurement volume will be used to enclose all the simultaneous transmitting antennas. For antennas transmitting simultaneously in different frequency bands, the volume scan is measured separately in each frequency band. In order to sum correctly to compute the 1g aggregate SAR, the EUT remain in the same test position for all measurements and all volume scan use the same spatial resolution and grid spacing. When all volume scan were completed, the software, SEMCAD post-processor scan combine and subsequently superpose these measurement data to calculating the multiband SAR.

SAR Averaged Methods

In MVG, the interpolation and extrapolation are both based on the modified Quadratic Shepard's method. The interpolation scheme combines a least-square fitted function method and a weighted average method which are the two basic types of computational interpolation and approximation.

Extrapolation routines are used to obtain SAR values between the lowest measurement points and the inner phantom surface. The extrapolation distance is determined by the surface detection distance and the probe sensor offset. The uncertainty increases with the extrapolation distance. To keep the uncertainty within 1% for the 1g and 10g cubes, the extrapolation distance should not be larger than 5 mm.

Power Drift Monitoring

All SAR testing is under the EUT install full charged battery and transmit maximum output power. In MVG measurement software, the power reference measurement and power drift measurement procedures are used for monitoring the power drift of EUT during SAR test. Both these procedures measure the field at a specified reference position before and after the SAR testing. The software will calculate the field difference in dB. If the power drifts more than 5%, the SAR will be retested.

Power Drift measurement

The drift job measures the field at the same location as the most recent reference job within the same procedure, and with the same settings. The drift measurement gives the field difference in dB from the reading conducted within the last reference measurement. Several drift measurements are possible for

Measurement Uncertainty

Per KDB 865664 D01 SAR Measurement 100KHz to 6GHz ,when the highest measurement 1-g SAR within a frequency band is <1.5W/kg, the extensive SAR measurement uncertainty analysis described IEEE Std 1528-2013 is not required in SAR report submitted for equipment approval.

8. Conducted Output Power

Band: GSM 850	Measured Power (dBm)			Calculation (dB)	Averaged Power (dBm)		
Channel	128	190	251		128	190	251
Frequency	824.2	836.6	848.8		824.2	836.6	848.8
GSM (GMSK, Voice)	34.19	33.76	33.75	-9.03	25.16	24.73	24.72
GPRS (GMSK, 1-slot)	33.77	33.75	33.74	-9.03	24.74	24.72	24.71
GPRS (GMSK, 2-slot)	32.25	32.80	32.13	-6.02	26.23	26.78	26.11
GPRS (GMSK, 3-slot)	30.41	30.46	30.15	-4.26	26.15	26.20	25.89
GPRS (GMSK, 4-slot)	28.43	28.32	28.21	-3.01	25.42	25.31	25.20
EGPRS (1-slot)	27.25	27.15	27.14	-9.03	18.22	18.12	18.11
EGPRS (2-slot)	26.10	26.66	25.88	-6.02	20.08	20.64	19.86
EGPRS (3-slot)	24.41	24.34	24.38	-4.26	20.15	20.08	20.12
EGPRS (4-slot)	23.33	23.10	23.17	-3.01	20.32	20.09	20.16

Note:

1. Division Factors

To average the power, the division factor is as follows:

1TX-slot = 1 transmit time slot out of 8 time slots=> conducted power divided by (8/1) => -9.03dB

2TX-slots = 2 transmit time slots out of 8 time slots=> conducted power divided by (8/2) => -6.02dB

3TX-slots = 3 transmit time slots out of 8 time slots=> conducted power divided by (8/3) => -4.26dB

4TX-slots = 4 transmit time slots out of 8 time slots=> conducted power divided by (8/4) => -3.01dB

2. According to the conducted power as above, the body measurements are performed with 1Tx slots for 850MHz for GPRS.

3. The device do not support power reduction, so power of hotspot activated as the same as hotspot disabled

Band: GSM 1900	Measured Power (dBm)			Calculation (dB)	Averaged Power (dBm)		
Channel	512	661	810		512	661	810
Frequency	1850.2	1880.0	1909.8		1850.2	1880.0	1909.8
GSM (GMSK, Voice)	30.09	30.42	29.97	-9.03	21.06	21.39	20.94
GPRS (GMSK, 1-slot)	30.10	29.97	29.94	-9.03	21.07	20.94	20.91
GPRS (GMSK, 2-slot)	29.10	28.89	28.84	-6.02	23.08	22.87	22.82
GPRS (GMSK, 3-slot)	27.08	26.79	26.72	-4.26	22.82	22.53	22.46
GPRS (GMSK, 4-slot)	25.28	25.04	25.04	-3.01	22.27	22.03	22.03
EGPRS (1-slot)	25.98	25.63	25.62	-9.03	16.95	16.60	16.59
EGPRS (2-slot)	24.71	24.42	24.34	-6.02	18.69	18.40	18.32
EGPRS (3-slot)	23.41	23.15	23.12	-4.26	19.15	18.89	18.86
EGPRS (4-slot)	22.21	21.82	21.90	-3.01	19.20	18.81	18.89

Note:

- Division Factors
To average the power, the division factor is as follows:
1TX-slot = 1 transmit time slot out of 8 time slots=> conducted power divided by (8/1) => -9.03dB
2TX-slots = 2 transmit time slots out of 8 time slots=> conducted power divided by (8/2) => -6.02dB
3TX-slots = 3 transmit time slots out of 8 time slots=> conducted power divided by (8/3) => -4.26dB
4TX-slots = 4 transmit time slots out of 8 time slots=> conducted power divided by (8/4) => -3.01dB
- According to the conducted power as above, the body measurements are performed with 1Tx slots for 1900MHz for GPRS.
- The device do not support power reduction, so power of hotspot activated as the same as hotspot disabled

Band	WCDMA Band II			WCDMA Band V		
Channel	9262	9400	9538	4132	4182	4233
Frequency	1852.40	1880.00	1907.60	826.40	836.40	846.60
RMC 12.2Kbps	23.25	23.23	23.31	23.45	23.42	23.43
HSDPA Subtest-1	20.82	21.14	21.17	20.47	20.77	20.65
HSDPA Subtest-2	20.85	21.21	21.26	20.54	20.74	20.64
HSDPA Subtest-3	20.85	21.20	21.26	20.55	20.74	20.64
HSDPA Subtest-4	20.85	20.12	21.24	20.53	20.74	20.62
HSUPA Subtest-1	20.98	21.54	21.13	21.73	22.06	21.97
HSUPA Subtest-2	21.47	21.56	21.58	21.83	22.12	22.05
HSUPA Subtest-3	21.47	21.61	21.61	21.82	22.11	20.95
HSUPA Subtest-4	23.08	23.17	23.21	21.89	22.10	22.03
HSUPA Subtest-5	21.45	21.58	20.99	21.90	22.10	22.03

Note:

1. According to the power listed above, the HSDPA and HSUPA were not determined for SAR testing.
2. The default test configuration is to measure SAR with an established radio link between the EUT and a communication test set using a 12.2kbps RMC(reference measurement channel) configuration in test loop mode
3. The device do not support power reduction, so power of hotspot activated as the same as hotspot disabled

WLAN 2.4G						
Mode	802.11b			802.11g		
Channel	1	6	11	1	6	11
Frequency	2412	2437	2462	2412	2437	2462
Average Power (dBm)	16.26	16.30	16.29	16.89	16.06	16.54
Mode	802.11n(HT20)			802.11n(HT40)		
Channel	1	6	11	3	6	9
Frequency	2412	2437	2462	2422	2437	2452
Average Power (dBm)	16.12	16.13	16.57	14.20	14.12	14.34

WLAN 5.2G						
Mode	IEEE 802.11a			IEEE 802.11n HT20		
Channel	36	40	48	36	40	48
Frequency	5180	5200	5240	5180	5200	5240
Average Power (dBm)	16.27	15.91	16.36	16.71	16.22	16.25
Mode	IEEE 802.11n HT40			IEEE 802.11ac VHT20		
Channel	38		46	36	40	48
Frequency	5190		5230	5180	5200	5240
Average Power (dBm)	14.98		15.20	16.33	16.21	16.35
Mode	EEE 802.11ac VHT40			IEEE 802.11ac VHT80		
Channel	38		46	42		
Frequency	5190		5230	5210		
Average Power (dBm)	15.22		15.27	13.62		
WLAN 5.8G						
Mode	IEEE 802.11a			IEEE 802.11n HT20		
Channel	149	157	165	149	157	165
Frequency	5745	5785	5825	5745	5785	5825
Average Power (dBm)	16.81	16.95	16.46	16.78	15.93	15.51
Mode	IEEE 802.11n HT40			IEEE 802.11ac VHT20		
Channel	151		159	149	157	165
Frequency	5755		5795	5745	5785	5825
Average Power (dBm)	15.47		15.73	17.72	17.07	16.39
Mode	EEE 802.11ac VHT40			IEEE 802.11ac VHT80		
Channel	151		159	155		
Frequency	5755		5795	5775		
Average Power (dBm)	16.03		15.57	14.95		

Note

1. Per KDB 248227 D01 v02r02, choose the highest output power channel to test SAR and determine further SAR exclusion.
2. The output power of all data rate were prescan , just the worst case (the lowest data rate) of all mode were shown in report

Bluetooth						
Mode	GFSK			Pi/4DQPSK		
Channel	0	39	78	0	39	78
Frequency	2402	2441	2480	2402	2441	2480
Average Power (dBm)	/	/	/	/	/	/
Mode	8DPSK			BLE		
Channel	0	39	78	0	20	39
Frequency	2402	2441	2480	2402	2442	2480
Average Power (dBm)	/	/	/	0.498	1.163	0.153

Channel	Frequency (GHz)	Max. Tune-up Power (dBm)	Max. Power (mW)	Test distance (mm)	Result	Exclusion thresholds for 1-g SAR	Exclusion thresholds for 10-g SAR
.20	2.442	1.50	1.41	5	0.44	3.0	7.5

Note

- Per KDB 447498 D01v06, the 1-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$$
for 1-g SAR, where
 ·f(GHz) is the RF channel transmit frequency in GHz
 ·Power and distance are rounded to the nearest mW and mm before calculation
 ·The result is rounded to one decimal place for comparison
- Base on the result of note1, RF exposure evaluation of BLE is not required.
- Per KDB 248227 D01 v02r02, choose the highest output power channel to test SAR and determine further SAR exclusion.
- The output power of all data rate were prescan, just the worst case (the lowest data rate) of all mode were shown in report.

Conducted Power of LTE Band 2						
Bandwidth	Modulation	RB size	RB offset	Channel	Channel	Channel
				18625	18900	19175
5MHz	QPSK	1	0.00	23.45	23.70	23.54
			12.00	23.87	24.08	23.77
			24.00	23.52	23.63	23.48
		12	0.00	22.61	22.79	22.60
			6.00	22.60	22.73	22.62
			11.00	22.60	22.71	22.58
		25	0.00	22.57	22.77	22.56
	16QAM	1	0.00	22.38	22.41	22.24
			12.00	22.70	22.85	22.53
			24.00	22.38	22.46	22.23
		12	0.00	21.51	21.63	21.49
			6.00	21.52	21.65	21.51
			11.00	21.44	21.58	21.44
		25	0.00	21.48	21.60	21.48
Bandwidth	Modulation	RB size	RB offset	Channel	Channel	Channel
				18650	18900	19150
10MHz	QPSK	1	0.00	23.69	23.83	23.90
			24.00	23.80	24.01	23.83
			49.00	23.81	23.74	23.77
		25	0.00	22.60	22.78	22.74
			12.00	22.63	22.84	22.68
			25.00	22.61	22.73	22.60
		50	0.00	22.60	22.81	22.61
	16QAM	1	0.00	22.45	22.74	22.64
			24.00	22.58	22.73	22.77
			49.00	22.31	22.70	22.35
		25	0.00	21.51	21.69	21.54
			24.00	21.55	21.74	21.47
			49.00	21.52	21.67	21.50
		50	0.00	21.47	21.69	21.50

Conducted Power of LTE Band 2

Bandwidth	Modulation	RB size	RB offset	Channel	Channel	Channel
				18675	18900	19125
15MHz	QPSK	1	0.00	23.78	23.72	23.62
			37.00	24.06	24.05	23.80
			74.00	23.89	23.66	23.45
		36	0.00	22.64	22.79	22.80
			16.00	22.68	22.79	22.75
			35.00	22.73	22.73	22.65
		75	0.00	22.66	22.81	22.71
	16QAM	1	0.00	22.40	22.63	22.59
			37.00	22.65	22.99	22.64
			74.00	22.65	22.55	22.57
		36	0.00	21.52	21.67	21.65
			16.00	21.56	21.67	21.65
			35.00	21.67	21.64	21.49
		75	0.00	21.55	21.65	21.61
Bandwidth	Modulation	RB size	RB offset	Channel	Channel	Channel
				18700	18900	19100
20MHz	QPSK	1	0.00	23.49	23.86	23.77
			49.00	23.77	23.88	23.97
			99.00	23.77	23.59	23.68
		50	0.00	22.68	22.77	22.67
			24.00	22.75	22.78	22.73
			49.00	22.78	22.78	22.64
		100	0.00	22.70	22.81	22.66
	16QAM	1	0.00	22.45	22.49	22.65
			49.00	22.72	22.87	22.83
			99.00	22.72	22.40	22.62
		50	0.00	21.50	21.69	21.57
			24.00	21.65	21.67	21.66
			49.00	21.65	21.69	21.49
		100	0.00	21.56	21.69	21.53

LTE Band 4

Conducted Power of LTE Band 4						
Bandwidth	Modulation	RB size	RB offset	Channel	Channel	Channel
				19957	20175	20393
1.4MHz	QPSK	1	0.00	23.46	23.37	23.46
			3.00	23.56	23.45	23.65
			5.00	23.50	23.33	23.58
		3	0.00	23.34	23.46	23.42
			1.00	23.49	23.53	23.54
			3.00	23.39	23.45	23.51
		6	0.00	22.42	22.52	22.52
	16QAM	1	0.00	22.11	22.34	22.25
			3.00	22.27	22.44	22.49
			5.00	22.09	22.18	22.37
		3	0.00	22.42	22.61	22.34
			1.00	22.45	22.68	22.42
			3.00	22.42	22.60	22.44
		6	0.00	21.29	21.37	21.48
Bandwidth	Modulation	RB size	RB offset	Channel	Channel	Channel
				19965	20175	20385
3MHz	QPSK	1	0.00	23.46	23.55	23.30
			7.00	23.46	23.46	23.33
			14.00	23.39	23.40	23.45
		8	0.00	22.47	22.56	22.43
			4.00	22.42	22.50	22.39
			7.00	22.43	22.42	22.39
		15	0.00	22.45	22.53	22.41
	16QAM	1	0.00	22.07	22.37	22.08
			7.00	22.05	22.44	22.03
			14.00	21.97	22.34	22.33
		8	0.00	21.28	21.39	21.31
			4.00	21.30	21.49	21.37
			7.00	21.33	21.33	21.27
		15	0.00	21.28	21.48	21.25

Conducted Power of LTE Band 4						
Bandwidth	Modulation	RB size	RB offset	Channel	Channel	Channel
				19975	20175	20375
5MHz	QPSK	1	0.00	23.30	23.45	23.28
			12.00	23.64	23.60	23.70
			24.00	23.19	23.36	23.61
		12	0.00	22.46	22.54	22.44
			6.00	22.47	22.56	22.45
			11.00	22.39	22.39	22.50
		25	0.00	22.43	22.51	22.48
	16QAM	1	0.00	22.23	22.20	21.93
			12.00	22.35	22.57	22.36
			24.00	22.04	22.12	22.27
		12	0.00	21.37	21.41	21.32
			6.00	21.31	21.45	21.29
			11.00	21.30	21.39	21.36
		25	0.00	21.30	21.47	21.25
Bandwidth	Modulation	RB size	RB offset	Channel	Channel	Channel
				20000	20175	20350
10MHz	QPSK	1	0.00	23.51	23.54	23.45
			24.00	23.53	23.68	23.55
			49.00	23.49	23.55	23.82
		25	0.00	22.42	22.56	22.32
			12.00	22.38	22.52	22.39
			24.00	22.35	22.56	22.43
		50	0.00	22.36	22.53	22.38
	16QAM	1	0.00	22.29	22.32	22.25
			24.00	22.13	22.48	22.21
			49.00	22.15	22.19	22.39
		25	0.00	21.36	21.41	21.29
			12.00	21.28	21.42	21.27
			24.00	21.24	21.38	21.35
		50	0.00	21.25	21.39	21.25

Conducted Power of LTE Band 4						
Bandwidth	Modulation	RB size	RB offset	Channel	Channel	Channel
				20025	20175	20325
15MHz	QPSK	1	0.00	23.51	23.39	23.46
			37.00	23.75	23.57	23.56
			74.00	23.55	23.39	23.49
		36	0.00	22.29	22.51	22.31
			16.00	22.33	22.54	22.35
			35.00	22.39	22.49	22.31
		75	0.00	22.44	22.49	22.35
	16QAM	1	0.00	22.20	22.30	22.50
			37.00	22.51	22.57	22.62
			74.00	22.40	22.25	22.32
		36	0.00	21.24	21.40	21.25
			16.00	21.26	21.45	21.25
			35.00	21.28	21.37	21.23
		75	0.00	21.31	21.44	21.24
Bandwidth	Modulation	RB size	RB offset	Channel	Channel	Channel
				20050	20175	20300
20MHz	QPSK	1	0.00	23.32	23.65	23.59
			49.00	23.52	23.70	23.47
			99.00	23.58	23.61	23.51
		50	0.00	22.34	22.57	22.63
			24.00	22.41	22.58	22.39
			49.00	22.48	22.53	22.36
		100	0.00	22.41	22.53	22.43
	16QAM	1	0.00	22.34	22.46	22.60
			49.00	22.25	22.74	22.40
			99.00	22.39	22.28	22.32
		50	0.00	21.24	21.43	21.45
			24.00	21.31	21.44	21.26
			49.00	21.39	21.42	21.25
		100	0.00	21.33	21.41	21.33

LTE Band 5

Conducted Power of LTE Band 5						
Bandwidth	Modulation	RB size	RB offset	Channel	Channel	Channel
				20407	20525	20643
1.4MHz	QPSK	1	0.00	24.35	24.24	24.22
			3.00	24.51	24.35	24.25
			5.00	24.40	24.37	24.26
		3	0.00	24.20	24.22	24.25
			1.00	24.24	24.23	24.26
			3.00	24.20	24.26	24.17
		6	0.00	23.29	23.33	23.27
	16QAM	1	0.00	23.03	22.98	23.07
			3.00	23.11	23.05	23.22
			5.00	22.89	23.03	23.15
		3	0.00	23.28	23.21	23.21
			1.00	23.34	23.37	23.42
			3.00	23.27	23.16	23.23
		6	0.00	22.17	22.09	22.21
Bandwidth	Modulation	RB size	RB offset	Channel	Channel	Channel
				20415	20525	20635
3MHz	QPSK	1	0.00	24.24	24.28	24.37
			7.00	24.29	24.26	24.23
			14.00	24.20	24.26	24.24
		8	0.00	23.29	23.25	23.30
			4.00	23.30	23.26	23.32
			7.00	23.27	23.25	23.27
		15	0.00	23.30	23.28	23.27
	16QAM	1	0.00	22.91	23.02	23.00
			7.00	22.95	23.05	22.89
			14.00	23.05	23.04	22.90
		8	0.00	22.27	22.17	22.22
			4.00	22.21	22.13	22.27
			7.00	22.22	22.19	22.20
		15	0.00	22.22	22.16	22.17

Conducted Power of LTE Band 5						
Bandwidth	Modulation	RB size	RB offset	Channel	Channel	Channel
				20425	20525	20625
5MHz	QPSK	1	0.00	24.16	24.15	24.28
			12.00	24.49	24.57	24.44
			24.00	24.14	24.15	24.11
		12	0.00	23.24	23.28	23.24
			6.00	23.21	23.32	23.24
			11.00	23.11	23.24	23.20
		25	0.00	23.23	23.22	23.29
	16QAM	1	0.00	22.96	22.84	22.97
			12.00	23.21	23.16	23.09
			24.00	22.96	22.72	22.78
		12	0.00	22.08	22.10	22.11
			6.00	22.08	22.16	22.20
			11.00	22.10	22.09	22.13
		25	0.00	22.20	22.14	22.15
Bandwidth	Modulation	RB size	RB offset	Channel	Channel	Channel
				20450	20525	20600
10MHz	QPSK	1	0.00	24.36	24.23	24.41
			24.00	24.46	24.37	24.58
			12.00	24.23	24.35	24.36
		25	0.00	23.25	23.29	23.28
			12.00	23.30	23.28	23.28
			24.00	23.22	23.27	23.27
		50	0.00	23.24	23.28	23.26
	16QAM	1	0.00	22.90	23.08	23.09
			24.00	23.18	23.09	23.26
			12.00	22.61	23.12	22.93
		25	0.00	22.23	22.20	22.12
			12.00	22.16	22.17	22.16
			24.00	22.16	22.21	22.16
		50	0.00	22.18	22.21	22.16

LTE Band 7

Conducted Power of LTE Band 7						
Bandwidth	Modulation	RB size	RB offset	Channel	Channel	Channel
				20775	21100	21425
5MHz	QPSK	1	0.00	23.82	23.59	23.55
			12.00	24.09	23.77	23.78
			24.00	23.64	23.50	23.62
		12	0.00	22.85	22.57	22.42
			6.00	22.92	22.62	22.41
			11.00	22.65	22.56	22.34
		25	0.00	22.78	22.54	22.45
	16QAM	1	0.00	22.79	22.36	22.27
			12.00	22.80	22.69	22.49
			24.00	22.42	22.21	22.12
		12	0.00	21.80	21.50	21.51
			6.00	21.75	21.45	21.56
			11.00	21.75	21.49	21.42
		25	0.00	21.75	21.59	21.51
Bandwidth	Modulation	RB size	RB offset	Channel	Channel	Channel
				20800	21100	21350
10MHz	QPSK	1	0.00	23.91	23.74	23.81
			24.00	23.91	23.78	23.69
			49.00	23.72	23.59	23.59
		25	0.00	22.82	22.53	22.66
			12.00	22.75	22.54	22.41
			24.00	22.62	22.49	22.48
		50	0.00	22.64	22.54	22.51
	16QAM	1	0.00	22.55	22.45	22.30
			24.00	22.53	22.46	22.40
			49.00	22.38	22.36	22.33
		25	0.00	21.71	21.53	21.68
			12.00	21.73	21.55	21.48
			24.00	21.66	21.52	21.53
		50	0.00	21.67	21.50	21.43

Conducted Power of LTE Band 7						
Bandwidth	Modulation	RB size	RB offset	Channel	Channel	Channel
				20825	21100	21375
15MHz	QPSK	1	0.00	23.83	23.49	23.63
			37.00	24.01	23.74	23.78
			74.00	23.83	23.52	23.50
		36	0.00	22.60	22.51	22.47
			16.00	22.64	22.49	22.42
			35.00	22.62	22.48	22.47
		75	0.00	22.62	22.50	22.55
	16QAM	1	0.00	22.53	22.48	22.29
			37.00	22.61	22.66	22.72
			74.00	22.53	22.41	22.34
		36	0.00	21.60	21.50	21.47
			16.00	21.61	21.49	21.45
			35.00	21.59	21.47	21.38
		75	0.00	21.60	21.50	21.53
Bandwidth	Modulation	RB size	RB offset	Channel	Channel	Channel
				20850	21100	21350
20MHz	QPSK	1	0.00	23.57	23.68	23.41
			49.00	23.60	23.74	23.63
			99.00	23.48	23.58	23.37
		50	0.00	22.67	22.45	22.44
			24.00	22.66	22.45	22.48
			49.00	22.57	22.37	22.43
		100	0.00	22.55	22.46	22.51
	16QAM	1	0.00	22.51	22.38	22.30
			49.00	22.65	22.60	22.49
			99.00	22.47	22.29	22.44
		50	0.00	21.54	21.42	21.49
			24.00	21.45	21.40	21.45
			49.00	21.60	21.40	21.47
		100	0.00	21.56	21.41	21.53

Conducted Power of LTE Band 26						
Bandwidth	Modulation	RB size	RB offset	Channel	Channel	Channel
				26797	26915	27033
1.4MHz	QPSK	1	0.00	24.11	24.04	23.82
			3.00	24.10	24.05	23.92
			5.00	24.00	24.08	23.86
		3	0.00	23.84	23.99	23.96
			1.00	23.97	24.05	23.92
			3.00	23.98	23.92	23.92
		6	0.00	23.01	23.00	23.03
	16QAM	1	0.00	22.73	22.93	22.83
			3.00	22.79	22.94	22.92
			5.00	22.78	22.94	22.88
		3	0.00	23.09	22.93	22.92
			1.00	23.05	23.08	22.98
			3.00	22.92	23.04	22.88
		6	0.00	21.98	22.03	22.03
Bandwidth	Modulation	RB size	RB offset	Channel	Channel	Channel
				26805	26915	27025
3MHz	QPSK	1	0.00	23.97	24.01	23.97
			7.00	23.97	23.98	23.97
			14.00	23.94	23.94	23.99
		8	0.00	23.01	23.06	23.04
			4.00	22.99	23.04	22.97
			7.00	23.00	23.04	22.92
		15	0.00	22.98	23.04	23.01
	16QAM	1	0.00	22.72	23.02	22.81
			7.00	22.71	23.01	22.57
			14.00	22.74	22.93	22.61
		8	0.00	22.02	21.94	22.09
			4.00	21.93	22.06	21.86
			7.00	21.86	21.97	21.92
		15	0.00	21.97	22.00	21.96

Conducted Power of LTE Band 26

Bandwidth	Modulation	RB size	RB offset	Channel	Channel	Channel
				26815	26915	27015
5MHz	QPSK	1	0.00	23.91	24.05	23.87
			12.00	24.24	24.37	24.24
			24.00	23.85	23.87	23.81
		12	0.00	22.99	23.08	22.98
			6.00	23.05	23.11	22.97
			11.00	22.98	22.97	22.97
		25	0.00	23.06	23.06	23.01
	16QAM	1	0.00	22.82	23.07	22.64
			12.00	22.99	23.20	23.08
			24.00	22.69	22.73	22.54
		12	0.00	21.95	21.97	21.91
			6.00	21.97	22.02	21.91
			11.00	21.93	21.92	21.87
		25	0.00	22.00	21.97	21.97
Bandwidth	Modulation	RB size	RB offset	Channel	Channel	Channel
				26840	26915	26990
10MHz	QPSK	1	0.00	24.06	24.14	24.26
			24.00	24.39	24.19	24.16
			49.00	24.23	23.85	23.92
		25	0.00	23.05	23.11	22.89
			12.00	23.17	23.09	22.90
			24.00	23.18	23.02	22.99
		50	0.00	23.16	23.04	22.99
	16QAM	1	0.00	22.98	23.05	22.86
			24.00	22.95	23.08	22.99
			49.00	22.79	22.62	22.52
		25	0.00	22.00	21.97	21.83
			12.00	22.11	21.93	21.89
			24.00	22.10	21.98	21.85
		50	0.00	22.13	22.03	21.83

Conducted Power of LTE Band 26

Bandwidth	Modulation	RB size	RB offset	Channel	Channel	Channel
				26765	26865	26965
15MHz	QPSK	1	0.00	24.17	24.07	23.87
			37.00	24.37	24.34	24.15
			74.00	24.23	23.86	23.77
		36	0.00	23.11	22.97	22.88
			16.00	23.20	22.97	22.92
			35.00	23.03	22.93	22.89
		75	0.00	23.01	22.90	22.85
	16QAM	1	0.00	22.82	22.91	22.71
			37.00	22.99	22.93	23.13
			74.00	22.57	22.69	22.72
		36	0.00	22.08	21.99	21.88
			16.00	22.02	21.96	21.85
			35.00	21.97	21.88	21.83
		75	0.00	22.04	21.96	21.86

LTE Band 41


Conducted Power of LTE Band 41						
Bandwidth	Modulation	RB size	RB offset	Channel	Channel	Channel
				40265	40740	41215
5MHz	QPSK	1	0.00	22.62	22.86	22.96
			12.00	23.28	23.28	23.41
			24.00	22.74	22.86	22.90
		12	0.00	21.71	22.03	22.17
			6.00	21.83	22.06	21.98
			11.00	21.81	22.01	21.80
		25	0.00	21.85	22.12	22.00
	16QAM	1	0.00	21.27	21.86	21.97
			12.00	21.92	22.34	22.01
			24.00	21.58	21.83	21.76
		12	0.00	20.68	21.07	21.13
			6.00	20.78	21.08	21.04
			11.00	20.78	21.00	21.05
		25	0.00	20.75	21.09	21.05
Bandwidth	Modulation	RB size	RB offset	Channel	Channel	Channel
				40290	40740	41190
10MHz	QPSK	1	0.00	22.76	22.97	23.11
			24.00	23.08	23.17	23.17
			49.00	23.08	23.01	22.98
		25	0.00	21.88	22.14	22.01
			12.00	21.93	22.05	22.02
			24.00	21.98	22.20	22.17
		50	0.00	21.90	22.14	22.08
	16QAM	1	0.00	21.38	22.07	22.05
			24.00	21.62	22.22	22.11
			49.00	21.70	22.05	21.79
		25	0.00	20.85	21.03	21.07
			12.00	20.89	21.13	21.09
			24.00	20.93	21.13	21.07
		50	0.00	20.85	21.12	21.17

Conducted Power of LTE Band 41

Bandwidth	Modulation	RB size	RB offset	Channel	Channel	Channel
				40315	40740	41165
15MHz	QPSK	1	0.00	22.74	23.04	23.11
			37.00	23.04	23.23	23.46
			74.00	23.13	23.00	22.99
		36	0.00	21.74	22.11	22.12
			16.00	21.87	22.14	21.97
			35.00	22.00	22.08	22.03
		75	0.00	21.87	22.11	22.01
	16QAM	1	0.00	21.17	22.03	22.05
			37.00	21.68	22.40	22.18
			74.00	21.60	22.09	21.74
		36	0.00	20.69	20.99	21.13
			16.00	20.85	21.13	21.02
			35.00	20.96	21.21	21.08
		75	0.00	20.83	21.19	21.19
Bandwidth	Modulation	RB size	RB offset	Channel	Channel	Channel
				39750	40620	41490
20MHz	QPSK	1	0.00	22.45	23.00	23.13
			49.00	22.90	23.28	23.40
			99.00	22.87	23.02	22.97
		50	0.00	21.76	22.13	22.00
			24.00	21.98	22.12	22.08
			49.00	22.03	22.00	22.01
		100	0.00	21.93	22.23	22.07
	16QAM	1	0.00	21.40	22.07	21.97
			49.00	21.92	22.25	22.29
			99.00	21.66	21.93	21.85
		50	0.00	20.73	20.92	21.11
			24.00	21.02	21.12	21.12
			49.00	21.06	21.09	21.01
		100	0.00	20.90	21.30	21.08

9. Exposure Position Consideration

9.1. EUT Antenna Location



9.2. Test Position Consideration

Test Positions						
Mode	Back	Front	Top Side	Bottom Side	Right Side	Left Side
GSM/WCDMA/CDMA /LTE	Yes	Yes	Yes	No	No	Yes
WIFI/BT	Yes	Yes	No	No	Yes	No

Note:

1. KDB 447498 D01v06, particular DUT edges were not required to be evaluated for SAR if the antenna-to-edge distance is greater than 2.5cm.

10. SAR Test Results Summary

10.1. Head 1g SAR Data

Band	Mode	Test Position	CH.	Freq. (MHz)	Ave. Power (dBm)	Tune-Up Limit (dBm)	Power Drift (%)	Meas. SAR1g (W/kg)	Scaling Factor	Reported SAR1g (W/kg)	Limit (W/Kg)
GSM850	voice	Left Cheek	128	824.2	34.19	34.50	3.24	0.42	1.054	0.44	1.60
		Left Tilt	128	824.2	34.19	34.50	-1.22	0.26	1.054	0.27	
		Right Cheek	128	824.2	34.19	34.50	-0.21	0.40	1.054	0.42	
		Right Tilt	128	824.2	34.19	34.50	0.02	0.31	1.054	0.33	
GSM1900	voice	Left Cheek	661	1880	30.42	30.50	0.42	0.38	1.054	0.40	
		Left Tilt	661	1880	30.42	30.50	-0.31	0.21	1.054	0.22	
		Right Cheek	661	1880	30.42	30.50	0.35	0.34	1.054	0.36	
		Right Tilt	661	1880	30.42	30.50	-2.64	0.19	1.054	0.20	
WCDMA Band II	RMC	Left Cheek	9262	1852.4	23.25	23.50	2.46	0.36	1.107	0.40	
		Left Tilt	9262	1852.4	23.25	23.50	-0.39	0.28	1.107	0.31	
		Right Cheek	9262	1852.4	23.25	23.50	-1.34	0.35	1.107	0.39	
		Right Tilt	9262	1852.4	23.25	23.50	-2.67	0.21	1.107	0.23	
WCDMA Band V	RMC	Left Cheek	4132	826.40	23.45	23.50	0.87	0.32	1.122	0.36	
		Left Tilt	4132	826.40	23.45	23.50	1.37	0.19	1.122	0.21	
		Right Cheek	4132	826.40	23.45	23.50	0.23	0.30	1.122	0.34	
		Right Tilt	4132	826.40	23.45	23.50	0.06	0.17	1.122	0.19	

2.4G	802.11g	Left Cheek	1	2412	16.89	17.00	-1.36	0.20	1.035	0.21
		Left Tilt	1	2412	16.89	17.00	-0.34	0.11	1.035	0.11
		Right Cheek	1	2412	16.89	17.00	0.47	0.19	1.035	0.20
		Right Tilt	1	2412	16.89	17.00	2.21	0.09	1.035	0.09
5.2G	802.11n HT20	Left Cheek	36	5180	16.71	17.00	-0.32	0.20	1.069	0.21
		Left Tilt	36	5180	16.71	17.00	2.24	0.13	1.069	0.14
		Right Cheek	36	5180	16.71	17.00	-0.47	0.21	1.069	0.22
		Right Tilt	36	5180	16.71	17.00	0.33	0.15	1.069	0.16
5.8G	802.11ac HT20	Left Cheek	149	5745	17.72	18.00	-1.11	0.25	1.067	0.27
		Left Tilt	149	5745	17.72	18.00	2.99	0.16	1.067	0.17
		Right Cheek	149	5745	17.72	18.00	0.24	0.27	1.067	0.29
		Right Tilt	149	5745	17.72	18.00	-2.36	0.18	1.067	0.19

Band	Mode	Test Position	CH.	Freq. (MHz)	RB allocation	RB offset	Ave. Power (dBm)	Tune-Up Limit (dBm)	Power Drift (%)	Meas. SAR1g (W/kg)	Scaling Factor	Reported SAR1g (W/kg)
LTE Band 2	QPSK (20MHz)	Right Cheek	19100	1900	1	49	23.97	24.00	0.34	0.26	1.050	0.27
					50	24	22.73	23.00	-0.21	0.19	1.026	0.19
		Right Tilt	19100	1900	1	49	23.97	24.00	-0.10	0.15	1.050	0.16
					50	24	22.73	23.00	1.27	0.08	1.026	0.08
		Left Cheek	19100	1900	1	49	23.97	24.00	0.21	0.29	1.050	0.30
					50	24	22.73	23.00	2.04	0.20	1.026	0.21
		Left Tilt	19100	1900	1	49	23.97	24.00	-1.79	0.17	1.050	0.18
					50	24	22.73	23.00	-2.69	0.09	1.026	0.09
LTE Band 4	QPSK (20MHz)	Right Cheek	20175	1732.5	1	49	23.70	24.00	-0.34	0.30	1.119	0.34
					50	24	22.58	23.00	0.05	0.25	1.023	0.26
		Right Tilt	20175	1732.5	1	49	23.70	24.00	0.11	0.19	1.119	0.21
					50	24	22.58	23.00	-3.02	0.09	1.023	0.09
		Left Cheek	20175	1732.5	1	49	23.70	24.00	-1.02	0.32	1.119	0.36
					50	24	22.58	23.00	-4.05	0.29	1.023	0.30
		Left Tilt	20175	1732.5	1	49	23.70	24.00	0.07	0.20	1.119	0.22
					50	24	22.58	23.00	1.67	0.11	1.023	0.11
LTE Band 5	QPSK (10MHz)	Right Cheek	20600	844	1	24	24.58	25.00	-2.21	0.20	1.057	0.21
					25	24	23.28	23.50	-1.07	0.15	1.102	0.17
		Right Tilt	20600	844	1	24	24.58	25.00	1.34	0.19	1.057	0.20
					25	24	23.28	23.50	0.65	0.10	1.102	0.11
		Left Cheek	20600	844	1	24	24.58	25.00	1.69	0.23	1.057	0.24
					25	24	23.28	23.50	-1.34	0.18	1.102	0.20
		Left Tilt	20600	844	1	24	24.58	25.00	2.14	0.16	1.057	0.17
					25	24	23.28	23.50	-1.37	0.12	1.102	0.13

LTE Band 7	QPSK (10MHz)	Right Cheek	21100	2535	1	49	23.74	24.00	-4.57	0.23	1.062	0.24
					50	24	22.45	22.50	2.60	0.21	1.012	0.21
		Right Tilt	21100	2535	1	49	23.74	24.00	2.65	0.14	1.062	0.15
					50	24	22.45	22.50	-3.54	0.12	1.012	0.12
		Left Cheek	21100	2535	1	49	23.74	24.00	-3.29	0.22	1.062	0.23
					50	24	22.45	22.50	2.34	0.20	1.012	0.20
		Left Tilt	21100	2535	1	49	23.74	24.00	-1.95	0.13	1.062	0.14
					50	24	22.45	22.50	-2.69	0.10	1.012	0.10
LTE Band 26	QPSK (15MHz)	Right Cheek	26765	821.5	1	37	24.37	24.50	1.35	0.20	1.089	0.22
					37	16	23.20	23.50	-0.92	0.15	1.026	0.15
		Right Tilt	26765	821.5	1	37	24.37	24.50	-2.24	0.17	1.089	0.19
					37	16	23.20	23.50	1.69	0.07	1.026	0.07
		Left Cheek	26765	821.5	1	37	24.37	24.50	1.32	0.22	1.089	0.24
					37	16	23.20	23.50	-1.14	0.17	1.026	0.17
		Left Tilt	26765	821.5	1	37	24.37	24.50	-2.03	0.19	1.089	0.21
					37	16	23.20	23.50	2.31	0.08	1.026	0.08
LTE Band 41	QPSK (20MHz)	Right Cheek	39750	2506	1	49	22.90	23.00	-1.05	0.20	1.026	0.21
					50	24	21.98	22.00	0.79	0.17	1.109	0.19
		Right Tilt	39750	2506	1	49	22.90	23.00	1.11	0.18	1.026	0.18
					50	24	21.98	22.00	-1.36	0.09	1.109	0.10
		Left Cheek	39750	2506	1	49	22.90	23.00	-0.57	0.23	1.026	0.24
					50	24	21.98	22.00	-3.11	0.19	1.109	0.21
		Left Tilt	39750	2506	1	49	22.90	23.00	2.64	0.20	1.026	0.21
					50	24	21.98	22.00	-2.68	0.10	1.109	0.11

10.2. Body-Worn 1g SAR Data

Band	Mode	Test Position with 10mm	CH.	Freq. (MHz)	Ave. Power (dBm)	Tune-Up Limit (dBm)	Power Drift (%)	Meas. SAR1g (W/kg)	Scaling Factor	Reported SAR1g (W/kg)	Limit (W/Kg)
GSM850	voice	Front	128	824.2	34.19	34.50	1.24	0.25	1.054	0.26	1.60
		Back	128	824.2	34.19	34.50	-4.60	0.34	1.054	0.36	
	GPRS 2 slots	Front	190	836.6	32.80	33.00	-2.37	0.42	1.002	0.42	
		Back	190	836.6	32.80	33.00	0.20	0.66	1.002	0.66	
GSM1900	voice	Front	661	1880	30.42	30.50	0.61	0.30	1.054	0.32	
		Back	661	1880	30.42	30.50	-1.68	0.54	1.054	0.57	
	GPRS 2 slots	Front	512	1850.2	29.10	29.50	-1.49	0.44	1.038	0.46	
		Back	512	1850.2	29.10	29.50	-0.93	0.61	1.038	0.63	
WCDMA Band II	RMC	Front	9262	1852.4	23.25	23.50	-2.32	0.45	1.107	0.50	
		Back	9262	1852.4	23.25	23.50	-1.73	0.67	1.107	0.74	
WCDMA Band V	RMC	Front	4132	826.40	23.45	23.50	2.19	0.15	1.122	0.17	
		Back	4132	826.40	23.45	23.50	1.11	0.31	1.122	0.35	
2.4G	802.11g	Front	1	2412	16.89	17.00	-3.60	0.10	1.035	0.10	
		Back	1	2412	16.89	17.00	4.01	0.17	1.035	0.18	
5.2G	802.11nH T20	Front	36	5180	16.71	17.00	2.01	0.20	1.069	0.21	
		Back	36	5180	16.71	17.00	1.01	0.25	1.069	0.27	
5.8G	802.11ac HT20	Front	149	5745	17.72	18.00	1.22	0.15	1.067	0.16	
		Back	149	5745	17.72	18.00	-0.92	0.19	1.067	0.20	

Band	Mode	Test Position with 10mm	CH.	Freq. (MHz)	RB allocation	RB offset	Ave. Power (dBm)	Tune-Up Limit (dBm)	Power Drift (%)	Meas. SAR1g (W/kg)	Scaling Factor	Reported SAR1g (W/kg)
LTE Band 2	QPSK (20MHz)	Front	19100	1900	1	49	23.97	24.00	-1.33	0.39	1.050	0.41
					50	24	22.73	23.00	1.04	0.25	1.026	0.26
		Back	19100	1900	1	49	23.97	24.00	0.17	0.45	1.050	0.47
					50	24	22.73	23.00	-0.16	0.36	1.026	0.37
LTE Band 4	QPSK (20MHz)	Front	20175	1732.5	1	49	23.70	24.00	1.54	0.49	1.062	0.52
					50	24	22.58	23.00	-0.24	0.28	1.096	0.31
		Back	20175	1732.5	1	49	23.70	24.00	0.21	0.56	1.062	0.59
					50	24	22.58	23.00	-1.67	0.30	1.096	0.33
LTE Band 5	QPSK (10MHz)	Front	20600	844	1	24	24.58	25.00	1.61	0.20	1.057	0.21
					25	24	23.28	23.50	0.67	0.17	1.102	0.19
		Back	20600	844	1	24	24.58	25.00	-0.16	0.22	1.057	0.23
					25	24	23.28	23.50	-3.30	0.19	1.102	0.21
LTE Band 7	QPSK (10MHz)	Front	21100	2535	1	49	23.74	24.00	-0.34	0.20	1.062	0.21
					50	24	22.45	22.50	2.33	0.18	1.012	0.18
		Back	21100	2535	1	49	23.74	24.00	0.24	0.30	1.062	0.32
					50	24	22.45	22.50	-3.66	0.28	1.012	0.28
LTE Band 26	QPSK (15MHz)	Front	26765	821.5	1	37	24.37	24.50	-0.21	0.45	1.089	0.49
					37	16	23.20	23.50	1.36	0.20	1.026	0.21
		Back	26765	821.5	1	37	24.37	24.50	1.10	0.50	1.089	0.54
					37	16	23.20	23.50	0.04	0.30	1.026	0.31
LTE Band 41	QPSK (20MHz)	Front	39750	2506	1	49	22.90	23.00	2.04	0.20	1.026	0.21
					50	24	21.98	22.00	0.67	0.12	1.109	0.13
		Back	39750	2506	1	49	22.90	23.00	-3.69	0.30	1.026	0.31
					50	24	21.98	22.00	2.04	0.15	1.109	0.17

Note:

- Per KDB 447498 D01 v06, for each exposure position, if the highest output power channel Reported SAR $\leq 0.8W/kg$, other channels SAR testing is not necessary.
- Per KDB 447498 D01 v06, body-worn use is evaluated with the device positioned at 10 mm from a flat phantom filled with head tissue-equivalent medium.
- Per KDB 447498 D01 v06, the report SAR is measured SAR value adjusted for maximum tune-up tolerance. Scaling Factor = $10^{\frac{(\text{tune-up limit power(dBm)} - \text{Ave.power power (dBm)})}{10}}$, where tune-up limit is the maximum rated power among all production units.
Reported SAR(W/kg) = Measured SAR (W/kg) * Scaling Factor.
- Per KDB865664D01 v01r04 perform a second repeated measurement only the ratio of largest to smallest SAR for the original and first repeated measurement is >1.20 or when the original or repeated measurement is $\geq 1.45W/kg$.
- Perform a second measurement only if the original, first and second repeated measurement is $\geq 1.5w/kg$ and the ratio of largest to smallest SAR for the original, first and second repeated measurement is >1.20 .

10.3. Hotspot 1g SAR Data

Band	Mode	Test Position with 10mm	CH.	Freq. (MHz)	Ave. Power (dBm)	Tune-Up Limit (dBm)	Power Drift (%)	Meas. SAR1g (W/kg)	Scaling Factor	Reported SAR1g (W/kg)	Limit (W/Kg)
GSM850	GPRS 2 slots	Front	190	836.6	32.80	33.00	-1.33	0.44	1.002	0.44	1.60
		Back	190	836.6	32.80	33.00	-0.37	0.71	1.002	0.71	
		Top	190	836.6	32.80	33.00	2.12	0.10	1.002	0.10	
		Left	190	836.6	32.80	33.00	0.07	0.12	1.002	0.12	
GSM1900	GPRS 2 slots	Front	512	1850.2	29.10	29.50	2.01	0.49	1.038	0.51	
		Back	512	1850.2	29.10	29.50	-0.93	0.61	1.038	0.63	
		Top	512	1850.2	29.10	29.50	1.39	0.11	1.038	0.11	
		Left	512	1850.2	29.10	29.50	-2.46	0.13	1.038	0.13	
WCDMA Band II	RMC	Front	1852.4	23.25	23.50	1852.4	1.14	0.52	1.107	0.58	
		Back	1852.4	23.25	23.50	1852.4	0.24	0.69	1.084	0.75	
		Top	1852.4	23.25	23.50	1852.4	0.67	0.13	1.107	0.14	
		Left	1852.4	23.25	23.50	1852.4	-0.47	0.14	1.107	0.15	
WCDMA Band V	RMC	Front	4132	826.40	23.45	23.50	-1.24	0.20	1.107	0.22	
		Back	4132	826.40	23.45	23.50	0.94	0.32	1.107	0.35	
		Top	4132	826.40	23.45	23.50	-2.31	0.12	1.107	0.13	
		Left	4132	826.40	23.45	23.50	0.47	0.17	1.107	0.19	
2.4G	802.11g	Front	1	2412	16.89	17.00	-1.21	0.12	1.035	0.12	
		Back	1	2412	16.89	17.00	-4.11	0.19	1.035	0.20	
		Right	1	2412	16.89	17.00	0.41	0.09	1.035	0.09	
5.2G	802.11n HT20	Front	36	5180	16.71	17.00	-3.62	0.22	1.069	0.24	
		Back	36	5180	16.71	17.00	-2.11	0.26	1.069	0.28	
		Right	36	5180	16.71	17.00	3.20	0.07	1.069	0.07	
5.8G	802.11ac HT20	Front	149	5745	17.72	18.00	-1.32	0.29	1.067	0.31	
		Back	149	5745	17.72	18.00	0.78	0.36	1.067	0.38	
		Right	149	5745	17.72	18.00	-3.10	0.06	1.067	0.06	

Band	Mode	Test Position with 10mm	CH.	Freq. (MHz)	RB allocation	RB offset	Ave. Power (dBm)	Tune-Up Limit (dBm)	Power Drift (%)	Meas. SAR1g (W/kg)	Scaling Factor	Reported SAR1g (W/kg)
LTE Band 2	QPSK (20MHz)	Front	19100	1900	1	49	23.97	24.00	0.45	0.41	1.050	0.43
					50	24	22.73	23.00	0.16	0.25	1.026	0.26
		Back	19100	1900	1	49	23.97	24.00	-2.55	0.48	1.050	0.50
					50	24	22.73	23.00	-2.22	0.24	1.026	0.25
		Top	19100	1900	1	49	23.97	24.00	-3.48	0.12	1.050	0.13
					50	24	22.73	23.00	-0.03	0.09	1.026	0.09
		Left	19100	1900	1	49	23.97	24.00	0.60	0.17	1.050	0.18
					50	24	22.73	23.00	-2.34	0.11	1.026	0.11
		Front	20175	1732.5	1	49	23.70	24.00	0.12	0.51	1.062	0.54
					50	24	22.58	23.00	1.14	0.34	1.096	0.37
LTE Band 4	QPSK (20MHz)	Back	20175	1732.5	1	49	23.70	24.00	0.91	0.57	1.062	0.61
					50	24	22.58	23.00	-2.11	0.41	1.096	0.45
		Top	20175	1732.5	1	49	23.70	24.00	-2.17	0.12	1.062	0.13
					50	24	22.58	23.00	0.61	0.7	1.096	0.77
		Left	20175	1732.5	1	49	23.70	24.00	-3.16	0.17	1.062	0.18
					50	24	22.58	23.00	2.10	0.08	1.096	0.09
LTE Band 5	QPSK (10MHz)	Front	20600	844	1	24	24.58	25.00	-2.50	0.21	1.057	0.22
					25	24	23.28	23.50	-1.31	0.10	1.102	0.11
		Back	20600	844	1	24	24.58	25.00	-1.19	0.23	1.057	0.24
					25	24	23.28	23.50	1.44	0.19	1.102	0.21
		Top	20600	844	1	24	24.58	25.00	3.46	0.11	1.057	0.12
					25	24	23.28	23.50	0.47	0.06	1.102	0.07
		Left	20600	844	1	24	24.58	25.00	3.31	0.14	1.057	0.15
					25	24	23.28	23.50	-0.68	0.08	1.102	0.09
LTE Band 7	QPSK (10MHz)	Front	21100	2535	1	49	23.74	24.00	2.33	0.25	1.062	0.27
					50	24	22.45	22.50	1.64	0.22	1.012	0.22
		Back	21100	2535	1	49	23.74	24.00	-4.81	0.33	1.062	0.35
					50	24	22.45	22.50	3.66	0.30	1.012	0.30
		Top	21100	2535	1	49	23.74	24.00	-2.88	0.06	1.062	0.06
					50	24	22.45	22.50	-2.36	0.04	1.012	0.04
		Left	21100	2535	1	49	23.74	24.00	3.16	0.08	1.062	0.08
					50	24	22.45	22.50	-1.30	0.06	1.012	0.06

LTE Band 26	QPSK (15MHz)	Front	26765	821.5	1	37	24.37	24.50	2.14	0.51	1.089	0.56
					37	16	23.20	23.50	0.61	0.31	1.026	0.32
		Back	26765	821.5	1	37	24.37	24.50	-1.26	0.57	1.089	0.62
					37	16	23.20	23.50	1.15	0.44	1.026	0.45
		Top	26765	821.5	1	37	24.37	24.50	-0.31	0.17	1.089	0.19
					37	16	23.20	23.50	0.21	0.09	1.026	0.09
		Left	26765	821.5	1	37	24.37	24.50	1.11	0.18	1.089	0.20
					37	16	23.20	23.50	2.49	0.10	1.026	0.10
LTE Band 41	QPSK (20MHz)	Front	39750	2506	1	49	22.90	23.00	-1.14	0.25	1.026	0.26
					50	24	21.98	22.00	2.31	0.13	1.109	0.14
		Back	39750	2506	1	49	22.90	23.00	-1.81	0.33	1.026	0.34
					50	24	21.98	22.00	0.42	0.24	1.109	0.27
		Top	39750	2506	1	49	22.90	23.00	1.66	0.17	1.026	0.17
					50	24	21.98	22.00	1.39	0.09	1.109	0.10
		Left	39750	2506	1	49	22.90	23.00	0.47	0.18	1.026	0.18
					50	24	21.98	22.00	-0.77	0.10	1.109	0.11


Note:

1. Per KDB 447498 D01 v06, for each exposure position, if the highest output power channel Reported SAR $\leq 0.8W/kg$, other channels SAR testing is not necessary.
2. Per KDB 447498 D01 v06, body-worn with hotspot use is evaluated with the device positioned at 10 mm from a flat phantom filled with head tissue-equivalent medium.
3. Per KDB 447498 D01 v06, the report SAR is measured SAR value adjusted for maximum tune-up tolerance. Scaling Factor = $10^{[(\text{tune-up limit power(dBm)} - \text{Ave. power (dBm)})/10]}$, where tune-up limit is the maximum rated power among all production units.
Reported SAR(W/kg) = Measured SAR (W/kg) * Scaling Factor.
4. Per KDB865664D01 v01r04 perform a second repeated measurement only the ratio of largest to smallest SAR for the original and first repeated measurement is >1.20 or when the original or repeated measurement is $\geq 1.45W/kg$.
5. Perform a second measurement only if the original, first and second repeated measurement is $\geq 1.5w/kg$ and the ratio of largest to smallest SAR for the original, first and second repeated measurement is >1.20 .

10.4. Simultaneous Transmission Conclusion

Multi-Band Simultaneous Transmission Considerations

According to FCC KDB Publication 447498 D01v05r02, transmitters are considered to be transmitting simultaneously when there is overlapping transmission, with the exception of transmissions during network hand-offs with maximum hand-off duration less than 30 seconds. Possible transmission paths for the EUT are shown in below Figure and are color-coded to indicate communication modes which share the same path. Modes which share the same transmission path cannot transmit simultaneously with one another.



Simultaneous Transmission Procedures

This device contains transmitters that may operate simultaneously. Therefore simultaneous transmission analysis is required. Per FCC KDB 447498 D01v05r02, simultaneous transmission SAR test exclusion may be applied when the sum of the 1-g SAR for all the simultaneous transmitting antennas in a specific a physical test configuration is ≤ 1.6 W/kg. When standalone SAR is not required to be measured, per FCC KDB 447498 D01v05r02 4.3.2.2), the following equation must be used to estimate the standalone 1g SAR and 10g extremity SAR for simultaneous transmission assessment involving that transmitter.

$$\text{Estimated SAR} = \frac{\sqrt{f(\text{GHz})}}{7.5(18.75)} \cdot \frac{\text{Max. power of channel, mW}}{\text{Min. Separation Distance, mm}}$$

Mode	Max. tune-up Power (dBm)	Exposure Position	Head	Body -worn
		Test Distance (mm)	5	5
BLE	1.41	Estimated SAR (W/kg)	0.06	0.06

Note:

- When the minimum *test separation distance* is < 5 mm, a distance of 5 mm according is applied to determine estimated SAR.
- (max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)] $\cdot [\sqrt{f(\text{GHz})}/x]$ W/kg for test separation distances ≤ 5 mm; where $x = 7.5$ for 1-g SAR, and $x = 18.75$ for 10-g SAR.
- Next to the mouth exposure requires 1-g SAR, and the wrist-worn condition requires 10-g extremity SAR.

Simultaneous Transmission Possibilities

The Simultaneous Transmission Possibilities of this device are as below:

NO.	Configuration	Head	Body-Worn	Hotspot
1	GSM850/1900(Voice)+WIFI(2.4)	YES	YES	NO
2	GPRS 850/1900(DATA)+WIFI(2.4)	NO	YES	YES
3	WCDMA+ WIFI(2.4)	YES	YES	YES
4.	LTE+WIFI(2.4)	YES	YES	YES
5.	GSM850/1900(Voice)+BT	YES	YES	NO
6	GPRS/EDGE 850/1900(DATA)+BT	YES	YES	NO
7.	WCDMA+ BT	YES	YES	NO
8.	LTE+BT	YES	YES	NO

10.5. SAR Simultaneous Transmission Analysis

Band	Test Position	Scaled SAR				Σ SAR (W/kg)	SPLSR	Remark
		Head	WIFI 2.4G	WIFI 5 G	BT			
GSM850 (voice)	Left Cheek	0.44	0.21	0.27	0.06	0.71	N/A	N/A
	Left Tilt	0.27	0.11	0.17	0.06	0.44	N/A	N/A
	Right Cheek	0.42	0.20	0.29	0.06	0.71	N/A	N/A
	Right Tilt	0.33	0.09	0.19	0.06	0.52	N/A	N/A
GSM1900 (voice)	Left Cheek	0.40	0.21	0.27	0.06	0.67	N/A	N/A
	Left Tilt	0.22	0.11	0.17	0.06	0.39	N/A	N/A
	Right Cheek	0.36	0.20	0.29	0.06	0.65	N/A	N/A
	Right Tilt	0.20	0.09	0.19	0.06	0.39	N/A	N/A
WCDMA Band II	Left Cheek	0.31	0.21	0.27	0.06	0.58	N/A	N/A
	Left Tilt	0.39	0.11	0.17	0.06	0.56	N/A	N/A
	Right Cheek	0.23	0.20	0.29	0.06	0.52	N/A	N/A
	Right Tilt	0.36	0.09	0.19	0.06	0.55	N/A	N/A
WCDMA Band V	Left Cheek	0.21	0.21	0.27	0.06	0.48	N/A	N/A
	Left Tilt	0.34	0.11	0.17	0.06	0.51	N/A	N/A
	Right Cheek	0.19	0.20	0.29	0.06	0.48	N/A	N/A
	Right Tilt	0.31	0.09	0.19	0.06	0.50	N/A	N/A

Band	Test Position	RB allocation	Scaled				Σ SAR (W/kg)	SPLSR	Remark
			Head	WIFI2.4G	WIFI 5G	Bluetooth			
LTE Band 2 QPSK (20MHz)	Right Cheek	1	0.27	0.20	0.29	0.06	0.56	N/A	N/A
		50	0.19	0.20	0.29	0.06	0.48	N/A	N/A
	Right Tilt	1	0.16	0.09	0.19	0.06	0.35	N/A	N/A
		50	0.08	0.09	0.19	0.06	0.27	N/A	N/A
	Left Cheek	1	0.30	0.21	0.27	0.06	0.57	N/A	N/A
		50	0.21	0.21	0.27	0.06	0.48	N/A	N/A
	Left Tilt	1	0.18	0.11	0.17	0.06	0.35	N/A	N/A
		50	0.09	0.11	0.17	0.06	0.26	N/A	N/A
LTE Band 4 QPSK (20MHz)	Right Cheek	1	0.34	0.20	0.29	0.06	0.63	N/A	N/A
		50	0.26	0.20	0.29	0.06	0.55	N/A	N/A
	Right Tilt	1	0.21	0.09	0.19	0.06	0.40	N/A	N/A
		50	0.09	0.09	0.19	0.06	0.28	N/A	N/A
	Left Cheek	1	0.36	0.21	0.27	0.06	0.63	N/A	N/A
		50	0.30	0.21	0.27	0.06	0.57	N/A	N/A
	Left Tilt	1	0.22	0.11	0.17	0.06	0.39	N/A	N/A
		50	0.11	0.11	0.17	0.06	0.28	N/A	N/A
LTE Band 5 QPSK (10MHz)	Right Cheek	1	0.21	0.20	0.29	0.06	0.50	N/A	N/A
		25	0.17	0.20	0.29	0.06	0.46	N/A	N/A
	Right Tilt	1	0.20	0.09	0.19	0.06	0.39	N/A	N/A
		25	0.11	0.09	0.19	0.06	0.30	N/A	N/A
	Left Cheek	1	0.24	0.21	0.27	0.06	0.51	N/A	N/A
		25	0.20	0.21	0.27	0.06	0.47	N/A	N/A
	Left Tilt	1	0.17	0.11	0.17	0.06	0.34	N/A	N/A
		25	0.13	0.11	0.17	0.06	0.30	N/A	N/A

LTE Band 7 QPSK (10MHz)	Right Cheek	1	0.24	0.20	0.29	0.06	0.53	N/A	N/A
		25	0.21	0.20	0.29	0.06	0.50	N/A	N/A
	Right Tilt	1	0.15	0.09	0.19	0.06	0.34	N/A	N/A
		25	0.12	0.09	0.19	0.06	0.31	N/A	N/A
	Left Cheek	1	0.23	0.21	0.27	0.06	0.50	N/A	N/A
		25	0.20	0.21	0.27	0.06	0.47	N/A	N/A
	Left Tilt	1	0.14	0.11	0.17	0.06	0.31	N/A	N/A
		25	0.10	0.11	0.17	0.06	0.27	N/A	N/A
LTE Band 26 QPSK (15MHz)	Right Cheek	1	0.22	0.20	0.29	0.06	0.51	N/A	N/A
		75	0.15	0.20	0.29	0.06	0.44	N/A	N/A
	Right Tilt	1	0.19	0.09	0.19	0.06	0.38	N/A	N/A
		75	0.07	0.09	0.19	0.06	0.26	N/A	N/A
	Left Cheek	1	0.24	0.21	0.27	0.06	0.51	N/A	N/A
		75	0.17	0.21	0.27	0.06	0.44	N/A	N/A
	Left Tilt	1	0.21	0.11	0.17	0.06	0.38	N/A	N/A
		75	0.08	0.11	0.17	0.06	0.25	N/A	N/A
LTE Band 41 QPSK (20MHz)	Right Cheek	1	0.21	0.20	0.29	0.06	0.50	N/A	N/A
		50	0.19	0.20	0.29	0.06	0.48	N/A	N/A
	Right Tilt	1	0.18	0.09	0.19	0.06	0.37	N/A	N/A
		50	0.10	0.09	0.19	0.06	0.29	N/A	N/A
	Left Cheek	1	0.24	0.21	0.27	0.06	0.51	N/A	N/A
		50	0.21	0.21	0.27	0.06	0.48	N/A	N/A
	Left Tilt	1	0.21	0.11	0.17	0.06	0.38	N/A	N/A
		50	0.11	0.11	0.17	0.06	0.28	N/A	N/A

Band	Test Position	Scaled SAR				Σ SAR (W/kg)	SPLSR	Remark
		Body-Worn	WIFI 2.4G	WIFI 5G	BT			
GSM850 (voice)	Front	0.26	0.10	0.21	0.06	0.47	N/A	N/A
	Back	0.36	0.18	0.27	0.06	0.63	N/A	N/A
GSM850 (GPRS 3slot)	Front	0.42	0.10	0.21	0.06	0.63	N/A	N/A
	Back	0.66	0.18	0.27	0.06	0.93	N/A	N/A
GSM1900 (voice)	Front	0.32	0.10	0.21	0.06	0.53	N/A	N/A
	Back	0.57	0.18	0.27	0.06	0.84	N/A	N/A
GSM1900 (GPRS 2slot)	Front	0.46	0.10	0.21	0.06	0.67	N/A	N/A
	Back	0.63	0.18	0.27	0.06	0.90	N/A	N/A
WCDMA Band II	Front	0.50	0.10	0.21	0.06	0.71	N/A	N/A
	Back	0.74	0.18	0.27	0.06	1.01	N/A	N/A
WCDMA Band V	Front	0.17	0.10	0.21	0.06	0.38	N/A	N/A
	Back	0.35	0.18	0.27	0.06	0.62	N/A	N/A

Band	Test Position	RB allocation	Scaled				Σ SAR (W/kg)	SPLSR	Remark
			Body-Worn	WIFI 2.4G	WIFI 5G	Bluetooth			
LTE Band 2 QPSK (20MHz)	Front	1	0.41	0.10	0.21	0.06	0.62	N/A	N/A
		50	0.26	0.10	0.21	0.06	0.47	N/A	N/A
	Back	1	0.47	0.18	0.27	0.06	0.74	N/A	N/A
		50	0.37	0.18	0.27	0.06	0.64	N/A	N/A
LTE Band 4 QPSK (20MHz)	Front	1	0.52	0.10	0.21	0.06	0.73	N/A	N/A
		50	0.31	0.10	0.21	0.06	0.52	N/A	N/A
	Back	1	0.59	0.18	0.27	0.06	0.86	N/A	N/A
		50	0.33	0.18	0.27	0.06	0.60	N/A	N/A
LTE Band 5 QPSK (10MHz)	Front	1	0.21	0.10	0.21	0.06	0.42	N/A	N/A
		25	0.19	0.10	0.21	0.06	0.40	N/A	N/A
	Back	1	0.23	0.18	0.27	0.06	0.50	N/A	N/A
		25	0.21	0.18	0.27	0.06	0.48	N/A	N/A
LTE Band 7 QPSK (10MHz)	Front	1	0.21	0.10	0.21	0.06	0.42	N/A	N/A
		50	0.18	0.10	0.21	0.06	0.39	N/A	N/A
	Back	1	0.32	0.18	0.27	0.06	0.59	N/A	N/A
		50	0.28	0.18	0.27	0.06	0.55	N/A	N/A
LTE Band 26 QPSK (15MHz)	Front	1	0.49	0.10	0.21	0.06	0.70	N/A	N/A
		36	0.21	0.10	0.21	0.06	0.42	N/A	N/A
	Back	1	0.54	0.18	0.27	0.06	0.81	N/A	N/A
		36	0.31	0.18	0.27	0.06	0.58	N/A	N/A
LTE Band 41 QPSK (20MHz)	Front	1	0.21	0.10	0.21	0.06	0.42	N/A	N/A
		50	0.13	0.10	0.21	0.06	0.34	N/A	N/A
	Back	1	0.31	0.18	0.27	0.06	0.58	N/A	N/A
		50	0.17	0.18	0.27	0.06	0.44	N/A	N/A

Band	Test Position	Scaled SAR			Σ SAR (W/kg)	SPLSR	Remark
		Hotspot	WIFI 2.4G	WIFI 5G			
GSM850 (GPRS)	Front	0.44	0.12	0.31	0.75	N/A	N/A
	Back	0.71	0.20	0.38	1.09	N/A	N/A
	Right	/	0.09	0.06	0.09	N/A	N/A
	Left	0.12	/	/	0.12	N/A	
	Top	0.10	/	/	0.10	N/A	N/A
GSM1900 (GPRS)	Front	0.51	0.12	0.31	0.82	N/A	N/A
	Back	0.63	0.20	0.38	1.01	N/A	N/A
	Right	/	0.09	0.06	0.09	N/A	N/A
	Left	0.13	/	/	0.13	N/A	N/A
	Top	0.11	/	/	0.11	N/A	N/A
WCDMA Band II	Front	0.58	0.12	0.31	0.89	N/A	N/A
	Back	0.81	0.20	0.38	1.19	N/A	N/A
	Right	/	0.09	0.06	0.09	N/A	N/A
	Left	0.15	/	/	0.15	N/A	N/A
	Top	0.14	/	/	0.14	N/A	N/A
WCDMA Band V	Front	0.22	0.12	0.31	0.53	N/A	N/A
	Back	0.35	0.20	0.38	0.73	N/A	N/A
	Right	/	0.09	0.06	0.09	N/A	N/A
	Left	0.19	/	/	0.19	N/A	N/A
	Top	0.13	/	/	0.13	N/A	N/A

Band	Test Position	RB allocation	Scaled			Σ SAR (W/kg)	SPLSR	Remark
			Hotspot	WIFI2.4G	WIFI 5G			
LTE Band 2 QPSK (20MHz)	Front	1	0.43	0.12	0.31	0.74	N/A	N/A
		50	0.26	0.12	0.31	0.57	N/A	N/A
	Back	1	0.50	0.20	0.38	0.88	N/A	N/A
		50	0.25	0.20	0.38	0.63	N/A	N/A
	Right	1	/	0.09	0.06	0.09	N/A	N/A
		50	/	0.09	0.06	0.09	N/A	N/A
	Left	1	0.18	/	/	0.18	N/A	N/A
		50	0.11	/	/	0.11	N/A	N/A
	Top	1	0.13	/	/	0.13	N/A	N/A
		50	0.09	/	/	0.09	N/A	N/A
LTE Band 4 QPSK (20MHz)	Front	1	0.54	0.12	0.31	0.85	N/A	N/A
		50	0.37	0.12	0.31	0.68	N/A	N/A
	Back	1	0.61	0.20	0.38	0.99	N/A	N/A
		50	0.45	0.20	0.38	0.83	N/A	N/A
	Right	1	/	0.09	0.06	0.09	N/A	N/A
		50	/	0.09	0.06	0.09	N/A	N/A
	Left	1	0.18	/	/	0.18	N/A	N/A
		50	0.09	/	/	0.09	N/A	N/A
	Top	1	0.13	/	/	0.13	N/A	N/A
		50	0.11	/	/	0.11	N/A	N/A
LTE Band 5 QPSK (10MHz)	Front	1	0.22	0.12	0.31	0.53	N/A	N/A
		25	0.11	0.12	0.31	0.42	N/A	N/A
	Back	1	0.24	0.20	0.38	0.62	N/A	N/A
		25	0.21	0.20	0.38	0.59	N/A	N/A
	Right	1	/	0.09	0.06	0.09	N/A	N/A
		25	/	0.09	0.06	0.09	N/A	N/A
	Left	1	0.15	/	/	0.15	N/A	N/A
		25	0.09	/	/	0.09	N/A	N/A
	Top	1	0.12	/	/	0.12	N/A	N/A
		25	0.07	/	/	0.07	N/A	N/A

LTE Band 7 QPSK (10MHz)	Front	1	0.27	0.12	0.31	0.58	N/A	N/A
		50	0.22	0.12	0.31	0.53	N/A	N/A
	Back	1	0.35	0.20	0.38	0.73	N/A	N/A
		50	0.30	0.20	0.38	0.68	N/A	N/A
	Right	1	/	0.09	0.06	0.09	N/A	N/A
		50	/	0.09	0.06	0.09	N/A	N/A
	Left	1	0.08	/	/	0.08	N/A	N/A
		50	0.06	/	/	0.06	N/A	N/A
	Top	1	0.06	/	/	0.06	N/A	N/A
		50	0.04	/	/	0.04	N/A	N/A
LTE Band 26 QPSK (15MHz)	Front	1	0.56	0.12	0.31	0.87	N/A	N/A
		36	0.32	0.12	0.31	0.63	N/A	N/A
	Back	1	0.62	0.20	0.38	1.00	N/A	N/A
		36	0.45	0.20	0.38	0.83	N/A	N/A
	Right	1	/	0.09	0.06	0.09	N/A	N/A
		36	/	0.09	0.06	0.09	N/A	N/A
	Left	1	0.20	/	/	0.20	N/A	N/A
		36	0.10	/	/	0.10	N/A	N/A
	Top	1	0.19	/	/	0.19	N/A	N/A
		36	0.09	/	/	0.09	N/A	N/A
LTE Band 41 QPSK (20MHz)	Front	1	0.26	0.12	0.31	0.57	N/A	N/A
		50	0.14	0.12	0.31	0.45	N/A	N/A
	Back	1	0.34	0.20	0.38	0.72	N/A	N/A
		50	0.27	0.20	0.38	0.65	N/A	N/A
	Right	1	/	0.09	0.06	0.09	N/A	N/A
		50	/	0.09	0.06	0.09	N/A	N/A
	Left	1	0.17	/	/	0.17	N/A	N/A
		50	0.10	/	/	0.10	N/A	N/A
	Top	1	0.18	/	/	0.18	N/A	N/A
		50	0.11	/	/	0.11	N/A	N/A

Simultaneous Transmission Conclusion

The above numerical summed SAR results for all the case simultaneous transmission conditions were below the SAR limit. Therefore, the above analysis is sufficient to determine that simultaneous transmission cases will not exceed the SAR limit and therefore measured volumetric simultaneous SAR summation is not required per FCC KDB Publication 447498 D01v05r02.

10.6. Measurement Uncertainty (450MHz-3GHz)

UNCERTAINTY EVALUATION FOR HEADSET SAR									
Uncertainty Component	Description	Uncertainty Value(%)	Probably Distribution	Div.	(Ci) 1g	(Ci) 10g	Std. Unc. 1g(%)	Std. Unc. 10g(%)	v
Measurement system									
Probe calibration	7.2.1	5.8	N	1	1	1	5.8	5.8	∞
Axial isotropy	7.2.1.1	3.5	R	$\sqrt{3}$	$(1-C_p)^{1/2}$	$(1-C_p)^{1/2}$	1.43	1.43	∞
Hemispherical isotropy	7.2.1.1	5.9	R	$\sqrt{3}$	$\sqrt{C_p}$	$\sqrt{C_p}$	2.41	2.41	∞
Boundary Effects	7.2.1.4	1.00	R	$\sqrt{3}$	1	1	0.58	0.58	∞
Linearity	7.2.1.2	4.70	R	$\sqrt{3}$	1	1	2.71	2.71	∞
System detection limits	7.2.1.2	1	R	$\sqrt{3}$	1	1	0.58	0.58	∞
Modulation Response	7.2.1.3	3	N	1	1	1	3.00	3.00	∞
Readout Electronics	7.2.1.5	0.5	N	1	1	1	0.50	0.50	∞
Response Time	7.2.1.6	0	R	$\sqrt{3}$	1	1	0.00	0.00	∞
Integration Time	7.2.1.7	1.4	R	$\sqrt{3}$	1	1	0.81	0.81	∞
RF Ambient Conditions-Noise	7.2.3.7	3	R	$\sqrt{3}$	1	1	1.73	1.73	∞
RF Ambient Conditions-Reflection	7.2.3.7	3	R	$\sqrt{3}$	1	1	1.73	1.73	∞
Probe positioned mechanical Tolerance	7.2.2.1	1.4	R	$\sqrt{3}$	1	1	0.81	0.81	∞
Probe positioning with respect to phantom shell	7.2.2.3	1.4	R	$\sqrt{3}$	1	1	0.81	0.81	∞
Extrapolation interpolation and integration algorithms for Max.SAR evaluation	7.2.4	2.3	R	1	1	1	1.33	1.33	∞
Test sample related									
Test sample positioning	7.2.2.4.4	2.6	N	1	1	1	2.60	2.60	∞
Device holder uncertainty	7.2.2.4.2 7.2.2.4.3	3	N	1	1	1	3.00	3.00	∞
output power variation-SAR drift measurement	7.2.3.6	5	R	$\sqrt{3}$	1	1	2.89	2.89	∞
SAR scaling	7.2.5	2	R	$\sqrt{3}$	1	1	1.15	1.15	∞
Phantom and tissue parameters									
Phantom uncertainty (shape and thickness tolerances)	7.2.2.2	4	R	$\sqrt{3}$	1	1	2.31	2.31	∞
uncertainty in SAR correction for deviation (in permittivity and conductivity)	7.2.6	2	N	1	1	0.84	2.00	1.68	∞
Liquid conductivity (temperature uncertainty)	7.2.3.5	2.5	N	1	0.78	0.71	1.95	1.78	∞
Liquid conductivity -measurement uncertainty	7.2.3.3	4	N	1	0.23	0.26	0.92	1.04	∞
Liquid permittivity (temperature uncertainty)	7.2.3.5	2.5	N	1	0.78	0.71	1.95	1.78	∞
Liquid permittivity measurement uncertainty	7.2.3.4	5	N	1	0.23	0.26	1.15	1.30	∞
Combined standard uncertainty			RSS				10.83	10.54	
Expanded uncertainty (95%CONFIDENCEINTERVAL)			k				21.26	21.08	

UNCERTAINTY FOR PERFORMANCE CHECK

Uncertainty Component	Description	Uncertainty Value(%)	Probably Distribution	Div.	(Ci) 1g	(Ci) 10g	Std. Unc. 1g(%)	Std. Unc. 10g(%)	v
Measurement system									
Probe calibration	7.2.1	5.8	N	1	1	1	5.8	5.8	∞
Axial isotropy	7.2.1.1	3.5	R	$\sqrt{3}$	$(1-C_p)^{1/2}$	$(1-C_p)^{1/2}$	1.43	1.43	∞
Hemispherical isotropy	7.2.1.1	5.9	R	$\sqrt{3}$	$\sqrt{C_p}$	$\sqrt{C_p}$	2.41	2.41	∞
Boundary Effects	7.2.1.4	1.00	R	$\sqrt{3}$	1	1	0.58	0.58	∞
Linearity	7.2.1.2	4.70	R	$\sqrt{3}$	1	1	2.71	2.71	∞
System detection limits	7.2.1.2	1	R	$\sqrt{3}$	1	1	0.58	0.58	∞
Modulation Response	7.2.1.3	3	N	1	1	1	0.00	0.00	∞
Readout Electronics	7.2.1.5	0.5	N	1	1	1	0.50	0.50	∞
Response Time	7.2.1.6	0	R	$\sqrt{3}$	1	1	0.00	0.00	∞
Integration Time	7.2.1.7	1.4	R	$\sqrt{3}$	1	1	0.81	0.81	∞
RF Ambient Conditions-Noise	7.2.3.7	3	R	$\sqrt{3}$	1	1	1.73	1.73	∞
RF Ambient Conditions-Reflection	7.2.3.7	3	R	$\sqrt{3}$	1	1	1.73	1.73	∞
Probe positioned mechanical Tolerance	7.2.2.1	1.4	R	$\sqrt{3}$	1	1	0.81	0.81	∞
Probe positioning with respect to phantom shell	7.2.2.3	1.4	R	$\sqrt{3}$	1	1	0.81	0.81	∞
Extrapolation interpolation and integration algorithms for Max.SAR evaluation	7.2.4	2.3	R	1	1	1	1.33	1.33	∞
Dipole									
Deviation of experimental source from numerical source		4	N	1	1	1	4.00	4.00	∞
Input power and SAR drift measurement	7.2.3.6	5	R	$\sqrt{3}$	1	1	2.89	2.89	∞
Dipole axis to liquid distance		2	R	$\sqrt{3}$	1	1			∞
Phantom and tissue parameters									
Phantom uncertainty (shape and thickness tolerances)	7.2.2.2	4	R	$\sqrt{3}$	1	1	2.31	2.31	∞
uncertainty in SAR correction for deviation (in permittivity and conductivity)	7.2.6	2	N	1	1	0.84	2.00	1.68	∞
Liquid conductivity (temperature uncertainty)	7.2.3.5	2.5	N	1	0.78	0.71	1.95	1.78	∞
Liquid conductivity -measurement uncertainty	7.2.3.3	4	N	1	0.23	0.26	0.92	1.04	∞
Liquid permittivity (temperature uncertainty)	7.2.3.5	2.5	N	1	0.78	0.71	1.95	1.78	∞
Liquid permittivity measurement uncertainty	7.2.3.4	5	N	1	0.23	0.26	1.15	1.30	∞
Combined standard uncertainty			RSS				10.15	10.05	
Expanded uncertainty (95%CONFIDENCEINTE RVAL			k				20.29	20.10	

10.7. Test Equipment List

Test Equipment	Manufacturer	Model	Serial Number	Calibration	
				Calibration Date (D.M.Y)	Calibration Due (D.M.Y)
PC	Lenovo	H3050	N/A	N/A	N/A
Signal Generator	Agilent	N5182A	MY47070282	Jun. 28, 2020	Jun. 27, 2021
Multimeter	Keithley	Multimeter 2000	4078275	Jun. 28, 2020	Jun. 27, 2021
Network Analyzer	Agilent	8753E	US38432457	Jun. 28, 2020	Jun. 27, 2021
Wireless Communication Test Set	R & S	CMU200	111382	Jun. 28, 2020	Jun. 27, 2021
Wideband Radio Communication Tester	R&S	CMW500	114220	Jun. 28, 2020	Jun. 27, 2021
Power Meter	Agilent	E4418B	GB43312526	Jun. 28, 2020	Jun. 27, 2021
Power Meter	Agilent	E4416A	MY45101555	Jun. 28, 2020	Jun. 27, 2021
Power Meter	Agilent	N1912A	MY50001018	Jun. 28, 2020	Jun. 27, 2021
Power Sensor	Agilent	E9301A	MY41497725	Jun. 28, 2020	Jun. 27, 2021
Power Sensor	Agilent	E9327A	MY44421198	Jun. 28, 2020	Jun. 27, 2021
Power Sensor	Agilent	E9323A	MY53070005	Jun. 28, 2020	Jun. 27, 2021
Power Amplifier	PE	PE15A4019	112342	N/A	N/A
Directional Coupler	Agilent	722D	MY52180104	N/A	N/A
Attenuator	Chensheng	FF779	134251	N/A	N/A
E-Field PROBE	MVG	SSE2	SN 41/18 EPGO331	Aug. 02, 2020	Aug. 01, 2021
DIPOLE 835	MVG	SID835	SN 16/15 DIP 0G835-369	Jun. 05, 2018	Jun. 04, 2021
DIPOLE 1800	MVG	SID 1800	SN 16/15 DIP 1G800-371	Jun. 05, 2018	Jun. 04, 2021
DIPOLE 1900	MVG	SID1900	SN 16/15 DIP 1G900-372	Jun. 05, 2018	Jun. 04, 2021
DIPOLE 2450	MVG	SID 2450	SN 16/15 DIP 2G450-374	Jun. 05, 2018	Jun. 04, 2021
DIPOLE 2600	MVG	SID 2600	SN 16/15 DIP 2G600-375	Jun. 05, 2018	Jun. 04, 2021
DIPOLE 5G	MVG	SID 5G	SN 13/14 WGA32	May. 15, 2019	May. 14, 2022
Limesar Dielectric Probe	MVG	SCLMP	SN 19/15 OCPG71	Jun. 05, 2018	Jun. 04, 2021
Communication Antenna	MVG	ANTA59	SN 39/14 ANTA59	N/A	N/A
Mobile Phone Position Device	MVG	MSH101	SN 19/15 MSH101	N/A	N/A
Dummy Probe	MVG	DP66	SN 13/15 DP66	N/A	N/A
SAM PHANTOM	MVG	SAM120	SN 19/15 SAM120	N/A	N/A
PHANTOM TABLE	MVG	TABP101	SN 19/15 TABP101	N/A	N/A
Robot TABLE	MVG	TABP61	SN 19/15 TABP61	N/A	N/A
6 AXIS ROBOT	KUKA	KR6-R900	501822	N/A	N/A

Note:1.N/A means this equipment no need to calibrate

2.Each Time means this device need to calibrate every use time

3. The dipole was not damaged properly repaired.

4. The measured SAR deviates from the calibrated SAR value by less than 10%

5. The most recent return-loss result meets the required 20 dB minimum return-loss requirement

6. The most recent measurement of the real or imaginary parts of the impedance deviates by less than 5 Ω from the previous measurement.

11. System Check Results

Date of measurement: 02/18/2021 Test mode: 835 (Head)


Product Description: Validation

Dipole Model: SID835



E-Field Probe: SSE2 (SN 41/18 EPGO331)

Phantom	Validation plane
Input Power	100mW
Crest Factor	1.0
Probe Conversion factor	1.80
Frequency (MHz)	835.000000
Relative permittivity (real part)	41.417760
Relative permittivity (imaginary part)	18.129852
Conductivity (S/m)	0.874923
Variation (%)	-0.090000
SAR 10g (W/Kg)	0.570250
SAR 1g (W/Kg)	0.886135


SURFACE SAR



VOLUME SAR



Z (mm)	0.00	4.00	9.00	14.00	19.00
SAR (W/Kg)	0.8625	0.5302	0.2594	0.1302	0.1025



Hot spot position



Date of measurement: 02/18/2021 Test mode: 835 (Body)


Product Description: Validation

Dipole Model: SID835



E-Field Probe: SSE2 (SN 41/18 EPGO331)

Phantom	Validation plane
Input Power	100mW
Crest Factor	1.0
Probe Conversion factor	1.86
Frequency (MHz)	835.000000
Relative permittivity (real part)	55.242077
Relative permittivity (imaginary part)	21.378187
Conductivity (S/m)	0.938883
Variation (%)	-0.150000
SAR 10g (W/Kg)	0.633123
SAR 1g (W/Kg)	0.949446


SURFACE SAR



VOLUME SAR



Z (mm)	0.00	4.00	9.00	14.00	19.00
SAR (W/Kg)	0.9625	0.6022	0.3594	0.2202	0.0725



Hot spot position



Date of measurement: 02/19/2021 Test mode: 1800MHz (Head)


Product Description: Validation

Dipole Model: SID1800



E-Field Probe: SSE2 (SN 41/18 EPGO331)

Phantom	Validation plane
Input Power	100mW
Crest Factor	1.0
Probe Conversion factor	2.08
Frequency (MHz)	1800.000000
Relative permittivity (real part)	39.070000
Relative permittivity (imaginary part)	14.000000
Conductivity (S/m)	1.38000
Variation (%)	1.250000
SAR 10g (W/Kg)	2.201458
SAR 1g (W/Kg)	3.752497


SURFACE SAR



VOLUME SAR



Z (mm)	0.00	4.00	9.00	14.00	19.00
SAR (W/Kg)	3.7625	2.6254	2.0245	1.6254	1.0214



Hot spot position



Date of measurement: 02/19/2021 Test mode: 1800MHz (Body)


Product Description: Validation

Dipole Model: SID1800



E-Field Probe: SSE2 (SN 41/18 EPGO331)

Phantom	Validation plane
Input Power	100mW
Crest Factor	1.0
Probe Conversion factor	2.16
Frequency (MHz)	1800.000000
Relative permittivity (real part)	53.292699
Relative permittivity (imaginary part)	15.200000
Conductivity (S/m)	1.530000
Variation (%)	3.050000
SAR 10g (W/Kg)	2.053687
SAR 1g (W/Kg)	3.782547


SURFACE SAR




VOLUME SAR



Z (mm)	0.00	4.00	9.00	14.00	19.00
SAR (W/Kg)	3.7545	2.4524	1.3520	0.8214	0.5525



Hot spot position



Date of measurement: 02/20/2021 Test mode: 1900MHz (Head)


Product Description: Validation

Dipole Model: SID1900



E-Field Probe: SSE2 (SN 41/18 EPGO331)

Phantom	Validation plane
Input Power	100mW
Crest Factor	1.0
Probe Conversion factor	2.23
Frequency (MHz)	1900.000000
Relative permittivity (real part)	39.076721
Relative permittivity (imaginary part)	12.607061
Conductivity (S/m)	1.367609
Variation (%)	-0.910000
SAR 10g (W/Kg)	1.899324
SAR 1g (W/Kg)	3.576354


SURFACE SAR



VOLUME SAR



Z (mm)	0.00	4.00	9.00	14.00	19.00
SAR (W/Kg)	3.5325	2.5687	1.7025	1.3025	0.1125



Hot spot position



Date of measurement: 02/20/2021 Test mode: 1900MHz (Body)


Product Description: Validation

Dipole Model: SID1900



E-Field Probe: SSE2 (SN 41/18 EPGO331)

Phantom	Validation plane
Input Power	100mW
Crest Factor	1.0
Probe Conversion factor	2.32
Frequency (MHz)	1900.000000
Relative permittivity (real part)	53.309999
Relative permittivity (imaginary part)	14.329440
Conductivity (S/m)	1.510354
Variation (%)	1.250000
SAR 10g (W/Kg)	1.994255
SAR 1g (W/Kg)	3.766112


SURFACE SAR



VOLUME SAR



Z (mm)	0.00	4.00	9.00	14.00	19.00
SAR (W/Kg)	3.7752	2.7154	1.9525	1.5694	0.9014



Hot spot position



Date of measurement: 02/22/2021 Test mode: 2450MHz (Head)


Product Description: Validation

Dipole Model: SID2450



E-Field Probe: SSE2 (SN 41/18 EPGO331)

Phantom	Validation plane
Input Power	100mW
Crest Factor	1.0
Probe Conversion factor	2.31
Frequency (MHz)	2450.000000
Relative permittivity (real part)	37.821613
Relative permittivity (imaginary part)	13.546980
Conductivity (S/m)	1.834111
Variation (%)	-0.470000
SAR 10g (W/Kg)	2.364445
SAR 1g (W/Kg)	4.994244


SURFACE SAR



VOLUME SAR



Z (mm)	0.00	4.00	9.00	14.00	19.00
SAR (W/Kg)	5.0262	2.7584	1.5026	0.8252	0.4125



Hot spot position



Date of measurement: 02/22/2021 Test mode: 2450MHz (Body)


Product Description: Validation

Dipole Model: SID2450



E-Field Probe: SSE2 (SN 41/18 EPGO331)

Phantom	Validation plane
Input Power	100mW
Crest Factor	1.0
Probe Conversion factor	2.37
Frequency (MHz)	2450.000000
Relative permittivity (real part)	54.616199
Relative permittivity (imaginary part)	14.930150
Conductivity (S/m)	2.012159
Variation (%)	-0.230000
SAR 10g (W/Kg)	2.416669
SAR 1g (W/Kg)	5.066368


SURFACE SAR



VOLUME SAR



Z (mm)	0.00	4.00	9.00	14.00	19.00
SAR (W/Kg)	5.0622	2.7984	1.5251	0.8352	0.4200



Hot spot position



Date of measurement: 02/23/2021 Test mode: 2600MHz (Head)


Product Description: Validation

Dipole Model: SID2600



E-Field Probe: SSE2 (SN 41/18 EPGO331)

Phantom	Validation plane
Input Power	100mW
Crest Factor	1.0
Probe Conversion factor	2.16
Frequency (MHz)	2535.000000
Relative permittivity (real part)	38.853477
Relative permittivity (imaginary part)	13.545489
Conductivity (S/m)	1.922567
Variation (%)	-1.360000
SAR 10g (W/Kg)	2.430127
SAR 1g (W/Kg)	5.413744


SURFACE SAR



VOLUME SAR



Z (mm)	0.00	4.00	9.00	14.00	19.00
SAR (W/Kg)	5.7893	3.2375	0.2098	0.0387	0.0249



Hot spot position





Date of measurement: 02/23/2021 Test mode: 2600MHz (Body)

Product Description: Validation


Dipole Model: SID2600

E-Field Probe: SSE2 (SN 41/18 EPGO331)

Phantom	Validation plane
Input Power	100mW
Crest Factor	1.0
Probe Conversion factor	2.23
Frequency (MHz)	2535.000000
Relative permittivity (real part)	52.013887
Relative permittivity (imaginary part)	14.935214
Conductivity (S/m)	2.114821
Variation (%)	-1.800000
SAR 10g (W/Kg)	2.382177
SAR 1g (W/Kg)	5.365098



Z (mm)	0.00	4.00	9.00	14.00	19.00
SAR (W/Kg)	5.7721	3.2210	0.1937	0.0321	0.0203



Hot spot position



Date of measurement: 02/23/2021 Test mode: 5200MHz (Head)


Product Description: Validation

Dipole Model: SID5200



E-Field Probe: SSE2 (SN 41/18 EPGO331)

Phantom	Validation plane
Input Power	100mW
Crest Factor	1.0
Probe Conversion factor	2.01
Frequency (MHz)	5200.000000
Relative permittivity (real part)	35.068832
Relative permittivity (imaginary part)	13.679428
Conductivity (S/m)	5.220788
Variation (%)	-0.820000
SAR 10g (W/Kg)	1.807521
SAR 1g (W/Kg)	5.012481


SURFACE SAR



VOLUME SAR



Z (mm)	0.00	4.00	9.00	14.00	19.00
SAR (W/Kg)	5.0132	2.7584	1.5026	0.8252	0.4125



Hot spot position



Date of measurement: 02/23/2021 Test mode: 5800MHz (Head)


Product Description: Validation

Dipole Model: SID5800



E-Field Probe: SSE2 (SN 41/18 EPGO331)

Phantom	Validation plane
Input Power	100mW
Crest Factor	1.0
Probe Conversion factor	2.06
Frequency (MHz)	5800.000000
Relative permittivity (real part)	38.352823
Relative permittivity (imaginary part)	13.671675
Conductivity (S/m)	5.430828
Variation (%)	-2.800000
SAR 10g (W/Kg)	2.005121
SAR 1g (W/Kg)	5.063573


SURFACE SAR




VOLUME SAR



Z (mm)	0.00	4.00	9.00	14.00	19.00
SAR (W/Kg)	5.0622	2.8054	1.5421	0.8321	0.4130



Hot spot position



Date of measurement: 02/23/2021 Test mode: 5200 (Body)


Product Description: Validation

Dipole Model: SID5000



E-Field Probe: SSE2 (SN 41/18 EPGO331)

Phantom	Validation plane
Input Power	100mW
Crest Factor	1.0
Probe Conversion factor	2.08
Frequency (MHz)	5200.000000
Relative permittivity (real part)	49.012077
Relative permittivity (imaginary part)	21.378187
Conductivity (S/m)	5.458883
Variation (%)	-3.140000
SAR 10g (W/Kg)	5.633123
SAR 1g (W/Kg)	2.949446


SURFACE SAR



VOLUME SAR



Z (mm)	0.00	4.00	9.00	14.00	19.00
SAR (W/Kg)	5.9525	0.6022	0.3594	0.2202	0.0725




Hot spot position





Date of measurement: 02/23/2021 Test mode: 5800MHz (Body)
 Product Description: Validation
 Dipole Model: SID5000
 E-Field Probe: SSE2 (SN 41/18 EPGO331)

Phantom	Validation plane
Input Power	100mW
Crest Factor	1.0
Probe Conversion factor	2.13
Frequency (MHz)	5800.000000
Relative permittivity (real part)	47.393887
Relative permittivity (imaginary part)	14.935214
Conductivity (S/m)	6.274821
Variation (%)	-1.420000
SAR 10g (W/Kg)	5.382177
SAR 1g (W/Kg)	2.365098


SURFACE SAR



VOLUME SAR



Z (mm)	0.00	4.00	9.00	14.00	19.00
SAR (W/Kg)	5.7721	3.2210	0.1937	0.0321	0.0203



Hot spot position



12. SAR Test Data

GSM850


MEASUREMENT 1

Lower Band SAR (Channel 128)


Date: 02/18/2021

Frequency (MHz)	824.200000
Relative permittivity (real part)	40.387760
Relative permittivity (imaginary part)	18.129852
Conductivity (S/m)	0.884923
Variation (%)	3.240000
Crest Factor:	1.0
Probe Conversion factor	1.80
E-Field Probe:	SSE2 (SN 41/18 EPG0331)
Area Scan	dx=8mm dy=8mm, h= 5.00 mm
ZoomScan	5x5x7, dx=8mm dy=8mm dz=5mm, Complete/ndx=8mm dy=8mm, h= 5.00 mm
Phantom	Left head
Device Position	Cheek
Band	GSM850(voice)

SURFACE SAR



VOLUME SAR




Maximum location: X=-49.00, Y=-39.00 SAR Peak: 0.75 W/kg

SAR 10g (W/Kg)


0.284282

SAR 1g (W/Kg)


0.421701



Z (mm)	0.00	4.00	9.00	14.00	19.00
SAR (W/Kg)	0.9139	0.6546	0.4255	0.2757	0.1792



Hot spot position




MEASUREMENT 2

Lower Band SAR (Channel 128)


Date: 02/18/2021

Frequency (MHz)	824.200000
Relative permittivity (real part)	55.212927
Relative permittivity (imaginary part)	21.368266
Conductivity (S/m)	0.971230
Variation (%)	-4.600000
Crest Factor:	1.0
Probe Conversion factor	1.86
E-Field Probe:	SSE2 (SN 41/18 EPG0331)
Area Scan	<u>dx=8mm dy=8mm, h= 5.00 mm</u>
ZoomScan	<u>5x5x7, dx=8mm dy=8mm</u> <u>dz=5mm, Complete/ndx=8mm dy=8mm, h=</u> <u>5.00 mm</u>
Phantom	<u>Validation plane</u>
Device Position	<u>Body back(10mm)</u>
Band	<u>GSM850(Voice)</u>

SURFACE SAR




VOLUME SAR




Maximum location: X=0.00, Y=-15.00 SAR Peak: 0.43 W/kg


SAR 10g (W/Kg)	0.259375
SAR 1g (W/Kg)	0.339121



Z (mm)	0.00	4.00	9.00	14.00	19.00
SAR (W/Kg)	0.9547	0.3493	0.2145	0.2163	0.1300



Hot spot position




MEASUREMENT 3

Middle Band SAR (Channel 190)


Date: 02/18/2021

Frequency (MHz)	836.600000
Relative permittivity (real part)	55.212927
Relative permittivity (imaginary part)	21.368266
Conductivity (S/m)	0.971230
Variation (%)	0.200000
Crest Factor:	1.0
Probe Conversion factor	1.86
E-Field Probe:	SSE2 (SN 41/18 EPG0331)
Area Scan	<u>dx=8mm dy=8mm, h= 5.00 mm</u>
ZoomScan	<u>5x5x7, dx=8mm dy=8mm</u> <u>dz=5mm, Complete/ndx=8mm dy=8mm, h=</u> <u>5.00 mm</u>
Phantom	<u>Validation plane</u>
Device Position	<u>Body back(10mm)</u>
Band	<u>GSM850(GPRS 2slot)</u>

SURFACE SAR




VOLUME SAR




Maximum location: X=-8.00, Y=-14.00 SAR Peak: 0.84 W/kg


SAR 10g (W/Kg)	0.494016
SAR 1g (W/Kg)	0.660314



Z (mm)	0.00	4.00	9.00	14.00	19.00
SAR (W/Kg)	0.8297	0.6798	0.5281	0.4101	0.3180



Hot spot position




MEASUREMENT 4

Middle Band SAR (Channel 190)


Date: 02/18/2021

Frequency (MHz)	836.600000
Relative permittivity (real part)	55.212927
Relative permittivity (imaginary part)	21.378266
Conductivity (S/m)	0.971230
Variation (%)	-0.370000
Crest Factor:	1.0
Probe Conversion factor	1.86
E-Field Probe:	SSE2 (SN 41/18 EPG0331)
Area Scan	<u>dx=8mm dy=8mm, h= 5.00 mm</u>
ZoomScan	<u>5x5x7, dx=8mm dy=8mm</u> <u>dz=5mm, Complete/ndx=8mm dy=8mm, h=</u> <u>5.00 mm</u>
Phantom	<u>Validation plane</u>
Device Position	<u>Body back(10mm)</u>
Band	<u>GSM850(GPRS 2slot hotspot)</u>

SURFACE SAR




VOLUME SAR




Maximum location: X=0.00, Y=-8.00 SAR Peak: 0.92 W/kg


SAR 10g (W/Kg)	0.530886
SAR 1g (W/Kg)	0.709812



Z (mm)	0.00	4.00	9.00	14.00	19.00
SAR (W/Kg)	1.0470	0.7349	0.5467	0.4377	0.3352



Hot spot position



GSM1900


MEASUREMENT 1

Middle Band SAR (Channel 661):


Date: 02/19/2021

Frequency (MHz)	1880.000000
Relative permittivity (real part)	39.075208
Relative permittivity (imaginary part)	12.607628
Conductivity (S/m)	1.372108
Variation (%)	0.420000
Crest Factor	1.0
Probe Conversion factor	2.23
E-Field Probe:	SSE2 (SN 41/18 EPG0331)
Area Scan	<u>dx=8mm dy=8mm, h= 5.00 mm</u>
ZoomScan	<u>5x5x7,dx=8mm dy=8mm</u> <u>dz=5mm,Complete/ndx=8mm dy=8mm, h=</u> <u>5.00 mm</u>
Phantom	<u>Left head</u>
Device Position	<u>Cheek</u>
Band	<u>GSM1900(voice)</u>

SURFACE SAR




VOLUME SAR




Maximum location: X=-74.00, Y=-23.00 SAR Peak: 0.56 W/kg


SAR 10g (W/Kg)	0.239449
SAR 1g (W/Kg)	0.377428



Z (mm)	0.00	4.00	9.00	14.00	19.00
SAR (W/Kg)	0.5344	0.3907	0.2608	0.1730	0.1144



Hot spot position




MEASUREMENT 2

Middle Band SAR (Channel 661):


Date: 02/19/2021

Frequency (MHz)	1880.000000
Relative permittivity (real part)	53.291337
Relative permittivity (imaginary part)	14.322400
Conductivity (S/m)	1.531736
Variation (%)	-1.680000
Crest Factor	1.0
Probe Conversion factor	2.32
E-Field Probe:	SSE2 (SN 41/18 EPG0331)
Area Scan	<u>dx=8mm dy=8mm, h= 5.00 mm</u>
ZoomScan	<u>5x5x7,dx=8mm dy=8mm</u> <u>dz=5mm,Complete/ndx=8mm dy=8mm, h=</u> <u>5.00 mm</u>
Phantom	<u>Validation plane</u>
Device Position	<u>Body back(10mm)</u>
Band	<u>GSM1900(voice)</u>

SURFACE SAR




VOLUME SAR




Maximum location: X=0.00, Y=-47.00 SAR Peak: 0.84 W/kg


SAR 10g (W/Kg)	0.305824
SAR 1g (W/Kg)	0.540363



Z (mm)	0.00	4.00	9.00	14.00	19.00
SAR (W/Kg)	0.8414	0.5805	0.3567	0.2159	0.1294



Hot spot position




MEASUREMENT 3

Lower Band SAR (Channel 512):


Date: 02/19/2021

Frequency (MHz)	1850.200000
Relative permittivity (real part)	53.291337
Relative permittivity (imaginary part)	14.322400
Conductivity (S/m)	1.531736
Variation (%)	-0.930000
Crest Factor	1.0
Probe Conversion factor	2.32
E-Field Probe:	SSE2 (SN 41/18 EPG0331)
Area Scan	<u>dx=8mm dy=8mm, h= 5.00 mm</u>
ZoomScan	<u>5x5x7, dx=8mm dy=8mm</u> <u>dz=5mm, Complete/ndx=8mm dy=8mm, h=</u> <u>5.00 mm</u>
Phantom	<u>Validation plane</u>
Device Position	<u>Body back(10mm)</u>
Band	<u>GSM1900(GPRS 2slot)</u>

SURFACE SAR




VOLUME SAR




Maximum location: X=-3.00, Y=-43.00 SAR Peak: 1.36 W/kg


SAR 10g (W/Kg)	0.469354
SAR 1g (W/Kg)	0.610432



Z (mm)	0.00	4.00	9.00	14.00	19.00
SAR (W/Kg)	1.3494	0.8980	0.5288	0.3119	0.1885



Hot spot position



MEASUREMENT 4


Lower Band SAR (Channel 512):
02/19/2021

Date:


Frequency (MHz)	1850.200000
Relative permittivity (real part)	53.341337
Relative permittivity (imaginary part)	14.322400
Conductivity (S/m)	1.491736
Variation (%)	1.840000
Crest Factor	1.0
Probe Conversion factor	2.32
E-Field Probe:	SSE2 (SN 41/18 EPG0331)
Area Scan	<u>dx=8mm dy=8mm, h= 5.00 mm</u>
ZoomScan	<u>5x5x7, dx=8mm dy=8mm</u> <u>dz=5mm, Complete/ndx=8mm dy=8mm, h=</u> <u>5.00 mm</u>

Phantom	<u>Validation plane</u>
Device Position	<u>Body back(10mm)</u>
Band	<u>GSM1900(GPRS 3slot hotspot)</u>

SURFACE SAR




VOLUME SAR




Maximum location: X=-2.00, Y=-38.00 SAR Peak: 1.80 W/kg


SAR 10g (W/Kg)	0.365070
SAR 1g (W/Kg)	0.641860





Z (mm)	0.00	4.00	9.00	14.00	19.00
SAR (W/Kg)	1.7861	1.1445	0.6398	0.3597	0.2111




Hot spot position




WCDMA Band II MEASUREMENT 1


Lower Band SAR (Channel 9262):		Date: 02/20/2021
Frequency (MHz)	1852.400000	
Relative permittivity (real part)	39.072437	
Relative permittivity (imaginary part)	12.607241	
Conductivity (S/m)	1.377279	
Variation (%)	2.460000	
Crest Factor	1.0	
Probe Conversion factor	2.23	
E-Field Probe:	SSE2 (SN 41/18 EPG0331)	
Area Scan	dx=8mm dy=8mm, h= 5.00 mm	
ZoomScan	5x5x7,dx=8mm dy=8mm dz=5mm,Complete/ndx=8mm dy=8mm, h= 5.00 mm	
Phantom	Left head	
Device Position	Cheek	
Band	BAND2 WCDMA1900	
SURFACE SAR	VOLUME SAR	
		
Maximum location: X=-66.00, Y=-5.00 SAR Peak: 0.83 W/kg		
SAR 10g (W/Kg)	0.148773	
SAR 1g (W/Kg)	0.362938	



Z (mm)	0.00	4.00	9.00	14.00	19.00
SAR (W/Kg)	0.8227	0.5938	0.3887	0.2521	0.1623



Hot spot position




MEASUREMENT 2

Lower Band SAR (Channel 9262):


Date: 02/20/2021

Frequency (MHz)	1852.400000
Relative permittivity (real part)	53.291337
Relative permittivity (imaginary part)	14.232400
Conductivity (S/m)	1.526736
Variation (%)	-1.730000
Crest Factor	1.0
Probe Conversion factor	2.32
E-Field Probe:	SSE2 (SN 41/18 EPGO331)
Area Scan	<u>dx=8mm dy=8mm, h= 5.00 mm</u>
ZoomScan	<u>5x5x7, dx=8mm dy=8mm</u> <u>dz=5mm, Complete/ndx=8mm dy=8mm, h=</u> <u>5.00 mm</u>
Phantom	<u>Validation plane</u>
Device Position	<u>Body back(10mm)</u>
Band	<u>BAND2 WCDMA1900</u>

SURFACE SAR



VOLUME SAR




Maximum location: X=18.00, Y=15.00 SAR Peak: 1.02 W/kg

SAR 10g (W/Kg)


0.403860

SAR 1g (W/Kg)


0.676382



Z (mm)	0.00	4.00	9.00	14.00	19.00
SAR (W/Kg)	1.0209	0.7136	0.4457	0.2737	0.1655



Hot spot position



MEASUREMENT 3


Lower Band SAR (Channel 9262):

Date: 02/20/2021


Frequency (MHz)	1852.400000
Relative permittivity (real part)	53.291337
Relative permittivity (imaginary part)	14.232400
Conductivity (S/m)	1.526736
Variation (%)	0.240000
Crest Factor	1.0
Probe Conversion factor	2.32
E-Field Probe:	SSE2 (SN 41/18 EPGO331)
Area Scan	<u>dx=8mm dy=8mm, h= 5.00 mm</u>
ZoomScan	<u>5x5x7, dx=8mm dy=8mm</u> <u>dz=5mm, Complete/ndx=8mm dy=8mm, h=</u> <u>5.00 mm</u>

Phantom	Validation plane
Device Position	Body back(10mm)
Band	BAND2 WCDMA1900(hotspot)


SURFACE SAR





Z (mm)	0.00	4.00	9.00	14.00	19.00
SAR (W/Kg)	1.1768	0.8159	0.5054	0.3095	0.1885




Hot spot position




WCDMA Band V MEASUREMENT 1


Lower Band SAR (Channel 4132):		Date: 02/18/2021
Frequency (MHz)	826.400000	
Relative permittivity (real part)	41.422883	
Relative permittivity (imaginary part)	18.129634	
Conductivity (S/m)	0.867241	
Variation (%)	1.480000	
Crest Factor:	1.0	
Probe Conversion factor	1.80	
E-Field Probe:	SSE2 (SN 41/18 EPG0331)	
Area Scan	dx=8mm dy=8mm, h= 5.00 mm	
ZoomScan	5x5x7,dx=8mm dy=8mm dz=5mm,Complete/ndx=8mm dy=8mm, h= 5.00 mm	
Phantom	Left head	
Device Position	Cheek	
Band	BAND5 WCDMA850	
SURFACE SAR		VOLUME SAR
		
Maximum location: X=-53.00, Y=-38.00 SAR Peak: 0.41 W/kg		
SAR 10g (W/Kg)		0.231938
SAR 1g (W/Kg)		0.323504



Z (mm)	0.00	4.00	9.00	14.00	19.00
SAR (W/Kg)	0.4100	0.3377	0.2619	0.2003	0.1504



Hot spot position




MEASUREMENT 2

Lower Band SAR (Channel 4132):


Date: 02/18/2021

Frequency (MHz)	826.400000
Relative permittivity (real part)	55.262927
Relative permittivity (imaginary part)	21.378266
Conductivity (S/m)	0.931230
Variation (%)	1.110000
Crest Factor:	1.0
Probe Conversion factor	1.86
E-Field Probe:	SSE2 (SN 41/18 EPG0331)
Area Scan	dx=8mm dy=8mm, h= 5.00 mm
ZoomScan	5x5x7, dx=8mm dy=8mm dz=5mm, Complete/ndx=8mm dy=8mm, h= 5.00 mm
Phantom	Validation plane
Device Position	Body back(10mm)
Band	BAND5 WCDMA850

SURFACE SAR




VOLUME SAR




Maximum location: X=-1.00, Y=0.00 SAR Peak: 0.40 W/kg


SAR 10g (W/Kg)	0.236853
SAR 1g (W/Kg)	0.318832



Z (mm)	0.00	4.00	9.00	14.00	19.00
SAR (W/Kg)	0.4019	0.3300	0.2561	0.1978	0.1515



Hot spot position




MEASUREMENT 3

Lower Band SAR (Channel 4132):


Date: 02/18/2021

Frequency (MHz)	826.400000
Relative permittivity (real part)	55.262927
Relative permittivity (imaginary part)	21.378266
Conductivity (S/m)	0.931230
Variation (%)	0.010000
Crest Factor:	1.0
Probe Conversion factor	1.86
E-Field Probe:	SSE2 (SN 41/18 EPG0331)
Area Scan	<u>dx=8mm dy=8mm, h= 5.00 mm</u>
ZoomScan	<u>5x5x7,dx=8mm dy=8mm</u> <u>dz=5mm,Complete/ndx=8mm dy=8mm, h=</u> <u>5.00 mm</u>
Phantom	<u>Validation plane</u>
Device Position	<u>Body back(10mm)</u>
Band	<u>BAND5 WCDMA850(hotspot)</u>

SURFACE SAR




VOLUME SAR




Maximum location: X=2.00, Y=-7.00 SAR Peak: 0.40 W/kg


SAR 10g (W/Kg)	0.239471
SAR 1g (W/Kg)	0.321681



Z (mm)	0.00	4.00	9.00	14.00	19.00
SAR (W/Kg)	0.4021	0.3326	0.2598	0.2008	0.1530



Hot spot position




LTE Band 2

MEASUREMENT 1


Hight Band SAR (Channel 19100): Date: 02/20/2021

Frequency (MHz)	1900.000000
Relative permittivity (real part)	39.065208
Relative permittivity (imaginary part)	12.607628
Conductivity (S/m)	1.382108
Variation (%)	0.210000
Crest Factor	1.0
Probe Conversion factor	2.23
E-Field Probe:	SSE2 (SN 41/18 EPG0331)
Area Scan	<u>dx=8mm dy=8mm, h= 5.00 mm</u>
ZoomScan	<u>5x5x7,dx=8mm dy=8mm</u> <u>dz=5mm,Complete/ndx=8mm dy=8mm, h=</u> <u>5.00 mm</u>
Phantom	<u>Left head</u>
Device Position	<u>Cheek</u>
Band	<u>LTE band 2 (1 RB#49)</u>

SURFACE SAR




VOLUME SAR




Maximum location: X=-22.00, Y=-21.00 SAR Peak: 0.40 W/kg


SAR 10g (W/Kg)	0.103810
SAR 1g (W/Kg)	0.293110



Z (mm)	0.00	4.00	9.00	14.00	19.00
SAR (W/Kg)	0.6282	0.4222	0.3397	0.2201	0.1424



Hot spot position




MEASUREMENT 2

Hight Band SAR (Channel 19100)::


Date: 02/20/2021

Frequency (MHz)	1900.000000
Relative permittivity (real part)	53.291337
Relative permittivity (imaginary part)	14.232400
Conductivity (S/m)	1.531736
Variation (%)	0.170000
Crest Factor	1.0
Probe Conversion factor	2.32
E-Field Probe:	SSE2 (SN 41/18 EPG0331)
Area Scan	<u>dx=8mm dy=8mm, h= 5.00 mm</u>
ZoomScan	<u>5x5x7,dx=8mm dy=8mm</u> <u>dz=5mm,Complete/ndx=8mm dy=8mm, h=</u> <u>5.00 mm</u>
Phantom	<u>Validation plane</u>
Device Position	<u>Body back(10mm)</u>
Band	<u>LTE band 2 (1 RB#49)</u>

SURFACE SAR




VOLUME SAR




Maximum location: X=24.00, Y=17.00 SAR Peak: 0.51 W/kg


SAR 10g (W/Kg)	0.227129
SAR 1g (W/Kg)	0.440050



Z (mm)	0.00	4.00	9.00	14.00	19.00
SAR (W/Kg)	0.8200	0.4342	0.2142	0.0900	0.0345



Hot spot position




MEASUREMENT 3

Hight Band SAR (Channel 19100)::


Date: 02/20/2021

Frequency (MHz)	1900.000000
Relative permittivity (real part)	53.291337
Relative permittivity (imaginary part)	14.232400
Conductivity (S/m)	1.531736
Variation (%)	-2.550000
Crest Factor	1.0
Probe Conversion factor	2.32
E-Field Probe:	SSE2 (SN 41/18 EPG0331)
Area Scan	<u>dx=8mm dy=8mm, h= 5.00 mm</u>
ZoomScan	<u>5x5x7,dx=8mm dy=8mm</u> <u>dz=5mm,Complete/ndx=8mm dy=8mm, h=</u> <u>5.00 mm</u>
Phantom	Validation plane
Device Position	<u>Body back(hotspot 10mm)</u>
Band	<u>LTE band 2 (1 RB#49)</u>

SURFACE SAR




VOLUME SAR




Maximum location: X=13.00, Y=17.00 SAR Peak: 0.70 W/kg


SAR 10g (W/Kg)	0.243211
SAR 1g (W/Kg)	0.482330



Z (mm)	0.00	4.00	9.00	14.00	19.00
SAR (W/Kg)	0.8721	0.5112	0.1933	0.0877	0.0287



Hot spot position



LTE Band 4


MEASUREMENT 1

Middle Band SAR (Channel 20175):


Date: 02/19/2021

Frequency (MHz)	1732.500000
Relative permittivity (real part)	39.101249
Relative permittivity (imaginary part)	12.468850
Conductivity (S/m)	1.350792
Variation (%)	-1.020000
Crest Factor	1.0
Probe Conversion factor	2.08
E-Field Probe:	SSE2 (SN 41/18 EPG0331)
Area Scan	dx=8mm dy=8mm, h= 5.00 mm
ZoomScan	5x5x7, dx=8mm dy=8mm dz=5mm, Complete/ndx=8mm dy=8mm, h= 5.00 mm
Phantom	Left head
Device Position	Cheek
Band	LTE band 4(1 RB#49)

SURFACE SAR



VOLUME SAR




Maximum location: X=-67.00, Y=-15.00 SAR Peak: 0.51 W/kg

SAR 10g (W/Kg)


0.155039

SAR 1g (W/Kg)


0.321117



Z (mm)	0.00	4.00	9.00	14.00	19.00
SAR (W/Kg)	0.6064	0.4440	0.2912	0.1923	0.1315



Hot spot position




MEASUREMENT 2

Middle Band SAR (Channel 20175):


Date: 02/19/2021

Frequency (MHz)	1732.500000
Relative permittivity (real part)	53.321249
Relative permittivity (imaginary part)	12.468850
Conductivity (S/m)	1.502592
Variation (%)	0.210000
Crest Factor	1.0
Probe Conversion factor	2.16
E-Field Probe:	SSE2 (SN 41/18 EPG0331)
Area Scan	<u>dx=8mm dy=8mm, h= 5.00 mm</u>
ZoomScan	<u>5x5x7,dx=8mm dy=8mm</u> <u>dz=5mm,Complete/ndx=8mm dy=8mm, h=</u> <u>5.00 mm</u>
Phantom	Validation plane
Device Position	Body back(10mm)
Band	LTE band 4(1 RB#49)

SURFACE SAR




VOLUME SAR




Maximum location: X=-23.00, Y=36.00 SAR Peak: 1.01 W/kg


SAR 10g (W/Kg)	0.289505
SAR 1g (W/Kg)	0.556694



Z (mm)	0.00	4.00	9.00	14.00	19.00
SAR (W/Kg)	1.0050	0.5801	0.2718	0.1204	0.0526



Hot spot position




MEASUREMENT 3

Middle Band SAR (Channel 20175):


Date: 02/19/2021

Frequency (MHz)	1732.500000
Relative permittivity (real part)	53.321249
Relative permittivity (imaginary part)	12.468850
Conductivity (S/m)	1.502592
Variation (%)	0.910000
Crest Factor	1.0
Probe Conversion factor	2.16
E-Field Probe:	SSE2 (SN 41/18 EPG0331)
Area Scan	<u>dx=8mm dy=8mm, h= 5.00 mm</u>
ZoomScan	<u>5x5x7,dx=8mm dy=8mm</u> <u>dz=5mm,Complete/ndx=8mm dy=8mm, h=</u> <u>5.00 mm</u>
Phantom	Validation plane
Device Position	<u>Body back(hotspot 10mm)</u>
Band	<u>LTE band 4(1 RB#49)</u>

SURFACE SAR




VOLUME SAR




Maximum location: X=-21.00, Y=40.00 SAR Peak: 1.00 W/kg


SAR 10g (W/Kg)	0.297565
SAR 1g (W/Kg)	0.566932



Z (mm)	0.00	4.00	9.00	14.00	19.00
SAR (W/Kg)	1.0151	0.5893	0.2786	0.1246	0.0547



Hot spot position




LTE Band 5


MEASUREMENT 1

High Band SAR (Channel 20600):		Date: 02/18/2021
Frequency (MHz)	844.000000	
Relative permittivity (real part)	41.432976	
Relative permittivity (imaginary part)	12.468860	
Conductivity (S/m)	0.862835	
Variation (%)	1.690000	
Crest Factor	1.0	
Probe Conversion factor	1.80	
E-Field Probe:	SSE2 (SN 41/18 EPG0331)	
Area Scan	dx=8mm dy=8mm, h= 5.00 mm	
ZoomScan	5x5x7, dx=8mm dy=8mm dz=5mm, Complete/ndx=8mm dy=8mm, h= 5.00 mm	
Phantom	Left head	
Device Position	Cheek	
Band	LTE band 5(1 RB#24)	

SURFACE SAR



VOLUME SAR




Maximum location: X=-51.00, Y=-37.00 SAR Peak: 0.29 W/kg

SAR 10g (W/Kg)


0.163789

SAR 1g (W/Kg)


0.229156



Z (mm)	0.00	4.00	9.00	14.00	19.00
SAR (W/Kg)	0.2913	0.2393	0.1850	0.1411	0.1058



Hot spot position




MEASUREMENT 2

High Band SAR (Channel 20600):


Date: 02/18/2021

Frequency (MHz)	844.000000
Relative permittivity (real part)	55.260832
Relative permittivity (imaginary part)	12.468860
Conductivity (S/m)	0.934272
Variation (%)	-0.160000
Crest Factor	1.0
Probe Conversion factor	1.86
E-Field Probe:	SSE2 (SN 41/18 EPG0331)
Area Scan	<u>dx=8mm dy=8mm, h= 5.00 mm</u>
ZoomScan	<u>5x5x7,dx=8mm dy=8mm</u> <u>dz=5mm,Complete/ndx=8mm dy=8mm, h=</u> <u>5.00 mm</u>
Phantom	<u>Validation plane</u>
Device Position	<u>Body back(10mm)</u>
Band	<u>LTE band 5(1 RB#49)</u>

SURFACE SAR




VOLUME SAR




Maximum location: X=-2.00, Y=-9.00 SAR Peak: 0.28 W/kg


SAR 10g (W/Kg)	0.157407
SAR 1g (W/Kg)	0.218518



Z (mm)	0.00	4.00	9.00	14.00	19.00
SAR (W/Kg)	0.2817	0.2268	0.1708	0.1268	0.0924



Hot spot position




MEASUREMENT 3

High Band SAR (Channel 20600):


Date: 02/18/2021

Frequency (MHz)	844.000000
Relative permittivity (real part)	55.260832
Relative permittivity (imaginary part)	12.468860
Conductivity (S/m)	0.934272
Variation (%)	-1.190000
Crest Factor	1.0
Probe Conversion factor	1.86
E-Field Probe:	SSE2 (SN 41/18 EPG0331)
Area Scan	<u>dx=8mm dy=8mm, h= 5.00 mm</u>
ZoomScan	<u>5x5x7, dx=8mm dy=8mm</u> <u>dz=5mm, Complete/ndx=8mm dy=8mm, h=</u> <u>5.00 mm</u>
Phantom	Validation plane
Device Position	<u>Body back((hotspot 10mm)</u>
Band	<u>LTE band 5(1 RB#49)</u>

SURFACE SAR



VOLUME SAR




Maximum location: X=-2.00, Y=-7.00 SAR Peak: 0.29 W/kg

SAR 10g (W/Kg)


0.165419

SAR 1g (W/Kg)


0.227376



Z (mm)	0.00	4.00	9.00	14.00	19.00
SAR (W/Kg)	0.2917	0.2356	0.1788	0.1345	0.1000



Hot spot position



LTE Band 7


MEASUREMENT 1

Middle Band SAR (Channel 21100):


Date: 02/23/2021

Frequency (MHz)	2535.000000
Relative permittivity (real part)	38.892754
Relative permittivity (imaginary part)	12.468850
Conductivity (S/m)	1.902731
Variation (%)	-4.570000
Crest Factor	1.0
Probe Conversion factor	2.16
E-Field Probe:	SSE2 (SN 41/18 EPG0331)
Area Scan	<u>dx=8mm dy=8mm, h= 5.00 mm</u>
ZoomScan	<u>5x5x7, dx=8mm dy=8mm</u> <u>dz=5mm, Complete/ndx=8mm dy=8mm, h=</u> <u>5.00 mm</u>
Phantom	<u>Left head</u>
Device Position	<u>Cheek</u>
Band	<u>LTE band 7(1 RB#49)</u>

SURFACE SAR



VOLUME SAR




Maximum location: X=-49.00, Y=-56.00 SAR Peak: 0.41 W/kg

SAR 10g (W/Kg)


0.113664

SAR 1g (W/Kg)


0.232488



Z (mm)	0.00	4.00	9.00	14.00	19.00
SAR (W/Kg)	0.4072	0.2483	0.1284	0.0660	0.0354



Hot spot position




MEASUREMENT 2

Middle Band SAR (Channel 21100):


Date: 02/23/2021

Frequency (MHz)	2535.000000
Relative permittivity (real part)	52.131509
Relative permittivity (imaginary part)	12.468850
Conductivity (S/m)	2.128245
Variation (%)	-3.690000
Crest Factor	1.0
Probe Conversion factor	2.23
E-Field Probe:	SSE2 (SN 41/18 EPG0331)
Area Scan	<u>dx=8mm dy=8mm, h= 5.00 mm</u>
ZoomScan	<u>5x5x7,dx=8mm dy=8mm</u> <u>dz=5mm,Complete/ndx=8mm dy=8mm, h=</u> <u>5.00 mm</u>
Phantom	<u>Validation plane</u>
Device Position	<u>Body back(10mm)</u>
Band	<u>LTE band 7(1 RB#49)</u>

SURFACE SAR




VOLUME SAR




Maximum location: X=5.00, Y=-42.00 SAR Peak: 0.56 W/kg


SAR 10g (W/Kg)	0.144922
SAR 1g (W/Kg)	0.301120



Z (mm)	0.00	4.00	9.00	14.00	19.00
SAR (W/Kg)	0.5568	0.3206	0.1482	0.0630	0.0249



Hot spot position




MEASUREMENT 3

Middle Band SAR (Channel 21100):


Date: 02/23/2021

Frequency (MHz)	2535.000000
Relative permittivity (real part)	52.131509
Relative permittivity (imaginary part)	12.468850
Conductivity (S/m)	2.128245
Variation (%)	-4.810000
Crest Factor	1.0
Probe Conversion factor	2.23
E-Field Probe:	SSE2 (SN 41/18 EPG0331)
Area Scan	dx=8mm dy=8mm, h= 5.00 mm
ZoomScan	5x5x7,dx=8mm dy=8mm dz=5mm,Complete/ndx=8mm dy=8mm, h= 5.00 mm
Phantom	Validation plane
Device Position	Body back(hotspot 10mm)
Band	LTE band 7(1 RB#49)

SURFACE SAR




VOLUME SAR




Maximum location: X=3.00, Y=-43.00 SAR Peak: 0.60 W/kg


SAR 10g (W/Kg)	0.159240
SAR 1g (W/Kg)	0.330210



Z (mm)	0.00	4.00	9.00	14.00	19.00
SAR (W/Kg)	0.6016	0.3528	0.1674	0.0728	0.0287



Hot spot position



LTE Band 26


MEASUREMENT 1

Lower Band SAR (Channel 26765):


Date: 02/18/2021

Frequency (MHz)	821.500000
Relative permittivity (real part)	41.422976
Relative permittivity (imaginary part)	18.468860
Conductivity (S/m)	0.882835
Variation (%)	1.320000
Crest Factor	1.0
Probe Conversion factor	1.80
E-Field Probe:	SSE2 (SN 41/18 EPG0331)
Area Scan	dx=8mm dy=8mm, h= 5.00 mm
ZoomScan	5x5x7, dx=8mm dy=8mm dz=5mm, Complete/ndx=8mm dy=8mm, h= 5.00 mm
Phantom	Left head
Device Position	Cheek
Band	LTE band 26(1 RB#37)

SURFACE SAR



VOLUME SAR




Maximum location: X=-40.00, Y=-41.00 SAR Peak: 0.17 W/kg

SAR 10g (W/Kg)


0.157551

SAR 1g (W/Kg)


0.215212



Z (mm)	0.00	4.00	9.00	14.00	19.00
SAR (W/Kg)	0.2741	0.2262	0.1734	0.1371	0.1037



Hot spot position




MEASUREMENT 2

Lower Band SAR (Channel 26765):


Date: 02/18/2021

Frequency (MHz)	821.500000
Relative permittivity (real part)	55.240832
Relative permittivity (imaginary part)	21.468860
Conductivity (S/m)	0.944272
Variation (%)	1.100000
Crest Factor	1.0
Probe Conversion factor	1.86
E-Field Probe:	SSE2 (SN 41/18 EPG0331)
Area Scan	<u>dx=8mm dy=8mm, h= 5.00 mm</u>
ZoomScan	<u>5x5x7,dx=8mm dy=8mm</u> <u>dz=5mm,Complete/ndx=8mm dy=8mm, h=</u> <u>5.00 mm</u>
Phantom	Validation plane
Device Position	Body back(10mm)
Band	<u>LTE band 26(1 RB#37)</u>

SURFACE SAR




VOLUME SAR




Maximum location: X=2.00, Y=32.00 SAR Peak: 0.52 W/kg


SAR 10g (W/Kg)	0.371244
SAR 1g (W/Kg)	0.501571



Z (mm)	0.00	4.00	9.00	14.00	19.00
SAR (W/Kg)	0.6443	0.5218	0.4011	0.3054	0.2324



Hot spot position




MEASUREMENT 3

Lower Band SAR (Channel 26765):


Date: 02/18/2021

Frequency (MHz)	821.500000
Relative permittivity (real part)	55.260832
Relative permittivity (imaginary part)	21.468860
Conductivity (S/m)	0.944272
Variation (%)	-1.260000
Crest Factor	1.0
Probe Conversion factor	1.86
E-Field Probe:	SSE2 (SN 41/18 EPG0331)
Area Scan	<u>dx=8mm dy=8mm, h= 5.00 mm</u>
ZoomScan	<u>5x5x7,dx=8mm dy=8mm</u> <u>dz=5mm,Complete/ndx=8mm dy=8mm, h=</u> <u>5.00 mm</u>
Phantom	Validation plane
Device Position	<u>Body back(hotspot 10mm)</u>
Band	<u>LTE band 26(1 RB#37)</u>

SURFACE SAR




VOLUME SAR




Maximum location: X=6.00, Y=12.00 SAR Peak: 0.70 W/kg


SAR 10g (W/Kg)	0.411566
SAR 1g (W/Kg)	0.568731



Z (mm)	0.00	4.00	9.00	14.00	19.00
SAR (W/Kg)	0.7311	0.5944	0.4521	0.3422	0.2562



Hot spot position



LTE Band 41


MEASUREMENT 1

Lower Band SAR (Channel 39750):


Date: 02/23/2021

Frequency (MHz)	2506.000000
Relative permittivity (real part)	38.862831
Relative permittivity (imaginary part)	13.546209
Conductivity (S/m)	1.932611
Variation (%)	-0.570000
Crest Factor	1.0
Probe Conversion factor	2.16
E-Field Probe:	SSE2 (SN 41/18 EPG0331)
Area Scan	dx=8mm dy=8mm, h= 5.00 mm
ZoomScan	5x5x7,dx=8mm dy=8mm dz=5mm,Complete/ndx=8mm dy=8mm, h= 5.00 mm
Phantom	Right head
Device Position	Cheek
Band	LTE band 41(1 RB#49)

SURFACE SAR



VOLUME SAR




Maximum location: X=-19.00, Y=-26.00 SAR Peak: 0.41 W/kg

SAR 10g (W/Kg)


0.111552

SAR 1g (W/Kg)


0.233455



Z (mm)	0.00	4.00	9.00	14.00	19.00
SAR (W/Kg)	0.4061	0.2471	0.1272	0.0656	0.0355



Hot spot position




MEASUREMENT 2

Lower Band SAR (Channel 39750):


Date: 02/23/2021

Frequency (MHz)	2593.000000
Relative permittivity (real part)	51.960667
Relative permittivity (imaginary part)	14.938428
Conductivity (S/m)	2.102536
Variation (%)	-3.690000
Crest Factor	1.0
Probe Conversion factor	2.23
E-Field Probe:	SSE2 (SN 41/18 EPG0331)
Area Scan	<u>dx=8mm dy=8mm, h= 5.00 mm</u>
ZoomScan	<u>5x5x7,dx=8mm dy=8mm</u> <u>dz=5mm,Complete/ndx=8mm dy=8mm, h=</u> <u>5.00 mm</u>
Phantom	Validation plane
Device Position	Body back(10mm)
Band	<u>LTE band 41(1 RB#49)</u>

SURFACE SAR




VOLUME SAR




Maximum location: X=5.00, Y=-42.00 SAR Peak: 0.56 W/kg


SAR 10g (W/Kg)	0.144922
SAR 1g (W/Kg)	0.301120



Z (mm)	0.00	4.00	9.00	14.00	19.00
SAR (W/Kg)	0.5568	0.3206	0.1482	0.0630	0.0249



Hot spot position




MEASUREMENT 3

Lower Band SAR (Channel 39750):


Date: 02/23/2021

Frequency (MHz)	2593.000000
Relative permittivity (real part)	51.960667
Relative permittivity (imaginary part)	14.938428
Conductivity (S/m)	2.102536
Variation (%)	-1.810000
Crest Factor	1.0
Probe Conversion factor	2.23
E-Field Probe:	SSE2 (SN 41/18 EPG0331)
Area Scan	<u>dx=8mm dy=8mm, h= 5.00 mm</u>
ZoomScan	<u>5x5x7,dx=8mm dy=8mm</u> <u>dz=5mm,Complete/ndx=8mm dy=8mm, h=</u> <u>5.00 mm</u>
Phantom	Validation plane
Device Position	Body back((hotspot10mm)
Band	<u>LTE band 41(1 RB#49)</u>

SURFACE SAR




VOLUME SAR




Maximum location: X=4.00, Y=-40.00 SAR Peak: 0.60 W/kg


SAR 10g (W/Kg)	0.157130
SAR 1g (W/Kg)	0.331301



Z (mm)	0.00	4.00	9.00	14.00	19.00
SAR (W/Kg)	0.6005	0.3517	0.1663	0.0719	0.0279



Hot spot position



WLAN 2.4


MEASUREMENT 1

Lower Band SAR (Channel 01):


Date: 02/22/2021

Frequency (MHz)	2412.000000
Relative permittivity (real part)	37.852831
Relative permittivity (imaginary part)	13.546209
Conductivity (S/m)	1.812611
Variation (%)	-1.360000
Crest Factor	1.0
Probe Conversion factor	2.31
E-Field Probe:	SSE2 (SN 41/18 EPG0331)
Area Scan	<u>dx=8mm dy=8mm, h= 5.00 mm</u>
ZoomScan	<u>5x5x7,dx=8mm dy=8mm</u> <u>dz=5mm,Complete/ndx=8mm dy=8mm, h=</u> <u>5.00 mm</u>
Phantom	<u>Right head</u>
Device Position	<u>Cheek</u>
Band	<u>IEEE 802.11g ISM</u>

SURFACE SAR




VOLUME SAR




Maximum location: X=-17.00, Y=24.00 SAR Peak: 0.78 W/kg


SAR 10g (W/Kg)	0.080066
SAR 1g (W/Kg)	0.195053



Z (mm)	0.00	4.00	9.00	14.00	19.00
SAR (W/Kg)	0.7682	0.4197	0.1767	0.0654	0.0210



Hot spot position




MEASUREMENT 2

Lower Band SAR (Channel 01):


Date: 02/22/2021

Frequency (MHz)	2412.000000
Relative permittivity (real part)	54.630667
Relative permittivity (imaginary part)	14.318428
Conductivity (S/m)	1.982536
Variation (%)	4.010000
Crest Factor	1.0
Probe Conversion factor	2.37
E-Field Probe:	SSE2 (SN 41/18 EPG0331)
Area Scan	<u>dx=8mm dy=8mm, h= 5.00 mm</u>
ZoomScan	<u>5x5x7,dx=8mm dy=8mm</u> <u>dz=5mm,Complete/ndx=8mm dy=8mm, h=</u> <u>5.00 mm</u>
Phantom	Validation plane
Device Position	Body back(10mm)
Band	IEEE 802.11g ISM

SURFACE SAR




VOLUME SAR




Maximum location: X=-15.00, Y=58.00 SAR Peak: 0.34 W/kg


SAR 10g (W/Kg)	0.077530
SAR 1g (W/Kg)	0.173292



Z (mm)	0.00	4.00	9.00	14.00	19.00
SAR (W/Kg)	0.3372	0.1876	0.0816	0.0317	0.0109



Hot spot position




MEASUREMENT 3

Lower Band SAR (Channel 01):


Date: 02/22/2021

Frequency (MHz)	2412.000000
Relative permittivity (real part)	54.630667
Relative permittivity (imaginary part)	14.318428
Conductivity (S/m)	1.982536
Variation (%)	-4.110000
Crest Factor	1.0
Probe Conversion factor	2.37
E-Field Probe:	SSE2 (SN 41/18 EPG0331)
Area Scan	<u>dx=8mm dy=8mm, h= 5.00 mm</u>
ZoomScan	<u>5x5x7,dx=8mm dy=8mm</u> <u>dz=5mm,Complete/ndx=8mm dy=8mm, h=</u> <u>5.00 mm</u>
Phantom	Validation plane
Device Position	Body back(10mm)
Band	<u>IEEE 802.11g ISM(hotspot)</u>

SURFACE SAR




VOLUME SAR




Maximum location: X=-15.00, Y=58.00 SAR Peak: 0.37 W/kg


SAR 10g (W/Kg)	0.087182
SAR 1g (W/Kg)	0.193788



Z (mm)	0.00	4.00	9.00	14.00	19.00
SAR (W/Kg)	0.3732	0.2107	0.0935	0.0368	0.0124



Hot spot position



WLAN 5.2


MEASUREMENT 1

SAR (Channel 36):


Date: 02/23/2021

Frequency (MHz)	5180.000000
Relative permittivity (real part)	50.110667
Relative permittivity (imaginary part)	21.378187
Conductivity (S/m)	5.408883
Variation (%)	-0.470000
Crest Factor	1.0
Probe Conversion factor	2.01
E-Field Probe:	SSE2 (SN 41/18 EPG0331)
Area Scan	<u>dx=8mm dy=8mm, h= 5.00 mm</u>
ZoomScan	<u>5x5x7,dx=8mm dy=8mm</u> <u>dz=5mm,Complete/ndx=8mm dy=8mm, h=</u> <u>5.00 mm</u>
Phantom	<u>Right head</u>
Device Position	<u>Cheek</u>
Band	<u>IEEE 802.11nHT20 ISM</u>

SURFACE SAR




VOLUME SAR




Maximum location: X=0.00, Y=24.00

SAR Peak: 0.40 W/kg

SAR 10g (W/Kg)	0.097184
SAR 1g (W/Kg)	0.210966



Z (mm)	0.00	4.00	9.00	14.00	19.00
SAR (W/Kg)	0.3970	0.2264	0.1062	0.0500	0.0263



Hot spot position




MEASUREMENT 2

Band SAR (Channel 36):


Date: 02/23/2021

Frequency (MHz)	5180.000000
Relative permittivity (real part)	50.110667
Relative permittivity (imaginary part)	21.378187
Conductivity (S/m)	5.408883
Variation (%)	1.010000
Crest Factor	1.0
Probe Conversion factor	2.08
E-Field Probe:	SSE2 (SN 41/18 EPG0331)
Area Scan	<u>dx=8mm dy=8mm, h= 5.00 mm</u>
ZoomScan	<u>5x5x7,dx=8mm dy=8mm</u> <u>dz=5mm,Complete/ndx=8mm dy=8mm, h=</u> <u>5.00 mm</u>
Phantom	Validation plane
Device Position	Body back(10mm)
Band	<u>IEEE 802.11nHT20 ISM</u>

SURFACE SAR




VOLUME SAR




Maximum location: X=-15.00, Y=58.00 SAR Peak: 0.34 W/kg


SAR 10g (W/Kg)	0.077530
SAR 1g (W/Kg)	0.253292



Z (mm)	0.00	4.00	9.00	14.00	19.00
SAR (W/Kg)	0.3372	0.1876	0.0816	0.0317	0.0109



Hot spot position




MEASUREMENT 3

SAR (Channel 36):


Date: 02/23/2021

Frequency (MHz)	5180.000000
Relative permittivity (real part)	50.110667
Relative permittivity (imaginary part)	21.378187
Conductivity (S/m)	5.408883
Variation (%)	-2.110000
Crest Factor	1.0
Probe Conversion factor	2.08
E-Field Probe:	SSE2 (SN 41/18 EPG0331)
Area Scan	<u>dx=8mm dy=8mm, h= 5.00 mm</u>
ZoomScan	<u>5x5x7,dx=8mm dy=8mm</u> <u>dz=5mm,Complete/ndx=8mm dy=8mm, h=</u> <u>5.00 mm</u>
Phantom	Validation plane
Device Position	Body back(10mm)
Band	<u>IEEE 802.11nHT20 ISM(hotspot)</u>

SURFACE SAR




VOLUME SAR




Maximum location: X=-15.00, Y=58.00 SAR Peak: 0.37 W/kg


SAR 10g (W/Kg)	0.087182
SAR 1g (W/Kg)	0.263788



Z (mm)	0.00	4.00	9.00	14.00	19.00
SAR (W/Kg)	0.3732	0.2107	0.0935	0.0368	0.0124



Hot spot position



WLAN 5.8


MEASUREMENT 1

SAR (Channel 149):


Date: 02/23/2021

Frequency (MHz)	5745.000000
Relative permittivity (real part)	47.393887
Relative permittivity (imaginary part)	14.935214
Conductivity (S/m)	6.274821
Variation (%)	0.240000
Crest Factor	1.0
Probe Conversion factor	2.06
E-Field Probe:	SSE2 (SN 41/18 EPG0331)
Area Scan	<u>dx=8mm dy=8mm, h= 5.00 mm</u>
ZoomScan	<u>5x5x7,dx=8mm dy=8mm</u> <u>dz=5mm,Complete/ndx=8mm dy=8mm, h=</u> <u>5.00 mm</u>
Phantom	<u>Right head</u>
Device Position	<u>Cheek</u>
Band	<u>IEEE 802.11acHT20 ISM</u>

SURFACE SAR




VOLUME SAR




Maximum location: X=-24.00, Y=29.00 SAR Peak: 0.53 W/kg


SAR 10g (W/Kg)	0.126159
SAR 1g (W/Kg)	0.271291



Z (mm)	0.00	4.00	9.00	14.00	19.00
SAR (W/Kg)	0.5019	0.2761	0.1209	0.0512	0.0235



Hot spot position



MEASUREMENT 2


SAR (Channel 149):
02/23/2021

Date:


Frequency (MHz)	5745.000000
Relative permittivity (real part)	47.393887
Relative permittivity (imaginary part)	14.935214
Conductivity (S/m)	6.274821
Variation (%)	-0.920000
Crest Factor	1.0
Probe Conversion factor	2.13
E-Field Probe:	SSE2 (SN 41/18 EPG0331)
Area Scan	<u>dx=8mm dy=8mm, h= 5.00 mm</u>
ZoomScan	<u>5x5x7,dx=8mm dy=8mm</u> <u>dz=5mm,Complete/ndx=8mm dy=8mm, h=</u> <u>5.00 mm</u>

Phantom	Validation plane
Device Position	Body back(10mm)
Band	<u>IEEE 802.11acHT20 ISM</u>

SURFACE SAR




VOLUME SAR




Maximum location: X=24.00, Y=30.00 SAR Peak: 0.35 W/kg

SAR 10g (W/Kg)	0.085389
SAR 1g (W/Kg)	0.192866



Z (mm)	0.00	4.00	9.00	14.00	19.00
SAR (W/Kg)	0.3510	0.2063	0.1009	0.0488	0.0251



Hot spot position

