FCC Radio Test Report

FCC ID: 2AM8GCHAMELEON8

Original Grant

Report No.	:	TB-FCC164421
Applicant	:	Guangzhou Lie Dun Electronics Technology CO.,Ltd
Equipment Under Test (EUT)		
EUT Name	:	RUGGEDIZED TABLET
Model No.	:	8-DUAL
Series Model No.	:	8-MICRO, 8-SINGLE, 8-SINGLE+, 8-SLAP
Brand Name	:	CHAMELEON
Receipt Date	:	2019-02-27
Test Date	:	2019-03-04 to 2019-06-25
Issue Date	:	2019-06-25
Standards	:	FCC Part 15, Subpart C 15.247
Test Method	:	ANSI C63.10: 2013
Conclusions	:	**PASS**

In the configuration tested, the EUT complied with the standards specified above,
The EUT technically complies with the FCC and IC requirements

Test/Witness Engineer	:	Jason Xu
Test/Witness Engineer	:	Ivan Su
Approved& Authorized	:	Ray Lai

This report details the results of the testing carried out on one sample. The results contained in this test report do not relate to other samples of the same product. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in the report.

1A/F., Bldg.6, Yusheng Industrial Zone, The National Road No.107 Xixiang Section 467, Xixiang, Bao'an, Shenzhen, China
Tel: +86 75526509301 Fax: +86 75526509195

Contents

CONTENTS 2
1. GENERAL INFORMATION ABOUT EUT 5
1.1 Client Information 5
1.2 General Description of EUT (Equipment Under Test) 5
1.3 Block Diagram Showing the Configuration of System Tested 7
1.4 Description of Support Units 7
1.5 Description of Test Mode 8
1.6 Description of Test Software Setting 9
1.7 Measurement Uncertainty 9
1.8 Test Facility 10
2. TEST SUMMARY 11
3. TEST EQUIPMENT 12
4. CONDUCTED EMISSION TEST 13
4.1 Test Standard and Limit 13
4.2 Test Setup 13
4.3 Test Procedure 13
4.4 EUT Operating Mode 14
4.5 Test Data 14
5. RADIATED EMISSION TEST 15
5.1 Test Standard and Limit 15
5.2 Test Setup 16
5.3 Test Procedure 17
5.4 EUT Operating Condition 18
5.5 Test Data 18
6. RESTRICTED BANDS REQUIREMENT 19
6.1 Test Standard and Limit 19
6.2 Test Setup 19
6.3 Test Procedure 19
6.4 EUT Operating Condition 20
6.5 Test Data 20
7. BANDWIDTH TEST 21
7.1 Test Standard and Limit 21
7.2 Test Setup 21
7.3 Test Procedure 21
7.4 EUT Operating Condition 21
7.5 Test Data 21
8. PEAK OUTPUT POWER TEST 22
8.1 Test Standard and Limit 22

8.2 Test Setup 22
8.3 Test Procedure 22
8.4 EUT Operating Condition 22
8.5 Test Data 22
9. POWER SPECTRAL DENSITY TEST 23
9.1 Test Standard and Limit 23
9.2 Test Setup 23
9.3 Test Procedure 23
9.4 EUT Operating Condition 23
9.5 Test Data 23
10. ANTENNA REQUIREMENT 24
10.1 Standard Requirement 24
10.2 Antenna Connected Construction 24
ATTACHMENT A-- CONDUCTED EMISSION TEST DATA 25
ATTACHMENT C-- RESTRICTED BANDS REQUIREMENT AND BAND-EDGE TEST DATA 53
ATTACHMENT D-- BANDWIDTH TEST DATA 77
ATTACHMENT E-- PEAK OUTPUT POWER TEST DATA 93
ATTACHMENT F-- POWER SPECTRAL DENSITY TEST DATA 97

Revision History

Report No.	Version	Description	Issued Date
TB-FCC164421	Rev.01	Initial issue of report	2019-06-25

1. General Information about EUT

1.1 Client Information

Applicant	:	Guangzhou Lie Dun Electronics Technology CO.,Ltd
Address	:	No.4 plant of No.43 South International Trade Avenue, Hualong Town, Panyu District, Guangzhou, Guangdong, China
Manufacturer	:	Guangzhou Lie Dun Electronics Technology CO.,Ltd
Address	:	No.4 plant of No.43 South International Trade Avenue, Hualong Town, Panyu District, Guangzhou, Guangdong, China

1.2 General Description of EUT (Equipment Under Test)

EUT Name	:	RUGGEDIZED TABLET	
Models No.	:	8-DUAL, 8-MICRO, 8-SINGLE, 8-SINGLE+, 8-SLAP	
Model Different	:	All these models are identical in the same PCB, layout and electrical circuit, the only difference is model name for commercial.	
Product Description	:	Operation Frequency:	802.11b/g/n(HT20): 2412MHz~2462MHz 802.11n(HT40): 2422MHz~2452MHz
		Number of Channel:	802.11b/g/n(HT20):11 channels **see note(3)** 802.11n(HT40): 7 channels **see note(3)**
		RF Output Power:	802.11b: 8.18 dBm 802.11g: 7.96 dBm 802.11n (HT20): 7.43 dBm 802.11n (HT40): 7.42 dBm
		Antenna Gain:	2 dBi FPC Antenna
		Modulation Type:	802.11b: DSSS(CCK, DQPSK, DBPSK) 802.11g/n:OFDM(BPSK,QPSK,16QAM,64QAM)
		Bit Rate of Transmitter:	802.11b:11/5.5/2/1 Mbps 802.11g:54/48/36/24/18/12/9/6 Mbps 802.11n:up to 150Mbps
Power Rating	:	Adapter(B036-125): Input: AC 100-240V, 50/60Hz, 1.2A max Output: DC 12V, 3A DC 7.6V by 7600mAh rechargeable Li-ion battery.	
Software Version	:	Windows Pro	
Hardware Version	:	V12	
Connecting I/O Port(S)	:	Please refer to the User's Manual	

Note:

(1) This Test Report is FCC Part 15.247 for 802.11b/g/n, the test procedure follows the FCC KDB 558074 D01 v05r02 and KDB 662911 D01 Multiple Transmitter Output v02r01.

(2) For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.

(3) Channel List:

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
01	**2412**	05	2432	09	2452
02	2417	**06**	**2437**	10	2457
03	2422	07	2442	**11**	**2462**
04	2427	08	2447		
Note: CH 01~CH 11 for 802.11b/g/n(HT20)					

(4) Antenna information

Mode	TX Antenna (s)	Remark
802.11b	1	The worst case is Main ANT. TX
802.11g	1	The worst case is Main ANT. 1 TX
802.11n(HT20)	2	Main ANT.+AUX ANT.
802.11n(HT40)	2	Main ANT.+AUX ANT.

Antenna	Brand	Model Name	Type	Antenna Gain(dBi)
Main ANT.	N/A	N/A	FPC	2
Main ANT.	N/A	N/A	FPC	2
Note:For MIMO mode: Directional gain=Gain(Ant1)+Gain(Ant1)=5.01 dBi in 2.4G 802.11 n(HT20/HT40) has MIMO mode.				

1.3 Block Diagram Showing the Configuration of System Tested



1.4 Description of Support Units

The EUT has been tested as an independent unit.

1.5 Description of Test Mode

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned follow was evaluated respectively.

For Conducted Test	
Final Test Mode	**Description**
Mode 1	Charging with TX B Mode

For Radiated Test	
Final Test Mode	**Description**
Mode 2	TX Mode B Mode Channel 01/06/11
Mode 3	TX Mode G Mode Channel 01/06/11
Mode 4	TX Mode N(HT20) Mode Channel 01/06/11
Mode 5	TX Mode N(HT40) Mode Channel 03/06/09

Note:

(1) For all test, we have verified the construction and function in typical operation. And all the test modes were carried out with the EUT in transmitting operation in maximum power with all kinds of data rate.

According to ANSI C63.10 standards, the measurements are performed at the highest, Middle, lowest available channels, and the worst case data rate as follows:

802.11b Mode: CCK (1 Mbps)
802.11g Mode: OFDM (6 Mbps)
802.11n (HT20) Mode: MCS 0 (6.5 Mbps)
802.11n (HT40) Mode: MCS 0 (30 Mbps)

(2) During the testing procedure, the continuously transmitting with the maximum power mode was programmed by the customer.

(3) The EUT is considered a portable unit; in normal use it was positioned on X-plane. The worst case was found positioned on X-plane. Therefore only the test data of this X-plane was used for radiated emission measurement test.

1.6 Description of Test Software Setting

During testing channel & Power controlling software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product power parameters of WLAN.

	Test Software:DRTU			
	Test Mode: Continuously transmitting			
Mode	**Data Rate**	**Channel**	**Parameters**	
			ANT 1	**ANT 2**
802.11b	CCK/ 1Mbps	01	DEF	DEF
	CCK/ 1Mbps	06	DEF	DEF
	CCK/ 1Mbps	11	DEF	DEF
802.11g	OFDM/ 6Mbps	01	DEF	DEF
	OFDM/ 6Mbps	06	DEF	DEF
	OFDM/ 6Mbps	11	DEF	DEF
802.11n(20)	MCS 0	01	DEF	DEF
	MCS 0	06	DEF	DEF
	MCS 0	11	DEF	DEF
802.11n(40)	MCS 0	03	DEF	DEF
	MCS 0	06	DEF	DEF
	MCS 0	09	DEF	DEF
Note: TX signal at 802.11b/g mode only could transmit at Ant.1 or Ant. 2. All the test mode have pretest with two Antenna, but the worst case is ANT 1.The report only show the worst case.				

1.7 Measurement Uncertainty

The reported uncertainty of measurement y ± U，where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of k=2，providing a level of confidence of approximately 95 %.

Test Item	**Parameters**	**Expanded Uncertainty (U_{Lab})**
Conducted Emission	Level Accuracy: 9kHz~150kHz 150kHz to 30MHz	 ±3.42 dB ±3.42 dB
Radiated Emission	Level Accuracy: 9kHz to 30 MHz	±4.60 dB
Radiated Emission	Level Accuracy: 30MHz to 1000 MHz	±4.40 dB
Radiated Emission	Level Accuracy: Above 1000MHz	±4.20 dB

1.8 Test Facility

The testing was performed by the Shenzhen Toby Technology Co., Ltd., in their facilities located at:1A/F., Bldg.6, Yusheng Industrial Zone, The National Road No.107 Xixiang Section 467, Xixiang, Bao'an, Shenzhen, Guangdong, China.
At the time of testing, the following bodies accredited the Laboratory:

CNAS (L5813)

The Laboratory has been accredited by CNAS to ISO/IEC 17025: 2005 General Requirements for the Competence of Testing and Calibration Laboratories for the competence in the field of testing. And the Registration No.: CNAS L5813.

A2LA Certificate No.: 4750.01

The laboratory has been accredited by American Association for Laboratory Accreditation(A2LA) to ISO/IEC 17025：2005 General Requirements for the Competence of Testing and Calibration Laboratories for the technical competence in the field of Electrical Testing. And the A2LA Certificate No.: 4750.01.FCC Accredited Test Site Number: 854351.

IC Registration No.: (11950A-1)

The Laboratory has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing. The site registration: Site# 11950A-1.

2. Test Summary

FCC Part 15 Subpart C(15.247)/ RSS 247 Issue 2				
Standard Section		Test Item	Judgment	Remark
FCC	IC			
15.203	/	Antenna Requirement	PASS	N/A
15.207	RSS-GEN 7.2.4	Conducted Emission	PASS	N/A
15.205	RSS-GEN 7.2.2	Restricted Bands	PASS	N/A
15.247(a)(2)	RSS 247 5.2 (1)	6dB Bandwidth	PASS	N/A
15.247(b)	RSS 247 5.4 (4)	Peak Output Power	PASS	N/A
15.247(e)	RSS 247 5.2 (2)	Power Spectral Density	PASS	N/A
15.247(d)	RSS 247 5.5	Band Edge	PASS	N/A
15.247(d)& 15.209	RSS 247 5.5	Transmitter Radiated Spurious Emission	PASS	N/A
Note: "/" for no requirement for this test item. N/A is an abbreviation for Not Applicable.				

3. Test Equipment

Conducted Emission Test					
Equipment	**Manufacturer**	**Model No.**	**Serial No.**	**Last Cal.**	**Cal. Due Date**
EMI Test Receiver	Rohde & Schwarz	ESCI	100321	Jul.18, 2018	Jul. 17, 2019
RF Switching Unit	Compliance Direction Systems Inc	RSU-A4	34403	Jul.18, 2018	Jul. 17, 2019
AMN	SCHWARZBECK	NNBL 8226-2	8226-2/164	Jul.18, 2018	Jul. 17, 2019
LISN	Rohde & Schwarz	ENV216	101131	Jul.18, 2018	Jul. 17, 2019
Radiation Emission Test					
Equipment	**Manufacturer**	**Model No.**	**Serial No.**	**Last Cal.**	**Cal. Due Date**
Spectrum Analyzer	Agilent	E4407B	MY45106456	Jul.18, 2018	Jul. 17, 2019
EMI Test Receiver	Rohde & Schwarz	ESPI	100010/007	Jul.18, 2018	Jul. 17, 2019
Bilog Antenna	ETS-LINDGREN	3142E	00117537	Jan. 27, 2019	Jan. 26, 2020
Bilog Antenna	ETS-LINDGREN	3142E	00117542	Jan. 27, 2019	Jan. 26, 2020
Horn Antenna	ETS-LINDGREN	3117	00143207	Mar.03, 2019	Mar. 02, 2020
Horn Antenna	ETS-LINDGREN	3117	00143209	Mar.03, 2019	Mar. 02, 2020
Loop Antenna	SCHWARZBECK	FMZB 1519 B	1519B-059	Jul. 14, 2018	Jul.13, 2019
Pre-amplifier	Sonoma	310N	185903	Mar.04, 2019	Mar. 03, 2020
Pre-amplifier	HP	8449B	3008A00849	Mar.03, 2019	Mar. 02, 2020
Cable	HUBER+SUHNER	100	SUCOFLEX	Mar.03, 2019	Mar. 02, 2020
Positioning Controller	ETS-LINDGREN	2090	N/A	N/A	N/A
Antenna Conducted Emission					
Equipment	**Manufacturer**	**Model No.**	**Serial No.**	**Last Cal.**	**Cal. Due Date**
Spectrum Analyzer	Agilent	E4407B	MY45106456	Jul.18, 2018	Jul. 17, 2019
Spectrum Analyzer	Rohde & Schwarz	ESCI	100010/007	Jul.18, 2018	Jul. 17, 2019
MXA Signal Analyzer	Agilent	N9020A	MY49100060	Sep. 15, 2018	Sep. 14, 2019
Vector Signal Generator	Agilent	N5182A	MY50141294	Sep. 15, 2018	Sep. 14, 2019
Analog Signal Generator	Agilent	N5181A	MY50141953	Sep. 15, 2018	Sep. 14, 2019
RF Power Sensor	DARE!! Instruments	RadiPowerRPR3006W	17I00015SNO26	Sep. 15, 2018	Sep. 14, 2019
	DARE!! Instruments	RadiPowerRPR3006W	17I00015SNO29	Sep. 15, 2018	Sep. 14, 2019
	DARE!! Instruments	RadiPowerRPR3006W	17I00015SNO31	Sep. 15, 2018	Sep. 14, 2019
	DARE!! Instruments	RadiPowerRPR3006W	17I00015SNO33	Sep. 15, 2018	Sep. 14, 2019

4. Conducted Emission Test

4.1 Test Standard and Limit

4.1.1Test Standard

FCC Part 15.207

4.1.2 Test Limit

Conducted Emission Test Limit

Frequency	Maximum RF Line Voltage (dBμV)	
	Quasi-peak Level	Average Level
150kHz~500kHz	66 ~ 56 *	56 ~ 46 *
500kHz~5MHz	56	46
5MHz~30MHz	60	50

Notes:

(1) *Decreasing linearly with logarithm of the frequency.

(2) The lower limit shall apply at the transition frequencies.

(3) The limit decrease in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

4.2 Test Setup



4.3 Test Procedure

The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.

Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.

I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.

LISN at least 80 cm from nearest part of EUT chassis.

The bandwidth of EMI test receiver is set at 9kHz, and the test frequency band is from 0.15MHz to 30MHz.

4.4 EUT Operating Mode

Please refer to the description of test mode.

4.5 Test Data

Please refer to the Attachment A.

5. Radiated Emission Test

5.1 Test Standard and Limit

5.1.1 Test Standard

FCC Part 15.209

5.1.2 Test Limit

Radiated Emission Limits (9 kHz~1000 MHz)

Frequency (MHz	Field Strength (microvolt/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

Radiated Emission Limit (Above 1000MHz)

Frequency (MHz)	Distance of 3m (dBuV/m)	
	Peak	Average
Above 1000	74	54

Note:

(1) The tighter limit applies at the band edges.

(2) Emission Level(dBuV/m)=20log Emission Level(uV/m)

5.2 Test Setup



Below 30MHz Test Setup



Below 1000MHz Test Setup



Above 1GHz Test Setup

5.3 Test Procedure

(1) Measurements at frequency above 1GHz. The EUT was placed on a rotating 1.5m high above the ground. RF absorbers covered the ground plane with a minimum area of 3.0m by 3.0m between the EUT and measurement receiver antenna. The RF absorber shall not exceed 30cm in high above the conducting floor. The table was rotated 360 degrees to determine the position of the highest radiation.

(2) Measurements at frequency Below 1GHz. The EUT was placed on a rotating 0.8m high above the ground. RF absorbers covered the ground plane with a minimum area of 3.0m by 3.0m between the EUT and measurement receiver antenna. The RF absorber shall not exceed 30cm in high above the conducting floor. The table was rotated 360 degrees to determine the position of the highest radiation.

(3) The Test antenna shall vary between 1m and 4m, Both Horizontal and Vertical antenna are set to make measurement.

(4) The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.

(5) If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit Bellow 1 GHz, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed. But the Peak Value and average value both need to comply with applicable limit above 1 GHz.

(6) Testing frequency range below 1GHz the measuring instrument use VBW=120 kHz with Quasi-peak detection.

(7) Testing frequency range above 1GHz the measuring instrument use RBW=1 MHz and VBW=3 MHz with Peak Detector for Peak Values, and use RBW=1 MHz and VBW=10 Hz with Peak Detector for Average Values.

(8) For the actual test configuration, please see the test setup photo.

5.4 EUT Operating Condition

The Equipment Under Test was set to Continual Transmitting in maximum power.

5.5 Test Data

Remark: During testing above 1GHz the measuring instrument use RBW=1 MHz and VBW=3 MHz with Peak Detector for Peak Values, and use RBW=1 MHz and VBW=10 Hz with Peak Detector for Average Values.

Please refer to the Attachment B.

6. Restricted Bands Requirement

6.1 Test Standard and Limit

6.1.1 Test Standard

FCC Part 15.247(d)
FCC Part 15.209
FCC Part 15.205

6.1.2 Test Limit

Restricted Frequency Band (MHz)	Distance of 3m (dBuV/m)	
	Peak	Average
2310 ~2390	74	54
2483.5 ~2500	74	54

6.2 Test Setup



6.3 Test Procedure

(1) The measuring distance of 3m shall be used for measurements at frequency Below 1GHz and above 1 GHz. The EUT was placed on a rotating 0.8m high above ground, the table was rotated 360 degrees to determine the position of the highest radiation.

(2) Measurements at frequency above 1GHz. The EUT was placed on a rotating 1.5m high above the ground. RF absorbers covered the ground plane with a minimum area of 3.0m by 3.0m between the EUT and measurement receiver antenna. The RF absorber shall not exceed 30cm in high above the conducting floor. The table was rotated 360 degrees to determine the position of the highest radiation.

(3) The Test antenna shall vary between 1m and 4m, Both Horizontal and Vertical antenna are set to make measurement.
(4) The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
(5) If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit Bellow 1 GHz, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed. But the Peak Value and average value both need to comply with applicable limit above 1 GHz.
(6) Testing frequency range below 1GHz the measuring instrument use VBW=120 kHz with Quasi-peak detection.
(7) Testing frequency range above 1GHz the measuring instrument use RBW=1 MHz and VBW=3 MHz with Peak Detector for Peak Values, and use RBW=1 MHz and VBW=10 Hz with Peak Detector for Average Values.
(8) For the actual test configuration, please see the test setup photo.

6.4 EUT Operating Condition

The Equipment Under Test was set to Continual Transmitting in maximum power.

6.5 Test Data

Please refer to the Attachment C.

7. Bandwidth Test

7.1 Test Standard and Limit

7.1.1 Test Standard

FCC Part 15.247 (a)(2)

7.1.2 Test Limit

FCC Part 15 Subpart C(15.247)		
Test Item	**Limit**	**Frequency Range(MHz)**
Bandwidth	>=500 KHz (6dB bandwidth)	2400~2483.5

7.2 Test Setup



7.3 Test Procedure

(1) The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.

(2) The bandwidth is measured at an amplitude level reduced 6dB from the reference level. The reference level is the level of the highest amplitude signal observed from the transmitter at the fundamental frequency. Once the reference level is established, the equipment is conditioned with typical modulating signal to produce the worst –case (i.e the widest) bandwidth.

(3)Measure the channel separation the spectrum analyzer was set to Resolution Bandwidth:100 kHz, and Video Bandwidth:300 kHz, Detector: Peak, Sweep Time set auto.

7.4 EUT Operating Condition

The EUT was set to continuously transmitting in each mode and low, Digital photo framesdle and high channel for the test.

7.5 Test Data

Please refer to the Attachment D.

8. Peak Output Power Test

8.1 Test Standard and Limit

8.1.1 Test Standard

FCC Part 15.247 (b)

8.1.2 Test Limit

FCC Part 15 Subpart C(15.247)		
Test Item	**Limit**	**Frequency Range(MHz)**
Peak Output Power	1 Watt or 30 dBm	2400~2483.5

8.2 Test Setup



8.3 Test Procedure

The measurement is according to section 9.1.2 of KDB 558074 D01 v05r02.
The EUT was connected to RF power meter via a broadband power sensor as show the block above. The power sensor video bandwidth is greater than or equal to the DTS bandwidth of the equipment.

8.4 EUT Operating Condition

The EUT was set to continuously transmitting in the max power during the test.

8.5 Test Data

Please refer to the Attachment E.

9. Power Spectral Density Test

9.1 Test Standard and Limit

9.1.1 Test Standard

FCC Part 15.247 (e)

9.1.2 Test Limit

FCC Part 15 Subpart C(15.247)		
Test Item	**Limit**	**Frequency Range(MHz)**
Power Spectral Density	8dBm(in any 3 kHz)	2400~2483.5

9.2 Test Setup



9.3 Test Procedure

The EUT was directly connected to the Spectrum Analyzer and antenna output port as show in the block diagram above. The measurement according to section 10.2 of KDB 558074 D01 D01 v05r02.

(1) The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.
(2) Set analyser center frequency to DTS channel center frequency.
(3) Set the span to 1.5 times the DTS bandwidth.
(4) Set the RBW to: 3 kHz
(5) Set the VBW to: 10 kHz
(6) Detector: peak
(7) Sweep time: auto
(8) Allow trace to fully stabilize. Then use the peak marker function to determine the maximum amplitude level.

9.4 EUT Operating Condition

The EUT was set to continuously transmitting in each mode and low, Digital photo framesdle and high channel for the test.

9.5 Test Data

Please refer to the Attachment F.

10. Antenna Requirement

10.1 Standard Requirement

10.1.1 Standard

FCC Part 15.203

10.1.2 Requirement

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

10.2 Antenna Connected Construction

The gains of the antenna used for transmitting is 2 dBi, and the antenna de-signed with permanent attachment and no consideration of replacement. Please see the EUT photo for details.

Result

The EUT antenna is a FPC Antenna. It complies with the standard requirement.

Antenna Type
☐Permanent attached antenna
☒Unique connector antenna
☐Professional installation antenna

Attachment A-- Conducted Emission Test Data

Remark: All channels have been tested and Shows only the worst channels.

Temperature:	25 ℃	**Relative Humidity:**	55%
Test Voltage:	AC 120V/60Hz		
Terminal:	Line		
Test Mode:	Mode 1		
Remark:	Only worse case is reported		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector
1	*	0.1660	38.27	9.58	47.85	65.15	-17.30	QP
2		0.1660	17.84	9.58	27.42	55.15	-27.73	AVG
3		0.2380	29.53	9.58	39.11	62.16	-23.05	QP
4		0.2380	17.26	9.58	26.84	52.16	-25.32	AVG
5		0.6180	28.94	9.61	38.55	56.00	-17.45	QP
6		0.6180	15.67	9.61	25.28	46.00	-20.72	AVG
7		0.6940	27.30	9.61	36.91	56.00	-19.09	QP
8		0.6940	11.15	9.61	20.76	46.00	-25.24	AVG
9		4.3020	22.40	9.70	32.10	56.00	-23.90	QP
10		4.3020	13.33	9.70	23.03	46.00	-22.97	AVG
11		21.1820	18.49	10.56	29.05	60.00	-30.95	QP
12		21.1820	12.89	10.56	23.45	50.00	-26.55	AVG

Emission Level= Read Level+ Correct Factor

Temperature:	25 ℃	**Relative Humidity:**	55%
Test Voltage:	AC 120V/60Hz		
Terminal:	Neutral		
Test Mode:	Mode 1		
Remark:	Only worse case is reported		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector
1		0.1660	36.83	9.58	46.41	65.15	-18.74	QP
2		0.1660	16.21	9.58	25.79	55.15	-29.36	AVG
3		0.2380	29.70	9.58	39.28	62.16	-22.88	QP
4		0.2380	18.77	9.58	28.35	52.16	-23.81	AVG
5		0.3060	27.07	9.59	36.66	60.08	-23.42	QP
6		0.3060	13.17	9.59	22.76	50.08	-27.32	AVG
7		0.4460	26.48	9.60	36.08	56.95	-20.87	QP
8		0.4460	12.87	9.60	22.47	46.95	-24.48	AVG
9	*	0.7780	29.40	9.61	39.01	56.00	-16.99	QP
10		0.7780	14.57	9.61	24.18	46.00	-21.82	AVG
11		28.5020	25.69	10.78	36.47	60.00	-23.53	QP
12		28.5020	20.24	10.78	31.02	50.00	-18.98	AVG

Emission Level= Read Level+ Correct Factor

Attachment B-- Radiated Emission Test Data

9KHz~30MHz

From 9KHz to 30MHz: Conclusion: PASS

Note: The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

30MHz~1GHz

Temperature:	25 ℃	**Relative Humidity:**	55%
Test Voltage:	AC 120V/60HZ		
Ant. Pol.	Horizontal		
Test Mode:	TX B Mode 2412MHz		
Remark:	Only worse case is reported.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1	*	31.7313	17.59	17.49	35.08	40.00	-4.92	peak
2	!	237.4756	26.24	13.83	40.07	46.00	-5.93	peak
3		263.8190	24.95	14.80	39.75	46.00	-6.25	peak
4		506.4791	17.58	21.22	38.80	46.00	-7.20	peak
5		554.8251	16.08	22.59	38.67	46.00	-7.33	peak
6		845.0878	14.16	25.45	39.61	46.00	-6.39	peak

*:Maximum data x:Over limit !:over margin

Emission Level= Read Level+ Correct Factor

Temperature:	25 ℃	**Relative Humidity:**	55%
Test Voltage:	AC 120V/60HZ		
Ant. Pol.	Vertical		
Test Mode:	TX B Mode 2412MHz		
Remark:	Only worse case is reported.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1	*	30.4237	17.71	18.48	36.19	40.00	-3.81	peak
2		49.0144	20.78	8.88	29.66	40.00	-10.34	peak
3		61.3462	23.80	7.54	31.34	40.00	-8.66	peak
4		85.8983	19.02	9.56	28.58	40.00	-11.42	peak
5		136.4598	20.56	9.28	29.84	43.50	-13.66	peak
6		263.8190	23.03	14.80	37.83	46.00	-8.17	peak

*:Maximum data x:Over limit !:over margin

Emission Level= Read Level+ Correct Factor

Above 1GHz

Temperature:	25 ℃	**Relative Humidity:**	55%
Test Voltage:	AC 120V/60 Hz		
Ant. Pol.	Horizontal		
Test Mode:	TX B Mode 2412MHz Main ANT.		
Remark:	No report for the emission which more than 10 dB below the prescribed limit. Only show the worse case Main ANT.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		4823.904	43.15	8.19	51.34	74.00	-22.66	peak
2	*	4823.904	33.19	8.19	41.38	54.00	-12.62	AVG

Emission Level= Read Level+ Correct Factor

Temperature:	25 ℃	**Relative Humidity:**	55%
Test Voltage:	AC 120V/60 Hz		
Ant. Pol.	Vertical		
Test Mode:	TX B Mode 2412MHz Main ANT.		
Remark:	No report for the emission which more than 10 dB below the prescribed limit. Only show the worse case Main ANT.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		4823.904	43.94	8.19	52.13	74.00	-21.87	peak
2	*	4823.904	33.99	8.19	42.18	54.00	-11.82	AVG

Emission Level= Read Level+ Correct Factor

Temperature:	25 ℃	**Relative Humidity:**	55%
Temperature:	25 ℃	**Relative Humidity:**	55%
Test Voltage:	AC 120V/60 Hz		
Ant. Pol.	Horizontal		
Test Mode:	TX B Mode 2437MHz Main ANT.		
Remark:	No report for the emission which more than 10 dB below the prescribed limit. Only show the worse case Main ANT.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		4873.921	42.24	8.21	50.45	74.00	-23.55	peak
2	*	4873.921	32.04	8.21	40.25	54.00	-13.75	AVG

Emission Level= Read Level+ Correct Factor

Temperature:	25 ℃	**Relative Humidity:**	55%
Test Voltage:	AC 120V/60 Hz		
Ant. Pol.	Vertical		
Test Mode:	TX B Mode 2437MHz Main ANT.		
Remark:	No report for the emission which more than 10 dB below the prescribed limit. Only show the worse case Main ANT.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		4873.921	44.35	8.21	52.56	74.00	-21.44	peak
2	*	4873.921	35.31	8.21	43.52	54.00	-10.48	AVG

Emission Level= Read Level+ Correct Factor

Temperature:	25 ℃	**Relative Humidity:**	55%
Test Voltage:	AC 120V/60 Hz		
Ant. Pol.	Horizontal		
Test Mode:	TX B Mode 2462MHz Main ANT.		
Remark:	No report for the emission which more than 10 dB below the prescribed limit. Only show the worse case Main ANT.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		4923.913	43.65	8.22	51.87	74.00	-22.13	peak
2	*	4923.913	33.63	8.22	41.85	54.00	-12.15	AVG

Emission Level= Read Level+ Correct Factor

Temperature:	25 ℃	Relative Humidity:	55%
Test Voltage:	AC 120V/60 Hz		
Ant. Pol.	Vertical		
Test Mode:	TX B Mode 2462MHz Main ANT.		
Remark:	No report for the emission which more than 10 dB below the prescribed limit. Only show the worse case Main ANT.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		4923.913	44.07	8.22	52.29	74.00	-21.71	peak
2	*	4923.913	34.76	8.22	42.98	54.00	-11.02	AVG

Emission Level= Read Level+ Correct Factor

Temperature:	25 ℃	**Relative Humidity:**	55%
Test Voltage:	AC 120V/60 Hz		
Ant. Pol.	Horizontal		
Test Mode:	TX G Mode 2412MHz Main ANT.		
Remark:	No report for the emission which more than 10 dB below the prescribed limit. Only show the worse case Main ANT.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		4823.927	39.76	8.19	47.95	74.00	-26.05	peak
2	*	4823.927	29.46	8.19	37.65	54.00	-16.35	AVG

Emission Level= Read Level+ Correct Factor

Temperature:	25 ℃	**Relative Humidity:**	55%
Test Voltage:	AC 120V/60 Hz		
Ant. Pol.	Vertical		
Test Mode:	TX G Mode 2412MHz Main ANT.		
Remark:	No report for the emission which more than 10 dB below the prescribed limit. Only show the worse case Main ANT.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		4823.973	41.70	8.19	49.89	74.00	-24.11	peak
2	*	4823.973	30.75	8.19	38.94	54.00	-15.06	AVG

Emission Level= Read Level+ Correct Factor

Temperature:	25 ℃	**Relative Humidity:**	55%
Test Voltage:	AC 120V/60 Hz		
Ant. Pol.	Horizontal		
Test Mode:	TX G Mode 2437MHz Main ANT.		
Remark:	No report for the emission which more than 10 dB below the prescribed limit. Only show the worse case Main ANT.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		4873.958	40.01	8.21	48.22	74.00	-25.78	peak
2	*	4873.958	30.44	8.21	38.65	54.00	-15.35	AVG

Emission Level= Read Level+ Correct Factor

Temperature:	25 ℃	**Relative Humidity:**	55%
Test Voltage:	AC 120V/60 Hz		
Ant. Pol.	Vertical		
Test Mode:	TX G Mode 2437MHz Main ANT.		
Remark:	No report for the emission which more than 10 dB below the prescribed limit. Only show the worse case Main ANT.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		4873.972	40.99	8.21	49.20	74.00	-24.80	peak
2	*	4873.972	30.36	8.21	38.57	54.00	-15.43	AVG

Emission Level= Read Level+ Correct Factor

Temperature:	25 ℃	Relative Humidity:	55%
Test Voltage:	AC 120V/60 Hz		
Ant. Pol.	Horizontal		
Test Mode:	TX G Mode 2462MHz Main ANT.		
Remark:	No report for the emission which more than 10 dB below the prescribed limit. Only show the worse case Main ANT.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		4923.968	41.88	8.22	50.10	74.00	-23.90	peak
2	*	4923.968	32.04	8.22	40.26	54.00	-13.74	AVG

Emission Level= Read Level+ Correct Factor

Temperature:	25 ℃	**Relative Humidity:**	55%
Test Voltage:	AC 120V/60 Hz		
Ant. Pol.	Vertical		
Test Mode:	TX G Mode 2462MHz Main ANT.		
Remark:	No report for the emission which more than 10 dB below the prescribed limit. Only show the worse case Main ANT.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		4923.968	41.23	8.22	49.45	74.00	-24.55	peak
2	*	4923.968	32.81	8.22	41.03	54.00	-12.97	AVG

Emission Level= Read Level+ Correct Factor

Temperature:	25 ℃	**Relative Humidity:**	55%
Test Voltage:	AC 120V/60 Hz		
Ant. Pol.	Horizontal		
Test Mode:	TX n(HT20) Mode 2412MHz Main ANT.+AUX ANT.		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		4823.978	41.41	8.19	49.60	74.00	-24.40	peak
2	*	4823.978	30.79	8.19	38.98	54.00	-15.02	AVG

Emission Level= Read Level+ Correct Factor

Temperature:	25 ℃	**Relative Humidity:**	55%
Test Voltage:	AC 120V/60 Hz		
Ant. Pol.	Vertical		
Test Mode:	TX n(HT20) Mode 2412MHz Main ANT.+AUX ANT.		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		4823.984	40.37	8.19	48.56	74.00	-25.44	peak
2	*	4823.984	30.85	8.19	39.04	54.00	-14.96	AVG

Emission Level= Read Level+ Correct Factor

Temperature:	25 ℃	**Relative Humidity:**	55%
Test Voltage:	AC 120V/60 Hz		
Ant. Pol.	Horizontal		
Test Mode:	TX n(HT20) Mode 2437MHz Main ANT.+AUX ANT.		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		4873.966	40.69	8.21	48.90	74.00	-25.10	peak
2	*	4873.966	30.46	8.21	38.67	54.00	-15.33	AVG

Emission Level= Read Level+ Correct Factor

Temperature:	25 ℃	**Relative Humidity:**	55%
Test Voltage:	AC 120V/60 Hz		
Ant. Pol.	Vertical		
Test Mode:	TX n(HT20) Mode 2437MHz Main ANT.+AUX ANT.		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		4873.976	41.65	8.21	49.86	74.00	-24.14	peak
2	*	4873.976	30.37	8.21	38.58	54.00	-15.42	AVG

Emission Level= Read Level+ Correct Factor

Temperature:	25 ℃	Relative Humidity:	55%
Test Voltage:	AC 120V/60 Hz		
Ant. Pol.	Horizontal		
Test Mode:	TX n(HT20) Mode 2462MHz Main ANT.+AUX ANT.		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		4923.976	41.43	8.22	49.65	74.00	-24.35	peak
2	*	4923.976	30.43	8.22	38.65	54.00	-15.35	AVG

Emission Level= Read Level+ Correct Factor

Temperature:	25 ℃	**Relative Humidity:**	55%
Test Voltage:	AC 120V/60 Hz		
Ant. Pol.	Vertical		
Test Mode:	TX n(HT20) Mode 2462MHz Main ANT.+AUX ANT.		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		4923.976	41.46	8.22	49.68	74.00	-24.32	peak
2	*	4923.976	30.43	8.22	38.65	54.00	-15.35	AVG

Emission Level= Read Level+ Correct Factor

Temperature:	25 ℃	**Relative Humidity:**	55%
Test Voltage:	AC 120V/60 Hz		
Ant. Pol.	Horizontal		
Test Mode:	TX n(HT40) Mode 2422MHz Main ANT.+AUX ANT.		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		4843.968	41.68	8.20	49.88	74.00	-24.12	peak
2	*	4843.968	31.75	8.20	39.95	54.00	-14.05	AVG

Emission Level= Read Level+ Correct Factor

Temperature:	25 ℃	**Relative Humidity:**	55%
Test Voltage:	AC 120V/60 Hz		
Ant. Pol.	Vertical		
Test Mode:	TX n(HT40) Mode 2422MHz Main ANT.+AUX ANT.		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		4843.967	41.67	8.20	49.87	74.00	-24.13	peak
2	*	4843.967	30.69	8.20	38.89	54.00	-15.11	AVG

Emission Level= Read Level+ Correct Factor

Temperature:	25 ℃	**Relative Humidity:**	55%
Test Voltage:	AC 120V/60 Hz		
Ant. Pol.	Horizontal		
Test Mode:	TX n(HT40) Mode 2437MHz Main ANT.+AUX ANT.		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		4873.968	41.57	8.21	49.78	74.00	-24.22	peak
2	*	4873.968	30.44	8.21	38.65	54.00	-15.35	AVG

Emission Level= Read Level+ Correct Factor

Temperature:	25 ℃	**Relative Humidity:**	55%
Test Voltage:	AC 120V/60 Hz		
Ant. Pol.	Vertical		
Test Mode:	TX n(HT40) Mode 2437MHz Main ANT.+AUX ANT.		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		4873.968	41.47	8.21	49.68	74.00	-24.32	peak
2	*	4873.968	30.48	8.21	38.69	54.00	-15.31	AVG

Emission Level= Read Level+ Correct Factor

Temperature:	25 ℃	**Relative Humidity:**	55%
Test Voltage:	AC 120V/60 Hz		
Ant. Pol.	Horizontal		
Test Mode:	TX n(HT40) Mode 2462MHz Main ANT.+AUX ANT.		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		4903.968	40.74	8.21	48.95	74.00	-25.05	peak
2	*	4903.968	30.74	8.21	38.95	54.00	-15.05	AVG

Emission Level= Read Level+ Correct Factor

Temperature:	25 ℃	**Relative Humidity:**	55%
Test Voltage:	AC 120V/60 Hz		
Ant. Pol.	Vertical		
Test Mode:	TX n(HT40) Mode 2462MHz Main ANT.+AUX ANT.		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		4903.968	41.51	8.21	49.72	74.00	-24.28	peak
2	*	4903.968	30.64	8.21	38.85	54.00	-15.15	AVG

Emission Level= Read Level+ Correct Factor

Attachment C-- Restricted Bands Requirement and Band-edge Test Data

(1) Radiation Test

Temperature:	25 ℃	**Relative Humidity:**	55%
Test Voltage:	AC 120V/60HZ		
Ant. Pol.	Horizontal		
Test Mode:	TX B Mode 2412MHz Main ANT.		
Remark:	Only show the worse case Main ANT.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		2390.000	41.36	0.77	42.13	74.00	-31.87	peak
2		2390.000	29.41	0.77	30.18	54.00	-23.82	AVG
3	X	2410.600	89.44	0.86	90.30	Fundamental Frequency		peak
4	*	2411.400	84.93	0.86	85.79	Fundamental Frequency		AVG

Emission Level= Read Level+ Correct Factor

Temperature:	25 ℃	**Relative Humidity:**	55%
Test Voltage:	AC 120V/60HZ		
Ant. Pol.	Vertical		
Test Mode:	TX B Mode 2412MHz Main ANT.		
Remark:	Only show the worse case Main ANT.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		2390.000	30.00	0.77	30.77	54.00	-23.23	AVG
2		2390.000	42.78	0.77	43.55	54.00	-10.45	AVG
3	X	2413.400	91.44	0.86	92.30	Fundamental Frequency		peak
4	*	2413.800	86.78	0.86	87.64	Fundamental Frequency		AVG

Emission Level= Read Level+ Correct Factor

Temperature:	25 ℃	**Relative Humidity:**	55%
Test Voltage:	AC 120V/60HZ		
Ant. Pol.	Horizontal		
Test Mode:	TX B Mode 2462MHz Main ANT.		
Remark:	Only show the worse case Main ANT.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1	*	2462.700	86.62	1.08	87.70	Fundamental Frequency		AVG
2	X	2463.400	91.48	1.08	92.56	Fundamental Frequency		peak
3		2483.500	43.10	1.17	44.27	74.00	-29.73	peak
4		2483.500	30.26	1.17	31.43	54.00	-22.57	AVG

Emission Level= Read Level+ Correct Factor

Temperature:	25 ℃	Relative Humidity:	55%
Test Voltage:	AC 120V/60HZ		
Ant. Pol.	Vertical		
Test Mode:	TX B Mode 2462MHz Main ANT.		
Remark:	Only show the worse case Main ANT.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1	*	2462.700	86.84	1.08	87.92	Fundamental Frequency		AVG
2	X	2463.400	91.55	1.08	92.63	Fundamental Frequency		peak
3		2483.500	41.91	1.17	43.08	74.00	-30.92	peak
4		2483.500	30.23	1.17	31.40	54.00	-22.60	AVG

Emission Level= Read Level+ Correct Factor

Temperature:	25 ℃	Relative Humidity:	55%
Test Voltage:	AC 120V/60HZ		
Ant. Pol.	Horizontal		
Test Mode:	TX G Mode 2412MHz Main ANT.		
Remark:	Only show the worse case Main ANT.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		2390.000	42.55	0.77	43.32	74.00	-30.68	peak
2		2390.000	31.12	0.77	31.89	54.00	-22.11	AVG
3	*	2405.200	79.99	0.84	80.83	Fundamental Frequency		AVG
4	X	2406.100	90.42	0.84	91.26	Fundamental Frequency		peak

Emission Level= Read Level+ Correct Factor

Temperature:	25 ℃	Relative Humidity:	55%
Test Voltage:	AC 120V/60HZ		
Ant. Pol.	Vertical		
Test Mode:	TX G Mode 2412MHz Main ANT.		
Remark:	Only show the worse case Main ANT.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		2390.000	41.83	0.77	42.60	74.00	-31.40	peak
2		2390.000	30.55	0.77	31.32	54.00	-22.68	AVG
3	*	2414.100	80.22	0.87	81.09	Fundamental Frequency		AVG
4	X	2414.500	90.45	0.88	91.33	Fundamental Frequency		peak

Emission Level= Read Level+ Correct Factor

Temperature:	25 ℃	**Relative Humidity:**	55%
Test Voltage:	AC 120V/60HZ		
Ant. Pol.	Horizontal		
Test Mode:	TX G Mode 2462MHz Main ANT.		
Remark:	Only show the worse case Main ANT.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1	*	2464.000	81.47	1.08	82.55	Fundamental Frequency		AVG
2	X	2466.800	91.89	1.10	92.99	Fundamental Frequency		peak
3		2483.500	42.30	1.17	43.47	74.00	-30.53	peak
4		2483.500	31.85	1.17	33.02	54.00	-20.98	AVG

Emission Level= Read Level+ Correct Factor

Temperature:	25 ℃	Relative Humidity:	55%
Test Voltage:	AC 120V/60HZ		
Ant. Pol.	Vertical		
Test Mode:	TX G Mode 2462MHz Main ANT.		
Remark:	Only show the worse case Main ANT.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1	X	2465.900	91.87	1.09	92.96	Fundamental Frequency		peak
2	*	2468.500	80.91	1.11	82.02	Fundamental Frequency		AVG
3		2483.500	31.74	1.17	32.91	54.00	-21.09	AVG
4		2483.500	43.95	1.17	45.12	74.00	-28.88	peak

Emission Level= Read Level+ Correct Factor

Temperature:	25 ℃	Relative Humidity:	55%
Test Voltage:	AC 120V/60HZ		
Ant. Pol.	Horizontal		
Test Mode:	TX N(HT20) Mode 2412MHz Main ANT.+Aux ANT.		
Remark:	N/A		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		2390.000	42.54	0.77	43.31	74.00	-30.69	peak
2		2390.000	30.83	0.77	31.60	54.00	-22.40	AVG
3	X	2404.600	90.18	0.83	91.01	Fundamental Frequency		peak
4	*	2405.500	79.73	0.84	80.57	Fundamental Frequency		AVG

Emission Level= Read Level+ Correct Factor

Temperature:	25 ℃	Relative Humidity:	55%
Test Voltage:	AC 120V/60HZ		
Ant. Pol.	Vertical		
Test Mode:	TX N(HT20) Mode 2412MHz Main ANT.+Aux ANT.		
Remark:	N/A		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		2390.000	42.02	0.77	42.79	74.00	-31.21	peak
2		2390.000	30.15	0.77	30.92	54.00	-23.08	AVG
3	X	2414.800	90.79	0.88	91.67	Fundamental Frequency		peak
4	*	2415.300	79.71	0.88	80.59	Fundamental Frequency		AVG

Emission Level= Read Level+ Correct Factor

Temperature:	25 ℃	**Relative Humidity:**	55%
Test Voltage:	AC 120V/60HZ		
Ant. Pol.	Horizontal		
Test Mode:	TX N(HT20) Mode 2462MHz +Aux ANT.		
Remark:	N/A		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1	X	2465.200	91.82	1.09	92.91	Fundamental Frequency		peak
2	*	2465.700	80.72	1.09	81.81	Fundamental Frequency		AVG
3		2483.500	42.40	1.17	43.57	74.00	-30.43	peak
4		2483.500	31.43	1.17	32.60	54.00	-21.40	AVG

Emission Level= Read Level+ Correct Factor

Temperature:	25 ℃	Relative Humidity:	55%
Test Voltage:	AC 120V/60HZ		
Ant. Pol.	Vertical		
Test Mode:	TX N(HT20) Mode 2462MHz Main ANT.+Aux ANT.		
Remark:	N/A		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1	X	2457.100	91.94	1.05	92.99	Fundamental Frequency		peak
2	*	2464.200	80.80	1.08	81.88	Fundamental Frequency		AVG
3		2483.500	42.99	1.17	44.16	74.00	-29.84	peak
4		2483.500	31.59	1.17	32.76	54.00	-21.24	AVG

Emission Level= Read Level+ Correct Factor

Temperature:	25 ℃	Relative Humidity:	55%
Test Voltage:	AC 120V/60HZ		
Ant. Pol.	Horizontal		
Test Mode:	TX N(HT40) Mode 2422MHz Main ANT.+Aux ANT.		
Remark:	N/A		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		2390.000	43.54	0.77	44.31	74.00	-29.69	peak
2		2390.000	31.02	0.77	31.79	54.00	-22.21	AVG
3		2400.000	50.79	0.81	51.60	74.00	-22.40	peak
4		2400.000	41.22	0.81	42.03	54.00	-11.97	AVG
5	*	2425.100	75.80	0.93	76.73	Fundamental Frequency		AVG
6	X	2432.400	86.32	0.95	87.27	Fundamental Frequency		peak

Emission Level= Read Level+ Correct Factor

Temperature:	25 ℃	Relative Humidity:	55%
Test Voltage:	AC 120V/60HZ		
Ant. Pol.	Vertical		
Test Mode:	TX N(HT40) Mode 2422MHz Main ANT.+Aux ANT.		
Remark:	N/A		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		2390.000	43.38	0.77	44.15	74.00	-29.85	peak
2		2390.000	31.24	0.77	32.01	54.00	-21.99	AVG
3		2400.000	51.33	0.81	52.14	74.00	-21.86	peak
4		2400.000	41.86	0.81	42.67	54.00	-11.33	AVG
5	*	2431.400	77.86	0.95	78.81	Fundamental Frequency		AVG
6	X	2432.500	88.40	0.95	89.35	Fundamental Frequency		peak

Emission Level= Read Level+ Correct Factor

Temperature:	25 ℃	**Relative Humidity:**	55%
Test Voltage:	AC 120V/60HZ		
Ant. Pol.	Horizontal		
Test Mode:	TX N(HT40) Mode 2452MHz Main ANT.+Aux ANT.		
Remark:	N/A		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1	*	2453.800	77.70	1.04	78.74	Fundamental Frequency		AVG
2	X	2454.700	87.82	1.05	88.87	Fundamental Frequency		peak
3		2483.500	43.13	1.17	44.30	74.00	-29.70	peak
4		2483.500	31.25	1.17	32.42	54.00	-21.58	AVG
5		2500.000	43.15	1.23	44.38	74.00	-29.62	peak
6		2500.000	30.68	1.23	31.91	54.00	-22.09	AVG

Emission Level= Read Level+ Correct Factor

Temperature:	25 ℃	Relative Humidity:	55%
Test Voltage:	AC 120V/60HZ		
Ant. Pol.	Vertical		
Test Mode:	TX N(HT40) Mode 2452MHz Main ANT.+Aux ANT.		
Remark:	N/A		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1	X	2454.900	89.33	1.05	90.38	Fundamental Frequency		peak
2	*	2455.000	82.52	1.05	83.57	Fundamental Frequency		AVG
3		2483.500	47.23	1.17	48.40	74.00	-25.60	peak
4		2483.500	34.97	1.17	36.14	54.00	-17.86	AVG
5		2500.000	45.67	1.23	46.90	74.00	-27.10	peak
6		2500.000	33.67	1.23	34.90	54.00	-19.10	AVG

Emission Level= Read Level+ Correct Factor

(2) Conducted Test

Temperature:	25 ℃	**Relative Humidity:**	55%
Test Voltage:	AC 120V/60HZ		
Test Mode:	TX B Mode 2412MHz / TX B Mode 2462MHz Main ANT.		
Remark:	The EUT is programed in continuously transmitting mode		





Temperature:	25 ℃	Relative Humidity:	55%
Test Voltage:	AC 120V/60HZ		
Test Mode:	TX B Mode 2412MHz / TX B Mode 2462MHz Aux ANT.		
Remark:	The EUT is programed in continuously transmitting mode		





Temperature:	25 ℃	Relative Humidity:	55%
Test Voltage:	AC 120V/60HZ		
Test Mode:	TX G Mode 2412MHz / TX G Mode 2462MHz Main ANT.		
Remark:	The EUT is programed in continuously transmitting mode		





Temperature:	25 ℃	**Relative Humidity:**	55%
Test Voltage:	AC 120V/60HZ		
Test Mode:	TX G Mode 2412MHz / TX G Mode 2462MHz Aux ANT.		
Remark:	The EUT is programed in continuously transmitting mode		





Temperature:	25 ℃	**Relative Humidity:**	55%
Test Voltage:	AC 120V/60HZ		
Test Mode:	TX N(HT20) Mode 2412MHz / TX N(HT20) Mode 2462MHz Main ANT.		
Remark:	The EUT is programed in continuously transmitting mode		





Temperature:	25 ℃	Relative Humidity:	55%
Test Voltage:	AC 120V/60HZ		
Test Mode:	TX N(HT20) Mode 2412MHz / TX N(HT20) Mode 2462MHz Aux ANT.		
Remark:	The EUT is programed in continuously transmitting mode		





Temperature:	25 ℃	Relative Humidity:	55%
Test Voltage:	AC 120V/60HZ		
Test Mode:	TX N(HT40) Mode 2422MHz / TX N(HT40) Mode 2452MHz Main ANT.		
Remark:	The EUT is programed in continuously transmitting mode		





Temperature:	25 ℃	Relative Humidity:	55%
Test Voltage:	AC 120V/60HZ		
Test Mode:	TX N(HT40) Mode 2422MHz / TX N(HT40) Mode 2452MHz Aux ANT.		
Remark:	The EUT is programed in continuously transmitting mode		





Attachment D-- Bandwidth Test Data

Temperature:	25 ℃	Relative Humidity:	55%
Test Voltage:	AC 120V/60HZ		
Test Mode:	TX 802.11B Mode Main ANT.		

Channel frequency (MHz)	6dB Bandwidth (MHz)	99% Bandwidth (MHz)	Limit (MHz)
2412	10.059	14.2108	>=0.5
2437	9.064	14.1733	
2462	9.617	14.2664	

802.11B Mode

2412 MHz



802.11B Mode

2437 MHz



802.11B Mode

2462 MHz



Temperature:	25 ℃	Relative Humidity:	55%
Test Voltage:	AC 120V/60HZ		
Test Mode:	TX 802.11B Mode Aux ANT.		

Channel frequency (MHz)	6dB Bandwidth (MHz)	99% Bandwidth (MHz)	Limit (MHz)
2412	10.078	14.2389	>=0.5
2437	10.053	14.1797	
2462	10.084	14.2204	

802.11B Mode

2412 MHz



802.11B Mode

2437 MHz



802.11B Mode

2462 MHz



Temperature:	25 ℃	Relative Humidity:	55%
Test Voltage:	AC 120V/60HZ		
Test Mode:	TX 802.11G Mode Main ANT.		

Channel frequency (MHz)	6dB Bandwidth (MHz)	99% Bandwidth (MHz)	Limit (MHz)
2412	16.407	16.5105	>=0.5
2437	16.575	16.5068	
2462	16.588	16.4824	

802.11G Mode

2412 MHz



802.11G Mode

2437 MHz



802.11G Mode

2462 MHz



Temperature:	25 ℃	Relative Humidity:	55%
Test Voltage:	AC 120V/60HZ		
Test Mode:	TX 802.11G Mode Aux ANT.		

Channel frequency (MHz)	6dB Bandwidth (MHz)	99% Bandwidth (MHz)	Limit (MHz)
2412	16.482	16.5372	>=0.5
2437	16.572	16.4760	
2462	16.606	16.4997	

802.11G Mode

2412 MHz



802.11G Mode

2437 MHz



802.11G Mode

2462 MHz



Temperature:	25 ℃	Relative Humidity:	55%
Test Voltage:	AC 120V/60HZ		
Test Mode:	TX 802.11N(HT20) Mode Main ANT.		

Channel frequency (MHz)	6dB Bandwidth (MHz)	99% Bandwidth (MHz)	Limit (MHz)
2412	17.846	17.6438	>=0.5
2437	17.843	17.6446	
2462	17.805	17.6747	

802.11N(HT20) Mode

2412 MHz



802.11N(HT20) Mode

2437 MHz



802.11N(HT20) Mode

2462 MHz



Temperature:	25 ℃	Relative Humidity:	55%
Test Voltage:	AC 120V/60HZ		
Test Mode:	TX 802.11N(HT20) Mode Aux ANT.		

Channel frequency (MHz)	6dB Bandwidth (MHz)	99% Bandwidth (MHz)	Limit (MHz)
2412	17.856	17.6612	>=0.5
2437	17.833	17.6356	
2462	17.838	17.6650	

802.11N(HT20) Mode

2412 MHz



802.11N(HT20) Mode

2437 MHz



802.11N(HT20) Mode

2462 MHz



Temperature:	25 ℃	Relative Humidity:	55%
Test Voltage:	AC 120V/60HZ		
Test Mode:	TX 802.11N(HT40) Mode Main ANT.		

Channel frequency (MHz)	6dB Bandwidth (MHz)	99% Bandwidth (MHz)	Limit (MHz)
2422	36.636	36.1317	>=0.5
2437	36.594	36.0684	
2452	36.567	36.0237	

802.11N(HT40) Mode

2422 MHz



802.11N(HT40) Mode

2437 MHz



802.11N(HT40) Mode

2452 MHz



Temperature:	25 ℃	Relative Humidity:	55%
Test Voltage:	AC 120V/60HZ		
Test Mode:	TX 802.11N(HT40) Mode Aux ANT.		

Channel frequency (MHz)	6dB Bandwidth (MHz)	99% Bandwidth (MHz)	Limit (MHz)
2422	36.600	36.0988	>=0.5
2437	36.658	36.1264	
2452	36.614	36.1204	

802.11N(HT40) Mode

2422 MHz



802.11N(HT40) Mode

2437 MHz



802.11N(HT40) Mode

2452 MHz



Attachment E-- Peak Output Power Test Data

Conducted Power					
802.11b Power					
Channel	**Frequency**	**Conducted Power (dBm)**			**Max. Limit (dBm)**
		Main Ant.	**Aux Ant.**	**Total**	
1	**2412 MHz**	8.13	8.07	---	**30**
6	**2437 MHz**	8.18	8.06	---	
11	**2462 MHz**	8.15	8.04	---	
802.11g Power					
Channel	**Frequency**	**Conducted Power (dBm)**			**Max. Limit (dBm)**
		Main Ant.	**Aux Ant.**	**Total**	
1	**2412 MHz**	7.89	7.68	---	**30**
6	**2437 MHz**	7.96	7.74	---	
11	**2462 MHz**	7.78	7.68	---	
802.11n(HT20) Power					
Channel	**Frequency**	**Conducted Power (dBm)**			**Max. Limit (dBm)**
		Main Ant.	**Aux Ant.**	**Total**	
1	**2412 MHz**	4.58	4.23	7.42	**30**
6	**2437 MHz**	4.63	4.19	7.43	
11	**2462 MHz**	4.57	4.22	7.41	
802.11n(HT40) Power					
Channel	**Frequency**	**Conducted Power (dBm)**			**Max. Limit (dBm)**
		Main Ant.	**Aux Ant.**	**Total**	
3	**2422 MHz**	4.68	4.15	7.42	**30**
6	**2437 MHz**	4.55	4.24	7.41	
9	**2452 MHz**	4.68	4.12	7.42	
Note: When Main ANT. and Aux ANT. transmitting simultaneously, the total Antenna Gain=Main Gain +Aux Gani =5.01 dBi＜ 6 dBi. **So P_{out} =P_{limit}=30dBm**					

Duty Cycle		
Mode	Channel frequency (MHz)	Test Result
802.11b	2412	>98%
	2437	
	2462	
802.11g	2412	
	2437	
	2462	
802.11n (HT20)	2412	
	2437	
	2462	
802.11n (HT40)	2422	
	2437	
	2452	
Please see below plots		

802.11 B Mode 2437 MHz



802.11 G Mode 2437 MHz



802.11 N(HT20) Mode 2437 MHz



802.11 N(HT40) Mode 2437 MHz



Attachment F-- Power Spectral Density Test Data

802.11b Mode					
Channel	Frequency	Conducted Power (dBm/3KHz)			Max. Limit (dBm/3KHz)
		Main Ant.	Aux Ant.	Total	
1	2412 MHz	-24.41	-24.36	---	8
6	2437 MHz	-24.69	-24.72	---	
11	2462 MHz	-25.05	-25.12	---	
802.11g Mode					
Channel	Frequency	Conducted Power (dBm/3KHz)			Max. Limit (dBm/3KHz)
		Main Ant.	Aux Ant.	Total	
1	2412 MHz	-25.57	-25.77	---	8
6	2437 MHz	-25.73	-25.79	---	
11	2462 MHz	-25.93	-26.00	---	
802.11n(HT20) Mode					
Channel	Frequency	Conducted Power (dBm/3KHz)			Max. Limit (dBm/3KHz)
		Main Ant.	Aux Ant.	Total	
1	2412 MHz	-29.31	-29.77	-26.52	8
6	2437 MHz	-29.27	-29.66	-26.45	
11	2462 MHz	-29.41	-30.00	-26.68	
802.11n(HT40) Mode					
Channel	Frequency	Conducted Power (dBm/3KHz)			Max. Limit (dBm/3KHz)
		Main Ant.	Aux Ant.	Total	
3	2422 MHz	-31.39	-30.80	-28.07	8
6	2437 MHz	-31.74	-31.77	-28.74	
9	2452 MHz	-31.09	-30.60	-27.83	
Note: When Main ANT. and Aux ANT. transmitting simultaneously, the total Antenna Gain=Main Gain + Aux Gani =5.01 dBi＜6 dBi. So P_{out} =P_{limit}=8					
Test plots please refer to below pages:					

802.11 b 2412 MHz (Main ANT.)



802.11 b 2437 MHz (Main ANT.)



802.11 b 2462MHz (Main ANT.)



802.11 b 2412 MHz (Aux ANT.)



802.11 b 2437 MHz (Aux ANT.)



802.11 b 2462MHz (Aux ANT.)



802.11 g 2412 MHz (Main ANT.)

802.11 g 2437 MHz (Main ANT.)

802.11 g 2462MHz (Main ANT.)


802.11 g 2412 MHz (Aux ANT.)



802.11 g 2437 MHz (Aux ANT.)



802.11 g 2462 MHz (Aux ANT.)



802.11 n(HT20) 2412 MHz (Main ANT.)

802.11 n(HT20) 2437 MHz (Main ANT.)

802.11 n(HT20) 2462MHz (Main ANT.)


802.11 n(HT20) 2412 MHz (Aux ANT.)

802.11 n(HT20) 2437 MHz (Aux ANT.)

802.11 n(HT20) 2462MHz (Aux ANT.)


802.11 n(HT40) 2422 MHz (Main ANT.)

802.11 n(HT40) 2437 MHz (Main ANT.)

802.11 n(HT40) 2452MHz (Main ANT.)


802.11 n(HT40) 2422 MHz (Aux ANT.)



802.11 n(HT40) 2437 MHz (Aux ANT.)



802.11 n(HT40) 2452MHz (Aux ANT.)



-----END OF REPORT-----