FCC PART 15C
TEST REPORT

No.24T04Z101135-021

for

Schok LLC

ChronoVolt Smartwatch

Model Name: ChronoVolt_CV16

FCC ID:2AM9L-CV16

with

Hardware Version:1V0

Software Version:CV16_01.02.01

IssuedDate:2024-9-23

Note:

The test results in this test report relate only to the devices specified in this report.This report shall not be reproduced except in full without the written approval of CTTL.

Test Laboratory:

CTTL, Telecommunication Technology Labs, CAICT

No.52, HuayuanNorth Road, Haidian District, Beijing, P. R. China 100191.

Tel:+86(0)10-62304633-2512,Fax:+86(0)10-62304633-2504

Email:cttl_terminals@caict.ac.cn, website:www.chinattl.com

©Copyright. All rights reserved by CTTL.

REPORT HISTORY

Report Number	Revision	Description	Issue Date
24T04Z101135-021	Rev.0	1st edition	2024-9-23

Note: the latest revision of the test report supersedes all previous version.

©Copyright. All rights reserved by CTTL .

CONTENTS

1. TEST LABORATORY 5

1.1. INTRODUCTION &ACCREDITATION 5
1.2. TESTING LOCATION 5
1.3. TESTING ENVIRONMENT 6
1.4. PROJECT DATA 6
1.5. SIGNATURE 6

2. CLIENT INFORMATION 7

2.1. APPLICANT INFORMATION 7
2.2. MANUFACTURER INFORMATION 7

3. EQUIPMENT UNDER TEST (EUT) AND ANCILLARY EQUIPMENT (AE) 8

3.1. ABOUT EUT 8
3.2. INTERNAL IDENTIFICATION OF EUT 8
3.3. INTERNAL IDENTIFICATION OF AE 8
3.4. NORMAL ACCESSORY SETTING 8
3.5. GENERAL DESCRIPTION 8

4. REFERENCE DOCUMENTS 9

4.1. DOCUMENTS SUPPLIED BY APPLICANT 9
4.2. REFERENCE DOCUMENTS FOR TESTING 9

5. TEST RESULTS 10

5.1. SUMMARY OF TEST RESULTS 10
5.2. STATEMENTS 10

6. TEST FACILITIES UTILIZED 11

7. MEASUREMENT UNCERTAINTY 12

7.1. PEAK OUTPUT POWER - CONDUCTED 12
7.2. FREQUENCY BAND EDGES - CONDUCTED 12
7.3. TRANSMITTER SPURIOUS EMISSION - CONDUCTED 12
7.4. TRANSMITTER SPURIOUS EMISSION - RADIATED 12
7.5. TIME OF OCCUPANCY (DWELL TIME) 12
7.6. 20DB BANDWIDTH 12
7.7. CARRIER FREQUENCY SEPARATION 13
7.8. AC POWERLINE CONDUCTED EMISSION 13

ANNEX A: EUT PARAMETERS 14

ANNEX B: DETAILED TEST RESULTS 15

B.1. MEASUREMENT METHOD 15
B.2. PEAK OUTPUT POWER 16
B.3. FREQUENCY BAND EDGES – CONDUCTED 18

©Copyright. All rights reserved by CTTL .

B.4. TRANSMITTER SPURIOUS EMISSION - CONDUCTED 25
B.5. RADIATED UNWANTED EMISSION 50
B.6. TIME OF OCCUPANCY (DWELL TIME) 61
B.7. 20DB BANDWIDTH 72
B.8. CARRIER FREQUENCY SEPARATION 78
B.9. NUMBER OF HOPPING CHANNELS 81
B.10. AC POWERLINE CONDUCTED EMISSION 85
B.11. ANTENNA REQUIREMENT 89

ANNEX C: ACCREDITATION CERTIFICATE 90

©Copyright. All rights reserved by CTTL .

1. Test Laboratory

1.1. Introduction &Accreditation

Telecommunication Technology Labs, CAICT is an ISO/IEC 17025:2017 accredited test laboratory under American Association for Laboratory Accreditation (A2LA) with lab code 7049.01, and is also an FCC accredited test laboratory (CN1349), and ISED accredited test laboratory (CAB identifier:CN0066). The detail accreditation scope can be found on A2LA website

1.2. Testing Location

Conducted testing Location:CTTL(huayuan North Road)

Address: No. 52, Huayuan North Road, Haidian District, Beijing, P. R. China100191

Radiated testing Location:CTTL(huayuan North Road)

Address: No. 52, Huayuan North Road, Haidian District, Beijing, P. R. China100191

©Copyright. All rights reserved by CTTL .

1.3. Testing Environment

Normal Temperature: 20-27℃

Relative Humidity: 20-50%

1.4. Project data

Testing Start Date: 2024-6-3

Testing End Date: 2024-9-23

1.5. Signature

Wu Le

(Prepared this test report)

Sun Zhenyu

(Reviewed this test report)

Hu Xiaoyu

(Approved this test report)

©Copyright. All rights reserved by CTTL .

2. ClientInformation

2.1. Applicant Information

Company Name:	Schok LLC
Address/Post:	5850 Town and Country Blvd, Suite 203, Frisco, TX 75034, USA
Contact:	Michael Harshbarger
Email:	mike.harsh@schokgear.com
Telephone:	+1-847-809-3294
Fax:	/

2.2. Manufacturer Information

Company Name:	Schok LLC
Address/Post:	5850 Town and Country Blvd, Suite 203, Frisco, TX 75034, USA
Contact:	Michael Harshbarger
Email:	mike.harsh@schokgear.com
Telephone:	+1-847-809-3294
Fax:	/

©Copyright. All rights reserved by CTTL .

3. Equipment UnderTest (EUT) and Ancillary Equipment (AE)

3.1. About EUT

Description	ChronoVolt Smartwatch
Model Name	ChronoVolt_CV16
FCC ID	2AM9L-CV16
Frequency Band	ISM 2400MHz~2483.5MHz
Type of Modulation	GFSK/π/4 DQPSK/8DPSK
Number of Channels	79
Power Supply	3.8V DC by Battery
Antenna gain	-1.5dBi

3.2. Internal Identification of EUT

EUT ID*	SN or IMEI	HW Version	SW Version	Date of receipt
UT27a	357167500002627	1V0	CV16_01.02.01	2024-6-3
UT14a	357167500000530	1V0	CV16_01.02.01	2024-6-3

*EUT ID: is used to identify the test sample in the lab internally.

3.3. Internal Identification of AE

AE ID*	Description	Model	Manufacturer
AE1	Battery1	572829A	HUATIANTONG
AE2	Charger1	UT-681A-5100UY	Baijunda
AE3	USB Cable1	K1-USB	pomagtor

*AE ID: is used to identify the test sample in the lab internally.

3.4. Normal Accessory setting

Fully charged battery should be used during the test.

3.5. General Description

The Equipment Under Test (EUT) is a model of ChronoVolt Smartwatch with integrated antenna. It consists of normal options: lithium battery, charger. Manual and specifications of the EUT were provided to fulfill the test.Samples undergoing test were selected by the Client.

©Copyright. All rights reserved by CTTL .

4. Reference Documents

4.1. Documents supplied by applicant

EUT parameters, referring to Annex A for detailed information, is supplied by the client or manufacturer, which is the basis of testing.

4.2. Reference Documents for testing

The following documents listed in this section are referred for testing.

Reference	Title	Version
FCC Part15	FCC CFR 47, Part 15, Subpart C: 15.205 Restricted bands of operation; 15.209 Radiated emission limits, general requirements; 15.247 Operation within the bands 902–928MHz, 2400–2483.5 MHz, and 5725–5850 MHz.	2023
ANSI C63.10	American National Standard of Procedures for ComplianceTesting of Unlicensed Wireless Devices	June,2013

©Copyright. All rights reserved by CTTL .

5. Test Results

5.1. Summary of Test Results

Abbreviations used in this clause:

P Pass, The EUT complies with the essential requirements in the standard.

F Fail, The EUT does not complywith the essential requirements in the standard

NA Not Applicable,The test was not applicable

NP Not Performed,The test was not performed by CTTL

SUMMARY OF MEASUREMENT RESULTS	Sub-clause	Verdict
Peak Output Power	15.247 (b)(1)	**P**
Frequency Band Edges- Conducted	15.247 (d)	**P**
Transmitter Spurious Emission - Conducted	15.247 (d)	**P**
Radiated Unwanted Emission	15.247, 15.205, 15.209	**P**
Time of Occupancy (Dwell Time)	15.247 (a) (1)(iii)	**P**
20dB Bandwidth	15.247 (a)(1)	**NA**
Carrier Frequency Separation	15.247 (a)(1)	**P**
Number of hopping channels	15.247 (a)(iii)	**P**
AC Powerline Conducted Emission	15.107, 15.207	**P**
Antenna Requirement	15.203	**P**

Please refer to **ANNEX A** for detail.

The measurement is made according to ANSI C63.10.

5.2. Statements

CTTL has evaluated the test cases requested by the applicant /manufacturer as listed in section 5.1 of this report for the EUT specified in section 3 according to the standards or reference documents listed in section 4.2

©Copyright. All rights reserved by CTTL .

6. Test Facilities Utilized

Conducted test system

No.	Equipment	Model	Serial Number	Manufacturer	Calibration Period	Calibration Due date
1	Vector Signal Analyzer	FSQ26	100024	R&S	1 year	2025-03-09
2	Bluetooth Tester	CBT	100315	R&S	1 year	2025-03-08
3	Test Receiver	ESCI 3	100344	R&S	1 year	2025-04-01
4	LISN	ENV216	101200	R&S	1 year	2025-05-16
5	Shielding Room	S81	/	ETS-Lindgren	/	/

Radiated emission test system

No.	Equipment	Model	Serial Number	Manufacturer	Calibration Period	Calibration Due date
1	Test Receiver	ESW44	103144	R&S	1 year	2024-11-26
2	EMI Antenna	VULB 9163	01223	SCHWARZBECK	1 year	2024-08-18
3	EMI Antenna	3115	00167250	ETS-Lindgren	1 year	2025-05-11

※Note: The EMI Antenna with series number of 01223 did not exceed the CAL.DUE.DATE when used.

©Copyright. All rights reserved by CTTL .

7. Measurement Uncertainty

7.1. Peak Output Power - Conducted

Measurement Uncertainty:

Measurement Uncertainty(k=2)	0.66dB

7.2. Frequency Band Edges- Conducted

Measurement Uncertainty:

Measurement Uncertainty(k=2)	0.66dB

7.3. Transmitter Spurious Emission - Conducted

Measurement Uncertainty:

FrequencyRange	Uncertainty(k=2)
30 MHz ~ 8 GHz	1.22dB
8 GHz ~ 12.75 GHz	1.51dB
12.7GHz ~ 26 GHz	1.51dB

7.4. Transmitter Spurious Emission - Radiated

Measurement Uncertainty:

FrequencyRange	Uncertainty(dBm) (k=2)
9kHz-30MHz	/
30MHz ≤ f ≤ 1GHz	4.72
1GHz ≤ f ≤18GHz	4.84
18GHz ≤ f ≤40GHz	5.12

7.5. Time of Occupancy (Dwell Time)

Measurement Uncertainty:

Measurement Uncertainty(k=2)	0.88ms

7.6. 20dB Bandwidth

Measurement Uncertainty:

Measurement Uncertainty(k=2)	61.936Hz

©Copyright. All rights reserved by CTTL .

7.7. Carrier Frequency Separation

Measurement Uncertainty:

Measurement Uncertainty(k=2)	61.936Hz

7.8. AC Powerline Conducted Emission

Measurement Uncertainty:

Measurement Uncertainty(k=2)	3.08dB

©Copyright. All rights reserved by CTTL .

ANNEX A: EUTparameters

Disclaimer: The antenna gain provided by the client may affect the validity of the measurement results in this report, and the client shall bear the impact and consequences arising therefrom.

©Copyright. All rights reserved by CTTL .

ANNEX B: Detailed Test Results

B.1. Measurement Method

B.1.1. Conducted Measurements

The measurement is made according to ANSI C63.10.

1). Connect the EUT to the test system correctly.

2). Set the EUT to the required work mode (Transmitter, receiver or transmitter & receiver).

3). Set the EUT to the required channel.

4). Set the EUT hopping mode (hopping or hopping off).

5). Set the spectrum analyzer to start measurement.

6). Record the values. Vector Signal Analyzer



B.1.2. Radiated Emission Measurements

The measurement is made according to ANSI C63.10

The radiated emission test is performed in semi-anechoic chamber. The EUT was placed on a non-conductive table with 80cm above the ground plane for measurement below 1GHz and 1.5m above the ground plane for measurement above 1GHz. The measurement antenna was placed at a distance of 3 meters from the EUT. The test is carried out on both vertical and horizontal polarization and only maximization result of both polarizations is kept. During the test, the turntable is rotated from 0° to 360°and the measurement antenna is moved from 1m to 4m to get the maximization result. The maximization process was repeated with the EUT positioned in each of its three orthogonal orientations.

©Copyright. All rights reserved by CTTL .

B.2. Peak Output Power

B.2.1. Peak Output Power – Conducted

Method of Measurement: See ANSI C63.10-clause 7.8.5

a) Use the following spectrum analyzer settings:

- Span: 6MHz
- RBW: 3MHz
- VBW: 3MHz
- Sweep time: 2.5ms
- Detector function: peak
- Trace: max hold

b) Allow trace to stabilize.

c) Use the marker-to-peak function to set the marker to the peak of the emission.

d) The indicated level is the peak output power.

Measurement Limit:

Standard	Limits	
FCC Part 15.247(b)(1)	Bandwidth≤1MHz	30dBm (1W)
	Bandwidth＞1MHz	21dBm (125mW)

Measurement Results:

For GFSK

Channel	Ch 0 2402 MHz	Ch 39 2441 MHz	Ch 78 2480 MHz	Conclusion
Peak Conducted Output Power (dBm)	8.47	9.61	8.58	P

Forπ/4 DQPSK

Channel	Ch 0 2402 MHz	Ch 39 2441 MHz	Ch 78 2480 MHz	Conclusion
Peak Conducted Output Power (dBm)	8.50	9.53	8.60	P

For 8DPSK

Channel	Ch 0 2402 MHz	Ch 39 2441 MHz	Ch 78 2480 MHz	Conclusion
Peak Conducted Output Power (dBm)	8.87	9.76	8.96	P

Conclusion: PASS

©Copyright. All rights reserved by CTTL .

B.2.2. E.I.R.P.

The radiated E.I.R.P. is listed below:

Antenna gain =-1.5dBi

For GFSK

Channel	Ch 0 2402 MHz	Ch 39 2441 MHz	Ch 78 2480 MHz	Conclusion
E.I.R.P (dBm)	6.97	8.11	7.08	P

Forπ/4 DQPSK

Channel	Ch 0 2402 MHz	Ch 39 2441 MHz	Ch 78 2480 MHz	Conclusion
E.I.R.P (dBm)	7.00	8.03	7.10	P

For 8DPSK

Channel	Ch 0 2402 MHz	Ch 39 2441 MHz	Ch 78 2480 MHz	Conclusion
E.I.R.P (dBm)	7.37	8.26	7.46	P

Note: E.I.R.P. are calculated with the antenna gain.

Conclusion: PASS

©Copyright. All rights reserved by CTTL .

B.3. Frequency Band Edges – Conducted

Method of Measurement: See ANSI C63.10-clause 7.8.6

Connect the spectrum analyzer to the EUT using an appropriate RF cable connected to the EUT output.Configure the spectrum analyzer settings as described below (be sure to enter all losses between theunlicensed wireless device output and the spectrum analyzer).

–Span: 10 MHz

– Resolution Bandwidth: 100 kHz

– Video Bandwidth: 300 kHz

– Sweep Time:Auto

– Detector: Peak

–Trace: max hold

Place a marker at the end of the restricted band closest to the transmit frequency to show compliance. Also measure any emissions in the restricted bands. Save the spectrum analyzer plot. Repeat for each power and modulation for lowest and highest channel.

Observe the stored trace and measure the amplitude deltabetween the peak of the fundamental and the peak of the band-edge emission. This is not anabsolute field strength measurement; it is only a relative measurement to determine the amount bywhich the emission drops at the band edge relative to the highest fundamental emission level.

Measurement Limit:

Standard	Limit (dBc)
FCC 47 CFR Part 15.247 (d)	<-20

Measurement Result:

For GFSK

Channel	Hopping	Band Edge Power (dBc)		Conclusion
0	Hopping OFF	Fig.1	-63.27	P
	Hopping ON	Fig.2	-57.02	P
78	Hopping OFF	Fig.3	-64.37	P
	Hopping ON	Fig.4	-63.82	P

Forπ/4 DQPSK

Channel	Hopping	Band Edge Power (dBc)		Conclusion
0	Hopping OFF	Fig.5	-59.12	P
	Hopping ON	Fig.6	-63.83	P
78	Hopping OFF	Fig.7	-61.68	P
	Hopping ON	Fig.8	-62.96	P

For 8DPSK

Channel	Hopping	Band Edge Power (dBc)		Conclusion
0	Hopping OFF	Fig.9	-56.25	P
	Hopping ON	Fig.10	-61.93	P

©Copyright. All rights reserved by CTTL .

78	Hopping OFF	Fig.11	-62.42	P
	Hopping ON	Fig.12	-61.96	P

Conclusion: PASS

Test graphs as below



Fig.1. Frequency Band Edges: GFSK, Channel 0, Hopping Off



Fig.2. Frequency Band Edges: GFSK, Channel 0, Hopping On

©Copyright. All rights reserved by CTTL .



Fig.3. Frequency Band Edges: GFSK, Channel 78, Hopping Off



Fig.4. Frequency Band Edges: GFSK, Channel 78, Hopping On

©Copyright. All rights reserved by CTTL .



Fig.5. Frequency Band Edges: π/4 DQPSK, Channel 0, Hopping Off



Fig.6. Frequency Band Edges: π/4 DQPSK, Channel 0, Hopping On

©Copyright. All rights reserved by CTTL .



Fig.7. Frequency Band Edges: π/4 DQPSK, Channel 78, Hopping Off



Fig.8. Frequency Band Edges: π/4 DQPSK, Channel 78, Hopping On

©Copyright. All rights reserved by CTTL .



Fig.9. Frequency Band Edges: 8DPSK, Channel 0, Hopping Off



Fig.10. Frequency Band Edges: 8DPSK, Channel 0, Hopping On

©Copyright. All rights reserved by CTTL .



Fig.11. Frequency Band Edges: 8DPSK, Channel 78, Hopping Off



Fig.12. Frequency Band Edges: 8DPSK, Channel 78, Hopping On

©Copyright. All rights reserved by CTTL .

B.4. Transmitter Spurious Emission - Conducted

Method of Measurement: See ANSI C63.10-clause 7.8.8

Measurement Procedure – Reference Level

1. Set the RBW = 100 kHz.

2. Set the VBW = 300 kHz.

3. Set the span to 5-30 % greater than the EBW.

4. Detector = peak.

5. Sweep time = auto couple.

6. Trace mode = max hold.

7. Allow trace to fully stabilize.

8. Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW. Next, determine the power in 100 kHz band segments outside of the authorized frequency band using the following measurement:

Measurement Procedure - Unwanted Emissions

1. Set RBW = 100 kHz.

2. Set VBW = 300 kHz.

3. Set span to encompass the spectrum to be examined.

4. Detector = peak.

5. Trace Mode = max hold.

6. Sweep = auto couple.

7. Allow the trace to stabilize (this may take some time, depending on the extent of the span).

Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) is attenuated by at least the minimum requirements specified above.

Measurement Limit:

Standard	Limit
FCC 47 CFR Part 15.247 (d)	20dB below peak output power in 100 kHz bandwidth

Measurement Results:

For GFSK

Channel	Frequency Range	Test Results	Conclusion
Ch 0	Center Frequency	Fig.13	P

©Copyright. All rights reserved by CTTL .

2402 MHz	30 MHz ~ 1 GHz	Fig.14	P
	1 GHz ~ 3 GHz	Fig.15	P
	3 GHz ~ 10 GHz	Fig.16	P
	10 GHz ~ 26 GHz	Fig.17	P
Ch 39 2441 MHz	Center Frequency	Fig.18	P
	30 MHz ~ 1 GHz	Fig.19	P
	1 GHz ~ 3 GHz	Fig.20	P
	3 GHz ~ 10 GHz	Fig.21	P
	10 GHz ~ 26 GHz	Fig.22	P
Ch 78 2480 MHz	Center Frequency	Fig.23	P
	30 MHz ~ 1 GHz	Fig.24	P
	1 GHz ~ 3 GHz	Fig.25	P
	3 GHz ~ 10 GHz	Fig.26	P
	10 GHz ~ 26 GHz	Fig.27	P

For π/4 DQPSK

Channel	Frequency Range	Test Results	Conclusion
Ch 0 2402 MHz	Center Frequency	Fig.28	P
	30 MHz ~ 1 GHz	Fig.29	P
	1 GHz ~ 3 GHz	Fig.30	P
	3 GHz ~ 10 GHz	Fig.31	P
	10 GHz ~ 26 GHz	Fig.32	P
Ch 39 2441 MHz	Center Frequency	Fig.33	P
	30 MHz ~ 1 GHz	Fig.34	P
	1 GHz ~ 3 GHz	Fig.35	P
	3 GHz ~ 10 GHz	Fig.36	P
	10 GHz ~ 26 GHz	Fig.37	P
Ch 78 2480 MHz	Center Frequency	Fig.38	P
	30 MHz ~ 1 GHz	Fig.39	P
	1 GHz ~ 3 GHz	Fig.40	P
	3 GHz ~ 10 GHz	Fig.41	P
	10 GHz ~ 26 GHz	Fig.42	P

For 8DPSK

Channel	Frequency Range	Test Results	Conclusion
Ch 0 2402 MHz	Center Frequency	Fig.43	P
	30 MHz ~ 1 GHz	Fig.44	P
	1 GHz ~ 3 GHz	Fig.45	P
	3 GHz ~ 10 GHz	Fig.46	P
	10 GHz ~ 26 GHz	Fig.47	P

©Copyright. All rights reserved by CTTL .

Ch 39 2441 MHz	Center Frequency	Fig.48	P
	30 MHz ~ 1 GHz	Fig.49	P
	1 GHz ~ 3 GHz	Fig.50	P
	3 GHz ~ 10 GHz	Fig.51	P
	10 GHz ~ 26 GHz	Fig.52	P
Ch 78 2480 MHz	Center Frequency	Fig.53	P
	30 MHz ~ 1 GHz	Fig.54	P
	1 GHz ~ 3 GHz	Fig.55	P
	3 GHz ~ 10 GHz	Fig.56	P
	10 GHz ~ 26 GHz	Fig.57	P

Conclusion: PASS

Test graphs as below



Fig.13. Conducted spurious emission: GFSK, Channel 0,2402MHz

©Copyright. All rights reserved by CTTL .



Fig.14. Conducted spurious emission: GFSK, Channel 0, 30MHz - 1GHz



Fig.15. Conducted spurious emission: GFSK, Channel 0, 1GHz - 3GHz

©Copyright. All rights reserved by CTTL .



Fig.16. Conducted spurious emission: GFSK, Channel 0, 3GHz - 10GHz



Fig.17. Conducted spurious emission: GFSK, Channel 0,10GHz - 26GHz

©Copyright. All rights reserved by CTTL .



Fig.18. Conducted spurious emission: GFSK, Channel 39, 2441MHz



Fig.19. Conducted spurious emission: GFSK, Channel 39, 30MHz - 1GHz

©Copyright. All rights reserved by CTTL .



Fig.20. Conducted spurious emission: GFSK, Channel 39, 1GHz – 3GHz



Fig.21. Conducted spurious emission: GFSK, Channel 39, 3GHz – 10GHz

©Copyright. All rights reserved by CTTL .



Fig.22. Conducted spurious emission: GFSK, Channel 39, 10GHz – 26GHz



Fig.23. Conducted spurious emission: GFSK, Channel 78, 2480MHz

©Copyright. All rights reserved by CTTL .



Fig.24. Conducted spurious emission: GFSK, Channel 78, 30MHz - 1GHz



Fig.25. Conducted spurious emission: GFSK, Channel 78, 1GHz - 3GHz

©Copyright. All rights reserved by CTTL .



Fig.26. Conducted spurious emission: GFSK, Channel 78, 3GHz - 10GHz



Fig.27. Conducted spurious emission: GFSK, Channel 78, 10GHz - 26GHz

©Copyright. All rights reserved by CTTL .



Fig.28. Conducted spurious emission: π/4 DQPSK, Channel 0,2402MHz



Fig.29. Conducted spurious emission: π/4 DQPSK, Channel 0, 30MHz - 1GHz

©Copyright. All rights reserved by CTTL .



Fig.30. Conducted spurious emission: π/4 DQPSK, Channel 0, 1GHz - 3GHz



Fig.31. Conducted spurious emission: π/4 DQPSK, Channel 0, 3GHz - 10GHz

©Copyright. All rights reserved by CTTL .



Fig.32. Conducted spurious emission: π/4 DQPSK, Channel 0,10GHz - 26GHz



Fig.33. Conducted spurious emission: π/4 DQPSK, Channel 39, 2441MHz

©Copyright. All rights reserved by CTTL .



Fig.34. Conducted spurious emission: π/4 DQPSK, Channel 39, 30MHz - 1GHz



Fig.35. Conducted spurious emission: π/4 DQPSK, Channel 39, 1GHz - 3GHz

©Copyright. All rights reserved by CTTL .



Fig.36. Conducted spurious emission: π/4 DQPSK, Channel 39, 3GHz - 10GHz



Fig.37. Conducted spurious emission: π/4 DQPSK, Channel 39, 10GHz – 26GHz

©Copyright. All rights reserved by CTTL .



Fig.38. Conducted spurious emission: π/4 DQPSK, Channel 78, 2480MHz



Fig.39. Conducted spurious emission: π/4 DQPSK, Channel 78, 30MHz - 1GHz

©Copyright. All rights reserved by CTTL .



Fig.40. Conducted spurious emission: π/4 DQPSK, Channel 78, 1GHz - 3GHz



Fig.41. Conducted spurious emission: π/4 DQPSK, Channel 78, 3GHz - 10GHz

©Copyright. All rights reserved by CTTL .



Fig.42. Conducted spurious emission: π/4 DQPSK, Channel 78, 10GHz - 26GHz



Fig.43. Conducted spurious emission: 8DPSK, Channel 0,2402MHz

©Copyright. All rights reserved by CTTL .



Fig.44. Conducted spurious emission: 8DPSK, Channel 0, 30MHz - 1GHz



Fig.45. Conducted spurious emission: 8DPSK, Channel 0, 1GHz - 3GHz

©Copyright. All rights reserved by CTTL .



Fig.46. Conducted spurious emission: 8DPSK, Channel 0, 3GHz - 10GHz



Fig.47. Conducted spurious emission: 8DPSK, Channel 0,10GHz - 26GHz

©Copyright. All rights reserved by CTTL .



Fig.48. Conducted spurious emission: 8DPSK, Channel 39, 2441MHz



Fig.49. Conducted spurious emission: 8DPSK, Channel 39, 30MHz - 1GHz

©Copyright. All rights reserved by CTTL .



Fig.50. Conducted spurious emission: 8DPSK, Channel 39, 1GHz - 3GHz



Fig.51. Conducted spurious emission: 8DPSK, Channel 39, 3GHz - 10GHz

©Copyright. All rights reserved by CTTL .



Fig.52. Conducted spurious emission: 8DPSK, Channel 39, 10GHz – 26GHz



Fig.53. Conducted spurious emission: 8DPSK, Channel 78, 2480MHz

©Copyright. All rights reserved by CTTL .



Fig.54. Conducted spurious emission: 8DPSK, Channel 78, 30MHz - 1GHz



Fig.55. Conducted spurious emission: 8DPSK, Channel 78, 1GHz - 3GHz

©Copyright. All rights reserved by CTTL .



Fig.56. Conducted spurious emission: 8DPSK, Channel 78, 3GHz - 10GHz



Fig.57. Conducted spurious emission: 8DPSK, Channel 78, 10GHz - 26GHz

©Copyright. All rights reserved by CTTL .

B.5. Radiated Unwanted Emission

Limits

Measurement Limit

Standard	Limit
FCC 47 CFR Part 15.247, 15.205, 15.209	20dB below peak output power

In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c)).

Limit in restricted band

Frequency (MHz)	Field strength(μV/m)	Measurement distance (m)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30

Frequency of emission (MHz)	Field strength (uV/m)	Field strength (dBuV/m)	Measurement distance (m)
30-88	100	40	3
88-216	150	43.5	3
216-960	200	46	3
Above 960	500	54	3

Note: When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor.

Test setup



Figure B.5.1. Test Site Diagram (9kHz-30MHz)

©Copyright. All rights reserved by CTTL .



Figure B.5.2. Test Site Diagram (30MHz-1GHz)



Figure B.5.3. Test Site Diagram (1GHz-40GHz)

Test Procedures

Radiated unwantedemissions from the EUT were measured according to ANSI C63.10-2013 (ANSI C63.10-2020).

Test setting

Frequency of emission (MHz)	RBW/VBW	Sweep Time(s)
30-1000	100kHz/300kHz	5
1000-3000	1MHz/3MHz	15
3000-18000	1MHz/3MHz	40
18000-26500	1MHz/3MHz	20

Sample Calculation

A "reference path loss" is established and the A_{Rpl} is the attenuation of “reference path loss”, and including the gain of receive antenna, the gain of the preamplifier, the cable loss.

P_{Mea} is the field strength recorded from the instrument.

The measurement results are obtained as described below:

©Copyright. All rights reserved by CTTL .

Result=P_{Mea}+A_{Rpl}=P_{Mea}+CableLoss+Antenna Factor

Test note

1. Investigation has been done on all modes and modulations/data rates. Only the radiated emissions of the configuration that produced the worst case emissions are reported in this section.
2. Spurious emissions for all channels were investigated and almost the same below 1GHz. According to FCC 47 CFR §15.31, emission levels are not report much lower than the limit by over 20dB
3. Measurement frequencies were performed from 9 kHzto the 10th harmonic of highest fundamental frequency or 40GHz, whichever is lower.

Test Result

EUT ID:EUT1

Radiated Spurious Emission

GFSK Ch 0

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17956.000	51.03	-29.40	46.00	34.43	74.00	22.97	V
13591.000	47.69	-31.30	40.80	38.19	74.00	26.31	H
4804.000	46.08	-37.70	33.00	50.78	74.00	27.92	V
12890.500	44.53	-31.50	40.00	36.03	74.00	29.47	H
8911.500	41.67	-33.90	37.70	37.87	74.00	32.33	V
2361.100	52.88	-19.70	28.20	44.38	74.00	21.12	V

GFSK Ch 39

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17963.500	50.46	-29.40	46.00	33.86	74.00	23.54	V
13726.500	47.48	-31.00	41.10	37.38	74.00	26.52	V
4881.500	44.44	-37.50	33.40	48.54	74.00	29.56	H
12844.500	44.17	-31.90	39.90	36.17	74.00	29.83	H
9491.000	42.83	-34.60	37.70	39.73	74.00	31.17	V
7321.000	41.30	-35.40	36.60	40.10	74.00	32.70	V

GFSK Ch 78

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17605.500	50.74	-29.60	45.10	35.14	74.00	23.26	H
14493.500	47.76	-29.70	41.90	35.56	74.00	26.24	H
12989.000	45.00	-31.90	40.10	36.80	74.00	29.00	V

©Copyright. All rights reserved by CTTL .

4960.000	43.26	-37.40	33.60	47.06	74.00	30.74	V
8868.500	42.50	-34.80	37.80	39.50	74.00	31.50	V
2497.100	53.49	-19.70	28.20	44.99	74.00	20.51	V

π/4 DQPSK Ch 0

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17952.000	50.48	-29.40	46.00	33.88	74.00	23.52	V
14182.000	47.88	-30.20	41.70	36.38	74.00	26.12	V
12659.000	44.27	-31.80	39.40	36.67	74.00	29.73	V
4803.500	43.84	-37.70	33.00	48.54	74.00	30.16	H
7268.000	42.27	-35.60	36.40	41.47	74.00	31.73	V
2329.300	53.03	-19.70	28.20	44.53	74.00	20.97	V

π/4 DQPSK Ch 39

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17332.500	50.70	-28.60	43.40	35.90	74.00	23.30	H
13646.000	47.62	-31.30	40.90	38.02	74.00	26.38	H
12659.000	43.86	-31.80	39.40	36.26	74.00	30.14	V
9393.000	42.44	-34.10	37.90	38.64	74.00	31.56	V
7905.000	42.11	-35.20	36.70	40.61	74.00	31.89	V
4881.500	41.95	-37.50	33.40	46.05	74.00	32.05	H

π/4 DQPSK Ch 78

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17569.000	50.76	-29.20	44.90	35.06	74.00	23.24	V
13733.000	47.51	-31.00	41.10	37.41	74.00	26.49	H
12918.500	44.90	-31.50	40.00	36.40	74.00	29.10	V
7416.500	42.66	-35.10	36.60	41.16	74.00	31.34	V
9872.000	42.44	-33.90	37.90	38.44	74.00	31.56	V
2489.900	53.74	-19.70	28.20	45.24	74.00	20.26	V

©Copyright. All rights reserved by CTTL .

8DPSK Ch 0

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17406.500	50.46	-29.50	43.80	36.16	74.00	23.54	V
13676.500	47.38	-31.00	41.00	37.38	74.00	26.62	V
4804.000	45.56	-37.70	33.00	50.26	74.00	28.44	H
12774.500	43.89	-31.50	39.80	35.59	74.00	30.11	V
9439.000	42.03	-33.60	37.90	37.73	74.00	31.97	V
2323.200	53.09	-19.90	28.10	44.89	74.00	20.91	H

8DPSK Ch 39

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17626.000	50.79	-29.50	45.40	34.89	74.00	23.21	H
14208.500	47.36	-30.60	41.80	36.26	74.00	26.64	H
4882.000	45.20	-37.50	33.40	49.30	74.00	28.80	H
12787.000	44.22	-31.50	39.80	35.92	74.00	29.78	V
9314.500	42.21	-34.10	37.80	38.51	74.00	31.79	V
7326.500	41.69	-35.40	36.60	40.49	74.00	32.31	V

8DPSK Ch 78

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17951.500	51.02	-29.40	46.00	34.42	74.00	22.98	V
13583.500	47.47	-31.30	40.80	37.97	74.00	26.53	H
12666.500	44.56	-31.80	39.40	36.96	74.00	29.44	H
9727.000	42.33	-34.50	37.80	39.03	74.00	31.67	V
7332.000	42.01	-35.90	36.60	41.31	74.00	31.99	V
2486.900	53.89	-19.70	28.20	45.39	74.00	20.11	V

©Copyright. All rights reserved by CTTL .

Average Measurement results

GFSK Ch 0

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
4804.000	43.27	-37.70	33.00	47.97	54.00	10.73	V
17603.000	41.13	-29.60	45.10	25.53	54.00	12.87	V
13721.000	37.93	-31.00	41.10	27.83	54.00	16.07	H
12903.000	34.09	-31.50	40.00	25.59	54.00	19.91	V
9200.000	32.31	-34.70	37.70	29.31	54.00	21.69	V
2375.900	41.04	-19.70	28.20	32.54	54.00	12.96	H

GFSK Ch 39

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
4881.500	41.29	-37.50	33.40	45.39	54.00	12.71	H
17946.500	41.19	-29.40	46.00	24.59	54.00	12.81	H
13747.000	37.72	-31.00	41.10	27.62	54.00	16.28	V
12998.000	34.69	-31.90	40.10	26.49	54.00	19.31	H
9403.000	33.43	-34.10	37.90	29.63	54.00	20.57	V
7314.500	31.98	-35.40	36.60	30.78	54.00	22.02	V

GFSK Ch 78

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17960.000	41.11	-29.40	46.00	24.51	54.00	12.89	V
4960.000	39.10	-37.40	33.60	42.90	54.00	14.90	V
13692.500	37.87	-31.00	41.00	27.87	54.00	16.13	H
12758.500	34.87	-31.80	39.60	26.97	54.00	19.13	V
7325.500	32.79	-35.40	36.60	31.59	54.00	21.21	V
2486.400	41.77	-19.70	28.20	33.27	54.00	12.23	V

©Copyright. All rights reserved by CTTL .

π/4 DQPSK Ch 0

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17999.000	41.14	-29.40	46.00	24.54	54.00	12.86	H
4803.500	38.81	-37.70	33.00	43.51	54.00	15.19	H
13724.500	37.67	-31.00	41.10	27.57	54.00	16.33	V
12772.500	34.61	-31.50	39.80	26.31	54.00	19.39	V
9424.500	32.64	-33.60	37.90	28.34	54.00	21.36	V
2388.200	41.22	-19.70	28.20	32.72	54.00	12.78	V

π/4 DQPSK Ch 39

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17628.500	41.28	-29.50	45.40	25.38	54.00	12.72	V
13781.500	37.65	-30.90	41.20	27.35	54.00	16.35	H
4881.500	35.78	-37.50	33.40	39.88	54.00	18.22	H
12640.000	34.53	-31.80	39.40	26.93	54.00	19.47	V
9925.500	32.52	-33.80	37.90	28.42	54.00	21.48	V
7162.000	32.50	-35.60	35.90	32.20	54.00	21.50	V

π/4 DQPSK Ch 78

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17594.000	41.18	-29.60	45.10	25.58	54.00	12.82	H
13684.500	38.05	-31.00	41.00	28.05	54.00	15.95	V
4959.500	34.55	-37.40	33.60	38.35	54.00	19.45	H
12760.500	34.42	-31.80	39.60	26.52	54.00	19.58	V
9398.500	32.87	-34.10	37.90	29.07	54.00	21.13	V
2485.800	41.93	-19.70	28.20	33.43	54.00	12.07	V

©Copyright. All rights reserved by CTTL .

8DPSK Ch 0

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17942.000	41.21	-29.40	46.00	24.61	54.00	12.79	H
4803.500	38.43	-37.70	33.00	43.13	54.00	15.57	H
14168.000	37.53	-30.20	41.70	26.03	54.00	16.47	V
12778.000	34.49	-31.50	39.80	26.19	54.00	19.51	V
9424.500	32.24	-33.60	37.90	27.94	54.00	21.76	V
2380.400	41.21	-19.80	28.20	32.81	54.00	12.79	V

8DPSK Ch 39

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17601.000	41.12	-29.60	45.10	25.52	54.00	12.88	V
4882.000	38.05	-37.50	33.40	42.15	54.00	15.95	H
13678.500	37.73	-31.00	41.00	27.73	54.00	16.27	V
12647.500	34.68	-31.80	39.40	27.08	54.00	19.32	V
9227.000	33.39	-34.30	37.60	30.09	54.00	20.61	V
7311.500	32.80	-35.40	36.60	31.60	54.00	21.20	V

8DPSK Ch 78

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17606.500	41.17	-29.60	45.10	25.57	54.00	12.83	V
13681.000	37.88	-31.00	41.00	27.88	54.00	16.12	H
11768.500	34.92	-32.90	39.20	28.62	54.00	19.08	H
4960.000	34.19	-37.40	33.60	37.99	54.00	19.81	H
8990.500	32.91	-34.70	37.70	29.91	54.00	21.09	V
2494.000	42.18	-19.70	28.20	33.68	54.00	11.82	V

Conclusion: Pass

Note: the spurious emission above 18G is noise only and did not show on the report.

Band edge compliance

Mode	Channel	Frequency Range	Test Results	Conclusion
GFSK	0	2.31GHz ~2.43GHz	Fig.58	P
	78	2.45GHz ~2.5GHz	Fig.59	P

©Copyright. All rights reserved by CTTL .

Mode	Channel	Frequency Range	Test Results	Conclusion
π/4 DQPSK	0	2.31GHz ~2.43GHz	Fig.60	P
	78	2.45GHz ~2.5GHz	Fig.61	P

Mode	Channel	Frequency Range	Test Results	Conclusion
8DPSK	0	2.31GHz ~2.43GHz	Fig.62	P
	78	2.45GHz ~2.5GHz	Fig.63	P

Conclusion: PASS

Test graphs as below



Fig.58. Frequency Band Edges: GFSK, Channel 0, Hopping Off, 2.31 GHz – 2.45GHz



Fig.59. Frequency Band Edges: GFSK, Channel 78, Hopping Off, ch11, 2.45 GHz - 2.50GHz

©Copyright. All rights reserved by CTTL .



Fig.60. Frequency Band Edges: π/4 DQPSK, Channel 0, Hopping Off, 2.31 GHz - 2.45GHz



Fig.61. Frequency Band Edges: π/4 DQPSK, Channel 78, Hopping Off, 2.45 GHz - 2.50GHz



Fig.62. Frequency Band Edges: 8DPSK, Channel 0, 2.31 GHz - 2.45GHz

©Copyright. All rights reserved by CTTL .



Fig.63. Frequency Band Edges: 8DPSK, Channel 78, 2.45 GHz - 2.50GHz

©Copyright. All rights reserved by CTTL .

B.6. Time of Occupancy (Dwell Time)

Method of Measurement: See ANSI C63.10-clause 7.8.4

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:

- Span = zero span, centered on a hopping channel
- RBW = 1 MHz
- VBW ≥ RBW
- Sweep = as necessary to capture the entire dwell time per hopping channel
- Detector function = peak
- Trace = max hold

Measure a pulse time in time domain at middle frequency and then count the hopping number in 31.6s(which equals with 0.4 multiply 79) of middle frequency ,then multiply the pulse time and hopping number and record them.

Measurement Limit:

Standard	Limit (ms)
FCC 47 CFR Part 15.247(a) (1)(iii)	< 400

Measurement Result:

For GFSK

Channel	Packet	Pulse time (ms)		Number of Transmissions		Dwell Time (ms)	Conclusion
39	DH1	Fig.64	0.38	Fig.65	319	121.22	P
	DH3	Fig.66	1.64	Fig.67	119	195.16	P
	DH5	Fig.68	2.89	Fig.69	69	199.41	P

For π/4 DQPSK

Channel	Packet	Pulse time (ms)		Number of Transmissions		Dwell Time (ms)	Conclusion
39	2DH1	Fig.70	0.39	Fig.71	317	123.63	P
	2DH3	Fig.72	1.64	Fig.73	111	182.04	P
	2DH5	Fig.74	2.89	Fig.75	63	182.07	P

©Copyright. All rights reserved by CTTL .

For 8DPSK

Channel	Packet	Pulse time (ms)		Number of Transmissions		Dwell Time (ms)	Conclusion
39	3DH1	Fig.76	0.39	Fig.77	318	124.02	P
	3DH3	Fig.78	1.64	Fig.79	109	178.76	P
	3DH5	Fig.80	2.89	Fig.81	61	176.29	P

Conclusion: PASS

Test graphs as below:



Fig.64. Time of occupancy (Dwell Time): Channel 39, Packet DH1

©Copyright. All rights reserved by CTTL .



Fig.65. Number of Transmissions Measurement:Channel 39,Packet DH1



Fig.66. Time of occupancy (Dwell Time): Channel 39, Packet DH3

©Copyright. All rights reserved by CTTL .



Fig.67. Number of Transmissions Measurement:Channel 39,Packet DH3



Fig.68. Time of occupancy (Dwell Time): Channel 39, Packet DH5

©Copyright. All rights reserved by CTTL .



Fig.69. Number of Transmissions Measurement:Channel 39,Packet DH5



Fig.70. Time of occupancy (Dwell Time): Channel 39, Packet 2-DH1

©Copyright. All rights reserved by CTTL .



Fig.71. Number of Transmissions Measurement:Channel 39,Packet 2-DH1



Fig.72. Time of occupancy (Dwell Time): Channel 39, Packet 2-DH3

©Copyright. All rights reserved by CTTL .



Fig.73. Number of Transmissions Measurement:Channel 39,Packet 2-DH3



Fig.74. Time of occupancy (Dwell Time): Channel 39, Packet 2-DH5

©Copyright. All rights reserved by CTTL .



Fig.75. Number of Transmissions Measurement:Channel 39,Packet 2-DH5



Fig.76. Time of occupancy (Dwell Time): Channel 39, Packet 3-DH1

©Copyright. All rights reserved by CTTL .



Fig.77. Number of Transmissions Measurement:Channel 39,Packet 3-DH1



Fig.78. Time of occupancy (Dwell Time): Channel 39, Packet 3-DH3

©Copyright. All rights reserved by CTTL .



Fig.79. Number of Transmissions Measurement:Channel 39,Packet 3-DH3



Fig.80. Time of occupancy (Dwell Time): Channel 39, Packet 3-DH5

©Copyright. All rights reserved by CTTL .



Fig.81. Number of Transmissions Measurement:Channel 39,Packet 3-DH5

©Copyright. All rights reserved by CTTL .

B.7. 20dB Bandwidth

Method of Measurement: See ANSI C63.10-clause 6.9.2

Measurement Procedure - Unwanted Emissions

1. Set RBW = 30kHz.

2. Set VBW = 100 kHz.

3. Set span to 3MHz

4. Detector = peak.

5. Trace Mode = max hold.

6. Sweep = auto couple.

7. Allow the trace to stabilize (this may take some time, depending on the extent of the span).

Measurement Limit:

Standard	Limit
FCC 47 CFR Part 15.247(a)(1)	NA *

Use NdB Down function of the SA to measure the 20dB Bandwidth

* Comment: This test case is not required according to the latest FCC 47 CFR Part 15.247. But the test results are necessary for "carrier frequency separation" test case, in Annex A.8.

Measurement Results:

For GFSK

Channel	20dB Bandwidth (kHz)		Conclusion
0	Fig.82	939.00	NA
39	Fig.83	939.00	NA
78	Fig.84	936.75	NA

Forπ/4 DQPSK

Channel	20dB Bandwidth (kHz)		Conclusion
0	Fig.85	1279.50	NA
39	Fig.86	1289.25	NA
78	Fig.87	1276.50	NA

For 8DPSK

Channel	20dB Bandwidth (kHz)		Conclusion
0	Fig.88	1298.25	NA
39	Fig.89	1296.75	NA
78	Fig.90	1296.75	NA

Conclusion: NA

Test graphs as below:

©Copyright. All rights reserved by CTTL .



Fig.82. 20dB Bandwidth: GFSK, Channel 0



Fig.83. 20dB Bandwidth: GFSK, Channel 39

©Copyright. All rights reserved by CTTL .



Fig.84. 20dB Bandwidth: GFSK, Channel 78



Fig.85. 20dB Bandwidth: π/4 DQPSK, Channel 0

©Copyright. All rights reserved by CTTL .



Fig.86. 20dB Bandwidth: π/4 DQPSK, Channel 39



Fig.87. 20dB Bandwidth: π/4 DQPSK, Channel 78

©Copyright. All rights reserved by CTTL .



Fig.88. 20dB Bandwidth: 8DPSK, Channel 0



Fig.89. 20dB Bandwidth: 8DPSK, Channel 39

©Copyright. All rights reserved by CTTL .



Fig.90. 20dB Bandwidth: 8DPSK, Channel 78

©Copyright. All rights reserved by CTTL .

B.8. Carrier Frequency Separation

Method of Measurement: See ANSI C63.10-clause 7.8.2

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:

- Span = 3MHz
- RBW=300kHz
- VBW=300kHz
- Sweep = auto
- Detector function = peak
- Trace = max hold
- Allow the trace to stabilize

Search the peak marks of the middle frequency and adjacent channel, then record the separation between them.

＊Comment: This limit should be over 25 kHz or (2/3) * 20dB bandwidth, whichever is greater.

Measurement Limit:

Standard	Limit(kHz)
FCC 47 CFR Part 15.247(a)(1)	over 25 kHz or (2/3) * 20dB bandwidth

Measurement Result:

For GFSK

Channel	Carrier frequency separation (kHz)		Conclusion
39	Fig.91	1008.00	P

For π/4 DQPSK

Channel	Carrier frequency separation (kHz)		Conclusion
39	Fig.92	1024.50	P

For 8DPSK

Channel	Carrier frequency separation (kHz)		Conclusion
39	Fig.93	996.00	P

Conclusion: PASS

Test graphs as below:

©Copyright. All rights reserved by CTTL .



Fig.91. Carrier frequency separation measurement: GFSK, Channel 39



Fig.92. Carrier frequency separation measurement: π/4 DQPSK, Channel 39

©Copyright. All rights reserved by CTTL .



Fig.93. Carrier frequency separation measurement: 8DPSK, Channel 39

©Copyright. All rights reserved by CTTL .

B.9. Number of Hopping Channels

Method of Measurement: See ANSI C63.10-clause 7.8.3

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:

- Span = the frequency band of operation
- RBW = 500kHz
- VBW = 500kHz
- Sweep = auto
- Detector function = peak
- Trace = max hold
- Allow the trace to stabilize

It might prove necessary to break the span up into subranges to show clearly all of the hopping frequencies. Compliance of an EUT with the appropriate regulatory limit shall be determined for the number of hopping channels. A plot of the data shall be included in the test report.

Measurement Limit:

Standard	Limit
FCC 47 CFR Part 15.247(a) (1)(iii)	At least 15 non-overlapping channels

Measurement Result:

For GFSK

Channel	Number of hopping channels		Conclusion
0~39	Fig.94	79	P
40~78	Fig.95		

Forπ/4 DQPSK

Channel	Number of hopping channels		Conclusion
0~39	Fig.96	79	P
40~78	Fig.97		

For 8DPSK

Channel	Number of hopping channels		Conclusion
0~39	Fig.98	79	P
40~78	Fig.99		

Conclusion: PASS

Test graphs as below:

©Copyright. All rights reserved by CTTL .



Fig.94. Number of hopping frequencies: GFSK, Channel 0 - 39



Fig.95. Number of hopping frequencies: GFSK, Channel 40 - 78

©Copyright. All rights reserved by CTTL .



Fig.96. Number of hopping frequencies: π/4 DQPSK, Channel 0 - 39



Fig.97. Number of hopping frequencies: π/4 DQPSK, Channel 40 - 78

©Copyright. All rights reserved by CTTL .



Fig.98. Number of hopping frequencies: 8DPSK, Channel 0 - 39



Fig.99. Number of hopping frequencies: 8DPSK, Channel 40 - 78

©Copyright. All rights reserved by CTTL .

B.10. AC Powerline Conducted Emission

Summary

All AC line conducted spurious emissions are measured with a receiver connected to a grounded LISN while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates and modes were investigated for conducted spurious emissions. Only the conducted emissions of the configuration that produced the worst case emissions are reported in this section

Method of Measurement:

See Clause 6.2 of ANSI C63.10 specifically.

See Clause 4 and Clause 5 of ANSI C63.10 generally.

The conducted emissions from the AC port of the EUT are measured in a shielding room. The EUT is connected to a Line Impedance Stabilization Network (LISN). An overview sweep with peak detection was performed. The measurements were performed with a quasi-peak detector and if required, an average detector.

The conducted emission measurements were made with the following detector of the test receiver:Quasi-Peak / Average Detector.

The measurement bandwidth is:

Frequency of Emission (MHz)	RBW/IF bandwidth
0.15-30	9kHz

Test Condition:

Voltage（V）	Frequency（Hz）
120	60

Test setup



©Copyright. All rights reserved by CTTL .

Measurement Result and limit:

Bluetooth (Quasi-peak Limit)

Frequency range (MHz)	Quasi-peak Limit (dBμV)	Result (dBμV)		Conclusion
		With charger		
		bluetooth	Idle	
0.15 to 0.5	66 to 56	Fig.B.10.1	Fig.B.10.2	P
0.5 to 5	56			
5 to 30	60			
NOTE: The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz.				

Bluetooth (Average Limit)

Frequency range (MHz)	Average Limit (dBμV)	Result (dBμV)		Conclusion
		With charger		
		bluetooth	Idle	
0.15 to 0.5	56 to 46	Fig.B.10.1	Fig.B.10.2	P
0.5 to 5	46			
5 to 30	50			
NOTE: The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz.				

Conclusion: Pass

Test graphs as below:

©Copyright. All rights reserved by CTTL .



Fig.B.10.1 AC Powerline Conducted Emission-bluetooth

Note: The graphic result above is the maximum of the measurements for both phase line and neutral line.

Final Result 1

Frequency (MHz)	QuasiPeak (dBµV)	Meas. Time	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)	Comment
0.414000	**39.9**	**2000.0**	**9.000**	**On**	**L1**	**20.0**	**17.6**	**57.6**	
0.622000	**30.3**	**2000.0**	**9.000**	**On**	**L1**	**20.0**	**25.7**	**56.0**	
0.842000	**30.4**	**2000.0**	**9.000**	**On**	**L1**	**19.9**	**25.6**	**56.0**	
1.650000	**25.8**	**2000.0**	**9.000**	**On**	**L1**	**19.8**	**30.2**	**56.0**	
3.226000	**24.7**	**2000.0**	**9.000**	**On**	**L1**	**19.8**	**31.3**	**56.0**	
4.446000	**23.0**	**2000.0**	**9.000**	**On**	**L1**	**19.8**	**33.0**	**56.0**	

Final Result 2

Frequency (MHz)	CAverage(dBµV)	Meas. Time	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)	Comment
0.414000	**33.3**	**2000.0**	**9.000**	**On**	**L1**	**20.0**	**14.3**	**47.6**	
0.622000	**23.8**	**2000.0**	**9.000**	**On**	**L1**	**20.0**	**22.2**	**46.0**	
0.842000	**22.7**	**2000.0**	**9.000**	**On**	**L1**	**19.9**	**23.3**	**46.0**	
1.678000	**19.0**	**2000.0**	**9.000**	**On**	**L1**	**19.8**	**27.0**	**46.0**	
2.386000	**17.7**	**2000.0**	**9.000**	**On**	**L1**	**19.8**	**28.3**	**46.0**	
4.738000	**16.5**	**2000.0**	**9.000**	**On**	**L1**	**19.8**	**29.6**	**46.0**	

©Copyright. All rights reserved by CTTL .



Fig.B.10.2 AC Powerline Conducted Emission-Idle

Note: The graphic result above is the maximum of the measurements for both phase line and neutral line.

Final Result 1

Frequency (MHz)	QuasiPeak (dBµV)	Meas. Time	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)	Comment
0.154000	**33.8**	**2000.0**	**9.000**	**On**	**N**	**20.0**	**32.0**	**65.8**	
0.418000	**40.4**	**2000.0**	**9.000**	**On**	**L1**	**20.0**	**17.1**	**57.5**	
0.622000	**30.3**	**2000.0**	**9.000**	**On**	**L1**	**20.0**	**25.7**	**56.0**	
0.846000	**29.8**	**2000.0**	**9.000**	**On**	**L1**	**19.9**	**26.2**	**56.0**	
1.654000	**25.8**	**2000.0**	**9.000**	**On**	**L1**	**19.8**	**30.2**	**56.0**	
2.386000	**24.6**	**2000.0**	**9.000**	**On**	**L1**	**19.8**	**31.4**	**56.0**	

Final Result 2

Frequency (MHz)	CAverage (dBµV)	Meas. Time	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)	Comment
0.418000	**34.0**	**2000.0**	**9.000**	**On**	**L1**	**20.0**	**13.5**	**47.5**	
0.650000	**21.9**	**2000.0**	**9.000**	**On**	**L1**	**20.0**	**24.1**	**46.0**	
0.830000	**23.2**	**2000.0**	**9.000**	**On**	**L1**	**19.9**	**22.8**	**46.0**	
1.642000	**19.6**	**2000.0**	**9.000**	**On**	**L1**	**19.8**	**26.4**	**46.0**	
2.398000	**18.1**	**2000.0**	**9.000**	**On**	**L1**	**19.8**	**27.9**	**46.0**	
3.970000	**17.4**	**2000.0**	**9.000**	**On**	**L1**	**19.8**	**28.6**	**46.0**	

©Copyright. All rights reserved by CTTL .

B.11.Antenna Requirement

The antenna of the device is permanently attached. There are no provisions for connection to an external antenna.
The unit complies with the requirement of FCC Part 15.203.

©Copyright. All rights reserved by CTTL .

ANNEX C: Accreditation Certificate

Accredited Laboratory

A2LA has accredited

TELECOMMUNICATION TECHNOLOGY LABS, CAICT

Beijing, People's Republic of China

for technical competence in the field of

Electrical Testing

This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2017 *General requirements for the competence of testing and calibration laboratories*. This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (*refer to joint ISO-ILAC-IAF Communiqué dated April 2017*).

Presented this 23rd day of July 2024.

Mr. Trace McInturff, Vice President, Accreditation Services
For the Accreditation Council
Certificate Number 7049.01
Valid to July 31, 2026

For the tests to which this accreditation applies, please refer to the laboratory's Electrical Scope of Accreditation.

*****END OF REPORT*****

©Copyright. All rights reserved by CTTL .