

FCC §15.247 (i), §2.1091 – RF Exposure

FCC ID: 2AMA8-T8PLUS-2**Applied procedures / limit**

According to FCC §15.247(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Limits for Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842 / f	4.89 / f	(900 / f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-100,000			5	6

Note: f is frequency in MHz

* = Power density limit is applicable at frequencies greater than 100 MHz

Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-100,000			1.0	30

Note: f = frequency in MHz

* = Plane-wave equivalent power density

MPE PREDICTION

Predication of MPE limit at a given distance, Equation from OET Bulletin 65, Edition 97-01

$$S = PG/4\pi R^2$$

Where: S = power density

P = power input to antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

TEST RESULTS**2.4G WIFI**

EUT Set Mode	CH	Result(dBm)	Total Power (dBm)	Limit	Conclusion
		Peak			
IEEE 802.11B	CH 1	14.71	/	30dBm	PASS
	CH 6	14.55	/	30dBm	PASS
	CH 11	13.92	/	30dBm	PASS
IEEE 802.11G	CH 1	13.46	/	30dBm	PASS
	CH 6	13.25	/	30dBm	PASS
	CH 11	13.87	/	30dBm	PASS
IEEE 802.11N20	CH 1	12.24	/	30dBm	PASS
	CH 6	12.17	/	30dBm	PASS
	CH 11	12.18	/	30dBm	PASS
IEEE 802.11N40	CH 3	12.46	/	30dBm	PASS
	CH 6	12.15	/	30dBm	PASS
	CH 9	12.37	/	30dBm	PASS

Mode	Range	Maximum peak output power (dBm)	Output power (mW)	Antenna Gain (numeric)	Power Density (S) (mW/ cm ²)	Limit of Power Density (S) (mW/ cm ²)	Result
802.11b	14~16	16	39.811	4.0(2.512)	0.01989	1	Pass
802.11g	13~15	15	31.623	4.0(2.512)	0.01580	1	Pass
802.11n-HT20	12~14	14	25.119	4.0(2.512)	0.01255	1	Pass
802.11n-HT40	12~14	14	25.119	4.0(2.512)	0.01255	1	Pass

Conclusion: No SAR is required.