

**Shenzhen Global Test Service Co.,Ltd.**

No.7-101 and 8A-104, Building 7 and 8, DCC Cultural and Creative Garden, No.98, Pingxin North Road, Shangmugu Community, Pinghu Street, Longgang District, Shenzhen, Guangdong


**FCC PART 15 SUBPART C TEST REPORT****FCC PART 15.247****Report Reference No.**.....: **GTS20201022015-1-2****FCC ID**.....: **2AMA8-UPRO**

Compiled by

( position+printed name+signature) .: File administrators Jimmy Wang

Supervised by

( position+printed name+signature) .: Test Engineer Aaron Tan



Approved by

( position+printed name+signature) .: Manager Jason Hu

Date of issue .....: Oct.25, 2020

**Representative Laboratory Name.:** **Shenzhen Global Test Service Co.,Ltd.****Address**.....: No.7-101 and 8A-104, Building 7 and 8, DCC Cultural and Creative Garden, No.98, Pingxin North Road, Shangmugu Community, Pinghu Street, Longgang District, Shenzhen, Guangdong, China**Applicant's name**.....: **Shen Zhen Zoomtak Electronics Co., Ltd****Address** .....: B4 Building, Anle Industrial Zone, No.172 Hangcheng Blvd, Baoan Xixiang District, Shenzhen, 518126 China**Test specification** .....**Standard**.....: **FCC Part 15.247****TRF Originator**.....: Shenzhen Global Test Service Co.,Ltd.**Shenzhen Global Test Service Co.,Ltd. All rights reserved.**

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen Global Test Service Co.,Ltd. is acknowledged as copyright owner and source of the material. Shenzhen Global Test Service Co.,Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

**Test item description** .....: media player

Trade Mark .....: Zoomtak

Manufacturer .....: Shen Zhen Zoomtak Electronics Co., Ltd

Model/Type reference .....: Uplus

Listed Models .....: U pro, mySDATV M20, Umax, Prodigy Elite, miracle

Modulation Type .....: CCK/DSSS/ OFDM

Operation Frequency.....: From 2412 - 2462MHz

Rating .....: DC 5V From External circuit

Result .....: **PASS**

**TEST REPORT**

|                                             |                               |
|---------------------------------------------|-------------------------------|
| <b>Test Report No. :</b> GTS20201022015-1-2 | Oct.25, 2020<br>Date of issue |
|---------------------------------------------|-------------------------------|

Equipment under Test : media player

Model /Type : UPlus

Listed Models : U pro,mySDATV M20,Umax,Prodigy Elite,miracle

**Applicant** : **Shen Zhen Zoomtak Electronics Co., Ltd**

Address : B4 Building,Anle Industrial Zone,No.172 Hangcheng Blvd,  
Baoan Xixiang District,Shenzhen,518126 China

**Manufacturer** : **Shen Zhen Zoomtak Electronics Co., Ltd**

Address : B4 Building,Anle Industrial Zone,No.172 Hangcheng Blvd,  
Baoan Xixiang District,Shenzhen,518126 China

|                     |             |
|---------------------|-------------|
| <b>Test Result:</b> | <b>PASS</b> |
|---------------------|-------------|

The test report merely corresponds to the test sample.  
It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

## Contents

|                 |                                                     |                  |
|-----------------|-----------------------------------------------------|------------------|
| <b><u>1</u></b> | <b><u>TEST STANDARDS .....</u></b>                  | <b><u>4</u></b>  |
| <b><u>2</u></b> | <b><u>SUMMARY .....</u></b>                         | <b><u>5</u></b>  |
| 2.1             | General Remarks                                     | 5                |
| 2.2             | Product Description                                 | 5                |
| 2.3             | Equipment Under Test                                | 5                |
| 2.4             | Short description of the Equipment under Test (EUT) | 5                |
| 2.5             | EUT operation mode                                  | 6                |
| 2.6             | Block Diagram of Test Setup                         | 6                |
| 2.7             | Related Submittal(s) / Grant (s)                    | 6                |
| 2.8             | Modifications                                       | 6                |
| <b><u>3</u></b> | <b><u>TEST ENVIRONMENT .....</u></b>                | <b><u>7</u></b>  |
| 3.1             | Address of the test laboratory                      | 7                |
| 3.2             | Test Facility                                       | 7                |
| 3.3             | Environmental conditions                            | 7                |
| 3.4             | Test Description                                    | 8                |
| 3.5             | Statement of the measurement uncertainty            | 8                |
| 3.6             | Equipments Used during the Test                     | 9                |
| <b><u>4</u></b> | <b><u>TEST CONDITIONS AND RESULTS.....</u></b>      | <b><u>10</u></b> |
| 4.1             | AC Power Conducted Emission                         | 10               |
| 4.2             | Radiated Emission                                   | 13               |
| 4.3             | Maximum Conducted Output Power                      | 19               |
| 4.4             | Power Spectral Density                              | 20               |
| 4.5             | 6dB Bandwidth                                       | 23               |
| 4.6             | Out-of-band Emissions                               | 26               |
| 4.7             | Antenna Requirement                                 | 33               |
| <b><u>5</u></b> | <b><u>TEST SETUP PHOTOS OF THE EUT .....</u></b>    | <b><u>34</u></b> |
| <b><u>6</u></b> | <b><u>PHOTOS OF THE EUT .....</u></b>               | <b><u>35</u></b> |

## **1 TEST STANDARDS**

The tests were performed according to following standards:

[FCC Rules Part 15.247](#): Frequency Hopping, Direct Spread Spectrum and Hybrid Systems that are in operation within the bands of 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz.

[ANSI C63.10-2013](#): American National Standard for Testing Unlicensed Wireless Devices

[KDB558074 D01 v05r02](#): Guidance for Compliance Measurements on Digital Transmission Systems (DTS) ,Frequency Hopping Spread Spectrum System(HFSS), and Hybrid System Devices Operating Under §15.247 of The FCC rules.

## 2 SUMMARY

### 2.1 General Remarks

|                                |   |              |
|--------------------------------|---|--------------|
| Date of receipt of test sample | : | Sep.18,2020  |
|                                |   |              |
| Testing commenced on           | : | Sep.19,2020  |
|                                |   |              |
| Testing concluded on           | : | Oct.25, 2020 |

### 2.2 Product Description

|                       |                                                                                |
|-----------------------|--------------------------------------------------------------------------------|
| Product Name:         | media player                                                                   |
| Model/Type reference: | Uplus                                                                          |
| Power supply:         | DC 5V From External circuit                                                    |
| Adapter:              | Mode:QFD12W-005300<br>Input:AC100-240V-50/60Hz, 0.4A<br>Output:DC 5V,3A        |
| testing sample ID:    | GTS20201022015-1-1#(Engineer sample)<br>GTS20201022015-1-2#(Normal sample)     |
| Hardware version:     | U PLUS V1.1                                                                    |
| Software version:     | V1.0                                                                           |
| <b>WIFI :</b>         |                                                                                |
| Supported type:       | 802.11b/802.11g/802.11n(H20) /802.11n(H40):                                    |
| Modulation:           | 802.11b: DSSS<br>802.11g/802.11n(H20) /802.11n(H40): OFDM                      |
| Operation frequency:  | 802.11b/802.11g/802.11n(H20): 2412MHz~2462MHz<br>802.11n(H40): 2422MHz~2452MHz |
| Channel number:       | 802.11b/802.11g/802.11n(H20): 11<br>802.11b/802.11g/802.11n(H40): 7            |
| Channel separation:   | 5MHz                                                                           |
| Antenna type:         | Internal antenna                                                               |
| Antenna gain:         | 0 dBi                                                                          |

### 2.3 Equipment Under Test

#### Power supply system utilised

|                      |   |                                                                   |                                   |
|----------------------|---|-------------------------------------------------------------------|-----------------------------------|
| Power supply voltage | : | <input type="radio"/> 230V / 50 Hz                                | <input type="radio"/> 120V / 60Hz |
|                      |   | <input type="radio"/> 12 V DC                                     | <input type="radio"/> 24 V DC     |
|                      |   | <input checked="" type="radio"/> Other (specified in blank below) |                                   |

DC 5V From external circuit

### 2.4 Short description of the Equipment under Test (EUT)

This is a SimCam Baby.

For more details, refer to the user's manual of the EUT.


## 2.5 EUT operation mode

The application provider specific test software(AT command) to control sample in continuous TX and RX (Duty Cycle >98%) for testing meet KDB558074 test requirement.

IEEE 802.11b/g/n: Thirteen channels are provided to the EUT.

| Channel | Frequency(MHz) | Channel | Frequency(MHz) |
|---------|----------------|---------|----------------|
| 1       | 2412           | 8       | 2447           |
| 2       | 2417           | 9       | 2452           |
| 3       | 2422           | 10      | 2457           |
| 4       | 2427           | 11      | 2462           |
| 5       | 2432           |         |                |
| 6       | 2437           |         |                |
| 7       | 2442           |         |                |

## 2.6 Block Diagram of Test Setup



## 2.7 Related Submittal(s) / Grant (s)

This submittal(s) (test report) is intended for **FCC ID:2AMA8-UPRO** filing to comply with Section 15.247 of the FCC Part 15, Subpart C Rules.

## 2.8 Modifications

No modifications were implemented to meet testing criteria.

### 3 TEST ENVIRONMENT

#### 3.1 Address of the test laboratory

**Shenzhen Global Test Service Co.,Ltd.**

No.7-101 and 8A-104, Building 7 and 8, DCC Cultural and Creative Garden, No.98, Pingxin North Road, Shangmugu Community, Pinghu Street, Longgang District, Shenzhen, Guangdong

The 3m-Semi anechoic test site fulfils CISPR 16-1-4 according to ANSI C63.4:2014 and CISPR 16-1-4:2010 SVSWR requirement for radiated emission above 1GHz.

#### 3.2 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

**FCC-Registration No.: 165725**

Shenzhen Global Test Service Co.,Ltd EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files.

**A2LA-Lab Cert. No.: 4758.01**

Shenzhen Global Test Service Co.,Ltd. EMC Laboratory has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025: 2005 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

**CNAS-Lab Code: L8169**

Shenzhen Global Test Service Co.,Ltd. has been assessed and proved to be in compliance with CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC 17025: 2005 General Requirements) for the Competence of Testing and Calibration Laboratories. Date of Registration: Dec. 11, 2015. Valid time is until Dec. 10, 2018.

#### 3.3 Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Radiated Emission:

|                       |              |
|-----------------------|--------------|
| Temperature:          | 25 ° C       |
|                       |              |
| Humidity:             | 45 %         |
|                       |              |
| Atmospheric pressure: | 950-1050mbar |

Conducted testing:

|                       |              |
|-----------------------|--------------|
| Temperature:          | 25 ° C       |
|                       |              |
| Humidity:             | 44 %         |
|                       |              |
| Atmospheric pressure: | 950-1050mbar |

AC Power Conducted Emission

|                       |              |
|-----------------------|--------------|
| Temperature:          | 24 ° C       |
|                       |              |
| Humidity:             | 44 %         |
|                       |              |
| Atmospheric pressure: | 950-1050mbar |

### 3.4 Test Description

|                                 |                                |      |
|---------------------------------|--------------------------------|------|
| FCC PART 15.247                 |                                |      |
| FCC Part 15.207                 | AC Power Conducted Emission    | PASS |
| FCC Part 15.247(a)(2)           | 6dB Bandwidth                  | PASS |
| FCC Part 15.247(d)              | Spurious RF Conducted Emission | PASS |
| FCC Part 15.247(b)              | Maximum Conducted Output Power | PASS |
| FCC Part 15.247(e)              | Power Spectral Density         | PASS |
| FCC Part 15.109/ 15.205/ 15.209 | Radiated Emissions             | PASS |
| FCC Part 15.247(d)              | Band Edge                      | PASS |
| FCC Part 15.203/15.247 (b)      | Antenna Requirement            | PASS |

#### Data Rate Used:

Preliminary tests were performed in different data rate to find the worst radiated emission. The data rate shown in the table below is the worst-case rate with respect to the specific test item. Investigation has been done on all the possible configurations for searching the worst cases. The following table is a list of the test modes shown in this test report.

| Test Items                                                                                                                                                                                           | Mode            | Data Rate | Channel |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------|-----------|---------|
| Maximum Peak Conducted Output Power<br>Power Spectral Density<br>6dB Bandwidth<br>Spurious RF conducted emission<br>Radiated Emission 9KHz~1GHz&<br>Radiated Emission 1GHz~10 <sup>th</sup> Harmonic | 11b/DSSS        | 1 Mbps    | 1/6/11  |
|                                                                                                                                                                                                      | 11g/OFDM        | 6 Mbps    | 1/6/11  |
|                                                                                                                                                                                                      | 11n(20MHz)/OFDM | 6.5Mbps   | 1/6/11  |
|                                                                                                                                                                                                      | 11n(40MHz)/OFDM | 6.5Mbps   | 3/6/9   |
| Band Edge                                                                                                                                                                                            | 11b/DSSS        | 1 Mbps    | 1/11    |
|                                                                                                                                                                                                      | 11g/OFDM        | 6 Mbps    | 1/11    |
|                                                                                                                                                                                                      | 11n(20MHz)/OFDM | 6.5Mbps   | 1/11    |
|                                                                                                                                                                                                      | 11n(40MHz)/OFDM | 6.5Mbps   | 3/9     |

### 3.5 Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to CISPR 16 - 4 „Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements“ and is documented in the Shenzhen Global Test Service Co.,Ltd quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for Shenzhen GTS laboratory is reported:

| Test                  | Range      | Measurement Uncertainty | Notes |
|-----------------------|------------|-------------------------|-------|
| Radiated Emission     | 30~1000MHz | 4.10 dB                 | (1)   |
| Radiated Emission     | 1~18GHz    | 4.32 dB                 | (1)   |
| Radiated Emission     | 18-40GHz   | 5.54 dB                 | (1)   |
| Conducted Disturbance | 0.15~30MHz | 3.12 dB                 | (1)   |

- (1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

### 3.6 Equipments Used during the Test


| Test Equipment             | Manufacturer                      | Model No.             | Serial No.      | Calibration Date | Calibration Due Date |
|----------------------------|-----------------------------------|-----------------------|-----------------|------------------|----------------------|
| LISN                       | R&S                               | ENV216                | 3560.6550.08    | 2020/09/19       | 2021/09/18           |
| LISN                       | R&S                               | ESH2-Z5               | 893606/008      | 2020/09/19       | 2021/09/18           |
| EMI Test Receiver          | R&S                               | ESPI3                 | 101841-cd       | 2020/09/19       | 2021/09/18           |
| EMI Test Receiver          | R&S                               | ESCI7                 | 101102          | 2020/09/19       | 2021/09/18           |
| Spectrum Analyzer          | Agilent                           | N9020A                | MY48010425      | 2020/09/19       | 2021/09/18           |
| Spectrum Analyzer          | R&S                               | FSV40                 | 100019          | 2020/09/19       | 2021/09/18           |
| Vector Signal generator    | Agilent                           | N5181A                | MY49060502      | 2020/09/19       | 2021/09/18           |
| Signal generator           | Agilent                           | E4421B                | 3610AO1069      | 2020/09/19       | 2021/09/18           |
| Climate Chamber            | ESPEC                             | EL-10KA               | A20120523       | 2020/09/19       | 2021/09/18           |
| Controller                 | EM Electronics                    | Controller EM 1000    | N/A             | N/A              | N/A                  |
| Horn Antenna               | Schwarzbeck                       | BBHA 9120D            | 01622           | 2020/09/19       | 2021/09/18           |
| Active Loop Antenna        | Beijing Da Ze Technology Co.,Ltd. | ZN30900C              | 15006           | 2020/10/11       | 2021/10/10           |
| Bilog Antenna              | Schwarzbeck                       | VULB9163              | 000976          | 2020/05/26       | 2021/05/25           |
| Broadband Horn Antenna     | SCHWARZBECK                       | BBHA 9170             | 791             | 2020/09/19       | 2021/09/18           |
| Amplifier                  | Schwarzbeck                       | BBV 9743              | #202            | 2020/09/19       | 2021/09/18           |
| Amplifier                  | Schwarzbeck                       | BBV9179               | 9719-025        | 2020/09/19       | 2021/09/18           |
| Amplifier                  | EMCI                              | EMC051845B            | 980355          | 2020/09/19       | 2021/09/18           |
| Temperature/Humidity Meter | Gangxing                          | CTH-608               | 02              | 2020/09/19       | 2021/09/18           |
| High-Pass Filter           | K&L                               | 9SH10-2700/X12750-O/O | KL142031        | 2020/09/19       | 2021/09/18           |
| High-Pass Filter           | K&L                               | 41H10-1375/U12750-O/O | KL142032        | 2020/09/19       | 2021/09/18           |
| RF Cable(below 1GHz)       | HUBER+SUHNER                      | RG214                 | RE01            | 2020/09/19       | 2021/09/18           |
| RF Cable(above 1GHz)       | HUBER+SUHNER                      | RG214                 | RE02            | 2020/09/19       | 2021/09/18           |
| Data acquisition card      | Agilent                           | U2531A                | TW53323507      | 2020/09/19       | 2021/09/18           |
| Power Sensor               | Agilent                           | U2021XA               | MY5365004       | 2020/09/19       | 2021/09/18           |
| Test Control Unit          | Tonscend                          | JS0806-1              | 178060067       | 2020/06/19       | 2021/06/18           |
| Automated filter bank      | Tonscend                          | JS0806-F              | 19F8060177      | 2020/06/19       | 2021/06/18           |
| EMI Test Software          | Tonscend                          | JS1120-1              | Ver 2.6.8.0518  | /                | /                    |
| EMI Test Software          | Tonscend                          | JS1120-3              | Ver 2.5.77.0418 | /                | /                    |
| EMI Test Software          | Tonscend                          | JS32-CE               | Ver 2.5         | /                | /                    |
| EMI Test Software          | Tonscend                          | JS32-RE               | Ver 2.5.1.8     | /                | /                    |

Note: The Cal.Interval was one year.

## 4 TEST CONDITIONS AND RESULTS

### 4.1 AC Power Conducted Emission

#### TEST CONFIGURATION



#### TEST PROCEDURE

- 1 The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. The EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10-2013.
- 2 Support equipment, if needed, was placed as per ANSI C63.10-2013
- 3 All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10-2013
- 4 The EUT received DC 12V power from adapter, the adapter received AC120V/60Hz and AC 240V/60Hz power through a Line Impedance Stabilization Network (LISN) which supplied power source and was grounded to the ground plane.
- 5 All support equipments received AC power from a second LISN, if any.
- 6 The EUT test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
- 7 Analyzer / Receiver scanned from 150 KHz to 30MHz for emissions in each of the test modes.
- 8 During the above scans, the emissions were maximized by cable manipulation.

#### AC Power Conducted Emission Limit

For intentional device, according to § 15.207(a) AC Power Conducted Emission Limits is as following :


| Frequency range (MHz) | Limit (dBuV) |           |
|-----------------------|--------------|-----------|
|                       | Quasi-peak   | Average   |
| 0.15-0.5              | 66 to 56*    | 56 to 46* |
| 0.5-5                 | 56           | 46        |
| 5-30                  | 60           | 50        |


\* Decreases with the logarithm of the frequency.

#### TEST RESULTS

Remark:

1. All modes of 802.11b/g/n were tested at Low, Middle, and High channel; only the worst result of 802.11b CH11 was reported as below:
2. Both 120 VAC, 50/60 Hz and 240 VAC, 50/60 Hz power supply have been tested, only the worst result of 120 VAC, 60 Hz was reported as below:.







## 4.2 Radiated Emission

### TEST CONFIGURATION


Frequency range 9 KHz – 30MHz



Frequency range 30MHz – 1000MHz



Frequency range above 1GHz-25GHz



**TEST PROCEDURE**

1. The EUT was placed on a turn table which is 0.8m above ground plane when testing frequency range 9 KHz –1GHz;the EUT was placed on a turn table which is 1.5m above ground plane when testing frequency range 1GHz – 25GHz.
2. Maximum procedure was performed by raising the receiving antenna from 1m to 4m and rotating the turn table from 0° to 360° to acquire the highest emissions from EUT.
3. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
4. Repeat above procedures until all frequency measurements have been completed.
5. Radiated emission test frequency band from 9KHz to 25GHz.
6. The distance between test antenna and EUT as following table states:

| Test Frequency range | Test Antenna Type          | Test Distance |
|----------------------|----------------------------|---------------|
| 9KHz-30MHz           | Active Loop Antenna        | 3             |
| 30MHz-1GHz           | Ultra-Broadband Antenna    | 3             |
| 1GHz-18GHz           | Double Ridged Horn Antenna | 3             |
| 18GHz-25GHz          | Horn Antenna               | 1             |

7. Setting test receiver/spectrum as following table states:

| Test Frequency range | Test Receiver/Spectrum Setting                                                                            | Detector |
|----------------------|-----------------------------------------------------------------------------------------------------------|----------|
| 9KHz-150KHz          | RBW=200Hz/VBW=3KHz, Sweep time=Auto                                                                       | QP       |
| 150KHz-30MHz         | RBW=9KHz/VBW=100KHz, Sweep time=Auto                                                                      | QP       |
| 30MHz-1GHz           | RBW=120KHz/VBW=1000KHz, Sweep time=Auto                                                                   | QP       |
| 1GHz-40GHz           | Peak Value: RBW=1MHz/VBW=3MHz,<br>Sweep time=Auto<br>Average Value: RBW=1MHz/VBW=10Hz,<br>Sweep time=Auto | Peak     |

**Field Strength Calculation**

The field strength is calculated by adding the Antenna Factor and Cable Factor and subtracting the Amplifier Gain and Duty Cycle Correction Factor(if any) from the measured reading. The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CL - AG$$

|                           |                                            |
|---------------------------|--------------------------------------------|
| Where FS = Field Strength | CL = Cable Attenuation Factor (Cable Loss) |
| RA = Reading Amplitude    | AG = Amplifier Gain                        |
| AF = Antenna Factor       |                                            |

$$\text{Transd} = \text{AF} + \text{CL} - \text{AG}$$

**RADIATION LIMIT**

For intentional device, according to § 15.209(a), the general requirement of field strength of radiated emission from intentional radiators at a distance of 3 meters shall not exceed the following table. According to § 15.247(d), in any 100kHz bandwidth outside the frequency band in which the EUT is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of desired power.

The pre-test have done for the EUT in three axes and found the worst emission at position shown in test setup photos.


| Frequency (MHz) | Distance (Meters) | Radiated (dBµV/m)                            | Radiated (µV/m)       |
|-----------------|-------------------|----------------------------------------------|-----------------------|
| 0.009-0.49      | 3                 | $20\log(2400/F(\text{KHz})) + 40\log(300/3)$ | $2400/F(\text{KHz})$  |
| 0.49-1.705      | 3                 | $20\log(24000/F(\text{KHz})) + 40\log(30/3)$ | $24000/F(\text{KHz})$ |
| 1.705-30        | 3                 | $20\log(30) + 40\log(30/3)$                  | 30                    |
| 30-88           | 3                 | 40.0                                         | 100                   |
| 88-216          | 3                 | 43.5                                         | 150                   |
| 216-960         | 3                 | 46.0                                         | 200                   |
| Above 960       | 3                 | 54.0                                         | 500                   |

**TEST RESULTS**

Remark:

1. This test was performed with EUT in X, Y, Z position and the worse case was found when EUT in X position.
2. All three channels (lowest/middle/highest) of each mode were measured below 1GHz and recorded worst case at 802.11b low channel.
3. Radiated emission test from 9 KHz to 10th harmonic of fundamental was verified, and no emission found except system noise floor in 9 KHz to 30MHz and not recorded in this report.
4. Remark: Result=Reading value+Factor

#### For 30MHz-1GHz




#### Suspected List

| NO. | Frequency [MHz] | Reading [dBμV/m] | Factor [dB] | Result [dBμV/m] | Limit [dBμV/m] | Margin [dB] | Height [cm] | Angle [°] | Detector | Polarity   | Remark |
|-----|-----------------|------------------|-------------|-----------------|----------------|-------------|-------------|-----------|----------|------------|--------|
| 1   | 30.9700         | 32.74            | -9.49       | 23.25           | 40.00          | 16.75       | 100         | 264       | PK       | Horizontal | PASS   |
| 2   | 42.1250         | 33.40            | -6.76       | 26.64           | 40.00          | 13.36       | 100         | 270       | PK       | Horizontal | PASS   |
| 3   | 107.1150        | 26.07            | -8.22       | 17.85           | 43.50          | 25.65       | 100         | 280       | PK       | Horizontal | PASS   |
| 4   | 159.9800        | 35.24            | -11.92      | 23.32           | 43.50          | 20.18       | 100         | 270       | PK       | Horizontal | PASS   |
| 5   | 388.4150        | 38.63            | -5.77       | 32.86           | 46.00          | 13.14       | 100         | 38        | PK       | Horizontal | PASS   |

Note:1. Result (dBμV/m) = Reading(dBμV/m) + Factor (dB) .

2. Factor (dB) = Antenna Factor (dB/m) + Cable loss (dB) - Pre Amplifier gain (dB).



**For 1GHz to 25GHz**

*Note: 802.11b/802.11g/802.11n (H20)all have been tested, only worse case 802.11b mode is reported*

| Polar (H/V)             | Frequency (MHz) | Meter Reading (dBuV) | Antenna Factor (dB) | Cable loss (dB) | Preamp factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Detector Type |
|-------------------------|-----------------|----------------------|---------------------|-----------------|--------------------|-------------------------|-----------------|-------------|---------------|
| <b>802.11b-2412MHz</b>  |                 |                      |                     |                 |                    |                         |                 |             |               |
| V                       | 4824            | 51.78                | 30.28               | 7.01            | 36.5               | 52.57                   | 74              | 21.43       | PK            |
| V                       | 4824            | 41.19                | 30.28               | 7.01            | 36.5               | 41.98                   | 54              | 12.02       | AV            |
| H                       | 4824            | 52.28                | 30.28               | 7.01            | 36.5               | 53.07                   | 74              | 20.93       | PK            |
| H                       | 4824            | 42.06                | 30.28               | 7.01            | 36.5               | 42.85                   | 54              | 11.15       | AV            |
| V                       | 7236            | 37.55                | 36.59               | 8.91            | 35.3               | 47.75                   | 74              | 26.25       | PK            |
| V                       | 7236            | 29.27                | 36.59               | 8.91            | 35.3               | 39.47                   | 54              | 14.53       | AV            |
| H                       | 7236            | 38.31                | 36.59               | 8.91            | 35.3               | 48.51                   | 74              | 25.49       | PK            |
| H                       | 7236            | 28.42                | 36.59               | 8.91            | 35.3               | 38.62                   | 54              | 15.38       | AV            |
| <b>802.11b -2437MHz</b> |                 |                      |                     |                 |                    |                         |                 |             |               |
| V                       | 4874            | 52.39                | 30.36               | 7.62            | 36.5               | 53.87                   | 74              | 20.13       | PK            |
| V                       | 4874            | 41.71                | 30.36               | 7.62            | 36.5               | 43.19                   | 54              | 10.81       | AV            |
| H                       | 4874            | 52.93                | 30.36               | 7.62            | 36.5               | 54.41                   | 74              | 19.59       | PK            |
| H                       | 4874            | 41.28                | 30.36               | 7.62            | 36.5               | 42.76                   | 54              | 11.24       | AV            |
| V                       | 7311            | 39.32                | 36.61               | 8.84            | 35.3               | 49.47                   | 74              | 24.53       | PK            |
| V                       | 7311            | 28.69                | 36.61               | 8.84            | 35.3               | 38.84                   | 54              | 15.16       | AV            |
| H                       | 7311            | 39.11                | 36.61               | 8.84            | 35.3               | 49.26                   | 74              | 24.74       | PK            |
| H                       | 7311            | 29.25                | 36.61               | 8.84            | 35.3               | 39.4                    | 54              | 14.6        | AV            |
| <b>802.11b -2462MHz</b> |                 |                      |                     |                 |                    |                         |                 |             |               |
| V                       | 4924            | 52.73                | 30.43               | 7.94            | 36.2               | 54.9                    | 74              | 19.1        | PK            |
| V                       | 4924            | 42.18                | 30.43               | 7.94            | 36.2               | 44.35                   | 54              | 9.65        | AV            |
| H                       | 4924            | 54.43                | 30.43               | 7.94            | 36.2               | 56.6                    | 74              | 17.4        | PK            |
| H                       | 4924            | 40.69                | 30.43               | 7.94            | 36.2               | 42.86                   | 54              | 11.14       | AV            |
| V                       | 7386            | 40.56                | 36.78               | 8.45            | 35.3               | 50.49                   | 74              | 23.51       | PK            |
| V                       | 7386            | 27.73                | 36.78               | 8.45            | 35.3               | 37.66                   | 54              | 16.34       | AV            |
| H                       | 7386            | 39.66                | 36.78               | 8.45            | 35.3               | 49.59                   | 74              | 24.41       | PK            |
| H                       | 7386            | 30.75                | 36.78               | 8.45            | 35.3               | 40.68                   | 54              | 13.32       | AV            |

**Note:**

- 1) Emission level (dBuV/m) = Meter Reading+ antenna Factor+ cable loss- preamp factor.
- 2) Margin value = Limits-Emission level.
- 3) -- Mean the PK detector measured value is below average limit.
- 4) The other emission levels were very low against the limit.
- 5) RBW1MHz VBW3MHz Peak detector is for PK value; RBW 1MHz VBW10Hz Peak detector is for AV value.

**Results of Band Edges Test (Radiated)**

Note: 802.11b/802.11g/802.11n (H20) all have been tested, only worse case 802.11b mode is reported

| Polar (H/V)             | Frequency (MHz) | Meter Reading (dBuV) | Antenna Factor (dB) | Cable loss (dB) | Preamplifier factor (dB) | Emission Level (dBuV/m) | Limits (dBuV/m) | Margin (dB) | Detector Type |
|-------------------------|-----------------|----------------------|---------------------|-----------------|--------------------------|-------------------------|-----------------|-------------|---------------|
| <b>802.11b -2412MHz</b> |                 |                      |                     |                 |                          |                         |                 |             |               |
| V                       | 2390            | 57.33                | 27.49               | 3.32            | 36.22                    | 51.92                   | 74              | 22.08       | PK            |
| V                       | 2390            | 44.28                | 27.49               | 3.32            | 36.22                    | 38.87                   | 54              | 15.13       | AV            |
| H                       | 2390            | 56.62                | 27.49               | 3.32            | 36.22                    | 51.21                   | 74              | 22.79       | PK            |
| H                       | 2390            | 42.87                | 27.49               | 3.32            | 36.22                    | 37.46                   | 54              | 16.54       | AV            |
| V                       | 2400            | 58.63                | 27.55               | 3.41            | 36.22                    | 53.37                   | 74              | 20.63       | PK            |
| V                       | 2400            | 44.29                | 27.55               | 3.41            | 36.22                    | 39.03                   | 54              | 14.97       | AV            |
| H                       | 2400            | 60.33                | 27.55               | 3.41            | 36.22                    | 55.07                   | 74              | 18.93       | PK            |
| H                       | 2400            | 45.28                | 27.55               | 3.41            | 36.22                    | 40.02                   | 54              | 13.98       | AV            |
| <b>802.11b -2462MHz</b> |                 |                      |                     |                 |                          |                         |                 |             |               |
| V                       | 2483.50         | 55.52                | 27.45               | 3.38            | 36.34                    | 50.01                   | 74              | 23.99       | PK            |
| V                       | 2483.50         | 44.79                | 27.45               | 3.38            | 36.34                    | 39.28                   | 54              | 14.72       | AV            |
| H                       | 2483.50         | 55.21                | 27.45               | 3.38            | 36.34                    | 49.7                    | 74              | 24.3        | PK            |
| H                       | 2483.50         | 44.22                | 27.45               | 3.38            | 36.34                    | 38.71                   | 54              | 15.29       | AV            |
| V                       | 2500.00         | 56.87                | 27.41               | 3.47            | 36.35                    | 51.4                    | 74              | 22.6        | PK            |
| V                       | 2500.00         | 44.72                | 27.41               | 3.47            | 36.35                    | 39.25                   | 54              | 14.75       | AV            |
| H                       | 2500.00         | 55.93                | 27.41               | 3.47            | 36.35                    | 50.46                   | 74              | 23.54       | PK            |
| H                       | 2500.00         | 44.58                | 27.41               | 3.47            | 36.35                    | 39.11                   | 54              | 14.89       | AV            |

Note:

- 1) Emission level (dBuV/m) = Meter Reading+ antenna Factor+ cable loss- preamp factor.
- 2) Margin value = Limits-Emission level.
- 3) -- Mean the PK detector measured value is below average limit.
- 4) The other emission levels were very low against the limit.
- 5) RBW1MHz VBW3MHz Peak detector is for PK value; RBW 1MHz VBW10Hz Peak detector is for AV value.

### 4.3 Maximum Conducted Output Power


#### Limit

The Maximum Peak Output Power Measurement is 30dBm.

#### Test Procedure

Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the power sensor.

#### Test Configuration



#### Test Results

| Type          | Channel | Output power PK (dBm) | Limit (dBm) | Result |
|---------------|---------|-----------------------|-------------|--------|
| 802.11b       | 01      | 15.93                 | 30.00       | Pass   |
|               | 06      | 15.42                 |             |        |
|               | 11      | 15.88                 |             |        |
| 802.11g       | 01      | 17.97                 | 30.00       | Pass   |
|               | 06      | 17.35                 |             |        |
|               | 11      | 17.95                 |             |        |
| 802.11n(HT20) | 01      | 16.71                 | 30.00       | Pass   |
|               | 06      | 16.16                 |             |        |
|               | 11      | 16.65                 |             |        |
| 802.11n(HT40) | 03      | 16.46                 | 30.00       | Pass   |
|               | 06      | 15.81                 |             |        |
|               | 09      | 16.98                 |             |        |

Note:

- 1) Measured output power at difference data rate for each mode and recorded worst case for each mode.
- 2) Test results including cable loss.
- 3) Worst case data at 1Mbps at IEEE 802.11b; 6Mbps at IEEE 802.11g; 6.5Mbps at IEEE 802.11n HT20; 6.5Mbps at IEEE 802.11n HT40;

## 4.4 Power Spectral Density


### Limit

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

### Test Procedure

1. Use this procedure when the maximum peak conducted output power in the fundamental emission is used to demonstrate compliance.
2. Set the RBW  $\geq 3$  kHz.
3. Set the VBW  $\geq 3 \times$  RBW.
4. Set the span to 1.5 times the DTS channel bandwidth.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum power level.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.
11. The resulting peak PSD level must be 8dBm.

### Test Configuration











### Test Results









| Type          | Channel | Power Spectral Density (dBm/3KHz) | Limit (dBm/3KHz) | Result |
|---------------|---------|-----------------------------------|------------------|--------|
| 802.11b       | 01      | -12.69                            | 8.00             | Pass   |
|               | 06      | -12.62                            |                  |        |
|               | 11      | -12.01                            |                  |        |
| 802.11g       | 01      | -12.91                            | 8.00             | Pass   |
|               | 06      | -14.82                            |                  |        |
|               | 11      | -14.65                            |                  |        |
| 802.11n(HT20) | 01      | -15.30                            | 8.00             | Pass   |
|               | 06      | -15.96                            |                  |        |
|               | 11      | -14.31                            |                  |        |
| 802.11n(HT40) | 03      | -16.59                            | 8.00             | Pass   |
|               | 06      | -17.04                            |                  |        |
|               | 09      | -16.83                            |                  |        |

Note:

- 1) Measured peak power spectrum density at difference data rate for each mode and recorded worst case for each mode.
- 2) Test results including cable loss;
- 3) Worst case data at 1Mbps at IEEE 802.11b; 6Mbps at IEEE 802.11g; 6.5Mbps at IEEE 802.11n HT20; 6.5Mbps at IEEE 802.11n HT40;

Please refer to following plots;





## 4.5 6dB Bandwidth


### Limit

For digital modulation systems, the minimum 6 dB bandwidth shall be at least 500 kHz

### Test Procedure

The transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with 100 KHz RBW and 300 KHz VBW. The 6dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 6dB.

### Test Configuration



### Test Results


| Type          | Channel | 6dB Bandwidth (MHz) | Limit (KHz) | Result |
|---------------|---------|---------------------|-------------|--------|
| 802.11b       | 01      | 9.75                | ≥500        | Pass   |
|               | 06      | 9.93                |             |        |
|               | 11      | 9.86                |             |        |
| 802.11g       | 01      | 16.41               | ≥500        | Pass   |
|               | 06      | 16.47               |             |        |
|               | 11      | 16.43               |             |        |
| 802.11n(HT20) | 01      | 17.45               | ≥500        | Pass   |
|               | 06      | 17.52               |             |        |
|               | 11      | 17.43               |             |        |
| 802.11n(HT40) | 03      | 35.98               | ≥500        | Pass   |
|               | 06      | 35.48               |             |        |
|               | 09      | 35.56               |             |        |

Note:


- 1) Measured peak power spectrum density at difference data rate for each mode and recorded worst case for each mode.
- 2) Test results including cable loss;
- 3) Worst case data at 1Mbps at IEEE 802.11b; 6Mbps at IEEE 802.11g; 6.5Mbps at IEEE 802.11n HT20; 6.5Mbps at IEEE 802.11n HT40;

Please refer to following plots;


## 802.11b




## 802.11g




## CH01




## CH01



## CH06




## CH06










## CH11



## CH11





## 4.6 Out-of-band Emissions


### Limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required.

### Test Procedure

Connect the transmitter output to spectrum analyzer using a low loss RF cable, and set the spectrum analyzer to RBW=100 kHz, VBW= 300 kHz, peak detector, and max hold. Measurements utilizing these settings are made of the in-band reference level, band edge and out-of-band emissions.


### Test Configuration



### Test Results

Remark: The measurement frequency range is from 30MHz to the 10th harmonic of the fundamental frequency. The lowest, middle and highest channels are tested to verify the spurious emissions and band edge measurement data. And record the worst data in the report.

Test plot as follows:



3GHz -25GHz

CH01

Agilent

R T

Ref 16 dBm

\*Atten 25 dB

Mkr1 2.436 GHz

2.33 dBm

#Peak

Log

10

dB/

Offst

1

dB

DI

-17.7

dBm

VAvg

44

M1 S2

S3 FC

AA

Center Freq

1.51500000 GHz

Start Freq

30.00000000 MHz

Stop Freq

3.000000000 GHz

CF Step

297.0000000 MHz

Auto Man

Freq Offset

0.00000000 Hz

Signal Track

On Off

Scale Type

Log Lin

Start 30 MHz

\*Res BW 100 kHz

\*VBW 300 kHz

Sweep 307.7 ms (401 pts)

Stop 3 GHz

30MHz-3GHz

Agilent

R T

Ref 16 dBm

\*Atten 25 dB

Mkr1 3.275 GHz

-47.77 dBm

#Peak

Log

10

dB/

Offst

1

dB

DI

-17.7

dBm

VAvg

Auto

M1 S2

S3 FC

AA

Center Freq

14.00000000 GHz

Start Freq

3.000000000 GHz

Stop Freq

25.00000000 GHz

CF Step

2.200000000 GHz

Auto Man

Freq Offset

0.00000000 Hz

Signal Track

On Off

Scale Type

Log Lin

Start 3 GHz

\*Res BW 100 kHz

\*VBW 300 kHz

Sweep 2.279 s (401 pts)

Stop 25 GHz

3GHz -25GHz

CH06

Agilent

R T

Ref 16 dBm

\*Atten 25 dB

Mkr1 2.465 GHz

2.906 dBm

#Peak

Log

10

dB/

Offst

1

dB

DI

-17.1

dBm

VAvg

Auto

M1 S2

S3 FC

AA

Center Freq

1.51500000 GHz

Start Freq

30.00000000 MHz

Stop Freq

3.000000000 GHz

CF Step

297.0000000 MHz

Auto Man

Freq Offset

0.00000000 Hz

Signal Track

On Off

Scale Type

Log Lin

Start 30 MHz

\*Res BW 100 kHz

\*VBW 300 kHz

Sweep 307.7 ms (401 pts)

Stop 3 GHz

30MHz-3GHz

Agilent

R T

Ref 16 dBm

\*Atten 25 dB

Mkr1 3.275 GHz

-48.27 dBm

#Peak

Log

10

dB/

Offst

1

dB

DI

-17.1

dBm

VAvg

Auto

M1 S2

S3 FC

AA

Center Freq

14.00000000 GHz

Start Freq

3.000000000 GHz

Stop Freq

25.00000000 GHz

CF Step

2.200000000 GHz

Auto Man

Freq Offset

0.00000000 Hz

Signal Track

On Off

Scale Type

Log Lin

Start 3 GHz

\*Res BW 100 kHz


\*VBW 300 kHz

Sweep 2.279 s (401 pts)

Stop 25 GHz

3GHz -25GHz

CH11



CH01

Agilent

Ref 16 dBm

\*Atten 25 dB

Mkr1 2.436 GHz

0.626 dBm

#Peak

Log

10

dB/

Offst

1

dB

DI

-19.4

dBm

M1 S2

S3 FC

AA

Freq/Channel

Center Freq

1.51500000 GHz

Start Freq

30.00000000 MHz

Stop Freq

3.000000000 GHz

CF Step

297.0000000 MHz

Auto

Man

Freq Offset

0.00000000 Hz

Signal Track

On

Off

Scale Type

Log

Lin

Start 30 MHz

\*Res BW 100 kHz

\*VBW 300 kHz

Sweep 307.7 ms (401 pts)

Stop 3 GHz

30MHz-3GHz

Agilent

Ref 16 dBm

\*Atten 25 dB

Mkr1 25.000 GHz

-48.57 dBm

#Peak

Log

10

dB/

Offst

1

dB

DI

-19.4

dBm

M1 S2

S3 FC

AA

Freq/Channel

Center Freq

14.00000000 GHz

Start Freq

3.000000000 GHz

Stop Freq

25.00000000 GHz

CF Step

2.200000000 GHz

Auto

Man

Freq Offset

0.00000000 Hz

Signal Track

On

Off

Scale Type

Log

Lin

Start 3 GHz

\*Res BW 100 kHz

\*VBW 300 kHz

Sweep 2.279 s (401 pts)

Stop 25 GHz

3GHz -25GHz

CH06

Agilent

Ref 16 dBm

\*Atten 25 dB

Mkr1 2.473 GHz

1.771 dBm

#Peak

Log

10

dB/

Offst

1

dB

DI

-18.3

dBm

M1 S2

S3 FC

AA

Freq/Channel

Center Freq

1.51500000 GHz

Start Freq

30.00000000 MHz

Stop Freq

3.000000000 GHz

CF Step

297.0000000 MHz

Auto

Man

Freq Offset

0.00000000 Hz

Signal Track

On

Off

Scale Type

Log

Lin

Start 30 MHz

\*Res BW 100 kHz

\*VBW 300 kHz

Sweep 307.7 ms (401 pts)

Stop 3 GHz

30MHz-3GHz

Agilent

Ref 16 dBm

\*Atten 25 dB

Mkr1 3.275 GHz

-48.37 dBm

#Peak

Log

10

dB/

Offst

1

dB

DI

-18.3

dBm

M1 S2

S3 FC

AA

Freq/Channel

Center Freq

14.00000000 GHz

Start Freq

3.000000000 GHz

Stop Freq

25.00000000 GHz

CF Step

2.200000000 GHz

Auto

Man

Freq Offset

0.00000000 Hz

Signal Track

On

Off

Scale Type

Log

Lin

Start 3 GHz

\*Res BW 100 kHz


\*VBW 300 kHz


Sweep 2.279 s (401 pts)

Stop 25 GHz

3GHz -25GHz

CH11





Start 3 GHz

\*Res BW 100 kHz

\*VBW 300 kHz

Sweep 2.279 s (401 pts)

Stop 25 GHz

3GHz -25GHz

CH03

Agilent

R T

Freq/Channel

Ref 16 dBm

\*Atten 25 dB

Mkr1 2.428 GHz

-1.903 dBm

#Peak

Log

10

dB/

Offst

1

dB

DI

-21.9

dBm

VAvg

34

M1 S2

S3 FC

AA

Center Freq

1.51500000 GHz

Start Freq

30.00000000 MHz

Stop Freq

3.000000000 GHz

CF Step

297.0000000 MHz

Auto

Man

Freq Offset

0.00000000 Hz

Signal Track

On

Off

Scale Type

Log

Lin

Start 30 MHz

\*Res BW 100 kHz

\*VBW 300 kHz

Sweep 307.7 ms (401 pts)

Stop 3 GHz

30MHz-3GHz

Agilent

R T

Freq/Channel

Ref 16 dBm

\*Atten 25 dB

Mkr1 25.000 GHz

-48.91 dBm

#Peak

Log

10

dB/

Offst

1

dB

DI

-21.9

dBm

VAvg

3

M1 S2

S3 FC

AA

Center Freq

14.00000000 GHz

Start Freq

3.000000000 GHz

Stop Freq

25.00000000 GHz

CF Step

2.200000000 GHz

Auto

Man

Freq Offset

0.00000000 Hz

Signal Track

On

Off

Scale Type

Log

Lin

Start 3 GHz

\*Res BW 100 kHz

\*VBW 300 kHz

Sweep 2.279 s (401 pts)

Stop 25 GHz

3GHz -25GHz

CH06

Agilent

R T

Freq/Channel

Ref 16 dBm

\*Atten 25 dB

Mkr1 2.465 GHz

-0.701 dBm

#Peak

Log

10

dB/

Offst

1

dB

DI

-20.7

dBm

VAvg

41

M1 S2

S3 FC

AA

Center Freq

1.51500000 GHz

Start Freq

30.00000000 MHz

Stop Freq

3.000000000 GHz

CF Step

297.0000000 MHz

Auto

Man

Freq Offset

0.00000000 Hz

Signal Track

On

Off

Scale Type

Log

Lin

Start 30 MHz

\*Res BW 100 kHz

\*VBW 300 kHz

Sweep 307.7 ms (401 pts)

Stop 3 GHz

30MHz-3GHz

Agilent

R T

Freq/Channel

Ref 16 dBm

\*Atten 25 dB

Mkr1 3.275 GHz

-47.91 dBm

#Peak

Log

10

dB/

Offst

1

dB

DI

-20.7

dBm

VAvg

4

M1 S2

S3 FC

AA

Center Freq

14.00000000 GHz

Start Freq

3.000000000 GHz

Stop Freq

25.00000000 GHz

CF Step

2.200000000 GHz

Auto

Man

Freq Offset

0.00000000 Hz

Signal Track

On

Off

Scale Type

Log

Lin

Start 3 GHz

\*Res BW 100 kHz




\*VBW 300 kHz


Sweep 2.279 s (401 pts)

Stop 25 GHz

3GHz -25GHz

CH09

**Band-edge Measurements for RF Conducted Emissions:**



## 4.7 Antenna Requirement

### Standard Applicable

**For intentional device, according to FCC 47 CFR Section 15.203:**

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited

**FCC CFR Title 47 Part 15 Subpart C Section 15.247(c) (1) (I):**

(i) Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.

### Test Result:


The maximum gain of antenna was 0 dBi for 2.4GHz WIFI.


## 5 Test Setup Photos of the EUT







## 6 Photos of the EUT














\*\*\*\*\* End of Report \*\*\*\*\*