



FCC TEST REPORT

**Test report
On Behalf of
Shenzhen Interstellar-clouds Technology Co.,LTD
For
Wireless Router**

**Model No.: GX-WRP300-C, GX-WRP300-M, GX-WRP300-B,
GX-WRP300-S, GX-WRP300-R, GX-WRP750, GX-WRP1200,
GX-WRT41, GX-WRT31, GX-RT28, GX-MRT20,
GX-AR41,GX-AR44, GX-AR31**

FCC ID: 2AL94-GXWRP300C

Prepared for : Shenzhen Interstellar-clouds Technology Co.,LTD
F Building, Xinhui Industrial Park, Bao'an District, Shenzhen, China

Prepared By : Shenzhen HUAKE Testing Technology Co., Ltd.
F1-008, Tai Yi Building, No.1, Haicheng West Road, Xixiang Street, Bao'an
District, Shenzhen City, China

Date of Test: May 12, 2017 ~ May 19, 2017

Date of Report: May 19, 2017

Report Number: HK170511021-E



TEST RESULT CERTIFICATION

Applicant's name : Shenzhen Interstellar-clouds Technology Co.,LTD
Address : F Building, Xinhui Industrial Park, Bao'an District, Shenzhen, China

Manufacture's Name : Shenzhen Interstellar-clouds Technology Co.,LTD
Address : F Building, Xinhui Industrial Park, Bao'an District, Shenzhen, China

Product description

Trade Mark: /

Product name : Wireless Router

Model and/or type reference : GX-WRP300-C, GX-WRP300-M, GX-WRP300-B, GX-WRP300-S, GX-WRP300-R, GX-WRP750, GX-WRP1200, GX-WRT41, GX-WRT31, GX-RT28, GX-MRT20, GX-AR41, GX-AR44, GX-AR31

Standards : FCC Rules and Regulations Part 15 Subpart C Section 15.247
ANSI C63.10: 2013

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen HUAKE Testing Technology Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen HUAKE Testing Technology Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Date of Test :

Date (s) of performance of tests : May 12, 2017 ~ May 19, 2017

Date of Issue : May 19, 2017

Test Result : Pass

Testing Engineer :

(Eric Xie)

Technical Manager :

(Dora Qin)

Authorized Signatory :

(Kait Chen)



Table of Contents	Page
1 . TEST SUMMARY	5
2 . GENERAL INFORMATION	6
2.1 GENERAL DESCRIPTION OF EUT	6
Operation of EUT during testing	7
2.2 DESCRIPTION OF TEST SETUP	7
2.3 MEASUREMENT INSTRUMENTS LIST	8
3 . CONDUCTED EMISSIONS TEST	9
3.1 Conducted Power Line Emission Limit	9
3.2 Test Setup	9
3.3 Test Procedure	9
3.4 Test Result	9
4 RADIATED EMISSION TEST	12
4.1 Radiation Limit	12
4.2 Test Setup	12
4.3 Test Procedure	13
4.4 Test Result	13
5 BAND EDGE	28
5.1 Limits	28
5.2 Test Procedure	28
5.3 Test Result	28
6 OCCUPIED BANDWIDTH MEASUREMENT	36
6.1 Test Limit	36
6.2 Test Procedure	36
6.3 Measurement Equipment Used	36
6.4 Test Result	36
7 POWER SPECTRAL DENSITY TEST	53
7.1 Test Limit	53
7.2 Test Procedure	53
7.3 Measurement Equipment Used	53
7.4 Test Result	53
8 PEAK OUTPUT POWER TEST	71
8.1 Test Limit	71
8.2 Test Procedure	71
8.3 Measurement Equipment Used	71



Table of Contents	Page
8.4 Test Result	71
9 OUT OF BAND EMISSIONS TEST	72
9.1 Test Limit	72
9.2 Test Procedure	72
9.3 Test Setup	72
9.4 Test Result	72
10 ANTENNA REQUIREMENT	97
11 PHOTOGRAPH OF TEST	98
11.1 Radiated Emission	98
11.2 Conducted Emission	99



1. TEST SUMMARY

1.1 TEST PROCEDURES AND RESULTS

DESCRIPTION OF TEST	RESULT
CONDUCTED EMISSIONS TEST	COMPLIANT
RADIATED EMISSION TEST	COMPLIANT
BAND EDGE	COMPLIANT
OCCUPIED BANDWIDTH MEASUREMENT	COMPLIANT
POWER SPECTRAL DENSITY	COMPLIANT
PEAK OUTPUT POWER _{Peak}	COMPLIANT
OUT OF BAND EMISSIONS	COMPLIANT
ANTENNA REQUIREMENT	COMPLIANT

1.2 TEST FACILITY

Test Firm : QTC Certification & Testing Co., Ltd.
Certificated by FCC, Registration No.: 588523
Address 2nd Floor,B1 Building,Fengyeyuan Industrial Plant, Liuxian 2st. Road,
Xin'an Street, Bao'an District, Shenzhen, China

1.3 MEASUREMENT UNCERTAINTY

Measurement Uncertainty	
Conducted Emission Expanded Uncertainty	= 2.23dB, k=2
Radiated emission expanded uncertainty(9kHz-30MHz)	= 3.08dB, k=2
Radiated emission expanded uncertainty(30MHz-1000MHz)	= 4.42dB, k=2
Radiated emission expanded uncertainty(Above 1GHz)	= 4.06dB, k=2



2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

Equipment	Wireless Router
Model Name	GX-WRP300-C
Serial Model	GX-WRP300-M, GX-WRP300-B, GX-WRP300-S, GX-WRP300-R, GX-WRP750, GX-WRP1200, GX-WRT41, GX-WRT31, GX-RT28, GX-MRT20, GX-AR41, GX-AR44, GX-AR31
Model Difference	All model's the function, software and electric circuit are the same, only with a product color and model named different. Test sample model: GX-WRP300-C
FCC ID	2AL94-GXWRP300C
Antenna Type	Antenna port 1: Integral Antenna Antenna port 2: Integral Antenna
Antenna Gain	Antenna port 1: 2 dBi Antenna port 2: 2 dBi
BT Operation frequency	802.11b/g/n 20: 2412~2462 MHz 802.11n 40: 2422~2452MHz
Number of Channels	802.11b/g/n20: 11CH 802.11n 40: 7CH
Modulation Type	CCK/OFDM/DBPSK/DAPSK
Power Source	AC Source
Power Rating	AC 120V/60Hz



2.1.1 Carrier Frequency of Channels

Channel List for 802.11b/g/n(20MHz)							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
01	2412	04	2427	07	2442	10	2457
02	2417	05	2432	08	2447	11	2462
03	2422	06	2437	09	2452		

Channel List for 802.11n(40MHz)							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
03	2422	06	2437	09	2452		
04	2427	07	2442				
05	2432	08	2447				

Operation of EUT during testing

Operating Mode

The mode is used: **Transmitting mode for 802.11b/g/n(20MHz)**

Low Channel: 2412MHz

Middle Channel: 2437MHz

High Channel: 2462MHz

Transmitting mode for 802.11n(40MHz)


Low Channel: 2422MHz

Middle Channel: 2437MHz

High Channel: 2452MHz

2.2 DESCRIPTION OF TEST SETUP

Operation of EUT during conducted and Radiation testing:





2.3 MEASUREMENT INSTRUMENTS LIST

Item	Equipment	Manufacturer	Model No.	Serial No.	Cal Date	Due Date
1.	EMI Receiver	Rohde & Schwarz	ESCI	100627	Feb. 18, 2017	Feb. 17, 2018
2.	LISN	SchwarzBeck	NSLK 8126	8126377	Feb. 18, 2017	Feb. 17, 2018
3.	RF Switching Unit	Compliance Direction	RSU-M2	38303	Feb. 18, 2017	1 Year
4.	EMI Test Software ES-K1	Rohde & Schwarz	N/A	N/A	N/A	N/A
5.	EMI Test Receiver	Rohde & Schwarz	ESCI	100627	Feb. 18, 2017	Feb. 17, 2018
6.	Trilog Broadband Antenna	Schwarzbeck	VULB9163	VULB 9163-289	Feb. 18, 2017	Feb. 17, 2018
7.	Pre-amplifier	Compliance Direction	PAP-0203	22008	Feb. 18, 2017	Feb. 17, 2018
8.	EMI Test Software EZ-EMC	SHURPLE	N/A	N/A	N/A	N/A
9.	EMI Receiver	Rohde & Schwarz	ESCI	100627	Feb. 18, 2017	Feb. 17, 2018
10.	LISN	SchwarzBeck	NSLK 8126	8126377	Feb. 18, 2017	Feb. 17, 2018
11.	RF Switching Unit	Compliance Direction	RSU-M2	38303	Feb. 18, 2017	Feb. 17, 2018
12.	EMI Test Software ES-K1	Rohde & Schwarz	N/A	N/A	N/A	N/A
13.	EMI Receiver	Rohde & Schwarz	ESCI	100627	Feb. 18, 2017	Feb. 17, 2018
14.	EMI Receiver	Rohde & Schwarz	ESCI	100627	Feb. 18, 2017	Feb. 17, 2018
15.	LISN	SchwarzBeck	NSLK 8126	8126377	Feb. 18, 2017	Feb. 17, 2018
16.	RF Switching Unit	Compliance Direction	RSU-M2	38303	Feb. 18, 2017	Feb. 17, 2018
17.	EMI Test Software ES-K1	Rohde & Schwarz	N/A	N/A	N/A	N/A
18.	Power Meter	R&S	NRVD	SEL0069	Feb. 18, 2017	Feb. 17, 2018
19.	Power Sensor	R&S	URV5-Z2	SEL0071	Feb. 18, 2017	Feb. 17, 2018
20.	Power Sensor	R&S	URV5-Z2	SEL0072	Feb. 18, 2017	Feb. 17, 2018
21.	Software EMC32	R&S	EMC32-S	SEL0082	N/A	N/A
22.	Log-periodic Antenna	Amplifier Reasearch	APT1.580	SEL0073	Feb. 18, 2017	Feb. 17, 2018
23.	Loop Antenna	Schwarz beck	FMZB 1516	9773	Feb. 18, 2017	Feb. 17, 2018
24.	Broadband Antenna	Schwarz beck	VULB9163	9163-333	Feb. 18, 2017	Feb. 17, 2018
25.	Horn Antenna	ETS	3117	00086197	Feb. 18, 2017	Feb. 17, 2018
26.	Horn Antenna	Schwarzbeck	BBHA9170	BBHA91705 82	Feb. 18, 2017	Feb. 17, 2018
27.	Antenna Tripod	Amplifier Reasearch	TP1000A	SEL0074	Feb. 18, 2017	Feb. 17, 2018
28.	High Gain Horn Antenna	Amplifier Reasearch	AT4002A	SEL0075	Feb. 18, 2017	Feb. 17, 2018
29.	Spectrum analyzer	Agilent	N9020A	MY49911004 8	Feb. 18, 2017	Feb. 17, 2018
30.	Spectrum analyzer	Agilent	E4407B	MY46184326	Feb. 18, 2017	Feb. 17, 2018
31.	Spectrum analyzer	R&S	FSP30	836079/035	Feb. 18, 2017	Feb. 17, 2018
32.	RF Cable	Micable	C10-01-01-1	100309	Feb. 18, 2017	Feb. 17, 2018



3. CONDUCTED EMISSIONS TEST

3.1 Conducted Power Line Emission Limit


For unintentional device, according to § 15.107(a) Line Conducted Emission Limits is as following

Frequency (MHz)	Maximum RF Line Voltage (dBμV)			
	CLASS A		CLASS B	
	Q.P.	Ave.	Q.P.	Ave.
0.15 - 0.50	79	66	66-56*	56-46*
0.50 - 5.00	73	60	56	46
5.00 - 30.0	73	60	60	50

* Decreasing linearly with the logarithm of the frequency

For intentional device, according to §15.207(a) Line Conducted Emission Limit is same as above table.

3.2 Test Setup



3.3 Test Procedure

- 1, The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. The EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10.
- 2, Support equipment, if needed, was placed as per ANSI C63.10.
- 3, All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10.
- 4, If a EUT received DC power from the USB Port of Notebook PC, the PC's adapter received AC120V/60Hz power through a Line Impedance Stabilization Network (LISN) which supplied power source and was grounded to the ground plane.
- 5, All support equipments received AC power from a second LISN, if any.
- 6, The EUT test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
- 7, Analyzer / Receiver scanned from 150 KHz to 30MHz for emissions in each of the test modes.


3.4 Test Result

PASS

All the test modes completed for test.




Test Specification: Line



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1*	0.4220	42.43	9.80	52.23	57.41	-5.18	QP
2	0.4540	31.25	9.80	41.05	46.80	-5.75	AVG
3	0.6780	20.59	9.79	30.38	46.00	-15.62	AVG
4	0.6980	37.31	9.78	47.09	56.00	-8.91	QP
5	0.8700	21.51	9.77	31.28	46.00	-14.72	AVG
6	0.8980	35.31	9.77	45.08	56.00	-10.92	QP



Test Specification: Neutral



No.	Frequency	Reading	Correct	Result	Limit	Margin	Detector
	(MHz)	(dBuV)	(dB/m)	(dBuV)	(dBuV)	(dB)	
1	0.4180	35.75	9.80	45.55	57.49	-11.94	QP
2*	0.4500	27.09	9.80	36.89	46.88	-9.99	AVG
3	1.2220	18.89	9.75	28.64	46.00	-17.36	AVG
4	1.2420	30.72	9.75	40.47	56.00	-15.53	QP
5	2.7900	15.96	9.72	25.68	46.00	-20.32	AVG
6	3.4500	31.78	9.70	41.48	56.00	-14.52	QP

4 RADIATED EMISSION TEST

4.1 Radiation Limit


For unintentional device, according to § 15.109(a), except for Class A digital devices, the field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the following values:

Frequency (MHz)	Distance (Meters)	Radiated (dB μ V/m)	Radiated (μ V/m)
30-88	3	40	100
88-216	3	43.5	150
216-960	3	46	200
Above 960	3	54	500


For intentional device, according to § 15.209(a), the general requirement of field strength of radiated emissions from intentional radiators at a distance of 3 meters shall not exceed the above table.

4.2 Test Setup


(1) Radiated Emission Test-Up Frequency Below 30MHz



(2) Radiated Emission Test-Up Frequency 30MHz~1GHz



(3) Radiated Emission Test-Up Frequency Above 1GHz



4.3 Test Procedure

1. Below 1GHz measurement the EUT is placed on turntable which is 0.8m above ground plane. And above 1GHz measurement EUT was placed on low permittivity and low tangent turn table which is 1.5m above ground plane.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
6. Repeat above procedures until the measurements for all frequencies are complete.
7. The test frequency range from 9KHz to 25GHz per FCC PART 15.33(a).

Note:

For battery operated equipment, the equipment tests shall be performed using a new battery.


4.4 Test Result

PASS

All the test modes completed for test. The worst case of Radiated Emission (802.11b Transmitting High Channel-2462MHz (worst case)); the test data of this mode was reported.




Below 1GHz Test Results:
Antenna polarity: H



No.	Frequency	Reading	Correct	Result	Limit	Margin	Degree	Height	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	()	(cm)	
1	102.0014	48.20	-11.63	36.57	43.50	-6.93	227	100	peak
2	147.9214	54.64	-14.92	39.72	43.50	-3.78	95	100	peak
3	206.3976	46.43	-11.88	34.55	43.50	-8.95	121	100	peak
4	250.3012	52.85	-10.49	42.36	46.00	-3.64	95	100	peak
5	319.9370	44.22	-9.63	34.59	46.00	-11.41	132	100	peak
6	480.5276	36.01	-5.36	30.65	46.00	-15.35	169	100	peak



Antenna polarity: V



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	38.8879	48.74	-10.66	38.08	40.00	-1.92	111	100	peak
2	45.6948	48.17	-10.45	37.72	40.00	-2.28	221	100	peak
3	102.0014	43.00	-11.63	31.37	43.50	-12.13	76	100	peak
4	147.9214	54.34	-14.92	39.42	43.50	-4.08	154	100	peak
5	250.3012	42.35	-10.49	31.86	46.00	-14.14	126	100	peak
6	480.5276	34.21	-5.36	28.85	46.00	-17.15	173	100	peak

Remark:

- (1) Measuring frequencies from 9 KHz to the 1 GHz, Radiated emission test from 9KHz to 30MHz was verified, and no any emission was found except system noise floor.
- (2) * denotes emission frequency which appearing within the Restricted Bands specified in provision of 15.205, then the general radiated emission limits in 15.209 apply.
- (3) The IF bandwidth of EMI Test Receiver between 30MHz to 1GHz was 120KHz, 1 MHz for measuring above 1 GHz, below 30MHz was 10KHz.

All the test modes completed for test. The worst case MIMO mode of Radiated Emission; the test data of this mode was reported.

For MIMO antenna port 1 and part 2 above 1 GHz Test Results:

LOW CH1 (802.11b Mode)/2412

Horizontal:

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
4824	61.23	-3.64	57.59	74	-16.41	peak
4824	45.23	-3.64	41.59	54	-12.41	AVG
7236	53.16	-0.95	52.21	74	-21.79	peak
7236	41.87	-0.95	40.92	54	-13.08	AVG
---	---	---	---	---	---	---
---	---	---	---	---	---	---

Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.

Vertical:

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
4824	63.17	-3.64	59.53	74	-14.47	peak
4824	41.26	-3.64	37.62	54	-16.38	AVG
7236	55.23	-0.95	54.28	74	-19.72	peak
7236	42.15	-0.95	41.2	54	-12.8	AVG
---	---	---	---	---	---	---
---	---	---	---	---	---	---

Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.



MID CH6 (802.11b Mode)/2437
Horizontal:

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
4874	61.87	-3.51	58.36	74	-15.64	peak
4874	45.81	-3.51	42.3	54	-11.7	AVG
7311	56.73	-0.82	55.91	74	-18.09	peak
7311	44.16	-0.82	43.34	54	-10.66	AVG
---	---	---	---	---	---	---
---	---	---	---	---	---	---

Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.

Vertical:

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
4874	62.16	-3.51	58.65	74	-15.35	peak
4874	45.23	-3.51	41.72	54	-12.28	AVG
7311	54.18	-0.82	53.36	74	-20.64	peak
7311	43.25	-0.82	42.43	54	-11.57	AVG
---	---	---	---	---	---	---
---	---	---	---	---	---	---

Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.



HIGH CH11 (802.11b Mode)/2462
Horizontal:

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
4924	62.22	-3.43	58.79	74	-15.21	peak
4924	45.75	-3.43	42.32	54	-11.68	AVG
7386	56.09	-0.75	55.34	74	-18.66	peak
7386	41.08	-0.75	40.33	54	-13.67	AVG
---	---	---	---	---	---	---
---	---	---	---	---	---	---

Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.

Vertical:

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
4924	62.15	-3.43	58.72	74	-15.28	peak
4924	42.98	-3.43	39.55	54	-14.45	AVG
7386	52.78	-0.75	52.03	74	-21.97	peak
7386	42.22	-0.75	41.47	54	-12.53	AVG
---	---	---	---	---	---	---
---	---	---	---	---	---	---

Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.

Remark:

- (1) Measuring frequencies from 1 GHz to the 25 GHz.
- (2) "F" denotes fundamental frequency; "H" denotes spurious frequency. "E" denotes band edge frequency.
- (3) * denotes emission frequency which appearing within the Restricted Bands specified in provision of 15.205, then the general radiated emission limits in 15.209 apply.
- (4) Data of measurement within this frequency range shown "---" in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (5) The IF bandwidth of EMI Test Receiver between 30MHz to 1GHz was 120KHz, 1 MHz for measuring above 1 GHz, below 30MHz was 10KHz.
- (6) When the test results of Peak Detected below the limits of Average Detected, the Average Detected is not need completed. For example: Top Channel at Fundamental 73.16dBuV/m(PK Value) <93.98(AV Limit), at harmonic 53.20 dBuV/m(PK Value) <54 dBuV/m(AV Limit), the Average Detected not need to completed.



LOW CH1 (802.11g Mode)/2412
Horizontal:

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
4824	61.28	-3.64	57.64	74	-16.36	peak
4824	45.19	-3.64	41.55	54	-12.45	AVG
7236	55.07	-0.95	54.12	74	-19.88	peak
7236	41.67	-0.95	40.72	54	-13.28	AVG
---	---	---	---	---	---	---
---	---	---	---	---	---	---

Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.

Vertical:

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
4824	61.09	-3.64	57.45	74	-16.55	peak
4824	42.07	-3.64	38.43	54	-15.57	AVG
7236	56.17	-0.95	55.22	74	-18.78	peak
7236	42.71	-0.95	41.76	54	-12.24	AVG
---	---	---	---	---	---	---
---	---	---	---	---	---	---

Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.



MID CH6 (802.11g Mode)/2437
Horizontal:

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
4874	60.92	-3.51	57.41	74	-16.59	peak
4874	46.37	-3.51	42.86	54	-11.14	AVG
7311	55.85	-0.82	55.03	74	-18.97	peak
7311	42.57	-0.82	41.75	54	-12.25	AVG
---	---	---	---	---	---	---
---	---	---	---	---	---	---

Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.

Vertical:

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
4874	61.46	-3.51	57.95	74	-16.05	peak
4874	45.28	-3.51	41.77	54	-12.23	AVG
7311	53.95	-0.82	53.13	74	-20.87	peak
7311	44.74	-0.82	43.92	54	-10.08	AVG
---	---	---	---	---	---	---
---	---	---	---	---	---	---

Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.



HIGH CH11 (802.11g Mode)/2462
Horizontal:

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
4924	61.25	-3.43	57.82	74	-16.18	peak
4924	45.36	-3.43	41.93	54	-12.07	AVG
7386	54.65	-0.75	53.9	74	-20.1	peak
7386	44.71	-0.75	43.96	54	-10.04	AVG
---	---	---	---	---	---	---
---	---	---	---	---	---	---

Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.

Vertical:

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
4924	61.08	-3.43	57.65	74	-16.35	peak
4924	47.36	-3.43	43.93	54	-10.07	AVG
7386	54.17	-0.75	53.42	74	-20.58	peak
7386	43.21	-0.75	42.46	54	-11.54	AVG
---	---	---	---	---	---	---
---	---	---	---	---	---	---

Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.

Remark:

- (1) Measuring frequencies from 1 GHz to the 25 GHz.
- (2) "F" denotes fundamental frequency; "H" denotes spurious frequency. "E" denotes band edge frequency.
- (3) * denotes emission frequency which appearing within the Restricted Bands specified in provision of 15.205, then the general radiated emission limits in 15.209 apply.
- (4) Data of measurement within this frequency range shown "—" in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (5) The IF bandwidth of EMI Test Receiver between 30MHz to 1GHz was 120KHz, 1 MHz for measuring above 1 GHz, below 30MHz was 10KHz.
- (6) When the test results of Peak Detected below the limits of Average Detected, the Average Detected is not need completed. For example: Top Channel at Fundamental 73.16dBuV/m(PK Value) <93.98(AV Limit), at harmonic 53.20 dBuV/m(PK Value) <54 dBuV/m(AV Limit), the Average Detected not need to completed.

LOW CH1 (802.11n/H20 Mode)/2412
Horizontal:

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
4824	60.15	-3.64	56.51	74	-17.49	peak
4824	46.07	-3.64	42.43	54	-11.57	AVG
7236	55.37	-0.95	54.42	74	-19.58	peak
7236	41.22	-0.95	40.27	54	-13.73	AVG
---	---	---	---	---	---	---
---	---	---	---	---	---	---

Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.

Vertical:

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
4824	60.12	-3.64	56.48	74	-17.52	peak
4824	44.36	-3.64	40.72	54	-13.28	AVG
7236	54.72	-0.95	53.77	74	-20.23	peak
7236	41.21	-0.95	40.26	54	-13.74	AVG
---	---	---	---	---	---	---
---	---	---	---	---	---	---

Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.



MID CH6 (802.11n/H20 Mode)/2437

Horizontal:

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
4874	61.02	-3.51	57.51	74	-16.49	peak
4874	43.82	-3.51	40.31	54	-13.69	AVG
7311	53.75	-0.82	52.93	74	-21.07	peak
7311	41.87	-0.82	41.05	54	-12.95	AVG
---	---	---	---	---	---	---
---	---	---	---	---	---	---

Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.

Vertical:

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
4874	60.59	-3.51	57.08	74	-16.92	peak
4874	44.34	-3.51	40.83	54	-13.17	AVG
7311	56.9	-0.82	56.08	74	-17.92	peak
7311	42.07	-0.82	41.25	54	-12.75	AVG
---	---	---	---	---	---	---
---	---	---	---	---	---	---

Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.

HIGH CH11 (802.11n/H20 Mode)/2462
Horizontal:

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
4924	61.23	-3.43	57.8	74	-16.2	peak
4924	44.22	-3.43	40.79	54	-13.21	AVG
7386	56.35	-0.75	55.6	74	-18.4	peak
7386	42.65	-0.75	41.9	54	-12.1	AVG
---	---	---	---	---	---	---
---	---	---	---	---	---	---

Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.

Vertical:

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
4924	60.19	-3.43	56.76	74	-17.24	peak
4924	44.89	-3.43	41.46	54	-12.54	AVG
7386	56.21	-0.75	55.46	74	-18.54	peak
7386	41.3	-0.75	40.55	54	-13.45	AVG
---	---	---	---	---	---	---
---	---	---	---	---	---	---

Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.



LOW CH3 (802.11n/H40 Mode)/2422
Horizontal:

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
4924	60.97	-3.63	57.34	74	-16.66	peak
4924	46.75	-3.63	43.12	54	-10.88	AVG
7386	55.87	-0.94	54.93	74	-19.07	peak
7386	42.78	-0.94	41.84	54	-12.16	AVG
---	---	---	---	---	---	---
---	---	---	---	---	---	---

Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.

Vertical:

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
4924	59.98	-3.63	56.35	74	-17.65	peak
4924	45.22	-3.63	41.59	54	-12.41	AVG
7386	55.25	-0.94	54.31	74	-19.69	peak
7386	41.47	-0.94	40.53	54	-13.47	AVG
---	---	---	---	---	---	---
---	---	---	---	---	---	---

Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.



MID CH6 (802.11n/H40 Mode)/2437
Horizontal:

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
4874	59.29	-3.51	55.78	74	-18.22	peak
4874	44.85	-3.51	41.34	54	-12.66	AVG
7311	54.62	-0.82	53.8	74	-20.2	peak
7311	41.76	-0.82	40.94	54	-13.06	AVG
---	---	---	---	---	---	---
---	---	---	---	---	---	---

Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.

Vertical:

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
4874	58.17	-3.51	54.66	74	-19.34	peak
4874	43.27	-3.51	39.76	54	-14.24	AVG
7311	55.13	-0.82	54.31	74	-19.69	peak
7311	41.92	-0.82	41.1	54	-12.9	AVG
---	---	---	---	---	---	---
---	---	---	---	---	---	---

Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.



HIGH CH9 (802.11n/H40 Mode)/2452
Horizontal:

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
4904	60.08	-3.43	56.65	74	-17.35	peak
4904	46.32	-3.43	42.89	54	-11.11	AVG
7356	56.18	-0.75	55.43	74	-18.57	peak
7356	41.37	-0.75	40.62	54	-13.38	AVG
---	---	---	---	---	---	---
---	---	---	---	---	---	---

Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.

Vertical:

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
4904	58.17	-3.43	54.74	74	-19.26	peak
4904	43.28	-3.43	39.85	54	-14.15	AVG
7356	55.32	-0.75	54.57	74	-19.43	peak
7356	39.18	-0.75	38.43	54	-15.57	AVG
---	---	---	---	---	---	---
---	---	---	---	---	---	---

Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.

Remark:

- (1) Measuring frequencies from 1 GHz to the 25 GHz.
- (2) "F" denotes fundamental frequency; "H" denotes spurious frequency. "E" denotes band edge frequency.
- (3) * denotes emission frequency which appearing within the Restricted Bands specified in provision of 15.205, then the general radiated emission limits in 15.209 apply.
- (4) Data of measurement within this frequency range shown "---" in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (5) The IF bandwidth of EMI Test Receiver between 30MHz to 1GHz was 120KHz, 1 MHz for measuring above 1 GHz, below 30MHz was 10KHz.
- (6) When the test results of Peak Detected below the limits of Average Detected, the Average Detected is not need completed. For example: Top Channel at Fundamental 73.16dBuV/m(PK Value) <93.98(AV Limit), at harmonic 53.20 dBuV/m(PK Value) <54 dBuV/m(AV Limit), the Average Detected not need to completed.



5 BAND EDGE

5.1 Limits

FCC PART 15.247 Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in §15.209, whichever is the lesser attenuation.

5.2 Test Procedure


The band edge compliance of RF radiated emission should be measured by following the guidance in ANSI C63.10 with respect to maximizing the emission by rotating the EUT, measuring the emission while the EUT is situated in three orthogonal planes (if appropriate), adjusting the measurement antenna height and polarization etc. Set RBW to 100KHz and VBM to 300KHz to measure the peak field strength and set RBW to 1MHz and VBW to 10Hz to measure the average radiated field strength. The conducted RF band edge was measured by using a spectrum analyzer. Set span wide enough to capture the highest in-band emission and the emission at the band edge. Set RBW to 100 KHz and VBW to 300 KHz, to measure the conducted peak band edge.

5.3 Test Result

PASS

NOTE: All the test modes completed for test. The worst mode of Radiated Band Edge test in this report.

Operation Mode:
802.11b-Lowest Bandedge
Vertical (Worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2310.000	32.55	-1.00	31.55	54.00	-22.45	Average Detector
	2310.000	45.83	-1.00	44.83	74.00	-29.17	Peak Detector
2	2390.000	34.68	-0.88	33.80	54.00	-20.20	Average Detector
	2390.000	48.99	-0.88	48.11	74.00	-25.89	Peak Detector
3	2400.000	47.10	-0.86	46.24	Delta =36.47dBc		Average Detector
4	2411.400	83.55	-0.84	82.71			Average Detector



802.11b-Highest Bandedge

Vertical (Worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2463.850	93.16	-0.76	92.40	/	/	Average Detector
	2463.400	103.74	-0.76	102.98	/	/	Peak Detector
2	2483.500	45.97	-0.73	45.24	54.00	-8.76	Average Detector
	2483.500	59.45	-0.73	58.72	74.00	-15.28	Peak Detector
3	2500.000	42.03	-0.70	41.33	54.00	-12.67	Average Detector
	2500.000	55.94	-0.70	55.24	74.00	-18.76	Peak Detector



802.11g-Lowest Bandedge

Vertical (Worst case)




No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	
1	2310.000	33.59	-1.00	32.59	54.00	-21.41	Average Detector
	2310.000	46.28	-1.00	45.28	74.00	-28.72	Peak Detector
2	2390.000	40.89	-0.88	40.01	54.00	-13.99	Average Detector
	2390.000	59.82	-0.88	58.94	74.00	-15.06	Peak Detector
3	2400.000	45.38	-0.86	44.52	Delta =34.74dBc		Average Detector
4	2416.320	80.09	-0.83	79.26			Average Detector



802.11g-Highest Bandedge

Vertical (Worst case)




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2461.300	79.55	-0.76	78.79	/	/	Average Detector
	2459.600	105.00	-0.76	104.24	/	/	Peak Detector
2	2483.500	45.06	-0.73	44.33	54.00	-9.67	Average Detector
	2483.500	67.83	-0.73	67.10	74.00	-6.90	Peak Detector
3	2500.000	41.59	-0.70	40.89	54.00	-13.11	Average Detector
	2500.000	57.85	-0.70	57.15	74.00	-16.85	Peak Detector



802.11n-HT20-Lowest Bandedge

Vertical (Worst case)




No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	
1	2310.000	33.36	-1.00	32.36	54.00	-21.64	Average Detector
	2310.000	46.55	-1.00	45.55	74.00	-28.45	Peak Detector
2	2390.000	39.24	-0.88	38.36	54.00	-15.64	Average Detector
	2390.000	63.39	-0.88	62.51	74.00	-11.49	Peak Detector
3	2400.000	43.36	-0.86	42.50	Delta =25.07dBc		Average Detector
4	2412.840	68.41	-0.84	67.57			Average Detector



802.11n-HT20-Highest Bandedge

Vertical (Worst case)




No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	
1	2460.900	81.62	-0.76	80.86	/	/	Average Detector
	2460.950	99.51	-0.76	98.75	/	/	Peak Detector
2	2483.500	43.13	-0.73	42.40	54.00	-11.60	Average Detector
	2483.500	61.51	-0.73	60.78	74.00	-13.22	Peak Detector
3	2500.000	37.79	-0.70	37.09	54.00	-16.91	Average Detector
	2500.000	53.83	-0.70	53.13	74.00	-20.87	Peak Detector



802.11n-HT40-Lowest Bandedge


Vertical (Worst case)



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2310.000	32.71	-1.00	31.71	54.00	-22.29	Average Detector
	2310.000	44.50	-1.00	43.50	74.00	-30.50	Peak Detector
2	2390.000	38.93	-0.88	38.05	54.00	-15.95	Average Detector
	2390.000	60.72	-0.88	59.84	74.00	-14.16	Peak Detector
3	2400.000	44.45	-0.86	43.59	Delta =36.67dBc		Average Detector
4	2413.600	81.10	-0.84	80.26			Average Detector



802.11n-HT40-Highest Bandedge
Vertical (Worst case)



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2454.150	64.53	-0.77	63.76	/	/	Average Detector
	2444.070	97.23	-0.79	96.44	/	/	Peak Detector
2	2483.500	41.91	-0.73	41.18	54.00	-12.82	Average Detector
	2483.500	63.03	-0.73	62.30	74.00	-11.70	Peak Detector
3	2500.000	38.43	-0.70	37.73	54.00	-16.27	Average Detector
	2500.000	57.92	-0.70	57.22	74.00	-16.78	Peak Detector



6 OCCUPIED BANDWIDTH MEASUREMENT

6.1 Test Limit

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(a)(2)	Bandwidth	$\geq 500\text{KHz}$ (6dB bandwidth)	2400-2483.5	PASS

6.2 Test Procedure

1. The EUT was placed on a turn table which is 0.8m above ground plane.
2. Set EUT as normal operation.
3. Based on FCC Part15 C Section 15.247: RBW= 100KHz. VBW= 300 KHz.
4. The useful radiated emission from the EUT was detected by the spectrum analyser with peak detector.

6.3 Measurement Equipment Used

Same as Radiated Emission Measurement

6.4 Test Result

PASS


All the test modes completed for test.



For antenna port 1:


TX 802.11b Mode			
Frequency	6dB Bandwidth (MHz)	Channel Separation (MHz)	Result
2412 MHz	8.403	>=500KHz	PASS
2437 MHz	9.445	>=500KHz	PASS
2462 MHz	7.935	>=500KHz	PASS

CH: 2412MHz






CH: 2437MHz




CH: 2462MHz






TX 802.11g Mode			
Frequency	6dB Bandwidth (MHz)	Channel Separation (MHz)	Result
2412 MHz	15.127	>=500KHz	PASS
2437 MHz	15.177	>=500KHz	PASS
2462 MHz	15.387	>=500KHz	PASS

CH: 2412MHz






CH: 2437MHz




CH: 2462MHz






TX 802.11n/HT20 Mode			
Frequency	6dB Bandwidth (MHz)	Channel Separation (MHz)	Result
2412 MHz	15.772	>=500KHz	PASS
2437 MHz	15.153	>=500KHz	PASS
2462 MHz	15.475	>=500KHz	PASS

CH: 2412MHz






CH: 2437MHz




CH: 2462MHz






TX 802.11n/HT40 Mode			
Frequency	6dB Bandwidth (MHz)	Channel Separation (MHz)	Result
2422 MHz	35.238	>=500KHz	PASS
2437 MHz	35.214	>=500KHz	PASS
2452 MHz	35.269	>=500KHz	PASS

CH: 2422MHz






CH: 2437MHz



CH: 2452MHz






For antenna port 2:


TX 802.11b Mode			
Frequency	6dB Bandwidth (MHz)	Channel Separation (MHz)	Result
2412 MHz	7.991	>=500KHz	PASS
2437 MHz	8.833	>=500KHz	PASS
2462 MHz	9.598	>=500KHz	PASS

CH: 2412MHz






CH: 2437MHz




CH: 2462MHz






TX 802.11g Mode			
Frequency	6dB Bandwidth (MHz)	Channel Separation (MHz)	Result
2412 MHz	15.165	>=500KHz	PASS
2437 MHz	15.175	>=500KHz	PASS
2462 MHz	15.186	>=500KHz	PASS

CH: 2412MHz






CH: 2437MHz




CH: 2462MHz






TX 802.11n/HT20 Mode			
Frequency	6dB Bandwidth (MHz)	Channel Separation (MHz)	Result
2412 MHz	15.467	>=500KHz	PASS
2437 MHz	15.204	>=500KHz	PASS
2462 MHz	15.180	>=500KHz	PASS

CH: 2412MHz






CH: 2437MHz




CH: 2462MHz






TX 802.11n/HT40 Mode			
Frequency	6dB Bandwidth (MHz)	Channel Separation (MHz)	Result
2422 MHz	35.213	>=500KHz	PASS
2437 MHz	35.215	>=500KHz	PASS
2452 MHz	35.232	>=500KHz	PASS

CH: 2422MHz






CH: 2437MHz



CH: 2452MHz





7 POWER SPECTRAL DENSITY TEST

7.1 Test Limit

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247	Power Spectral Density	8 dBm (in any 3KHz)	2400-2483.5	PASS

7.2 Test Procedure

1. The EUT was placed on a turn table which is 0.8m above ground plane.
2. Set EUT as normal operation.
3. Based on FCC Part15 C Section 15.247: RBW= 3KHz. VBW= 10 KHz, Span=3MHz.
4. The useful radiated emission from the EUT was detected by the spectrum analyser with peak detector.

7.3 Measurement Equipment Used

Same as Radiated Emission Measurement

7.4 Test Result


PASS

All the test modes completed for test.

**For antenna port 1**


TX 802.11b Mode			
Frequency	Power Density (dBm)	Limit (dBm)	Result
2412 MHz	-5.49	8	PASS
2437 MHz	-2.061	8	PASS
2462 MHz	-6.183	8	PASS

CH: 2412MHz






CH: 2437MHz




CH: 2462MHz






TX 802.11g Mode			
Frequency	Power Density (dBm)	Limit (dBm)	Result
2412 MHz	-10.17	8	PASS
2437 MHz	-10.93	8	PASS
2462 MHz	-13.16	8	PASS

CH: 2412MHz






CH: 2437MHz




CH: 2462MHz






TX 802.11n/HT20 Mode			
Frequency	Power Density (dBm)	Limit (dBm)	Result
2412 MHz	-8.838	8	PASS
2437 MHz	-9.63	8	PASS
2462 MHz	-12.01	8	PASS

CH: 2412MHz






CH: 2437MHz




CH: 2462MHz






TX 802.11n/HT40 Mode			
Frequency	Power Density (dBm)	Limit (dBm)	Result
2422 MHz	-14.77	8	PASS
2437 MHz	-14.83	8	PASS
2452 MHz	-14.47	8	PASS

CH: 2422MHz






CH: 2437MHz




CH: 2452MHz



**For antenna port 2**


TX 802.11b Mode			
Frequency	Power Density (dBm)	Limit (dBm)	Result
2412 MHz	-3.013	8	PASS
2437 MHz	-4.121	8	PASS
2462 MHz	-4.393	8	PASS

CH: 2412MHz






CH: 2437MHz




CH: 2462MHz






TX 802.11g Mode			
Frequency	Power Density (dBm)	Limit (dBm)	Result
2412 MHz	-9.456	8	PASS
2437 MHz	-9.536	8	PASS
2462 MHz	-10.77	8	PASS

CH: 2412MHz






CH: 2437MHz




CH: 2462MHz






TX 802.11n/HT20 Mode			
Frequency	Power Density (dBm)	Limit (dBm)	Result
2412 MHz	-8.88	8	PASS
2437 MHz	-10.13	8	PASS
2462 MHz	-13.11	8	PASS

CH: 2412MHz






CH: 2437MHz




CH: 2462MHz






TX 802.11n/HT40 Mode			
Frequency	Power Density (dBm)	Limit (dBm)	Result
2422 MHz	-14.13	8	PASS
2437 MHz	-14.63	8	PASS
2452 MHz	-13.65	8	PASS

CH: 2422MHz






CH: 2437MHz



CH: 2452MHz



**For MIMO antenna port 1+antenna port 2**

TX 802.11b Mode			
Frequency	Power Density (dBm)	Limit (dBm)	Result
2412 MHz	-1.08	8	PASS
2437 MHz	0.04	8	PASS
2462 MHz	-2.22	8	PASS
TX 802.11g Mode			
2412 MHz	-6.78	8	PASS
2437 MHz	-7.21	8	PASS
2462 MHz	-8.86	8	PASS
TX 802.11n/HT20 Mode			
2412 MHz	-5.85	8	PASS
2437 MHz	-6.78	8	PASS
2462 MHz	-9.59	8	PASS
TX 802.11n/HT40 Mode			
2422 MHz	-11.55	8	PASS
2437 MHz	-12.22	8	PASS
2452 MHz	-10.97	8	PASS
Note: 1 According to KDB 662911, Result power = $10\log(10^{(\text{ant1}/10)} + 10^{(\text{ant2}/10)})$.			
2 Result unit: W, The end result is converted to units of dBm.			



8 PEAK OUTPUT POWER TEST

8.1 Test Limit

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(b)(3)	Peak Output Power	1 watt or 30dBm	2400-2483.5	PASS

8.2 Test Procedure

1. The EUT was placed on a turn table which is 0.8m above ground plane.
2. The EUT was directly connected to the Power meter.

8.3 Measurement Equipment Used

Same as Radiated Emission Measurement

8.4 Test Result

PASS

All the test modes completed for test.

Test Channel	Frequency	Maximum Peak Conducted Output Power (dBm)			LIMIT
	(MHz)	Antenna port 1	Antenna port 2	MIMO	dBm
TX 802.11b Mode					
CH01	2412	18.21	18.34	/	30
CH06	2437	18.26	18.45	/	30
CH11	2462	18.18	18.58	/	30
TX 802.11g Mode					
CH01	2412	17.48	17.92	/	30
CH06	2437	17.35	17.81	/	30
CH11	2462	17.43	17.87	/	30
TX 802.11n20 Mode					
CH01	2412	16.53	17.07	19.82	30
CH06	2437	16.41	17.24	19.85	30
CH11	2462	16.56	17.12	19.86	30
TX 802.11n40 Mode					
CH03	2422	15.24	15.82	18.55	30
CH06	2437	15.33	15.73	18.54	30
CH09	2452	15.14	15.65	18.41	30

Note: 1 MIMO is Antenna port 1 and Antenna port 2.

2 According to KDB 662911, Result power = $10\log(10^{(\text{ant1}/10)} + 10^{(\text{ant2}/10)})$.

3 Result unit: W, The end result is converted to units of dBm.



9 OUT OF BAND EMISSIONS TEST


9.1 Test Limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.

9.2 Test Procedure

1. The EUT was placed on a turn table which is 0.8m above ground plane.
2. Set EUT as TX operation and connect directly to the spectrum analyzer.
3. Set spectrum analyzer RBW= 100KHz. VBW= 300 KHz
4. Set detected by the spectrum analyser with peak detector.

9.3 Test Setup





9.4 Test Result



PASS



All the test modes completed for test.



Chain 1 TX 802.11b Mode















TX 802.11g Mode















TX 802.11n/HT20 Mode















TX 802.11n/HT40 Mode















Chain 2 TX 802.11b Mode















802.11g Mode















802.11n/H20 Mode















802.11n/HT40 Mode







10 ANTENNA REQUIREMENT

Standard Applicable

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.249, if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

Refer to statement below for compliance.


The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited. Further, this requirement does not apply to intentional radiators that must be professionally installed.

Antenna Connected Construction

The antenna used in this product is a Integral Antenna, The directional gains of antenna used for transmitting for antenna port 1 is 2dBi and antenna port 2 is 2dBi



Antenna port 1

Antenna port 2



11 PHOTOGRAPH OF TEST

11.1 Radiated Emission





11.2 Conducted Emission

