



FCC RF Test Report

APPLICANT : Relay, Inc.
EQUIPMENT : RSM PRO
BRAND NAME : Relay
MODEL NAME : RSMP1
FCC ID : 2AMBHRSMPI
STANDARD : FCC Part 15 Subpart C §15.247
CLASSIFICATION : (DSS) Spread Spectrum Transmitter
TEST DATE(S) : Mar. 21, 2026 ~ Apr. 01, 2026

We, Sporton International Inc. (Kunshan), would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International Inc. (Kunshan), the test report shall not be reproduced except in full.

Jason Jia

Approved by: Jason Jia



Sporton International Inc. (Kunshan)

No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300
People's Republic of China



TABLE OF CONTENTS

REVISION HISTORY.....	3
SUMMARY OF TEST RESULT	4
1 GENERAL DESCRIPTION.....	5
1.1 Applicant.....	5
1.2 Manufacturer.....	5
1.3 Product Feature of Equipment Under Test.....	5
1.4 Product Specification of Equipment Under Test.....	5
1.5 Modification of EUT	5
1.6 Testing Location	6
1.7 Test Software.....	6
1.8 Applicable Standards.....	6
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST.....	7
2.1 Carrier Frequency Channel	7
2.2 Test Mode.....	8
2.3 Connection Diagram of Test System.....	9
2.4 Support Unit used in test configuration and system	10
2.5 EUT Operation Test Setup	10
2.6 Measurement Results Explanation Example.....	10
3 TEST RESULT	11
3.1 Number of Channel Measurement	11
3.2 Hopping Channel Separation Measurement	12
3.3 Dwell Time Measurement.....	13
3.4 20dB and 99% Bandwidth Measurement	14
3.5 Output Power Measurement.....	15
3.6 Conducted Band Edges Measurement.....	16
3.7 Conducted Spurious Emission Measurement	17
3.8 Radiated Band Edges and Spurious Emission Measurement	18
3.9 AC Conducted Emission Measurement.....	22
3.10 Antenna Requirements.....	24
4 LIST OF MEASURING EQUIPMENT.....	25
5 MEASUREMENT UNCERTAINTY	26
APPENDIX A. CONDUCTED TEST RESULTS	
APPENDIX B. AC CONDUCTED EMISSION TEST RESULT	
APPENDIX C. RADIATED SPURIOUS EMISSION	
APPENDIX D. DUTY CYCLE PLOTS	
APPENDIX E. SETUP PHOTOGRAPHS	



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR622605A	Rev. 01	Initial issue of report	Apr. 17, 2026



SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.247(a)(1)	Number of Channels	$\geq 15\text{Chs}$	Pass	-
3.2	15.247(a)(1)	Hopping Channel Separation	$\geq 2/3$ of 20dB BW	Pass	-
3.3	15.247(a)(1)	Dwell Time of Each Channel	$\leq 0.4\text{sec}$ in 31.6sec period	Pass	-
3.4	15.247(a)(1)	20dB Bandwidth	-	Report only	-
3.4	-	99% Bandwidth	-	Report only	-
3.5	15.247(b)(1)	Conducted Output Power	$\leq 125\text{ mW}$	Pass	-
3.6	15.247(d)	Conducted Band Edges	$\leq 20\text{dBc}$	Pass	-
3.7	15.247(d)	Conducted Spurious Emission	$\leq 20\text{dBc}$	Pass	-
3.8	15.247(d)	Radiated Band Edges and Radiated Spurious Emission	15.209(a) & 15.247(d)	Pass	Under limit 9.28 dB at 41.64 MHz
3.9	15.207	AC Conducted Emission	15.207(a)	Pass	Under limit 12.34 dB at 0.538 MHz
3.10	15.203 & 15.247(b)	Antenna Requirement	15.203 & 15.247(b)	Pass	-

Conformity Assessment Condition:

- The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/manufacture who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account.
- The measurement uncertainty please refer to each test result in the section "Measurement Uncertainty"

Disclaimer:

The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.



1 General Description

1.1 Applicant

Relay, Inc.

2230 Bandmate Way, Suite 500, Raleigh, NC 27607 USA

1.2 Manufacturer

Bluebank Communication Technology Co., Ltd

NO. 6, Chanyi Road , Yubei District, Chongqing P.R. China 400000

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	RSM PRO
Brand Name	Relay
Model Name	RSMP1
FCC ID	2AMBHRSMP1
SN	Conducted: RSMPRO01260221 Conduction: RSMPRO01260255 Radiation: RSMPRO01260002
EUT Stage	Identical Prototype

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.4 Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx/Rx Frequency Range	2402 MHz ~ 2480 MHz
Number of Channels	79
Carrier Frequency of Each Channel	2402+n*1 MHz; n=0~78
Maximum Output Power to Antenna	Bluetooth BR(1Mbps) : 13.36 dBm (0.0217 W) Bluetooth EDR (2Mbps) : 12.34 dBm (0.0171 W) Bluetooth EDR (3Mbps) : 12.81 dBm (0.0191 W)
99% Occupied Bandwidth	Bluetooth BR(1Mbps) : 0.872MHz Bluetooth EDR (2Mbps) : 1.169MHz Bluetooth EDR (3Mbps) : 1.157MHz
Antenna Type / Gain	FPC Antenna type with gain 0.88 dBi
Type of Modulation	Bluetooth BR (1Mbps) : GFSK Bluetooth EDR (2Mbps) : $\pi/4$ -DQPSK Bluetooth EDR (3Mbps) : 8-DPSK

1.5 Modification of EUT

No modifications are made to the EUT during all test items.



1.6 Testing Location

Sporton International Inc. (Kunshan) is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.02.

Test Firm	Sporton International Inc. (Kunshan)		
Test Site Location	No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300 People's Republic of China TEL : +86-512-57900158		
Test Site No.	Sporton Site No.	FCC Designation No.	FCC Test Firm Registration No.
	CO01-KS 03CH03-KS TH01-KS	CN1257	314309

1.7 Test Software

Item	Site	Manufacturer	Name	Version
1.	TH01-KS	Tonscend	JS1120-3 test system China_210602	3.3.10
2.	03CH03-KS	AUDIX	E3	210616
3.	CO01-KS	AUDIX	E3	6.2009-8-24

1.8 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR Part 15 Subpart C §15.247
- ♦ FCC KDB 558074 D01 15.247 Meas Guidance v05r02
- ♦ ANSI C63.10-2020+Cor.1-2023
- ♦

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.



2 Test Configuration of Equipment Under Test

2.1 Carrier Frequency Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)
2400-2483.5 MHz	0	2402	27	2429	54	2456
	1	2403	28	2430	55	2457
	2	2404	29	2431	56	2458
	3	2405	30	2432	57	2459
	4	2406	31	2433	58	2460
	5	2407	32	2434	59	2461
	6	2408	33	2435	60	2462
	7	2409	34	2436	61	2463
	8	2410	35	2437	62	2464
	9	2411	36	2438	63	2465
	10	2412	37	2439	64	2466
	11	2413	38	2440	65	2467
	12	2414	39	2441	66	2468
	13	2415	40	2442	67	2469
	14	2416	41	2443	68	2470
	15	2417	42	2444	69	2471
	16	2418	43	2445	70	2472
	17	2419	44	2446	71	2473
	18	2420	45	2447	72	2474
	19	2421	46	2448	73	2475
	20	2422	47	2449	74	2476
	21	2423	48	2450	75	2477
	22	2424	49	2451	76	2478
	23	2425	50	2452	77	2479
	24	2426	51	2453	78	2480
	25	2427	52	2454	-	-
	26	2428	53	2455	-	-

2.2 Test Mode


- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (Z/X plane) were recorded in this report, and the worst mode of radiated spurious emissions is Bluetooth 1Mbps mode, and recorded in this report.
- b. AC power line Conducted Emission was tested under maximum output power.

The following summary table is showing all test modes to demonstrate in compliance with the standard.


Summary table of Test Cases			
Test Item	Data Rate / Modulation		
	Bluetooth BR 1Mbps GFSK	Bluetooth EDR 2Mbps $\pi/4$ -DQPSK	Bluetooth EDR 3Mbps 8-DPSK
Conducted Test Cases	Mode 1: CH00_2402 MHz	Mode 4: CH00_2402 MHz	Mode 7: CH00_2402 MHz
	Mode 2: CH39_2441 MHz	Mode 5: CH39_2441 MHz	Mode 8: CH39_2441 MHz
	Mode 3: CH78_2480 MHz	Mode 6: CH78_2480 MHz	Mode 9: CH78_2480 MHz
Radiated Test Cases	Bluetooth BR 1Mbps GFSK		
	Mode 1: CH00_2402 MHz		
	Mode 2: CH39_2441 MHz		
AC Conducted Emission	Mode 3: CH78_2480 MHz		
	Mode 1 : BT Link + USB cable + Adapter + Earphone		
	Remark: For radiated test cases, the worst mode data rate 1Mbps was reported only, because this data rate has the highest RF output power at preliminary tests, and no other significantly frequencies found in conducted spurious emission.		

2.3 Connection Diagram of Test System

AC Conducted Emission:



Radiated Emission:



2.4 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	Relay device	Relay	N/A	N/A	N/A	N/A
2.	Earphone	N/A	N/A	N/A	N/A	N/A
3.	Adapter	N/A	N/A	N/A	N/A	N/A
4.	BT Base Station	R&S	CBT	N/A	N/A	Unshielded, 1.8m

2.5 EUT Operation Test Setup

For Bluetooth function, the engineering test program was provided and enabled to make EUT connect with Bluetooth base station to continuous transmit.

For AC power line conducted emissions, the EUT was set to connect with the Relay device under large package sizes transmission.

2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example :

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 2.11 dB and 20dB attenuator.

$$\begin{aligned}\text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)} \\ &= 2.11 + 20 = 22.11 \text{ (dB)}\end{aligned}$$

3 Test Result

3.1 Number of Channel Measurement

3.1.1 Limits of Number of Hopping Frequency

Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels.


3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedure

1. The testing follows ANSI C63.10-2020 clause 7.8.3.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Enable the EUT hopping function.
5. Use the following spectrum analyzer settings: Span = the frequency band of operation;
RBW = 300kHz; VBW $\geq$ RBW; Sweep = auto; Detector function = peak; Trace = max hold.
6. The number of hopping frequency used is defined as the number of total channel.
7. Record the measurement data derived from spectrum analyzer.

3.1.4 Test Setup



3.1.5 Test Result of Number of Hopping Frequency

Please refer to Appendix A.

3.2 Hopping Channel Separation Measurement

3.2.1 Limit of Hopping Channel Separation

Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater.


3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.2.3 Test Procedures

1. The testing follows ANSI C63.10-2020 clause 7.8.2.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Enable the EUT hopping function.
5. Use the following spectrum analyzer settings:
Span = wide enough to capture the peaks of two adjacent channels;
RBW = 300kHz; VBW $\geq$ RBW; Sweep = auto; Detector function = peak; Trace = max hold.
6. Measure and record the results in the test report.

3.2.4 Test Setup



3.2.5 Test Result of Hopping Channel Separation

Please refer to Appendix A.

3.3 Dwell Time Measurement

3.3.1 Limit of Dwell Time

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.


3.3.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.3.3 Test Procedures

1. The testing follows ANSI C63.10-2020 clause 7.8.4.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Enable the EUT hopping function.
5. Use the following spectrum analyzer settings: Span = zero span, centered on a hopping channel; RBW = 1 MHz; VBW $\geq$ RBW; Sweep = as necessary to capture the entire dwell time per hopping channel; Detector function = peak; Trace = max hold.
6. Measure and record the results in the test report.

3.3.4 Test Setup



3.3.5 Test Result of Dwell Time

Please refer to Appendix A.

3.4 20dB and 99% Bandwidth Measurement

3.4.1 Limit of 20dB and 99% Bandwidth

Reporting only


3.4.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.4.3 Test Procedures

1. The testing follows ANSI C63.10-2020 clause 6.9.2 and 6.9.3.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Use the following spectrum analyzer settings for 20dB Bandwidth measurement.
Span = approximately 2 to 5 times the 20 dB bandwidth, centered on a hopping channel;
The RBW is set to 1% to 5% of the 99% OBW, the VBW is set to 3 times the RBW;
Sweep = auto; Detector function = peak;
Trace = max hold.
5. Use the following spectrum analyzer settings for 99 % Bandwidth measurement.
Span = approximately 1.5 to 5 times the 99% bandwidth, centered on a hopping channel;
The RBW is set to 1% to 5% of the 99% OBW, the VBW is set to 3 times the RBW;
Sweep = auto; Detector function = peak;
Trace = max hold.
6. Measure and record the results in the test report.

3.4.4 Test Setup



3.4.5 Test Result of 20dB and 99% Occupied Bandwidth

Please refer to Appendix A.

3.5 Output Power Measurement

3.5.1 Limit of Output Power

The maximum peak conducted output power of the intentional radiator shall not exceed the following:
For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band 0.125 watts. The power limit for 1Mbps, 2Mbps, 3Mbps and AFH modes are 0.125 watts.


3.5.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.5.3 Test Procedures

1. The testing follows ANSI C63.10-2020 clause 7.8.5.
2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Measure the conducted output power with cable loss and record the results in the test report.
5. Measure and record the results in the test report.

3.5.4 Test Setup



3.5.5 Test Result of Peak Output Power

Please refer to Appendix A.

3.5.6 Test Result of Average Output Power (Reporting Only)

Please refer to Appendix A.

3.6 Conducted Band Edges Measurement

3.6.1 Limit of Band Edges

In any 100 kHz bandwidth outside the intentional radiation frequency band, the radio frequency power shall be at least 20 dB below the highest level of the radiated power. In addition, radiated emissions which fall in the restricted bands must also comply with the radiated emission limits.


3.6.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.6.3 Test Procedures

1. The testing follows ANSI C63.10-2020 clause 7.8.7.
2. Set to the maximum power setting and enable the EUT transmit continuously.
3. Set RBW = 100kHz, VBW = 300kHz. Band edge emissions must be at least 20 dB down from the highest emission level within the authorized band as measured with a 100kHz RBW. The attenuation shall be 30 dB instead of 20 dB when RMS conducted output power procedure is used.
4. Enable hopping function of the EUT and then repeat step 2. and 3.
5. Measure and record the results in the test report.

3.6.4 Test Setup



3.6.5 Test Result of Conducted Band Edges

Please refer to Appendix A.

3.6.6 Test Result of Conducted Hopping Mode Band Edges

Please refer to Appendix A.

3.7 Conducted Spurious Emission Measurement

3.7.1 Limit of Spurious Emission Measurement

In any 100 kHz bandwidth outside the intentional radiation frequency band, the radio frequency power shall be at least 20 dB below the highest level of the radiated power. In addition, radiated emissions which fall in the restricted bands must also comply with the radiated emission limits.


3.7.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.7.3 Test Procedure

1. The testing follows ANSI C63.10-2020 clause 7.8.7.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 kHz, VBW = 300kHz, scan up through 10th harmonic. All harmonics / spurs must be at least 20 dB down from the highest emission level within the authorized band as measured with a 100 kHz RBW.
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

3.7.4 Test Setup



3.7.5 Test Result of Conducted Spurious Emission

Please refer to Appendix A.

3.8 Radiated Band Edges and Spurious Emission Measurement

3.8.1 Limit of Radiated Band Edges and Spurious Emission

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. In addition, radiated emissions which fall in the restricted bands must also comply with the limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.8.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.


3.8.3 Test Procedures

1. The testing follows ANSI C63.10-2020 clause 6.3, 6.5 and 6.6.
2. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
3. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
4. For each suspected emission, the EUT was arranged to its worst case and then tune the Antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level to comply with the guidelines.
5. Set to the maximum power setting and enable the EUT transmit continuously.
6. Use the following spectrum analyzer settings:
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Set RBW=100 kHz for $f < 1$ GHz, RBW=1MHz for $f > 1$ GHz ; VBW $\geq$ RBW; Sweep = auto; Detector function = peak; Trace = max hold for peak
 - (3) For average measurement: use duty cycle correction factor method per 15.35(c).
Duty cycle = On time/100 milliseconds
On time = $N_1 * L_1 + N_2 * L_2 + \dots + N_{n-1} * L_{n-1} + N_n * L_n$
Where N_1 is number of type 1 pulses, L_1 is length of type 1 pulses, etc.
Average Emission Level = Peak Emission Level + $20 * \log(\text{Duty cycle})$
7. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
8. For testing below 1GHz, if the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the CISPR quasi-peak method and reported.
9. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than peak limit (that means the emission level in average mode also complies with the limit in average mode), then peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.


Note: The average levels were calculated from the peak level corrected with duty cycle correction factor (-24.73dB) derived from $20 \log(\text{dwell time}/100\text{ms})$. This correction is only for signals that hop with the fundamental signal, such as band-edge and harmonic. Other spurious signals that are independent of the hopping signal would not use this correction.

3.8.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz





3.8.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

There is a comparison data of both open-field test site and semi-Anechoic chamber, and the result came out very similar.

3.8.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix C.

3.8.7 Test Result of Radiated Spurious Emission (30MHz ~ 10th Harmonic or 40GHz, whichever is lower)

Please refer to Appendix C.

3.8.8 Duty cycle correction factor for average measurement

Please refer to Appendix D.

3.9 AC Conducted Emission Measurement

3.9.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dBμV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.9.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.9.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.

3.9.4 Test Setup



3.9.5 Test Result of AC Conducted Emission

Please refer to Appendix B.



3.10 Antenna Requirements

3.10.1 Standard Applicable

If directional gain of transmitting antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the rule.

3.10.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.10.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.



4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
EMI Test Receiver	Keysight	N9038A	MY56400004	3Hz~8.5GHz;Max 30dBm	Oct. 10, 2025	Mar. 21, 2026	Oct. 09, 2026	Radiation (03CH03-KS)
EXA Spectrum Analyzer	Keysight	N9010A	MY55150244	10Hz~44GHz	Apr. 18, 2025	Mar. 21, 2026	Apr. 17, 2026	Radiation (03CH03-KS)
Active loop antenna	R&S	HFH2-Z2E	101125	9kHz~30MHz	Aug. 10, 2025	Mar. 21, 2026	Aug. 09, 2026	Radiation (03CH03-KS)
Bilog Antenna	TeseQ	CBL6111D	44483	30MHz~1GHz	Nov. 22, 2025	Mar. 21, 2026	Nov. 21, 2026	Radiation (03CH03-KS)
Double Ridge Horn Antenna	ETS-Lindgren	3117	00251982	1GHz~18GHz	Aug. 22, 2025	Mar. 21, 2026	Aug. 21, 2026	Radiation (03CH03-KS)
SHF-EHF Horn	com-power	AH-840	101116	18GHz~40GHz	Oct. 18, 2025	Mar. 21, 2026	Oct. 17, 2026	Radiation (03CH03-KS)
Amplifier	SONOMA	310N	380826	9KHz~1GHz	Jul. 02, 2025	Mar. 21, 2026	Jul. 01, 2026	Radiation (03CH03-KS)
Amplifier	EM	EM18G40GA	060851	18~40GHz	Dec. 26, 2025	Mar. 21, 2026	Dec. 25, 2026	Radiation (03CH03-KS)
high gain Amplifier	EM	EM01G18GA	060834	1Ghz~18Ghz	Dec. 26, 2025	Mar. 21, 2026	Dec. 25, 2026	Radiation (03CH03-KS)
Amplifier	EM	EM01G18GA	060892	1Ghz~18Ghz	Oct. 11, 2025	Mar. 21, 2026	Oct. 10, 2026	Radiation (03CH03-KS)
AC Power Source	Chroma	61601	F104090004	N/A	NCR	Mar. 21, 2026	NCR	Radiation (03CH03-KS)
Turn Table	ChamPro	EM 1000-T	060762-T	0~360 degree	NCR	Mar. 21, 2026	NCR	Radiation (03CH03-KS)
Antenna Mast	ChamPro	EM 1000-A	060762-A	1 m~4 m	NCR	Mar. 21, 2026	NCR	Radiation (03CH03-KS)
EMI Receiver	R&S	ESCI7	100768	9kHz~7GHz;	Apr. 16, 2025	Mar. 29, 2026	Apr. 15, 2026	Conduction (CO01-KS)
AC LISN (for auxiliary equipment)	MessTec	AN3016	060103	9kHz~30MHz	Jul. 03, 2025	Mar. 29, 2026	Jul. 02, 2026	Conduction (CO01-KS)
AC LISN	MessTec	AN3016	060105	9kHz~30MHz	Dec. 24, 2025	Mar. 29, 2026	Dec. 23, 2026	Conduction (CO01-KS)
AC Power Source	Ouhan	APW-130NYT	202201040060	AC 0V~300V,45Hz~1000Hz	Apr. 16, 2025	Mar. 29, 2026	Apr. 15, 2026	Conduction (CO01-KS)
Spectrum Analyzer	R&S	FSV40	101040	10Hz~40GHz	Jul. 07, 2025	Apr. 01, 2026	Jul. 06, 2026	Conducted (TH01-KS)
Pulse Power Sensor	Anritsu	MA2411B	0917070	300MHz~40GHz	Jul. 07, 2025	Apr. 01, 2026	Jul. 06, 2026	Conducted (TH01-KS)
Power Meter	Anritsu	ML2495A	1005002	50MHz Bandwidth	Dec. 25, 2025	Apr. 01, 2026	Dec. 24, 2026	Conducted (TH01-KS)

NCR: No Calibration Required

5 Measurement Uncertainty

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI 63.10. All the measurement uncertainty value were shown with a coverage K=2 to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

Uncertainty of Conducted Measurement

Conducted Spurious Emission & Bandedge	±2.00 dB
Occupied Channel Bandwidth	±0.384%
Conducted Power	±0.90 dB
Conducted Power Spectral Density	±1.70 dB
Frequency	±0.38 ppm

Uncertainty of AC Conducted Emission Measurement (0.15 MHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	2.84 dB
---	---------

Uncertainty of Radiated Emission Measurement (9 KHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	3.3 dB
---	--------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	6.2 dB
---	--------

Uncertainty of Radiated Emission Measurement (1 GHz ~ 18 GHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	4.88 dB
---	---------

Uncertainty of Radiated Emission Measurement (18 GHz ~ 40 GHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	5.32 dB
---	---------

----- THE END -----



Appendix A. Conducted Test Results

Ambient Condition: 25 °C, 45 %RH

Test Date: 2026.4.1

Test Engineer: ZHU


20dB Emission Bandwidth


Test Result


TestMode	Antenna	Freq(MHz)	20dB EBW[MHz]	FL[MHz]	FH[MHz]
DH5	Ant1	2402	0.95	2401.51	2402.46
		2441	0.95	2440.51	2441.46
		2480	0.95	2479.50	2480.46
2DH1	Ant1	2402	1.30	2401.31	2402.61
		2441	1.30	2440.31	2441.61
		2480	1.30	2479.31	2480.61
3DH1	Ant1	2402	1.27	2401.34	2402.61
		2441	1.26	2440.34	2441.60
		2480	1.27	2479.34	2480.61






Test Graphs














Occupied Channel Bandwidth



Test Result


TestMode	Antenna	Freq(MHz)	OCB [MHz]	FL[MHz]	FH[MHz]
DH5	Ant1	2402	0.872	2401.5355	2402.4076
		2441	0.869	2440.5355	2441.4046
		2480	0.866	2479.5355	2480.4016
2DH1	Ant1	2402	1.169	2401.3796	2402.5485
		2441	1.169	2440.3766	2441.5455
		2480	1.169	2479.3766	2480.5455
3DH1	Ant1	2402	1.157	2401.4036	2402.5604
		2441	1.154	2440.4036	2441.5574
		2480	1.154	2479.4036	2480.5574





Test Graphs











Maximum conducted output power

Test Result Peak

TestMode	Antenna	CH.	Peak Power (dBm)	Power Limit (dBm)	Pass/Fail	Power Setting
DH5	Ant 1	0	13.31	20.97	Pass	Default
		39	13.36	20.97	Pass	Default
		78	13.35	20.97	Pass	Default
2DH1	Ant 1	0	12.25	20.97	Pass	Default
		39	12.30	20.97	Pass	Default
		78	12.34	20.97	Pass	Default
3DH1	Ant 1	0	12.73	20.97	Pass	Default
		39	12.74	20.97	Pass	Default
		78	12.81	20.97	Pass	Default

Test Result Average

TestMode	Antenna	CH.	Avg Power (dBm)	Pass/Fail	Power Setting
DH5	Ant 1	0	13.28	Pass	Default
		39	13.30	Pass	Default
		78	13.29	Pass	Default
2DH1	Ant 1	0	9.80	Pass	Default
		39	9.67	Pass	Default
		78	9.93	Pass	Default
3DH1	Ant 1	0	9.68	Pass	Default
		39	9.82	Pass	Default
		78	9.87	Pass	Default




Carrier frequency separation



Test Result



TestMode	Antenna	Freq(MHz)	Result[MHz]	Limit[MHz]	Verdict
DH5	Ant1	2402	1	≥ 0.633	PASS
		2441	1.004	≥ 0.633	PASS
		2480	0.996	≥ 0.633	PASS
2DH1	Ant1	2402	1	≥ 0.867	PASS
		2441	1.004	≥ 0.867	PASS
		2480	0.996	≥ 0.867	PASS
3DH1	Ant1	2402	1.004	≥ 0.847	PASS
		2441	1	≥ 0.840	PASS
		2480	1.004	≥ 0.847	PASS






Test Graphs











Time of occupancy

Test Result


TestMode	Antenna	Hopping Channel Number Rate	Hops Over Occupancy Time(hops)	Package Transfer Time (msec)	Dwell Time (sec)	Limits (sec)	Pass/Fail
Normal	Ant 1	79	106.67	2.9087	0.31	0.4	Pass
AFH	Ant 1	20	53.33	2.9087	0.16	0.4	Pass

Remark:

1. In normal mode, hopping rate is 1600 hops/s with 6 slots (5 Transmit and 1 Receive slot)
in 79 hopping channels.
With channel hopping rate (1600 / 6 / 79) in Occupancy Time Limit (0.4 x 79) (s),
Hops Over Occupancy Time comes to (1600 / 6 / 79) x (0.4 x 79) = 106.67 hops.
2. In AFH mode, hopping rate is 800 hops/s with 6 slots in 20 hopping channels.
With channel hopping rate (800 / 6 / 20) in Occupancy Time Limit (0.4 x 20) (s),
Hops Over Occupancy Time comes to (800 / 6 / 20) x (0.4 x 20) = 53.33 hops.
3. Dwell Time(s) = Hops Over Occupancy Time (hops) x Package Transfer Time



Test Graphs




Number of hopping channels

Test Result

TestMode	Antenna	Freq(MHz)	Result[Num]	Limit[Num]	Verdict
DH5	Ant1	Hop	79	≥15	PASS

Test Graphs






Band edge measurements


Test Result


TestMode	Antenna	ChName	Freq(MHz)	RefLevel [dBm]	Result [dBm]	Limit [dBm]	Verdict
DH5	Ant1	Low	2402	13.07	-42.19	≤ -6.93	PASS
		High	2480	12.90	-42.94	≤ -7.1	PASS
		Low	Hop_2402	12.71	-44.07	≤ -7.29	PASS
		High	Hop_2480	13.25	-42.97	≤ -6.75	PASS
2DH1	Ant1	Low	2402	9.33	-43.12	≤ -10.67	PASS
		High	2480	9.29	-42.33	≤ -10.71	PASS
		Low	Hop_2402	9.15	-43.55	≤ -10.85	PASS
		High	Hop_2480	9.50	-42.87	≤ -10.5	PASS
3DH1	Ant1	Low	2402	9.31	-42.41	≤ -10.69	PASS
		High	2480	9.28	-43.16	≤ -10.72	PASS
		Low	Hop_2402	9.19	-43.87	≤ -10.81	PASS
		High	Hop_2480	9.60	-42.24	≤ -10.4	PASS





Test Graphs















Conducted Spurious Emission



Test Result



TestMode	Antenna	Freq(MHz)	FreqRange [MHz]	RefLevel [dBm]	Result [dBm]	Limit [dBm]	Verdict
DH5	Ant1	2402	Reference	13.06	13.06	---	PASS
			30~1000	13.06	-44.52	≤-6.94	PASS
			1000~26500	13.06	-35.99	≤-6.94	PASS
		2441	Reference	13.25	13.25	---	PASS
			30~1000	13.25	-44.43	≤-6.75	PASS
			1000~26500	13.25	-35.26	≤-6.75	PASS
		2480	Reference	12.86	12.86	---	PASS
			30~1000	12.86	-44.67	≤-7.14	PASS
			1000~26500	12.86	-35.86	≤-7.14	PASS
2DH1	Ant1	2402	Reference	9.28	9.28	---	PASS
			30~1000	9.28	-44.79	≤-10.72	PASS
			1000~26500	9.28	-35.75	≤-10.72	PASS
		2441	Reference	9.47	9.47	---	PASS
			30~1000	9.47	-44.11	≤-10.53	PASS
			1000~26500	9.47	-36.24	≤-10.53	PASS
		2480	Reference	9.20	9.20	---	PASS
			30~1000	9.20	-44.46	≤-10.8	PASS
			1000~26500	9.20	-35.82	≤-10.8	PASS
3DH1	Ant1	2402	Reference	9.26	9.26	---	PASS
			30~1000	9.26	-45.11	≤-10.74	PASS
			1000~26500	9.26	-35.41	≤-10.74	PASS
		2441	Reference	9.45	9.45	---	PASS
			30~1000	9.45	-44.78	≤-10.55	PASS
			1000~26500	9.45	-35.87	≤-10.55	PASS
		2480	Reference	9.20	9.20	---	PASS
			30~1000	9.20	-44.72	≤-10.8	PASS
			1000~26500	9.20	-35.99	≤-10.8	PASS







Test Graphs































Date: 1.APR.2026 16:59:27




Date: 1.APR.2026 16:59:34













Appendix B. AC Conducted Emission Test Results



Test Engineer :	Amos	Temperature :	25.3~26.2°C
		Relative Humidity :	38~40%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Remark :	All emissions not reported here are more than 10 dB below the prescribed limit.		



Site : CO01-KS
Condition : 15C RSS247-QP LISN-100334-N 2025 NEUTRAL

	Freq	Level	Over	Limit	Read	LISN	Cable	Remark
	MHz	dBuV	Limit	Line	Level	Factor	Loss	
			dB	dBuV	dBuV	dB	dB	
1	0.177	40.51	-24.13	64.64	20.49	9.56	10.46	QP
2	0.177	30.21	-24.43	54.64	10.19	9.56	10.46	Average
3	0.538	43.36	-12.64	56.00	23.21	9.76	10.39	QP
4 *	0.538	33.66	-12.34	46.00	13.51	9.76	10.39	Average
5	1.106	39.41	-16.59	56.00	19.19	9.95	10.27	QP
6	1.106	28.41	-17.59	46.00	8.19	9.95	10.27	Average
7	1.381	36.06	-19.94	56.00	15.90	9.90	10.26	QP
8	1.381	26.96	-19.04	46.00	6.80	9.90	10.26	Average
9	2.422	36.59	-19.41	56.00	16.60	9.76	10.23	QP
10	2.422	26.79	-19.21	46.00	6.80	9.76	10.23	Average
11	3.661	35.45	-20.55	56.00	15.60	9.64	10.21	QP
12	3.661	28.05	-17.95	46.00	8.20	9.64	10.21	Average
13	11.438	46.26	-13.74	60.00	26.30	9.71	10.25	QP
14	11.438	31.46	-18.54	50.00	11.50	9.71	10.25	Average

Note:

- Level(dBuV) = Read Level(dBuV) + LISN Factor(dB) + Cable Loss(dB)
- Over Limit(dB) = Level(dBuV) – Limit Line(dBuV)



Appendix C Radiated Spurious Emission

Test Engineer :	Jerry Xu	Relative Humidity :	41~ 42%
		Temperature :	22~23℃



Radiated Spurious Emission Test Modes

Mode	Band (MHz)	Antenna	Modulation	Channel	Frequency	Data Rate	RU	Remark
Mode 1	2400-2483.5	1	Bluetooth BR_GFSK	00	2402	1Mbps	-	-
Mode 2	2400-2483.5	1	Bluetooth BR_GFSK	39	2441	1Mbps	-	-
Mode 3	2400-2483.5	1	Bluetooth BR_GFSK	78	2480	1Mbps	-	-



Summary of each worse mode

Mode	Modulation	Ch.	Freq. (MHz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Pol.	Peak Avg.	Result	Remark
1	Bluetooth BR_GFSK	00	2384.49	49.85	74.00	-24.15	H	PEAK	Pass	Band Edge
1	Bluetooth BR_GFSK	00	9607.50	49.33	81.02	-31.69	V	PEAK	Pass	Harmonic
2	Bluetooth BR_GFSK	39	-	-	-	-	-	-	-	Band Edge
2	Bluetooth BR_GFSK	39	7323.00	43.68	74.00	-30.32	H	PEAK	Pass	Harmonic
3	Bluetooth BR_GFSK	78	2483.56	59.78	74.00	-14.22	V	PEAK	Pass	Band Edge
3	Bluetooth BR_GFSK	78	7440.00	44.32	74.00	-29.68	H	PEAK	Pass	Harmonic



Mode	1																																																																																																																								
	Band Edge																																																																																																																								
	2400-2483.5_Bluetooth BR_GFSK_CH00_2402MHz																																																																																																																								
ANT	1																																																																																																																								
Pol.	Horizontal						Fundamental																																																																																																																		
Peak																																																																																																																									
	<table><tr><th></th><th>Limit</th><th>Over</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Limit</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2384.49</td><td>49.85</td><td>74.00</td><td>-24.15</td><td>41.41</td><td>31.88</td><td>7.16</td><td>36.60</td><td>6.00</td><td>372</td><td>29 PEAK</td></tr><tr><td>2</td><td>2384.49</td><td>25.12</td><td>54.00</td><td>-28.88</td><td>16.68</td><td>31.88</td><td>7.16</td><td>36.60</td><td>6.00</td><td>372</td><td>29 AVERAGE</td></tr></table>							Limit	Over	Read	Ant	Cable	Preamp	Aux	APos	TPos	Freq	Level	Line	Limit	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2384.49	49.85	74.00	-24.15	41.41	31.88	7.16	36.60	6.00	372	29 PEAK	2	2384.49	25.12	54.00	-28.88	16.68	31.88	7.16	36.60	6.00	372	29 AVERAGE	<table><tr><th></th><th>Limit</th><th>Over</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Limit</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2402.00</td><td>103.16</td><td>-----</td><td>-----</td><td>94.55</td><td>32.01</td><td>7.18</td><td>36.58</td><td>6.00</td><td>372</td><td>29 PEAK</td></tr><tr><td>2</td><td>2402.00</td><td>78.43</td><td>-----</td><td>-----</td><td>69.82</td><td>32.01</td><td>7.18</td><td>36.58</td><td>6.00</td><td>372</td><td>29 AVERAGE</td></tr></table>						Limit	Over	Read	Ant	Cable	Preamp	Aux	APos	TPos	Freq	Level	Line	Limit	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2402.00	103.16	-----	-----	94.55	32.01	7.18	36.58	6.00	372	29 PEAK	2	2402.00	78.43	-----	-----	69.82	32.01	7.18	36.58	6.00	372	29 AVERAGE
		Limit	Over	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																															
	Freq	Level	Line	Limit	Level	Factor	Loss	Factor	Factor	Remark																																																																																																															
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																															
1	2384.49	49.85	74.00	-24.15	41.41	31.88	7.16	36.60	6.00	372	29 PEAK																																																																																																														
2	2384.49	25.12	54.00	-28.88	16.68	31.88	7.16	36.60	6.00	372	29 AVERAGE																																																																																																														
	Limit	Over	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																																
Freq	Level	Line	Limit	Level	Factor	Loss	Factor	Factor	Remark																																																																																																																
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																															
1	2402.00	103.16	-----	-----	94.55	32.01	7.18	36.58	6.00	372	29 PEAK																																																																																																														
2	2402.00	78.43	-----	-----	69.82	32.01	7.18	36.58	6.00	372	29 AVERAGE																																																																																																														





Mode	1																																																																																																																											
	Band Edge																																																																																																																											
	2400-2483.5_Bluetooth BR_GFSK_CH00_2402MHz																																																																																																																											
ANT	1																																																																																																																											
Pol.	Vertical						Fundamental																																																																																																																					
Peak																																																																																																																												
	<table><tr><th></th><th>Limit</th><th>Over</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Limit</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2389.69</td><td>49.67</td><td>74.00</td><td>-24.33</td><td>41.18</td><td>31.92</td><td>7.16</td><td>36.59</td><td>6.00</td><td>173</td><td>253</td><td>PEAK</td></tr><tr><td>2</td><td>2389.69</td><td>24.94</td><td>54.00</td><td>-29.06</td><td>16.45</td><td>31.92</td><td>7.16</td><td>36.59</td><td>6.00</td><td>173</td><td>253</td><td>AVERAGE</td></tr></table>							Limit	Over	Read	Ant	Cable	Preamp	Aux	APos	TPos	Freq	Level	Line	Limit	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2389.69	49.67	74.00	-24.33	41.18	31.92	7.16	36.59	6.00	173	253	PEAK	2	2389.69	24.94	54.00	-29.06	16.45	31.92	7.16	36.59	6.00	173	253	AVERAGE	<table><tr><th></th><th>Limit</th><th>Over</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Limit</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2402.00</td><td>110.24</td><td>-----</td><td>101.63</td><td>32.01</td><td>7.18</td><td>36.58</td><td>6.00</td><td>173</td><td>253</td><td>PEAK</td></tr><tr><td>2</td><td>2402.00</td><td>85.51</td><td>-----</td><td>76.90</td><td>32.01</td><td>7.18</td><td>36.58</td><td>6.00</td><td>173</td><td>253</td><td>AVERAGE</td></tr></table>							Limit	Over	Read	Ant	Cable	Preamp	Aux	APos	TPos	Freq	Level	Line	Limit	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2402.00	110.24	-----	101.63	32.01	7.18	36.58	6.00	173	253	PEAK	2	2402.00	85.51	-----	76.90	32.01	7.18	36.58	6.00	173	253	AVERAGE
		Limit	Over	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																																		
	Freq	Level	Line	Limit	Level	Factor	Loss	Factor	Factor	Remark																																																																																																																		
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																		
1	2389.69	49.67	74.00	-24.33	41.18	31.92	7.16	36.59	6.00	173	253	PEAK																																																																																																																
2	2389.69	24.94	54.00	-29.06	16.45	31.92	7.16	36.59	6.00	173	253	AVERAGE																																																																																																																
	Limit	Over	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																																			
Freq	Level	Line	Limit	Level	Factor	Loss	Factor	Factor	Remark																																																																																																																			
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																		
1	2402.00	110.24	-----	101.63	32.01	7.18	36.58	6.00	173	253	PEAK																																																																																																																	
2	2402.00	85.51	-----	76.90	32.01	7.18	36.58	6.00	173	253	AVERAGE																																																																																																																	





Mode	1																																																																																																																						
	Harmonic																																																																																																																						
	2400-2483.5_Bluetooth BR_GFSK_CH00_2402MHz																																																																																																																						
ANT	1																																																																																																																						
Pol.	Horizontal						Vertical																																																																																																																
Peak Avg	Horizontal Polarization Spectrum Plot showing Level (dBuV/m) vs Frequency (MHz). The plot includes a blue signal line, a red limit line at 73.1 dBuV/m (FCC PART 15C), and a red average limit line at 58.5 dBuV/m (FCC PART 15C (AVG)). A peak is marked at 4804.00 MHz with a level of 41.23 dBuV/m. <table><thead><tr><th></th><th>Limit</th><th>Over</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Limit</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>4804.00</td><td>41.23</td><td>74.00</td><td>-32.77</td><td>61.36</td><td>33.00</td><td>10.27</td><td>64.20</td><td>0.00</td><td>---</td><td>---</td><td>PEAK</td></tr></tbody></table>							Limit	Over	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Limit	Level	Factor	Loss	Factor	Factor		Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	1	4804.00	41.23	74.00	-32.77	61.36	33.00	10.27	64.20	0.00	---	---	PEAK	Vertical Polarization Spectrum Plot showing Level (dBuV/m) vs Frequency (MHz). The plot includes a blue signal line, a red limit line at 73.1 dBuV/m (FCC PART 15C), and a red average limit line at 58.5 dBuV/m (FCC PART 15C (AVG)). Two peaks are marked: one at 4804.00 MHz (level 40.33 dBuV/m) and another at 9607.50 MHz (level 49.33 dBuV/m). <table><thead><tr><th></th><th>Limit</th><th>Over</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Limit</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>4804.00</td><td>40.33</td><td>74.00</td><td>-33.67</td><td>60.46</td><td>33.00</td><td>10.27</td><td>64.20</td><td>0.00</td><td>---</td><td>---</td><td>PEAK</td></tr><tr><td>2</td><td>9607.50</td><td>49.33</td><td>81.02</td><td>-31.69</td><td>65.17</td><td>36.62</td><td>14.78</td><td>67.24</td><td>0.00</td><td>---</td><td>---</td><td>PEAK</td></tr></tbody></table>							Limit	Over	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Limit	Level	Factor	Loss	Factor	Factor		Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	1	4804.00	40.33	74.00	-33.67	60.46	33.00	10.27	64.20	0.00	---	---	PEAK	2	9607.50	49.33	81.02	-31.69	65.17	36.62	14.78	67.24	0.00	---	---	PEAK
		Limit	Over	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																													
	Freq	Level	Line	Limit	Level	Factor	Loss	Factor	Factor		Remark																																																																																																												
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																												
1	4804.00	41.23	74.00	-32.77	61.36	33.00	10.27	64.20	0.00	---	---	PEAK																																																																																																											
	Limit	Over	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																														
Freq	Level	Line	Limit	Level	Factor	Loss	Factor	Factor		Remark																																																																																																													
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																												
1	4804.00	40.33	74.00	-33.67	60.46	33.00	10.27	64.20	0.00	---	---	PEAK																																																																																																											
2	9607.50	49.33	81.02	-31.69	65.17	36.62	14.78	67.24	0.00	---	---	PEAK																																																																																																											





Mode	2																																																																																																																																																													
	Harmonic																																																																																																																																																													
	2400-2483.5_Bluetooth BR_GFSK_CH39_2441MHz																																																																																																																																																													
ANT	1																																																																																																																																																													
Pol.	Horizontal						Vertical																																																																																																																																																							
Peak Avg																																																																																																																																																														
	<table><tr><th></th><th>Limit</th><th>Over</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Limit</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>4882.00</td><td>41.48</td><td>74.00</td><td>-32.52</td><td>61.55</td><td>33.86</td><td>10.35</td><td>64.28</td><td>0.00</td><td>---</td><td>---</td><td>PEAK</td></tr><tr><td>2</td><td>7323.00</td><td>43.68</td><td>74.00</td><td>-30.32</td><td>61.46</td><td>35.55</td><td>12.79</td><td>66.12</td><td>0.00</td><td>---</td><td>---</td><td>PEAK</td></tr><tr><td>3</td><td>9765.00</td><td>47.44</td><td>87.81</td><td>-40.37</td><td>62.88</td><td>36.83</td><td>14.87</td><td>67.14</td><td>0.00</td><td>---</td><td>---</td><td>PEAK</td></tr></table>							Limit	Over	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Limit	Level	Factor	Loss	Factor	Factor		Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	1	4882.00	41.48	74.00	-32.52	61.55	33.86	10.35	64.28	0.00	---	---	PEAK	2	7323.00	43.68	74.00	-30.32	61.46	35.55	12.79	66.12	0.00	---	---	PEAK	3	9765.00	47.44	87.81	-40.37	62.88	36.83	14.87	67.14	0.00	---	---	PEAK	<table><tr><th></th><th>Limit</th><th>Over</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Limit</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>4882.00</td><td>40.64</td><td>74.00</td><td>-33.36</td><td>60.71</td><td>33.86</td><td>10.35</td><td>64.28</td><td>0.00</td><td>---</td><td>---</td><td>PEAK</td></tr><tr><td>2</td><td>7323.00</td><td>43.31</td><td>74.00</td><td>-30.69</td><td>61.09</td><td>35.55</td><td>12.79</td><td>66.12</td><td>0.00</td><td>---</td><td>---</td><td>PEAK</td></tr><tr><td>3</td><td>9763.50</td><td>49.78</td><td>83.02</td><td>-33.24</td><td>65.22</td><td>36.83</td><td>14.87</td><td>67.14</td><td>0.00</td><td>---</td><td>---</td><td>PEAK</td></tr></table>							Limit	Over	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Limit	Level	Factor	Loss	Factor	Factor		Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	1	4882.00	40.64	74.00	-33.36	60.71	33.86	10.35	64.28	0.00	---	---	PEAK	2	7323.00	43.31	74.00	-30.69	61.09	35.55	12.79	66.12	0.00	---	---	PEAK	3	9763.50	49.78	83.02	-33.24	65.22	36.83	14.87	67.14	0.00	---	---	PEAK
		Limit	Over	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																																																																				
	Freq	Level	Line	Limit	Level	Factor	Loss	Factor	Factor		Remark																																																																																																																																																			
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																																																																			
1	4882.00	41.48	74.00	-32.52	61.55	33.86	10.35	64.28	0.00	---	---	PEAK																																																																																																																																																		
2	7323.00	43.68	74.00	-30.32	61.46	35.55	12.79	66.12	0.00	---	---	PEAK																																																																																																																																																		
3	9765.00	47.44	87.81	-40.37	62.88	36.83	14.87	67.14	0.00	---	---	PEAK																																																																																																																																																		
	Limit	Over	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																																																																					
Freq	Level	Line	Limit	Level	Factor	Loss	Factor	Factor		Remark																																																																																																																																																				
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																																																																			
1	4882.00	40.64	74.00	-33.36	60.71	33.86	10.35	64.28	0.00	---	---	PEAK																																																																																																																																																		
2	7323.00	43.31	74.00	-30.69	61.09	35.55	12.79	66.12	0.00	---	---	PEAK																																																																																																																																																		
3	9763.50	49.78	83.02	-33.24	65.22	36.83	14.87	67.14	0.00	---	---	PEAK																																																																																																																																																		





Mode	3																																																																																																																												
	Band Edge																																																																																																																												
	2400-2483.5_Bluetooth BR_GFSK_CH78_2480MHz																																																																																																																												
ANT	1																																																																																																																												
Pol.	Horizontal						Fundamental																																																																																																																						
Peak																																																																																																																													
	<table><tr><th></th><th>Limit</th><th>Over</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Limit</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2483.56</td><td>59.78</td><td>74.00</td><td>-14.22</td><td>50.75</td><td>32.27</td><td>7.33</td><td>36.57</td><td>6.00</td><td>188</td><td>70 PEAK</td></tr><tr><td>2</td><td>2483.56</td><td>35.05</td><td>54.00</td><td>-18.95</td><td>26.02</td><td>32.27</td><td>7.33</td><td>36.57</td><td>6.00</td><td>188</td><td>70 AVERAGE</td></tr></table>							Limit	Over	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Limit	Level	Factor	Loss	Factor	Factor		Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	1	2483.56	59.78	74.00	-14.22	50.75	32.27	7.33	36.57	6.00	188	70 PEAK	2	2483.56	35.05	54.00	-18.95	26.02	32.27	7.33	36.57	6.00	188	70 AVERAGE	<table><tr><th></th><th>Limit</th><th>Over</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Limit</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2480.00</td><td>110.04</td><td>-----</td><td>-----</td><td>101.03</td><td>32.26</td><td>7.32</td><td>36.57</td><td>6.00</td><td>188</td><td>70 PEAK</td></tr><tr><td>2</td><td>2480.00</td><td>85.31</td><td>-----</td><td>-----</td><td>76.30</td><td>32.26</td><td>7.32</td><td>36.57</td><td>6.00</td><td>188</td><td>70 AVERAGE</td></tr></table>						Limit	Over	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Limit	Level	Factor	Loss	Factor	Factor		Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	1	2480.00	110.04	-----	-----	101.03	32.26	7.32	36.57	6.00	188	70 PEAK	2	2480.00	85.31	-----	-----	76.30	32.26	7.32	36.57	6.00	188	70 AVERAGE
		Limit	Over	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																																			
Freq	Level	Line	Limit	Level	Factor	Loss	Factor	Factor		Remark																																																																																																																			
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																																			
1	2483.56	59.78	74.00	-14.22	50.75	32.27	7.33	36.57	6.00	188	70 PEAK																																																																																																																		
2	2483.56	35.05	54.00	-18.95	26.02	32.27	7.33	36.57	6.00	188	70 AVERAGE																																																																																																																		
	Limit	Over	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																																				
Freq	Level	Line	Limit	Level	Factor	Loss	Factor	Factor		Remark																																																																																																																			
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																																			
1	2480.00	110.04	-----	-----	101.03	32.26	7.32	36.57	6.00	188	70 PEAK																																																																																																																		
2	2480.00	85.31	-----	-----	76.30	32.26	7.32	36.57	6.00	188	70 AVERAGE																																																																																																																		





Mode	3																																																																																																																										
	Band Edge																																																																																																																										
	2400-2483.5_Bluetooth BR_GFSK_CH78_2480MHz																																																																																																																										
ANT	1																																																																																																																										
Pol.	Vertical						Fundamental																																																																																																																				
Peak																																																																																																																											
	<table><tr><th></th><th>Limit</th><th>Over</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Limit</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2483.62</td><td>52.02</td><td>74.00</td><td>-21.98</td><td>42.99</td><td>32.27</td><td>7.33</td><td>36.57</td><td>6.00</td><td>128</td><td>75 PEAK</td></tr><tr><td>2</td><td>2483.62</td><td>27.29</td><td>54.00</td><td>-26.71</td><td>18.26</td><td>32.27</td><td>7.33</td><td>36.57</td><td>6.00</td><td>128</td><td>75 AVERAGE</td></tr></table>							Limit	Over	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Limit	Level	Factor	Loss	Factor	Factor		Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	1	2483.62	52.02	74.00	-21.98	42.99	32.27	7.33	36.57	6.00	128	75 PEAK	2	2483.62	27.29	54.00	-26.71	18.26	32.27	7.33	36.57	6.00	128	75 AVERAGE	<table><tr><th></th><th>Limit</th><th>Over</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Limit</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2480.00</td><td>102.67</td><td>-----</td><td>93.66</td><td>32.26</td><td>7.32</td><td>36.57</td><td>6.00</td><td>128</td><td>75 PEAK</td></tr><tr><td>2</td><td>2480.00</td><td>77.94</td><td>-----</td><td>68.93</td><td>32.26</td><td>7.32</td><td>36.57</td><td>6.00</td><td>128</td><td>75 AVERAGE</td></tr></table>						Limit	Over	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Limit	Level	Factor	Loss	Factor	Factor		Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	1	2480.00	102.67	-----	93.66	32.26	7.32	36.57	6.00	128	75 PEAK	2	2480.00	77.94	-----	68.93	32.26	7.32	36.57	6.00	128	75 AVERAGE
		Limit	Over	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																																	
Freq	Level	Line	Limit	Level	Factor	Loss	Factor	Factor		Remark																																																																																																																	
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																																	
1	2483.62	52.02	74.00	-21.98	42.99	32.27	7.33	36.57	6.00	128	75 PEAK																																																																																																																
2	2483.62	27.29	54.00	-26.71	18.26	32.27	7.33	36.57	6.00	128	75 AVERAGE																																																																																																																
	Limit	Over	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																																		
Freq	Level	Line	Limit	Level	Factor	Loss	Factor	Factor		Remark																																																																																																																	
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																																	
1	2480.00	102.67	-----	93.66	32.26	7.32	36.57	6.00	128	75 PEAK																																																																																																																	
2	2480.00	77.94	-----	68.93	32.26	7.32	36.57	6.00	128	75 AVERAGE																																																																																																																	





Mode	3																																																																																																																																																												
	Harmonic																																																																																																																																																												
	2400-2483.5 Bluetooth BR_GFSK_CH78_2480MHz																																																																																																																																																												
ANT	1																																																																																																																																																												
Pol.	Horizontal						Vertical																																																																																																																																																						
Peak Avg																																																																																																																																																													
	<table><tr><th></th><th>Limit</th><th>Over</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Limit</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>4960.00</td><td>41.86</td><td>74.00</td><td>-32.14</td><td>61.82</td><td>33.90</td><td>10.44</td><td>64.30</td><td>0.00</td><td>---</td><td>---</td><td>PEAK</td></tr><tr><td>2</td><td>7440.00</td><td>44.32</td><td>74.00</td><td>-29.68</td><td>62.09</td><td>35.60</td><td>12.93</td><td>66.30</td><td>0.00</td><td>---</td><td>---</td><td>PEAK</td></tr><tr><td>3</td><td>9919.50</td><td>46.61</td><td>87.57</td><td>-40.96</td><td>61.64</td><td>37.04</td><td>14.98</td><td>67.05</td><td>0.00</td><td>---</td><td>---</td><td>PEAK</td></tr></table>							Limit	Over	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Limit	Level	Factor	Loss	Factor	Factor		Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	1	4960.00	41.86	74.00	-32.14	61.82	33.90	10.44	64.30	0.00	---	---	PEAK	2	7440.00	44.32	74.00	-29.68	62.09	35.60	12.93	66.30	0.00	---	---	PEAK	3	9919.50	46.61	87.57	-40.96	61.64	37.04	14.98	67.05	0.00	---	---	PEAK	<table><tr><th></th><th>Limit</th><th>Over</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Limit</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>4960.00</td><td>40.95</td><td>74.00</td><td>-33.05</td><td>60.91</td><td>33.90</td><td>10.44</td><td>64.30</td><td>0.00</td><td>---</td><td>---</td><td>PEAK</td></tr><tr><td>2</td><td>7440.00</td><td>43.13</td><td>74.00</td><td>-30.87</td><td>60.90</td><td>35.60</td><td>12.93</td><td>66.30</td><td>0.00</td><td>---</td><td>---</td><td>PEAK</td></tr><tr><td>3</td><td>9919.50</td><td>47.71</td><td>81.18</td><td>-33.47</td><td>62.74</td><td>37.04</td><td>14.98</td><td>67.05</td><td>0.00</td><td>---</td><td>---</td><td>PEAK</td></tr></table>							Limit	Over	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Limit	Level	Factor	Loss	Factor	Factor		Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	1	4960.00	40.95	74.00	-33.05	60.91	33.90	10.44	64.30	0.00	---	---	PEAK	2	7440.00	43.13	74.00	-30.87	60.90	35.60	12.93	66.30	0.00	---	---	PEAK	3	9919.50	47.71	81.18	-33.47	62.74	37.04	14.98	67.05	0.00	---	---
	Limit	Over	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																																																																				
Freq	Level	Line	Limit	Level	Factor	Loss	Factor	Factor		Remark																																																																																																																																																			
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																																																																		
1	4960.00	41.86	74.00	-32.14	61.82	33.90	10.44	64.30	0.00	---	---	PEAK																																																																																																																																																	
2	7440.00	44.32	74.00	-29.68	62.09	35.60	12.93	66.30	0.00	---	---	PEAK																																																																																																																																																	
3	9919.50	46.61	87.57	-40.96	61.64	37.04	14.98	67.05	0.00	---	---	PEAK																																																																																																																																																	
	Limit	Over	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																																																																				
Freq	Level	Line	Limit	Level	Factor	Loss	Factor	Factor		Remark																																																																																																																																																			
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																																																																		
1	4960.00	40.95	74.00	-33.05	60.91	33.90	10.44	64.30	0.00	---	---	PEAK																																																																																																																																																	
2	7440.00	43.13	74.00	-30.87	60.90	35.60	12.93	66.30	0.00	---	---	PEAK																																																																																																																																																	
3	9919.50	47.71	81.18	-33.47	62.74	37.04	14.98	67.05	0.00	---	---	PEAK																																																																																																																																																	




Mode	3																																																																																																																																																																																																																											
	LF																																																																																																																																																																																																																											
	2400-2483.5_Bluetooth BR_GFSK_CH78_2480MHz																																																																																																																																																																																																																											
ANT	1																																																																																																																																																																																																																											
Pol.	Horizontal						Vertical																																																																																																																																																																																																																					
QP																																																																																																																																																																																																																												
	<table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Over</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>94.02</td><td>23.42</td><td>43.50</td><td>-20.08</td><td>38.90</td><td>15.24</td><td>1.34</td><td>32.06</td><td>0.00</td><td>---</td><td>---</td><td>Peak</td></tr><tr><td>2</td><td>112.45</td><td>24.76</td><td>43.50</td><td>-18.74</td><td>38.12</td><td>17.19</td><td>1.48</td><td>32.03</td><td>0.00</td><td>---</td><td>---</td><td>Peak</td></tr><tr><td>3</td><td>223.03</td><td>23.68</td><td>46.00</td><td>-22.32</td><td>38.18</td><td>15.47</td><td>2.09</td><td>32.06</td><td>0.00</td><td>---</td><td>---</td><td>Peak</td></tr><tr><td>4</td><td>340.40</td><td>22.75</td><td>46.00</td><td>-23.25</td><td>32.22</td><td>20.05</td><td>2.59</td><td>32.11</td><td>0.00</td><td>---</td><td>---</td><td>Peak</td></tr><tr><td>5</td><td>568.35</td><td>24.65</td><td>46.00</td><td>-21.35</td><td>27.43</td><td>26.17</td><td>3.36</td><td>32.31</td><td>0.00</td><td>---</td><td>---</td><td>Peak</td></tr><tr><td>6</td><td>792.42</td><td>28.22</td><td>46.00</td><td>-17.78</td><td>27.87</td><td>28.38</td><td>3.97</td><td>32.00</td><td>0.00</td><td>---</td><td>---</td><td>Peak</td></tr></table>							Freq	Level	Limit	Over	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	94.02	23.42	43.50	-20.08	38.90	15.24	1.34	32.06	0.00	---	---	Peak	2	112.45	24.76	43.50	-18.74	38.12	17.19	1.48	32.03	0.00	---	---	Peak	3	223.03	23.68	46.00	-22.32	38.18	15.47	2.09	32.06	0.00	---	---	Peak	4	340.40	22.75	46.00	-23.25	32.22	20.05	2.59	32.11	0.00	---	---	Peak	5	568.35	24.65	46.00	-21.35	27.43	26.17	3.36	32.31	0.00	---	---	Peak	6	792.42	28.22	46.00	-17.78	27.87	28.38	3.97	32.00	0.00	---	---	Peak	<table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Over</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>41.64</td><td>30.72</td><td>40.00</td><td>-9.28</td><td>43.38</td><td>18.79</td><td>0.63</td><td>32.08</td><td>0.00</td><td>---</td><td>---</td><td>Peak</td></tr><tr><td>2</td><td>93.05</td><td>22.99</td><td>43.50</td><td>-20.51</td><td>38.62</td><td>15.11</td><td>1.32</td><td>32.06</td><td>0.00</td><td>---</td><td>---</td><td>Peak</td></tr><tr><td>3</td><td>140.34</td><td>22.65</td><td>43.50</td><td>-20.85</td><td>35.88</td><td>17.11</td><td>1.69</td><td>32.03</td><td>0.00</td><td>---</td><td>---</td><td>Peak</td></tr><tr><td>4</td><td>294.81</td><td>21.42</td><td>46.00</td><td>-24.58</td><td>31.79</td><td>19.29</td><td>2.42</td><td>32.08</td><td>0.00</td><td>---</td><td>---</td><td>Peak</td></tr><tr><td>5</td><td>618.79</td><td>27.34</td><td>46.00</td><td>-18.66</td><td>30.01</td><td>26.10</td><td>3.50</td><td>32.27</td><td>0.00</td><td>---</td><td>---</td><td>Peak</td></tr><tr><td>6</td><td>944.71</td><td>31.10</td><td>46.00</td><td>-14.90</td><td>27.17</td><td>30.52</td><td>4.35</td><td>30.94</td><td>0.00</td><td>---</td><td>---</td><td>Peak</td></tr></table>							Freq	Level	Limit	Over	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1	41.64	30.72	40.00	-9.28	43.38	18.79	0.63	32.08	0.00	---	---	Peak	2	93.05	22.99	43.50	-20.51	38.62	15.11	1.32	32.06	0.00	---	---	Peak	3	140.34	22.65	43.50	-20.85	35.88	17.11	1.69	32.03	0.00	---	---	Peak	4	294.81	21.42	46.00	-24.58	31.79	19.29	2.42	32.08	0.00	---	---	Peak	5	618.79	27.34	46.00	-18.66	30.01	26.10	3.50	32.27	0.00	---	---	Peak	6	944.71	31.10	46.00	-14.90	27.17	30.52	4.35	30.94	0.00	---	---	Peak
		Freq	Level	Limit	Over	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																																																																																															
		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																																																																																																																																
	1	94.02	23.42	43.50	-20.08	38.90	15.24	1.34	32.06	0.00	---	---	Peak																																																																																																																																																																																																															
	2	112.45	24.76	43.50	-18.74	38.12	17.19	1.48	32.03	0.00	---	---	Peak																																																																																																																																																																																																															
	3	223.03	23.68	46.00	-22.32	38.18	15.47	2.09	32.06	0.00	---	---	Peak																																																																																																																																																																																																															
	4	340.40	22.75	46.00	-23.25	32.22	20.05	2.59	32.11	0.00	---	---	Peak																																																																																																																																																																																																															
	5	568.35	24.65	46.00	-21.35	27.43	26.17	3.36	32.31	0.00	---	---	Peak																																																																																																																																																																																																															
	6	792.42	28.22	46.00	-17.78	27.87	28.38	3.97	32.00	0.00	---	---	Peak																																																																																																																																																																																																															
	Freq	Level	Limit	Over	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																																																																																																
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																																																																																																																																	
1	41.64	30.72	40.00	-9.28	43.38	18.79	0.63	32.08	0.00	---	---	Peak																																																																																																																																																																																																																
2	93.05	22.99	43.50	-20.51	38.62	15.11	1.32	32.06	0.00	---	---	Peak																																																																																																																																																																																																																
3	140.34	22.65	43.50	-20.85	35.88	17.11	1.69	32.03	0.00	---	---	Peak																																																																																																																																																																																																																
4	294.81	21.42	46.00	-24.58	31.79	19.29	2.42	32.08	0.00	---	---	Peak																																																																																																																																																																																																																
5	618.79	27.34	46.00	-18.66	30.01	26.10	3.50	32.27	0.00	---	---	Peak																																																																																																																																																																																																																
6	944.71	31.10	46.00	-14.90	27.17	30.52	4.35	30.94	0.00	---	---	Peak																																																																																																																																																																																																																




Mode	3	
	18G-25G	
	2400-2483.5_Bluetooth BR_GFSK_CH78_2480MHz	
ANT	1	
Pol.	Horizontal	Vertical
Peak Avg		

Appendix D. Duty Cycle Plots

DH5 on time (One Pulse) Plot on Channel 78



DH5 on time (Count Pulses) Plot on Channel 78



Note:

1. Worst case Duty cycle = on time/100 milliseconds = 2 * 2.90 / 100 = 5.80 %
2. Worst case Duty cycle correction factor = 20*log(Duty cycle) = -24.73 dB
3. DH5 has the highest duty cycle worst case and is reported.