


















5.8G


Condition	Mode	Frequency (MHz)	Duty Cycle (%)	Correction Factor (dB)	1/T (kHz)
NVNT	a	5745	93.96	0.27	0.71
NVNT	a	5785	93.96	0.27	0.71
NVNT	a	5825	93.33	0.3	0.71
NVNT	n20	5745	98.08	0.08	0.2
NVNT	n20	5785	98.08	0.08	0.2
NVNT	n20	5825	98.08	0.08	0.2
NVNT	n40	5755	98	0.09	0.2
NVNT	n40	5795	98	0.09	0.2
NVNT	ac20	5745	98.28	0.08	0.19
NVNT	ac20	5785	98.08	0.08	0.2
NVNT	ac20	5825	98.08	0.08	0.2
NVNT	ac40	5755	98.01	0.09	0.2
NVNT	ac40	5795	98.01	0.09	0.2
NVNT	ac80	5775	98.08	0.08	0.2
NVNT	ax20	5745	97.5	0.11	0.26
NVNT	ax20	5785	97.74	0.1	0.26
NVNT	ax20	5825	97.5	0.11	0.26
NVNT	ax40	5755	97.49	0.11	0.26
NVNT	ax40	5795	97.49	0.11	0.26
NVNT	ax80	5775	97.66	0.1	0.24

NOLOG
ED
al




Test Graphs



Duty Cycle NVNT a 5745MHz Ant1







Duty Cycle NVNT a 5785MHz Ant1







CO., LTD





















CO., LTD







15. Antenna Requirement

15.1 Limit



An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §§ 15.211, 15.213, 15.217, 15.219, 15.221, or § 15.236. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with § 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

15.2 Test Result


The EUT antenna is Internal antenna, fulfill the requirement of this section.

16. EUT Test Setup Photographs

Radiated Measurement Photos



RF Conducted Test



STATEMENT

1. The equipment lists are traceable to the International System of Units (SI)
2. The test report can not be partially copied unless prior written approval is issued from our lab.
3. The test report is invalid without the "special seal for inspection and testing".
4. The test report is invalid without the signature of the approver.
5. The test process and test result is only related to the Unit Under Test.
6. Sample information is provided by the client and the laboratory is not responsible for its authenticity.
7. The quality system of our laboratory is in accordance with ISO/IEC 17025:2017.
8. If there is any objection to this test report, the client should inform issuing laboratory within 15 days from the date of receiving test report.

Address:

Room 101M, Unit 1, Building1, Pengyuan, No.18, Lilang Road, Shanglilang, Nanwan Subdistrict, Longgang District, Shenzhen, Guangdong, China

TEL: 400-788-9558

C.: 518103

FAX: 0755-33229357

Website: <http://www.chnbctc.com>

Consultation E-mail: bctc@bctc-lab.com.cn

Complaint/Advice E-mail: advice@bctc-lab.com.cn

***** END *****