

ELECTROMAGNETIC EMISSION COMPLIANCE REPORT FOR LOW-POWER, NON-LICENSED TRANSMITTER

Test Report No. : W176R-D060

AGR No. : A173A-493R

Applicant : ANYRACTIVE

Address : #1101 R&D Tower, Nuritkum Square, 396, World Cup-buk ro, Mapo-gu, Seoul,
South Korea

Manufacturer : ANYRACTIVE

Address : #1101 R&D Tower, Nuritkum Square, 396, World Cup-buk ro, Mapo-gu, Seoul,
South Korea

Type of Equipment : GoTouch

FCC ID. : 2AMDVGOTOUCH20

Model Name : GoTouch2.0

Serial number : N/A

Total page of Report : 8 pages (including this page)

Date of Incoming : May 12, 2017

Date of issue : June 14, 2017

SUMMARY

The equipment complies with the regulation; **FCC PART 15 SUBPART C Section 15.247**

This test report only contains the result of a single test of the sample supplied for the examination.


It is not a generally valid assessment of the features of the respective products of the mass-production.

Reviewed by:



Jae-Ho Lee / Chief Engineer
ONETECH Corp.

Approved by:



Keun-Young, Choi / Vice President
ONETECH Corp.

CONTENTS

PAGE

1. VERIFICATION OF COMPLIANCE	4
2. GENERAL INFORMATION.....	5
2.1 PRODUCT DESCRIPTION.....	5
2.2 ALTERNATIVE TYPE(S)/MODEL(S); ALSO COVERED BY THIS TEST REPORT.	5
3. EUT MODIFICATIONS.....	5
4. MAXIMUM PERMISSIBLE EXPOSURE.....	6
4.1 RF EXPOSURE CALCULATION	6
4.2 EUT DESCRIPTION.....	7
4.3 CALCULATED MPE SAFE DISTANCE	8

Revision History

Issued Report No.	Issued Date	Revisions	Effect Section
W176R-D060	June 14, 2017	Initial Issue	All

DOCUMENT HISTORY

Revision No.	Issued Date	Revisions	Effect Section
Original	June 14, 2017	Initial Issue	-
Revision 01	June 23, 2017	Separation distance	4.3 Test Result
Revision 02	June 26, 2017	Calculated MPE	4.3 Calculated MPE Safe Distance

1. VERIFICATION OF COMPLIANCE

Applicant : ANYRACTIVE
Address : #1101 R&D Tower, Nuritkum Square, 396, World Cup-buk ro, Mapo-gu, Seoul, South Korea
Contact Person : Heeyoung Eom / manager
Telephone No. : +82-70-4910-8012
FCC ID : 2AMDVGOTOUCH20
Model Name : GoTouch2.0
Serial Number : N/A
Date : June 14, 2017

EQUIPMENT CLASS	DTS – DIGITAL TRNSMISSION SYSTEM
E.U.T. DESCRIPTION	GoTouch
THIS REPORT CONCERNS	Original Grant
MEASUREMENT PROCEDURES	ANSI C63.10: 2013
TYPE OF EQUIPMENT TESTED	Pre-Production
KIND OF EQUIPMENT AUTHORIZATION REQUESTED	Certification
EQUIPMENT WILL BE OPERATED UNDER FCC RULES PART(S)	FCC PART 15 SUBPART C Section 15.247
Modifications on the Equipment to Achieve Compliance	None
Final Test was Conducted On	3 m, Semi Anechoic Chamber

-. The above equipment was tested by ONETECH Corp. for compliance with the requirement set forth in the FCC Rules and Regulations. This said equipment in the configuration described in this report, shows the maximum emission levels emanating from equipment are within the compliance requirements.

2. GENERAL INFORMATION

2.1 Product Description

The ANYRACTIVE, Model GoTouch2.0 (referred to as the EUT in this report) is a GoTouch. Product specification information described herein was obtained from product data sheet or user's manual.

DEVICE TYPE	GoTouch
OPERATING FREQUENCY	2 402 MHz ~ 2 480 MHz
RF OUTPUT POWER	-1.61 dBm
NUMBER OF CHANNEL	40 Channels
MODULATION TYPE	GFSK
ANTENNA TYPE	Chip Antenna
ANTENNA GAIN	3.14 dBi
LIST OF EACH OSC. OR CRYSTAL. FREQ.(FREQ.>=1 MHz)	8 MHz
RATED SUPPLY VOLTAGE	DC 3.7 V

2.2 Alternative type(s)/model(s); also covered by this test report.

-. None

3. EUT MODIFICATIONS

-. None

4. MAXIMUM PERMISSIBLE EXPOSURE

4.1 RF Exposure Calculation

According to the FCC rule 1.1310 table 1B, the limit for the maximum permissible RF exposure for an uncontrolled environment are $f/1500 \text{ mW/cm}^2$ for the frequency range between 300 MHz and 1 500 MHz and 1.0 mW/cm^2 for the frequency range between 1 500 MHz and 100 000 MHz.

The electric field generated for a 1 mW/cm^2 exposure is calculated as follows:

$$E = \sqrt{(30 * P * G) / d}, \text{ and } S = E^2 / Z = E^2 / 377, \text{ because } 1 \text{ mW/cm}^2 = 10 \text{ W/m}^2$$

Where

S = Power density in mW/cm^2 , Z = Impedance of free space, 377Ω

E = Electric field strength in V/m , G = Numeric antenna gain, and d = distance in meter

Combining equations and rearranging the terms to express the distance as a function of the remaining variable

$$d = \sqrt{(30 * P * G) / (377 * 10 S)}$$

Changing to units of mW and cm , using $P (\text{mW}) = P (\text{W}) / 1\,000$, $d (\text{cm}) = 0.01 * d (\text{m})$

$$d = 0.282 * \sqrt{(P * G) / S}$$

Where

d = distance in cm , P = Power in mW , G = Numeric antenna gain, and S = Power density in mW/cm^2


4.2 EUT Description

Kind of EUT	GoTouch
Operating Frequency Band	☐ Wireless Microphone: 494.000 MHz ~ 501.000 MHz and 498.200 MHz ~ 505.200 MHz ☐ WLAN: 2 412 MHz ~ 2 462 MHz ☐ WLAN: 5 180 MHz ~ 5 240 MHz ☐ WLAN: 5 745 MHz ~ 5 825 MHz ☐ Bluetooth: 2 402 MHz ~ 2 480 MHz ☒ Bluetooth BLE: 2 402 MHz ~ 2 480 MHz
MAX. RF OUTPUT POWER	-1.61 dBm
Antenna Gain	3.14 dBi
Exposure Evaluation Applied	☒ MPE ☐ SAR ☐ N/A

4.3 Calculated MPE Safe Distance

According to above equation, the following result was obtained.

Operating Freq. Band (MHz)	Operating Mode	Target Power W/tolerance	Max tune up power		Antenna Gain		Power Density (mW/cm ²) @ 20 cm Separation	Limit (mW/cm ²)
		(dBm)	(dBm)	(mW)	Log	Linear		
2 402 ~ 2 480	BLE (GFSK)	-1.16 ± 0.5	-1.61	0.69	3.14	2.061	0.000 13	1.00



Tested by: Ha-Ram, Lee / Assistant Manager