

RF Exposure Report

FCC ID: 2AMEITH01-09

1. GENERAL INFORMATION

1.1 GENERAL DESCRIPTION OF EUT

Equipment	Wireless remote
Model Name	TH01-09
Additional Model Number(s)	N/A
Model Difference	N/A
Frequency Range	2.4G: 2402~2480 MHz
Number of Channel:	79 Channels
Modulation Type	GFSK
RF Output Power	1.211 dBm
Antenna Type	PCB Antenna (Gain: 0dBi)
Power Source	DC power by AAA Battery.
Power Rating	DC 3*1.5V by AAA Battery.
Remark	More details EUT technical specifications, please refer to the User's Manual.

2. RF EXPOSURE INFORMATION

SAR Test Exclusion Calculations

2.1 FCC: According to KDB 447498 D01 Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies v06.

(1) Clause 4.3: General SAR test reduction and exclusion guidance

Sub clause 4.31: Standalone SAR test exclusion considerations

1) The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6GHz at test separation distances ≤ 5 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation, mm})] \cdot [\sqrt{f_{\text{(GHz)}}}] \leq 3.0$ for 1-g SAR

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation, mm})] \cdot [\sqrt{f_{\text{(GHz)}}}] \leq 7.5.0$ for 10-g SAR

2.2

Calculation:

2.4G TX Mode						
GFSK(1Mbps)						
Frequency (MHz)	Conducted Power (dBm)	Turn-up Power Tolerance (dB)	MAX Power of Turn-up Tolerance (dbm)	MAX Power of Turn-up Tolerance (mW)	Calculation Value	Threshold Value
2402	1.211	1 $\pm$ 1	2	1.585	0.491	3.0
2441	0.911	1 $\pm$ 1	2	1.585	0.495	3.0
2480	0.892	1 $\pm$ 1	2	1.585	0.499	3.0

So standalone SAR measurements are not required.

*****END OF REPORT*****