

Prüfbericht-Nr.: Test report no.:	CN26E9RY 001	Auftrags-Nr.: Order no.:	27219597	Seite 1 von 22 Page 1 of 22
Kunden-Referenz-Nr.: Client reference no.:	N/A	Auftragsdatum: Order date:	2026-01-24	
Auftraggeber: Client:	Shining 3D Tech Co., Ltd. No. 1398 Xiangbin Road, Wenyan Street, Xiaoshan District, Hangzhou, Zhejiang, 311258, P.R. China			
Prüfgegenstand: Test item:	3D Printer			
Bezeichnung / Typ-Nr.: Identification / Type no.:	Ceramix-Nano			
Auftrags-Inhalt: Order content:	Test Report			
Prüfgrundlage: Test specification:	CFR Title 47 FCC Part 15: Subpart C Section 15.247 RSS-247 Issue 4 July 2025 RSS-Gen Issue 5 February 2021			
Wareneingangsdatum: Date of sample receipt:	2026-04-01	Please refer to photo documents		
Prüfmuster-Nr.: Test sample no.:	A004240480-001 A004243109-001-003			
Prüfzeitraum: Testing period:	2026-04-08 - 2026-05-23			
Ort der Prüfung: Place of testing:	Refer to section 2.1			
Prüflaboratorium: Testing laboratory:	TÜV Rheinland (Shenzhen) Co., Ltd.			
Prüfergebnis*: Test result*:	Pass			
geprüft von: tested by:			genehmigt von: authorized by:	
Datum: Date:	2026-06-30	Ausstellungsdatum: Issue date:		2026-06-30
Stellung / Position:	Sachverständige(r)/Expert	Stellung / Position:		Sachverständige(r)/Expert
Sonstiges / Other:	FCC ID: 24652-NANO IC: 24652-NANO HVIN: Ceramix-Nano PMN: Ceramix-Nano This report is for 2.4GHz Wi-Fi.			
Zustand des Prüfgegenstandes bei Anlieferung: Condition of the test item at delivery:	Prüfmuster vollständig und unbeschädigt Test item complete and undamaged			
* Legende:	P(ass) = entspricht o.g. Prüfgrundlage(n) F(ail) = entspricht nicht o.g. Prüfgrundlage(n) N/A = nicht anwendbar N/T = nicht getestet			
* Legend:	P(ass) = passed a.m. test specification(s) F(ail) = failed a.m. test specification(s) N/A = not applicable N/T = not tested			
Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens. This test report only relates to the above mentioned test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any test mark.				

Prüfbericht-Nr.: CN26E9RY 001
Test report no.:

Seite 2 von 22
Page 2 of 22

Anmerkungen
Remarks

1	Alle eingesetzten Prüfmittel waren zum angegebenen Prüfzeitraum gemäß eines festgelegten Kalibrierungsprogramms unseres Prüfhauses kalibriert. Sie entsprechen den in den Prüfprogrammen hinterlegten Anforderungen. Die Rückverfolgbarkeit der eingesetzten Prüfmittel ist durch die Einhaltung der Regelungen unseres Managementsystems gegeben. Detaillierte Informationen bezüglich Prüfbedingungen, Prüfequipment und Messunsicherheiten sind im Prüflabor vorhanden und können auf Wunsch bereitgestellt werden. <i>The equipment used during the specified testing period was calibrated according to our test laboratory calibration program. The equipment fulfils the requirements included in the relevant standards. The traceability of the test equipment used is ensured by compliance with the regulations of our management system. Detailed information regarding test conditions, equipment and measurement uncertainty is available in the test laboratory and could be provided on request.</i>
2	Wie vertraglich vereinbart, wurde dieses Dokument nur digital unterzeichnet. Der TÜV Rheinland hat nicht überprüft, welche rechtlichen oder sonstigen diesbezüglichen Anforderungen für dieses Dokument gelten. Diese Überprüfung liegt in der Verantwortung des Benutzers dieses Dokuments. Auf Verlangen des Kunden kann der TÜV Rheinland die Gültigkeit der digitalen Signatur durch ein gesondertes Dokument bestätigen. Diese Anfrage ist an unseren Vertrieb zu richten. Eine Umweltgebühr für einen solchen zusätzlichen Service wird erhoben. Informationen zur Verifizierung der Authentizität unserer Dokumente erhalten Sie auf folgender Webseite: go.tuv.com/digital-signature <i>As contractually agreed, this document has been signed digitally only. TUV Rheinland has not verified and unable to verify which legal or other pertaining requirements are applicable for this document. Such verification is within the responsibility of the user of this document. Upon request by its client, TUV Rheinland can confirm the validity of the digital signature by a separate document. Such request shall be addressed to our Sales department. An environmental fee for such additional service will be charged. For information on verifying the authenticity of our documents, please visit the following website: go.tuv.com/digital-signature</i>
3	Prüfklausel mit der Note * wurden an qualifizierte Unterauftragnehmer vergeben und sind unter der jeweiligen Prüfklausel des Berichts beschrieben. Abweichungen von Prüfspezifikation(en) oder Kundenanforderungen sind in der jeweiligen Prüfklausel im Bericht aufgeführt. <i>Test clauses with remark of * are subcontracted to qualified subcontractors and described under the respective test clause in the report.</i> <i>Deviations of testing specification(s) or customer requirements are listed in specific test clause in the report.</i>
4	Die Entscheidungsregel für Konformitätserklärungen basierend auf numerischen Messergebnissen in diesem Prüfbericht basiert auf der "Null-Grenzwert-Regel" und der "Einfachen Akzeptanz" gemäß ILAC G8:2019 und IEC Guide 115:2023, es sei denn, in der auf Seite 1 dieses Berichts genannten angewandten Norm ist etwas anderes festgelegt oder vom Kunden gewünscht. Dies bedeutet, dass die Messunsicherheit nicht berücksichtigt wird und daher auch nicht im Prüfbericht angegeben wird. Zu weiteren Informationen bezüglich des Risikos durch diese Entscheidungsregel siehe ILAC G8:2019. <i>The decision rule for statements of conformity, based on numerical measurement results, in this test report is based on the "Zero Guard Band Rule" and "Simple Acceptance" in accordance with ILAC G8:2019 and IEC Guide 115:2023, unless otherwise specified in the applied standard mentioned on Page 1 of this report or requested by the customer. This means that measurement uncertainty is not taken in account and hence also not declared in the test report. For additional information to the resulting risk based of this decision rule please refer to ILAC G8:2019.</i>

Prüfbericht - Nr.: CN26E9RY 001
Test Report No.:

Seite 3 von 22
Page 3 of 22

Test Summary

5.1.1 ANTENNA REQUIREMENT

RESULT: Pass

5.1.2 MAXIMUM PEAK CONDUCTED OUTPUT POWER

RESULT: Pass

5.1.3 CONDUCTED POWER SPECTRAL DENSITY

RESULT: Pass

5.1.4 6dB BANDWIDTH

RESULT: Pass

5.1.5 99% BANDWIDTH

RESULT: Pass

5.1.6 CONDUCTED SPURIOUS EMISSIONS MEASURED IN 100 KHz BANDWIDTH

RESULT: Pass

5.1.7 RADIATED SPURIOUS EMISSION

RESULT: Pass

5.1.8 CONDUCTED EMISSION ON AC MAINS

RESULT: Pass

Contents

1	GENERAL REMARKS	5
1.1	COMPLEMENTARY MATERIALS	5
2	TEST SITES	6
2.1	TEST FACILITIES	6
2.2	LIST OF TEST AND MEASUREMENT INSTRUMENTS.....	6
2.3	TRACEABILITY	7
2.4	CALIBRATION	7
2.5	MEASUREMENT UNCERTAINTY.....	7
2.6	LOCATION OF ORIGINAL DATA.....	7
2.7	STATUS OF FACILITY USED FOR TESTING.....	7
3	GENERAL PRODUCT INFORMATION	8
3.1	PRODUCT FUNCTION AND INTENDED USE.....	8
3.2	RATINGS AND SYSTEM DETAILS	8
3.3	INDEPENDENT OPERATION MODES	10
3.4	NOISE GENERATING AND NOISE SUPPRESSING PARTS.....	10
3.5	SUBMITTED DOCUMENTS.....	10
4	TEST SET-UP AND OPERATION MODES	11
4.1	PRINCIPLE OF CONFIGURATION SELECTION	11
4.2	TEST OPERATION AND TEST SOFTWARE.....	11
4.3	SPECIAL ACCESSORIES AND AUXILIARY EQUIPMENT	11
4.4	COUNTERMEASURES TO ACHIEVE EMC COMPLIANCE.....	11
4.5	TEST SETUP DIAGRAM	12
5	TEST RESULTS	13
5.1	TRANSMITTER REQUIREMENT & TEST SUITES	13
5.1.1	<i>Antenna Requirement</i>	<i>13</i>
5.1.2	<i>Maximum Peak Conducted Output Power</i>	<i>14</i>
5.1.3	<i>Conducted Power Spectral Density</i>	<i>16</i>
5.1.4	<i>6dB Bandwidth</i>	<i>17</i>
5.1.5	<i>99% Bandwidth</i>	<i>18</i>
5.1.6	<i>Conducted Spurious Emissions Measured in 100 kHz Bandwidth</i>	<i>19</i>
5.1.7	<i>Radiated Spurious Emission</i>	<i>20</i>
5.1.8	<i>Conducted Emission on AC Mains.....</i>	<i>21</i>
6	PHOTOGRAPHS OF THE TEST SET-UP	22
7	LIST OF TABLES.....	22

Prüfbericht - Nr.: CN26E9RY 001
Test Report No.:

Seite 5 von 22
Page 5 of 22

1 General Remarks

1.1 Complementary Materials

All attachments are integral parts of this test report. This applies especially to the following appendix:

Appendix A: Photographs of the Test Set-up

Appendix B: Test Results of 2.4GHz Wi-Fi

2 Test Sites

2.1 Test Facilities

Shenzhen PSI Testing Co., Ltd.

1-2F, Building 5, Yudafu Industrial Park, No. 10, Xingye West Road, Shajing Street, Bao'an District, Shenzhen, Guangdong, China 518104
A2LA Certificate Number: 6975.01

CNAS Registration Number: CNAS L19010

Note: TÜV Rheinland (Shenzhen) Co., Ltd. subcontracts the whole test to Shenzhen PSI Testing Co., Ltd., the tests at the test sites have been conducted under the supervision of a TÜV engineer

2.2 List of Test and Measurement Instruments

Table 1: List of Test and Measurement Equipment

1. RF Test Equipment						
Item	Equipment	Manufacturer	Model No.	Serial No.	Firmware Version	Calibrated until
1.	9*6*6 anechoic chamber	SKET	9*6*6	N/A	/	2026.12.19
2.	Test Receiver	Rohde&Schwarz	ESCI 7	101032/003	4.42 SP3	2026.12.17
3.	Loop Antenna	Schwarz beck	FMZB 1519B	00128	/	2026.12.24
4.	Bilog Antenna	Schwarz beck	VULB 9168	01448	/	2026.12.24
5.	Spectrum Analyzer	Rohde&Schwarz	FSV-40N	101648	3.70	2026.12.17
6.	Horn Antenna	Schwarz beck	BBHA 9120 D	02706	/	2026.12.24
7.	Amplifier	SKET	LAPA_01G18G-45dB	SK2022032901	/	2026.12.17
8.	Horn Antenna	Schwarz beck	BBHA 9170	00946	/	2026.12.24
9.	Amplifier	SKET	LNPA 0118G-45	SK2020010801	/	2026.12.17
10.	RF Power Probe	Rohde&Schwarz	NRP-Z11	1138.3004.02-117725-vh	/	2026.12.17
11.	RF Power Probe	Rohde&Schwarz	NRP-Z11	1138.3004.02-1111533-Fz	/	2026.12.17
12.	Vector Signal Generator	Agilent	N5182A	MY47420724	/	2026.12.17
13.	Analog signal generator	Agilent	N5181A	MY50145363	/	2026.12.17
14.	Comprehensive Test Instrument	Rohde&Schwarz	CMW 500	145266	/	2026.12.17
15.	Spectrum Analyzer	Agilent	N9020A	MY51281067	A.14.03	2026.12.17
16.	Temp. & Humid Chamber	Auchno	9606	/	/	2026.12.17
17.	Regulated DC Power Supply	Xinouhua	ADC120V10A	202211251638		2026.12.17
18.	Power meter	Agilent	E4419B	GB40202121	/	2026.12.17

Conducted Emission				
Description	Manufacturer	Model	Serial No.	Calibrated until (DD.MM.YYYY)
Test Receiver	Rohde&Schwarz	ESCI 7	101032/003	2026.12.17
L.I.S.N.	Rohde&Schwarz	ENV 216	102282	2026.12.17
L.I.S.N.	RFT	NNB111	13835240	2026.12.17

2.3 Traceability

All measurement equipment calibrations are traceable to NIM (National Institute of Metrology) or where calibration is performed in other countries, to equivalent nationally recognized standards organizations.

2.4 Calibration

Equipment requiring calibration is calibrated periodically by the manufacturer or according to manufacturer's specifications. Additionally all equipment is verified for proper performance on a regular basis using in house standards or comparisons.

2.5 Measurement Uncertainty

The estimated combined standard uncertainty for radiated emissions and conducted emissions measurements as below table.

Table 2: Measurement Uncertainty

Parameter	Uncertainty (k=2)
RF output power, conducted	± 0.99 dB
Occupied Channel Bandwidth	± 2.08 %
RF power density, conducted	± 0.99 dB
Unwanted Emissions, conducted	± 0.89 dB
All emissions, radiated	± 4.17 dB

2.6 Location of Original Data

The original copies of all test data taken during actual testing were attached at Appendix A & B of this report and delivered to the applicant. A copy has been retained in the TÜV Rheinland (Shenzhen) Co., Ltd. file for certification follow-up purposes.

2.7 Status of Facility Used for Testing

The Shenzhen PSI Testing Co., Ltd. Test facility located at 1-2F, Building 5, Yudafu Industrial Park, No. 10, Xingye West Road, Shajing Street, Bao'an District, Shenzhen, Guangdong, China 518104 is listed on the US Federal Communications Commission list of facilities approved to perform measurements.

3 General Product Information

3.1 Product Function and Intended Use

The product is 3D Printer. It supports 5GHz Wi-Fi and 2.4GHz Wi-Fi.
This report is for 2.4GHz Wi-Fi operation only.

For details refer to the User Manual, Technical Description and Circuit Diagram.

3.2 Ratings and System Details

Table 3: Technical Specification of EUT

General Information of EUT	Description
Kind of Equipment:	3D Printer
Type Designation:	Ceramix-Nano
Operating Voltage:	SHINING 3D
Testing Voltage:	120V AC Via AC/DC Adapter
FCC ID:	24652-NANO
IC ID:	24652-NANO
HVIN	Ceramix-Nano
PMN:	Ceramix-Nano
Technical Specification of Wi-Fi 802.11 b/g/n	
Characteristic	Description
Operating Frequency:	2412 - 2462 MHz for 802.11b/g/n(HT20) 2422 - 2452 MHz for 802.11n(HT40)
Type of Modulation:	DSSS, OFDM
Data Rate:	1/2/5.5/11 Mbps for 802.11b 6/9/12/18/24/36/48/54 Mbps for 802.11g MCS0~MCS 7 for 802.11n(HT20/40) (All data rates considered, only the Worst-cases reported)
Channel Number:	11 channels for 802.11b/g/n(HT20) 7 channels for 802.11n(HT40)
Channel Separation:	5 MHz
Beamforming:	Not Support
Antenna Type:	Integral Antennas
Number of Antenna:	2Tx2Rx
Antenna Gain:	4.15dBi for Antenna 1; 3.23dBi for Antenna 2; Max (Provided by the Client)
Technical Specification of Wi-Fi 802.11 a/n/ac	
Characteristic	Description
Frequency Band:	5150-5250MHz, 5725-5875MHz
Operating Frequency:	5180-5240MHz, 5745-5825MHz
Protocol:	802.11 a/n20/n40/ac20/ac40/ac80
Channel Number:	5180-5240MHz, 7CHs 5745-5825MHz, 8CHs
Type of Modulation:	OFDM(BPSK/QPSK/16QAM/64QAM/256QAM)
Data Rate:	6/9/12/18/24/36/48/54 Mbps for 802.11a

	MCS0~MCS7 for 802.11n MCS0~MCS9 for 802.11ac
Channel Separation:	20MHz, 40MHz, 80MHz
Beamforming:	Not Support
Antenna Type:	Integral Antenna
Antenna Number:	2Tx2Rx
Antenna Gain:	5150-5250MHz: 3.15dBi for Antenna 1; 2.03dBi for Antenna 2; 5725-5875MHz 5.19dBi for Antenna 1; 1.95dBi for Antenna 2; Max (Provided by the Client)

Note: The correctness of all data provided by customer in the test report is ensured and responsible of the customer. Any misjudgment of the test results caused by the use of incorrect data provided by customer shall be borne by the customer.

Table 4: RF Test Channel and Frequency

Technologies	Bandwidth	Test Channels (MHz)
2.4GHz Wi-Fi	20MHz	L/M/H: 2412, 2437, 2462
	40MHz	L/M/H: 2422, 2437, 2452

3.3 Independent Operation Modes

The basic operation modes are:

- A. On, 2.4GHz Wi-Fi transmitting mode
 - 1) Low Channel
 - 2) Middle Channel
 - 3) High Channel
- B. Off

3.4 Noise Generating and Noise Suppressing Parts

Refer to Circuit Diagram for further details.

3.5 Submitted Documents

- | | |
|-------------------------|----------------------------------|
| - Application Form | - User Manual |
| - Operation Description | - FCC/IC Label and Location Info |

4 Test Set-up and Operation Modes

4.1 Principle of Configuration Selection

Radio Spectrum: The equipment under test (EUT) was configured at its highest power output in order to measure its highest possible radiation and conducted level. The test modes were adapted accordingly in reference to the instructions for use.

Emission: The equipment under test (EUT) was configured to measure its highest possible radiation level. The test modes were adapted accordingly in reference to the instructions for use.

4.2 Test Operation and Test Software

Test operation refers to test setup in chapter 5. All tests were performed according to the procedures in ANSI C63.10:2020, ANSI C63.10:2020+Cor. 1:2023+ C63.10a:2024.

4.3 Special Accessories and Auxiliary Equipment

Table 5: List of Accessories and Auxiliary Equipment

Description	Manufacturer	Model	Remark
Power Supply	Inyuanpower	TYPE-C1001C	Input: 100~240V AC Output: 20/5A, 100W max

4.4 Countermeasures to Achieve EMC Compliance

The test sample which has been tested contained the noise suppression parts as described in the Technical Construction File (TCF).

No additional measures were employed to achieve compliance.

4.5 Test Setup Diagram

Diagram of Measurement Configuration for Radiation Test (Below 1GHz)




Diagram of Measurement Configuration for Radiation Test (Above 1GHz)




Diagram of Measurement Configuration for Conducted Transmitter Measurement





Diagram of Measurement Configuration for Mains Conduction Measurement



5 Test Results

5.1 Transmitter Requirement & Test Suites

5.1.1 Antenna Requirement

RESULT:

Pass

Test Specification

Test standard : FCC Part 15.247(b)(4) and Part 15.203
RSS-Gen Clause 6.8

According to the manufacturer declared, the EUT has Integral Antennas, permanent attachment and no consideration of replacement, refer to section 3.2 for details.

Therefore the EUT is considered sufficient to comply with the provision.

Refer to EUT Photo for further details.

Prüfbericht - Nr.: CN26E9RY 001
Test Report No.:Seite 14 von 22
Page 14 of 22

5.1.2 Maximum Peak Conducted Output Power

RESULT:

Pass

Test Specification

Test standard	: FCC Part 15.247(b)(3) RSS-247 Clause 6.3.2
Basic standard	: ANSI C63.10:2020, ANSI C63.10:2020+Cor. 1:2023+ C63.10a:2024
Limits	: < 1.0 W (30dBm)
Kind of test site	: Shielded Room

Test Setup

Date of testing	: 2026-04-08 - 2026-05-23
Input voltage	: 120V AC Via AC/DC Adapter
Operation mode	: A
Test channel	: Low / Middle / High
Ambient temperature	: 24.8 °C
Relative humidity	: 55 %
Atmospheric pressure	: 101 kPa

For details refer to following test result.

Table 6: Test Result of Maximum Conducted Output Power, 2.4GHz Wi-Fi

Condition	Antenna	Modulation	Frequency (MHz)	Detector	Conducted Power(dBm)	limit(dBm)	Result
NVNT	ANT1	802.11b	2412.00	Peak	15.56	30	Pass
NVNT	ANT2	802.11b	2412.00	Peak	14.52	30	Pass
NVNT	ANT1	802.11b	2437.00	Peak	14.62	30	Pass
NVNT	ANT2	802.11b	2437.00	Peak	13.91	30	Pass
NVNT	ANT1	802.11b	2462.00	Peak	14.33	30	Pass
NVNT	ANT2	802.11b	2462.00	Peak	13.26	30	Pass
NVNT	ANT1	802.11g	2412.00	Peak	15.12	30	Pass
NVNT	ANT2	802.11g	2412.00	Peak	14.30	30	Pass
NVNT	ANT1	802.11g	2437.00	Peak	14.07	30	Pass
NVNT	ANT2	802.11g	2437.00	Peak	13.88	30	Pass
NVNT	ANT1	802.11g	2462.00	Peak	13.11	30	Pass
NVNT	ANT2	802.11g	2462.00	Peak	13.00	30	Pass
NVNT	ANT1	802.11n(HT20)	2412.00	Peak	14.86	30	Pass
NVNT	ANT2	802.11n(HT20)	2412.00	Peak	13.90	30	Pass
NVNT	ANT1	802.11n(HT20)	2437.00	Peak	14.35	30	Pass
NVNT	ANT2	802.11n(HT20)	2437.00	Peak	13.50	30	Pass
NVNT	ANT1	802.11n(HT20)	2462.00	Peak	14.11	30	Pass
NVNT	ANT2	802.11n(HT20)	2462.00	Peak	13.39	30	Pass
NVNT	ANT1	802.11n(HT40)	2422.00	Peak	16.12	30	Pass
NVNT	ANT2	802.11n(HT40)	2422.00	Peak	14.97	30	Pass
NVNT	ANT1	802.11n(HT40)	2437.00	Peak	15.36	30	Pass
NVNT	ANT2	802.11n(HT40)	2437.00	Peak	14.45	30	Pass
NVNT	ANT1	802.11n(HT40)	2452.00	Peak	14.98	30	Pass
NVNT	ANT2	802.11n(HT40)	2452.00	Peak	14.17	30	Pass

Condition	Antenna	Mode	Frequency(MHz)	MIMO_Conducted_Peak Power(dBm)	Limit(dBm)	Result
NVNT	MIMO_TX	802.11n(HT20)	2412.00	17.41	30	Pass
NVNT	MIMO_TX	802.11n(HT20)	2437.00	16.95	30	Pass
NVNT	MIMO_TX	802.11n(HT20)	2462.00	16.77	30	Pass
NVNT	MIMO_TX	802.11n(HT40)	2422.00	18.59	30	Pass
NVNT	MIMO_TX	802.11n(HT40)	2437.00	17.94	30	Pass
NVNT	MIMO_TX	802.11n(HT40)	2452.00	17.60	30	Pass

Max. e.i.r.p.= 18.59dBm+4.15dBi=22.74dBm, which is less than 36dBm=4W.

Note:

- 1) The cable loss is taken into account in results.
- 2) e.i.r.p.=P_(Peak power)+ G, which is far below the 4 W

Prüfbericht - Nr.: CN26E9RY 001
Test Report No.:Seite 16 von 22
Page 16 of 22

5.1.3 Conducted Power Spectral Density

RESULT:

Pass

Test Specification

Test standard	: FCC Part 15.247(e) RSS-247 Clause 6.3.1
Basic standard	: ANSI C63.10:2020, ANSI C63.10:2020+Cor. 1:2023+ C63.10a:2024
Limits	: < 8 dBm / 3kHz
Kind of test site	: Shielded Room

Test Setup

Date of testing	: 2026-04-08 - 2026-05-23
Input voltage	: 120V AC Via AC/DC Adapter
Operation mode	: A
Test channel	: Low / Middle / High
Ambient temperature	: 24.8 °C
Relative humidity	: 55 %
Atmospheric pressure	: 101 kPa

For the measurement records, refer to the appendix B.

Prüfbericht - Nr.: CN26E9RY 001
Test Report No.:Seite 17 von 22
Page 17 of 22

5.1.4 6dB Bandwidth

RESULT:**Pass****Test Specification**

Test standard	: FCC Part 15.247(a)(2) RSS-247 Clause 6.3.1
Basic standard	: ANSI C63.10:2020, ANSI C63.10:2020+Cor. 1:2023+ C63.10a:2024
Limits	: > 500 kHz
Kind of test site	: Shielded Room

Test Setup

Date of testing	: 2026-04-08 - 2026-05-23
Input voltage	: 120V AC Via AC/DC Adapter
Operation mode	: A
Test channel	: Low / Middle / High
Ambient temperature	: 24.8 °C
Relative humidity	: 55 %
Atmospheric pressure	: 101 kPa

For the measurement records, refer to the appendix B.

Prüfbericht - Nr.: CN26E9RY 001
Test Report No.:Seite 18 von 22
Page 18 of 22

5.1.5 99% Bandwidth

RESULT:**Pass****Test Specification**

Test standard	: FCC Part 15.247(a) RSS-Gen Clause 6.7
Basic standard	: ANSI C63.10:2020, ANSI C63.10:2020+Cor. 1:2023+ C63.10a:2024
Limits	: Within assigned band 2400-2483.5MHz
Kind of test site	: Shielded Room

Test Setup

Date of testing	: 2026-04-08 - 2026-05-23
Input voltage	: 120V AC Via AC/DC Adapter
Operation mode	: A
Test channel	: Low / Middle / High
Ambient temperature	: 24.8 °C
Relative humidity	: 55 %
Atmospheric pressure	: 101 kPa

For the measurement records, refer to the appendix B.

Prüfbericht - Nr.: CN26E9RY 001
Test Report No.:Seite 19 von 22
Page 19 of 22

5.1.6 Conducted Spurious Emissions Measured in 100 kHz Bandwidth

RESULT:

Pass

Test Specification

Test standard	: FCC Part 15.247(d) RSS-247 Clause 6.6
Basic standard	: ANSI C63.10:2020, ANSI C63.10:2020+Cor. 1:2023+ C63.10a:2024
Limits	: 20dB (below that in the 100kHz bandwidth within the band that contains the highest level of the desired power); In addition, radiated emissions which fall in the restricted bands, must also comply with the radiated emission limits specified in 15.209(a)
Kind of test site	: Shielded Room

Test Setup

Date of testing	: 2026-04-08 - 2026-05-23
Input voltage	: 120V AC Via AC/DC Adapter
Operation mode	: A
Test channel	: Low / Middle / High
Ambient temperature	: 24.8 °C
Relative humidity	: 55 %
Atmospheric pressure	: 101 kPa

Test results of 100kHz Bandwidth of Frequency Band Edge by Conducted method refer to test plots, and compliance is achieved as well.

For the measurement records, refer to the appendix B.

Prüfbericht - Nr.: CN26E9RY 001
Test Report No.:Seite 20 von 22
Page 20 of 22

5.1.7 Radiated Spurious Emission

RESULT:**Pass****Test Specification**

Test standard	: FCC Part 15.247(d) & FCC Part 15.205 RSS-247 Clause 2.4
Basic standard	: ANSI C63.10:2020, ANSI C63.10:2020+Cor. 1:2023+ C63.10a:2024
Limits	: Refer to 15.209(a) of FCC part 15.247(d) RSS-Gen Section 8.9 & 8.10
Kind of test site	: 3m Semi-anechoic Chamber

Test Setup

Date of testing	: 2026-05-19 to 2026-05-22
Input voltage	: 120V AC Via AC/DC Adapter
Operation mode	: A
Test channel	: Low / Middle / High
Ambient temperature	: Refer to test results
Relative humidity	: Refer to test results
Atmospheric pressure	: 101 kPa

Remark:

Testing was carried out within frequency range 9kHz to the tenth harmonics. Only the worst case spurious emissions configuration of the each mode were reported.

For the measurement records, refer to the appendix B.

Prüfbericht - Nr.: CN26E9RY 001
Test Report No.:Seite 21 von 22
Page 21 of 22

5.1.8 Conducted Emission on AC Mains

RESULT:**Pass****Test Specification**

Test standard	: FCC Part 15.207(a) RSS-Gen Section 8.8
Basic standard	: ANSI C63.10:2020, ANSI C63.10:2020+Cor. 1:2023+ C63.10a:2024
Frequency range	: 0.15 – 30MHz
Classification	: Class B
Limits	: FCC Part 15.207(a) RSS-Gen Table 4
Kind of test site	: Shielded Room

Test Setup

Date of testing	: 2026-05-19 to 2026-05-22
Input voltage	: AC 120V, 60Hz
Operation mode	: A
Ambient temperature	: Refer to test result
Relative humidity	: Refer to test result
Atmospheric pressure	: 101 kPa

For the measurement records, refer to the appendix B.

6 Photographs of the Test Set-Up

For photographs of the test set-up, refer to the appendix A.

7 List of Tables

Table 1: List of Test and Measurement Equipment.....	6
Table 2: Measurement Uncertainty.....	7
Table 3: Technical Specification of EUT	8
Table 4: RF Test Channel and Frequency	9
Table 5: List of Accessories and Auxiliary Equipment.....	11
Table 6: Test Result of Maximum Conducted Output Power, 2.4GHz Wi-Fi	15