

Prüfbericht-Nr.: Test report no.:	CN25OGF0 001	Auftrags-Nr.: Order no.:	168572621	Seite 1 von 14 Page 1 of 14
Kunden-Referenz-Nr.: Client reference no.:	N/A	Auftragsdatum: Order date:	2025-09-01	
Auftraggeber: Client:	Shining 3D Tech Co., Ltd. No. 1398, Xiangbin Road, Wenyan, Xiaoshan, Hangzhou, Zhejiang, P.R. China			
Prüfgegenstand: Test item:	3D Scanner			
Bezeichnung / Typ-Nr.: Identification / Type no.:	EinScan Rigil, EinScan Medixa			
Auftrags-Inhalt: Order content:	Test Report			
Prüfgrundlage: Test specification:	CFR47 FCC Part 15: Subpart C Section 15.247 RSS-247 Issue 3 August 2023			
Wareneingangsdatum: Date of sample receipt:	2025-09-04	Please refer to Photo Document		
Prüfmuster-Nr.: Test sample no.:	A004073505-001~010			
Prüfzeitraum: Testing period:	2025-09-05 - 2025-09-16			
Ort der Prüfung: Place of testing:	Refer to section 2.1			
Prüflaboratorium: Testing laboratory:	TÜV Rheinland (Shenzhen) Co., Ltd.			
Prüfergebnis*: Test result*:	Pass			
geprüft von: tested by:			genehmigt von: authorized by:	
Datum: Date: 2025-11-15	Signed by: Bell Hu		Ausstellungsdatum: Issue date: 2025-11-15	Signed by: Jonathan Li
Stellung / Position:	Sachverständige(r)/Expert		Stellung / Position:	Sachverständige(r)/Expert
Sonstiges / Other:	FCC ID: 2AMG4-RIGIL, IC: 24652-RIGIL, HVIN: EinScan Rigil, EinScan Medixa, PMN: 3D Scanner This report is based on original report CN25WXZO 001, under class 2 permissive changes as listed below: Add a new model EinScan Medixa, and the differences between them (EinScan Rigil and EinScan Medixa) are mainly in the laser module, White light speckle projector and appearance colors, there is no variations on RF circuits. The changes above have no impacts on RF characteristics, only RSE re-checked for worst case on model EinScan Medixa.			
Zustand des Prüfgegenstandes bei Anlieferung: Condition of the test item at delivery:	Prüfmuster vollständig und unbeschädigt Test item complete and undamaged			
* Legende:	P(ass) = entspricht o.g. Prüfgrundlage(n)	F(ail) = entspricht nicht o.g. Prüfgrundlage(n)	N/A = nicht anwendbar	N/T = nicht getestet
* Legend:	P(ass) = passed a.m. test specification(s)	F(ail) = failed a.m. test specification(s)	N/A = not applicable	N/T = not tested
Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens. This test report only relates to the above mentioned test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any test mark.				

Prüfbericht-Nr.: CN25OGF0 001
Test report no.:

Seite 2 von 14
Page 2 of 14

Anmerkungen
Remarks

1	Alle eingesetzten Prüfmittel waren zum angegebenen Prüfzeitraum gemäß eines festgelegten Kalibrierungsprogramms unseres Prüfhauses kalibriert. Sie entsprechen den in den Prüfprogrammen hinterlegten Anforderungen. Die Rückverfolgbarkeit der eingesetzten Prüfmittel ist durch die Einhaltung der Regelungen unseres Managementsystems gegeben. Detaillierte Informationen bezüglich Prüfkonditionen, Prüfequipment und Messunsicherheiten sind im Prüflabor vorhanden und können auf Wunsch bereitgestellt werden. <i>The equipment used during the specified testing period was calibrated according to our test laboratory calibration program. The equipment fulfils the requirements included in the relevant standards. The traceability of the test equipment used is ensured by compliance with the regulations of our management system. Detailed information regarding test conditions, equipment and measurement uncertainty is available in the test laboratory and could be provided on request.</i>
2	Wie vertraglich vereinbart, wurde dieses Dokument nur digital unterzeichnet. Der TÜV Rheinland hat nicht überprüft, welche rechtlichen oder sonstigen diesbezüglichen Anforderungen für dieses Dokument gelten. Diese Überprüfung liegt in der Verantwortung des Benutzers dieses Dokuments. Auf Verlangen des Kunden kann der TÜV Rheinland die Gültigkeit der digitalen Signatur durch ein gesondertes Dokument bestätigen. Diese Anfrage ist an unseren Vertrieb zu richten. Eine Umweltgebühr für einen solchen zusätzlichen Service wird erhoben. Informationen zur Verifizierung der Authentizität unserer Dokumente erhalten Sie auf folgender Webseite: go.tuv.com/digital-signature <i>As contractually agreed, this document has been signed digitally only. TUV Rheinland has not verified and unable to verify which legal or other pertaining requirements are applicable for this document. Such verification is within the responsibility of the user of this document. Upon request by its client, TUV Rheinland can confirm the validity of the digital signature by a separate document. Such request shall be addressed to our Sales department. An environmental fee for such additional service will be charged. For information on verifying the authenticity of our documents, please visit the following website: go.tuv.com/digital-signature</i>
3	Prüfklausel mit der Note * wurden an qualifizierte Unterauftragnehmer vergeben und sind unter der jeweiligen Prüfklausel des Berichts beschrieben. Abweichungen von Prüfspezifikation(en) oder Kundenanforderungen sind in der jeweiligen Prüfklausel im Bericht aufgeführt. <i>Test clauses with remark of * are subcontracted to qualified subcontractors and described under the respective test clause in the report.</i> <i>Deviations of testing specification(s) or customer requirements are listed in specific test clause in the report.</i>
4	Die Entscheidungsregel für Konformitätserklärungen basierend auf numerischen Messergebnissen in diesem Prüfbericht basiert auf der "Null-Grenzwert-Regel" und der "Einfachen Akzeptanz" gemäß ILAC G8:2019 und IEC Guide 115:2021, es sei denn, in der auf Seite 1 dieses Berichts genannten angewandten Norm ist etwas anderes festgelegt oder vom Kunden gewünscht. Dies bedeutet, dass die Messunsicherheit nicht berücksichtigt wird und daher auch nicht im Prüfbericht angegeben wird. Zu weiteren Informationen bezüglich des Risikos durch diese Entscheidungsregel siehe ILAC G8:2019. <i>The decision rule for statements of conformity, based on numerical measurement results, in this test report is based on the "Zero Guard Band Rule" and "Simple Acceptance" in accordance with ILAC G8:2019 and IEC Guide 115:2021, unless otherwise specified in the applied standard mentioned on Page 1 of this report or requested by the customer. This means that measurement uncertainty is not taken in account and hence also not declared in the test report. For additional information to the resulting risk based of this decision rule please refer to ILAC G8:2019.</i>

Prüfbericht - Nr.: CN25OGF0 001
Test Report No.:

Seite 3 von 14
Page 3 of 14

Test Summary

5.1.1 ANTENNA REQUIREMENT

RESULT: Pass

5.1.2 RADIATED SPURIOUS EMISSION

RESULT: Pass

Contents

1	GENERAL REMARKS	5
1.1	COMPLEMENTARY MATERIALS	5
2	TEST SITES	5
2.1	TEST FACILITIES	5
2.2	LIST OF TEST AND MEASUREMENT INSTRUMENTS.....	6
2.3	TRACEABILITY	7
2.4	CALIBRATION	7
2.5	MEASUREMENT UNCERTAINTY.....	7
2.6	LOCATION OF ORIGINAL DATA.....	7
3	GENERAL PRODUCT INFORMATION	8
3.1	PRODUCT FUNCTION AND INTENDED USE.....	8
3.2	RATINGS AND SYSTEM DETAILS	8
3.3	INDEPENDENT OPERATION MODES	9
3.4	NOISE GENERATING AND NOISE SUPPRESSING PARTS.....	9
3.5	SUBMITTED DOCUMENTS.....	9
4	TEST SET-UP AND OPERATION MODES	10
4.1	PRINCIPLE OF CONFIGURATION SELECTION	10
4.2	TEST OPERATION AND TEST SOFTWARE.....	10
4.3	SPECIAL ACCESSORIES AND AUXILIARY EQUIPMENT	10
4.4	COUNTERMEASURES TO ACHIEVE EMC COMPLIANCE.....	10
4.5	TEST SETUP DIAGRAM.....	11
5	TEST RESULTS	12
5.1	TRANSMITTER REQUIREMENT & TEST SUITES	12
5.1.1	<i>Antenna Requirement</i>	<i>12</i>
5.1.2	<i>Radiated Spurious Emission</i>	<i>13</i>
6	PHOTOGRAPHS OF THE TEST SET-UP	14
7	LIST OF TABLES.....	14

1 General Remarks

1.1 Complementary Materials

All attachments are integral parts of this test report. This applies especially to the following appendix:

Appendix A: Photographs of Test Set-up

Appendix B: Test Results of Wi-Fi

2 Test Sites

2.1 Test Facilities

Shenzhen PSI Testing Co., Ltd.

1-2F, Building 5, Yudafu Industrial Park, No. 10, Xingye West Road, Shajing Street, Bao'an District, Shenzhen, Guangdong, China 518104

A2LA Certificate Number: 6975.01

CNAS Registration Number: CNAS L19010

Note: TÜV Rheinland (Shenzhen) Co., Ltd. subcontracts the whole test to Shenzhen PSI Testing Co., Ltd., the tests at the test sites have been conducted under the supervision of a TÜV engineer.

2.2 List of Test and Measurement Instruments

Table 1: List of Test and Measurement Equipment

1. RF Test Equipment						
Item	Equipment	Manufacturer	Model No.	Serial No.	Firmware Version	Calibrated until
1.	9*6*6 anechoic chamber	SKET	9*6*6	N/A	/	2026.12.19
2.	Test Receiver	Rohde&Schwarz	ESCI 7	101032/003	4.42 SP3	2025.12.17
3.	Loop Antenna	Schwarz beck	FMZB 1519B	00128	/	2026.12.24
4.	Bilog Antenna	Schwarz beck	VULB 9168	01448	/	2026.12.24
5.	Spectrum Analyzer	Rohde&Schwarz	FSV-40N	101648	3.70	2025.12.17
6.	Horn Antenna	Schwarz beck	BBHA 9120 D	02706	/	2026.12.24
7.	Amplifier	SKET	LAPA_01G18G-45dB	SK2022032901	/	2025.12.17
8.	Horn Antenna	Schwarz beck	BBHA 9170	00946	/	2026.12.24
9.	Amplifier	SKET	LNPA_0118G-45	SK2020010801	/	2025.12.17
10.	RF Power Probe	Rohde&Schwarz	NRP-Z11	1138.3004.02-117725-vh	/	2025.12.17
11.	RF Power Probe	Rohde&Schwarz	NRP-Z11	1138.3004.02-1111533-Fz	/	2025.12.17
12.	Vector Signal Generator	Agilent	N5182A	MY47420724	/	2025.12.17
13.	Analog signal generator	Agilent	N5181A	MY50145363	/	2025.12.17
14.	Comprehensive Test Instrument	Rohde&Schwarz	CMW 500	145266	/	2025.12.17
15.	Spectrum Analyzer	Agilent	N9020A	MY51281067	A.14.03	2025.12.17
16.	Temp. & Humid Chamber	Auchno	9606	/	/	2025.12.17
17.	Regulated DC Power Supply	Xinouhua	ADC120V10A	202211251638		2025.12.17
18.	Power meter	Agilent	E4419B	GB40202121	/	2025.12.17

Item	Software Name	Manufacturer
RE	EZ EMC	Farad
RF	RTS	TACHOY

Conducted Emission				
Description	Manufacturer	Model	Serial No.	Calibrated until (DD.MM.YYYY)
Test Receiver	Rohde&Schwarz	ESCI 7	101032/003	2025.12.17
L.I.S.N.	Rohde&Schwarz	ENV 216	102282	2025.12.17
L.I.S.N.	RFT	NNB111	13835240	2025.12.17

2.3 Traceability

All measurement equipment calibrations are traceable to NIM (National Institute of Metrology) or where calibration is performed in other countries, to equivalent nationally recognized standards organizations.

2.4 Calibration

Equipment requiring calibration is calibrated periodically by the manufacturer or according to manufacturer's specifications. Additionally all equipment is verified for proper performance on a regular basis using in house standards or comparisons.

2.5 Measurement Uncertainty

The estimated combined standard uncertainty for radiated emissions and conducted emissions measurements as below table.

Parameter	Uncertainty (k=2)
RF output power, conducted	± 0.99 dB
Occupied Channel Bandwidth	± 2.08 %
RF power density, conducted	± 0.99 dB
Unwanted Emissions, conducted	± 0.89 dB
All emissions, radiated	± 4.17 dB
Conducted Emission, (9kHz to 150kHz)/(150kHz to 30MHz)	± 3.70 dB / ± 3.30 dB

2.6 Location of Original Data

The original copies of all test data taken during actual testing were attached at Appendix A & B of this report and delivered to the applicant. A copy has been retained in the TÜV Rheinland (Shenzhen) Co., Ltd. file for certification follow-up purposes.

3 General Product Information

3.1 Product Function and Intended Use

The product is 3D Scanner which supports 2.4GHz Wi-Fi and 5GHz Wi-Fi functions.

This report is for 2.4GHz Wi-Fi operations only.

This report is based on original report CN25WXZO 001, under class 2 permissive changes as listed below:

1. Add a new model **EinScan Medixa**, and the differences between them (EinScan Rigil and EinScan Medixa) are mainly in the lazer module, White light speckle projector and apperance colors, there is no variations on RF circuits. Detials as listed in below table.

Differences items	EinScan Rigil	EinScan Medixa
Lazer module-25 lines	2pcs	0pcs
Lazer module-25 lines	1pcs	0pcs
White light speckle projector	0pcs	1pcs
Appearance Color	Gary	White

The changes above have no impacts on RF characteristics, only RSE re-checked for worst case on model **EinScan Medixa**.

For details refer to the User Manual, Technical Description and Circuit Diagram.

3.2 Ratings and System Details

Table 2: Technical Specification of EUT

General Information of EUT	Value
Kind of Equipment:	3D Scanner
Type Designation:	EinScan Rigil, EinScan Medixa
FCC ID:	2AMG4-RIGIL
IC:	24652-RIGIL
PMN:	3D Scanner
HVIN:	EinScan Rigil, EinScan Medixa
Operating Voltage:	DC 7.2V from the battery or DC 20V from AC/DC Adapter
Technical Specification of Wi-Fi 802.11 b/g/n/ax	
Operating Frequency:	2412 - 2462 MHz for 802.11b/g/n(HT20)/ax(HE20)
Type of Modulation:	DSSS, OFDM, OFDMA
Data Rate:	1/2/5.5/11 Mbps for 802.11b 6/9/12/18/24/36/48/54 Mbps for 802.11g MCS0~MCS 7 for 802.11n(HT20) MCS0~MCS11 for 802.11ax(HE20)* (All data rates considered, only the Worst-cases reported) *Only Full RU mode supported in 802.11ax.
Channel Number:	11 channels for 802.11b/g/n(HT20)/ax(HE20)
Channel Separation:	5 MHz

Antenna Type:	Integral Antennas
Antenna Systems	2T2R, No beamforming
Antenna Gain:	Antenna 1: 0.10dBi (Provided by the Client) Antenna 2: -1.02dBi (Provided by the Client)
Technical Specification of Wi-Fi 802.11 a/n/ac/ax	
Operating Frequency:	5180-5240MHz, 5745-5825MHz
Type of Modulation:	OFDM(BPSK/QPSK/16QAM/64QAM) OFDMA(BPSK/QPSK/16QAM/64QAM/256QAM/1024QAM)
Data Rate:	6/9/12/18/24/36/48/54 Mbps for 802.11a MCS0 ~ MCS7 for 802.11n MCS0 ~ MCS9 for 802.11ac MCS0 ~ MCS11 for 802.11ax* *Only Full RU mode supported for 802.11ax.
Antenna Type:	Integral Antennas
Antenna Systems	2T2R, No beamforming
Antenna Gain:	Antenna 1: 3.84dBi (Provided by the Client) Antenna 2: 3.42dBi (Provided by the Client)

The correctness of all data provided by customer in the test report is ensured and responsible of the customer. Any misjudgment of the test results caused using incorrect data provided by customer shall be borne by the customer.

3.3 Independent Operation Modes

The basic operation modes are:

- A. On, Wi-Fi 802.11 b/g/n/ax wireless transmitting mode
 - 1) Low Channel
 - 2) Middle Channel
 - 3) High Channel
- B. On, Wi-Fi 802.11 b/g/n/ax connecting mode

3.4 Noise Generating and Noise Suppressing Parts

Refer to Circuit Diagram for further details.

3.5 Submitted Documents

- Application Form
- User Manual
- Block Diagram
- Operation Description

4 Test Set-up and Operation Modes

4.1 Principle of Configuration Selection

Radio Spectrum: The equipment under test (EUT) was configured at its highest power output in order to measure its highest possible radiation and conducted level. The test modes were adapted accordingly in reference to the instructions for use.

Emission: The equipment under test (EUT) was configured to measure its highest possible radiation level. The test modes were adapted accordingly in reference to the instructions for use.

4.2 Test Operation and Test Software

Test operation refers to test setup in chapter 5. All tests were performed according to the procedures in ANSI C63.10: 2020 (FCC), ANSI C63.10-2020+Cor. 1-2023+C63.10a-2024 (ISED).

According to clause 3.1, all tests were performed in this report.

Table 3: Test environments

Environment Parameter	Selected Values During Tests		
	Temperature	Voltage	Relative Humidity
NTNV	24.6°C	Normal	Ambient

Table 4: Test channel and frequency

Mode	Test Channels
20MHz	L: CH01, 2412MHz; M: CH06, 2437MHz; H: CH11, 2462MHz

4.3 Special Accessories and Auxiliary Equipment

Table 5: Auxiliary Equipment Used during Test

Description	Manufacturer	Model	SN
Laptop	Lenovo	T480	PF-16A6N8
Adapter	MOSO Power supply Technology Co., ITD	P30T-V3250U200-06510-US	/

4.4 Countermeasures to Achieve EMC Compliance

The test sample which has been tested contained the noise suppression parts as described in the Technical Construction File (TCF).

No additional measures were employed to achieve compliance.

4.5 Test Setup Diagram

Diagram of Measurement Configuration for Radiation Test (Below 1GHz)





Diagram of Measurement Configuration for Radiation Test (Above 1GHz)



5 Test Results

5.1 Transmitter Requirement & Test Suites

5.1.1 Antenna Requirement

RESULT:

Pass

Test Specification

Test standard : FCC Part 15.247(b)(4) and Part 15.203
RSS-Gen Clause 6.8

The EUT has two integral antennas with unique connector, which is designed with permanent attachment and no consideration of replacement, as detailed on section 3.2.

Therefore, the EUT is considered sufficient to comply with the provision.

Refer to EUT Photo for further details.

5.1.2 Radiated Spurious Emission

RESULT:**Pass****Test Specification**

Test standard	:	FCC Part 15.247(d) & FCC Part 15.205 RSS-247 Clause 3.3
Basic standard	:	ANSI C63.10
Limits	:	Refer to 15.209(a) of FCC part 15.247(d) RSS-Gen Table 5
Kind of test site	:	3m Semi-anechoic Chamber

Test Setup

Date of testing	:	2025-09-10 - 2025-09-15
Input voltage	:	DC 7.2V
Operation mode	:	A
Test channel	:	Low / Middle / High
Ambient temperature	:	Refer to test result
Relative humidity	:	Refer to test result
Atmospheric pressure	:	101 kPa

Remark:

Testing was carried out within frequency range 9kHz to the tenth harmonics. Only the worst-case spurious emissions configuration of the each mode were reported.

For the measurement records, refer to the appendix B.

6 Photographs of the Test Set-Up

For photographs of the test set-up, refer to the appendix A.

7 List of Tables

Table 1: List of Test and Measurement Equipment.....	6
Table 2: Technical Specification of EUT	8
Table 3: Test environments	10
Table 4: Test channel and frequency.....	10
Table 5: Auxiliary Equipment Used during Test	10