

FCC 47 CFR PART15 SUBPART E

For

Prepared by

Product Name: 4G LTE Mobile Router

Brand Name: macaroon

Model No.: macaroon M1

Series Model.:N/A

FCC ID: 2AMIWM1

Test Report Number:

C170614R01-RPW1

Issued for

Beijing ULINK Technology Co., Ltd.

East Area of 5F,No.16 Wangjing North Rd.,Chaoyang District,Beijing,China

Issued by

Compliance Certification Services Inc.

Kun shan Laboratory

No.10 Weiye Rd., Innovation park, Eco&Tec,
Development Zone, Kunshan City, Jiangsu, China

TEL: 86-512-57355888

FAX: 86-512-57370818



TESTING CERT #2541.01

Note: This report shall not be reproduced except in full, without the written approval of Compliance Certification Services Inc. This document may be altered or revised by Compliance Certification Services Inc. personnel only, and shall be noted in the revision section of the document. The client should not use it to claim product endorsement by A2LA or any government agencies. The test results in the report only apply to the tested sample.

TABLE OF CONTENTS

1	TEST RESULT CERTIFICATION	4
2	EUT DESCRIPTION.....	5
3	TEST METHODOLOGY.....	6
3.1	EUT CONFIGURATION	6
3.2	EUT EXERCISE.....	6
3.3	GENERAL TEST PROCEDURES.....	6
3.4	FCC PART 15.205 RESTRICTED BANDS OF OPERATIONS	7
3.5	DESCRIPTION OF TEST MODES.....	8
3.6	ANTENNA DESCRIPTION.....	9
4	INSTRUMENT CALIBRATION	9
4.1	MEASUREMENT EQUIPMENT USED	10
4.2	MEASUREMENT UNCERTAINTY	11
5	FACILITIES AND ACCREDITATIONS	12
5.1	FACILITIES.....	12
5.2	EQUIPMENT.....	12
5.3	TABLE OF ACCREDITATIONS AND LISTINGS	12
5.4	TABLE OF ACCREDITATIONS AND LISTINGS.....	13
6	SETUP OF EQUIPMENT UNDER TEST	14
6.1	SETUP CONFIGURATION OF EUT.....	14
6.2	SUPPORT EQUIPMENT.....	14
7	FCC PART 15 REQUIREMENTS	15
7.1	26 DB EMISSION BANDWIDTH.....	15
7.2	99% DB EMISSION BANDWIDTH.....	24
7.3	MAXIMUM CONDUCTED OUTPUT POWER	33
7.4	BAND EDGES MEASUREMENT	35
7.5	MAXIMUM POWER SPECTRAL DENSITY.....	42
7.6	FREQUENCY STABILITY MEASUREMENT.....	51
7.7	RADIATED UNDESIRABLE EMISSION	53
7.8	POWERLINE CONDUCTED EMISSIONS	64

Revision History

Rev.	Issue Date	Report NO.	Effect Page	Contents
00	July 26, 2017	C170614R01-RPW1	ALL	N/A
01	September 5, 2017	C170614R01-RPW1	P34	Add data of Max EIRP

1 TEST RESULT CERTIFICATION


Product Name:	4G LTE Mobile Router
Trade Name:	macaroon
Model Name.:	macaroon M1
Series Model:	N/A
Applicant Discrepancy:	Initial
Device Category:	portable unit
Date of Test:	June 23, 2017 ~ July 24, 2017
Applicant:	Beijing ULINK Technology Co., Ltd. East Area of 5F,No.16 Wangjing North Rd.,Chaoyang District,Beijing,China
Manufacturer:	Beijing ULINK Technology Co., Ltd. East Area of 5F,No.16 Wangjing North Rd.,Chaoyang District,Beijing,China
Application Type:	Certification

APPLICABLE STANDARDS	
STANDARD	TEST RESULT
FCC 47 CFR Part 15 Subpart E	No non-compliance noted

The above equipment was tested by Compliance Certification Services Inc. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.10: 2013 and the energy emitted by the sample EUT tested as described in this report is in compliance with the requirements of FCC Rules Part 15.207, 15.209, 15.407 and KDB 789033.

The test results of this report relate only to the tested sample EUT identified in this report.

Approved by:




Jeff.Fang

RF Manager

Compliance Certification Service Inc.

Tested by:



Lily.Wang

Test Engineer

Compliance Certification Service Inc.

2 EUT DESCRIPTION

Product Name:	4G LTE Mobile Router			
Brand Name:	macaroon			
Model Name:	macaroon M1			
Series Model:	N/A			
Model Discrepancy:	N/A			
Power Adapter:	Power Adapter: Model :TUUS050100-K00 Input: 100-240V~50/60Hz, 0.2A Output: 5V $\overline{\text{---}}$ 1A Battery (rating): capacity: 11.4WH 3.8V			
Frequency Range :	Band	Mode	Frequency Range(MHz)	Number of Channels
	Band I UNII-I	IEEE802.11a mode	5150 MHz~5250 MHz	4
		IEEE802.11an HT20 mode		4
		IEEE802.11an HT40 mode		2
		IEEE802.11ac VHT20 mode		4
		IEEE802.11ac VHT40 mode		2
		IEEE802.11ac VHT80 mode		1
Average Transmit Power :	IEEE802.11a mode: 13.97dBm IEEE802.11an HT20 mode: 12.92dBm IEEE802.11an HT40 mode: 12.75dBm IEEE802.11ac VHT20 mode: 11.85dBm IEEE802.11ac VHT40 mode: 11.71dBm IEEE802.11ac VHT80 mode: 11.99dBm			
Modulation Technique :	IEEE802.11a mode: OFDM (6,9,12,18,24,36,48 and 54 Mbps) IEEE802.11an HT20 mode: OFDM (MCS0~MCS7) IEEE802.11an HT40 mode: OFDM (MCS0~MCS7) IEEE802.11ac VHT20 mode: OFDM (MCS0~MCS8) IEEE802.11ac VHT40 mode: OFDM (MCS0~MCS9) IEEE802.11ac VHT80 mode: OFDM (MCS0~MCS9)			
Antenna Specification:	Internal Antenna Antenna Gain: -1.01 dBi			

Remark:

1. The sample selected for test was engineering sample that approximated to production product and was provided by manufacturer.
2. This submittal(s) (test report) is intended for **FCC ID: 2AMIWM1** filing to comply with FCC Part 15, Subpart E Rules.

3 TEST METHODOLOGY

The tests documented in this report were performed in accordance with ANSI C63.10:2013 and FCC CFR 47 15.207, 15.209 and 15.407.

3.1 EUT CONFIGURATION

The EUT configuration for testing is installed for RF field strength measurement to meet the Commissions requirement, and is operated in a manner intended to generate the maximum emission in a continuous normal application.

3.2 EUT EXERCISE

The EUT is operated in the engineering mode to fix the Tx frequency for the purposes of measurement.

According to its specifications, the EUT must comply with the requirements of Section 15.407 under the FCC Rules Part 15 Subpart E.

3.3 GENERAL TEST PROCEDURES

Conducted Emissions

The EUT is placed on the turntable, which is positioned at 0.8 m above the ground plane. According to the requirements in Section 13.3 of ANSI C63.10:2013, the conducted emission from the EUT is measured in the frequency range between 0.15 MHz and 30MHz, using the CISPR Quasi-Peak detector mode.

Radiated Emissions

Under 1GHz

The EUT is placed on a turn table, which is 0.8 m above ground plane. The turntable shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3m away from the receiving antenna, which varied from 1m to 4m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the maximum emissions, exploratory radiated emission measurements were made according to the requirements in Section 13.1.4.1 of ANSI C63.10:2013.

Above 1GHz

The EUT is placed on a turn table, which is 1.5 m above ground plane. The turntable shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3m away from the receiving antenna, which varied from 1m to 4m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the maximum emissions, exploratory radiated emission measurements were made according to the requirements in Section 13.1.4.1 of ANSI C63.10:2013.

3.4 FCC PART 15.205 RESTRICTED BANDS OF OPERATIONS

(a) Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.50 - 5.15
0.495 - 0.505 ⁽¹⁾	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960.0 - 1240	7.25 - 7.75
4.125 - 4.128	25.50 - 25.67	1300 - 1427	8.025 - 8.500
4.17725 - 4.17775	37.50 - 38.25	1435.0 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73.00 - 74.60	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.80 - 75.20	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108.00 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.90 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500.0	17.7 - 21.4
8.37625 - 8.38675	156.70 - 156.90	2655 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.1700	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.20	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358.0	36.43 - 36.5 ⁽²⁾
12.57675 - 12.57725	322.0 - 335.4	3600 - 4400	
13.36 - 13.41			

¹ Until February 1, 1999, this restricted band shall be 0.490-0.510MHz.

² Above 38.6

(b) Except as provided in paragraphs (d) and (e), the field strength of emissions appearing within these frequency bands shall not exceed the limits shown in Section 15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in Section 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000 MHz, compliance with the emission limits in Section 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in Section 15.35 apply to these measurements.

3.5 DESCRIPTION OF TEST MODES

Description	Modulation Technology	Modulation Type
26dB Bandwidth and 99% bandwidth	OFDM	BPSK
Maximum conducted output power	OFDM	BPSK
Band edges measurement	OFDM	BPSK
Peak Power Spectral Density	OFDM	BPSK
Radiated undesirable emission	OFDM	BPSK
Powerline conducted emission	OFDM	BPSK

IEEE 802.11a mode:

Channel (5180MHz),Channel (5200MHz) and Channel (5240MHz) with 54Mbps data rate were chosen for full testing.

IEEE 802.11an HT20 mode:

Channel (5180MHz),Channel (5200MHz) and Channel (5240MHz) with MCS7 data rate were chosen for full testing.

IEEE 802.11an HT40 mode:

Channel (5190MHz) and Channel (5230MHz) with MCS7 data rate were chosen for full testing.

IEEE 802.11ac VHT20 mode:

Channel (5180MHz),Channel (5200MHz) and Channel (5240MHz) with MCS8 data rate were chosen for full testing.

IEEE 802.11ac VHT40 mode:

Channel (5190MHz) and Channel (5230MHz) with MCS9 data rate were chosen for full testing.

IEEE 802.11ac VHT80 mode:

Channel (5210MHz) with MCS9 data rate were chosen for full testing.

3.6 ANTENNA DESCRIPTION

an intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached or an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section"

- * the antenna of this EUT is a unique (Internal Antenna for WLAN).
- * the EUT complies with the requirement of 15.203.



4 INSTRUMENT CALIBRATION

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipment, which is traceable to recognized national standards.

4.1 MEASUREMENT EQUIPMENT USED

Conducted Emissions Test Site					
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Data	Calibration Due
Spectrum Analyzer	Agilent	E4446A	MY44020154	2016-9-10	2017-9-9
Spectrum Analyzer	RS	FSU26	200789	2016-7-21	2017-7-20
Spectrum Analyzer	RS	FSU26	200789	2017-7-20	2018-7-19
Power meter	Anritsu	ML2495A	1445010	2017-4-26	2018-4-25
Power sensor	Anritsu	MA2411B	1339220	2017-4-26	2018-4-25
Power SPLITTER	Mini-Circuits	ZN2PD-9G	SF078500430	N.C.R	N.C.R
DC Power Supply	AGILENT	E3632A	MY50340053	N.C.R	N.C.R
Temp. / Humidity Gauge	Anymetre	TH603	CCS007	2016-11-1	2017-10-31
Test Software			EZ-EMC		

977 Chamber					
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Data	Calibration Due
Spectrum Analyzer	Agilent	E4446A	MY44020154	2016-9-10	2017-9-9
Spectrum Analyzer	RS	FSU26	200789	2016-7-21	2017-7-20
Spectrum Analyzer	RS	FSU26	200789	2017-7-20	2018-7-19
EMI Test Receiver	R&S	ESCI	101378	2017-1-5	2018-1-4
Pre-Amplifier	MITEQ	AMF-6F-260400-40-8P	1037496	2016-11-15	2017-11-14
Amplifier	MITEQ	JS41-00101800-32-10P	1675713	2017-7-20	2018-7-19
Broad-Band Horn Antenna	SCHWARZBECK	BBHA 9170	9170-515	2017-3-6	2018-3-5
Bilog Antenna	Sunol	JB1	A062604	2017-5-27	2018-5-26
Bilog Antenna	Sunol	JB1	A110204-1	2017-5-27	2018-5-26
Loop Antenna	Hengweiyi	39501C	2014012	2017-1-5	2018-1-4
Horn-antenna	SCHWARZBECK	9120D	D:266	2017-2-28	2018-2-27
Horn-antenna	SCHWARZBECK	9120D	D:267	2016-11-10	2017-11-9
Turn Table	CT	CT123	4165	N.C.R	N.C.R
Antenna Tower	CT	CTERG23	3256	N.C.R	N.C.R
Controller	CT	CT100	95637	N.C.R	N.C.R
Test Software			EZ-EMC		

Conducted Emission					
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Data	Calibration Due
EMI TEST RECEIVER	R&S	ESCI	100781	2017-2-28	2018-2-27
V (V-LISN)	SCHWARZBECK	NNLK 8129	8129-143	2016-11-1	2017-10-31
TWO-LINE V-NETWORK	R&S	ENV216	101604	2016-11-1	2017-10-31
Pulse LIMITER	R&S	ESH3-Z2	100524	2017-1-5	2018-1-4
Test Software			EZ-EMC		

Remark: Each piece of equipment is scheduled for calibration once a year.

4.2 MEASUREMENT UNCERTAINTY

For the test methods, according to the present document, the measurement uncertainty figures shall be calculated in accordance with TR 100 028-1 [2] and shall correspond to an expansion factor (coverage factor) $k = 1,96$ or $k = 2$ (which provide confidence levels of respectively 95 % and 95,45 % in the case where the distributions characterizing the actual measurement uncertainties are normal (Gaussian)).

Table 6 is based on such expansion factors.

Table 6: Maximum measurement uncertainty

Parameter	UNCERTAINTY
Radio frequency	$\pm 0.8 \times 10^{-7}$
RF power, conducted	0.2054
Maximum frequency deviation:	
-within 300 Hz and 6 kHz of audio frequency	1.3%
-within 6 kHz and 25 kHz of audio frequency	0.65 dB
Adjacent channel power	0.2054
Conducted spurious emission of transmitter, valid up to 6 GHz	0.2892
Conducted emission of receivers	+1.2/-1.1 dB
Radiated emission of transmitter, valid up to 6 GHz	± 3.94 dB
Radiated emission of receiver, valid up to 6 GHz	± 3.94 dB
RF level uncertainty for a given BER	± 0.3 dB
Temperature	0.1979
Humidity	± 1 %

5 FACILITIES AND ACCREDITATIONS

5.1 FACILITIES

All measurement facilities used to collect the measurement data are located at

☒ **No.10Weiye Rd., Innovation park, Eco&Tec, Development Zone, Kunshan City, Jiangsu, China.**

The sites are constructed in conformance with the requirements of ANSI C63.10:2013 and CISPR Publication 22. All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."

5.2 EQUIPMENT

Radiated emissions are measured with one or more of the following types of linearly polarized antennas: tuned dipole, biconical, log periodic, bi-log, and/or ridged waveguide, horn. Spectrum analyzers with preselectors and quasi-peak detectors are used to perform radiated measurements.

Conducted emissions are measured with Line Impedance Stabilization Networks and EMI Test Receivers.

Calibrated wideband preamplifiers, coaxial cables, and coaxial attenuators are also used for making measurements.

All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."

5.3 TABLE OF ACCREDITATIONS AND LISTINGS

FCC –Designation Number: CN1172.

Compliance Certification Services Inc. Kun shan Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files and the Designation Number: CN1172.

5.4 TABLE OF ACCREDITATIONS AND LISTINGS

Country	Agency	Scope of Accreditation	Logo
USA	A2LA	47 CFR FCC Part 15/18 (using ANSI C63.10 :2013); VCCI V3; CNS 13438; CNS 13439; CNS 13803; CISPR 11; EN 55011; CISPR 13; EN 55013; CISPR 22:2005; CISPR 22:1997 +A1 :2000+A2 :2002; EN 55022:2006; EN55022 :1998 +A1 :2001+A2 :2003; EN 61000-6-3 (excluding discontinuous interference); EN 61000-6-4; AS/NZS CISPR 22; CAN/CSA-CEI/IEC CISPR 22; EN 61000-3-2; EN 61000-3-3; EN550024; EN 61000-4-2; EN 61000-4-3; EN61000-4-4; EN 61000-4-5; EN 61000-4-6; IEC 61000-4-8; EN 61000-4-11; IEC61000-3-2; IEC61000-3-3; IEC 61000-4-2; IEC 61000-4-3; IEC 61000-4-4; IEC 61000-4-5; IEC 61000-4-6; IEC 61000-4-8; IEC 61000-4-11; EN 300 220-3; EN 300 328; EN 300 330-2; EN 300 440-1; EN 300-440-2; EN 300 893; EN 301 489-01; EN 301 489-3; EN 301 489-07; EN 301 489-17; 47 CFR FCC Part 15, 22, 24	 TESTING CERT #2541.01
USA	FCC	3/10 meter Sites to perform FCC Part 15/18 measurements	 CN1172
Japan	VCCI	3/10 meter Sites and conducted test sites to perform radiated/conducted measurements	VCCI R-1600 C-1707 G-216

* No part of this report may be used to claim or imply product endorsement by A2LA or any agency of the US Government.

6 SETUP OF EQUIPMENT UNDER TEST

6.1 SETUP CONFIGURATION OF EUT

See test photographs attached in Appendix 1 for the actual connections between EUT and support equipment.

6.2 SUPPORT EQUIPMENT

No.	Equipment	Model No.	Serial No.
1	N/A		

Remark:

1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.

7 FCC PART 15 REQUIREMENTS


7.1 26 DB EMISSION BANDWIDTH

LIMIT

According to §15.403(i), for purposes of this subpart the emission bandwidth shall be determined by measuring the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, that are 26 dB down relative to the maximum level of the modulated carrier. Compliance with the emissions limits is based on the use of measurement instrumentation employing a peak detector function with an instrument resolutions bandwidth approximately equal to 1.0 percent of the emission bandwidth of the device under measurement.

Test Configuration

TEST PROCEDURE



1. Place the EUT on the table and set it in the transmitting mode.
2. Remove the antenna from the EUT and then connect a low-loss RF cable from the antenna port to the spectrum analyzer.
3. Set the spectrum analyzer as RBW = approximately 1% of the emission bandwidth, VBW > RBW, Detector = Peak, Span > 26dB bandwidth, and Sweep = auto, Trace mode = max hold.
4. Measure the maximum width of the emission that is 26 dB down from the maximum of the emission. Compare this with the RBW setting of the analyzer. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1%.
5. Repeat until all the rest channels were investigated.

TEST RESULTS

No non-compliance noted

Test Data

Test mode: IEEE 802.11a mode

Channel	Frequency (MHz)	Bandwidth (B) (MHz)
Low	5180	22.452
Mid	5200	22.574
High	5240	22.596

Test mode: IEEE 802.11n HT20MHz mode

Channel	Frequency (MHz)	Bandwidth (B) (MHz)
Low	5180	22.776
Mid	5200	22.728
High	5240	22.676

Test mode: IEEE 802.11n HT40MHz mode

Channel	Frequency (MHz)	Bandwidth (B) (MHz)
Low	5190	43.942
High	5230	43.269

Test mode: IEEE 802.11ac VHT20MHz mode



Channel	Frequency (MHz)	Bandwidth (B) (MHz)
Low	5180	22.756
Mid	5200	22.949
High	5240	22.837

Test mode: IEEE 802.11ac VHT40MHz mode


Channel	Frequency (MHz)	Bandwidth (B) (MHz)
Low	5190	45.096
High	5230	44.231

Test mode: IEEE 802.11ac VHT80MHz mode

Channel	Frequency (MHz)	Bandwidth (B) (MHz)
Mid	5210	91.346


Test Plot**IEEE 802.11a mode:****CH Low****CH Mid**

CH High




IEEE 802.11n HT20 mode


CH Low







CH Mid



CH High




IEEE 802.11n HT40 mode**CH Low****CH High**

IEEE 802.11ac VHT20 mode**CH Low****CH Mid**

CH High



Ref 20 dBm * Att 10 dB * RBW 300 kHz Delta 2 [T1]
* VBW 1 MHz 0.05 dB
SWT 20 ms 22.836538462 MHz




IEEE 802.11ac VHT40 mode


CH Low




Ref 20 dBm * Att 10 dB * RBW 300 kHz Delta 2 [T1]
* VBW 1 MHz 0.08 dB
SWT 20 ms 45.096153846 MHz



CH High

IEEE 802.11ac VHT80 mode

CH Mid




7.2 99% DB EMISSION BANDWIDTH

LIMIT

None; for reporting purposes only.

Test Configuration



Test Procedure

1. Set center frequency to the nominal EUT channel center frequency.
2. Set span = 1.5 times to 5.0 times the OBW.
3. Set RBW = 1 % to 5 % of the OBW
4. Set VBW $\geq 3 \cdot$ RBW
5. Video averaging is not permitted. Where practical, a sample detection and single sweep mode shall be used. Otherwise, peak detection and max hold mode (until the trace stabilizes) shall be used.
6. Use the 99 % power bandwidth function of the instrument (if available).

TEST RESULTS

No non-compliance noted

Test Data

Test mode: IEEE 802.11a mode

Channel	Frequency (MHz)	99% Bandwidth (MHz)
Low	5180	16.987
Mid	5200	16.907
High	5240	16.987

Test mode: IEEE 802.11n HT20MHz mode

Channel	Frequency (MHz)	99% Bandwidth (MHz)
Low	5180	18.029
Mid	5200	18.029
High	5240	18.029

Test mode: IEEE 802.11n HT40MHz mode

Channel	Frequency (MHz)	99% Bandwidth (MHz)
Low	5190	36.923
High	5230	36.827

Test mode: IEEE 802.11ac VHT20MHz mode



Channel	Frequency (MHz)	99% Bandwidth (MHz)
Low	5180	18.109
Mid	5200	18.029
High	5240	18.029

Test mode: IEEE 802.11ac VHT40MHz mode


Channel	Frequency (MHz)	99% Bandwidth (MHz)
Low	5190	36.731
High	5230	36.635

Test mode: IEEE 802.11ac VHT80MHz mode

Channel	Frequency (MHz)	99% Bandwidth (MHz)
Mid	5210	76.538


Test Plot**IEEE 802.11a mode:****5150~5250MHz****CH Low****CH Mid**

CH High

IEEE 802.11n HT20 mode

5150~5250MHz


CH Low



CH Mid




1 PK
MATH







CH High




1 PK
MATH




IEEE 802.11n HT40 mode
5150~5250MHz**CH Low****CH High**

IEEE 802.11ac HT20 mode
5150~5250MHz**CH Low****CH Mid**


CH High

**IEEE 802.11ac HT40 mode**
5150~5250MHz

CH Low




CH High



IEEE 802.11ac HT80 mode 5150~5250MHz

CH Mid



7.3 MAXIMUM CONDUCTED OUTPUT POWER

LIMIT


According to §15.407(a),

(i) For an outdoor access point operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6dBi. The maximum e.i.r.p. at any elevation angle above 30 degrees as measured from the horizon must not exceed 125mW (21dBm).

If transmitting antennas of directional gain greater than 6dBi are used, both the peak transmit power and the peak power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

The peak power shall not exceed the limit as follow:

Test Configuration



The EUT was connected to a spectrum analyzer through a 50Ω RF cable.

TEST PROCEDURE

The testing follows Method PM of FCC KDB 789033 D02 General UNII Test Procedures New Rules v01.

Method PM (Measurement using an RF average power meter):

1. Measurement is performed using a wideband RF power meter.
2. The EUT is configured to transmit continuously with a consistent duty cycle at its maximum power control level.
3. Measure the average power of the transmitter, and the average power is corrected with duty factor, $10 \log(1/x)$, where x is the duty cycle.

TEST RESULTS

No non-compliance noted

TEST RESULTS

No non-compliance noted

Test Data**Test mode: IEEE 802.11a mode**

Channel	Frequency (MHz)	AV Output Power (dBm)	Power Limit (dBm)	Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)
Low	5180	13.68	30.00	-1.01	12.67	21
Mid	5200	13.97	30.00	-1.01	12.96	21
High	5240	13.95	30.00	-1.01	12.94	21

Test mode: IEEE 802.11n HT20MHz mode

Channel	Frequency (MHz)	AV Output Power (dBm)	Power Limit (dBm)	Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)
Low	5180	12.72	30.00	-1.01	11.71	21
Mid	5200	12.51	30.00	-1.01	11.50	21
High	5240	12.72	30.00	-1.01	11.71	21

Test mode: IEEE 802.11n HT40MHz mode

Channel	Frequency (MHz)	AV Output Power (dBm)	Power Limit (dBm)	Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)
Low	5190	12.75	30.00	-1.01	11.74	21
High	5230	12.37	30.00	-1.01	11.36	21

Test mode: IEEE 802.11ac VHT20MHz mode

Channel	Frequency (MHz)	AV Output Power (dBm)	Power Limit (dBm)	Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)
Low	5180	11.69	30.00	-1.01	10.68	21
Mid	5200	11.46	30.00	-1.01	10.45	21
High	5240	11.66	30.00	-1.01	10.65	21

Test mode: IEEE 802.11ac VHT40MHz mode

Channel	Frequency (MHz)	AV Output Power (dBm)	Power Limit (dBm)	Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)
Low	5190	11.71	30.00	-1.01	10.70	21
High	5230	11.47	30.00	-1.01	10.46	21

Test mode: IEEE 802.11ac VHT80MHz mode

Channel	Frequency (MHz)	AV Output Power (dBm)	Power Limit (dBm)	Gain (dBi)	EIRP (dBm)	EIRP Limit (dBm)
Mid	5210	11.81	30.00	-1.01	10.80	21

Note:Duty factor has been offsetted with cableloss


7.4 BAND EDGES MEASUREMENT

LIMIT

According to §15.407(b),

- (1) The provisions of Section 15.205 of this part apply to intentional radiators operating under this section.
- (2) When measuring the emission limits, the nominal carrier frequency shall be adjusted as close to the upper and lower frequency block edges as the design of the equipment permits.

Test Configuration



TEST PROCEDURE

1. The EUT is placed on a turntable, which is 1.5m above the ground plane.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emission.
4. Set the spectrum analyzer in the following setting in order to capture the lower and upper band-edges of the emission:
 - (a) PEAK: RBW=VBW=1MHz / Sweep=AUTO
 - (b) AVERAGE: RBW=1MHz / Sweep=AUTO

VBW=10Hz, when duty cycle is no less than 98 percent.

$VBW \geq 1/T$, when duty cycle is less than 98 percent, where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.


Band	Duty Cycle(%)	T(ms)	1/T(kHz)	VBW Setting
IEEE 802.11 a	96	2.267	0.44	0.5KHz
IEEE 802.11n HT20	96.8	3.750	0.27	0.3KHz
IEEE 802.11n HT40	96.9	3.617	0.28	0.3KHz
IEEE 802.11ac HT20	96.5	3.167	0.32	0.5KHz
IEEE 802.11ac HT40	97	3.750	0.27	0.3KHz
IEEE 802.11ac HT80	93.1	3.167	0.32	0.5KHz

TEST RESULTS

Refer to attach spectrum analyzer data chart.


Band Edges (IEEE 802.11a mode)

Polarity: Vertical



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Degree (deg.)	Remark
1	5150.000	56.22	-4.40	51.82	74.00	-22.18	100	209	peak


Polarity: Horizontal



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Degree (deg.)	Remark
1	5150.000	56.92	-4.40	52.52	74.00	-21.48	100	160	peak


Band Edges (IEEE 802.11n HT20 mode)

Polarity: Vertical




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Degree (deg.)	Remark
1	5150.000	56.16	-4.40	51.76	74.00	-22.24	100	145	peak


Polarity: Horizontal



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Degree (deg.)	Remark
1	5150.000	56.70	-4.40	52.30	74.00	-21.70	100	244	peak

Band Edges (IEEE 802.11n HT40 mode)**Polarity: Vertical**


No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Degree (deg.)	Remark
1	5139.744	58.16	-4.44	53.72	74.00	-20.28	200	17	peak
2	5150.000	56.28	-4.40	51.88	74.00	-22.12	100	147	peak

Polarity: Horizontal

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Degree (deg.)	Remark
1	5150.000	56.80	-4.40	52.40	74.00	-21.60	100	212	peak


Band Edges (IEEE 802.11ac VHT20 mode)

Polarity: Vertical



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Degree (deg.)	Remark
1	5150.000	55.70	-4.40	51.30	74.00	-22.70	100	315	peak


Polarity: Horizontal



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Degree (deg.)	Remark
1	5119.551	58.00	-4.54	53.46	74.00	-20.54	200	31	peak
2	5150.000	56.24	-4.40	51.84	74.00	-22.16	100	225	peak


Band Edges (IEEE 802.11ac VHT40 mode)

Polarity: Vertical



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Degree (deg.)	Remark
1	5150.000	56.78	-4.40	52.38	74.00	-21.62	100	139	peak


Polarity: Horizontal



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Degree (deg.)	Remark
1	5148.397	59.64	-4.40	55.24	74.00	-18.76	100	225	peak
2	5148.397	45.25	-4.40	40.85	54.00	-13.15	100	232	AVG
3	5150.000	59.52	-4.40	55.12	74.00	-18.88	100	216	peak
4	5150.000	45.43	-4.40	41.03	54.00	-12.97	100	204	AVG


Band Edges (IEEE 802.11ac VHT80 mode)

Polarity: Vertical



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Degree (deg.)	Remark
1	5150.000	55.88	-4.40	51.48	74.00	-22.52	100	127	peak

Polarity: Horizontal



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Degree (deg.)	Remark
1	5135.032	59.45	-4.47	54.98	74.00	-19.02	100	224	peak
2	5135.032	46.09	-4.47	41.62	54.00	-12.38	100	216	AVG
3	5150.000	57.95	-4.40	53.55	74.00	-20.45	100	149	peak

7.5 MAXIMUM POWER SPECTRAL DENSITY

LIMIT


According to §15.407(a),

(i) For an outdoor access point operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band.

(ii) For an indoor access point operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band.

If transmitting antennas of directional gain greater than 6dBi are used, both the peak transmit power and the peak power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

Test Configuration



TEST PROCEDURE

1. Place the EUT on the table and set it in transmitting mode.
Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
2. Set the spectrum analyzer as RBW = 1MHz, VBW = 3MHz, Span must be greater than 26dB bandwidth, adjust as necessary, Sweep= auto, Detector RMS
3. Record the max. reading.

TEST RESULTS

No non-compliance noted

Test Data

Test mode: IEEE 802.11a mode

Channel	Frequency (MHz)	PPSD (dBm)	Limit (dBm)	Result
Low	5180	3.23	17.00	PASS
Mid	5200	3.73	17.00	PASS
High	5240	4.09	17.00	PASS

Test mode: IEEE 802.11n HT20MHz mode

Channel	Frequency (MHz)	PPSD (dBm)	Limit (dBm)	Result
Low	5180	2.15	17.00	PASS
Mid	5200	2.03	17.00	PASS
High	5240	4.19	17.00	PASS

Test mode: IEEE 802.11n HT40MHz mode

Channel	Frequency (MHz)	PPSD (dBm)	Limit (dBm)	Result
Low	5190	-0.78	17.00	PASS
High	5230	-0.66	17.00	PASS

Test mode: IEEE 802.11ac VHT20MHz mode

Channel	Frequency (MHz)	PPSD (dBm)	Limit (dBm)	Result
Low	5180	1.08	17.00	PASS
Mid	5200	1.26	17.00	PASS
High	5240	1.66	17.00	PASS



Test mode: IEEE 802.11ac VHT40MHz mode

Channel	Frequency (MHz)	PPSD (dBm)	Limit (dBm)	Result
Low	5190	-1.90	17.00	PASS
High	5230	-1.66	17.00	PASS


Test mode: IEEE 802.11ac VHT80MHz mode

Channel	Frequency (MHz)	PPSD (dBm)	Limit (dBm)	Result
Mid	5210	-4.16	17.00	PASS

Note:Duty factor has been offsetted with cableloss


Test Plot
IEEE 802.11a mode:**CH Low****CH Mid**

CH High




IEEE 802.11n HT20 mode


CH Low





CH Mid




CH High




IEEE 802.11n HT40 mode
CH Low**CH High**


IEEE 802.11ac VHT20 mode CH Low




CH Mid




CH High




IEEE 802.11ac VHT40 mode CH Low



CH High

IEEE 802.11ac VHT80 mode

CH Mid




7.6 FREQUENCY STABILITY MEASUREMENT

LIMIT

According to §15.407(g), Manufacturers of U-NII devices are responsible for ensuring frequency stability such that an emission is maintained within the band of operation under all conditions of normal operation as specified in the user's manual.

TEST CONFIGURATION



TEST PROCEDURE

1. To ensure emission at the band edge is maintained within the authorized band, those values shall be measured by radiation emissions at upper and lower frequency points, and finally compensated by frequency deviation as procedures below.
2. The EUT was operated at the maximum output power, and connected to the spectrum analyzer, which is set to maximum hold function and peak detector. The peak value of the power envelope was measured and noted. The upper and lower frequency points were respectively measured relatively 10dB lower than the measured peak value.
3. The frequency deviation was calculated by adding the upper frequency point and the lower frequency point divided by two. Those detailed values of frequency deviation are provided in table below.

TEST RESULTS

U-NII-1-(5150MHz-5250MHz)					
Freq.(MHz)	Center Frequency (MHz)	Frequency Deviation (MHz)	Frequency Stability (ppm)	Temperature (°C)	Voltage (V)
5180	5179.915	0.085	16.41	25	V _{min}
5180	5179.919	0.081	15.64	25	V _{max}
5180	5179.916	0.084	16.22	25	V _{nor}
5180	5179.915	0.085	16.41	-10	V _{nor}
5180	5179.920	0.080	13.93	55	V _{nor}

7.7 RADIATED UNDESIRABLE EMISSION

LIMIT

Radiated emissions from 9 kHz to 25 GHz were measured according to the methods defines in ANSI C63.10-2013. The EUT was placed above the ground plane, 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz. The interface cables and equipment positions were varied within limits of reasonable applications to determine the positions producing maximum radiated emissions.



- For transmitters operating in the 5150-5250 MHz band: all emissions outside of the 5150-5350 MHz band shall not exceed an EIRP of -27dBm/MHz.
For transmitters operating in the 5250-5350 MHz band: all emissions outside of the 5150-5350 MHz band shall not exceed an EIRP of -27 dBm/MHz. Devices operating in the 5250-5350 MHz band that generate emissions in the 5150-5250 MHz band must meet all applicable technical requirements for operation in the 5150-5250 MHz band (including indoor use) or alternatively meet an out-of-band emission EIRP limit of -27 dBm/MHz in the 5150-5250 MHz band.
For transmitters operating in the 5470-5600 MHz and 5650-5725MHz band: all emissions outside of the 5470-5600 MHz and 5650-5725MHz band shall not exceed an EIRP of -27 dBm/MHz.
- KDB789033 v01 G)2)c) As specified in 15.407(b), emissions above 1000 MHz that are outside of the restricted bands are subject to a peak emission limit of -27 dBm/MHz (or -17 dBm/MHz as specified in 15.407(b)(4)). However, an out-of-band emission that complies with both the average and peak limits of 15.209 is not required to satisfy the -27 dBm/MHz or -17 dBm/MHz peak emission limit.
- According to §15.209(a), except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:


FREQUENCIES(MHz)	FIELD STRENGTH (microvolts/meter)	MEASUREMENT DISTANCE(meters)
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

Remark: Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g., Sections 15.231 and 15.241.

- In the emission table above, the tighter limit applies at the band edges.

Frequency (MHz)	Field Strength (μ V/m at 3-meter)	Field Strength (dB μ V/m at 3-meter)
30-88	100	40
88-216	150	43.5
216-960	200	46
Above 960	500	54

Test Configuration**Below 30MHz****Below 1 GHz**

Above 1 GHz**TEST PROCEDURE**

1. The EUT is placed on a turntable above ground plane, which is 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
6. Set the spectrum analyzer in the following setting as:

Below 1GHz:

RBW=100kHz / VBW=300kHz / Sweep=AUTO

Above 1GHz:

(a) PEAK: RBW=VBW=1MHz / Sweep=AUTO

(b) AVERAGE: RBW=1MHz / Sweep=AUTO

VBW=10Hz, when duty cycle is no less than 98 percent.

$VBW \geq 1/T$, when duty cycle is less than 98 percent, where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

Band	Duty Cycle(%)	T(ms)	1/T(kHz)	VBW Setting
IEEE 802.11 a	96	2.267	0.44	0.5KHz
IEEE 802.11n HT20	96.8	3.750	0.27	0.3KHz
IEEE 802.11n HT40	96.9	3.617	0.28	0.3KHz
IEEE 802.11ac HT20	96.5	3.167	0.32	0.5KHz
IEEE 802.11ac HT40	97	3.750	0.27	0.3KHz
IEEE 802.11ac HT80	93.1	3.167	0.32	0.5KHz

7. Repeat above procedures until the measurements for all frequencies are complete.

TEST RESULTS**Test Result of Radiated Emission****Below 30MHz**

The interference of the frequency value is lower than the limit below 20 db, measured as the background noise values and will not be recorded.

30MHz-1GHz

Operation Mode:	Normal Link	Test Date:	2017-7-22
Temperature:	25°C	Tested by:	Lily.Wang
Humidity:	48% RH	Polarity:	Ver. / Hor.

Frequency (MHz)	Ant. Pol. (H/V)	Reading (dBuV)	Correction Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
45.3300	V	16.46	13.37	29.83	40.00	-10.17	QP
171.6200	V	8.70	15.12	23.82	43.50	-19.68	peak
650.8000	V	6.19	24.45	30.64	46.00	-15.36	peak
763.3200	V	6.40	25.96	32.36	46.00	-13.64	peak
851.5900	V	5.42	26.14	31.56	46.00	-14.44	peak
993.2100	V	4.76	27.47	32.23	54.00	-21.77	peak
168.7100	H	9.54	15.05	24.59	43.50	-18.91	peak
673.1100	H	5.47	24.62	30.09	46.00	-15.91	peak
748.7700	H	5.31	26.42	31.73	46.00	-14.27	peak
870.9900	H	5.27	26.06	31.33	46.00	-14.67	peak
929.1900	H	5.53	26.43	31.96	46.00	-14.04	peak
998.0600	H	5.30	27.55	32.85	54.00	-21.15	peak

Remark:

1. Measuring frequencies from 30 MHz to the 1GHz.(no emission found from the lowest internal used/generated frequency to 30MHz)
2. Radiated emissions measured were made with an instrument using peak/quasi-peak detector mode.
3. Quasi-peak test would be performed if the peak result were greater than the quasi-peak limit or as required by the applicant.
4. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
5. Margin (dB) = Remark result (dBuV/m) – Quasi-peak limit (dBuV/m).

Above 1 GHz

Operation Mode:	Tx / IEEE 802.11a mode CH Low	Test Date:	2017-7-23
Temperature:	25°C	Tested by:	Lily.Wang
Humidity:	55% RH	Polarity:	Ver. / Hor.

Horizontal

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Degree (deg.)	Remark
1	10644.231	41.07	11.53	52.60	74.00	-21.40	100	24	peak
2	16365.385	37.51	15.22	52.73	74.00	-21.27	100	257	peak
N/A									

Vertical

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Degree (deg.)	Remark
1	10671.474	41.25	11.64	52.89	74.00	-21.11	100	5	peak
2	16365.385	38.37	15.22	53.59	74.00	-20.41	100	357	peak
N/A									

Operation Mode:	Tx / IEEE 802.11a mode CH Mid	Test Date:	2017-7-23
Temperature:	25°C	Tested by:	Lily.Wang
Humidity:	55% RH	Polarity:	Ver. / Hor.

Horizontal

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Degree (deg.)	Remark
1	10644.231	42.17	11.53	53.70	74.00	-20.30	100	220	peak
2	16038.461	36.44	13.60	50.04	74.00	-23.96	100	194	peak
N/A									

Vertical

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Degree (deg.)	Remark
1	10671.474	41.25	11.64	52.89	74.00	-21.11	100	263	peak
2	15248.397	36.52	13.65	50.17	74.00	-23.83	100	91	peak
N/A									

Operation Mode:	Tx / IEEE 802.11a mode CH High	Test Date:	2017-7-23
Temperature:	25°C	Tested by:	Lily.Wang
Humidity:	55% RH	Polarity:	Ver. / Hor.

Horizontal

No.	Frequency	Reading	Correct	Result	Limit	Margin	Height	Degree	Remark
	(MHz)	(dBuV)	Factor(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	(cm)	(deg.)	
1	10535.256	40.85	11.11	51.96	74.00	-22.04	100	60	peak
2	14567.308	37.41	15.56	52.97	74.00	-21.03	100	101	peak
N/A									

Vertical

No.	Frequency	Reading	Correct	Result	Limit	Margin	Height	Degree	Remark
	(MHz)	(dBuV)	Factor(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	(cm)	(deg.)	
1	10453.526	41.93	10.71	52.64	74.00	-21.36	100	321	peak
2	16338.141	37.63	15.08	52.71	74.00	-21.29	100	293	peak
N/A									

Operation Mode:	TX / IEEE 802.11n HT20 mode /CH Low	Test Date:	2017-7-23
Temperature:	25°C	Tested by:	Lily.Wang
Humidity:	55% RH	Polarity:	Ver. / Hor.

Horizontal

No.	Frequency	Reading	Correct	Result	Limit	Margin	Height	Degree	Remark
	(MHz)	(dBuV)	Factor(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	(cm)	(deg.)	
1	10889.423	40.04	12.49	52.53	74.00	-21.47	100	73	peak
2	15357.372	36.43	12.87	49.30	74.00	-24.70	100	193	peak
N/A									

Vertical

No.	Frequency	Reading	Correct	Result	Limit	Margin	Height	Degree	Remark
	(MHz)	(dBuV)	Factor(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	(cm)	(deg.)	
1	10862.180	40.89	12.38	53.27	74.00	-20.73	100	1	peak
2	15330.128	35.85	13.07	48.92	74.00	-25.08	100	1	peak
N/A									

Operation Mode:	TX / IEEE 802.11n HT20 mode /CH Mid	Test Date:	2017-7-23
Temperature:	25°C	Tested by:	Lily.Wang
Humidity:	55% RH	Polarity:	Ver. / Hor.

Horizontal

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Degree (deg.)	Remark
1	10508.013	42.24	11.00	53.24	74.00	-20.76	100	72	peak
2	16201.923	35.85	14.41	50.26	74.00	-23.74	100	316	peak
N/A									

Vertical

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Degree (deg.)	Remark
1	11080.128	40.60	12.69	53.29	74.00	-20.71	100	360	peak
2	15248.397	36.99	13.65	50.64	74.00	-23.36	100	141	peak
N/A									

Operation Mode:	TX / IEEE 802.11n HT20 mode /CH High	Test Date:	2017-7-23
Temperature:	25°C	Tested by:	Lily.Wang
Humidity:	55% RH	Polarity:	Ver. / Hor.

Horizontal

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Degree (deg.)	Remark
1	10671.474	41.59	11.64	53.23	74.00	-20.77	100	21	peak
2	16283.654	36.03	14.81	50.84	74.00	-23.16	100	333	peak
N/A									

Vertical

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Degree (deg.)	Remark
1	10889.423	41.45	12.49	53.94	74.00	-20.06	100	335	peak
2	16038.461	37.64	13.60	51.24	74.00	-22.76	100	120	peak
N/A									

Operation Mode:	TX / IEEE 802.11n HT40 mode /CH Low	Test Date:	2017-7-23
Temperature:	25°C	Tested by:	Lily.Wang
Humidity:	55% RH	Polarity:	Ver. / Hor.

Horizontal

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Degree (deg.)	Remark
1	10453.526	41.30	10.71	52.01	74.00	-21.99	100	274	peak
2	15983.974	37.15	13.36	50.51	74.00	-23.49	100	263	peak
N/A									

Vertical

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Degree (deg.)	Remark
1	10317.308	41.24	9.96	51.20	74.00	-22.80	100	165	peak
2	15112.180	35.16	14.61	49.77	74.00	-24.23	100	334	peak
N/A									

Operation Mode:	TX / IEEE 802.11n HT40 mode /CH High	Test Date:	2017-7-23
Temperature:	25°C	Tested by:	Lily.Wang
Humidity:	55% RH	Polarity:	Ver. / Hor.

Horizontal

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Degree (deg.)	Remark
1	10562.500	40.98	11.21	52.19	74.00	-21.81	100	336	peak
2	16092.949	36.14	13.87	50.01	74.00	-23.99	100	83	peak
N/A									

Vertical

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Degree (deg.)	Remark
1	10181.090	41.23	9.21	50.44	74.00	-23.56	100	49	peak
2	15493.590	37.36	11.91	49.27	74.00	-24.73	100	67	peak
N/A									

Operation Mode:	TX / IEEE 802.11ac VHT20 mode /CH Low	Test Date:	2017-7-23
Temperature:	25°C	Tested by:	Lily.Wang
Humidity:	55% RH	Polarity:	Ver. / Hor.

Horizontal

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Degree (deg.)	Remark
1	10453.526	41.27	10.71	51.98	74.00	-22.02	100	302	peak
2	15929.487	37.18	13.19	50.37	74.00	-23.63	100	93	peak
N/A									

Vertical

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Degree (deg.)	Remark
1	10644.231	41.66	11.53	53.19	74.00	-20.81	100	333	peak
2	15983.974	36.86	13.36	50.22	74.00	-23.78	100	202	peak
N/A									

Operation Mode:	TX / IEEE 802.11ac VHT20 mode /CH Mid	Test Date:	2017-7-23
Temperature:	25°C	Tested by:	Lily.Wang
Humidity:	55% RH	Polarity:	Ver. / Hor.

Horizontal

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Degree (deg.)	Remark
1	10508.013	40.92	11.00	51.92	74.00	-22.08	100	122	peak
2	15112.180	35.06	14.61	49.67	74.00	-24.33	100	89	peak
N/A									

Vertical

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Degree (deg.)	Remark
1	10453.526	40.81	10.71	51.52	74.00	-22.48	100	15	peak
2	15956.731	37.17	13.28	50.45	74.00	-23.55	100	182	peak
N/A									

Operation Mode:	TX / IEEE 802.11ac VHT20 mode /CH High	Test Date:	2017-7-23
Temperature:	25°C	Tested by:	Lily.Wang
Humidity:	55% RH	Polarity:	Ver. / Hor.

Horizontal

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Degree (deg.)	Remark
1	10453.526	41.69	10.71	52.40	74.00	-21.60	100	283	peak
2	16365.385	37.79	15.22	53.01	74.00	-20.99	100	246	peak
N/A									

Vertical

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Degree (deg.)	Remark
1	10371.795	40.82	10.26	51.08	74.00	-22.92	100	209	peak
2	15956.731	37.14	13.28	50.42	74.00	-23.58	100	166	peak
N/A									

Operation Mode:	TX / IEEE 802.11ac VHT40 mode /CH Low	Test Date:	2017-7-23
Temperature:	25°C	Tested by:	Lily.Wang
Humidity:	55% RH	Polarity:	Ver. / Hor.

Horizontal

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Degree (deg.)	Remark
1	10508.013	40.94	11.00	51.94	74.00	-22.06	100	203	peak
2	16120.192	36.26	14.00	50.26	74.00	-23.74	100	93	peak
N/A									

Vertical

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Degree (deg.)	Remark
1	10916.667	40.47	12.60	53.07	74.00	-20.93	100	290	peak
2	16147.436	36.03	14.14	50.17	74.00	-23.83	100	128	peak
N/A									

Operation Mode:	TX / IEEE 802.11ac VHT40 mode /CH High	Test Date:	2017-7-23
Temperature:	25°C	Tested by:	Lily.Wang
Humidity:	55% RH	Polarity:	Ver. / Hor.

Horizontal

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Degree (deg.)	Remark
1	10508.013	41.12	11.00	52.12	74.00	-21.88	100	67	peak
2	16365.385	37.77	15.22	52.99	74.00	-21.01	100	344	peak
N/A									

Vertical

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Degree (deg.)	Remark
1	10725.961	41.35	11.85	53.20	74.00	-20.80	100	192	peak
2	15575.320	37.35	12.09	49.44	74.00	-24.56	100	272	peak
N/A									

Operation Mode:	TX / IEEE 802.11ac VHT80 mode /CH Mid	Test Date:	2017-7-23
Temperature:	25°C	Tested by:	Lily.Wang
Humidity:	55% RH	Polarity:	Ver. / Hor.

Horizontal

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Degree (deg.)	Remark
1	10616.987	41.39	11.43	52.82	74.00	-21.18	100	351	peak
2	15575.320	37.39	12.09	49.48	74.00	-24.52	100	241	peak
N/A									

Vertical

No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Degree (deg.)	Remark
1	10562.500	42.25	11.21	53.46	74.00	-20.54	100	126	peak
2	15466.346	38.35	12.10	50.45	74.00	-23.55	100	126	peak
N/A									

7.8 POWERLINE CONDUCTED EMISSIONS

LIMIT

According to §15.207(a), except as shown in paragraphs (b) and (c) of this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50 μ H/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequency ranges.

Frequency Range (MHz)	Limits (dB μ V)	
	Quasi-peak	Average
0.15 to 0.50	66 to 56*	56 to 46*
0.50 to 5	56	46
5 to 30	60	50

* Decreases with the logarithm of the frequency.

TEST CONFIGURATION

See test photographs attached in Appendix 1 for the actual connections between EUT and support equipment.

TEST PROCEDURE

1. The EUT was placed on a table, which is 0.8m above ground plane.
2. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
3. Repeat above procedures until all frequency measured were complete.

TEST RESULTS


The initial step in collecting conducted data is a spectrum analyzer peak scan of the measurement range. Significant peaks are then marked as shown on the following data page, and these signals are then quasi-peaked.

Test Data

Job No.:	C170614R01	Date:	2017/7/1
Model No.:	macaroon M1	Time:	AM 10:12:25
Standard:	FCC Class B	Temp.(C)/Hum.(%):	22(C)/48%
Test item:	Conduction test	Test By:	Lily.Wang
Line:	L1	Test Voltage:	AC 120V/60Hz
Model:		Description:	

L1


80.0 dBuV



No.	Frequency (MHz)	QuasiPeak reading (dBuV)	Average reading (dBuV)	Correction factor (dB)	QuasiPeak result (dBuV)	Average result (dBuV)	QuasiPeak limit (dBuV)	Average limit (dBuV)	QuasiPeak margin (dB)	Average margin (dB)	Remark
1	0.1581	5.68	-0.33	20.58	26.26	20.25	65.56	55.56	-39.30	-35.31	Pass
2*	0.4145	7.14	-0.26	20.53	27.67	20.27	57.56	47.56	-29.89	-27.29	Pass
3	0.7927	1.34	-2.74	20.50	21.84	17.76	56.00	46.00	-34.16	-28.24	Pass
4	1.1601	2.52	-2.49	20.44	22.96	17.95	56.00	46.00	-33.04	-28.05	Pass
5	4.9717	0.93	-4.57	20.61	21.54	16.04	56.00	46.00	-34.46	-29.96	Pass
6	23.6432	0.33	-4.88	20.86	21.19	15.98	60.00	50.00	-38.81	-34.02	Pass

Note: 1. L1 = Line One (Live Line) / L2 = Line Two (Neutral Line).


Job No.:	C170614R01	Date:	2017/7/1
Model No.:	macaroon M1	Time:	AM 10:17:44
Standard:	FCC Class B	Temp.(C)/Hum.(%):	22(C)/48%
Test item:	Conduction test	Test By:	Lily.Wang
Line:	L2	Test Voltage:	AC 120V/60Hz
Model:		Description:	



No.	Frequency (MHz)	QuasiPeak reading (dBuV)	Average reading (dBuV)	Correction factor (dB)	QuasiPeak result (dBuV)	Average result (dBuV)	QuasiPeak limit (dBuV)	Average limit (dBuV)	QuasiPeak margin (dB)	Average margin (dB)	Remark
1	0.1547	5.86	-0.26	20.36	26.22	20.10	65.74	55.74	-39.52	-35.64	Pass
2	0.2236	5.83	-0.49	20.42	26.25	19.93	62.68	52.68	-36.43	-32.75	Pass
3	0.4052	6.61	-1.05	20.46	27.07	19.41	57.75	47.75	-30.68	-28.34	Pass
4*	0.7867	1.30	-2.53	20.46	21.76	17.93	56.00	46.00	-34.24	-28.07	Pass
5	1.2947	-0.31	-3.50	20.47	20.16	16.97	56.00	46.00	-35.84	-29.03	Pass
6	4.8494	0.99	-4.36	20.74	21.73	16.38	56.00	46.00	-34.27	-29.62	Pass

Note: 1. L1 = Line One (Live Line) / L2 = Line Two (Neutral Line).


Job No.:	C170614R01	Date:	2017/7/1
Model No.:	macaroon M1	Time:	AM 10:02:30
Standard:	FCC Class B	Temp.(C)/Hum.(%):	22(C)/48%
Test item:	Conduction test	Test By:	Lily.Wang
Line:	L1	Test Voltage:	AC 240V/60Hz
Model:		Description:	



No.	Frequency (MHz)	QuasiPeak reading (dBuV)	Average reading (dBuV)	Correction factor (dB)	QuasiPeak result (dBuV)	Average result (dBuV)	QuasiPeak limit (dBuV)	Average limit (dBuV)	QuasiPeak margin (dB)	Average margin (dB)	Remark
1	0.1882	4.58	-0.76	20.53	25.11	19.77	64.12	54.12	-39.01	-34.35	Pass
2	0.4904	6.41	-1.07	20.49	26.90	19.42	56.16	46.16	-29.26	-26.74	Pass
3*	0.7947	6.74	-0.52	20.50	27.24	19.98	56.00	46.00	-28.76	-26.02	Pass
4	3.0876	2.93	-3.89	20.52	23.45	16.63	56.00	46.00	-32.55	-29.37	Pass
5	4.5040	2.44	-3.95	20.59	23.03	16.64	56.00	46.00	-32.97	-29.36	Pass
6	23.4295	1.72	-4.83	20.86	22.58	16.03	60.00	50.00	-37.42	-33.97	Pass

Note: 1. L1 = Line One (Live Line) / L2 = Line Two (Neutral Line).

Job No.:	C170614R01	Date:	2017/7/1
Model No.:	macaroon M1	Time:	AM 10:07:28
Standard:	FCC Class B	Temp.(C)/Hum.(%):	22(C)/48%
Test item:	Conduction test	Test By:	Lily.Wang
Line:	L2	Test Voltage:	AC 240V/60Hz
Model:		Description:	



No.	Frequency (MHz)	QuasiPeak reading (dBuV)	Average reading (dBuV)	Correction factor (dB)	QuasiPeak result (dBuV)	Average result (dBuV)	QuasiPeak limit (dBuV)	Average limit (dBuV)	QuasiPeak margin (dB)	Average margin (dB)	Remark
1	0.2121	5.79	-0.76	20.41	26.20	19.65	63.12	53.12	-36.92	-33.47	Pass
2*	0.5159	4.91	-1.63	20.45	25.36	18.82	56.00	46.00	-30.64	-27.18	Pass
3	1.0129	3.56	-1.80	20.45	24.01	18.65	56.00	46.00	-31.99	-27.35	Pass
4	1.3487	1.84	-2.81	20.48	22.32	17.67	56.00	46.00	-33.68	-28.33	Pass
5	4.7531	1.92	-3.99	20.73	22.65	16.74	56.00	46.00	-33.35	-29.26	Pass
6	22.9604	0.30	-5.06	20.87	21.17	15.81	60.00	50.00	-38.83	-34.19	Pass

Note: 1. L1 = Line One (Live Line) / L2 = Line Two (Neutral Line).

Remark:

- 1.The measuring frequencies range between 0.15 MHz and 30 MHz.
- 2.The emissions measured in the frequency range between 0.15 MHz and 30MHz were made with an instrument using Quasi-peak detector and Average detector.
- 3.“---” denotes the emission level was or more than 2dB below the Average limit, and no re-check was made.
- 4.The IF bandwidth of SPA between 0.15MHz and 30MHz was 10KHz. The IF bandwidth of Test Receiver between 0.15MHz and 30MHz was 9kHz.

END OF REPORT