FCC Part 15C
Measurement and Test Report

For

Xiamen Jinchan Electronics Co., Ltd.

8 Floor, No.3 Zhongwan Road, Jimei District, Xiamen,

Fujian Province, China.

FCC ID: 2AMJ4CS-1000T

FCC Rule(s):	FCC Part 15.231
Product Description:	Transmitter
Tested Model:	CS-1000T
Report No.:	STR17068237I
Tested Date:	2017-06-16 to 2017-08-18
Issued Date:	2017-08-18
Tested By:	Iven Guo / Engineer
Reviewed By:	Silin Chen / EMC Manager
Approved & Authorized By:	Jandy So / PSQ Manager

Prepared By:

Shenzhen SEM.Test Technology Co., Ltd.
1/F, Building A, Hongwei Industrial Park, Liuxian 2nd Road,
Bao'an District, Shenzhen, P.R.C.（518101）
Tel.: +86-755-33663308 Fax.: +86-755-33663309 Website: www.semtest.com.cn

Note: This test report is limited to the above client company and the product model only. It may not be duplicated without prior permitted by Shenzhen SEM.Test Technology Co., Ltd.

TABLE OF CONTENTS

1. GENERAL INFORMATION 3
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT) 3
1.2 TEST STANDARDS 4
1.3 TEST METHODOLOGY 4
1.4 TEST FACILITY 4
1.5 EUT SETUP AND TEST MODE 5
1.6 MEASUREMENT UNCERTAINTY 5
1.7 TEST EQUIPMENT LIST AND DETAILS 6
2. SUMMARY OF TEST RESULTS 7
3. ANTENNA REQUIREMENT 8
3.1 STANDARD APPLICABLE 8
3.2 TEST RESULT 8
4. CONDUCTED EMISSIONS 9
4.1 TEST PROCEDURE 9
4.2 BASIC TEST SETUP BLOCK DIAGRAM 9
4.3 ENVIRONMENTAL CONDITIONS 9
4.4 TEST RECEIVER SETUP 9
4.5 SUMMARY OF TEST RESULTS/PLOTS 10
4.6 CONDUCTED EMISSIONS TEST DATA 10
5. RADIATED EMISSIONS 12
5.1 STANDARD APPLICABLE 12
5.2 TEST PROCEDURE 13
5.3 CORRECTED AMPLITUDE & MARGIN CALCULATION 14
5.4 ENVIRONMENTAL CONDITIONS 14
5.5 SUMMARY OF TEST RESULTS/PLOTS 14
6. 20DB BANDWIDTH 17
6.1 STANDARD APPLICABLE 17
6.1 TEST PROCEDURE 17
6.2 ENVIRONMENTAL CONDITIONS 17
6.3 SUMMARY OF TEST RESULTS/PLOTS 17
7. TRANSMISSION TIME 19
7.1 STANDARD APPLICABLE 19
7.2 TEST PROCEDURE 19
7.3 ENVIRONMENTAL CONDITIONS 19
7.4 SUMMARY OF TEST RESULTS/PLOTS 19
8. DUTY CYCLE 21
8.1 STANDARD APPLICABLE 21
8.2 TEST PROCEDURE 21
8.3 ENVIRONMENTAL CONDITIONS 21
8.4 SUMMARY OF TEST RESULTS/PLOTS 21

1. GENERAL INFORMATION

1.1 Product Description for Equipment Under Test (EUT)

Client Information

Applicant:	Xiamen Jinchan Electronics Co., Ltd.
Address of applicant:	8 Floor, No.3 Zhongwan Road, Jimei District, Xiamen, Fujian Province, China.
Manufacturer:	Xiamen Jinchan Electronics Co., Ltd.
Address of manufacturer:	8 Floor, No.3 Zhongwan Road, Jimei District, Xiamen, Fujian Province, China.

General Description of EUT	
Product Name:	Transmitter
Trade Name:	Xiamen Jinchan
Model No.:	CS-1000T
Adding Model(s):	/
Rated Voltage:	DC 5V Adapter
Power Adaptor :	YMX-PO50020E641 I/P: 100-240V~500/60Hz, 0.6A; O/P: DC 5V/2A
Software Version:	/
Hardware Version:	/
Note: The test data is gathered from a production sample provided by the manufacturer.	

Technical Characteristics of EUT	
Frequency Range:	433.92 MHz
Max. Field Strength:	85.63dBuV/m (at 3m distance)
Data Rate:	/
Modulation:	ASK
Antenna Type:	Reverse Threads External Antenna
Antenna Gain:	0dBi
Lowest Internal Frequency of EUT:	22.1184MHz

1.2 Test Standards

The following report is prepared on behalf of the Xiamen Jinchan Electronics Co., Ltd. in accordance with FCC Part 15, Subpart C, and section 15.231, 15.203, 15.205 and 15.209 of the Federal Communication Commissions rules.

The objective is to determine compliance with FCC Part 15, Subpart C, and section 15.231, 15.203, 15.205 and 15.209 of the Federal Communication Commissions rules.

Maintenance of compliance is the responsibility of the manufacturer. Any modification of the product, which result in lowering the emission/immunity, should be checked to ensure compliance has been maintained.

1.3 Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard for Testing Unlicensed Wireless Devices, and ANSI C63.4-2014, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

1.4 Test Facility

FCC – Registration No.: 125990

Shenzhen SEM Test Technology Co., Ltd. Laboratory has been recognized to perform compliance testing on equipment subject to the Commissions Declaration Of Conformity (DOC). The Designation Number is CN5010, and Test Firm Registration Number is 125990.

Industry Canada (IC) Registration No.: 11464A

The 3m Semi-anechoic chamber of Shenzhen SEM.Test Technology Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 11464A.

1.5 EUT Setup and Test Mode

The EUT was operated at continuous transmitting mode that was for the purpose of the measurements. All testing shall be performed under maximum output power condition, and to measure its highest possible emissions level, more detailed description as follows:

Test Mode List		
Test Mode	Description	Remark
TM1	Transmitting	With modulation(433.92MHz)

EUT Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
USB Cable	1.0	Shielded	Without Ferrite

Special Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
/	/	/	/

Auxiliary Equipment List and Details			
Description	Manufacturer	Model	Serial Number
/	/	/	/

1.6 Measurement Uncertainty

Measurement uncertainty		
Parameter	Conditions	Uncertainty
Occupied Bandwidth	Conducted	±1.5%
Conducted Spurious Emission	Conducted	±2.17dB
Transmission Time	Conducted	±5%
Conducted Emissions	Conducted	±2.88dB
Transmitter Spurious Emissions	Radiated	±5.1dB

1.7 Test Equipment List and Details

No.	Description	Manufacturer	Model	Serial No.	Cal Date	Due Date
SEMT-1072	Spectrum Analyzer	Agilent	E4407B	MY41440400	2017-06-12	2018-06-11
SEMT-1031	Spectrum Analyzer	Rohde & Schwarz	FSP30	836079/035	2017-06-12	2018-06-11
SEMT-1007	EMI Test Receiver	Rohde & Schwarz	ESVB	825471/005	2017-06-12	2018-06-11
SEMT-1008	Amplifier	Agilent	8447F	3113A06717	2017-06-12	2018-06-11
SEMT-1043	Amplifier	C&D	PAP-1G18	2002	2017-06-12	2018-06-11
SEMT-1011	Broadband Antenna	Schwarz beck	VULB9163	9163-333	2017-06-12	2018-06-11
SEMT-1042	Horn Antenna	ETS	3117	00086197	2017-06-12	2018-06-11
SEMT-1121	Horn Antenna	Schwarzbeck	BBHA 9170	BBHA9170582	2017-06-12	2018-06-11
SEMT-1069	Loop Antenna	Schwarz beck	FMZB 1516	9773	2017-06-12	2018-06-11
SEMT-1001	EMI Test Receiver	Rohde & Schwarz	ESPI	101611	2017-06-12	2018-06-11
SEMT-1003	L.I.S.N	Schwarz beck	NSLK8126	8126-224	2017-06-12	2018-06-11
SEMT-1002	Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100911	2017-06-12	2018-06-11

2. SUMMARY OF TEST RESULTS

FCC Rules	Description of Test Item	Result
§ 15.203	Antenna Requirement	Compliant
§15.205	Restricted Band of Operation	Compliant
§ 15.207(a)	Conducted Emission	Compliant
§ 15.209	Radiated Spurious Emissions	Compliant
§15.231(a)	Deactivation Testing	Compliant
§15.231(b)	Radiated Emissions	Compliant
§15.231(c)	20dB Bandwidth Testing	Compliant

3. Antenna Requirement

3.1 Standard Applicable

According to FCC Part 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

3.2 Test Result

This product has a reverse threads external antenna, fulfill the requirement of this section.

4. Conducted Emissions

4.1 Test Procedure

The setup of EUT is according with per ANSI C63.4-2014 measurement procedure. The specification used was with the FCC Part 15.207 Limit.
The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.
The spacing between the peripherals was 10 cm.

4.2 Basic Test Setup Block Diagram



4.3 Environmental Conditions

Temperature:	25 °C
Relative Humidity:	52%
ATM Pressure:	1012 mbar

4.4 Test Receiver Setup

During the conducted emission test, the test receiver was set with the following configurations:

Start Frequency ..... 150 kHz
Stop Frequency..... 30 MHz
Sweep Speed ..... Auto
IF Bandwidth..... 10 kHz
Quasi-Peak Adapter Bandwidth ..... 9 kHz
Quasi-Peak Adapter Mode ..... Normal

4.5 Summary of Test Results/Plots

According to the data in section 4.6, the EUT complied with the FCC Part 15.207 Conducted margin for a Class B device, with the *worst* margin reading of:

-3.86 dB at **0.4420 MHz** in the **Line** mode, **QP** detector, 0.15-30MHz

4.6 Conducted Emissions Test Data

Plot of Conducted Emissions Test Data

EUT: *Transmitter*
Tested Model: *CS-1000T*
Operating Condition: *Transmitting*
Comment: *AC 120V/60Hz, Adapter DC 5V*

Test Specification: *Neutral*



No.	Frequency	Reading	Correct	Result	Limit	Margin	Detector
	(MHz)	(dBuV)	(dB/m)	(dBuV)	(dBuV)	(dB)	
1	0.1620	32.28	9.84	42.12	55.36	-13.24	AVG
2*	0.1660	48.45	9.83	58.28	65.16	-6.88	QP
3	0.1900	34.82	9.81	44.63	54.04	-9.41	AVG
4	0.1940	47.13	9.81	56.94	63.86	-6.92	QP
5	0.2900	29.84	9.80	39.64	50.52	-10.88	AVG
6	0.2940	42.27	9.80	52.07	60.41	-8.34	QP

Test Specification: *Line*



No.	Frequency	Reading	Correct	Result	Limit	Margin	Detector
	(MHz)	(dBuV)	(dB/m)	(dBuV)	(dBuV)	(dB)	
1	0.1620	48.59	9.84	58.43	65.36	-6.93	QP
2	0.1660	30.55	9.83	40.38	55.16	-14.78	AVG
3	0.2500	44.81	9.80	54.61	61.76	-7.15	QP
4	0.2500	27.95	9.80	37.75	51.76	-14.01	AVG
5*	0.4420	43.36	9.80	53.16	57.02	-3.86	QP
6	0.4580	23.22	9.80	33.02	46.73	-13.71	AVG

5. Radiated Emissions

5.1 Standard Applicable

According to §15.231(b), the field strength of emissions from intentional radiators operated under this section shall not exceed the following:

Fundamental Frequency (MHz)	Field Strength of Fundamental (microvolts/meter)	Field Strength of Spurious Emissions (microvolts/meter)
40.66 - 40.70	2,250	225
70 - 130	1,250	125
130 - 174	1,250 to 3,750 **	125 to 375 **
174 - 260	3,750	375
260 - 470	3,750 to 12,500 **	375 to 1,250 **
Above 470	12,500	1,250

** linear interpolations

The limits on the field strength of the spurious emissions in the above table are based on the fundamental frequency of the intentional radiator. Spurious emissions shall be attenuated to the average (or, alternatively, CISPR quasi-peak) limits shown in this table or to the general limits shown in §15.209, whichever limit permits a higher field strength.

The emission limit in this paragraph is based on measurement instrumentation employing an average detector. The provisions in §15.35 for limiting peak emissions apply. Spurious Radiated Emissions measurements starting below or at the lowest crystal frequency.

Compliance with the provisions of §15.205 shall be demonstrated using the measurement instrumentation specified in that section.

5.2 Test Procedure

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.205 15.231(b) and FCC Part 15.209 Limit.





5.3 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and the Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

Corr. Ampl. = Indicated Reading +Ant.Loss +Cab. Loss – Ampl.Gain

The "**Margin**" column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -6dBμV means the emission is 6dBμV below the maximum limit. The equation for margin calculation is as follows:

Margin = Corr. Ampl. – FCC Part 15C Limit

5.4 Environmental Conditions

Temperature:	21° C
Relative Humidity:	50%
ATM Pressure:	1011 mbar

5.5 Summary of Test Results/Plots

According to the data below, the FCC Part 15.205, 15.209 and 15.231 standards, and had the worst margin of:

Note: this EUT was tested in 3 orthogonal positions and the worst case position data was reported.

Plot of Radiated Emissions Test Data

EUT: *Transmitter*
Tested Model: *CS-1000T*
Operating Condition: *Transmitting(433.92MHz)*
Comment: *AC 120V/60Hz, Adapter DC 5V*
Test Specification: *Horizontal*



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Dutycycle Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ( )	Height (cm)	Remark
1	433.92	96.37	-10.74	N/A	85.63	100.83	-15.2	169	100	Peak
	433.92	/	/	-8.87	76.76	80.83	-4.07	175	100	Ave
2	867.84	63.95	-5.42	N/A	58.53	80.83	-22.3	23	100	Peak
	867.84	/	/	-8.87	49.66	60.83	-11.17	69	100	Ave

Above 1GHz

No.	Frequency MHz	Reading dBuV/m	Corr. Factor (dB)	Dutycycle Factor (dB)	Result dBuV/m	Limit dBuV/m	Margin dB	Deg. (°)	Height (cm)	Remark
1	1215.983	68.42	-13.80	N/A	54.62	74.00	-19.38	210	150	Peak
	1215.983	/	/	-8.87	45.75	54.00	-8.25	123	150	Ave
2	1301.760	71.49	-13.14	N/A	58.35	74.00	-15.65	180	150	Peak
	1301.760	/	/	-8.87	49.48	54.00	-4.52	228	150	Ave
3	2603.520	66.41	-2.47	N/A	63.94	80.83	-16.89	210	150	Peak
	2603.520	/	/	-8.87	55.07	60.83	-5.76	159	150	Ave

Test Specification: *Vertical*



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Dutycycle Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ( )	Height (cm)	Remark
1	433.92	95.37	-10.74	N/A	84.63	100.83	-16.2	161	100	Peak
	433.92	N/A	N/A	-8.87	75.76	80.83	-5.07	113	100	Ave
2	867.84	54.32	-5.42	N/A	48.9	80.83	-31.93	96	100	Peak
	867.84	N/A	N/A	-8.87	40.03	60.83	20.8	2	100	Ave

Above 1GHz

No.	Frequency MHz	Reading dBuV/m	Corr. Factor (dB)	Dutycycle Factor (dB)	Result dBuV/m	Limit dBuV/m	Margin dB	Deg. (°)	Height (cm)	Remark
1	1301.760	71.53	-13.14	N/A	58.39	74.00	-15.61	211	150	Peak
	1301.760	/	/	-8.87	49.52	54.00	-4.48	143	150	Ave
2	2169.600	61.34	-2.79	N/A	58.55	80.83	-22.28	123	150	Peak
	2169.600	/	/	-8.87	49.68	60.83	-11.15	258	150	Ave
3	2603.520	63.44	-2.48	N/A	60.96	80.83	-19.87	256	150	Peak
	2603.520	/	/	-8.87	51.82	60.83	-9.01	149	150	Ave

Note: Testing is carried out with frequency rang 9kHz to the tenth harmonics, which above 6th Harmonics are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

The fundamental frequency is 433.92MHz, so the fundamental and spurious emissions radiated limit base on the the operating frequency 433.92MHz.

6. 20dB Bandwidth

6.1 Standard Applicable

According to FCC Part 15.231(c), The bandwidth of the emission shall be no wider than 0.25% of the center frequency for devices operating above 70 MHz and below 900 MHz. Bandwidth is determined at the points 20 dB down from the modulated carrier.

6.1 Test Procedure

With the EUT's antenna attached, the EUT's 20dB Bandwidth power was received by the test antenna, which was connected to the spectrum analyzer with the START, and STOP frequencies set to the EUT's operation band.

6.2 Environmental Conditions

Temperature:	21° C
Relative Humidity:	52%
ATM Pressure:	1011 mbar

6.3 Summary of Test Results/Plots

Test Frequency MHz	20dB Bandwidth kHz	Limit kHz	Result
433.92	36.496	1084.8	Pass

Limit = Fundamental Frequency X 0.25% = 433.92 MHz X 0.25% = 1084 kHz

Please refer to the attached plots.

433.92MHz:

20dB Bandwidth Test Plot



7. Transmission Time

7.1 Standard Applicable

According to FCC Part 15.231 (a), the transmitter shall be complied the following requirements:

1) A manually operated transmitter shall employ a switch that will automatically deactivate the transmitter within not more than 5 seconds of being released.
(2) A transmitter activated automatically shall cease transmission within 5 seconds after activation.
(3) Periodic transmissions at regular predetermined intervals are not permitted. However, polling or supervision transmissions, including data, to determine system integrity of transmitters used in security or safety applications are allowed if the total duration of transmissions does not exceed more than two seconds per hour for each transmitter. There is no limit on the number of individual transmissions, provided the total transmission time does not exceed two seconds per hour.

7.2 Test Procedure

With the EUT's antenna attached, the EUT's output signal was received by the test antenna, which was connected to the spectrum analyzer. Set the center frequency to 433.92MHz, than set the spectrum analyzer to Zero Span for the release time reading. During the testing, the switch was released then the EUT automatically deactivated.

7.3 Environmental Conditions

Temperature:	20° C
Relative Humidity:	52%
ATM Pressure:	1011 mbar

7.4 Summary of Test Results/Plots

Transmission Type	Test Frequency MHz	Transmission Time seconds	Limit s	Result
Manually	433.92	0.240	5	Pass

Please refer to the attached plots.

433.92MHz:

Transmission Time



8. Duty Cycle

8.1 Standard Applicable

According to FCC Part 15.231 (b)(2) and 15.35 (c), For pulse operation transmitter, the averaging pulsed emissions are calculated by peak value of measured emission plus duty cycle factor.

8.2 Test Procedure

With the EUT's antenna attached, the EUT's output signal was received by the test antenna, which was connected to the spectrum analyzer. Set the center frequency to 433.92MHz, than set the spectrum analyzer to Zero Span for the release time reading. During the testing, the switch was released then the EUT automatically deactivated.

8.3 Environmental Conditions

Temperature:	20° C
Relative Humidity:	52%
ATM Pressure:	1011 mbar

8.4 Summary of Test Results/Plots

433.93MHz:

Type of Pulse	Width of Pulse ms	Quantity of Pulse	Transmission Time ms	Total Time (T_{on}) ms
Pulse 1 (Wide)	0.870	9	7.83	12.87
Pulse 2 (Narrow)	0.315	16	5.04	

Test Period (T_p) ms	Total Time (T_{on}) ms	Duty Cycle %	Duty Cycle Factor dB
35.4	12.87	36.35	-8.87

Remark: Duty Cycle Factor=20*log(Duty Cycle)

Please refer to the attached test plots

433.92MHz:







******* END OF REPORT *******