RF EXPOSURE
Test Report

Report No.	:	**MTi260403008-0205E2**
Date of issue	:	**2026-05-08**
Applicant	:	**Shenzhen Gudsen Technology Co., Ltd.**
Product	:	**R16 Ultra Direct Drive Wheel Base** **R16S Ultra Direct Drive Wheel Base**
Model(s)	:	**R16S Ultra, R16 Ultra**
FCC ID	:	**2AMJR-D12**

Shenzhen Microtest Co., Ltd.

Table of contents

1 RF EXPOSURE EVALUATION 4
2 Measurement Result 5

TEST REPORT

Report No.: MTi260403008-0205E2

Test Result Certification		
Applicant	Shenzhen Gudsen Technology Co., Ltd.	
Applicant Address	Room 1903-1904, Building 3.Nanshan Zhiyuan Chongwen Park, No. 3370 Liuxian Avenue, Nanshan District, Shenzhen, China	
Manufacturer	Shenzhen Gudsen Technology Co., Ltd.	
Manufacturer Address	Room 1903-1904, Building 3.Nanshan Zhiyuan Chongwen Park, No. 3370 Liuxian Avenue, Nanshan District, Shenzhen, China	
Factory	Shenzhen Gudsen Technology Co., Ltd.	
Factory Address	Room 1903-1904, Building 3.Nanshan Zhiyuan Chongwen Park, No. 3370 Liuxian Avenue, Nanshan District, Shenzhen, China	
Product description		
Product name	R16 Ultra Direct Drive Wheel Base R16S Ultra Direct Drive Wheel Base	
Trademark	MOZA	
Model name	R16S Ultra	
Series Model(s)	R16 Ultra	
Standards	47 CFR Part 2.1091	
Test method	KDB 447498 D01 v06	
Testing Information		
Date of test	2026-04-30 to 2026-05-08	
Test Result	Pass	
Prepared by:	Letter Lan	Letter. Lan.
Reviewed by:	David Lee	David. Lee
Approved by:	Lewis Lian	Lewis Lian

1 RF EXPOSURE EVALUATION

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) Radiation as specified in §1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm^2)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	*100	6
3.0-30	1842/f	4.89/f	*900/f^2	6
30-300	61.4	0.163	1.0	6
300-1,500			f/300	6
1,500-100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f^2	30
30-300	27.5	0.073	0.2	30
300-1,500			f/1500	30
1,500-100,000			1.0	30

f = frequency in MHz * = Plane-wave equivalent power density

MPE Calculation Method

Friis transmission formula: Pd= (Pout*G)\ (4*pi*R^2)

Where

Pd= Power density in mW/cm^2

Pout=output power to antenna in mW

G= Numeric gain of the antenna relative to isotropic antenna

Pi=3.1415926

R= distance between observation point and center of the radiator in cm(20cm)

Pd the limit of MPE, 1mW/cm^2. If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

2 Measurement Result

BT:
Operation Frequency: 2402-2480MHz,
Power density limited: 1mW/ cm2

Antenna Type: PCB Antenna

Antenna gain: 0dBi
R=20cm
mW=10^(dBm/10)
Antenna gain Numeric=10^(dBi/10)= 10^(0/10)=1

BT:

Channel Freq. (MHz)	modulation	conducted power (dBm)	Tune-up power (dBm)	Max		Antenna		Evaluation result (mW/cm^2)	Power density Limits (mW/cm^2)
				tune-up power		Gain			
				(dBm)	(mW)	(dBi)	Numeric		
2402	GFSK	-5.22	-5±1	-4	0.398	0	1.00	0.0001	1
2441		-4.79	-4±1	-3	0.501	0	1.00	0.0001	1
2480		-4.46	-4±1	-3	0.501	0	1.00	0.0001	1
2402	π/4-DQPSK	-5.44	-5±1	-4	0.398	0	1.00	0.0001	1
2441		-5.00	-5±1	-4	0.398	0	1.00	0.0001	1
2480		-4.55	-4±1	-3	0.501	0	1.00	0.0001	1
2402	8DPSK	-5.36	-5±1	-4	0.398	0	1.00	0.0001	1
2441		-4.95	-4±1	-3	0.501	0	1.00	0.0001	1
2480		-4.41	-4±1	-3	0.501	0	1.00	0.0001	1

Conclusion:

Simultaneous:

For the max result: 0.0001≤ 1.0 test exclusion threshold, No SAR is required.

Statement

1. This report is invalid without the seal and signature of the laboratory.

2. The test results of this report are only responsible for the samples submitted.Client shall be responsible for representativeness of the sample and authenticity of the material.
3. The report shall not be partially reproduced without the written consent of the Laboratory.
4. This report is invalid if transferred, altered or tampered with in any form without authorization.
5. The observations or tests with special mark fall outside the scope of accreditation, and are only used for purpose of commission, research, training, internal quality control etc.
6. Any objection to this report shall be submitted to the laboratory within 15 days from the date of receipt of the report.

****** END OF REPORT ******