

Appendix B

WPT 13.56MHz

Device Under Test Properties

Model	Dimensions [mm]
RM12A	228.0 x 188.0 x 6.0

Exposure Conditions

Phantom Section, TSL	Position, Test Distance [mm]	Band	Group, UID	Frequency [MHz], Channel Number	Conversion Factor	TSL Conductivity [S/m]	TSL Permittivity
Flat, Head Simulating Liquid	BACK, 0.00	Custom Band	CW, 0--	13.600, 13600	18.19	0.781	54.8

Hardware Setup

Phantom	TSL	Probe, Calibration Date	DAE, Calibration Date
ELI V8.0 (20deg probe tilt) – 2227	HSL13MHz	EX3DV4 – SN7858, 2025–02–20	DAE4ip Sn1847, 2024–12–31

Scans Setup

	Area Scan	Zoom Scan
Grid Extents [mm]	240.0 x 270.0	32.0 x 32.0 x 30.0
Grid Steps [mm]	15.0 x 15.0	8.0 x 8.0 x 5.0
Sensor Surface [mm]	3.0	1.4
Graded Grid	N/A	Yes
Grading Ratio	N/A	1.5
MAIA	N/A	N/A
Surface Detection	VMS	VMS + 6p
Scan Method	Measured	Measured

Measurement Results

	Area Scan	Zoom Scan
Date	2025–12–29, 15:26	2025–12–29, 15:29
psSAR1g [W/Kg]	0.095	0.101
psSAR10g [W/Kg]	0.048	0.031
Power Drift [dB]	–0.15	–0.08
Power Scaling	Disabled	Disabled
Scaling Factor [dB]		
TSL Correction	No correction	No correction
M2/M1 [%]		47.8
Dist 3dB Peak [mm]		14.8

