

# TEST REPORT

of

FCC Part 15 Subpart C §15.247

FCC ID: 2AMKA-R750NRCBB

Equipment Under Test : InforTab  
Model Name : R750  
Variant Model Name : R420  
Applicant : RAINUS Co., Ltd.  
Manufacturer : RAINUS Co., Ltd.  
Date of Receipt : 2018.01.04  
Date of Test(s) : 2018.02.01 ~ 2018.07.11  
Date of Issue : 2018.07.30

In the configuration tested, the EUT complied with the standards specified above.

Tested By:



Nancy Park

Date:

2018.07.30

Technical  
Manager:



Jungmin Yang

Date:

2018.07.30

*The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.*

# INDEX

## Table of contents

|                                                                                  | Page |
|----------------------------------------------------------------------------------|------|
| 1. General Information -----                                                     | 3    |
| 2. Transmitter Radiated Spurious Emissions and Conducted Spurious Emission ----- | 8    |
| 3. 6 dB Bandwidth -----                                                          | 30   |
| 4. Maximum Peak Conducted Output Power -----                                     | 34   |
| 5. Power Spectral Density -----                                                  | 37   |
| 6. Antenna Requirement -----                                                     | 40   |

*The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.*

**SGS Korea Co., Ltd. (Gunpo Laboratory)** 4, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807 <http://www.sgsgroup.kr>

RTT5041-19(2017.07.10)(0)

Tel. +82 31 428 5700 / Fax. +82 31 427 2370

A4(210 mm x 297 mm)

## 1. General Information

### 1.1. Testing Laboratory

SGS Korea Co., Ltd. (Gunpo Laboratory)

-Wireless Div. 2FL, 10-2, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807

-Designation number: KR0150

All SGS services are rendered in accordance with the applicable SGS conditions of service available on request and accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx>.

Phone No. : +82 31 688 0901

Fax No. : +82 31 688 0921

### 1.2. Details of Applicant

Applicant : RAINUS Co., Ltd.

Address : 3rd-Floor, 173-36, Saneop-ro, Gwonseon-gu, Suwon-si, Gyeonggi-do, Korea

Contact Person : Do, Gi-tae

Phone No. : +82 31 548 0782

### 1.3. Details of manufacturer

Company : Same as applicant

Address : Same as applicant

### 1.4. Description of EUT

|                      |                       |
|----------------------|-----------------------|
| Kind of Product      | InforTab              |
| Model Name           | R750                  |
| Variant Model Names  | R420                  |
| Power Supply         | DC 3.0 V              |
| Frequency Range      | 2 405 MHz ~ 2 480 MHz |
| Modulation Technique | DSSS                  |
| Number of Channels   | 16 channels           |
| Antenna Type         | PCB Antenna           |
| Antenna Gain         | 0.88 dB i             |

*The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.*

**SGS Korea Co., Ltd. (Gunpo Laboratory)** 4, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807 <http://www.sgsgroup.kr>

RTT5041-19(2017.07.10)(0)

Tel. +82 31 428 5700 / Fax. +82 31 427 2370

A4(210 mm x 297 mm)

## 1.5. Test Equipment List

| Equipment                | Manufacturer                | Model                                | S/N                    | Cal. Date     | Cal. Interval | Cal. Due      |
|--------------------------|-----------------------------|--------------------------------------|------------------------|---------------|---------------|---------------|
| Signal Generator         | R&S                         | SMBV100A                             | 259067                 | Jun. 15, 2018 | Annual        | Jun. 15, 2019 |
| Signal Generator         | R&S                         | SMR40                                | 100272                 | Jun. 12, 2018 | Annual        | Jun. 12, 2019 |
| Spectrum Analyzer        | R&S                         | FSV30                                | 100955                 | Mar. 12, 2018 | Annual        | Mar. 12, 2019 |
| Spectrum Analyzer        | Agilent                     | N9020A                               | MY53421758             | Sep. 25, 2017 | Annual        | Sep. 25, 2018 |
| Attenuator               | MCLI                        | FAS-12-10                            | 1                      | Jun. 12, 2018 | Annual        | Jun. 12, 2019 |
| Attenuator               | MCLI                        | FAS-23-20                            | 23834                  | Jun. 12, 2018 | Annual        | Jun. 12, 2019 |
| High Pass Filter         | Wainwright Instrument GmbH  | WHK3.0/18G-10SS                      | 344                    | May 27, 2018  | Annual        | May 27, 2019  |
| High Pass Filter         | Wainwright Instrument GmbH  | WHNX7.5/26.5G-6SS                    | 15                     | Jun. 11, 2018 | Annual        | Jun. 11, 2019 |
| Low Pass Filter          | Mini-Circuits               | NLP-1200+                            | V 8979400903-1         | May 24, 2018  | Annual        | May 24, 2019  |
| Power Sensor             | R&S                         | NRP-Z81                              | 100669                 | Feb. 22, 2018 | Annual        | Feb. 22, 2019 |
| DC Power Supply          | Agilent                     | U8002A                               | MY50020026             | Dec. 07, 2017 | Annual        | Dec. 07, 2018 |
| Preamplifier             | H.P.                        | 8447F                                | 2944A03909             | Aug. 11, 2017 | Annual        | Aug. 11, 2018 |
| Signal Conditioning Unit | R&S                         | SCU-18                               | 102244                 | Sep. 22, 2017 | Annual        | Sep. 22, 2018 |
| Preamplifier             | MITEQ Inc.                  | JS44-18004000-35-8P                  | 1546891                | May 13, 2018  | Annual        | May 13, 2019  |
| Loop Antenna             | Schwarzbeck Mess-Elektronik | FMZB 1519                            | 1519-039               | Aug. 23, 2017 | Biennial      | Aug. 23, 2019 |
| Bilog Antenna            | Schwarzbeck Mess-Elektronik | VULB 9163                            | 01126                  | Mar. 26, 2018 | Biennial      | Mar. 26, 2020 |
| Horn Antenna             | R&S                         | HF906                                | 100326                 | Feb. 14, 2018 | Biennial      | Feb. 14, 2020 |
| Horn Antenna             | Schwarzbeck Mess-Elektronik | BBHA 9170                            | BBHA9170431            | Aug. 25, 2016 | Biennial      | Aug. 25, 2018 |
| Antenna Master           | INNCO systems GmbH          | MA4640-XP-ET                         | MA4640/536/383 30516/L | N.C.R.        | N/A           | N.C.R.        |
| Controller               | INNCO systems GmbH          | CONTROLLER CO3000-4P                 | CO3000/963/383 30516/L | N.C.R.        | N/A           | N.C.R.        |
| Turn Table               | INNCO systems GmbH          | DS 1200 S                            | N/A                    | N.C.R.        | N/A           | N.C.R.        |
| Test Receiver            | R&S                         | ESU26                                | 100109                 | Feb. 07, 2018 | Annual        | Feb. 07, 2019 |
| Anechoic Chamber         | SY Corporation              | L × W × H<br>(9.6 m × 6.4 m × 6.6 m) | N/A                    | N.C.R.        | N/A           | N.C.R.        |
| Coaxial Cable            | SUCOFLEX                    | 104 (3 m)                            | MY3258414              | Jul. 04, 2018 | Semi-annual   | Jan. 04, 2019 |
| Coaxial Cable            | SUCOFLEX                    | 104 (10 m)                           | MY3145814              | Jul. 04, 2018 | Semi-annual   | Jan. 04, 2019 |
| Coaxial Cable            | Rosenberger                 | LA1-C006-1500                        | 131014 01/20           | Mar. 05, 2018 | Semi-annual   | Sep. 05, 2018 |

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.

**SGS Korea Co., Ltd. (Gunpo Laboratory)** 4, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807 <http://www.sgsgroup.kr>

RTT5041-19(2017.07.10)(0)

Tel. +82 31 428 5700 / Fax. +82 31 427 2370

A4(210 mm × 297 mm)

## 1.6. Information of Variant models

| Model Name    |      | Information                                                                                         |
|---------------|------|-----------------------------------------------------------------------------------------------------|
| Basic Model   | R750 | - Basic Model                                                                                       |
| Variant Model | R420 | - Same to Basic model, but the only difference is other signal line patterns for the each PCB size. |

## 1.7. Summary of Test Results

The EUT has been tested according to the following specifications:

| APPLIED STANDARD: FCC Part15 Subpart C |                                                                        |          |
|----------------------------------------|------------------------------------------------------------------------|----------|
| Section                                | Test item(s)                                                           | Result   |
| 15.205(a)<br>15.209<br>15.247(d)       | Transmitter Radiated Spurious Emissions<br>Conducted Spurious Emission | Complied |
| 15.247(a)(2)                           | 6 dB Bandwidth                                                         | Complied |
| 15.247(b)(3)                           | Maximum Peak Conducted Output Power                                    | Complied |
| 15.247(e)                              | Power Spectral Density                                                 | Complied |

## 1.8. Test Procedure(s)

The measurement procedures described in the American National Standard for Testing Unlicensed Wireless Devices (ANSI C63.10-2013) and the guidance provided in KDB 558074 D01 DTS Meas Guidance v04 were used in the measurement of the DUT.

## 1.9. Sample calculation

Where relevant, the following sample calculation is provided:

### 1.9.1. Conducted test

Offset value (dB) = Attenuator (dB) + Cable loss (dB)

### 1.9.2. Radiation test

Field strength level (dB $\mu$ V/m) = Measured level (dB $\mu$ V) + Antenna factor (dB) + Cable loss (dB) - Amplifier gain (dB)

*The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.*

**SGS Korea Co., Ltd. (Gunpo Laboratory)** 4, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807 <http://www.sgsgroup.kr>

RTT5041-19(2017.07.10)(0)

Tel. +82 31 428 5700 / Fax. +82 31 427 2370

A4(210 mm x 297 mm)

### 1.10. Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

| Parameter                             | Uncertainty (dB) |
|---------------------------------------|------------------|
| Radiated Disturbance, 9 kHz to 30 MHz | $\pm 3.59$       |
| Radiated Disturbance, below 1 GHz     | $\pm 5.88$       |
| Radiated Disturbance, above 1 GHz     | $\pm 5.94$       |

Uncertainty figures are valid to a confidence level of 95 %.

### 1.11. Test report revision

| Revision | Report number        | Date of Issue | Description |
|----------|----------------------|---------------|-------------|
| 0        | F690501/RF-RTL012912 | 2018.07.30    | Initial     |

*The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.*

**SGS Korea Co., Ltd. (Gunpo Laboratory)** 4, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807 <http://www.sgsgroup.kr>

RTT5041-19(2017.07.10)(0)

Tel. +82 31 428 5700 / Fax. +82 31 427 2370

A4(210 mm x 297 mm)

## 1.12. Duty Cycle of EUT

Regarding to KDB 558074 D01 DTS Meas Guidance v04, 6.0, the maximum duty cycles of all modes were investigated and set the spectrum analyzer as below:


Set RBW ≥ OBW if possible; otherwise, set RBW to the largest available value. Set detector = peak or average. The zero-span measurement method shall not be used unless both RBW and VBW are > 50/T and the number of sweep points across duration T exceeds 100.

|                        |       |
|------------------------|-------|
| Duty cycle (%)         | 17.65 |
| Correction factor (dB) | 7.53  |

### Remark:

1. Duty cycle (%) = (Tx on time / Tx on + off time) x 100
2. Correction factor (dB) = 10 log (1 / Duty cycle)

### Test Plot




The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.

## 2. Transmitter Radiated Spurious Emissions and Conducted Spurious Emission


### 2.1. Test Setup

#### 2.1.1. Transmitter Radiated Spurious Emissions

The diagram below shows the test setup that is utilized to make the measurements for emission from 9 kHz to 30 MHz.




The diagram below shows the test setup that is utilized to make the measurements for emission from 30 MHz to 1 GHz.



*The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.*

The diagram below shows the test setup that is utilized to make the measurements for emission. The spurious emissions were investigated from 1 GHz to the 10<sup>th</sup> harmonic of the highest fundamental frequency or 40 GHz, whichever is lower.



*The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.*


**SGS Korea Co., Ltd. (Gunpo Laboratory)** 4, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807 <http://www.sgsgroup.kr>

RTT5041-19(2017.07.10)(0)

Tel. +82 31 428 5700 / Fax. +82 31 427 2370

A4(210 mm x 297 mm)

## 2.1.2. Conducted Spurious Emission



## 2.2. Limit

According to §15.247(d), in any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph(b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in section §15.209(a) is not required. In addition, radiated emission which fall in the restricted bands, as defined in section §15.205(a), must also comply with the radiated emission limits specified in section §15.209(a) (see §15.205(c)).

According to §15.209(a), except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

| Frequency<br>(MHz) | Field Strength<br>( $\mu V/m$ ) | Measurement Distance<br>(Meters) |
|--------------------|---------------------------------|----------------------------------|
| 0.009-0.490        | 2 400/F(kHz)                    | 300                              |
| 0.490-1.705        | 24 000/F(kHz)                   | 30                               |
| 1.705-30.0         | 30                              | 30                               |
| 30-88              | 100**                           | 3                                |
| 88-216             | 150**                           | 3                                |
| 216-960            | 200**                           | 3                                |
| Above 960          | 500                             | 3                                |

\*\* Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§15.231 and 15.241.

*The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.*

**SGS Korea Co., Ltd. (Gunpo Laboratory)** 4, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807 <http://www.sgsgroup.kr>

RTT5041-19(2017.07.10)(0)

Tel. +82 31 428 5700 / Fax. +82 31 427 2370

A4(210 mm x 297 mm)

## 2.3. Test Procedures

Radiated emissions from the EUT were measured according to the dictates in section 11.0 & 12.0 of KDB 558074 D01 DTS Meas Guidance v04 and ANSI C63.10-2013.

### 2.3.1. Test Procedures for emission below 30 MHz

1. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter anechoic chamber test site. The table was rotated 360 degrees to determine the position of the highest radiation.
2. Then antenna is a loop antenna is fixed at one meter above the ground to determine the maximum value of the field strength. Both parallel and perpendicular of the antenna are set to make the measurement.
3. For each suspected emission, the EUT was arranged to its worst case and then the table was turned from 0 degrees to 360 degrees to find the maximum reading.
4. The test-receiver system was set to average or quasi peak detect function and Specified Bandwidth with Maximum Hold Mode.

#### Note;

Although these tests were performed other than open field test site, adequate comparison measurements were confirmed against 30 meter open field test site. Therefore sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field based on KDB 414788 D01 Radiated Test Site v01.

### 2.3.2. Test Procedures for emission from above 30 MHz

1. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter anechoic chamber test site below 1 GHz and 1.5 meters above the ground at a 3 meter anechoic chamber test site above 1 GHz. The table was rotated 360 degrees to determine the position of the highest radiation.
2. During performing radiated emission below 1 GHz, the EUT was set 3 meters away from the interference receiving antenna, which was mounted on the top of a variable-height antenna tower. During performing radiated emission above 1 GHz, the EUT was set 3 meter away from the interference-receiving antenna.
3. The antenna is a bi-log antenna, a horn antenna and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the table was turned from 0 degrees to 360 degrees to find the maximum reading.
5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
6. If the emission level of the EUT in peak mode was 10 dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10 dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

*The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.*

# NOTE;

## 1. Unwanted Emissions into Non-Restricted Frequency Bands

- The Reference Level Measurement refer to section 11.2

Set analyzer center frequency to DTS channel center frequency, SPAN  $\geq 1.5$  times the DTS bandwidth, the RBW = 100 kHz and VBW  $\geq 3 \times$  RBW, Detector = Peak, Sweep time = Auto couple, Trace = Max hold.

- Unwanted Emissions Level Measurement refer to section 11.3

Set the center frequency and span to encompass frequency range to be measured, the RBW = 100 kHz and VBW  $\geq 3 \times$  RBW, Detector = Peak, Sweep time = Auto couple, Trace = Max hold.

## 2. Unwanted Emissions into Restricted Frequency Bands

- Peak Power measurement procedure refer to section 12.2.4

Set RBW = as specified in Table 1, VBW  $\geq 3 \times$  RBW, Detector = Peak, Sweep time = auto, Trace = Max hold.

**Table 1- RBW as a function of frequency**

| Frequency    | RBW         |
|--------------|-------------|
| 9-150 kHz    | 200-300 Hz  |
| 0.15-30 MHz  | 9-10 kHz    |
| 30-1 000 MHz | 100-120 kHz |
| > 1 000 MHz  | 1 MHz       |

- Average Power measurements procedure refer to section 12.2.5.2

The EUT shall be configured to operate at the maximum achievable duty cycle.

Measure the duty cycle, x, of the transmitter output signal as described in section 6.0.

Set RBW = 1 MHz, VBW  $\geq 3 \times$  RBW, Detector = RMS, if span / (# of points in sweep)  $\leq$  (RBW/2).

Satisfying this condition may require increasing the number of points in the sweep or reducing the span. If this condition cannot be satisfied then the detector mode shall be set to peak.

Averaging type = power (i.e., RMS).

As an alternative the detector and averaging type may be set for linear voltage averaging.

Some instruments require linear display mode in order to use linear voltage averaging. Log or dB averaging shall not be used. Sweep time = auto, Perform a trace average of at least 100 traces.

A correction factor shall be added to the measurement results prior to comparing to the emission limit in order to compute the emission level that would have been measured had the test been performed at 100 percent duty cycle. The correction factor is computed as follows:

- 1) If power averaging (RMS) mode was used in step f), then the applicable correction factor is  $10 \log(1/x)$ , where x is the duty cycle.

3. To get a maximum emission level from the EUT, the EUT is manipulated through three orthogonal planes (X, Y, Z). Worst orthogonal plan of EUT is **X - axis** during radiation test.

*The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.*

**SGS Korea Co., Ltd. (Gunpo Laboratory)** 4, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807 <http://www.sgsgroup.kr>

RTT5041-19(2017.07.10)(0)

Tel. +82 31 428 5700 / Fax. +82 31 427 2370

A4(210 mm x 297 mm)

### 2.3.3. Test Procedures for Conducted Spurious Emissions

Per the guidance of KDB 558074 D01 DTS Meas Guidance v04, section 11.1 & 11.2 & 11.3, the reference level for out of band emissions is established from the plots of this section since the band edge emissions are measured with a RBW of 100 kHz. This reference level is then used as the limit in subsequent plots for out of band spurious emissions shown in section 2.4.3. The limit for out of band spurious emission at the band edge is 20 dB below the fundamental emission level measured in a 100 kHz bandwidth.

#### 1. Conducted Emissions at Band Edge

- The Measurement refer to section 11.2

Set the center frequency and span to encompass frequency range to be measured, the RBW = 100 kHz and VBW  $\geq 3 \times$  RBW, Detector = Peak, Sweep time = Auto couple, Trace = Max hold, Ensure that the number of measurement points  $\geq$  span/RBW, The trace was allowed to stabilize.

#### 2. Conducted Spurious Emissions

- The Measurement refer to section 11.3

Start frequency was set to 9 kHz and stop frequency was set to 25 GHz (separated into two plots per channel), RBW = 1 MHz, VBW  $\geq 3 \times$  RBW, Detector = Peak, Sweep time = Auto couple, Trace = Max hold, The trace was allowed to stabilize.

#### 3. TDF function

- For plots showing conducted spurious emissions from 9 kHz to 25 GHz, all path loss of wide frequency range was investigated and compensated to spectrum analyzer as TDF function.  
So, the reading values shown in plots were final result.

*The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.*

## 2.4. Test Results

Ambient temperature : (23 ± 1) °C  
Relative humidity : 47 % R.H.

### 2.4.1. Radiated Spurious Emission below 1 000 MHz

The frequency spectrum from 9 kHz to 1 000 MHz was investigated. All reading values are peak values.

#### -R750

| Radiated Emissions |                |             | Ant  | Correction Factors |               | Total           | Limit          |             |
|--------------------|----------------|-------------|------|--------------------|---------------|-----------------|----------------|-------------|
| Frequency (MHz)    | Reading (dBμV) | Detect Mode | Pol. | AF (dB/m)          | AMP + CL (dB) | Actual (dBμV/m) | Limit (dBμV/m) | Margin (dB) |
| 44.87              | 39.50          | Peak        | V    | 14.28              | -26.91        | 26.87           | 40.00          | 13.13       |
| 125.42             | 44.00          | Peak        | H    | 9.47               | -25.91        | 27.56           | 43.50          | 15.94       |
| 213.90             | 38.70          | Peak        | V    | 11.13              | -25.12        | 24.71           | 43.50          | 18.79       |
| 364.65             | 41.80          | Peak        | V    | 14.73              | -24.53        | 32.00           | 46.00          | 14.00       |
| 627.32             | 37.80          | Peak        | H    | 19.43              | -24.69        | 32.54           | 46.00          | 13.46       |
| 908.25             | 39.10          | Peak        | H    | 22.47              | -23.27        | 38.30           | 46.00          | 7.70        |

#### -R420

| Radiated Emissions |                |             | Ant  | Correction Factors |               | Total           | Limit          |             |
|--------------------|----------------|-------------|------|--------------------|---------------|-----------------|----------------|-------------|
| Frequency (MHz)    | Reading (dBμV) | Detect Mode | Pol. | AF (dB/m)          | AMP + CL (dB) | Actual (dBμV/m) | Limit (dBμV/m) | Margin (dB) |
| 50.37              | 37.40          | Peak        | V    | 14.35              | -26.81        | 24.94           | 40.00          | 15.06       |
| 104.53             | 40.70          | Peak        | V    | 12.28              | -26.20        | 26.78           | 43.50          | 16.72       |
| 138.40             | 42.70          | Peak        | H    | 8.50               | -25.86        | 25.34           | 43.50          | 18.16       |
| 213.82             | 42.70          | Peak        | V    | 11.13              | -25.12        | 28.71           | 43.50          | 14.79       |
| 289.23             | 40.20          | Peak        | V    | 13.28              | -24.51        | 28.97           | 46.00          | 17.03       |
| 832.92             | 38.00          | Peak        | H    | 21.33              | -23.69        | 35.64           | 46.00          | 10.36       |
| Above 900.00       | Not detected   | -           | -    | -                  | -             | -               | -              | -           |

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.

SGS Korea Co., Ltd. (Gunpo Laboratory) 4, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807 <http://www.sgsgroup.kr>

RTT5041-19(2017.07.10)(0)

Tel. +82 31 428 5700 / Fax. +82 31 427 2370


A4(210 mm x 297 mm)

## Remark:


1. Spurious emissions for all channels were investigated and almost the same below 1 GHz.
2. Reported spurious emissions are in **Low channel** as worst case among other channels.
3. Radiated spurious emission measurement as below.  
(Actual = Reading + AF + AMP + CL)
4. According to §15.31(o), emission levels are not report much lower than the limits by over 20 dB.

## Test Plot

### -R750



### -R420



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.

## 2.4.2. Radiated Spurious Emission above 1 000 MHz

The frequency spectrum above 1 000 MHz was investigated. All reading values are peak and average values.

### -R750

Low Channel (2 405 MHz)

| Radiated Emissions |                      |             | Ant. | Correction Factors |         |           | Total                 | Limit                |             |
|--------------------|----------------------|-------------|------|--------------------|---------|-----------|-----------------------|----------------------|-------------|
| Frequency (MHz)    | Reading (dB $\mu$ V) | Detect Mode | Pol. | AF (dB/m)          | CL (dB) | Duty (dB) | Actual (dB $\mu$ V/m) | Limit (dB $\mu$ V/m) | Margin (dB) |
| *2 310.00          | 13.47                | Peak        | H    | 27.82              | 7.46    | -         | 48.75                 | 74.00                | 25.25       |
| *2 310.00          | 3.63                 | Average     | H    | 27.82              | 7.46    | 7.53      | 46.44                 | 54.00                | 7.56        |
| *2 377.28          | 16.25                | Peak        | H    | 27.95              | 7.60    | -         | 51.80                 | 74.00                | 22.20       |
| *2 367.05          | 4.13                 | Average     | H    | 27.93              | 7.56    | 7.53      | 47.15                 | 54.00                | 6.85        |
| *2 390.00          | 15.90                | Peak        | H    | 27.98              | 7.60    | -         | 51.48                 | 74.00                | 22.52       |
| *2 390.00          | 3.87                 | Average     | H    | 27.98              | 7.60    | 7.53      | 46.98                 | 54.00                | 7.02        |

| Radiated Emissions |                      |             | Ant. | Correction Factors |             |           | Total                 | Limit                |             |
|--------------------|----------------------|-------------|------|--------------------|-------------|-----------|-----------------------|----------------------|-------------|
| Frequency (MHz)    | Reading (dB $\mu$ V) | Detect Mode | Pol. | AF (dB/m)          | AMP+CL (dB) | Duty (dB) | Actual (dB $\mu$ V/m) | Limit (dB $\mu$ V/m) | Margin (dB) |
| Above 1 000.00     | Not detected         | -           | -    | -                  | -           | -         | -                     | -                    | -           |

Middle Channel (2 440 MHz)

| Radiated Emissions |                      |             | Ant. | Correction Factors |             |           | Total                 | Limit                |             |
|--------------------|----------------------|-------------|------|--------------------|-------------|-----------|-----------------------|----------------------|-------------|
| Frequency (MHz)    | Reading (dB $\mu$ V) | Detect Mode | Pol. | AF (dB/m)          | AMP+CL (dB) | Duty (dB) | Actual (dB $\mu$ V/m) | Limit (dB $\mu$ V/m) | Margin (dB) |
| Above 1 000.00     | Not detected         | -           | -    | -                  | -           | -         | -                     | -                    | -           |

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.

SGS Korea Co., Ltd. (Gunpo Laboratory) 4, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807 <http://www.sgsgroup.kr>

RTT5041-19(2017.07.10)(0)

Tel. +82 31 428 5700 / Fax. +82 31 427 2370

A4(210 mm x 297 mm)

High Channel (2 480 MHz)

| Radiated Emissions |                      |             | Ant. | Correction Factors |         |           | Total                 | Limit                |             |
|--------------------|----------------------|-------------|------|--------------------|---------|-----------|-----------------------|----------------------|-------------|
| Frequency (MHz)    | Reading (dB $\mu$ V) | Detect Mode | Pol. | AF (dB/m)          | CL (dB) | Duty (dB) | Actual (dB $\mu$ V/m) | Limit (dB $\mu$ V/m) | Margin (dB) |
| *2 483.50          | 14.45                | Peak        | H    | 28.00              | 7.72    | -         | 50.17                 | 74.00                | 23.83       |
| *2 483.50          | 4.53                 | Average     | H    | 28.00              | 7.72    | 7.53      | 47.78                 | 54.00                | 6.22        |
| *2 498.10          | 16.55                | Peak        | H    | 28.00              | 7.69    | -         | 52.24                 | 74.00                | 21.76       |
| *2 484.51          | 4.62                 | Average     | H    | 28.00              | 7.72    | 7.53      | 47.87                 | 54.00                | 6.13        |
| *2 500.00          | 13.77                | Peak        | H    | 28.00              | 7.69    | -         | 49.46                 | 74.00                | 24.54       |
| *2 500.00          | 4.29                 | Average     | H    | 28.00              | 7.69    | 7.53      | 47.51                 | 54.00                | 6.49        |

| Radiated Emissions |                      |             | Ant. | Correction Factors |             |           | Total                 | Limit                |             |
|--------------------|----------------------|-------------|------|--------------------|-------------|-----------|-----------------------|----------------------|-------------|
| Frequency (MHz)    | Reading (dB $\mu$ V) | Detect Mode | Pol. | AF (dB/m)          | AMP+CL (dB) | Duty (dB) | Actual (dB $\mu$ V/m) | Limit (dB $\mu$ V/m) | Margin (dB) |
| Above 1 000.00     | Not detected         | -           | -    | -                  | -           | -         | -                     | -                    | -           |

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.

**SGS Korea Co., Ltd. (Gunpo Laboratory)** 4, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807 <http://www.sgsgroup.kr>

RTT5041-19(2017.07.10)(0)

Tel. +82 31 428 5700 / Fax. +82 31 427 2370

A4(210 mm x 297 mm)

**-R420**

Low Channel (2 405 MHz)

| Radiated Emissions |                      |             | Ant. | Correction Factors |         |           | Total                 | Limit                |             |
|--------------------|----------------------|-------------|------|--------------------|---------|-----------|-----------------------|----------------------|-------------|
| Frequency (MHz)    | Reading (dB $\mu$ V) | Detect Mode | Pol. | AF (dB/m)          | CL (dB) | Duty (dB) | Actual (dB $\mu$ V/m) | Limit (dB $\mu$ V/m) | Margin (dB) |
| *2 310.00          | 12.98                | Peak        | H    | 27.82              | 7.46    | -         | 48.26                 | 74.00                | 25.74       |
| *2 310.00          | 3.00                 | Average     | H    | 27.82              | 7.46    | 7.53      | 45.81                 | 54.00                | 8.19        |
| *2 383.54          | 16.16                | Peak        | H    | 27.97              | 7.60    | -         | 51.73                 | 74.00                | 22.27       |
| *2 379.13          | 4.49                 | Average     | H    | 27.96              | 7.60    | 7.53      | 47.58                 | 54.00                | 6.42        |
| *2 390.00          | 13.41                | Peak        | H    | 27.98              | 7.60    | -         | 48.99                 | 74.00                | 25.01       |
| *2 390.00          | 3.65                 | Average     | H    | 27.98              | 7.60    | 7.53      | 46.76                 | 54.00                | 7.24        |

| Radiated Emissions |                      |             | Ant. | Correction Factors |             |           | Total                 | Limit                |             |
|--------------------|----------------------|-------------|------|--------------------|-------------|-----------|-----------------------|----------------------|-------------|
| Frequency (MHz)    | Reading (dB $\mu$ V) | Detect Mode | Pol. | AF (dB/m)          | AMP+CL (dB) | Duty (dB) | Actual (dB $\mu$ V/m) | Limit (dB $\mu$ V/m) | Margin (dB) |
| Above 1 000.00     | Not detected         | -           | -    | -                  | -           | -         | -                     | -                    | -           |

Middle Channel (2 440 MHz)

| Radiated Emissions |                      |             | Ant. | Correction Factors |             |           | Total                 | Limit                |             |
|--------------------|----------------------|-------------|------|--------------------|-------------|-----------|-----------------------|----------------------|-------------|
| Frequency (MHz)    | Reading (dB $\mu$ V) | Detect Mode | Pol. | AF (dB/m)          | AMP+CL (dB) | Duty (dB) | Actual (dB $\mu$ V/m) | Limit (dB $\mu$ V/m) | Margin (dB) |
| Above 1 000.00     | Not detected         | -           | -    | -                  | -           | -         | -                     | -                    | -           |

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.

**SGS Korea Co., Ltd. (Gunpo Laboratory)** 4, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807 <http://www.sgsgroup.kr>

RTT5041-19(2017.07.10)(0)

Tel. +82 31 428 5700 / Fax. +82 31 427 2370

A4(210 mm x 297 mm)

High Channel (2 480 MHz)

| Radiated Emissions |                      |             | Ant. | Correction Factors |         |           | Total                 | Limit                |             |
|--------------------|----------------------|-------------|------|--------------------|---------|-----------|-----------------------|----------------------|-------------|
| Frequency (MHz)    | Reading (dB $\mu$ V) | Detect Mode | Pol. | AF (dB/m)          | CL (dB) | Duty (dB) | Actual (dB $\mu$ V/m) | Limit (dB $\mu$ V/m) | Margin (dB) |
| *2 483.50          | 14.02                | Peak        | H    | 28.00              | 7.72    | -         | 49.74                 | 74.00                | 24.26       |
| *2 483.50          | 4.14                 | Average     | H    | 28.00              | 7.72    | 7.53      | 47.39                 | 54.00                | 6.61        |
| *2 498.34          | 16.09                | Peak        | H    | 28.00              | 7.69    | -         | 51.78                 | 74.00                | 22.22       |
| *2 483.73          | 4.58                 | Average     | H    | 28.00              | 7.72    | 7.53      | 47.83                 | 54.00                | 6.17        |
| *2 500.00          | 15.23                | Peak        | H    | 28.00              | 7.69    | -         | 50.92                 | 74.00                | 23.08       |
| *2 500.00          | 4.41                 | Average     | H    | 28.00              | 7.69    | 7.53      | 47.63                 | 54.00                | 6.37        |

| Radiated Emissions |                      |             | Ant. | Correction Factors |             |           | Total                 | Limit                |             |
|--------------------|----------------------|-------------|------|--------------------|-------------|-----------|-----------------------|----------------------|-------------|
| Frequency (MHz)    | Reading (dB $\mu$ V) | Detect Mode | Pol. | AF (dB/m)          | AMP+CL (dB) | Duty (dB) | Actual (dB $\mu$ V/m) | Limit (dB $\mu$ V/m) | Margin (dB) |
| Above 1 000.00     | Not detected         | -           | -    | -                  | -           | -         | -                     | -                    | -           |

**Remark:**

1. "\*" means the restricted band.
2. Measuring frequencies from 1 GHz to the 10<sup>th</sup> harmonic of highest fundamental frequency.
3. Radiated emissions measured in frequency above 1 000 MHz were made with an instrument using peak/average detector mode.
4. Actual = Reading + AF + CL + (Duty) or Reading + AF + AMP + CL + (Duty).
5. According to § 15.31(o), emission levels are not reported much lower than the limits by over 20 dB.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.

SGS Korea Co., Ltd. (Gunpo Laboratory) 4, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807 <http://www.sgsgroup.kr>

RTT5041-19(2017.07.10)(0)


Tel. +82 31 428 5700 / Fax. +82 31 427 2370

A4(210 mm x 297 mm)


## 2.4.3. Plot of Transmitter Radiated Spurious Emissions

-R750

Low channel Band edge (Peak)




Low channel Band edge (Average)




The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.

## High channel Band edge (Peak)




## High channel Band edge (Average)




The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.

## -R420

### Low channel Band edge (Peak)



### Low channel Band edge (Average)



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.


SGS Korea Co., Ltd. (Gunpo Laboratory) 4, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807 <http://www.sgsgroup.kr>

RTT5041-19(2017.07.10)(0)


Tel. +82 31 428 5700 / Fax. +82 31 427 2370

A4(210 mm x 297 mm)

## High channel Band edge (Peak)




## High channel Band edge (Average)




The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.

## 2.4.4. Spurious RF Conducted Emissions: Plot of Spurious RF Conducted Emission

Low Channel



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.


SGS Korea Co., Ltd. (Gunpo Laboratory) 4, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807 <http://www.sgsgroup.kr>

RTT5041-19(2017.07.10)(0)


Tel. +82 31 428 5700 / Fax. +82 31 427 2370

A4(210 mm x 297 mm)

## Middle Channel



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.


SGS Korea Co., Ltd. (Gunpo Laboratory) 4, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807 <http://www.sgsgroup.kr>

RTT5041-19(2017.07.10)(0)


Tel. +82 31 428 5700 / Fax. +82 31 427 2370

A4(210 mm x 297 mm)

## High Channel



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.

SGS Korea Co., Ltd. (Gunpo Laboratory) 4, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807 <http://www.sgsgroup.kr>


RTT5041-19(2017.07.10)(0)

Tel. +82 31 428 5700 / Fax. +82 31 427 2370

A4(210 mm x 297 mm)

## 3. 6 dB Bandwidth

### 3.1. Test Setup



### 3.2. Limit

According to §15.247(a)(2), systems using digital modulation techniques may operate in the 902-928 MHz, 2 400-2 483.5 MHz, and 5 725-5 850 MHz bands. The minimum 6 dB Bandwidth shall be at least 500 kHz.

### 3.3. Test Procedure

The test follows section 8.0 DTS bandwidth of KDB 558074 D01 DTS Meas Guidance v04.

Tests performed using section 8.1 Option 1.

- Option 1:

1. Set RBW to = 100 kHz.
2. Set the video bandwidth(VBW)  $\geq 3 \times$  RBW.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude point (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

*The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.*

**SGS Korea Co., Ltd. (Gunpo Laboratory)** 4, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807 <http://www.sgsgroup.kr>

RTT5041-19(2017.07.10)(0)

Tel. +82 31 428 5700 / Fax. +82 31 427 2370

A4(210 mm x 297 mm)

### 3.4. Test Results

Ambient temperature : (23 ± 1) °C  
Relative humidity : 47 % R.H.

| Mode | Channel | Frequency<br>(MHz) | 6 dB Bandwidth<br>(MHz) |
|------|---------|--------------------|-------------------------|
| DSSS | Low     | 2 405              | 1.563                   |
|      | Middle  | 2 440              | 1.577                   |
|      | High    | 2 480              | 1.563                   |

*The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.*

**SGS Korea Co., Ltd. (Gunpo Laboratory)** 4, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807 <http://www.sgsgroup.kr>


RTT5041-19(2017.07.10)(0)

Tel. +82 31 428 5700 / Fax. +82 31 427 2370


A4(210 mm x 297 mm)

## 6 dB Bandwidth

### Low Channel




### Middle Channel



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.

## High Channel



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.

SGS Korea Co., Ltd. (Gunpo Laboratory) 4, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807 <http://www.sgsgroup.kr>


RTT5041-19(2017.07.10)(0)

Tel. +82 31 428 5700 / Fax. +82 31 427 2370

A4(210 mm x 297 mm)

## 4. Maximum Peak Conducted Output Power

### 4.1. Test Setup



### 4.2. Limit

According to §15.247(b)(3), for systems using digital modulation in the 902-928 MHz, 2 400-2 483.5 MHz, and 5 725-5 850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

According to §15.247(b)(4), the conducted output power limit specified in paragraph (b) of this section is based on the use of antenna with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraph (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

*The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.*

**SGS Korea Co., Ltd. (Gunpo Laboratory)** 4, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807 <http://www.sgsgroup.kr>

RTT5041-19(2017.07.10)(0)

Tel. +82 31 428 5700 / Fax. +82 31 427 2370

A4(210 mm x 297 mm)

---

### 4.3. Test Procedure

The test follows section 9.1.3 of KDB 558074 D01 DTS Meas Guidance v04.

#### **PKPM1 Peak-reading power meter method**

- The maximum peak conducted output power may be measured using a broadband peak RF power meter. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall utilize a fast-responding diode detector.

The test follows section 9.2.3.2 of KDB 558074 D01 DTS Meas Guidance v04.

#### **Method AVGPM-G (Measurement using a gated RF average-reading power meter)**

- Alternatively, measurements may be performed using a wideband gated RF power meter provided that the gate parameters are adjusted such that the power is measured only when the EUT is transmitting at its maximum power control level. Since this measurement is made only during the ON time of the transmitter, no duty cycle correction is required.

#### **Test program: (S/W name: R&S Power Viewer, Version: 3.2.0)**

1. Initially overall offset for attenuator and cable loss is measured per frequency.
2. Measured offset is inserted in test program in advance of measurement for output power.
3. Power for each frequency (channel) of device is investigated as final result.
4. Final result reported on this section from R&S power viewer program includes with several factors and test program shows only final result.

---

*The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.*

**SGS Korea Co., Ltd. (Gunpo Laboratory)** 4, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807 <http://www.sgsgroup.kr>

RTT5041-19(2017.07.10)(0)

Tel. +82 31 428 5700 / Fax. +82 31 427 2370

A4(210 mm x 297 mm)

#### 4.4. Test Results

Ambient temperature : (23 ± 1) °C

Relative humidity : 47 % R.H.

| Mode | Channel | Frequency (MHz) | Average Power Result (dB m) | Peak Power Result (dB m) | Limit (dB m) |
|------|---------|-----------------|-----------------------------|--------------------------|--------------|
| DSSS | Low     | 2 405           | <u>-11.95</u>               | <u>-9.84</u>             | 30           |
|      | Middle  | 2 440           | -12.44                      | -10.31                   |              |
|      | High    | 2 480           | -12.84                      | -10.56                   |              |

#### Remark:

Attenuator and cable offset was compensated in test program (R&S Power Viewer) before measuring.

*The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.*

**SGS Korea Co., Ltd. (Gunpo Laboratory)** 4, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807 <http://www.sgsgroup.kr>


RTT5041-19(2017.07.10)(0)

Tel. +82 31 428 5700 / Fax. +82 31 427 2370

A4(210 mm x 297 mm)

## 5. Power Spectral Density

### 5.1. Test Setup



### 5.2. Limit

According to §15.247(e), for digitally modulated system, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

### 5.3. Test Procedure

The measurements are recorded using the PKPSD measurement procedure in section 10.2 of KDB 558074 D01 DTS Meas Guidance v04.

- This procedure shall be used if maximum peak conducted output power was used to demonstrate compliance, and is optional if the maximum conducted (average) output power was used to demonstrate compliance.

1. Set analyzer center frequency to DTS channel center frequency.
2. Set the span to at least 1.5 times the DTS bandwidth.
3. Set the RBW to:  $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$ .
4. Set the VBW  $\geq 3 \times \text{RBW}$ .
5. Detector = Peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level within the RBW.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.


*The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.*

## 5.4. Test Results

Ambient temperature : (23 ± 1) °C  
Relative humidity : 47 % R.H.

| Mode | Channel | Frequency (MHz) | Measured PSD (dB m) | Maximum Limit (dB m) |
|------|---------|-----------------|---------------------|----------------------|
| DSSS | Low     | 2 405           | -26.85              | 8                    |
|      | Middle  | 2 440           | -27.14              |                      |
|      | High    | 2 480           | -27.60              |                      |

### Low Channel



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.


SGS Korea Co., Ltd. (Gunpo Laboratory) 4, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807 <http://www.sgsgroup.kr>

RTT5041-19(2017.07.10)(0)


Tel. +82 31 428 5700 / Fax. +82 31 427 2370

A4(210 mm x 297 mm)

## Middle Channel



## High Channel



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.

---

## 6. Antenna Requirement

### 6.1. Standard Applicable

For intentional device, according to FCC 47 CFR Section §15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section §15.247 (b) if transmitting antennas of directional gain greater than 6 dB i are used, the power shall be reduced by the amount in dB that the gain of the antenna exceeds 6 dB i.

### 6.2. Antenna Connected Construction

Antenna used in this product is PCB Antenna with gain of 0.88 dB i.

**- End of the Test Report -**

---

*The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company. This test report does not assure KOLAS accreditation.*

**SGS Korea Co., Ltd. (Gunpo Laboratory)** 4, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807 <http://www.sgsgroup.kr>

RTT5041-19(2017.07.10)(0)

Tel. +82 31 428 5700 / Fax. +82 31 427 2370

A4(210 mm x 297 mm)