

TEST REPORT

Applicant: Shenzhen Jimi IoT Co., Ltd.
Address: 3-4/F, Block A, Building #7, Shenzhen International Innovation Valley, Dashi 1st Road, Nanshan District, Shenzhen, Guangdong, China
Equipment Type: Portable GNSS Tracker
Model Name: P6401 NA (refer to section 2.3)
Brand Name: Jimi IoT
FCC ID: 2AMLF-P6401NA
Test Standard: 47 CFR Part 15 Subpart B
ANSI C63.4-2014
Sample Arrival Date: Apr. 27, 2025
Test Date: Apr. 29, 2025 - May. 06, 2025
Date of Issue: May 19, 2025

ISSUED BY:

Shenzhen BALUN Technology Co., Ltd.

**Tested by:** Zhang Guoxi**Checked by:** Liu Zhen Xiang**Approved by:** Tolan Tu
(Technical Director)

Revision History

Version	Issue Date	Revisions
<u>Rev. 01</u>	<u>May 19, 2025</u>	<u>Initial Issue</u>

TABLE OF CONTENTS

1	GENERAL INFORMATION	3
1.1	Test Laboratory	3
1.2	Test Location	3
2	PRODUCT INFORMATION	4
2.1	Applicant Information	4
2.2	Manufacturer Information	4
2.3	General Description for Equipment under Test (EUT)	4
2.4	Ancillary Equipment	5
2.5	Technical Information	5
3	SUMMARY OF TEST RESULTS	6
3.1	Test Standards	6
3.2	Verdict	6
3.3	Test Uncertainty	6
4	GENERAL TEST CONFIGURATIONS	7
4.1	Test Enclosure List	7
4.2	Test Configurations	7
4.3	Test Setups	8
5	TEST ITEMS	10
5.1	Emission Tests	10
ANNEX A	TEST RESULTS	15
A.1	Radiated Emission	15
A.2	Conducted Emission, AC Ports	22
ANNEX B	TEST SETUP PHOTOS	25
ANNEX C	EUT EXTERNAL PHOTOS	25
ANNEX D	EUT INTERNAL PHOTOS	25

1 GENERAL INFORMATION

1.1 Test Laboratory

Name	Shenzhen BALUN Technology Co., Ltd.
Address	Block B, 1/F, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China
Phone Number	+86 755 6685 0100

1.2 Test Location

Name	Shenzhen BALUN Technology Co., Ltd.
Location	☒ Block B, 1/F, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China
	☐ 1/F, Building B, Ganghongji High-tech Intelligent Industrial Park, No. 1008, Songbai Road, Yangguang Community, Xili Sub-district, Nanshan District, Shenzhen, Guangdong Province, P. R. China
Accreditation Certificate	The laboratory is a testing organization accredited by FCC as a accredited testing laboratory. The designation number is CN1196. The certification body is American Association for Laboratory Accreditation (A2LA).

2 PRODUCT INFORMATION

2.1 Applicant Information

Applicant	Shenzhen Jimi IoT Co., Ltd.
Address	3-4/F, Block A, Building #7, Shenzhen International Innovation Valley, Dashi 1st Road, Nanshan District, Shenzhen, Guangdong, China

2.2 Manufacturer Information

Manufacturer	Shenzhen Jimi IoT Co., Ltd.
Address	3-4/F, Block A, Building #7, Shenzhen International Innovation Valley, Dashi 1st Road, Nanshan District, Shenzhen, Guangdong, China

2.3 General Description for Equipment under Test (EUT)

EUT Name	Portable GNSS Tracker
Model Name Under Test	P6401 NA
Series Model Name	PL601NA, PL601N, A410, P6401, PL601
Description of Model name differentiation	All models are same with electrical parameters and internal circuit structure, but only differ in model name. (this information provided by the applicant)
Hardware Version	P6401-MB-V1.1
Software Version	P6401_P6401_WFBI_NA_V1.0.0_250331.1015
Dimensions (Approx.)	N/A
Weight (Approx.)	N/A

2.4 Ancillary Equipment

Ancillary Equipment 1	Battery	
	Brand Name	N/A
	Model No.	SP0601
	Serial No.	N/A
	Capacity	650mAh
	Rated Voltage	3.8V
	Limit Charge Voltage	4.35V
Ancillary Equipment 2	Adapter	
	Brand Name	N/A
	Model No.	HBA10
	Serial No.	N/A
	Rated Input	100-240V, 0.3A
	Rated Output	5.0V $\Rightarrow$ 1.0A
Ancillary Equipment 3	USB Cable	
	Length (Approx.)	0.3m
Note 1: Letter in () means plug type.		

2.5 Technical Information

Network and Wireless connectivity	4G Network LTE FDD Band 2/4/5/7/12/14/17/25/26/66 LTE TDD Band 41 Bluetooth BLE GPS, BDS
Classification of equipment	Class B
The highest internal frequency of EUT	2689.9MHz

3 SUMMARY OF TEST RESULTS

3.1 Test Standards

No.	Identity	Document Title
1	47 CFR Part 15 Subpart B	Unintentional Radiators
2	ANSI C63.4-2014	American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz

3.2 Verdict

No.	Description	FCC Rule	Test Verdict	Remark
1	Radiated Emission	15.109	Pass	--
2	Conducted Emission, AC Ports	15.107	Pass	--

3.3 Test Uncertainty

The following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

Measurement	Value
Conducted emissions (9 kHz-30 MHz)	3.2 dB
Radiated emissions (30 MHz-1 GHz)-966#2	4.4 dB
Radiated emissions (1 GHz-18 GHz)-966#2	5.0 dB

4 GENERAL TEST CONFIGURATIONS

4.1 Test Enclosure List

Note: Not applicable.


4.2 Test Configurations

All test modes of EUT are listed in the table below.


Test Mode Configuration	Description
Mode 1	<u>The Only Charging Test Mode</u> EUT + Adapter + USB Cable + Battery

4.3 Test Setups


Test Setup 1



Radiated Emission (30 MHz-1 GHz)



Radiated Emission (above 1 GHz)

Test Setup 2

Conducted Emissions, AC Ports

5 TEST ITEMS

5.1 Emission Tests

5.1.1 Radiated Emission

5.1.1.1 Limit

Frequency range (MHz)	Class B (at 3 m)		Class A (at 3 m)
	Field Strength ($\mu\text{V/m}$)	Field Strength (dB $\mu\text{V/m}$)	Field Strength (dB $\mu\text{V/m}$)
30 - 88	100	40	49.5
88 - 216	150	43.5	54
216 - 960	200	46	56.9
Above 960	500	54	60

NOTE:

- 1) Field Strength (dB $\mu\text{V/m}$) = $20 \cdot \log [\text{Field Strength } (\mu\text{V/m})]$.
- 2) In the emission tables above, the tighter limit applies at the band edges.
- 3) For 30 MHz to 1000 MHz, the CISPR quasi-peak is employed.

For above 1000 MHz, according to the requirements of FCC 15.35, unless otherwise specified, the limit on peak radio frequency emissions is 20 dB above the maximum permitted average emission limit applicable to the equipment under test.

Frequency range (GHz)	Class B (at 3 m)			Class A (at 3 m)	
	Field Strength ($\mu\text{V/m}$)	Field Strength Average (dB $\mu\text{V/m}$)	Field Strength Peak (dB $\mu\text{V/m}$)	Field Strength Average (dB $\mu\text{V/m}$)	Field Strength Peak (dB $\mu\text{V/m}$)
1 - F_M	500	54	74	60	80

Note 1: The highest measurement frequency, F_M , in GHz, shall be determined as next Table.

Note 2: Average Class A limit at 3m L_{3m} is determined by the following conversion formula:

$$L_{3m} = L_{10m} + 20 \cdot \log(d_{10m}/d_{3m})$$

Where:

L_{3m} is Average Class A limit at 3m;

L_{10m} is Average Class A limit at 10m;

d_{10m} is Measurement distance in 10m;

d_{3m} is Measurement distance in 3m.

For this case: $L_{3m} = 49.5 + 20 \cdot \log(10/3) = 60$ (dB $\mu\text{V/m}$).

Highest internal frequency (F_X)	Highest measurement frequency (F_M)
$F_X \leq 108 \text{ MHz}$	1 GHz
$108 \text{ MHz} \leq F_X \leq 500 \text{ MHz}$	2 GHz
$500 \text{ MHz} \leq F_X \leq 1 \text{ GHz}$	5 GHz
$F_X \geq 1 \text{ GHz}$	$5 * F_X$ or 40 GHz, whichever is lower.
Note: F_X is Highest frequency generated or used in the device or on which the device operates or tunes.	

5.1.1.2 Test Setup

Refer to 4.3 section (test setup 1) for radiated emission test, the photo of test setup please refer to ANNEX B.

5.1.1.3 Test Procedure

All Radiated Emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

An initial pre-scan was performed in the chamber using the EMI Receiver in peak detection mode. Quasi-peak measurements were conducted based on the peak sweep graph. The EUT was measured by Bi-Log antenna with 2 orthogonal polarities.

The measurement frequency range is from 30 MHz to the 5th harmonic of the maximum frequency of the EUT internal source. The Turn Table is actuated to turn from 0° to 360° , and both horizontal and vertical polarizations of the Test Antenna are used to find the maximum radiated power. Mid channels on all channel bandwidth verified. Only the worst RB size/offset presented.

Use the following spectrum analyzer settings:

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz for $f \geq 1 \text{ GHz}$, 100 kHz for $f < 1 \text{ GHz}$

VBW $\geq$ RBW

Sweep = auto

Detector function = peak for $f < 1 \text{ GHz}$, peak & RMS Average for $f \geq 1 \text{ GHz}$

Trace = max hold

5.1.1.4 Test Result and Test Equipment List

Please refer to ANNEX A.1.

NOTE:

1. $\text{Results (dB}\mu\text{V/m)} = \text{Reading (dB}\mu\text{V)} + \text{Factor (dB/m)}$

The reading level is calculated by software which is not shown in the sheet

2. $\text{Factor (dB/m)} = \text{Antenna Factor (dB/m)} + \text{Cable Factor (dB)} - \text{Amplifier Gain (dB)}$

3. $\text{Margin} = \text{Limit} - \text{Results}$

5.1.2 Conducted Emission, AC Ports

5.1.2.1 Test Limit

Frequency range (MHz)	Class A	
	Quasi-peak (dB μ V)	Average (dB μ V)
0.15 - 0.50	79	66
0.50 - 30	73	60

Frequency range (MHz)	Class B	
	Quasi-peak (dB μ V)	Average (dB μ V)
0.15 - 0.50	66 to 56	56 to 46
0.50 - 5	56	46
5 - 30	60	50

NOTE:

- 1) The lower limit shall apply at the band edges.
- 2) The limit decreases linearly with the logarithm of the frequency in the range 0.15 - 0.50 MHz.

5.1.2.2 Test Setup

Refer to 4.3 section test (test setup 2) for conducted emission, the photo of test setup please refer to ANNEX B.

5.1.2.3 Test Procedure

The EUT is connected to the power mains through a LISN which provides 50 Ω /50 μ H of coupling impedance for the measuring instrument. The test frequency range is from 150 kHz to 30 MHz. The maximum conducted interference is searched using Peak (PK), Quasi-peak (QP) and Average (AV) detectors; the emission levels that are more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors. Tests for both L phase and N phase lines of the power mains connected to the EUT are performed.

Devices subject to Part 15 must be tested for all available U.S. voltages and frequencies (such as a nominal 120 VAC, 50/60 Hz and 240 VAC, 50/60 Hz) for which the device is capable of operation. A device rated for 50/60 Hz operation need not be tested at both frequencies provided the radiated and line conducted emissions are the same at both frequencies.

Use the following spectrum analyzer settings:

RBW = 9 kHz

VBW $\geq$ RBW

Sweep = 10ms

Detector function =peak & Average

Trace = max hold

5.1.2.4 Test Result and Test Equipment List

Please refer to ANNEX A.2.

NOTE:

1. Results (dB μ V) = Reading (dB μ V) + Factor (dB)

The reading level is calculated by software which is not shown in the sheet

2. Factor = Insertion loss + Cable loss

3. Margin = Limit - Results

ANNEX A TEST RESULTS

A.1 Radiated Emission


Note 1: The symbol of “--” in the table which means not application.

Note 2: For the test data above 1 GHz, according the ANSI C63.4-2014, where limits are specified for both average and peak (or quasi-peak) detector functions, if the peak (or quasi-peak) measured value complies with the average limit, it is unnecessary to perform an average measurement.

Sample No.	S02	Temperature	20.5℃
Humidity	43%RH	Pressure	101kPa
Test Engineer	Chen Jingran	Test Date	2025.04.29


Test Mode 1

1) Test Antenna Vertical, 30 MHz – 1 GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	49.545	25.32	-25.64	40.0	14.68	Peak	325.00	100	Vertical	Pass
2	51.583	24.81	-24.30	40.0	15.19	Peak	101.00	100	Vertical	Pass
3	116.282	15.59	-27.58	43.5	27.91	Peak	226.00	100	Vertical	Pass
4	144.508	12.47	-30.55	43.5	31.03	Peak	309.00	100	Vertical	Pass
5	221.818	18.17	-26.01	46.0	27.83	Peak	298.00	100	Vertical	Pass
6	988.409	30.54	-8.54	54.0	23.46	Peak	0.00	200	Vertical	Pass


2) Test Antenna Horizontal, 30 MHz – 1 GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	43.047	13.22	-25.41	40.0	26.78	Peak	265.00	100	Horizontal	Pass
2	51.291	13.61	-24.00	40.0	26.39	Peak	360.00	200	Horizontal	Pass
3	97.755	11.91	-26.93	43.5	31.59	Peak	151.00	100	Horizontal	Pass
4	133.305	11.88	-30.03	43.5	31.62	Peak	239.00	200	Horizontal	Pass
5	221.915	18.78	-26.00	46.0	27.22	Peak	150.00	200	Horizontal	Pass
6	908.093	30.14	-9.77	46.0	15.86	Peak	63.00	100	Horizontal	Pass

Equipment Information						
Equipment Name	Supplier	Model	Serial No.	Cal. Date	Cal. Due	Use
Frequency Below 1 GHz						
EMI Receiver	Keysight	N9038A	MY55330120	2024.08.01	2025.07.31	☒
Amplifier (30-1GHz)	COM-MV	ZT30-1000M	B2017119081	2024.11.28	2025.11.27	☒
Test Antenna- Bi-Log	SCHWARZB ECK	VULB 9168	00883	2025.03.23	2028.03.22	☒
Anechoic Chamber (#2)	YiHeng	9m*6m*6m	142	2024.07.21	2027.07.20	☒
Description	Supplier	Name	Version	/		Use
Test Software	BALUN	BL410-E	V22.930	/		☒

3) Test Antenna Vertical, 1 GHz – 14 GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1251.030	39.54	-15.75	74.0	34.46	Peak	230.00	100	Vertical	Pass
1**	1251.030	29.81	-15.75	54.0	24.19	AV	230.00	100	Vertical	Pass
2	2378.910	44.60	-10.95	74.0	29.40	Peak	126.00	100	Vertical	Pass
2**	2378.910	34.21	-10.95	54.0	19.79	AV	126.00	100	Vertical	Pass
3	3243.410	47.50	-5.81	74.0	26.50	Peak	210.00	100	Vertical	Pass
3**	3243.410	38.17	-5.81	54.0	15.83	AV	210.00	100	Vertical	Pass
4	4797.680	52.44	0.91	74.0	21.56	Peak	242.00	100	Vertical	Pass
4**	4797.680	42.14	0.91	54.0	11.86	AV	242.00	100	Vertical	Pass
5	7736.660	54.16	0.50	74.0	19.84	Peak	289.00	100	Vertical	Pass
5**	7736.660	43.53	0.50	54.0	10.47	AV	289.00	100	Vertical	Pass
6	13381.500	56.58	5.02	74.0	17.42	Peak	260.00	100	Vertical	Pass
6**	13381.500	47.40	5.02	54.0	6.60	AV	260.00	100	Vertical	Pass

4) Test Antenna Horizontal, 1 GHz – 18 GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1499.850	40.76	-15.50	74.0	33.24	Peak	74.00	100	Horizontal	Pass
1**	1499.850	29.93	-15.50	54.0	24.07	AV	74.00	100	Horizontal	Pass
2	2288.040	43.08	-11.74	74.0	30.92	Peak	292.00	100	Horizontal	Pass
2**	2288.040	32.80	-11.74	54.0	21.20	AV	292.00	100	Horizontal	Pass
3	3130.570	46.91	-6.02	74.0	27.09	Peak	0.00	100	Horizontal	Pass
3**	3130.570	38.15	-6.02	54.0	15.85	AV	0.00	100	Horizontal	Pass
4	5856.540	54.32	2.31	74.0	19.68	Peak	360.00	100	Horizontal	Pass
4**	5856.540	44.27	2.31	54.0	9.73	AV	360.00	100	Horizontal	Pass
5	7750.080	53.78	0.41	74.0	20.22	Peak	303.00	100	Horizontal	Pass
5**	7750.080	43.58	0.41	54.0	10.42	AV	303.00	100	Horizontal	Pass
6	13653.000	56.09	5.04	74.0	17.91	Peak	275.00	100	Horizontal	Pass
6**	13653.000	46.60	5.04	54.0	7.40	AV	275.00	100	Horizontal	Pass

Equipment Information						
Equipment Name	Supplier	Model	Serial No.	Cal. Date	Cal. Due	Use
Frequency Above 1 GHz						
EMI Receiver	Keysight	N9038A	MY55330120	2024.08.01	2025.07.31	☒
Amplifier (1-12GHz)	Advanced Microwave	WLA652A	1740103	2024.11.28	2025.11.27	☒
Amplifier (0.8-21GHz)	Mini-Circuits	ZVA-213-S+	225321316	2024.11.28	2025.11.27	☒
Test Antenna- Horn	SCHWARZB ECK	BBHA 9120D	01917	2022.06.09	2025.06.08	☒
Anechoic Chamber (#2)	YiHeng	9m*6m*6m	142	2024.07.21	2027.07.20	☒
Description	Supplier	Name	Version	/		Use
Test Software	BALUN	BL410-E	V22.930	/		☒


A.2 Conducted Emission, AC Ports

Note: Devices subject to Part 15 must be tested for all available U.S. voltages and frequencies (such as a nominal 120 VAC, 50/60 Hz and 240 VAC, 50/60 Hz) for which the device is capable of operation. So, The configuration 120 VAC, 60 Hz and 240 VAC, 50 Hz were tested respectively, but only the worst configuration (240 VAC, 60 Hz) shown here.

Sample No.	S02	Temperature	16.8℃
Humidity	54%RH	Pressure	101kPa
Test Engineer	Yang Yang	Test Date	2025.05.06


Test Mode 1

1) AC Ports - L Phase



No.	Frequency (MHz)	Results (dBuV)	Factor (dB)	Limit (dBuV)	Margin (dB)	Detector	Line	Verdict
1	0.350	47.31	10.76	58.96	11.65	Peak	L	Pass
1**	0.350	35.68	10.76	48.96	13.28	AV	L	Pass
2	0.446	49.59	10.07	56.95	7.36	Peak	L	Pass
2**	0.446	42.43	10.07	46.95	4.52	AV	L	Pass
3	0.742	46.24	10.25	56.00	9.76	Peak	L	Pass
3**	0.742	33.09	10.25	46.00	12.91	AV	L	Pass
4	0.834	46.45	10.59	56.00	9.55	Peak	L	Pass
4**	0.834	34.07	10.59	46.00	11.93	AV	L	Pass
5	1.366	43.01	9.92	56.00	12.99	Peak	L	Pass
5**	1.366	31.90	9.92	46.00	14.10	AV	L	Pass
6	1.874	43.07	10.44	56.00	12.93	Peak	L	Pass
6**	1.874	29.57	10.44	46.00	16.43	AV	L	Pass

2) AC Ports - N Phase



No.	Frequency (MHz)	Results (dBuV)	Factor (dB)	Limit (dBuV)	Margin (dB)	Detector	Line	Verdict
1	0.346	45.05	10.68	59.06	14.01	Peak	N	Pass
1**	0.346	34.27	10.68	49.06	14.79	AV	N	Pass
2	0.446	47.93	10.07	56.95	9.02	Peak	N	Pass
2**	0.446	42.21	10.07	46.95	4.74	AV	N	Pass
3	0.742	44.34	10.25	56.00	11.66	Peak	N	Pass
3**	0.742	33.18	10.25	46.00	12.82	AV	N	Pass
4	0.830	43.54	10.58	56.00	12.46	Peak	N	Pass
4**	0.830	34.56	10.58	46.00	11.44	AV	N	Pass
5	1.394	41.79	9.76	56.00	14.21	Peak	N	Pass
5**	1.394	31.86	9.76	46.00	14.14	AV	N	Pass
6	1.890	41.94	10.65	56.00	14.06	Peak	N	Pass
6**	1.890	29.46	10.65	46.00	16.54	AV	N	Pass

Equipment Information						
Equipment Name	Supplier	Model	Serial No.	Cal. Date	Cal. Due	Use
EMI Receiver	KEYSIGHT	N9010B	MY57110309	2024.08.01	2025.07.31	☒
LISN	SCHWARZB ECK	NSLK 8127	8127-687	2024.05.09	2025.05.08	☒
Shielded Room	YiHeng Electronic Co., Ltd	3.5m*3.1m*2. 8m	112	2025.02.14	2028.02.13	☒
Description	Supplier	Name	Version	/		Use
Test Software	BALUN	BL410-E	V22.930	/		☒

ANNEX B TEST SETUP PHOTOS

Please refer the document “BL-SZ2541441-AE.PDF”.

ANNEX C EUT EXTERNAL PHOTOS

Please refer the document “BL-SZ2541441-AW.PDF”.

ANNEX D EUT INTERNAL PHOTOS

Please refer the document “BL-SZ2541441-AI.PDF”.

Statement

1. The laboratory guarantees the scientificity, accuracy and impartiality of the test, and is responsible for all the information in the report, except the information provided by the customer. The customer is responsible for the impact of the information provided on the validity of the results.
2. The report without China inspection body and laboratory Mandatory Approval (CMA) mark has no effect of proving to the society.
3. For the report with CNAS mark or A2LA mark, the items marked with "☆" are not within the accredited scope.
4. This report is invalid if it is altered, without the signature of the testing and approval personnel, or without the "inspection and testing dedicated stamp" or test report stamp.
5. The test data and results are only valid for the tested samples provided by the customer.
6. This report shall not be partially reproduced without the written permission of the laboratory.
7. Any objection shall be raised to the laboratory within 30 days after receiving the report.

--END OF REPORT--