

Single Modular approval Declaration letter

We, *Earda Technologies Co.,Ltd.* applies single modular approval for

Product Name: *Wi-Fi6+BT5.3 Combo Module*

Model: *EWN-8852DET3CA*

FCC ID: *2AMM6 -EWN8852DET3CA*

According to 996369 D01 Module Equip Auth Guide v01r04 and 15.212 requirement:

1) The radio elements must have the radio frequency circuitry shielded. Physical components and tuning capacitor(s) may be located external to the shield, but must be on the module assembly;

Answer: *Yes, shielded.*

2) The module must have buffered modulation/data inputs to ensure that the device will comply with Part 15 requirements with any type of input signal;

Answer: *Yes; All inputs to the modules are buffered through logic or microprocessor inputs.*

3) The modular transmitter must have its own power supply regulation.

Answer: *Yes; A low drop out regulator is used for modular power supply regulation.*

4) The module must contain a permanently attached antenna, or contain a unique antenna connector, and be marketed and operated only with specific antenna(s), per Sections 15.203, 15.204(b), 15.204(c), 15.212(a), 2.929(b);

Answer: *Yes; Device is equipped with a permanently attached trace design FPC antenna, no detachable antenna connector, complying with the specified FCC sections requirements.*

(5) The module must demonstrate compliance in a stand-alone configuration;

Answer: *Yes, distance between modular and all AEs are bigger than 10cm, refer to setup photo.*

(6) The module must be labeled with its permanently affixed FCC ID label, or use an electronic display (See KDB Publication 784748 about labeling requirements);

Answer: *Yes; The modular has a permanent fixed label, and below statement was listed in the User Manual; The host device must be labeled to display the FCCID of the module "Contains FCC ID: 2AMM6 -EWN8852DET3CA"*

(7) The module must comply with all specific rules applicable to the transmitter including all the conditions provided in the integration instructions by the grantee;

Answer: *Yes; The module comply with all specific rules applicable to the transmitter including all the conditions provided in the integration instructions by the grantee, Refer to test report and user manual .*

(8) The module must comply with RF exposure requirements



Answer: Yes; Transmitter meets MPE calculation of 47 CFR 1.1307 . Refer to MPE Reports and Refer to modular installation manual.

*Please contact me if you have any further questions. Thanks for your attention.
Best Regards,*

<Signature>

Name: Chengjiu.Wang

Title: Manager

Company: Earda Technologies Co.,Ltd.

